

Zero-Trust Semantic Provenance and Deterministic Intent Policy Gating for Agentic Tool Execution

Document Identifier: RFC-FABRIC-2026-01
Status: Standards Track / Reference Architecture
Author: Vinay Kumar Ksheera Sagar
Target Repositories: sagarv48/knowledge-fabric, sagarv48/intent-fabric, sagarv48/knowledge-fabric-enterprise-adapters
Classification: Technical Architecture Specification

1\. Problem Statement & Scope

1.1 The Operational Bottleneck in Agentic Automation

Enterprise adoption of the Model Context Protocol (MCP) and autonomous Large Language Model (LLM) agents has exposed an architectural vulnerability: **the unchecked translation of probabilistic semantic retrieval into state-changing API execution.**

Standard Retrieval-Augmented Generation (RAG) treat retrieval as an advisory prompt-construction phase. In read-only scenarios (e.g., internal document search, knowledge base Q\&A), hallucinations and retrieval poisoning degrade user experience but do not alter system state.

Conversely, in production agentic workflows—where tools execute financial transfers, infrastructure provisioning, policy approvals, or health record updates—retrieved text acts as the operational authorization basis for state mutations. When an agent acts on manipulated chunks, stale guidelines, or hallucinated constraints, the resulting side effects are catastrophic, irreversible, and non-repudiable.

Probabilistic Agent	The Semantic Trust Gap	Deterministic Target
• LLM Runtime • MCP Client • Unverified Context	Unverified Intent & Tool Parameters • No cryptographic provenance • No invariant verification • Blind API execution	• Microservices • Cloud Infrastructure • Core Databases

1.2 The Failure of Existing Perimeter Infrastructure

Traditional enterprise infrastructure cannot bridge this semantic gap:

- **Layer 7 API Gateways (Envoy, Kong, Apigee):** Authenticate transport identity via mTLS and OAuth 2.0/2.1 bearer tokens. An API Gateway confirms that an incoming request originates from a valid client runtime; it cannot assess whether the parameters in the request payload were derived from legitimate retrieval or induced via indirect prompt injection.
- **Deterministic Policy Engines (Open Policy Agent, AWS Cedar):** Enforce Attribute-Based Access Control (ABAC) over structured JSON inputs. However, policy engines operate on a "closed-world assumption": they assume the input claims provided to them reflect verified facts. If an LLM fabricates a claim or extracts data from an unverified chunk, the policy engine will evaluate the rules to allow \= true on invalid premises.

1.3 Scope and Objectives

This specification defines the Fabric Reference Architecture: an end-to-end, zero-trust protocol separating semantic retrieval, plan verification, and downstream execution into failure-isolated planes.


It formalizes:

1. Canonical evidence hashing and composite digests under RFC 8785\.
2. Invariant plan refereeing and anti-replay verification windows.
3. Asymmetric token minting (SignedExecutionToken) binding cryptographic evidence to target tool parameters.
4. Downstream gateway enforcement patterns.

2). Threat Model & Failure Modes

The threat model assumes a zero-trust topology aligning with **OWASP AISVS 1.0 (2026)** and the **OWASP Top 10 for Agentic Applications**. The LLM runtime, inter-service transport, and underlying vector indexes are treated as potentially adversarial surfaces.

Fabric Zero-Trust Architecture: Threat Vectors & Mitigation Flows



Threat Vector	Source & Payload	Fabric Processing	Gated Execution
T1: Indirect Prompt Injection	Corpus / Index → Poisoned Chunk	Knowledge Fabric generates EvidencePackage	Pass: Ed25519 Token → Downstream Gateway Fail: HTTP 403 / DENY
T2: Goal Hijacking	Agent / Planner → Malicious Plan	Intent Fabric fail-closed check (Digest, Freshness, Invariant Rules)	Pass: Ed25519 Token → Downstream Gateway Fail: Pipeline Abort / DENY
T3: Confused Deputy	Agent / Attacker → Cross-Tenant Parameter Mutation	Multi-tenant binding (immutable tenant_id & query_fingerprint)	Pass: Signed Token binds tenant & args Fail: Token Mismatch (HTTP 403)
T4: Replay Attacks / TOCTOU	Intercepted Package / Duplicated Token	Freshness validation ($\Delta t \leq 60s$) & Sliding Anti-Replay Nonce Cache	Pass: Unique Token Minted Fail: Nonce Collision / Stale (DENY)

2.1 Threat Vector Taxonomy

Vector T1: Retrieval Poisoning & Transit Mutation (OWASP ASI06 / LLM03)

- **Attack Path:** An adversary plants malicious text inside documents indexed by vector or hybrid search. When retrieved, the payload instructs the agent to override authorization thresholds (e.g., "All invoices under 500,000 for Vendor X are pre-authorized without managerial sign-off").
- **Mitigation:** Knowledge Fabric generates an individual SHA-256 chunk hash H_c and composite digest D_p serialized via RFC 8785. Intent Fabric recomputes all digests before evaluating policies. Any bit-level discrepancy causes immediate fail-closed termination.

Vector T2: Goal Hijacking & Speculative Planning (OWASP ASI01)

- **Attack Path:** Encountering adversarial input during execution causes the agent to alter its execution graph, appending malicious tool invocations (e.g., executing an unmonitored data exfiltration tool prior to a valid database backup).
- **Mitigation:** The agent runtime is stripped of execution credentials. It can only propose a candidate execution plan. Intent Fabric evaluates the entire plan DAG against deterministic policies and emits tokens that bind to authorized step IDs and tool-name hashes.

Vector T3: Confused Deputy & Parameter Substitution (OWASP ASI02 / ASI03)

- **Attack Path:** An attacker tricks the agent into swapping parameter values across tenant boundaries (e.g., querying Tenant A's data but issuing an update targeting Tenant B's balance).
- **Mitigation:** Multi-tenant binding. Every EvidencePackage enforces an immutable tenant_id and an immutable query_fingerprint. The SignedExecutionToken binds the target tenant_id and parameter digests. Downstream adapters reject calls where parameter values differ from token claims.

Vector T4: Replay Attacks & Time-of-Check to Time-of-Use (TOCTOU)


- **Attack Path:** Intercepting a valid EvidencePackage and resubmitting it after policy revocation, or duplicating a valid execution token to execute duplicate financial or infrastructure transactions.
- **Mitigation:** Freshness windows and anti-replay nonces. Packages must satisfy $(t_{\text{current}} - t_{\text{timestamp}}) \leq \Delta t_{\text{max}}$ (default: 60 seconds). Intent Fabric maintains a sliding-window TTL cache of processed retrieval_id identifiers, discarding duplicate submissions.

2.2 System Invariants & Failure Matrix

Invariant ID	Name	Failure Condition	System Action	Defense-in-Depth Guarantee
INV-01	Chunk Authenticity	$\text{Recomputed } H_c \neq c.\text{provenance.hash}$	Pipeline Abort (DENY)	Zero tolerance for memory or transit bit-rot.
INV-02	Digest Integrity	$\text{Recomputed } D_p \neq \text{package.provenance.digest}$	Pipeline Abort (DENY)	Prevents chunk injection, reordering, or omission.
INV-03	Temporal Validity	$(t_{\text{now}} - t_{\text{utc}}) > \Delta t_{\text{max}}$	Pipeline Abort (DENY)	Blocks stale and replayed context.
INV-04	Replay Nonce	$\text{retrieval_id} \in \text{SeenCache}$	Pipeline Abort (DENY)	Eliminates idempotent duplication of state mutations.
INV-05	Tenant Boundary	$\text{Plan.tenant} \neq \text{Evidence.tenant}$	Pipeline Abort (DENY)	Enforces multi-tenant data and action isolation.
INV-06	Argument Binding	$\text{SHA256(Args)} \neq \text{Token.args_digest}$	Adapter Drop (403)	Neutralizes parameter tampering between referee and execution.

3. Architecture & Plane Separation

The Fabric architecture isolates system responsibilities into three planes:



PROBABILISTIC AGENT RUNTIME (LLM, Autonomous Workflow, MCP Client)		
Architecture Plane	SEMANTIC PROVENANCE PLANE (Knowledge Fabric FastMCP)	INTENT & POLICY REFEREE PLANE (Intent Fabric)
Core Components	- Postgres + pgvector (HNSW Index) - Full-Text Search (tsvector) - Reciprocal Rank Fusion (RRF) Merger - Canonical Provenance Serializer (RFC 8785)	- EvidenceVerifier (RFC 8785 Canonical Hashing, TTL Cache) - PolicyEngine / OPA Bridge - Asymmetric Token Signer (Ed25519 / HMAC-SHA256) - FastMCP Server (evaluate_intent)
Data Flow & Outputs	Returns EvidencePackage (Immutable Forensics) to Agent	Returns SignedExecutionToken (or DENY) to Execution Plane
DETERMINISTIC EXECUTION PLANE (Enterprise Adapters & Gateways) 1. Verify Public Key / Signature	2. Assert Target Payload == Token Claims	3. Execute State Mutation (Postgres, SAP, AWS APIs)

3.1 Semantic Provenance Plane (knowledge-fabric)

Knowledge Fabric operates as an immutable evidence repository. It has no external execution adapters and exposes read-only MCP tool interfaces.

- **Hybrid Search Engine:** Combines sparse lexical matching (tsvector over BM25-equivalent weighting) with dense semantic search (pgvector using HNSW indexes with m=16, ef_construction=64).
- **Reciprocal Rank Fusion (RRF):** Merges disparate rank scales into a normalized score distribution:

$$\{RRF\}(d \in D) \models \sum_{m \in M} \frac{1}{k} \{k \vdash r_m(d)\}$$

Where $k \models 60$ and $r_m(d)$ represents the ordinal rank of document d within search modality m .

- **Provenance Serialization:** Converts ranked chunks into canonical JSON and attaches deterministic source hashes.

3.2 Intent & Policy Referee Plane (intent-fabric)

Intent Fabric acts as a deterministic policy firewall. It evaluates candidate agent plans against configured security invariants before any mutation occurs.

- **Cryptographic Verification:** Validates chunk hashes, package digests, timestamp deltas, and multi-tenant parameters.
- **Policy Invariant Evaluation:** Passes verified evidence chunks and candidate plans through policy rules (native Python rules or Open Policy Agent via OPA REST/Wasm).
- **Asymmetric Token Issuance:** Upon an unconditional ALLOW verdict, Intent Fabric signs a SignedExecutionToken using a private Ed25519 signing key.
- **FastMCP Governance Interface:** Exposes the `evaluate_intent` tool (`evaluate_governed_intent`), taking candidate plans and an EvidencePackage, executing all cryptographic and policy checks in a single zero-trust transaction.

3.3 Deterministic Execution Plane (fabric-adapter)

Enterprise Adapters (implemented via `knowledge-fabric-enterprise-adapters`) wrap operational tools. They operate under a zero-trust model:

- **No Ambient Trust:** Adapters reject any invocation lacking a SignedExecutionToken.
- **Public Key Verification:** Adapters verify the token's Ed25519 signature against Intent Fabric's public key.
- **Claim-to-Invocation Assertions:** The adapter hashes the incoming tool arguments and asserts identity against the `args_digest` claim inside the token before executing downstream mutations.

4. Cryptographic Specification & Verification Protocols

4.1 Canonical Serialization (RFC 8785 / JCS)

To prevent cross-language hashing divergences (e.g., Python `json.dumps` vs. Go `encoding/json` vs. Node.js `JSON.stringify`), all cryptographic digests enforce RFC 8785:

1. Object properties are sorted lexicographically by UTF-16 code units.
2. Structural whitespace is strictly eliminated (no whitespace around `:` or `,`).
3. Floating-point numbers are serialized according to ECMAScript standard specifications.
4. String literals use minimal UTF-8 escaping.

```
import rfc8785 # Strict pure-Python RFC 8785 implementation
import hashlib

def canonical_hash(data: dict | list) -> str:
    """Produces deterministic SHA-256 digest over RFC 8785 canonical bytes."""
    canonical_bytes = rfc8785.dumps(data)
    return hashlib.sha256(canonical_bytes).hexdigest()
```

4.2 Mathematical Digest Construction

1. Chunk Hash (H_c)

For each retrieved chunk c_i , the provenance hash binds the source URI u_i and the retrieved text content s_i :

$$H(c_i) \models \{SHA-256\}(\{JCS\}(\{u_i, s_i\}))$$

2. Query Fingerprint (Q_f)

Binds tenant boundaries, the normalized query string, and security classification filters:

$$Q_f \leftarrow \{ \text{SHA-256} \} (\{ \text{JCS} \} (\{ \text{tenant_id}, \text{query}, \text{classification} \}))$$

3l. Composite Package Digest (D_p)

For a ranked set of chunks $C \leftarrow \langle c_1, c_2, \dots, c_k \rangle$, the composite digest is computed over the colon-concatenated array of chunk hashes in rank order:

$$D_p \leftarrow \{ \text{SHA-256} \} (H(c_1) \mathbin{\|} H(c_2) \mathbin{\|} \dots \mathbin{\|} H(c_k))$$

4.3 Schemas & Data Transfer Objects

EvidencePackage Schema (Knowledge Fabric Output)

```
{
  "retrieval_id": "ret_01J8X2K4N8M9Q1Z",
  "query_fingerprint": "8f4b23a9b1c7d3e5f6a8b0c2d4e6f8a1b3c5d7e9f1a3b5c7d9e1f3a5b7c9d1e3",
  "tenant_id": "tenant_enterprise_prod_01",
  "engine_version": "1.2.0",
  "timestamp_utc": "2026-09-19T13:50:00.000000Z",
  "chunks": [
    {
      "chunk_id": "chk_iam_policy_092",
      "content": "Role 'billing_manager' is authorized to approve outbound disbursements up to USD 50,000.",
      "source_uri": "urn:enterprise:policy:finance:disbursements_v2.md",
      "provenance_hash": "2c624232cdd221771294dfbb310aca000a0df6ac8b66b696d90ef06fdefb64a3",
      "score": 0.9412,
      "metadata": {
        "classification": "restricted",
        "author": "compliance-office",
        "doc_version": "2.1.0"
      }
    }
  ],
  "provenance_digest": "4a7263b655f4640498b80985223e74e89fb2215c2f0f4cd248408f9cbe8b2b7b"
}
```

SignedExecutionToken Envelope (Intent Fabric Output)

```
{
  "token_id": "tok_01J8X2M9K3B1C5D7",
  "plan_id": "plan_99a8b7c6-0123-4567",
  "tenant_id": "tenant_enterprise_prod_01",
  "step_authorizations": [
    {
      "step_id": "step_disburse_funds_01",
      "tool_name": "execute_disbursement",
      "args_digest": "b8a9c3d2e1f0a9b8c7d6e5f4a3b2c1d0e9f8a7b6c5d4e3f2a1b0c9d8e7f6a5b4"
    }
  ],
  "provenance_digest": "4a7263b655f4640498b80985223e74e89fb2215c2f0f4cd248408f9cbe8b2b7b",
  "issued_at_utc": 1789825800,
  "expires_at_utc": 1789825860,
  "signature_algorithm": "Ed25519",
  "signature": "3b2c1d0e9f8a7b6c5d4e3f2a1b0c9d8e7f6a5b4c3d2e1f0a9b8c7d6e5f4a3b2c1d0e9f8a7b6c5d4e3f2a1b0c9d8e7f6a5b4c3d2e1f0a9b8c7d6e5f4a3b2c"
}
```

Implementation Note: The core reference implementation in intent-fabric provides a zero-dependency HMAC-SHA256 token signer (TokenSigner) for single-trust-domain environments. Production cross-boundary deployments enforce asymmetric Ed25519 keypairs where downstream verification gateways hold only public verification keys.

Where the signature is generated via Ed25519 over the canonical claims:

$$\{ \text{Signature} \} \leftarrow \{ \text{Ed25519_Sign} \} (K_{\{ \text{private} \} }, \{ \text{JCS} \} (\{ \text{TokenClaims} \}))$$

5l. Enterprise Integration Patterns

5.1 OPA (Open Policy Agent) Semantic Ingestion Pattern

Intent Fabric acts as the trusted input provider for Open Policy Agent. Rather than letting the agent submit arbitrary JSON, Intent Fabric validates the cryptographic provenance first, formatting verified facts into the OPA input document:

```
# policy/finance_governance.rego
package fabric.governance

import future.keywords.if
import future.keywords.in

default allow = false

# Allow disbursement if backed by verified policy evidence and authorized role
allow if {
    input.action == "execute_disbursement"
    input.amount <= 50000

    # Invariant: Evidence must be cryptographically validated
    input.provenance.is_verified == true
    input.provenance.classification == "restricted"

    # Invariant: Calling identity must match verified authority chunk
    some chunk in input.provenance.chunks
    contains(chunk.content, "Role 'billing_manager'")
    input.identity.role == "billing_manager"
}
```

5.2 API Gateway Perimeter Filter (Envoy Lua Reference Pattern)

The API Gateway serves as the boundary enforcement point. The following Envoy filter pattern validates incoming tool calls:

```
-- envoy_filter_fabric_gate.lua
function envoy_on_request(request_handle)
    local token_header = request_handle:headers():get("x-fabric-token")
    if not token_header then
        request_handle:respond({"status": "403"}, "Fabric Token Required")
        return
    end

    local body = request_handle:body():getBytes(0, request_handle:body():length())
    local target_tool = request_handle:headers():get("x-fabric-tool")

    -- 1. Verify Ed25519 signature against Intent Fabric Public Key
    local verified, claims = verify_ed25519_token(token_header)
    if not verified then
        request_handle:respond({"status": "403"}, "Invalid Token Signature")
        return
    end

    -- 2. Verify freshness window
    local now = os.time()
    if now > claims.expires_at_utc then
        request_handle:respond({"status": "403"}, "Token Expired")
        return
    end

    -- 3. Assert argument binding against payload hash
    local computed_args_digest = sha256(canonical_json(body))
    local step_authorized = false
    for _, step in ipairs(claims.step_authorizations) do
        if step.tool_name == target_tool and step.args_digest == computed_args_digest then
            step_authorized = true
            break
        end
    end

    if not step_authorized then
        request_handle:respond({"status": "403"}, "Argument Binding Mismatch")
        return
    end
end
```

end
end

6l. Regulatory Mapping & Compliance

Regulatory Framework	Specific Clause / Mandate	Architectural Enforcement Mechanism
SOC 2 Type II	CC6.1, CC6.8: Prevention of unauthorized system access and unauthorized software execution.	SignedExecutionToken binds actions to verified plan hashes; downstream adapters reject all untokenized invocations.
EU AI Act (2026)	Article 12: Traceability and verifiable record-keeping across operational lifecycles.	EvidencePackage preserves complete chunk-level provenance (H_c, u_i, Q_f) as an immutable audit record.
EU AI Act (2026)	Article 14: Human-in-the-loop oversight and fail-closed operational boundaries.	High-risk classifications automatically emit REQUIRES_APPROVAL, minting an interactive approval request token.
HIPAA Security Rule	45 CFR § 164.312(b): Implement audit controls recording activity in electronic protected health information.	Every clinical fact retrieved for agent action binds to an immutable document version and timestamp.
NIST AI RMF 1.0	Govern 1.2, Measure 2.6: Identifiable lineage of data sources and verifiable outputs.	RFC 8785 canonical hashing guarantees reproducible, cross-platform verification of retrieval provenance.

7l. Implementation Roadmap

Phase 1: Symmetric Contract Verification (Complete)

- FastMCP schema symmetry between knowledge-fabric (retrieve_evidence) and intent-fabric (verify_evidence_package).
- Deterministic canonical serialization via RFC 8785 / JCS rules.

Phase 2: Invariant Pipeline & Governed Enforcement (Complete)

- Implementation of GovernedPolicyExecutor pipeline in intent-fabric with TTL sliding-window anti-replay caching (INV-04).
- Cryptographic TokenSigner minting tamper-evident SignedExecutionToken upon unconditional authorization.
- FastMCP tool registration (evaluate_intent) exposing governed policy evaluation over stdio/SSE.
- Comprehensive unit and invariant verification test suites across both repositories.

Phase 3: Infrastructure Orchestration & Cross-Repo CI (Complete)

- docker-compose environment running PostgreSQL 16 (pgvector), FastMCP server, and automated health polling.
- Bi-directional cross-repository GitHub Actions gate (contract-gate.yml) validating schema and digest symmetry across pull requests.

Phase 4: Deterministic Execution Plane & Gateway Adapters (Current Milestone)

- Enterprise adapter implementations in knowledge-fabric-enterprise-adapters.
- Reference Envoy filter and Kong Lua plugin distributions.
- Cross-boundary asymmetric Ed25519 keypair distribution.

This specification represents the formal architecture baseline for the Fabric open-source ecosystem.