

PIZZA Sales SQL QUERFIES

A.KPI`S

1.Total Revenue

```
select sum(total_price) As Total_Revenue from pizza_sales;
```

Results		Messages
Total_Revenue		
1	817860.05083847	

2.Average Order Value

```
select Round(sum(total_price)/count(distinct order_id),0) As Average_Order_Value  
from pizza_sales;
```

Results		Messages
Average_Order_Value		
1	38	

3.Total Pizza Sold

```
select sum(quantity) AS Total_Pizza_Sold from pizza_sales;
```

Results		Messages
Total_Pizza_Sold		
1	49574	

4.Total Orders

```
select count(Distinct order_id) As Total_Orders from pizza_sales;
```

Results		Messages
Total_Orders		
1	21350	

5. Average Pizza Per order

```
select sum(quantity)/count(Distinct order_id) As Average_Pizza_Per_order
from pizza_sales;
```



The screenshot shows a SQL query results window with two tabs: 'Results' and 'Messages'. The 'Results' tab is active, displaying a single row of data. The column header is 'Averae_Pizza_Per_order' (note the typo) and the value is '2'.

	Averae_Pizza_Per_order
1	2

6. Daily Trend For Total Orders

```
select
DATENAME(DW,order_date) As Order_day,
count(Distinct order_id)As Total_Orders
from pizza_sales
GROUP BY DATENAME(DW,order_date)
order by Total_Orders DESC;
```



The screenshot shows a SQL query results window with two tabs: 'Results' and 'Messages'. The 'Results' tab is active, displaying a table with two columns: 'Order_day' and 'Total_Orders'. The data is ordered by 'Total_Orders' in descending order.

	Order_day	Total_Orders
1	Friday	3538
2	Thursday	3239
3	Saturday	3158
4	Wednesday	3024
5	Tuesday	2973
6	Monday	2794
7	Sunday	2624

7. HOURLY TREND FOR TOTAL ORDERS

```
select
DATEPART(HOUR,order_time) As Order_Hours,
count(Distinct order_id)As Total_Orders
from pizza_sales
GROUP BY DATEPART(HOUR,order_time)
ORDER BY Total_Orders DESC
```

	Order_Hours	Total_Orders
1	12	2520
2	13	2455
3	18	2399
4	17	2336
5	19	2009
6	16	1920
7	20	1642
8	14	1472
9	15	1468
10	11	1231
11	21	1198
12	22	663
13	23	28
14	10	8
15	9	1

8. Percentage of sales by Pizza Category

```
SELECT pizza_category, sum(total_price) As Total_Sales,
sum(total_price)*100/(select sum(total_price) from pizza_sales) As PCT
from pizza_sales
GROUP BY pizza_category
Order by PCT desc
```

	pizza_category	Total_Sales	PCT
1	Classic	220053.100021362	26.9059602306976
2	Supreme	208196.99981308	25.4563112111462
3	Chicken	195919.5	23.9551375322885
4	Veggie	193690.451004028	23.6825910258677

9. Percentage of sales by Pizza size

```
SELECT pizza_size,
cast (sum(total_price) As decimal(10,2)) As Total_Sales,
cast(sum(total_price)*100/(select sum(total_price) from pizza_sales) As decimal (10,2)) As PCT
from pizza_sales
GROUP BY pizza_size
Order by PCT desc;
```

	pizza_size	Total_Sales	PCT
1	L	375318.70	45.89
2	M	249382.25	30.49
3	S	178076.50	21.77
4	XL	14076.00	1.72
5	XXL	1006.60	0.12

10.Total Pizza Sold By Pizza Category

```
select pizza_category,
sum(quantity) As Total_Pizza_sold
from pizza_sales
group by pizza_category
order by Total_Pizza_sold desc;
```

	pizza_category	Total_Pizza_sold
1	Classic	14888
2	Supreme	11987
3	Veggie	11649
4	Chicken	11050

11.Top 5 Best sellers by Total Pizza sold

```
select Top 5 pizza_name,sum(quantity) As Total_Pizza_sold
from pizza_sales
group by pizza_name
order by Total_Pizza_sold Desc;
```

	pizza_name	Total_Pizza_sold
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Pizza	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

12. Bottom 5 worst By total Pizza sold

```
select top 5 pizza_name,sum(quantity) As Total_Pizza_sold
from pizza_sales
group by pizza_name
order by Total_Pizza_sold Asc;
```

	pizza_name	Total_Pizza_sold
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Pizza	950
5	The Soppresata Pizza	961