
Quaternion Algebras

Release 10.1

The Sage Development Team

Aug 21, 2023

CONTENTS

1	Quaternion Algebras	1
2	Elements of Quaternion Algebras	29
3	Indices and Tables	37
	Python Module Index	39
	Index	41

QUATERNION ALGEBRAS

AUTHORS:

- Jon Bobber (2009): rewrite
- William Stein (2009): rewrite
- Julian Rueth (2014-03-02): use UniqueFactory for caching
- Peter Bruin (2021): do not require the base ring to be a field

This code is partly based on Sage code by David Kohel from 2005.

class sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebraFactory

Bases: UniqueFactory

Construct a quaternion algebra.

INPUT:

There are three input formats:

- QuaternionAlgebra(a , b), where a and b can be coerced to units in a common field K of characteristic different from 2.
- QuaternionAlgebra(K , a , b), where K is a ring in which 2 is a unit and a and b are units of K .
- QuaternionAlgebra(D), where $D \geq 1$ is a squarefree integer. This constructs a quaternion algebra of discriminant D over $K = \mathbb{Q}$. Suitable nonzero rational numbers a , b as above are deduced from D .

OUTPUT:

The quaternion algebra $(a, b)_K$ over K generated by i, j subject to $i^2 = a$, $j^2 = b$, and $ji = -ij$.

EXAMPLES:

QuaternionAlgebra(a , b) – return the quaternion algebra $(a, b)_K$, where the base ring K is a suitably chosen field containing a and b :

```
sage: QuaternionAlgebra(-2, -3)
Quaternion Algebra (-2, -3) with base ring Rational Field
sage: QuaternionAlgebra(GF(5)(2), GF(5)(3))
Quaternion Algebra (2, 3) with base ring Finite Field of size 5
sage: QuaternionAlgebra(2, GF(5)(3))
Quaternion Algebra (2, 3) with base ring Finite Field of size 5
sage: QuaternionAlgebra(QQ[sqrt(2)](-1), -5)
Quaternion Algebra (-1, -5) with base ring Number Field in sqrt2 with defining
↪ polynomial x^2 - 2 with sqrt2 = 1.414213562373095?
sage: QuaternionAlgebra(sqrt(-1), sqrt(-3))
```

(continues on next page)

(continued from previous page)

```
Quaternion Algebra (I, sqrt(-3)) with base ring Symbolic Ring
sage: QuaternionAlgebra(1r,1)
Quaternion Algebra (1, 1) with base ring Rational Field
sage: A.<t> = ZZ[]
sage: QuaternionAlgebra(-1, t)
Quaternion Algebra (-1, t) with base ring Fraction Field of Univariate Polynomial_
↳Ring in t over Integer Ring
```

Python ints and floats may be passed to the `QuaternionAlgebra(a, b)` constructor, as may all pairs of nonzero elements of a domain not of characteristic 2.

The following tests address the issues raised in [github issue #10601](#):

```
sage: QuaternionAlgebra(1r,1)
Quaternion Algebra (1, 1) with base ring Rational Field
sage: QuaternionAlgebra(1,1.0r)
Quaternion Algebra (1.0000000000000000, 1.0000000000000000) with base ring Real Field_
↳with 53 bits of precision
sage: QuaternionAlgebra(0,0)
Traceback (most recent call last):
...
ValueError: defining elements of quaternion algebra (0, 0) are not invertible in_
↳Rational Field
sage: QuaternionAlgebra(GF(2)(1),1)
Traceback (most recent call last):
...
ValueError: 2 is not invertible in Finite Field of size 2
sage: a = PermutationGroupElement([1,2,3])
sage: QuaternionAlgebra(a, a)
Traceback (most recent call last):
...
ValueError: a and b must be elements of a ring with characteristic not 2
```

`QuaternionAlgebra(K, a, b)` – return the quaternion algebra defined by (a, b) over the ring K :

```
sage: QuaternionAlgebra(QQ, -7, -21)
Quaternion Algebra (-7, -21) with base ring Rational Field
sage: QuaternionAlgebra(QQ[sqrt(2)], -2,-3)
Quaternion Algebra (-2, -3) with base ring Number Field in sqrt2 with defining_
↳polynomial x^2 - 2 with sqrt2 = 1.414213562373095?
```

`QuaternionAlgebra(D)` – D is a squarefree integer; return a rational quaternion algebra of discriminant D :

```
sage: QuaternionAlgebra(1)
Quaternion Algebra (-1, 1) with base ring Rational Field
sage: QuaternionAlgebra(2)
Quaternion Algebra (-1, -1) with base ring Rational Field
sage: QuaternionAlgebra(7)
Quaternion Algebra (-1, -7) with base ring Rational Field
sage: QuaternionAlgebra(2*3*5*7)
Quaternion Algebra (-22, 210) with base ring Rational Field
```

If the coefficients a and b in the definition of the quaternion algebra are not integral, then a slower generic type is used for arithmetic:

```
sage: type(QuaternionAlgebra(-1,-3).0)
<... 'sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_
↳rational_field'>
sage: type(QuaternionAlgebra(-1,-3/2).0)
<... 'sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_
↳generic'>
```

Make sure caching is sane:

```
sage: A = QuaternionAlgebra(2,3); A
Quaternion Algebra (2, 3) with base ring Rational Field
sage: B = QuaternionAlgebra(GF(5)(2),GF(5)(3)); B
Quaternion Algebra (2, 3) with base ring Finite Field of size 5
sage: A is QuaternionAlgebra(2,3)
True
sage: B is QuaternionAlgebra(GF(5)(2),GF(5)(3))
True
sage: Q = QuaternionAlgebra(2); Q
Quaternion Algebra (-1, -1) with base ring Rational Field
sage: Q is QuaternionAlgebra(QQ,-1,-1)
True
sage: Q is QuaternionAlgebra(-1,-1)
True
sage: Q.<ii,jj,kk> = QuaternionAlgebra(15); Q.variable_names()
('ii', 'jj', 'kk')
sage: QuaternionAlgebra(15).variable_names()
('i', 'j', 'k')
```

create_key(arg0, arg1=None, arg2=None, names='i,j,k')

Create a key that uniquely determines a quaternion algebra.

create_object(version, key, **extra_args)

Create the object from the key (extra arguments are ignored). This is only called if the object was not found in the cache.

class sage.algebras.quatalg.quaternion_algebra.**QuaternionAlgebra_ab**(base_ring, a, b, names='i,j,k')

Bases: *QuaternionAlgebra_abstract*

A quaternion algebra of the form $(a, b)_K$.

See *QuaternionAlgebra* for many more examples.

INPUT:

- base_ring – a commutative ring K in which 2 is invertible
- a, b – units of K
- names – string (optional, default 'i,j,k') names of the generators

OUTPUT:

The quaternion algebra (a, b) over K generated by i and j subject to $i^2 = a$, $j^2 = b$, and $ji = -ij$.

EXAMPLES:

```
sage: QuaternionAlgebra(QQ, -7, -21) # indirect doctest
Quaternion Algebra (-7, -21) with base ring Rational Field
```

discriminant()

Given a quaternion algebra A defined over a number field, return the discriminant of A , i.e. the product of the ramified primes of A .

EXAMPLES:

```
sage: QuaternionAlgebra(210, -22).discriminant()
210
sage: QuaternionAlgebra(19).discriminant()
19

sage: x = polygen(ZZ, 'x')
sage: F.<a> = NumberField(x^2 - x - 1)
sage: B.<i,j,k> = QuaternionAlgebra(F, 2*a, F(-1))
sage: B.discriminant()
Fractional ideal (2)

sage: QuaternionAlgebra(QQ[sqrt(2)], 3, 19).discriminant()
Fractional ideal (1)
```

gen($i=0$)

Return the i^{th} generator of self.

INPUT:

- i - integer (optional, default 0)

EXAMPLES:

```
sage: Q.<ii,jj,kk> = QuaternionAlgebra(QQ, -1, -2); Q
Quaternion Algebra (-1, -2) with base ring Rational Field
sage: Q.gen(0)
ii
sage: Q.gen(1)
jj
sage: Q.gen(2)
kk
sage: Q.gens()
[ii, jj, kk]
```

ideal($gens$, $left_order=None$, $right_order=None$, $check=True$, kws)**

Return the quaternion ideal with given gens over \mathbb{Z} .

Neither a left or right order structure need be specified.

INPUT:

- $gens$ – a list of elements of this quaternion order
- $check$ – bool (default: True)
- $left_order$ – a quaternion order or None
- $right_order$ – a quaternion order or None

EXAMPLES:


```
sage: R = QuaternionAlgebra(-11,-1)
sage: R.ideal([2*a for a in R.basis()])
Fractional ideal (2, 2*i, 2*j, 2*k)
```

inner_product_matrix()

Return the inner product matrix associated to `self`, i.e. the Gram matrix of the reduced norm as a quadratic form on `self`. The standard basis $1, i, j, k$ is orthogonal, so this matrix is just the diagonal matrix with diagonal entries $1, a, b, ab$.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(-5,-19)
sage: Q.inner_product_matrix()
[ 2  0  0  0]
[ 0 10  0  0]
[ 0  0 38  0]
[ 0  0  0 190]

sage: R.<a,b> = QQ[]; Q.<i,j,k> = QuaternionAlgebra(Frac(R),a,b)
sage: Q.inner_product_matrix()
[ 2  0  0  0]
[ 0 -2*a 0  0]
[ 0  0 -2*b 0]
[ 0  0  0 2*a*b]
```

invariants()

Return the structural invariants a, b of this quaternion algebra: `self` is generated by i, j subject to $i^2 = a$, $j^2 = b$ and $ji = -ij$.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(15)
sage: Q.invariants()
(-3, 5)
sage: i^2
-3
sage: j^2
5
```

maximal_order(*take_shortcuts=True*)

Return a maximal order in this quaternion algebra.

The algorithm used is from [Voi2012].

INPUT:

- `take_shortcuts` – (default: `True`) if the discriminant is prime and the invariants of the algebra are of a nice form, use Proposition 5.2 of [Piz1980].

OUTPUT:

A maximal order in this quaternion algebra.

EXAMPLES:

```

sage: QuaternionAlgebra(-1,-7).maximal_order()
Order of Quaternion Algebra (-1, -7) with base ring Rational Field with basis
↪(1/2 + 1/2*j, 1/2*i + 1/2*k, j, k)

sage: QuaternionAlgebra(-1,-1).maximal_order().basis()
(1/2 + 1/2*i + 1/2*j + 1/2*k, i, j, k)

sage: QuaternionAlgebra(-1,-11).maximal_order().basis()
(1/2 + 1/2*j, 1/2*i + 1/2*k, j, k)

sage: QuaternionAlgebra(-1,-3).maximal_order().basis()
(1/2 + 1/2*j, 1/2*i + 1/2*k, j, k)

sage: QuaternionAlgebra(-3,-1).maximal_order().basis()
(1/2 + 1/2*i, 1/2*j - 1/2*k, i, -k)

sage: QuaternionAlgebra(-2,-5).maximal_order().basis()
(1/2 + 1/2*j + 1/2*k, 1/4*i + 1/2*j + 1/4*k, j, k)

sage: QuaternionAlgebra(-5,-2).maximal_order().basis()
(1/2 + 1/2*i - 1/2*k, 1/2*i + 1/4*j - 1/4*k, i, -k)

sage: QuaternionAlgebra(-17,-3).maximal_order().basis()
(1/2 + 1/2*j, 1/2*i + 1/2*k, -1/3*j - 1/3*k, k)

sage: QuaternionAlgebra(-3,-17).maximal_order().basis()
(1/2 + 1/2*i, 1/2*j - 1/2*k, -1/3*i + 1/3*k, -k)

sage: QuaternionAlgebra(-17*9,-3).maximal_order().basis()
(1, 1/3*i, 1/6*i + 1/2*j, 1/2 + 1/3*j + 1/18*k)

sage: QuaternionAlgebra(-2, -389).maximal_order().basis()
(1/2 + 1/2*j + 1/2*k, 1/4*i + 1/2*j + 1/4*k, j, k)

```

If you want bases containing 1, switch off take_shortcuts:

```

sage: QuaternionAlgebra(-3,-89).maximal_order(take_shortcuts=False)
Order of Quaternion Algebra (-3, -89) with base ring Rational Field with basis
↪(1, 1/2 + 1/2*i, j, 1/2 + 1/6*i + 1/2*j + 1/6*k)

sage: QuaternionAlgebra(1,1).maximal_order(take_shortcuts=False)    # Matrix
↪ring
Order of Quaternion Algebra (1, 1) with base ring Rational Field with basis (1,
↪1/2 + 1/2*i, j, 1/2*j + 1/2*k)

sage: QuaternionAlgebra(-22,210).maximal_order(take_shortcuts=False)
Order of Quaternion Algebra (-22, 210) with base ring Rational Field with basis
↪(1, i, 1/2*i + 1/2*j, 1/2 + 17/22*i + 1/44*k)

sage: for d in ( m for m in range(1, 750) if is_squarefree(m) ):    # long
↪time (3s)
.....:     A = QuaternionAlgebra(d)
.....:     R = A.maximal_order(take_shortcuts=False)

```

(continues on next page)

(continued from previous page)

```
.....:      assert A.discriminant() == R.discriminant()
```

We do not support number fields other than the rationals yet:

```
sage: K = QuadraticField(5)
sage: QuaternionAlgebra(K, -1, -1).maximal_order()
Traceback (most recent call last):
...
NotImplementedError: maximal order only implemented for rational quaternion.
↪algebras
```

modp_splitting_data(p)

Return mod p splitting data for this quaternion algebra at the unramified prime p .

This is 2×2 matrices I, J, K over the finite field \mathbf{F}_p such that if the quaternion algebra has generators i, j, k , then $I^2 = i^2$, $J^2 = j^2$, $IJ = K$ and $IJ = -JI$.

Note: Currently only implemented when p is odd and the base ring is \mathbf{Q} .

INPUT:

- p – unramified odd prime

OUTPUT:

- 2-tuple of matrices over finite field

EXAMPLES:

```
sage: Q = QuaternionAlgebra(-15, -19)
sage: Q.modp_splitting_data(7)
(
[0 6]  [6 1]  [6 6]
[1 0], [1 1], [6 1]
)
sage: Q.modp_splitting_data(next_prime(10^5))
(
[ 0 99988]  [97311 4]  [99999 59623]
[ 1 0], [13334 2692], [97311 4]
)
sage: I, J, K = Q.modp_splitting_data(23)
sage: I
[0 8]
[1 0]
sage: I^2
[8 0]
[0 8]
sage: J
[19 2]
[17 4]
sage: J^2
[4 0]
[0 4]
sage: I*J == -J*I
```

(continues on next page)

(continued from previous page)

```
True
sage: I*J == K
True
```

The following is a good test because of the asserts in the code:

```
sage: v = [Q.modp_splitting_data(p) for p in primes(20,1000)]
```

Proper error handling:

```
sage: Q.modp_splitting_data(5)
Traceback (most recent call last):
...
NotImplementedError: algorithm for computing local splittings not implemented.
↳ in general (currently require the first invariant to be coprime to p)

sage: Q.modp_splitting_data(2)
Traceback (most recent call last):
...
NotImplementedError: p must be odd
```

modp_splitting_map(*p*)

Return Python map from the (*p*-integral) quaternion algebra to the set of 2×2 matrices over \mathbb{F}_p .

INPUT:

- *p* – prime number

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(-1, -7)
sage: f = Q.modp_splitting_map(13)
sage: a = 2+i-j+3*k; b = 7+2*i-4*j+k
sage: f(a*b)
[12  3]
[10  5]
sage: f(a)*f(b)
[12  3]
[10  5]
```

quaternion_order(*basis*, *check=True*)

Return the order of this quaternion order with given basis.

INPUT:

- *basis* - list of 4 elements of self
- *check* - bool (default: True)

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(-11, -1)
sage: Q.quaternion_order([1,i,j,k])
Order of Quaternion Algebra (-11, -1) with base ring Rational Field with basis
↳ (1, i, j, k)
```

We test out *check=False*:

```
sage: Q.quaternion_order([1,i,j,k], check=False)
Order of Quaternion Algebra (-11, -1) with base ring Rational Field with basis
↳ (1, i, j, k)
sage: Q.quaternion_order([i,j,k], check=False)
Order of Quaternion Algebra (-11, -1) with base ring Rational Field with basis
↳ (i, j, k)
```

ramified_primes()

Return the primes that ramify in this quaternion algebra.

Currently only implemented over the rational numbers.

EXAMPLES:

```
sage: QuaternionAlgebra(QQ, -1, -1).ramified_primes()
[2]
```

class sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract

Bases: [Algebra](#)

basis()

Return the fixed basis of self, which is $1, i, j, k$, where i, j, k are the generators of self.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -5, -2)
sage: Q.basis()
(1, i, j, k)

sage: Q.<xyz,abc,theta> = QuaternionAlgebra(GF(9, 'a'), -5, -2)
sage: Q.basis()
(1, xyz, abc, theta)
```

The basis is cached:

```
sage: Q.basis() is Q.basis()
True
```

free_module()

Return the free module associated to self with inner product given by the reduced norm.

EXAMPLES:

```
sage: A.<t> = LaurentPolynomialRing(GF(3))
sage: B = QuaternionAlgebra(A, -1, t)
sage: B.free_module()
Ambient free quadratic module of rank 4 over the principal ideal domain
↳ Univariate Laurent Polynomial Ring in t over Finite Field of size 3
Inner product matrix:
[2 0 0 0]
[0 2 0 0]
[0 0 t 0]
[0 0 0 t]
```

`inner_product_matrix()`

Return the inner product matrix associated to `self`.

This is the Gram matrix of the reduced norm as a quadratic form on `self`. The standard basis $1, i, j, k$ is orthogonal, so this matrix is just the diagonal matrix with diagonal entries $2, 2a, 2b, 2ab$.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(-5,-19)
sage: Q.inner_product_matrix()
[ 2  0  0  0]
[ 0 10  0  0]
[ 0  0 38  0]
[ 0  0  0 190]
```

`is_commutative()`

Return `False` always, since all quaternion algebras are noncommutative.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3,-7)
sage: Q.is_commutative()
False
```

`is_division_algebra()`

Return `True` if the quaternion algebra is a division algebra (i.e. every nonzero element in `self` is invertible), and `False` if the quaternion algebra is isomorphic to the 2×2 matrix algebra.

EXAMPLES:

```
sage: QuaternionAlgebra(QQ,-5,-2).is_division_algebra()
True
sage: QuaternionAlgebra(1).is_division_algebra()
False
sage: QuaternionAlgebra(2,9).is_division_algebra()
False
sage: QuaternionAlgebra(RR(2.),1).is_division_algebra()
Traceback (most recent call last):
...
NotImplementedError: base field must be rational numbers
```

`is_exact()`

Return `True` if elements of this quaternion algebra are represented exactly, i.e. there is no precision loss when doing arithmetic. A quaternion algebra is exact if and only if its base field is exact.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3, -7)
sage: Q.is_exact()
True
sage: Q.<i,j,k> = QuaternionAlgebra(Qp(7), -3, -7)
sage: Q.is_exact()
False
```

`is_field(proof=True)`

Return `False` always, since all quaternion algebras are noncommutative and all fields are commutative.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3, -7)
sage: Q.is_field()
False
```

is_finite()

Return True if the quaternion algebra is finite as a set.

Algorithm: A quaternion algebra is finite if and only if the base field is finite.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3, -7)
sage: Q.is_finite()
False
sage: Q.<i,j,k> = QuaternionAlgebra(GF(5), -3, -7)
sage: Q.is_finite()
True
```

is_integral_domain(*proof=True*)

Return False always, since all quaternion algebras are noncommutative and integral domains are commutative (in Sage).

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3, -7)
sage: Q.is_integral_domain()
False
```

is_matrix_ring()

Return True if the quaternion algebra is isomorphic to the 2x2 matrix ring, and False if self is a division algebra (i.e. every nonzero element in self is invertible).

EXAMPLES:

```
sage: QuaternionAlgebra(QQ,-5,-2).is_matrix_ring()
False
sage: QuaternionAlgebra(1).is_matrix_ring()
True
sage: QuaternionAlgebra(2,9).is_matrix_ring()
True
sage: QuaternionAlgebra(RR(2.),1).is_matrix_ring()
Traceback (most recent call last):
...
NotImplementedError: base field must be rational numbers
```

is_noetherian()

Return True always, since any quaternion algebra is a noetherian ring (because it is a finitely generated module over a field).

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3, -7)
sage: Q.is_noetherian()
True
```

ngens()

Return the number of generators of the quaternion algebra as a K-vector space, not including 1.

This value is always 3: the algebra is spanned by the standard basis $1, i, j, k$.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ,-5,-2)
sage: Q.ngens()
3
sage: Q.gens()
[i, j, k]
```

order()

Return the number of elements of the quaternion algebra, or +Infinity if the algebra is not finite.

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(QQ, -3, -7)
sage: Q.order()
+Infinity
sage: Q.<i,j,k> = QuaternionAlgebra(GF(5), -3, -7)
sage: Q.order()
625
```

random_element(*args, **kwds)

Return a random element of this quaternion algebra.

The args and kwds are passed to the random_element method of the base ring.

EXAMPLES:

```
sage: g = QuaternionAlgebra(QQ[sqrt(2)], -3, 7).random_element()
sage: g.parent() is QuaternionAlgebra(QQ[sqrt(2)], -3, 7)
True
sage: g = QuaternionAlgebra(-3, 19).random_element()
sage: g.parent() is QuaternionAlgebra(-3, 19)
True
sage: g = QuaternionAlgebra(GF(17)(2), 3).random_element()
sage: g.parent() is QuaternionAlgebra(GF(17)(2), 3)
True
```

Specify the numerator and denominator bounds:

```
sage: g = QuaternionAlgebra(-3,19).random_element(10^6, 10^6)
sage: for h in g:
.....:     assert h.numerator() in range(-10^6, 10^6 + 1)
.....:     assert h.denominator() in range(10^6 + 1)

sage: g = QuaternionAlgebra(-3,19).random_element(5, 4)
sage: for h in g:
.....:     assert h.numerator() in range(-5, 5 + 1)
.....:     assert h.denominator() in range(4 + 1)
```

vector_space()

Alias for `free_module()`.

EXAMPLES:

```
sage: QuaternionAlgebra(-3,19).vector_space()
Ambient quadratic space of dimension 4 over Rational Field
Inner product matrix:
[  2   0   0   0]
[  0   6   0   0]
[  0   0 -38   0]
[  0   0   0 -114]
```

```
class sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal(ring, gens,
                                                                           coerce=True)
```

Bases: `Ideal_fractional`

```
class sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational(Q, basis,
                                                                           left_order=None,
                                                                           right_order=None,
                                                                           check=True)
```

Bases: `QuaternionFractionalIdeal`

A fractional ideal in a rational quaternion algebra.

INPUT:

- `left_order` – a quaternion order or `None`
- `right_order` – a quaternion order or `None`
- `basis` – tuple of length 4 of elements in of ambient quaternion algebra whose \mathbf{Z} -span is an ideal
- `check` – bool (default: `True`); if `False`, do no type checking.

basis()

Return a basis for this fractional ideal.

OUTPUT: tuple

EXAMPLES:

```
sage: QuaternionAlgebra(-11,-1).maximal_order().unit_ideal().basis()
(1/2 + 1/2*i, 1/2*j - 1/2*k, i, -k)
```

basis_matrix()

Return basis matrix M in Hermite normal form for self as a matrix with rational entries.

If Q is the ambient quaternion algebra, then the \mathbf{Z} -span of the rows of M viewed as linear combinations of $Q.basis() = [1, i, j, k]$ is the fractional ideal self. Also, $M * M.denominator()$ is an integer matrix in Hermite normal form.

OUTPUT: matrix over \mathbf{Q}

EXAMPLES:

```
sage: QuaternionAlgebra(-11,-1).maximal_order().unit_ideal().basis_matrix()
[1/2 1/2  0  0]
[  0  1  0  0]
[  0  0 1/2 1/2]
[  0  0  0  1]
```

conjugate()

Return the ideal with generators the conjugates of the generators for self.

OUTPUT: a quaternionic fractional ideal

EXAMPLES:

```
sage: I = BrandtModule(3,5).right_ideals()[1]; I
Fractional ideal (2 + 6*j + 4*k, 2*i + 4*j + 34*k, 8*j + 32*k, 40*k)
sage: I.conjugate()
Fractional ideal (2 + 2*j + 28*k, 2*i + 4*j + 34*k, 8*j + 32*k, 40*k)
```

cyclic_right_subideals(p, alpha=None)

Let $I = \text{self}$. This function returns the right subideals J of I such that I/J is an \mathbb{F}_p -vector space of dimension 2.

INPUT:

- p – prime number (see below)
- α – (default: None) element of quaternion algebra, which can be used to parameterize the order of the ideals J . More precisely the J 's are the right annihilators of $(1, 0)\alpha^i$ for $i = 0, 1, 2, \dots, p$

OUTPUT:

- list of right ideals

Note: Currently, p must satisfy a bunch of conditions, or a `NotImplementedError` is raised. In particular, p must be odd and unramified in the quaternion algebra, must be coprime to the index of the right order in the maximal order, and also coprime to the normal of self. (The Brandt modules code has a more general algorithm in some cases.)

EXAMPLES:

```
sage: B = BrandtModule(2,37); I = B.right_ideals()[0]
sage: I.cyclic_right_subideals(3)
[Fractional ideal (2 + 2*i + 10*j + 90*k, 4*i + 4*j + 152*k, 12*j + 132*k, 444*k), Fractional ideal (2 + 2*i + 2*j + 150*k, 4*i + 8*j + 196*k, 12*j + 132*k, 444*k), Fractional ideal (2 + 2*i + 6*j + 194*k, 4*i + 8*j + 344*k, 12*j + 132*k, 444*k), Fractional ideal (2 + 2*i + 6*j + 46*k, 4*i + 4*j + 4*k, 12*j + 132*k, 444*k)]

sage: B = BrandtModule(5,389); I = B.right_ideals()[0]
sage: C = I.cyclic_right_subideals(3); C
[Fractional ideal (2 + 10*j + 546*k, i + 6*j + 133*k, 12*j + 3456*k, 4668*k), Fractional ideal (2 + 2*j + 2910*k, i + 6*j + 3245*k, 12*j + 3456*k, 4668*k), Fractional ideal (2 + i + 2295*k, 3*i + 2*j + 3571*k, 4*j + 2708*k, 4668*k), Fractional ideal (2 + 2*i + 2*j + 4388*k, 3*i + 2*j + 2015*k, 4*j + 4264*k, 4668*k)]
sage: [(I.free_module()/J.free_module()).invariants() for J in C]
[(3, 3), (3, 3), (3, 3), (3, 3)]
sage: I.scale(3).cyclic_right_subideals(3)
[Fractional ideal (6 + 30*j + 1638*k, 3*i + 18*j + 399*k, 36*j + 10368*k, 14004*k), Fractional ideal (6 + 6*j + 8730*k, 3*i + 18*j + 9735*k, 36*j + 10368*k, 14004*k), Fractional ideal (6 + 3*i + 6885*k, 9*i + 6*j + 10713*k, 12*j + 8124*k, 14004*k), Fractional ideal (6 + 6*i + 6*j + 13164*k, 9*i + 6*j + 10713*k, 12*j + 8124*k, 14004*k)]
```

(continues on next page)

(continued from previous page)

```

↪ + 6045*k, 12*j + 12792*k, 14004*k])
sage: C = I.scale(1/9).cyclic_right_subideals(3); C
[Fractional ideal (2/9 + 10/9*j + 182/3*k, 1/9*i + 2/3*j + 133/9*k, 4/3*j + ↪
↪ 384*k, 1556/3*k), Fractional ideal (2/9 + 2/9*j + 970/3*k, 1/9*i + 2/3*j + ↪
↪ 3245/9*k, 4/3*j + 384*k, 1556/3*k), Fractional ideal (2/9 + 1/9*i + 255*k, 1/
↪ 3*i + 2/9*j + 3571/9*k, 4/9*j + 2708/9*k, 1556/3*k), Fractional ideal (2/9 + ↪
↪ 2/9*i + 2/9*j + 4388/9*k, 1/3*i + 2/9*j + 2015/9*k, 4/9*j + 4264/9*k, 1556/
↪ 3*k)]
sage: [(I.scale(1/9).free_module()/J.free_module()).invariants() for J in C]
[(3, 3), (3, 3), (3, 3), (3, 3)]

sage: Q.<i,j,k> = QuaternionAlgebra(-2,-5)
sage: I = Q.ideal([Q(1),i,j,k])
sage: I.cyclic_right_subideals(3)
[Fractional ideal (1 + 2*j, i + k, 3*j, 3*k), Fractional ideal (1 + j, i + 2*k, ↪
↪ 3*j, 3*k), Fractional ideal (1 + 2*i, 3*i, j + 2*k, 3*k), Fractional ideal (1 ↪
↪ + i, 3*i, j + k, 3*k)]

```

The general algorithm is not yet implemented here:

```

sage: I.cyclic_right_subideals(3)[0].cyclic_right_subideals(3)
Traceback (most recent call last):
...
NotImplementedError: general algorithm not implemented (The given basis vectors ↪
↪ must be linearly independent.)

```

free_module()

Return the underlying free \mathbf{Z} -module corresponding to this ideal.

OUTPUT:

Free \mathbf{Z} -module of rank 4 embedded in an ambient \mathbf{Q}^4 .

EXAMPLES:

```

sage: X = BrandtModule(3,5).right_ideals()
sage: X[0]
Fractional ideal (2 + 2*j + 8*k, 2*i + 18*k, 4*j + 16*k, 20*k)
sage: X[0].free_module()
Free module of degree 4 and rank 4 over Integer Ring
Echelon basis matrix:
[ 2  0  2  8]
[ 0  2  0 18]
[ 0  0  4 16]
[ 0  0  0 20]
sage: X[0].scale(1/7).free_module()
Free module of degree 4 and rank 4 over Integer Ring
Echelon basis matrix:
[ 2/7  0  2/7  8/7]
[  0  2/7  0 18/7]
[  0  0  4/7 16/7]
[  0  0  0 20/7]
sage: QuaternionAlgebra(-11,-1).maximal_order().unit_ideal().basis_matrix()

```

(continues on next page)

(continued from previous page)

```
[1/2 1/2  0  0]
[  0  1  0  0]
[  0  0 1/2 1/2]
[  0  0  0  1]
```

The free module method is also useful since it allows for checking if one ideal is contained in another, computing quotients I/J , etc.:

```
sage: X = BrandtModule(3,17).right_ideals()
sage: I = X[0].intersection(X[2]); I
Fractional ideal (2 + 2*j + 164*k, 2*i + 4*j + 46*k, 16*j + 224*k, 272*k)
sage: I.free_module().is_submodule(X[3].free_module())
False
sage: I.free_module().is_submodule(X[1].free_module())
True
sage: X[0].free_module() / I.free_module()
Finitely generated module V/W over Integer Ring with invariants (4, 4)
```

This shows that the issue at [github issue #6760](#) is fixed:

```
sage: R.<i,j,k> = QuaternionAlgebra(-1, -13)
sage: I = R.ideal([2+i, 3*i, 5*j, j+k]); I
Fractional ideal (2 + i, 3*i, j + k, 5*k)
sage: I.free_module()
Free module of degree 4 and rank 4 over Integer Ring
Echelon basis matrix:
[2 1 0 0]
[0 3 0 0]
[0 0 1 1]
[0 0 0 5]
```

gram_matrix()

Return the Gram matrix of this fractional ideal.

OUTPUT: 4×4 matrix over \mathbb{Q} .

EXAMPLES:

```
sage: I = BrandtModule(3,5).right_ideals()[1]; I
Fractional ideal (2 + 6*j + 4*k, 2*i + 4*j + 34*k, 8*j + 32*k, 40*k)
sage: I.gram_matrix()
[ 640 1920 2112 1920]
[ 1920 14080 13440 16320]
[ 2112 13440 13056 15360]
[ 1920 16320 15360 19200]
```

intersection(J)

Return the intersection of the ideals self and J .

EXAMPLES:

```
sage: X = BrandtModule(3,5).right_ideals()
sage: I = X[0].intersection(X[1]); I
Fractional ideal (2 + 6*j + 4*k, 2*i + 4*j + 34*k, 8*j + 32*k, 40*k)
```

is_equivalent(*J*, *B=10*)

Return True if self and *J* are equivalent as right ideals.

INPUT:

- *J* – a fractional quaternion ideal with same order as *self*
- *B* – a bound to compute and compare theta series before doing the full equivalence test

OUTPUT: bool

EXAMPLES:

```
sage: R = BrandtModule(3,5).right_ideals(); len(R)
2
sage: R[0].is_equivalent(R[1])
False
sage: R[0].is_equivalent(R[0])
True
sage: OO = R[0].left_order()
sage: S = OO.right_ideal([3*a for a in R[0].basis()])
sage: R[0].is_equivalent(S)
True
```

left_order()

Return the left order associated to this fractional ideal.

OUTPUT: an order in a quaternion algebra

EXAMPLES:

```
sage: B = BrandtModule(11)
sage: R = B.maximal_order()
sage: I = R.unit_ideal()
sage: I.left_order()
Order of Quaternion Algebra (-1, -11) with base ring Rational Field with basis_
↪ (1/2 + 1/2*j, 1/2*i + 1/2*k, j, k)
```

We do a consistency check:

```
sage: B = BrandtModule(11,19); R = B.right_ideals()
sage: [r.left_order().discriminant() for r in R]
[209, 209, 209, 209, 209, 209, 209, 209, 209, 209, 209, 209, 209, 209, 209,
↪ 209, 209]
```

multiply_by_conjugate(*J*)

Return product of self and the conjugate *J*bar of *J*.

INPUT:

- *J* – a quaternion ideal.

OUTPUT: a quaternionic fractional ideal.

EXAMPLES:

```
sage: R = BrandtModule(3,5).right_ideals()
sage: R[0].multiply_by_conjugate(R[1])
Fractional ideal (8 + 8*j + 112*k, 8*i + 16*j + 136*k, 32*j + 128*k, 160*k)
```

(continues on next page)

(continued from previous page)

```
sage: R[0]*R[1].conjugate()
Fractional ideal (8 + 8*j + 112*k, 8*i + 16*j + 136*k, 32*j + 128*k, 160*k)
```

norm()

Return the reduced norm of this fractional ideal.

OUTPUT: rational number

EXAMPLES:

```
sage: M = BrandtModule(37)
sage: C = M.right_ideals()
sage: [I.norm() for I in C]
[16, 32, 32]

sage: (a,b) = M.quaternion_algebra().invariants()
↪ # optional - magma
sage: magma.eval('A<i,j,k> := QuaternionAlgebra<Rationals() | %s, %s>' % (a,b))
↪ # optional - magma
''

sage: magma.eval('O := QuaternionOrder(%s)' % str(list(C[0].right_order().
↪ basis())))) # optional - magma
''

sage: [ magma('ideal<O | %s>' % str(list(I.basis()))).Norm() for I in C]
↪ # optional - magma
[16, 32, 32]

sage: A.<i,j,k> = QuaternionAlgebra(-1,-1)
sage: R = A.ideal([i,j,k,1/2 + 1/2*i + 1/2*j + 1/2*k]) # this is actually
↪ an order, so has reduced norm 1
sage: R.norm()
1
sage: [ J.norm() for J in R.cyclic_right_subideals(3) ] # enumerate maximal
↪ right R-ideals of reduced norm 3, verify their norms
[3, 3, 3, 3]
```

quadratic_form()

Return the normalized quadratic form associated to this quaternion ideal.

OUTPUT: quadratic form

EXAMPLES:

```
sage: I = BrandtModule(11).right_ideals()[1]
sage: Q = I.quadratic_form(); Q
Quadratic form in 4 variables over Rational Field with coefficients:
[ 18 22 33 22 ]
[ * 7 22 11 ]
[ * * 22 0 ]
[ * * * 22 ]
sage: Q.theta_series(10)
1 + 12*q^2 + 12*q^3 + 12*q^4 + 12*q^5 + 24*q^6 + 24*q^7 + 36*q^8 + 36*q^9 + O(q^
↪ 10)
sage: I.theta_series(10)
```

(continues on next page)

(continued from previous page)

```
1 + 12*q^2 + 12*q^3 + 12*q^4 + 12*q^5 + 24*q^6 + 24*q^7 + 36*q^8 + 36*q^9 + 0(q^
↪10)
```

quaternion_algebra()

Return the ambient quaternion algebra that contains this fractional ideal.

OUTPUT: a quaternion algebra

EXAMPLES:

```
sage: I = BrandtModule(3,5).right_ideals()[1]; I
Fractional ideal (2 + 6*j + 4*k, 2*i + 4*j + 34*k, 8*j + 32*k, 40*k)
sage: I.quaternion_algebra()
Quaternion Algebra (-1, -3) with base ring Rational Field
```

quaternion_order()

Return the order for which this ideal is a left or right fractional ideal.

If this ideal has both a left and right ideal structure, then the left order is returned. If it has neither structure, then an error is raised.

OUTPUT: QuaternionOrder

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: R.unit_ideal().quaternion_order() is R
doctest:...: DeprecationWarning: quaternion_order() is deprecated, please use
↪left_order() or right_order()
See https://github.com/sagemath/sage/issues/31583 for details.
True
```

right_order()

Return the right order associated to this fractional ideal.

OUTPUT: an order in a quaternion algebra

EXAMPLES:

```
sage: I = BrandtModule(389).right_ideals()[1]; I
Fractional ideal (2 + 6*j + 2*k, i + 2*j + k, 8*j, 8*k)
sage: I.right_order()
Order of Quaternion Algebra (-2, -389) with base ring Rational Field with basis
↪(1/2 + 1/2*j + 1/2*k, 1/4*i + 1/2*j + 1/4*k, j, k)
sage: I.left_order()
Order of Quaternion Algebra (-2, -389) with base ring Rational Field with basis
↪(1/2 + 1/2*j + 3/2*k, 1/8*i + 1/4*j + 9/8*k, j + k, 2*k)
```

The following is a big consistency check. We take reps for all the right ideal classes of a certain order, take the corresponding left orders, then take ideals in the left orders and from those compute the right order again:

```
sage: B = BrandtModule(11,19); R = B.right_ideals()
sage: O = [r.left_order() for r in R]
sage: J = [O[i].left_ideal(R[i].basis()) for i in range(len(R))]
```

(continues on next page)

(continued from previous page)

```
sage: len(set(J))
18
sage: len(set([I.right_order() for I in J]))
1
sage: J[0].right_order() == B.order_of_level_N()
True
```

ring()

Return ring that this is a fractional ideal for.

The `ring()` method will be removed from this class in the future. Calling `ring()` will then return the ambient quaternion algebra. This is consistent with the behaviour for number fields.

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: R.unit_ideal().ring() is R
doctest:...: DeprecationWarning: ring() will return the quaternion algebra in_
↳ the future, please use left_order() or right_order()
See https://github.com/sagemath/sage/issues/31583 for details.
True
```

scale(alpha, left=False)

Scale the fractional ideal `self` by multiplying the basis by `alpha`.

INPUT:

- α – element of quaternion algebra
- `left` – bool (default: False); if true multiply α on the left, otherwise multiply α on the right

OUTPUT:

- a new fractional ideal

EXAMPLES:

```
sage: B = BrandtModule(5,37); I = B.right_ideals()[0]; i,j,k = B.quaternion_
↳ algebra().gens(); I
Fractional ideal (2 + 2*j + 106*k, i + 2*j + 105*k, 4*j + 64*k, 148*k)
sage: I.scale(i)
Fractional ideal (2*i + 212*j - 2*k, -2 + 210*j - 2*k, 128*j - 4*k, 296*j)
sage: I.scale(i, left=True)
Fractional ideal (2*i - 212*j + 2*k, -2 - 210*j + 2*k, -128*j + 4*k, -296*j)
sage: I.scale(i, left=False)
Fractional ideal (2*i + 212*j - 2*k, -2 + 210*j - 2*k, 128*j - 4*k, 296*j)
sage: i * I.gens()[0]
2*i - 212*j + 2*k
sage: I.gens()[0] * i
2*i + 212*j - 2*k
```

theta_series(B, var='q')

Return normalized theta series of `self`, as a power series over \mathbb{Z} in the variable `var`, which is 'q' by default.

The normalized theta series is by definition

$$\theta_I(q) = \sum_{x \in I} q^{\frac{N(x)}{N(I)}}.$$

INPUT:

- B – positive integer
- `var` – string (default: 'q')

OUTPUT: power series

EXAMPLES:

```
sage: I = BrandtModule(11).right_ideals()[1]; I
Fractional ideal (2 + 6*j + 4*k, 2*i + 4*j + 2*k, 8*j, 8*k)
sage: I.norm()
32
sage: I.theta_series(5)
1 + 12*q^2 + 12*q^3 + 12*q^4 + 0(q^5)
sage: I.theta_series(5,'T')
1 + 12*T^2 + 12*T^3 + 12*T^4 + 0(T^5)
sage: I.theta_series(3)
1 + 12*q^2 + 0(q^3)
```

theta_series_vector(B)

Return theta series coefficients of `self`, as a vector of B integers.

INPUT:

- B – positive integer

OUTPUT:

Vector over \mathbb{Z} with B entries.

EXAMPLES:

```
sage: I = BrandtModule(37).right_ideals()[1]; I
Fractional ideal (2 + 6*j + 2*k, i + 2*j + k, 8*j, 8*k)
sage: I.theta_series_vector(5)
(1, 0, 2, 2, 6)
sage: I.theta_series_vector(10)
(1, 0, 2, 2, 6, 4, 8, 6, 10, 10)
sage: I.theta_series_vector(5)
(1, 0, 2, 2, 6)
```

class `sage.algebras.quatalg.quaternion_algebra.QuaternionOrder(A , $basis$, $check=True$)`

Bases: `Parent`

An order in a quaternion algebra.

EXAMPLES:

```
sage: QuaternionAlgebra(-1,-7).maximal_order()
Order of Quaternion Algebra (-1, -7) with base ring Rational Field with basis (1/2_
↪+ 1/2*j, 1/2*i + 1/2*k, j, k)
sage: type(QuaternionAlgebra(-1,-7).maximal_order())
<class 'sage.algebras.quatalg.quaternion_algebra.QuaternionOrder_with_category'>
```

basis()

Return fix choice of basis for this quaternion order.

EXAMPLES:

```
sage: QuaternionAlgebra(-11,-1).maximal_order().basis()
(1/2 + 1/2*i, 1/2*j - 1/2*k, i, -k)
```

discriminant()

Return the discriminant of this order.

This is defined as $\sqrt{\det(\text{Tr}(e_i \bar{e}_j))}$, where $\{e_i\}$ is the basis of the order.

OUTPUT: rational number

EXAMPLES:

```
sage: QuaternionAlgebra(-11,-1).maximal_order().discriminant()
11
sage: S = BrandtModule(11,5).order_of_level_N()
sage: S.discriminant()
55
sage: type(S.discriminant())
<... 'sage.rings.rational.Rational'>
```

free_module()

Return the free \mathbf{Z} -module that corresponds to this order inside the vector space corresponding to the ambient quaternion algebra.

OUTPUT:

A free \mathbf{Z} -module of rank 4.

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: R.basis()
(1/2 + 1/2*i, 1/2*j - 1/2*k, i, -k)
sage: R.free_module()
Free module of degree 4 and rank 4 over Integer Ring
Echelon basis matrix:
[1/2 1/2  0  0]
[ 0  1  0  0]
[ 0  0 1/2 1/2]
[ 0  0  0  1]
```

gen(n)

Return the n -th generator.

INPUT:

- n - an integer between 0 and 3, inclusive.

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order(); R
Order of Quaternion Algebra (-11, -1) with base ring Rational Field with basis_
↪ (1/2 + 1/2*i, 1/2*j - 1/2*k, i, -k)
sage: R.gen(0)
1/2 + 1/2*i
sage: R.gen(1)
1/2*j - 1/2*k
```

(continues on next page)

(continued from previous page)

```
sage: R.gen(2)
i
sage: R.gen(3)
-k
```

gens()

Return generators for self.

EXAMPLES:

```
sage: QuaternionAlgebra(-1,-7).maximal_order().gens()
(1/2 + 1/2*j, 1/2*i + 1/2*k, j, k)
```

intersection(*other*)

Return the intersection of this order with other.

INPUT:

- *other* - a quaternion order in the same ambient quaternion algebra

OUTPUT: a quaternion order

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: R.intersection(R)
Order of Quaternion Algebra (-11, -1) with base ring Rational Field with basis_
↪(1/2 + 1/2*i, i, 1/2*j + 1/2*k, k)
```

We intersect various orders in the quaternion algebra ramified at 11:

```
sage: B = BrandtModule(11,3)
sage: R = B.maximal_order(); S = B.order_of_level_N()
sage: R.intersection(S)
Order of Quaternion Algebra (-1, -11) with base ring Rational Field with basis_
↪(1/2 + 1/2*j, 1/2*i + 5/2*k, j, 3*k)
sage: R.intersection(S) == S
True
sage: B = BrandtModule(11,5)
sage: T = B.order_of_level_N()
sage: S.intersection(T)
Order of Quaternion Algebra (-1, -11) with base ring Rational Field with basis_
↪(1/2 + 1/2*j, 1/2*i + 23/2*k, j, 15*k)
```

left_ideal(*gens*, *check=True*)

Return the ideal with given gens over \mathbb{Z} .

INPUT:

- *gens* – a list of elements of this quaternion order
- *check* – bool (default: True)

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: R.left_ideal([2*a for a in R.basis()])
Fractional ideal (1 + i, 2*i, j + k, 2*k)
```

ngens()

Return the number of generators (which is 4).

EXAMPLES:

```
sage: QuaternionAlgebra(-1,-7).maximal_order().ngens()
4
```

one()

Return the multiplicative unit of this quaternion order.

EXAMPLES:

```
sage: QuaternionAlgebra(-1,-7).maximal_order().one()
1
```

quadratic_form()

Return the normalized quadratic form associated to this quaternion order.

OUTPUT: quadratic form

EXAMPLES:

```
sage: R = BrandtModule(11,13).order_of_level_N()
sage: Q = R.quadratic_form(); Q
Quadratic form in 4 variables over Rational Field with coefficients:
[ 14 253 55 286 ]
[ * 1455 506 3289 ]
[ * * 55 572 ]
[ * * * 1859 ]
sage: Q.theta_series(10)
1 + 2*q + 2*q^4 + 4*q^6 + 4*q^8 + 2*q^9 + O(q^10)
```

quaternion_algebra()

Return ambient quaternion algebra that contains this quaternion order.

EXAMPLES:

```
sage: QuaternionAlgebra(-11,-1).maximal_order().quaternion_algebra()
Quaternion Algebra (-11, -1) with base ring Rational Field
```

random_element(*args, **kws)

Return a random element of this order.

The args and kws are passed to the random_element method of the integer ring, and we return an element of the form

$$ae_1 + be_2 + ce_3 + de_4$$

where e_1, \dots, e_4 are the basis of this order and a, b, c, d are random integers.

EXAMPLES:

```
sage: QuaternionAlgebra(-11,-1).maximal_order().random_element() # random
-4 - 4*i + j - k
sage: QuaternionAlgebra(-11,-1).maximal_order().random_element(-10,10) # random
-9/2 - 7/2*i - 7/2*j - 3/2*k
```

right_ideal(gens, check=True)

Return the ideal with given gens over \mathbf{Z} .

INPUT:

- gens – a list of elements of this quaternion order
- check – bool (default: True)

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: R.right_ideal([2*a for a in R.basis()])
Fractional ideal (1 + i, 2*i, j + k, 2*k)
```

ternary_quadratic_form(include_basis=False)

Return the ternary quadratic form associated to this order.

INPUT:

- include_basis – bool (default: False), if True also return a basis for the dimension 3 subspace G

OUTPUT:

- QuadraticForm
- optional basis for dimension 3 subspace

This function computes the positive definite quadratic form obtained by letting G be the trace zero subspace of $\mathbf{Z} + 2 \cdot \text{self}$, which has rank 3, and restricting the pairing [QuaternionAlgebraElement_abstract.pair\(\)](#):

```
(x,y) = (x.conjugate()*y).reduced_trace()
```

to G .

APPLICATIONS: Ternary quadratic forms associated to an order in a rational quaternion algebra are useful in computing with Gross points, in deciding whether quaternion orders have embeddings from orders in quadratic imaginary fields, and in computing elements of the Kohnen plus subspace of modular forms of weight $3/2$.

EXAMPLES:

```
sage: R = BrandtModule(11,13).order_of_level_N()
sage: Q = R.ternary_quadratic_form(); Q
Quadratic form in 3 variables over Rational Field with coefficients:
[ 5820 1012 13156 ]
[ * 55 1144 ]
[ * * 7436 ]
sage: factor(Q.disc())
2^4 * 11^2 * 13^2
```

The following theta series is a modular form of weight $3/2$ and level $4 \cdot 11 \cdot 13$:

```
sage: Q.theta_series(100)
1 + 2*q^23 + 2*q^55 + 2*q^56 + 2*q^75 + 4*q^92 + O(q^100)
```

unit_ideal()

Return the unit ideal in this quaternion order.

EXAMPLES:

```
sage: R = QuaternionAlgebra(-11,-1).maximal_order()
sage: I = R.unit_ideal(); I
Fractional ideal (1/2 + 1/2*i, 1/2*j - 1/2*k, i, -k)
```

sage.algebras.quatalg.quaternion_algebra.basis_for_quaternion_lattice(gens, reverse=None)

Return a basis for the \mathbf{Z} -lattice in a quaternion algebra spanned by the given gens.

INPUT:

- **gens** – list of elements of a single quaternion algebra
- **reverse** – when computing the HNF do it on the basis $(k, j, i, 1)$ instead of $(1, i, j, k)$; this ensures that if gens are the generators for an order, the first returned basis vector is 1

EXAMPLES:

```
sage: from sage.algebras.quatalg.quaternion_algebra import basis_for_quaternion_
↪ lattice
sage: A.<i,j,k> = QuaternionAlgebra(-1,-7)
sage: basis_for_quaternion_lattice([i+j, i-j, 2*k, A(1/3)])
doctest:warning ... DeprecationWarning: ...
[1/3, i + j, 2*j, 2*k]

sage: basis_for_quaternion_lattice([A(1),i,j,k])
[1, i, j, k]
```

sage.algebras.quatalg.quaternion_algebra.intersection_of_row_modules_over_ZZ(v)

Intersect the \mathbf{Z} -modules with basis matrices the full rank 4×4 \mathbf{Q} -matrices in the list v .

The returned intersection is represented by a 4×4 matrix over \mathbf{Q} . This can also be done using modules and intersection, but that would take over twice as long because of overhead, hence this function.

EXAMPLES:

```
sage: a = matrix(QQ,4,[-2, 0, 0, 0, 0, -1, -1, 1, 2, -1/2, 0, 0, 1, 1, -1, 0])
sage: b = matrix(QQ,4,[0, -1/2, 0, -1/2, 2, 1/2, -1, -1/2, 1, 2, 1, -2, 0, -1/2, -2,
↪ 0])
sage: c = matrix(QQ,4,[0, 1, 0, -1/2, 0, 0, 2, 2, 0, -1/2, 1/2, -1, 1, -1, -1/2, 0])
sage: v = [a,b,c]
sage: from sage.algebras.quatalg.quaternion_algebra import intersection_of_row_
↪ modules_over_ZZ
sage: M = intersection_of_row_modules_over_ZZ(v); M
[ 2  0 -1 -1]
[ -4  1  1 -3]
[ -3 19/2 -1 -4]
[ 2 -3 -8  4]
sage: M2 = a.row_module(ZZ).intersection(b.row_module(ZZ)).intersection(c.row_
↪ module(ZZ))
```

(continues on next page)

(continued from previous page)

```
sage: M.row_module(ZZ) == M2
True
```

`sage.algebras.quatalg.quaternion_algebra.is_QuaternionAlgebra(A)`

Return True if A is of the QuaternionAlgebra data type.

EXAMPLES:

```
sage: sage.algebras.quatalg.quaternion_algebra.is_
      ↪ QuaternionAlgebra(QuaternionAlgebra(QQ,-1,-1))
True
sage: sage.algebras.quatalg.quaternion_algebra.is_QuaternionAlgebra(ZZ)
False
```

`sage.algebras.quatalg.quaternion_algebra.maxord_solve_aux_eq(a, b, p)`

Given a and b and an even prime ideal p find (y,z,w) with y a unit mod p^{2e} such that

$$1 - ay^2 - bz^2 + abw^2 \equiv 0 \pmod{p^{2e}},$$

where e is the ramification index of p .

Currently only $p = 2$ is implemented by hardcoding solutions.

INPUT:

- a – integer with $v_p(a) = 0$
- b – integer with $v_p(b) \in \{0, 1\}$
- p – even prime ideal (actually only $p=ZZ(2)$ is implemented)

OUTPUT:

- A tuple (y, z, w)

EXAMPLES:

```
sage: from sage.algebras.quatalg.quaternion_algebra import maxord_solve_aux_eq
sage: for a in [1,3]:
.....:     for b in [1,2,3]:
.....:         (y,z,w) = maxord_solve_aux_eq(a, b, 2)
.....:         assert mod(y, 4) == 1 or mod(y, 4) == 3
.....:         assert mod(1 - a*y^2 - b*z^2 + a*b*w^2, 4) == 0
```

`sage.algebras.quatalg.quaternion_algebra.normalize_basis_at_p(e, p, B=<method 'pair' of 'sage.algebras.quatalg.quaternion_algebra_element.Qobjects>)`

Compute a (at p) normalized basis from the given basis e of a \mathbf{Z} -module.

The returned basis is (at p) a \mathbf{Z}_p basis for the same module, and has the property that with respect to it the quadratic form induced by the bilinear form B is represented as a orthogonal sum of atomic forms multiplied by p -powers.

If $p \neq 2$ this means that the form is diagonal with respect to this basis.

If $p = 2$ there may be additional 2-dimensional subspaces on which the form is represented as $2^e(ax^2 + bxy + cx^2)$ with $0 = v_2(b) = v_2(a) \leq v_2(c)$.

INPUT:

- `e` – list; basis of a \mathbb{Z} module. WARNING: will be modified!
- `p` – prime for at which the basis should be normalized
- `B` – (default: `QuaternionAlgebraElement_abstract.pair()`) a bilinear form with respect to which to normalize

OUTPUT:

- A list containing two-element tuples: The first element of each tuple is a basis element, the second the valuation of the orthogonal summand to which it belongs. The list is sorted by ascending valuation.

EXAMPLES:

```
sage: from sage.algebras.quatalg.quaternion_algebra import normalize_basis_at_p
sage: A.<i,j,k> = QuaternionAlgebra(-1, -1)
sage: e = [A(1), i, j, k]
sage: normalize_basis_at_p(e, 2)
[(1, 0), (i, 0), (j, 0), (k, 0)]

sage: A.<i,j,k> = QuaternionAlgebra(210)
sage: e = [A(1), i, j, k]
sage: normalize_basis_at_p(e, 2)
[(1, 0), (i, 1), (j, 1), (k, 2)]

sage: A.<i,j,k> = QuaternionAlgebra(286)
sage: e = [A(1), k, 1/2*j + 1/2*k, 1/2 + 1/2*i + 1/2*k]
sage: normalize_basis_at_p(e, 5)
[(1, 0), (1/2*j + 1/2*k, 0), (-5/6*j + 1/6*k, 1), (1/2*i, 1)]

sage: A.<i,j,k> = QuaternionAlgebra(-1,-7)
sage: e = [A(1), k, j, 1/2 + 1/2*i + 1/2*j + 1/2*k]
sage: normalize_basis_at_p(e, 2)
[(1, 0), (1/2 + 1/2*i + 1/2*j + 1/2*k, 0), (-34/105*i - 463/735*j + 71/105*k, 1), (-
↪ 34/105*i - 463/735*j + 71/105*k, 1)]
```

`sage.algebras.quatalg.quaternion_algebra.unpickle_QuaternionAlgebra_v0(*key)`

The 0th version of pickling for quaternion algebras.

EXAMPLES:

```
sage: Q = QuaternionAlgebra(-5,-19)
sage: t = (QQ, -5, -19, ('i', 'j', 'k'))
sage: sage.algebras.quatalg.quaternion_algebra.unpickle_QuaternionAlgebra_v0(*t)
Quaternion Algebra (-5, -19) with base ring Rational Field
sage: loads(dumps(Q)) == Q
True
sage: loads(dumps(Q)) is Q
True
```


ELEMENTS OF QUATERNION ALGEBRAS

Sage allows for computation with elements of quaternion algebras over a nearly arbitrary base field of characteristic not 2. Sage also has very highly optimized implementation of arithmetic in rational quaternion algebras and quaternion algebras over number fields.

class sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract

Bases: AlgebraElement

coefficient_tuple()

Return 4-tuple of coefficients of this quaternion.

EXAMPLES:

```
sage: K.<x> = QQ['x']
sage: Q.<i,j,k> = QuaternionAlgebra(Frac(K),-5,-2)
sage: a = 1/2*x^2 + 2/3*x*i - 3/4*j + 5/7*k
sage: type(a)
<class 'sage.algebras.quatalg.quaternion_algebra_element.
↳QuaternionAlgebraElement_generic'>
sage: a.coefficient_tuple()
(1/2*x^2, 2/3*x, -3/4, 5/7)
```

conjugate()

Return the conjugate of the quaternion: if $\theta = x + yi + zj + wk$, return $x - yi - zj - wk$; that is, return `theta.reduced_trace() - theta`.

EXAMPLES:

```
sage: A.<i,j,k> = QuaternionAlgebra(QQ,-5,-2)
sage: a = 3*i - j + 2
sage: type(a)
<class 'sage.algebras.quatalg.quaternion_algebra_element.
↳QuaternionAlgebraElement_rational_field'>
sage: a.conjugate()
2 - 3*i + j
```

The “universal” test:

```
sage: K.<x,y,z,w,a,b> = QQ[]
sage: Q.<i,j,k> = QuaternionAlgebra(a,b)
sage: theta = x+y*i+z*j+w*k
sage: theta.conjugate()
x + (-y)*i + (-z)*j + (-w)*k
```

`is_constant()`

Return True if this quaternion is constant, i.e., has no i, j, or k term.

OUTPUT:

bool

EXAMPLES:

```
sage: A.<i,j,k> = QuaternionAlgebra(-1,-2)
sage: A(1).is_constant()
True
sage: A(1+i).is_constant()
False
sage: A(i).is_constant()
False
```

`matrix(action='right')`

Return the matrix of right or left multiplication of self on the basis for the ambient quaternion algebra.

In particular, if action is 'right' (the default), returns the matrix of the mapping sending x to x*self.

INPUT:

- action – (default: 'right') 'right' or 'left'.

OUTPUT:

- a matrix

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(-3,-19)
sage: a = 2/3 - 1/2*i + 3/5*j - 4/3*k
sage: a.matrix()
[ 2/3 -1/2 3/5 -4/3]
[ 3/2 2/3 4 3/5]
[-57/5 -76/3 2/3 1/2]
[ 76 -57/5 -3/2 2/3]
sage: a.matrix() == a.matrix(action='right')
True
sage: a.matrix(action='left')
[ 2/3 -1/2 3/5 -4/3]
[ 3/2 2/3 -4 -3/5]
[-57/5 76/3 2/3 -1/2]
[ 76 57/5 3/2 2/3]
sage: (i*a,j*a,k*a)
(3/2 + 2/3*i + 4*j + 3/5*k, -57/5 - 76/3*i + 2/3*j + 1/2*k, 76 - 57/5*i - 3/2*j
↪ + 2/3*k)
sage: a.matrix(action='foo')
Traceback (most recent call last):
...
ValueError: action must be either 'left' or 'right'
```

We test over a more generic base field:

```
sage: K.<x> = QQ['x']
sage: Q.<i,j,k> = QuaternionAlgebra(Frac(K),-5,-2)
```

(continues on next page)

(continued from previous page)

```

sage: a = 1/2*x^2 + 2/3*x*i - 3/4*j + 5/7*k
sage: type(a)
<class 'sage.algebras.quatalg.quaternion_algebra_element.
↳QuaternionAlgebraElement_generic'>
sage: a.matrix()
[1/2*x^2  2/3*x   -3/4    5/7]
[-10/3*x 1/2*x^2  -25/7   -3/4]
[   3/2   10/7  1/2*x^2  -2/3*x]
[ -50/7    3/2  10/3*x  1/2*x^2]
    
```

pair(right)

Return the result of pairing self and right, which should both be elements of a quaternion algebra. The pairing is $(x,y) = (x.\text{conjugate()}*y).\text{reduced_trace}()$.

INPUT:

- right – quaternion

EXAMPLES:

```

sage: A.<i,j,k>=QuaternionAlgebra(-1,-2)
sage: (1+i+j-2*k).pair(2/3+5*i-3*j+k)
-26/3
sage: x = 1+i+j-2*k; y = 2/3+5*i-3*j+k
sage: x.pair(y)
-26/3
sage: y.pair(x)
-26/3
sage: (x.conjugate()*y).reduced_trace()
-26/3
    
```

reduced_characteristic_polynomial(var='x')

Return the reduced characteristic polynomial of this quaternion algebra element, which is $X^2 - tX + n$, where t is the reduced trace and n is the reduced norm.

INPUT:

- var – string (default: 'x'); indeterminate of characteristic polynomial

EXAMPLES:

```

sage: A.<i,j,k>=QuaternionAlgebra(-1,-2)
sage: i.reduced_characteristic_polynomial()
x^2 + 1
sage: j.reduced_characteristic_polynomial()
x^2 + 2
sage: (i+j).reduced_characteristic_polynomial()
x^2 + 3
sage: (2+j+k).reduced_trace()
4
sage: (2+j+k).reduced_characteristic_polynomial('T')
T^2 - 4*T + 8
    
```

reduced_norm()

Return the reduced norm of self: if $\theta = x + yi + zj + wk$, then θ has reduced norm $x^2 - ay^2 - bz^2 + abw^2$.

EXAMPLES:

```
sage: K.<x,y,z,w,a,b> = QQ[]
sage: Q.<i,j,k> = QuaternionAlgebra(a,b)
sage: theta = x+y*i+z*j+w*k
sage: theta.reduced_norm()
w^2*a*b - y^2*a - z^2*b + x^2
```

reduced_trace()

Return the reduced trace of self: if $\theta = x + yi + zj + wk$, then θ has reduced trace $2x$.

EXAMPLES:

```
sage: K.<x,y,z,w,a,b> = QQ[]
sage: Q.<i,j,k> = QuaternionAlgebra(a,b)
sage: theta = x+y*i+z*j+w*k
sage: theta.reduced_trace()
2*x
```

class sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_generic

Bases: [QuaternionAlgebraElement_abstract](#)

class

sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_number_field

Bases: [QuaternionAlgebraElement_abstract](#)

EXAMPLES:

```
sage: K.<a> = QQ[2^(1/3)]; Q.<i,j,k> = QuaternionAlgebra(K,-a,a+1)
sage: Q([a,-2/3,a^2-1/2,a*2]) # implicit doctest
a + (-2/3)*i + (a^2 - 1/2)*j + 2*a*k
```

class

sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field

Bases: [QuaternionAlgebraElement_abstract](#)

coefficient_tuple()

Return 4-tuple of rational numbers which are the coefficients of this quaternion.

EXAMPLES:

```
sage: A.<i,j,k> = QuaternionAlgebra(-1,-2)
sage: (2/3 + 3/5*i + 4/3*j - 5/7*k).coefficient_tuple()
(2/3, 3/5, 4/3, -5/7)
```

conjugate()

Return the conjugate of this quaternion.

EXAMPLES:

```
sage: A.<i,j,k> = QuaternionAlgebra(QQ,-5,-2)
sage: a = 3*i - j + 2
sage: type(a)
<class 'sage.algebras.quatalg.quaternion_algebra_element.
QuaternionAlgebraElement_rational_field'>
sage: a.conjugate()
```

(continues on next page)

(continued from previous page)

```

2 - 3*i + j
sage: b = 1 + 1/3*i + 1/5*j - 1/7*k
sage: b.conjugate()
1 - 1/3*i - 1/5*j + 1/7*k
    
```

denominator()

Return the lowest common multiple of the denominators of the coefficients of i, j and k for this quaternion.

EXAMPLES:

```

sage: A = QuaternionAlgebra(QQ, -1, -1)
sage: A.<i,j,k> = QuaternionAlgebra(QQ, -1, -1)
sage: a = (1/2) + (1/5)*i + (5/12)*j + (1/13)*k
sage: a
1/2 + 1/5*i + 5/12*j + 1/13*k
sage: a.denominator()
780
sage: lcm([2, 5, 12, 13])
780
sage: (a * a).denominator()
608400
sage: (a + a).denominator()
390
    
```

denominator_and_integer_coefficient_tuple()

Return 5-tuple d, x, y, z, w, where this rational quaternion is equal to $(x + yi + zj + wk)/d$ and x, y, z, w do not share a common factor with d.

OUTPUT:

5-tuple of Integers

EXAMPLES:

```

sage: A.<i,j,k>=QuaternionAlgebra(-1,-2)
sage: (2 + 3*i + 4/3*j - 5*k).denominator_and_integer_coefficient_tuple()
(3, 6, 9, 4, -15)
    
```

integer_coefficient_tuple()

Return the integer part of this quaternion, ignoring the common denominator.

OUTPUT:

4-tuple of Integers

EXAMPLES:

```

sage: A.<i,j,k>=QuaternionAlgebra(-1,-2)
sage: (2 + 3*i + 4/3*j - 5*k).integer_coefficient_tuple()
(6, 9, 4, -15)
    
```

is_constant()

Return True if this quaternion is constant, i.e., has no i, j, or k term.

OUTPUT:

bool

EXAMPLES:

```
sage: A.<i,j,k>=QuaternionAlgebra(-1,-2)
sage: A(1/3).is_constant()
True
sage: A(-1).is_constant()
True
sage: (1+i).is_constant()
False
sage: j.is_constant()
False
```

reduced_norm()

Return the reduced norm of `self`.

Given a quaternion $x + yi + zj + wk$, this is $x^2 - ay^2 - bz^2 + abw^2$.

EXAMPLES:

```
sage: K.<i,j,k> = QuaternionAlgebra(QQ, -5, -2)
sage: i.reduced_norm()
5
sage: j.reduced_norm()
2
sage: a = 1/3 + 1/5*i + 1/7*j + k
sage: a.reduced_norm()
22826/2205
```

reduced_trace()

Return the reduced trace of `self`.

This is $2x$ if `self` is $x + iy + zj + wk$.

EXAMPLES:

```
sage: K.<i,j,k> = QuaternionAlgebra(QQ, -5, -2)
sage: i.reduced_trace()
0
sage: j.reduced_trace()
0
sage: a = 1/3 + 1/5*i + 1/7*j + k
sage: a.reduced_trace()
2/3
```

`sage.algebras.quatalg.quaternion_algebra_element.unpickle_QuaternionAlgebraElement_generic_v0(*args)`

EXAMPLES:

```
sage: K.<X> = QQ[]
sage: Q.<i,j,k> = QuaternionAlgebra(Frac(K), -5,-19); z = 2/3 + i*X - X^2*j + X^3*k
sage: f, t = z.__reduce__()
sage: sage.algebras.quatalg.quaternion_algebra_element.unpickle_
↳QuaternionAlgebraElement_generic_v0(*t)
2/3 + X*i + (-X^2)*j + X^3*k
sage: sage.algebras.quatalg.quaternion_algebra_element.unpickle_
↳QuaternionAlgebraElement_generic_v0(*t) == z
True
```

sage.algebras.quatalg.quaternion_algebra_element.**unpickle_QuaternionAlgebraElement_number_field_v0**(*args)

EXAMPLES:

```
sage: K.<a> = QQ[2^(1/3)]; Q.<i,j,k> = QuaternionAlgebra(K, -3, a); z = i + j
sage: f, t = z.__reduce__()
sage: sage.algebras.quatalg.quaternion_algebra_element.unpickle_
↳QuaternionAlgebraElement_number_field_v0(*t)
i + j
sage: sage.algebras.quatalg.quaternion_algebra_element.unpickle_
↳QuaternionAlgebraElement_number_field_v0(*t) == z
True
```

sage.algebras.quatalg.quaternion_algebra_element.**unpickle_QuaternionAlgebraElement_rational_field_v0**(*args)

EXAMPLES:

```
sage: Q.<i,j,k> = QuaternionAlgebra(-5,-19); a = 2/3 + i*5/7 - j*2/5 + 19/2
sage: f, t = a.__reduce__()
sage: sage.algebras.quatalg.quaternion_algebra_element.unpickle_
↳QuaternionAlgebraElement_rational_field_v0(*t)
61/6 + 5/7*i - 2/5*j
```


INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

a

`sage.algebras.quatalg.quaternion_algebra`, [1](#)
`sage.algebras.quatalg.quaternion_algebra_element`,
[29](#)

INDEX

B

`basis()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 9

`basis()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 13

`basis()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionOrder* method), 21

`basis_for_quaternion_lattice()` (in module *sage.algebras.quatalg.quaternion_algebra*), 26

`basis_matrix()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 13

C

`coefficient_tuple()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract* method), 29

`coefficient_tuple()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field* method), 32

`conjugate()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 13

`conjugate()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract* method), 29

`conjugate()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field* method), 32

`create_key()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 3

`create_object()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 3

`cyclic_right_subideals()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 14

D

`denominator()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field* method), 33

`denominator_and_integer_coefficient_tuple()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field* method), 33

`discriminant()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 4

`discriminant()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 22

F

`free_module()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 9

`free_module()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 15

`free_module()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionOrder* method), 22

G

`gen()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 4

`gen()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionOrder* method), 22

`gens()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionOrder* method), 33

`gram_matrix()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 16

I

`ideal()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 5

`inner_product_matrix()`

(*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 5

`inner_product_matrix()`

(*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 9

`integer_coefficient_tuple()` (*sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field* method), 33

`intersection()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 16

`intersection()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational* method), 23

`intersection_of_free_modules_over_Z()` (in module *sage.algebras.quatalg.quaternion_algebra*), 26

`invariants()` (*sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract* method), 5

N
 is_commutative() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 10
 is_constant() (sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract
 method), 29
 is_constant() (sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field
 method), 33
 is_division_algebra()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 10
 is_equivalent() (sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational
 method), 16
 is_exact() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 10
 is_field() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 10
 is_finite() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 11
 is_integral_domain()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 11
 is_matrix_ring() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 11
 is_noetherian() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 11
 is_QuaternionAlgebra() (in module
 sage.algebras.quatalg.quaternion_algebra), 27
L
 left_ideal() (sage.algebras.quatalg.quaternion_algebra.QuaternionOrder
 method), 23
 left_order() (sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational
 method), 17
M
 matrix() (sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract
 method), 30
 maximal_order() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 5
 maxord_solve_aux_eq() (in module
 sage.algebras.quatalg.quaternion_algebra), 27
 modp_splitting_data()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 7
 modp_splitting_map()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 8
 module
 sage.algebras.quatalg.quaternion_algebra,
 1
 sage.algebras.quatalg.quaternion_algebra_element,
 29
 multiply_by_conjugate()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational
 method), 17
 norm() (sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational
 method), 18
 normalize_basis_at_p() (in module
 sage.algebras.quatalg.quaternion_algebra), 27
O
 one() (sage.algebras.quatalg.quaternion_algebra.QuaternionOrder
 method), 24
 order() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 12
P
 pair() (sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract
 method), 31
Q
 quadratic_form() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 18
 quadratic_form() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract
 method), 24
 quaternion_algebra()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational
 method), 19
 quaternion_algebra()
 (sage.algebras.quatalg.quaternion_algebra.QuaternionOrder
 method), 24
 quaternion_order() (sage.algebras.quatalg.quaternion_algebra.QuaternionOrder
 method), 8
 quaternion_order() (sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebraElement_abstract
 method), 19
 QuaternionAlgebra_ab (class in
 sage.algebras.quatalg.quaternion_algebra), 3
 QuaternionAlgebra_abstract (class in
 sage.algebras.quatalg.quaternion_algebra), 9
 QuaternionAlgebraElement_abstract (class in
 sage.algebras.quatalg.quaternion_algebra_element),
 29
 QuaternionAlgebraElement_generic (class in
 sage.algebras.quatalg.quaternion_algebra_element),
 32
 QuaternionAlgebraElement_number_field (class in
 sage.algebras.quatalg.quaternion_algebra_element),
 32
 QuaternionAlgebraElement_rational_field (class
 in sage.algebras.quatalg.quaternion_algebra_element),
 32
 QuaternionAlgebraFactory (class in
 sage.algebras.quatalg.quaternion_algebra), 1

QuaternionFractionalIdeal (class in `unpickle_QuaternionAlgebra_v0()` (in module `sage.algebras.quatalg.quaternion_algebra`), 13
 QuaternionFractionalIdeal_rational (class in `unpickle_QuaternionAlgebraElement_generic_v0()` (in module `sage.algebras.quatalg.quaternion_algebra_element`), 13
 QuaternionOrder (class in `unpickle_QuaternionAlgebraElement_number_field_v0()` (in module `sage.algebras.quatalg.quaternion_algebra_element`), 21
R
 ramified_primes() (`sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract` method), 9
 random_element() (`sage.algebras.quatalg.quaternion_algebra.QuaternionAlgebra_abstract` method), 12
 random_element() (`sage.algebras.quatalg.quaternion_algebra.QuaternionOrder` method), 24
 reduced_characteristic_polynomial() (`sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract` method), 31
 reduced_norm() (`sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract` method), 31
 reduced_norm() (`sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field` method), 34
 reduced_trace() (`sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_abstract` method), 32
 reduced_trace() (`sage.algebras.quatalg.quaternion_algebra_element.QuaternionAlgebraElement_rational_field` method), 34
 right_ideal() (`sage.algebras.quatalg.quaternion_algebra.QuaternionOrder` method), 25
 right_order() (`sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational` method), 19
 ring() (`sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational` method), 20
S
 sage.algebras.quatalg.quaternion_algebra module, 1
 sage.algebras.quatalg.quaternion_algebra_element module, 29
 scale() (`sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational` method), 20
T
 ternary_quadratic_form() (`sage.algebras.quatalg.quaternion_algebra.QuaternionOrder` method), 25
 theta_series() (`sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational` method), 20
 theta_series_vector() (`sage.algebras.quatalg.quaternion_algebra.QuaternionFractionalIdeal_rational` method), 21
U
 unit_ideal() (`sage.algebras.quatalg.quaternion_algebra.QuaternionOrder` method), 26