
Constants

Release 10.4

The Sage Development Team

Jul 23, 2024

CONTENTS

1	Mathematical constants	1
2	Indices and Tables	15
	Python Module Index	17
	Index	19

MATHEMATICAL CONSTANTS

The following standard mathematical constants are defined in Sage, along with support for coercing them into GAP, PARI/GP, KASH, Maxima, Mathematica, Maple, Octave, and Singular:

```
sage: pi
pi
sage: e          # base of the natural logarithm
e
sage: NaN        # Not a number
NaN
sage: golden_ratio
golden_ratio
sage: log2       # natural logarithm of the real number 2
log2
sage: euler_gamma # Euler's gamma constant
euler_gamma
sage: catalan    # the Catalan constant
catalan
sage: khinchin   # Khinchin's constant
khinchin
sage: twinprime
twinprime
sage: mertens
mertens
```

```
>>> from sage.all import *
>>> pi
pi
>>> e          # base of the natural logarithm
e
>>> NaN        # Not a number
NaN
>>> golden_ratio
golden_ratio
>>> log2       # natural logarithm of the real number 2
log2
>>> euler_gamma # Euler's gamma constant
euler_gamma
>>> catalan    # the Catalan constant
catalan
>>> khinchin   # Khinchin's constant
khinchin
>>> twinprime
twinprime
```

(continues on next page)

(continued from previous page)

```
>>> mertens
mertens
```

Support for coercion into the various systems means that if, e.g., you want to create π in Maxima and Singular, you don't have to figure out the special notation for each system. You just type the following:

```
sage: maxima(pi)
%pi
sage: singular(pi)
pi
sage: gap(pi)
pi
sage: gp(pi)
3.141592653589793238462643383      # 32-bit
3.1415926535897932384626433832795028842  # 64-bit
sage: pari(pi)
3.14159265358979
sage: kash(pi)                      # optional - kash
3.14159265358979323846264338328
sage: mathematica(pi)              # optional - mathematica
Pi
sage: pi._maple_init_()
'Pi'
sage: octave(pi)                  # optional - octave
3.14159
```

```
>>> from sage.all import *
>>> maxima(pi)
%pi
>>> singular(pi)
pi
>>> gap(pi)
pi
>>> gp(pi)
3.141592653589793238462643383      # 32-bit
3.1415926535897932384626433832795028842  # 64-bit
>>> pari(pi)
3.14159265358979
>>> kash(pi)                      # optional - kash
3.14159265358979323846264338328
>>> mathematica(pi)              # optional - mathematica
Pi
>>> pi._maple_init_()
'Pi'
>>> octave(pi)                  # optional - octave
3.14159
```

Arithmetic operations with constants also yield constants, which can be coerced into other systems or evaluated.

```
sage: a = pi + e*4/5; a
pi + 4/5*e
sage: maxima(a)
%pi+(4*%e)/5
sage: RealField(15)(a)          # 15 *bits* of precision
5.316
sage: gp(a)
```

(continues on next page)

(continued from previous page)

```
5.316218116357029426750873360      # 32-bit
5.3162181163570294267508733603616328824  # 64-bit
sage: print(mathematica(a))          # optional - mathematica
4 E
--- + Pi
5
```

```
>>> from sage.all import *
>>> a = pi + e*Integer(4)/Integer(5); a
pi + 4/5*e
>>> maxima(a)
%pi+(4*%e)/5
>>> RealField(Integer(15))(a)          # 15 *bits* of precision
5.316
>>> gp(a)
5.316218116357029426750873360      # 32-bit
5.3162181163570294267508733603616328824  # 64-bit
>>> print(mathematica(a))          # optional - mathematica
4 E
--- + Pi
5
```

EXAMPLES: Decimal expansions of constants

We can obtain floating point approximations to each of these constants by coercing into the real field with given precision. For example, to 200 binary places we have the following:

```
sage: R = RealField(200); R
Real Field with 200 bits of precision
```

```
>>> from sage.all import *
>>> R = RealField(Integer(200)); R
Real Field with 200 bits of precision
```

```
sage: R(pi)
3.1415926535897932384626433832795028841971693993751058209749
```

```
>>> from sage.all import *
>>> R(pi)
3.1415926535897932384626433832795028841971693993751058209749
```

```
sage: R(e)
2.7182818284590452353602874713526624977572470936999595749670
```

```
>>> from sage.all import *
>>> R(e)
2.7182818284590452353602874713526624977572470936999595749670
```

```
sage: R(NaN)
NaN
```

```
>>> from sage.all import *
>>> R(NaN)
NaN
```

```
sage: R(golden_ratio)
1.6180339887498948482045868343656381177203091798057628621354
```

```
>>> from sage.all import *
>>> R(golden_ratio)
1.6180339887498948482045868343656381177203091798057628621354
```

```
sage: R(log2)
0.69314718055994530941723212145817656807550013436025525412068
```

```
>>> from sage.all import *
>>> R(log2)
0.69314718055994530941723212145817656807550013436025525412068
```

```
sage: R(euler_gamma)
0.57721566490153286060651209008240243104215933593992359880577
```

```
>>> from sage.all import *
>>> R(euler_gamma)
0.57721566490153286060651209008240243104215933593992359880577
```

```
sage: R(catalan)
0.91596559417721901505460351493238411077414937428167213426650
```

```
>>> from sage.all import *
>>> R(catalan)
0.91596559417721901505460351493238411077414937428167213426650
```

```
sage: R(khinchin)
2.6854520010653064453097148354817956938203822939944629530512
```

```
>>> from sage.all import *
>>> R(khinchin)
2.6854520010653064453097148354817956938203822939944629530512
```

EXAMPLES: Arithmetic with constants

```
sage: f = I*(e+1); f
I*e + I
sage: f^2
(I*e + I)^2
sage: _.expand()
-e^2 - 2*e - 1
```

```
>>> from sage.all import *
>>> f = I*(e+Integer(1)); f
I*e + I
>>> f**Integer(2)
(I*e + I)^2
>>> _.expand()
-e^2 - 2*e - 1
```

```
sage: pp = pi+pi; pp
2*pi
sage: R(pp)
6.2831853071795864769252867665590057683943387987502116419499
```

```
>>> from sage.all import *
>>> pp = pi+pi; pp
2*pi
>>> R(pp)
6.2831853071795864769252867665590057683943387987502116419499
```

```
sage: s = (1 + e^pi); s
e^pi + 1
sage: R(s)
24.140692632779269005729086367948547380266106242600211993445
sage: R(s-1)
23.140692632779269005729086367948547380266106242600211993445
```

```
>>> from sage.all import *
>>> s = (Integer(1) + e**pi); s
e^pi + 1
>>> R(s)
24.140692632779269005729086367948547380266106242600211993445
>>> R(s-Integer(1))
23.140692632779269005729086367948547380266106242600211993445
```

```
sage: l = (1-log2)/(1+log2); l
-(log2 - 1)/(log2 + 1)
sage: R(l)
0.18123221829928249948761381864650311423330609774776013488056
```

```
>>> from sage.all import *
>>> l = (Integer(1)-log2)/(Integer(1)+log2); l
-(log2 - 1)/(log2 + 1)
>>> R(l)
0.18123221829928249948761381864650311423330609774776013488056
```

```
sage: pim = maxima(pi)
sage: maxima.eval('fpprec : 100')
'100'
sage: pim.bfloat()
3.
↪14159265358979323846264338327950288419716939937510582097494459230781640628620899862803482534211706
```

```
>>> from sage.all import *
>>> pim = maxima(pi)
>>> maxima.eval('fpprec : 100')
'100'
>>> pim.bfloat()
3.
↪14159265358979323846264338327950288419716939937510582097494459230781640628620899862803482534211706
```

AUTHORS:

- Alex Clemesha (2006-01-15)

- William Stein
- Alex Clemesha, William Stein (2006-02-20): added new constants; removed todos
- Didier Deshommes (2007-03-27): added constants from RQDF (deprecated)

class sage.symbolic.constants.**Catalan** (*name='catalan'*)

Bases: *Constant*

A number appearing in combinatorics defined as the Dirichlet beta function evaluated at the number 2.

EXAMPLES:

```
sage: catalan^2 + mertens
mertens + catalan^2
```

```
>>> from sage.all import *
>>> catalan**Integer(2) + mertens
mertens + catalan^2
```

class sage.symbolic.constants.**Constant** (*name, conversions=None, latex=None, mathml="", domain='complex'*)

Bases: object

EXAMPLES:

```
sage: from sage.symbolic.constants import Constant
sage: p = Constant('p')
sage: loads(dumps(p))
p
```

```
>>> from sage.all import *
>>> from sage.symbolic.constants import Constant
>>> p = Constant('p')
>>> loads(dumps(p))
p
```

domain()

Returns the domain of this constant. This is either positive, real, or complex, and is used by Pynac to make inferences about expressions containing this constant.

EXAMPLES:

```
sage: p = pi.pyobject(); p
pi
sage: type(_)
<class 'sage.symbolic.constants.Pi'>
sage: p.domain()
'positive'
```

```
>>> from sage.all import *
>>> p = pi.pyobject(); p
pi
>>> type(_)
<class 'sage.symbolic.constants.Pi'>
>>> p.domain()
'positive'
```

expression()

Returns an expression for this constant.

EXAMPLES:

```
sage: a = pi.pyobject()
sage: pi2 = a.expression()
sage: pi2
pi
sage: pi2 + 2
pi + 2
sage: pi - pi2
0
```

```
>>> from sage.all import *
>>> a = pi.pyobject()
>>> pi2 = a.expression()
>>> pi2
pi
>>> pi2 + Integer(2)
pi + 2
>>> pi - pi2
0
```

name()

Returns the name of this constant.

EXAMPLES:

```
sage: from sage.symbolic.constants import Constant
sage: c = Constant('c')
sage: c.name()
'c'
```

```
>>> from sage.all import *
>>> from sage.symbolic.constants import Constant
>>> c = Constant('c')
>>> c.name()
'c'
```

class sage.symbolic.constants.**EulerGamma** (name='euler_gamma')

Bases: *Constant*

The limiting difference between the harmonic series and the natural logarithm.

EXAMPLES:

```
sage: R = RealField()
sage: R(euler_gamma)
0.577215664901533
sage: R = RealField(200); R
Real Field with 200 bits of precision
sage: R(euler_gamma)
0.57721566490153286060651209008240243104215933593992359880577
sage: eg = euler_gamma + euler_gamma; eg
2*euler_gamma
sage: R(eg)
1.1544313298030657212130241801648048620843186718798471976115
```

```
>>> from sage.all import *
>>> R = RealField()
>>> R(euler_gamma)
0.577215664901533
>>> R = RealField(Integer(200)); R
Real Field with 200 bits of precision
>>> R(euler_gamma)
0.57721566490153286060651209008240243104215933593992359880577
>>> eg = euler_gamma + euler_gamma; eg
2*euler_gamma
>>> R(eg)
1.1544313298030657212130241801648048620843186718798471976115
```

class sage.symbolic.constants.**Glaisher** (*name='glaisher'*)

Bases: *Constant*

The Glaisher-Kinkelin constant $A = \exp(\frac{1}{12} - \zeta'(-1))$.

EXAMPLES:

```
sage: float(glaisher)
1.2824271291006226
sage: glaisher.n(digits=60)
1.28242712910062263687534256886979172776768892732500119206374
sage: a = glaisher + 2
sage: a
glaisher + 2
sage: parent(a)
Symbolic Ring
```

```
>>> from sage.all import *
>>> float(glaisher)
1.2824271291006226
>>> glaisher.n(digits=Integer(60))
1.28242712910062263687534256886979172776768892732500119206374
>>> a = glaisher + Integer(2)
>>> a
glaisher + 2
>>> parent(a)
Symbolic Ring
```

class sage.symbolic.constants.**GoldenRatio** (*name='golden_ratio'*)

Bases: *Constant*

The number $(1+\sqrt{5})/2$

EXAMPLES:

```
sage: gr = golden_ratio
sage: RR(gr)
1.61803398874989
sage: R = RealField(200)
sage: R(gr)
1.6180339887498948482045868343656381177203091798057628621354
sage: grm = maxima(golden_ratio); grm
(sqrt(5)+1)/2
sage: grm + grm
sqrt(5)+1
```

(continues on next page)

(continued from previous page)

```
sage: float(grm + grm)
3.23606797749979
```

```
>>> from sage.all import *
>>> gr = golden_ratio
>>> RR(gr)
1.61803398874989
>>> R = RealField(Integer(200))
>>> R(gr)
1.6180339887498948482045868343656381177203091798057628621354
>>> grm = maxima(golden_ratio); grm
(sqrt(5)+1)/2
>>> grm + grm
sqrt(5)+1
>>> float(grm + grm)
3.23606797749979
```

minpoly (*bits=None, degree=None, epsilon=0*)

EXAMPLES:

```
sage: golden_ratio.minpoly()
x^2 - x - 1
```

```
>>> from sage.all import *
>>> golden_ratio.minpoly()
x^2 - x - 1
```

class sage.symbolic.constants.**Khinchin** (*name='khinchin'*)

Bases: *Constant*

The geometric mean of the continued fraction expansion of any (almost any) real number.

EXAMPLES:

```
sage: float(khinchin)
2.6854520010653062
sage: khinchin.n(digits=60)
2.68545200106530644530971483548179569382038229399446295305115
sage: m = mathematica(khinchin); m
Khinchin
sage: m.N(200)
2.685452001065306445309714835481795693820382293...32852204481940961807
# optional - mathematica
```

```
>>> from sage.all import *
>>> float(khinchin)
2.6854520010653062
>>> khinchin.n(digits=Integer(60))
2.68545200106530644530971483548179569382038229399446295305115
>>> m = mathematica(khinchin); m
Khinchin
>>> m.N(Integer(200))
2.685452001065306445309714835481795693820382293...32852204481940961807
# optional - mathematica
```

class sage.symbolic.constants.**Log2** (*name='log2'*)

Bases: *Constant*

The natural logarithm of the real number 2.

EXAMPLES:

```
sage: log2
log2
sage: float(log2)
0.6931471805599453
sage: RR(log2)
0.693147180559945
sage: R = RealField(200); R
Real Field with 200 bits of precision
sage: R(log2)
0.69314718055994530941723212145817656807550013436025525412068
sage: l = (1-log2)/(1+log2); l
-(log2 - 1)/(log2 + 1)
sage: R(l)
0.18123221829928249948761381864650311423330609774776013488056
sage: maxima(log2)
log(2)
sage: maxima(log2).float()
0.6931471805599453
sage: gp(log2)
0.6931471805599453094172321215          # 32-bit
0.69314718055994530941723212145817656807 # 64-bit
sage: RealField(150)(2).log()
0.69314718055994530941723212145817656807550013
```

```
>>> from sage.all import *
>>> log2
log2
>>> float(log2)
0.6931471805599453
>>> RR(log2)
0.693147180559945
>>> R = RealField(Integer(200)); R
Real Field with 200 bits of precision
>>> R(log2)
0.69314718055994530941723212145817656807550013436025525412068
>>> l = (Integer(1)-log2)/(Integer(1)+log2); l
-(log2 - 1)/(log2 + 1)
>>> R(l)
0.18123221829928249948761381864650311423330609774776013488056
>>> maxima(log2)
log(2)
>>> maxima(log2).float()
0.6931471805599453
>>> gp(log2)
0.6931471805599453094172321215          # 32-bit
0.69314718055994530941723212145817656807 # 64-bit
>>> RealField(Integer(150))(Integer(2)).log()
0.69314718055994530941723212145817656807550013
```

class sage.symbolic.constants.**Mertens** (*name='mertens'*)

Bases: *Constant*

The Mertens constant is related to the Twin Primes constant and appears in Mertens' second theorem.

EXAMPLES:

```
sage: float(mertens)
0.26149721284764277
sage: mertens.n(digits=60)
0.261497212847642783755426838608695859051566648261199206192064
```

```
>>> from sage.all import *
>>> float(mertens)
0.26149721284764277
>>> mertens.n(digits=Integer(60))
0.261497212847642783755426838608695859051566648261199206192064
```

class sage.symbolic.constants.**NotANumber** (name='NaN')

Bases: *Constant*

Not a Number

class sage.symbolic.constants.**Pi** (name='pi')

Bases: *Constant*

class sage.symbolic.constants.**TwinPrime** (name='twinprime')

Bases: *Constant*

The Twin Primes constant is defined as $\prod (1 - 1/(p-1)^2)$ for primes $p > 2$.

EXAMPLES:

```
sage: float(twinprime)
0.6601618158468696
sage: twinprime.n(digits=60)
0.660161815846869573927812110014555778432623360284733413319448
```

```
>>> from sage.all import *
>>> float(twinprime)
0.6601618158468696
>>> twinprime.n(digits=Integer(60))
0.660161815846869573927812110014555778432623360284733413319448
```

sage.symbolic.constants.**pi** = **pi**

The formal square root of -1.

EXAMPLES:

```
sage: SR.I()
I
sage: SR.I()^2
-1
```

```
>>> from sage.all import *
>>> SR.I()
I
>>> SR.I()**Integer(2)
-1
```

Note that conversions to real fields will give `TypeError`s:

```
sage: float(SR.I())
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
TypeError: unable to simplify to float approximation
sage: gp(SR.I())
I
sage: RR(SR.I())
Traceback (most recent call last):
...
TypeError: unable to convert '1.0000000000000000*I' to a real number
```

```
>>> from sage.all import *
>>> float(SR.I())
Traceback (most recent call last):
...
TypeError: unable to simplify to float approximation
>>> gp(SR.I())
I
>>> RR(SR.I())
Traceback (most recent call last):
...
TypeError: unable to convert '1.0000000000000000*I' to a real number
```

Expressions involving I that are real-valued can be converted to real fields:

```
sage: float(I*I)
-1.0
sage: RR(I*I)
-1.0000000000000000
```

```
>>> from sage.all import *
>>> float(I*I)
-1.0
>>> RR(I*I)
-1.0000000000000000
```

We can convert to complex fields:

```
sage: C = ComplexField(200); C
Complex Field with 200 bits of precision
sage: C(SR.I())
1.00000000000000000000000000000000000000000000000000000000000000*I
sage: SR.I()._complex_mpfr_field_(ComplexField(53))
1.000000000000000*I
sage: SR.I()._complex_double_(CDF)
1.0*I
sage: CDF(SR.I())
1.0*I
sage: z = SR.I() + I; z
2*I
sage: C(z)
2.00000000000000000000000000000000000000000000000000000000000000*I
sage: 1e8*SR.I()
1.000000000000000e8*I
sage: complex(SR.I())
```

(continues on next page)

```
1j
sage: QQbar(SR.I())
I
sage: abs(SR.I())
1
sage: SR.I().minpoly()
x^2 + 1
sage: maxima(2*SR.I())
2*%i
```

```
>>> from sage.all import *
>>> C = ComplexField(Integer(200)); C
Complex Field with 200 bits of precision
>>> C(SR.I())
1.00000000000000000000000000000000000000000000000000000000000000*I
>>> SR.I()._complex_mpf_field_(ComplexField(Integer(53)))
1.000000000000000*I
>>> SR.I()._complex_double_(CDF)
1.0*I
>>> CDF(SR.I())
1.0*I
>>> z = SR.I() + I; z
2*I
>>> C(z)
2.00000000000000000000000000000000000000000000000000000000000000*I
>>> RealNumber('1e8')*SR.I()
1.000000000000000e8*I
>>> complex(SR.I())
1j
>>> QQbar(SR.I())
I
>>> abs(SR.I())
1
>>> SR.I().minpoly()
x^2 + 1
>>> maxima(Integer(2)*SR.I())
2*%i
```

```
sage.symbolic.constants.unpickle_Constant(class_name, name, conversions, latex, mathml,  
                                           domain)
```

EXAMPLES:

```
sage: from sage.symbolic.constants import unpickle_Constant
sage: a = unpickle_Constant('Constant', 'a', {}, 'aa', '', 'positive')
sage: a.domain()
'positive'
sage: latex(a)
```

(continues on next page)

(continued from previous page)

```
aa
```

```
>>> from sage.all import *
>>> from sage.symbolic.constants import unpickle_Constant
>>> a = unpickle_Constant('Constant', 'a', {}, 'aa', '', 'positive')
>>> a.domain()
'positive'
>>> latex(a)
aa
```

Note that if the name already appears in the `constants_name_table`, then that will be returned instead of constructing a new object:

```
sage: pi = unpickle_Constant('Pi', 'pi', None, None, None, None)
sage: pi._maxima_init_()
'%pi'
```

```
>>> from sage.all import *
>>> pi = unpickle_Constant('Pi', 'pi', None, None, None, None)
>>> pi._maxima_init_()
'%pi'
```

INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

S

`sage.symbolic.constants`, [1](#)

INDEX

C

Catalan (*class in sage.symbolic.constants*), 6
Constant (*class in sage.symbolic.constants*), 6

D

domain() (*sage.symbolic.constants.Constant method*), 6

E

EulerGamma (*class in sage.symbolic.constants*), 7
expression() (*sage.symbolic.constants.Constant method*), 6

G

Glaisher (*class in sage.symbolic.constants*), 8
GoldenRatio (*class in sage.symbolic.constants*), 8

K

Khinchin (*class in sage.symbolic.constants*), 9

L

Log2 (*class in sage.symbolic.constants*), 9

M

Mertens (*class in sage.symbolic.constants*), 10
minpoly() (*sage.symbolic.constants.GoldenRatio method*), 9
module
 sage.symbolic.constants, 1

N

name() (*sage.symbolic.constants.Constant method*), 7
NotANumber (*class in sage.symbolic.constants*), 11

P

Pi (*class in sage.symbolic.constants*), 11
pi (*in module sage.symbolic.constants*), 11

S

sage.symbolic.constants
 module, 1

T

TwinPrime (*class in sage.symbolic.constants*), 11

U

unpickle_Constant() (*in module sage.symbolic.constants*), 13