
Power Series Rings and Laurent Series Rings

Release 10.8

The Sage Development Team

Dec 23, 2025

CONTENTS

1	Power Series Rings	1
2	Power Series	21
3	Power Series Methods	69
4	Power series implemented using PARI	81
5	Multivariate Power Series Rings	91
6	Multivariate Power Series	107
7	Laurent Series Rings	137
8	Laurent Series	147
9	Lazy Series	171
10	Lazy Series Rings	267
11	Puiseux Series Ring	321
12	Puiseux Series Ring Element	327
13	Tate algebras	341
14	Indices and Tables	361
	Python Module Index	363
	Index	365

POWER SERIES RINGS

Power series rings are constructed in the standard Sage fashion. See also *Multivariate Power Series Rings*.

EXAMPLES:

Construct rings and elements:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: R.random_element(6) # random
-4 - 1/2*t^2 - 1/95*t^3 + 1/2*t^4 - 12*t^5 + O(t^6)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.random_element(Integer(6)) # random
-4 - 1/2*t^2 - 1/95*t^3 + 1/2*t^4 - 12*t^5 + O(t^6)
```

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: p = -t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + R.O(6); p
-t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + O(t, u, v)^6
sage: p in R
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t', 'u', 'v',)); (t, u, v,) = R._first_ngens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field
>>> p = -t + Integer(1)/Integer(2)*t**Integer(3)*u - Integer(1)/
↳Integer(4)*t**Integer(4)*u + Integer(2)/Integer(3)*v**Integer(5) + R.O(Integer(6));
↳p
-t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + O(t, u, v)^6
>>> p in R
True
```

The default precision is specified at construction, but does not bound the precision of created elements.

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=5)
sage: R.random_element(6) # random
1/2 - 1/4*t + 2/3*t^2 - 5/2*t^3 + 2/3*t^5 + O(t^6)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(5), names=('t',)); (t,) = R._first_
```

(continues on next page)

(continued from previous page)

```

↪ngens(1)
>>> R.random_element(Integer(6)) # random
1/2 - 1/4*t + 2/3*t^2 - 5/2*t^3 + 2/3*t^5 + O(t^6)

```

Construct univariate power series from a list of coefficients:

```

sage: S = R([1, 3, 5, 7]); S
1 + 3*t + 5*t^2 + 7*t^3

```

```

>>> from sage.all import *
>>> S = R([Integer(1), Integer(3), Integer(5), Integer(7)]); S
1 + 3*t + 5*t^2 + 7*t^3

```

The default precision of a power series ring stays fixed and cannot be changed. To work with different default precision, create a new power series ring:

```

sage: R.<x> = PowerSeriesRing(QQ, default_prec=10)
sage: sin(x)
x - 1/6*x^3 + 1/120*x^5 - 1/5040*x^7 + 1/362880*x^9 + O(x^10)
sage: R.<x> = PowerSeriesRing(QQ, default_prec=15)
sage: sin(x)
x - 1/6*x^3 + 1/120*x^5 - 1/5040*x^7 + 1/362880*x^9 - 1/39916800*x^11
+ 1/6227020800*x^13 + O(x^15)

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(10), names=('x',)); (x,) = R._first_
↪ngens(1)
>>> sin(x)
x - 1/6*x^3 + 1/120*x^5 - 1/5040*x^7 + 1/362880*x^9 + O(x^10)
>>> R = PowerSeriesRing(QQ, default_prec=Integer(15), names=('x',)); (x,) = R._first_
↪ngens(1)
>>> sin(x)
x - 1/6*x^3 + 1/120*x^5 - 1/5040*x^7 + 1/362880*x^9 - 1/39916800*x^11
+ 1/6227020800*x^13 + O(x^15)

```

An iterated example:

```

sage: R.<t> = PowerSeriesRing(ZZ)
sage: S.<t2> = PowerSeriesRing(R)
sage: S
Power Series Ring in t2 over Power Series Ring in t over Integer Ring
sage: S.base_ring()
Power Series Ring in t over Integer Ring

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> S = PowerSeriesRing(R, names=('t2',)); (t2,) = S._first_ngens(1)
>>> S
Power Series Ring in t2 over Power Series Ring in t over Integer Ring
>>> S.base_ring()
Power Series Ring in t over Integer Ring

```

Sage can compute with power series over the symbolic ring.

```
sage: # needs sage.symbolic
sage: K.<t> = PowerSeriesRing(SR, default_prec=5)
sage: a, b, c = var('a,b,c')
sage: f = a + b*t + c*t^2 + O(t^3)
sage: f*f
a^2 + 2*a*b*t + (b^2 + 2*a*c)*t^2 + O(t^3)
sage: f = sqrt(2) + sqrt(3)*t + O(t^3)
sage: f^2
2 + 2*sqrt(3)*sqrt(2)*t + 3*t^2 + O(t^3)
```

```
>>> from sage.all import *
>>> # needs sage.symbolic
>>> K = PowerSeriesRing(SR, default_prec=Integer(5), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> a, b, c = var('a,b,c')
>>> f = a + b*t + c*t**Integer(2) + O(t**Integer(3))
>>> f*f
a^2 + 2*a*b*t + (b^2 + 2*a*c)*t^2 + O(t^3)
>>> f = sqrt(Integer(2)) + sqrt(Integer(3))*t + O(t**Integer(3))
>>> f**Integer(2)
2 + 2*sqrt(3)*sqrt(2)*t + 3*t^2 + O(t^3)
```

Elements are first coerced to constants in base_ring, then coerced into the PowerSeriesRing:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: f = Mod(2, 3) * t; (f, f.parent())
(2*t, Power Series Ring in t over Ring of integers modulo 3)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = Mod(Integer(2), Integer(3)) * t; (f, f.parent())
(2*t, Power Series Ring in t over Ring of integers modulo 3)
```

We make a sparse power series.

```
sage: R.<x> = PowerSeriesRing(QQ, sparse=True); R
Sparse Power Series Ring in x over Rational Field
sage: f = 1 + x^1000000
sage: g = f*f
sage: g.degree()
2000000
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, sparse=True, names=('x',)); (x,) = R._first_ngens(1); R
Sparse Power Series Ring in x over Rational Field
>>> f = Integer(1) + x**Integer(1000000)
>>> g = f*f
>>> g.degree()
2000000
```

We make a sparse Laurent series from a power series generator:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: latex(-2/3*(1/t^3) + 1/t + 3/5*t^2 + O(t^5))
\frac{-\frac{2}{3}}{t^3} + \frac{1}{t} + \frac{3}{5}t^2 + O(t^5)
sage: S = parent(1/t); S
Sparse Laurent Series Ring in t over Rational Field
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, sparse=True, names=('t',)); (t,) = R._first_ngens(1)
>>> latex(-Integer(2)/Integer(3)*(Integer(1)/t**Integer(3)) + Integer(1)/t +
↳ Integer(3)/Integer(5)*t**Integer(2) + O(t**Integer(5)))
\frac{-\frac{2}{3}}{t^3} + \frac{1}{t} + \frac{3}{5}t^2 + O(t^5)
>>> S = parent(Integer(1)/t); S
Sparse Laurent Series Ring in t over Rational Field
```

Choose another implementation of the attached polynomial ring:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: type(t.polynomial()) #_
↳ needs sage.libs.flint
<... 'sage.rings.polynomial.polynomial_integer_dense_flint.Polynomial_integer_dense_
↳ flint'>
sage: S.<s> = PowerSeriesRing(ZZ, implementation='NTL') #_
↳ needs sage.libs.ntl
sage: type(s.polynomial()) #_
↳ needs sage.libs.ntl
<... 'sage.rings.polynomial.polynomial_integer_dense_ntl.Polynomial_integer_dense_ntl
↳ '>
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> type(t.polynomial()) #_
↳ needs sage.libs.flint
<... 'sage.rings.polynomial.polynomial_integer_dense_flint.Polynomial_integer_dense_
↳ flint'>
>>> S = PowerSeriesRing(ZZ, implementation='NTL', names=('s',)); (s,) = S._first_
↳ ngens(1) # needs sage.libs.ntl
>>> type(s.polynomial()) #_
↳ needs sage.libs.ntl
<... 'sage.rings.polynomial.polynomial_integer_dense_ntl.Polynomial_integer_dense_ntl
↳ '>
```

AUTHORS:

- William Stein: the code
- Jeremy Cho (2006-05-17): some examples (above)
- Niles Johnson (2010-09): implement multivariate power series
- Simon King (2012-08): use category and coercion framework, [Issue #13412](#)

```
sage.rings.power_series_ring.PowerSeriesRing(base_ring, name=None, arg2=None, names=None,
sparse=False, default_prec=None, order='negdeglex',
num_gens=None, implementation=None)
```

Create a univariate or multivariate power series ring over a given (commutative) base ring.

INPUT:

- `base_ring` – a commutative ring
- `name, names` – name(s) of the indeterminate
- `default_prec` – the default precision used if an exact object must be changed to an approximate object in order to do an arithmetic operation. If left as `None`, it will be set to the global default (20) in the univariate case, and 12 in the multivariate case.
- `sparse` – boolean (default: `False`); whether power series are represented as sparse objects
- `order` – (default: `negdeglex`) term ordering, for multivariate case
- `num_gens` – number of generators, for multivariate case

There is a unique power series ring over each base ring with given variable name. Two power series over the same base ring with different variable names are not equal or isomorphic.

EXAMPLES (Univariate):

```
sage: R = PowerSeriesRing(QQ, 'x'); R
Power Series Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, 'x'); R
Power Series Ring in x over Rational Field
```

```
sage: S = PowerSeriesRing(QQ, 'y'); S
Power Series Ring in y over Rational Field
```

```
>>> from sage.all import *
>>> S = PowerSeriesRing(QQ, 'y'); S
Power Series Ring in y over Rational Field
```

```
sage: R = PowerSeriesRing(QQ, 10)
Traceback (most recent call last):
...
ValueError: variable name '10' does not start with a letter
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, Integer(10))
Traceback (most recent call last):
...
ValueError: variable name '10' does not start with a letter
```

```
sage: S = PowerSeriesRing(QQ, 'x', default_prec=15); S
Power Series Ring in x over Rational Field
sage: S.default_prec()
15
```

```
>>> from sage.all import *
>>> S = PowerSeriesRing(QQ, 'x', default_prec=Integer(15)); S
Power Series Ring in x over Rational Field
>>> S.default_prec()
15
```

EXAMPLES (Multivariate) See also *Multivariate Power Series Rings*:

```
sage: R = PowerSeriesRing(QQ, 't,u,v'); R
Multivariate Power Series Ring in t, u, v over Rational Field
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, 't,u,v'); R
Multivariate Power Series Ring in t, u, v over Rational Field
```

```
sage: N = PowerSeriesRing(QQ, 'w', num_gens=5); N
Multivariate Power Series Ring in w0, w1, w2, w3, w4 over Rational Field
```

```
>>> from sage.all import *
>>> N = PowerSeriesRing(QQ, 'w', num_gens=Integer(5)); N
Multivariate Power Series Ring in w0, w1, w2, w3, w4 over Rational Field
```

Number of generators can be specified before variable name without using keyword:

```
sage: M = PowerSeriesRing(QQ, 4, 'k'); M
Multivariate Power Series Ring in k0, k1, k2, k3 over Rational Field
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 'k'); M
Multivariate Power Series Ring in k0, k1, k2, k3 over Rational Field
```

Multivariate power series can be constructed using angle bracket or double square bracket notation:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ, 't,u,v'); R
Multivariate Power Series Ring in t, u, v over Rational Field
```

```
sage: ZZ[['s,t,u']]
Multivariate Power Series Ring in s, t, u over Integer Ring
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, 't,u,v', names=('t', 'u', 'v')); (t, u, v) = R._
↳first_gens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field

>>> ZZ[['s,t,u']]
Multivariate Power Series Ring in s, t, u over Integer Ring
```

Sparse multivariate power series ring:

```
sage: M = PowerSeriesRing(QQ, 4, 'k', sparse=True); M
Sparse Multivariate Power Series Ring in k0, k1, k2, k3 over
Rational Field
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 'k', sparse=True); M
Sparse Multivariate Power Series Ring in k0, k1, k2, k3 over
Rational Field
```

Power series ring over polynomial ring:

```
sage: H = PowerSeriesRing(PolynomialRing(ZZ, 3, 'z'), 4, 'f'); H
Multivariate Power Series Ring in f0, f1, f2, f3 over Multivariate
Polynomial Ring in z0, z1, z2 over Integer Ring
```

```
>>> from sage.all import *
>>> H = PowerSeriesRing(PolynomialRing(ZZ, Integer(3), 'z'), Integer(4), 'f'); H
Multivariate Power Series Ring in f0, f1, f2, f3 over Multivariate
Polynomial Ring in z0, z1, z2 over Integer Ring
```

Power series ring over finite field:

```
sage: S = PowerSeriesRing(GF(65537), 'x,y'); S #_
↳ needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size
65537
```

```
>>> from sage.all import *
>>> S = PowerSeriesRing(GF(Integer(65537)), 'x,y'); S _
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size
65537
```

Power series ring with many variables:

```
sage: R = PowerSeriesRing(ZZ, ['x%s'%p for p in primes(100)]); R #_
↳ needs sage.libs.pari
Multivariate Power Series Ring in x2, x3, x5, x7, x11, x13, x17, x19,
x23, x29, x31, x37, x41, x43, x47, x53, x59, x61, x67, x71, x73, x79,
x83, x89, x97 over Integer Ring
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, ['x%s'%p for p in primes(Integer(100))]); R _
↳ # needs sage.libs.pari
Multivariate Power Series Ring in x2, x3, x5, x7, x11, x13, x17, x19,
x23, x29, x31, x37, x41, x43, x47, x53, x59, x61, x67, x71, x73, x79,
x83, x89, x97 over Integer Ring
```

- Use `inject_variables()` to make the variables available for interactive use.

```
sage: R.inject_variables() _
↳ # needs sage.libs.pari
Defining x2, x3, x5, x7, x11, x13, x17, x19, x23, x29, x31, x37,
x41, x43, x47, x53, x59, x61, x67, x71, x73, x79, x83, x89, x97

sage: f = x47 + 3*x11*x29 - x19 + R.O(3) _
↳ # needs sage.libs.pari
sage: f in R _
↳ # needs sage.libs.pari
True
```

```
>>> from sage.all import *
>>> R.inject_variables()
```

(continues on next page)

(continued from previous page)

```

↪ # needs sage.libs.pari
Defining x2, x3, x5, x7, x11, x13, x17, x19, x23, x29, x31, x37,
x41, x43, x47, x53, x59, x61, x67, x71, x73, x79, x83, x89, x97

>>> f = x47 + Integer(3)*x11*x29 - x19 + R.O(Integer(3))
↪ # needs sage.libs.pari
>>> f in R
↪ # needs sage.libs.pari
True

```

Variable ordering determines how series are displayed:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,order='deglex'); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: T.term_order()
Degree lexicographic term order
sage: p = - 2*b^6 + a^5*b^2 + a^7 - b^2 - a*b^3 + T.O(9); p
a^7 + a^5*b^2 - 2*b^6 - a*b^3 - b^2 + O(a, b)^9

sage: U = PowerSeriesRing(ZZ,'a,b',order='negdeglex'); U
Multivariate Power Series Ring in a, b over Integer Ring
sage: U.term_order()
Negative degree lexicographic term order
sage: U(p)
-b^2 - a*b^3 - 2*b^6 + a^7 + a^5*b^2 + O(a, b)^9

```

```

>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,order='deglex', names=('a', 'b',)); (a, b,) = T._first_
↪ ngens(2); T
Multivariate Power Series Ring in a, b over Integer Ring
>>> T.term_order()
Degree lexicographic term order
>>> p = - Integer(2)*b**Integer(6) + a**Integer(5)*b**Integer(2) + a**Integer(7) -
↪ b**Integer(2) - a*b**Integer(3) + T.O(Integer(9)); p
a^7 + a^5*b^2 - 2*b^6 - a*b^3 - b^2 + O(a, b)^9

>>> U = PowerSeriesRing(ZZ,'a,b',order='negdeglex'); U
Multivariate Power Series Ring in a, b over Integer Ring
>>> U.term_order()
Negative degree lexicographic term order
>>> U(p)
-b^2 - a*b^3 - 2*b^6 + a^7 + a^5*b^2 + O(a, b)^9

```

➡ See also

- `sage.misc.defaults.set_series_precision()`

```

class sage.rings.power_series_ring.PowerSeriesRing_domain(base_ring, name=None,
                                                             default_prec=None, sparse=False,
                                                             implementation=None, category=None)

```

Bases: *PowerSeriesRing_generic*

fraction_field()

Return the Laurent series ring over the fraction field of the base ring.

This is actually *not* the fraction field of this ring, but its completion with respect to the topology defined by the valuation. When we are working at finite precision, these two fields are indistinguishable; that is the reason why we allow ourselves to make this confusion here.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.fraction_field()
Laurent Series Ring in t over Rational Field
sage: Frac(R)
Laurent Series Ring in t over Rational Field
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.fraction_field()
Laurent Series Ring in t over Rational Field
>>> Frac(R)
Laurent Series Ring in t over Rational Field
```

```
class sage.rings.power_series_ring.PowerSeriesRing_generic(base_ring, name=None,
                                                            default_prec=None, sparse=False,
                                                            implementation=None,
                                                            category=None)
```

Bases: *UniqueRepresentation, Parent, Nonexact*

A power series ring.

base_extend(R)

Return the power series ring over R in the same variable as `self`, assuming there is a canonical coerce map from the base ring of `self` to R .

EXAMPLES:

```
sage: R.<T> = GF(7)[[]]; R
Power Series Ring in T over Finite Field of size 7
sage: R.change_ring(ZZ)
Power Series Ring in T over Integer Ring
sage: R.base_extend(ZZ)
Traceback (most recent call last):
...
TypeError: no base extension defined
```

```
>>> from sage.all import *
>>> R = GF(Integer(7))['T']; (T,) = R._first_ngens(1); R
Power Series Ring in T over Finite Field of size 7
>>> R.change_ring(ZZ)
Power Series Ring in T over Integer Ring
>>> R.base_extend(ZZ)
Traceback (most recent call last):
...
TypeError: no base extension defined
```

change_ring(*R*)

Return the power series ring over R in the same variable as `self`.

EXAMPLES:

```
sage: R.<T> = QQ[[]]; R
Power Series Ring in T over Rational Field
sage: R.change_ring(GF(7))
Power Series Ring in T over Finite Field of size 7
sage: R.base_extend(GF(7))
Traceback (most recent call last):
...
TypeError: no base extension defined
sage: R.base_extend(QuadraticField(3, 'a')) #_
↳needs sage.rings.number_field
Power Series Ring in T over Number Field in a
with defining polynomial x^2 - 3 with a = 1.732050807568878?
```

```
>>> from sage.all import *
>>> R = QQ[['T']]; (T,) = R._first_ngens(1); R
Power Series Ring in T over Rational Field
>>> R.change_ring(GF(Integer(7)))
Power Series Ring in T over Finite Field of size 7
>>> R.base_extend(GF(Integer(7)))
Traceback (most recent call last):
...
TypeError: no base extension defined
>>> R.base_extend(QuadraticField(Integer(3), 'a')) _
↳ # needs sage.rings.number_field
Power Series Ring in T over Number Field in a
with defining polynomial x^2 - 3 with a = 1.732050807568878?
```

change_var(*var*)

Return the power series ring in variable `var` over the same base ring.

EXAMPLES:

```
sage: R.<T> = QQ[[]]; R
Power Series Ring in T over Rational Field
sage: R.change_var('D')
Power Series Ring in D over Rational Field
```

```
>>> from sage.all import *
>>> R = QQ[['T']]; (T,) = R._first_ngens(1); R
Power Series Ring in T over Rational Field
>>> R.change_var('D')
Power Series Ring in D over Rational Field
```

characteristic()

Return the characteristic of this power series ring, which is the same as the characteristic of the base ring of the power series ring.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.characteristic()
0
sage: R.<w> = Integers(2^50)[[]]; R
Power Series Ring in w over Ring of integers modulo 1125899906842624
sage: R.characteristic()
1125899906842624

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.characteristic()
0
>>> R = Integers(Integer(2)**Integer(50))[['w']]; (w,) = R._first_ngens(1); R
Power Series Ring in w over Ring of integers modulo 1125899906842624
>>> R.characteristic()
1125899906842624

```

construction()

Return the functorial construction of `self`, namely, completion of the univariate polynomial ring with respect to the indeterminate (to a given precision).

EXAMPLES:

```

sage: R = PowerSeriesRing(ZZ, 'x')
sage: c, S = R.construction(); S
Univariate Polynomial Ring in x over Integer Ring
sage: R == c(S)
True
sage: R = PowerSeriesRing(ZZ, 'x', sparse=True)
sage: c, S = R.construction()
sage: R == c(S)
True

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, 'x')
>>> c, S = R.construction(); S
Univariate Polynomial Ring in x over Integer Ring
>>> R == c(S)
True
>>> R = PowerSeriesRing(ZZ, 'x', sparse=True)
>>> c, S = R.construction()
>>> R == c(S)
True

```

gen($n=0$)

Return the generator of this power series ring.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.gen()
t
sage: R.gen(3)

```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
IndexError: generator n>0 not defined
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.gen()
t
>>> R.gen(Integer(3))
Traceback (most recent call last):
...
IndexError: generator n>0 not defined
```

gens()

Return the generators of this ring.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.gens()
(t,)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.gens()
(t,)
```

is_dense()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_dense()
True
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_dense()
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> t.is_dense()
True
>>> R = PowerSeriesRing(ZZ, sparse=True, names=('t',)); (t,) = R._first_
↳ngens(1)
>>> t.is_dense()
False
```

is_exact()

Return False since the ring of power series over any ring is not exact.

EXAMPLES:


```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.is_exact()
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.is_exact()
False
```

is_field(*proof=True*)

Return False since the ring of power series over any ring is never a field.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.is_field()
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.is_field()
False
```

is_finite()

Return False since the ring of power series over any ring is never finite.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.is_finite()
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.is_finite()
False
```

is_sparse()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_sparse()
False
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_sparse()
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> t.is_sparse()
False
>>> R = PowerSeriesRing(ZZ, sparse=True, names=('t',)); (t,) = R._first_
```

(continues on next page)

(continued from previous page)

```

↪ngens(1)
>>> t.is_sparse()
True

```

laurent_series_ring()

If this is the power series ring $R[[t]]$, return the Laurent series ring $R((t))$.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(ZZ, default_prec=5)
sage: S = R.laurent_series_ring(); S
Laurent Series Ring in t over Integer Ring
sage: S.default_prec()
5
sage: f = 1 + t; g = 1/f; g
1 - t + t^2 - t^3 + t^4 + O(t^5)

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, default_prec=Integer(5), names=('t',)); (t,) = R._
↪first_ngens(1)
>>> S = R.laurent_series_ring(); S
Laurent Series Ring in t over Integer Ring
>>> S.default_prec()
5
>>> f = Integer(1) + t; g = Integer(1)/f; g
1 - t + t^2 - t^3 + t^4 + O(t^5)

```

ngens()

Return the number of generators of this power series ring.

This is always 1.

EXAMPLES:

```

sage: R.<t> = ZZ[[t]]
sage: R.ngens()
1

```

```

>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> R.ngens()
1

```

random_element (*prec=None, *args, **kws*)

Return a random power series.

INPUT:

- *prec* – integer specifying precision of output (default: default precision of *self*)
- **args, **kws* – passed on to the `random_element` method for the base ring

OUTPUT:

Power series with precision *prec* whose coefficients are random elements from the base ring, randomized subject to the arguments **args* and ***kws*.

ALGORITHM:

Call the `random_element` method on the underlying polynomial ring.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: R.random_element(5) # random
-4 - 1/2*t^2 - 1/95*t^3 + 1/2*t^4 + O(t^5)
sage: R.random_element(10) # random
-1/2 + 2*t - 2/7*t^2 - 25*t^3 - t^4 + 2*t^5 - 4*t^7 - 1/3*t^8 - t^9 + O(t^10)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.random_element(Integer(5)) # random
-4 - 1/2*t^2 - 1/95*t^3 + 1/2*t^4 + O(t^5)
>>> R.random_element(Integer(10)) # random
-1/2 + 2*t - 2/7*t^2 - 25*t^3 - t^4 + 2*t^5 - 4*t^7 - 1/3*t^8 - t^9 + O(t^10)
```

If given no argument, `random_element` uses default precision of self:

```
sage: T = PowerSeriesRing(ZZ, 't')
sage: T.default_prec()
20
sage: T.random_element() # random
4 + 2*t - t^2 - t^3 + 2*t^4 + t^5 + t^6 - 2*t^7 - t^8 - t^9 + t^11
- 6*t^12 + 2*t^14 + 2*t^16 - t^17 - 3*t^18 + O(t^20)
sage: S = PowerSeriesRing(ZZ, 't', default_prec=4)
sage: S.random_element() # random
2 - t - 5*t^2 + t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, 't')
>>> T.default_prec()
20
>>> T.random_element() # random
4 + 2*t - t^2 - t^3 + 2*t^4 + t^5 + t^6 - 2*t^7 - t^8 - t^9 + t^11
- 6*t^12 + 2*t^14 + 2*t^16 - t^17 - 3*t^18 + O(t^20)
>>> S = PowerSeriesRing(ZZ, 't', default_prec=Integer(4))
>>> S.random_element() # random
2 - t - 5*t^2 + t^3 + O(t^4)
```

Further arguments are passed to the underlying base ring ([Issue #9481](#)):

```
sage: SZ = PowerSeriesRing(ZZ, 'v')
sage: SQ = PowerSeriesRing(QQ, 'v')
sage: SR = PowerSeriesRing(RR, 'v')

sage: SZ.random_element(x=4, y=6) # random
4 + 5*v + 5*v^2 + 5*v^3 + 4*v^4 + 5*v^5 + 5*v^6 + 5*v^7 + 4*v^8
+ 5*v^9 + 4*v^10 + 4*v^11 + 5*v^12 + 5*v^13 + 5*v^14 + 5*v^15
+ 5*v^16 + 5*v^17 + 4*v^18 + 5*v^19 + O(v^20)
sage: SZ.random_element(3, x=4, y=6) # random
5 + 4*v + 5*v^2 + O(v^3)
```

(continues on next page)

(continued from previous page)

```
sage: SQ.random_element(3, num_bound=3, den_bound=100) # random
1/87 - 3/70*v - 3/44*v^2 + O(v^3)
sage: SR.random_element(3, max=10, min=-10) # random
2.85948321262904 - 9.73071330911226*v - 6.60414378519265*v^2 + O(v^3)
```

```
>>> from sage.all import *
>>> SZ = PowerSeriesRing(ZZ, 'v')
>>> SQ = PowerSeriesRing(QQ, 'v')
>>> SR = PowerSeriesRing(RR, 'v')

>>> SZ.random_element(x=Integer(4), y=Integer(6)) # random
4 + 5*v + 5*v^2 + 5*v^3 + 4*v^4 + 5*v^5 + 5*v^6 + 5*v^7 + 4*v^8
+ 5*v^9 + 4*v^10 + 4*v^11 + 5*v^12 + 5*v^13 + 5*v^14 + 5*v^15
+ 5*v^16 + 5*v^17 + 4*v^18 + 5*v^19 + O(v^20)
>>> SZ.random_element(Integer(3), x=Integer(4), y=Integer(6)) # random
5 + 4*v + 5*v^2 + O(v^3)
>>> SQ.random_element(Integer(3), num_bound=Integer(3), den_
↳bound=Integer(100)) # random
1/87 - 3/70*v - 3/44*v^2 + O(v^3)
>>> SR.random_element(Integer(3), max=Integer(10), min=-Integer(10)) # random
2.85948321262904 - 9.73071330911226*v - 6.60414378519265*v^2 + O(v^3)
```

residue_field()

Return the residue field of this power series ring.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(GF(17))
sage: R.residue_field()
Finite Field of size 17
sage: R.<x> = PowerSeriesRing(Zp(5)) #_
↳needs sage.rings.padics
sage: R.residue_field() #_
↳needs sage.rings.padics
Finite Field of size 5
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(GF(Integer(17)), names=('x',)); (x,) = R._first_
↳ngens(1)
>>> R.residue_field()
Finite Field of size 17
>>> R = PowerSeriesRing(Zp(Integer(5)), names=('x',)); (x,) = R._first_
↳ngens(1) # needs sage.rings.padics
>>> R.residue_field() #_
↳needs sage.rings.padics
Finite Field of size 5
```

uniformizer()

Return a uniformizer of this power series ring if it is a discrete valuation ring (i.e., if the base ring is actually a field). Otherwise, an error is raised.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(QQ)
sage: R.uniformizer()
t

sage: R.<t> = PowerSeriesRing(ZZ)
sage: R.uniformizer()
Traceback (most recent call last):
...
TypeError: The base ring is not a field

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.uniformizer()
t

>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.uniformizer()
Traceback (most recent call last):
...
TypeError: The base ring is not a field

```

variable_names_recursive (*depth=None*)

Return the list of variable names of this and its base rings.

EXAMPLES:

```

sage: R = QQ[['x']][['y']][['z']]
sage: R.variable_names_recursive()
('x', 'y', 'z')
sage: R.variable_names_recursive(2)
('y', 'z')

```

```

>>> from sage.all import *
>>> R = QQ[['x']][['y']][['z']]
>>> R.variable_names_recursive()
('x', 'y', 'z')
>>> R.variable_names_recursive(Integer(2))
('y', 'z')

```

```

class sage.rings.power_series_ring.PowerSeriesRing_over_field(base_ring, name=None,
                                                                default_prec=None, sparse=False,
                                                                implementation=None,
                                                                category=None)

```

Bases: *PowerSeriesRing_domain*

fraction_field()

Return the fraction field of this power series ring, which is defined since this is over a field.

This fraction field is just the Laurent series ring over the base field.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(GF(7))
sage: R.fraction_field()

```

(continues on next page)

(continued from previous page)

```
Laurent Series Ring in t over Finite Field of size 7
sage: Frac(R)
Laurent Series Ring in t over Finite Field of size 7
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(GF(Integer(7)), names=('t',)); (t,) = R._first_
↳ngens(1)
>>> R.fraction_field()
Laurent Series Ring in t over Finite Field of size 7
>>> Frac(R)
Laurent Series Ring in t over Finite Field of size 7
```

`sage.rings.power_series_ring.is_PowerSeriesRing(R)`

Return True if this is a *univariate* power series ring. This is in keeping with the behavior of `is_PolynomialRing` versus `is_MPolynomialRing`.

EXAMPLES:

```
sage: from sage.rings.power_series_ring import is_PowerSeriesRing
sage: is_PowerSeriesRing(10)
doctest:warning...
DeprecationWarning: The function is_PowerSeriesRing is deprecated;
use 'isinstance(..., (PowerSeriesRing_generic, LazyPowerSeriesRing) and ....
↳ngens() == 1)' instead.
See https://github.com/sagemath/sage/issues/38290 for details.
False
sage: is_PowerSeriesRing(QQ[['x']])
True
sage: is_PowerSeriesRing(LazyPowerSeriesRing(QQ, 'x'))
True
sage: is_PowerSeriesRing(LazyPowerSeriesRing(QQ, 'x, y'))
False
```

```
>>> from sage.all import *
>>> from sage.rings.power_series_ring import is_PowerSeriesRing
>>> is_PowerSeriesRing(Integer(10))
doctest:warning...
DeprecationWarning: The function is_PowerSeriesRing is deprecated;
use 'isinstance(..., (PowerSeriesRing_generic, LazyPowerSeriesRing) and ....
↳ngens() == 1)' instead.
See https://github.com/sagemath/sage/issues/38290 for details.
False
>>> is_PowerSeriesRing(QQ[['x']])
True
>>> is_PowerSeriesRing(LazyPowerSeriesRing(QQ, 'x'))
True
>>> is_PowerSeriesRing(LazyPowerSeriesRing(QQ, 'x, y'))
False
```

`sage.rings.power_series_ring.unpickle_power_series_ring_v0` (*base_ring*, *name*, *default_prec*, *sparse*)

Unpickle (deserialize) a univariate power series ring according to the given inputs.

EXAMPLES:

```
sage: P.<x> = PowerSeriesRing(QQ)
sage: loads(dumps(P)) == P # indirect doctest
True
```

```
>>> from sage.all import *
>>> P = PowerSeriesRing(QQ, names=('x',)); (x,) = P._first_ngens(1)
>>> loads(dumps(P)) == P # indirect doctest
True
```


POWER SERIES

Sage provides an implementation of dense and sparse power series over any Sage base ring. This is the base class of the implementations of univariate and multivariate power series ring elements in Sage (see also *Power Series Methods*, *Multivariate Power Series*).

AUTHORS:

- William Stein
- David Harvey (2006-09-11): added `solve_linear_de()` method
- Robert Bradshaw (2007-04): `sqrt`, `rmul`, `lmul`, `shifting`
- Robert Bradshaw (2007-04): Cython version
- Simon King (2012-08): use category and coercion framework, [Issue #13412](#)

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: TestSuite(R).run()
sage: R([1,2,3])
1 + 2*x + 3*x^2
sage: R([1,2,3], 10)
1 + 2*x + 3*x^2 + O(x^10)
sage: f = 1 + 2*x - 3*x^3 + O(x^4); f
1 + 2*x - 3*x^3 + O(x^4)
sage: f^10
1 + 20*x + 180*x^2 + 930*x^3 + O(x^4)
sage: g = 1/f; g
1 - 2*x + 4*x^2 - 5*x^3 + O(x^4)
sage: g * f
1 + O(x^4)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> TestSuite(R).run()
>>> R([Integer(1),Integer(2),Integer(3)])
1 + 2*x + 3*x^2
>>> R([Integer(1),Integer(2),Integer(3)], Integer(10))
1 + 2*x + 3*x^2 + O(x^10)
>>> f = Integer(1) + Integer(2)*x - Integer(3)*x**Integer(3) + O(x**Integer(4)); f
1 + 2*x - 3*x^3 + O(x^4)
>>> f**Integer(10)
1 + 20*x + 180*x^2 + 930*x^3 + O(x^4)
```

(continues on next page)

(continued from previous page)

```
>>> g = Integer(1)/f; g
1 - 2*x + 4*x^2 - 5*x^3 + O(x^4)
>>> g * f
1 + O(x^4)
```

In Python (as opposed to Sage) create the power series ring and its generator as follows:

```
sage: R = PowerSeriesRing(ZZ, 'x')
sage: x = R.gen()
sage: parent(x)
Power Series Ring in x over Integer Ring
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, 'x')
>>> x = R.gen()
>>> parent(x)
Power Series Ring in x over Integer Ring
```

EXAMPLES:

This example illustrates that coercion for power series rings is consistent with coercion for polynomial rings.

```
sage: poly_ring1.<gen1> = PolynomialRing(QQ)
sage: poly_ring2.<gen2> = PolynomialRing(QQ)
sage: huge_ring.<x> = PolynomialRing(poly_ring1)
```

```
>>> from sage.all import *
>>> poly_ring1 = PolynomialRing(QQ, names=('gen1',)); (gen1,) = poly_ring1._first_
↳ngens(1)
>>> poly_ring2 = PolynomialRing(QQ, names=('gen2',)); (gen2,) = poly_ring2._first_
↳ngens(1)
>>> huge_ring = PolynomialRing(poly_ring1, names=('x',)); (x,) = huge_ring._first_
↳ngens(1)
```

The generator of the first ring gets coerced in as itself, since it is the base ring.

```
sage: huge_ring(gen1)
gen1
```

```
>>> from sage.all import *
>>> huge_ring(gen1)
gen1
```

The generator of the second ring gets mapped via the natural map sending one generator to the other.

```
sage: huge_ring(gen2)
x
```

```
>>> from sage.all import *
>>> huge_ring(gen2)
x
```

With power series the behavior is the same.

```

sage: power_ring1.<gen1> = PowerSeriesRing(QQ)
sage: power_ring2.<gen2> = PowerSeriesRing(QQ)
sage: huge_power_ring.<x> = PowerSeriesRing(power_ring1)
sage: huge_power_ring(gen1)
gen1
sage: huge_power_ring(gen2)
x

```

```

>>> from sage.all import *
>>> power_ring1 = PowerSeriesRing(QQ, names=('gen1',)); (gen1,) = power_ring1._first_
↳ngens(1)
>>> power_ring2 = PowerSeriesRing(QQ, names=('gen2',)); (gen2,) = power_ring2._first_
↳ngens(1)
>>> huge_power_ring = PowerSeriesRing(power_ring1, names=('x',)); (x,) = huge_power_
↳ring._first_ngens(1)
>>> huge_power_ring(gen1)
gen1
>>> huge_power_ring(gen2)
x

```

class sage.rings.power_series_ring_element.**PowerSeries**

Bases: [AlgebraElement](#)

A power series. Base class of univariate and multivariate power series. The following methods are available with both types of objects.

O(*prec*)

Return this series plus $O(x^{\text{prec}})$. Does not change *self*.

EXAMPLES:

```

sage: R.<x> = PowerSeriesRing(ZZ)
sage: p = 1 + x^2 + x^10; p
1 + x^2 + x^10
sage: p.O(15)
1 + x^2 + x^10 + O(x^15)
sage: p.O(5)
1 + x^2 + O(x^5)
sage: p.O(-5)
Traceback (most recent call last):
...
ValueError: prec (= -5) must be nonnegative

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = Integer(1) + x**Integer(2) + x**Integer(10); p
1 + x^2 + x^10
>>> p.O(Integer(15))
1 + x^2 + x^10 + O(x^15)
>>> p.O(Integer(5))
1 + x^2 + O(x^5)
>>> p.O(-Integer(5))
Traceback (most recent call last):

```

(continues on next page)

(continued from previous page)

```
...
ValueError: prec (= -5) must be nonnegative
```

V(n)

If $f = \sum a_m x^m$, then this function returns $\sum a_m x^{nm}$.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: p = 1 + x^2 + x^10; p
1 + x^2 + x^10
sage: p.V(3)
1 + x^6 + x^30
sage: (p + O(x^20)).V(3)
1 + x^6 + x^30 + O(x^60)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = Integer(1) + x**Integer(2) + x**Integer(10); p
1 + x^2 + x^10
>>> p.V(Integer(3))
1 + x^6 + x^30
>>> (p + O(x**Integer(20))).V(Integer(3))
1 + x^6 + x^30 + O(x^60)
```

add_bigoh(prec)

Return the power series of precision at most prec got by adding $O(q^{\text{prec}})$ to f , where q is the variable.

EXAMPLES:

```
sage: R.<A> = RDF[[[]]
sage: f = (1+A+O(A^5))^5; f
1.0 + 5.0*A + 10.0*A^2 + 10.0*A^3 + 5.0*A^4 + O(A^5)
sage: f.add_bigoh(3)
1.0 + 5.0*A + 10.0*A^2 + O(A^3)
sage: f.add_bigoh(5)
1.0 + 5.0*A + 10.0*A^2 + 10.0*A^3 + 5.0*A^4 + O(A^5)
```

```
>>> from sage.all import *
>>> R = RDF[['A']]; (A,) = R._first_ngens(1)
>>> f = (Integer(1)+A+O(A**Integer(5))**Integer(5); f
1.0 + 5.0*A + 10.0*A^2 + 10.0*A^3 + 5.0*A^4 + O(A^5)
>>> f.add_bigoh(Integer(3))
1.0 + 5.0*A + 10.0*A^2 + O(A^3)
>>> f.add_bigoh(Integer(5))
1.0 + 5.0*A + 10.0*A^2 + 10.0*A^3 + 5.0*A^4 + O(A^5)
```

base_extend(R)

Return a copy of this power series but with coefficients in R .

The following coercion uses `base_extend` implicitly:

```
sage: R.<t> = ZZ[['t']]
sage: (t - t^2) * Mod(1, 3)
t + 2*t^2
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (t - t**Integer(2)) * Mod(Integer(1), Integer(3))
t + 2*t^2
```

base_ring()

Return the base ring that this power series is defined over.

EXAMPLES:

```
sage: R.<t> = GF(49, 'alpha')[[]] #_
↳needs sage.rings.finite_rings
sage: (t^2 + O(t^3)).base_ring() #_
↳needs sage.rings.finite_rings
Finite Field in alpha of size 7^2
```

```
>>> from sage.all import *
>>> R = GF(Integer(49), 'alpha')[['t']]; (t,) = R._first_ngens(1) # needs sage.
↳rings.finite_rings
>>> (t**Integer(2) + O(t**Integer(3))).base_ring() _
↳ # needs sage.rings.finite_rings
Finite Field in alpha of size 7^2
```

change_ring(R)

Change if possible the coefficients of self to lie in R.

EXAMPLES:

```
sage: R.<T> = QQ[[]]; R
Power Series Ring in T over Rational Field
sage: f = 1 - 1/2*T + 1/3*T^2 + O(T^3)
sage: f.base_extend(GF(5))
Traceback (most recent call last):
...
TypeError: no base extension defined
sage: f.change_ring(GF(5))
1 + 2*T + 2*T^2 + O(T^3)
sage: f.change_ring(GF(3))
Traceback (most recent call last):
...
ZeroDivisionError: inverse of Mod(0, 3) does not exist
```

```
>>> from sage.all import *
>>> R = QQ[['T']]; (T,) = R._first_ngens(1); R
Power Series Ring in T over Rational Field
>>> f = Integer(1) - Integer(1)/Integer(2)*T + Integer(1)/
↳Integer(3)*T**Integer(2) + O(T**Integer(3))
>>> f.base_extend(GF(Integer(5)))
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```

...
TypeError: no base extension defined
>>> f.change_ring(GF(Integer(5)))
1 + 2*T + 2*T^2 + O(T^3)
>>> f.change_ring(GF(Integer(3)))
Traceback (most recent call last):
...
ZeroDivisionError: inverse of Mod(0, 3) does not exist

```

We can only change the ring if there is a `__call__` coercion defined. The following succeeds because `ZZ(K(4))` is defined.

```

sage: K.<a> = NumberField(cyclotomic_polynomial(3), 'a') #_
↪needs sage.rings.number_field
sage: R.<t> = K[['t']] #_
↪needs sage.rings.number_field
sage: (4*t).change_ring(ZZ) #_
↪needs sage.rings.number_field
4*t

```

```

>>> from sage.all import *
>>> K = NumberField(cyclotomic_polynomial(Integer(3)), 'a', names=('a',)); (a,
↪) = K._first_ngens(1) # needs sage.rings.number_field
>>> R = K[['t']]; (t,) = R._first_ngens(1) # needs sage.rings.number_field
>>> (Integer(4)*t).change_ring(ZZ) _
↪ # needs sage.rings.number_field
4*t

```

This does not succeed because `ZZ(K(a+1))` is not defined.

```

sage: K.<a> = NumberField(cyclotomic_polynomial(3), 'a') #_
↪needs sage.rings.number_field
sage: R.<t> = K[['t']] #_
↪needs sage.rings.number_field
sage: ((a+1)*t).change_ring(ZZ) #_
↪needs sage.rings.number_field
Traceback (most recent call last):
...
TypeError: Unable to coerce a + 1 to an integer

```

```

>>> from sage.all import *
>>> K = NumberField(cyclotomic_polynomial(Integer(3)), 'a', names=('a',)); (a,
↪) = K._first_ngens(1) # needs sage.rings.number_field
>>> R = K[['t']]; (t,) = R._first_ngens(1) # needs sage.rings.number_field
>>> ((a+Integer(1))*t).change_ring(ZZ) _
↪ # needs sage.rings.number_field
Traceback (most recent call last):
...
TypeError: Unable to coerce a + 1 to an integer

```

`coefficients()`

Return the nonzero coefficients of `self`.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2 - 10/3*t^3
sage: f.coefficients()
[1, 1, -10/3]
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t + t**Integer(2) - Integer(10)/Integer(3)*t**Integer(3)
>>> f.coefficients()
[1, 1, -10/3]
```

`common_prec(f)`

Return minimum precision of f and `self`.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
```

```
sage: f = t + t^2 + O(t^3)
sage: g = t + t^3 + t^4 + O(t^4)
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2) + O(t**Integer(3))
>>> g = t + t**Integer(3) + t**Integer(4) + O(t**Integer(4))
>>> f.common_prec(g)
3
>>> g.common_prec(f)
3
```

```
sage: f = t + t^2 + O(t^3)
sage: g = t^2
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2) + O(t**Integer(3))
>>> g = t**Integer(2)
>>> f.common_prec(g)
3
>>> g.common_prec(f)
3
```

```
sage: f = t + t^2
sage: f = t^2
sage: f.common_prec(g)
+Infinity
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2)
>>> f = t**Integer(2)
>>> f.common_prec(g)
+Infinity
```

`cos` (*prec*='infinity')

Apply `cos` to the formal power series.

INPUT:

- *prec* – integer or infinity; the degree to truncate the result to

OUTPUT: a new power series

EXAMPLES:

For one variable:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = (t + t**2).O(4)
sage: cos(f)
1 - 1/2*t^2 - t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> f = (t + t**Integer(2)).O(Integer(4))
>>> cos(f)
1 - 1/2*t^2 - t^3 + O(t^4)
```

For several variables:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: cos(f)
1 - 1/2*a^2 - a*b - 1/2*b^2 + O(a, b)^3
sage: f.cos()
1 - 1/2*a^2 - a*b - 1/2*b^2 + O(a, b)^3
sage: f.cos(prec=2)
1 + O(a, b)^2
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> cos(f)
1 - 1/2*a^2 - a*b - 1/2*b^2 + O(a, b)^3
>>> f.cos()
1 - 1/2*a^2 - a*b - 1/2*b^2 + O(a, b)^3
```

(continues on next page)

(continued from previous page)

```
>>> f.cos(prec=Integer(2))
1 + O(a, b)^2
```

If the power series has a nonzero constant coefficient c , one raises an error:

```
sage: g = 2+f
sage: cos(g)
Traceback (most recent call last):
...
ValueError: can only apply cos to formal power series with zero constant term
```

```
>>> from sage.all import *
>>> g = Integer(2)+f
>>> cos(g)
Traceback (most recent call last):
...
ValueError: can only apply cos to formal power series with zero constant term
```

If no precision is specified, the default precision is used:

```
sage: T.default_prec()
12
sage: cos(a)
1 - 1/2*a^2 + 1/24*a^4 - 1/720*a^6 + 1/40320*a^8 - 1/3628800*a^10 + O(a, b)^12
sage: a.cos(prec=5)
1 - 1/2*a^2 + 1/24*a^4 + O(a, b)^5
sage: cos(a + T.O(5))
1 - 1/2*a^2 + 1/24*a^4 + O(a, b)^5
```

```
>>> from sage.all import *
>>> T.default_prec()
12
>>> cos(a)
1 - 1/2*a^2 + 1/24*a^4 - 1/720*a^6 + 1/40320*a^8 - 1/3628800*a^10 + O(a, b)^12
>>> a.cos(prec=Integer(5))
1 - 1/2*a^2 + 1/24*a^4 + O(a, b)^5
>>> cos(a + T.O(Integer(5)))
1 - 1/2*a^2 + 1/24*a^4 + O(a, b)^5
```

cosh (*prec*='infinity')

Apply cosh to the formal power series.

INPUT:

- *prec* – integer or infinity; the degree to truncate the result to

OUTPUT: a new power series

EXAMPLES:

For one variable:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = (t + t**2).O(4)
```

(continues on next page)

(continued from previous page)

```
sage: cosh(f)
1 + 1/2*t^2 + t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> f = (t + t**Integer(2)).O(Integer(4))
>>> cosh(f)
1 + 1/2*t^2 + t^3 + O(t^4)
```

For several variables:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: cosh(f)
1 + 1/2*a^2 + a*b + 1/2*b^2 + O(a, b)^3
sage: f.cosh()
1 + 1/2*a^2 + a*b + 1/2*b^2 + O(a, b)^3
sage: f.cosh(prec=2)
1 + O(a, b)^2
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> cosh(f)
1 + 1/2*a^2 + a*b + 1/2*b^2 + O(a, b)^3
>>> f.cosh()
1 + 1/2*a^2 + a*b + 1/2*b^2 + O(a, b)^3
>>> f.cosh(prec=Integer(2))
1 + O(a, b)^2
```

If the power series has a nonzero constant coefficient c , one raises an error:

```
sage: g = 2 + f
sage: cosh(g)
Traceback (most recent call last):
...
ValueError: can only apply cosh to formal power series with zero
constant term
```

```
>>> from sage.all import *
>>> g = Integer(2) + f
>>> cosh(g)
Traceback (most recent call last):
...
ValueError: can only apply cosh to formal power series with zero
constant term
```

If no precision is specified, the default precision is used:

```
sage: T.default_prec()
12
```

(continues on next page)

(continued from previous page)

```
sage: cosh(a)
1 + 1/2*a^2 + 1/24*a^4 + 1/720*a^6 + 1/40320*a^8 + 1/3628800*a^10 +
O(a, b)^12
sage: a.cosh(prec=5)
1 + 1/2*a^2 + 1/24*a^4 + O(a, b)^5
sage: cosh(a + T.O(5))
1 + 1/2*a^2 + 1/24*a^4 + O(a, b)^5
```

```
>>> from sage.all import *
>>> T.default_prec()
12
>>> cosh(a)
1 + 1/2*a^2 + 1/24*a^4 + 1/720*a^6 + 1/40320*a^8 + 1/3628800*a^10 +
O(a, b)^12
>>> a.cosh(prec=Integer(5))
1 + 1/2*a^2 + 1/24*a^4 + O(a, b)^5
>>> cosh(a + T.O(Integer(5)))
1 + 1/2*a^2 + 1/24*a^4 + O(a, b)^5
```

degree()

Return the degree of this power series, which is by definition the degree of the underlying polynomial.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: f = t^100000 + O(t^1000000)
sage: f.degree()
100000
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, sparse=True, names=('t',)); (t,) = R._first_
    ↪ngens(1)
>>> f = t**Integer(100000) + O(t**Integer(1000000))
>>> f.degree()
100000
```

derivative(*args)

The formal derivative of this power series, with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the global derivative() function for more details.

 See also

`_derivative()`

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(QQ)
sage: g = -x + x^2/2 - x^4 + O(x^6)
sage: g.derivative()
-1 + x - 4*x^3 + O(x^5)
```

(continues on next page)

(continued from previous page)

```
sage: g.derivative(x)
-1 + x - 4*x^3 + O(x^5)
sage: g.derivative(x, x)
1 - 12*x^2 + O(x^4)
sage: g.derivative(x, 2)
1 - 12*x^2 + O(x^4)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> g = -x + x**Integer(2)/Integer(2) - x**Integer(4) + O(x**Integer(6))
>>> g.derivative()
-1 + x - 4*x^3 + O(x^5)
>>> g.derivative(x)
-1 + x - 4*x^3 + O(x^5)
>>> g.derivative(x, x)
1 - 12*x^2 + O(x^4)
>>> g.derivative(x, Integer(2))
1 - 12*x^2 + O(x^4)
```

egf_to_ogf()

Return the ordinary generating function power series, assuming `self` is an exponential generating function power series.

This is a formal Laplace transform.

This function is known as `pari:serlaplace` in PARI/GP.

 See also

`ogf_to_egf()` for the inverse method.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2/factorial(2) + 2*t^3/factorial(3)
sage: f.egf_to_ogf()
t + t^2 + 2*t^3
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t + t**Integer(2)/factorial(Integer(2)) + Integer(2)*t**Integer(3)/
↳ factorial(Integer(3))
>>> f.egf_to_ogf()
t + t^2 + 2*t^3
```

exp(prec=None)

Return exp of this power series to the indicated precision.

INPUT:

- `prec` – integer (default: `self.parent().default_prec`)

ALGORITHM: See `solve_linear_de()`.

Note

- Screwy things can happen if the coefficient ring is not a field of characteristic zero. See `solve_linear_de()`.

AUTHORS:

- David Harvey (2006-09-08): rewrote to use simplest possible “lazy” algorithm.
- David Harvey (2006-09-10): rewrote to use divide-and-conquer strategy.
- David Harvey (2006-09-11): factored functionality out to `solve_linear_de()`.
- Sourav Sen Gupta, David Harvey (2008-11): handle constant term

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=10)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(10), names=('t',)); (t,) = R.
↳_first_ngens(1)
```

Check that $\exp(t)$ is, well, $\exp(t)$:

```
sage: (t + O(t^10)).exp()
1 + t + 1/2*t^2 + 1/6*t^3 + 1/24*t^4 + 1/120*t^5 + 1/720*t^6
+ 1/5040*t^7 + 1/40320*t^8 + 1/362880*t^9 + O(t^10)
```

```
>>> from sage.all import *
>>> (t + O(t**Integer(10))).exp()
1 + t + 1/2*t^2 + 1/6*t^3 + 1/24*t^4 + 1/120*t^5 + 1/720*t^6
+ 1/5040*t^7 + 1/40320*t^8 + 1/362880*t^9 + O(t^10)
```

Check that $\exp(\log(1+t))$ is $1+t$:

```
sage: (sum([(-t)^n/n for n in range(1, 10)]) + O(t^10)).exp()
1 + t + O(t^10)
```

```
>>> from sage.all import *
>>> (sum([(-t)**n/n for n in range(Integer(1), Integer(10))]) +
↳ O(t**Integer(10))).exp()
1 + t + O(t^10)
```

Check that $\exp(2t + t^2 - t^5)$ is whatever it is:

```
sage: (2*t + t^2 - t^5 + O(t^10)).exp()
1 + 2*t + 3*t^2 + 10/3*t^3 + 19/6*t^4 + 8/5*t^5 - 7/90*t^6
- 538/315*t^7 - 425/168*t^8 - 30629/11340*t^9 + O(t^10)
```

```
>>> from sage.all import *
>>> (Integer(2)*t + t**Integer(2) - t**Integer(5) + O(t**Integer(10))).exp()
1 + 2*t + 3*t^2 + 10/3*t^3 + 19/6*t^4 + 8/5*t^5 - 7/90*t^6
- 538/315*t^7 - 425/168*t^8 - 30629/11340*t^9 + O(t^10)
```

Check requesting lower precision:

```
sage: (t + t^2 - t^5 + O(t^10)).exp(5)
1 + t + 3/2*t^2 + 7/6*t^3 + 25/24*t^4 + O(t^5)
```

```
>>> from sage.all import *
>>> (t + t**Integer(2) - t**Integer(5) + O(t**Integer(10))).exp(Integer(5))
1 + t + 3/2*t^2 + 7/6*t^3 + 25/24*t^4 + O(t^5)
```

Can't get more precision than the input:

```
sage: (t + t^2 + O(t^3)).exp(10)
1 + t + 3/2*t^2 + O(t^3)
```

```
>>> from sage.all import *
>>> (t + t**Integer(2) + O(t**Integer(3))).exp(Integer(10))
1 + t + 3/2*t^2 + O(t^3)
```

Check some boundary cases:

```
sage: (t + O(t^2)).exp(1)
1 + O(t)
sage: (t + O(t^2)).exp(0)
O(t^0)
```

```
>>> from sage.all import *
>>> (t + O(t**Integer(2))).exp(Integer(1))
1 + O(t)
>>> (t + O(t**Integer(2))).exp(Integer(0))
O(t^0)
```

Handle nonzero constant term (fixes [Issue #4477](#)):

```
sage: # needs sage.rings.real_mpfr
sage: R.<x> = PowerSeriesRing(RR)
sage: (1 + x + x^2 + O(x^3)).exp()
2.71828182845905 + 2.71828182845905*x + 4.07742274268857*x^2 + O(x^3)
```

```
>>> from sage.all import *
>>> # needs sage.rings.real_mpfr
>>> R = PowerSeriesRing(RR, names=('x',)); (x,) = R._first_ngens(1)
>>> (Integer(1) + x + x**Integer(2) + O(x**Integer(3))).exp()
2.71828182845905 + 2.71828182845905*x + 4.07742274268857*x^2 + O(x^3)
```

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: (1 + x + O(x^2)).exp()
↳needs sage.symbolic
Traceback (most recent call last):
...
ArithmeticError: exponential of constant term does not belong
to coefficient ring (consider working in a larger ring)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> (Integer(1) + x + O(x**Integer(2))).exp()
↳ # needs sage.symbolic
Traceback (most recent call last):
...
ArithmeticError: exponential of constant term does not belong
to coefficient ring (consider working in a larger ring)
```

```
sage: R.<x> = PowerSeriesRing(GF(5))
sage: (1 + x + O(x^2)).exp()
Traceback (most recent call last):
...
ArithmeticError: constant term of power series does not support exponentiation
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(GF(Integer(5)), names=('x',)); (x,) = R._first_
↳ ngens(1)
>>> (Integer(1) + x + O(x**Integer(2))).exp()
Traceback (most recent call last):
...
ArithmeticError: constant term of power series does not support exponentiation
```

exponents()

Return the exponents appearing in `self` with nonzero coefficients.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2 - 10/3*t^3
sage: f.exponents()
[1, 2, 3]
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t + t**Integer(2) - Integer(10)/Integer(3)*t**Integer(3)
>>> f.exponents()
[1, 2, 3]
```

inverse()

Return the inverse of `self`, i.e., `self^(-1)`.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: t.inverse()
t^-1
sage: type(_)
<class 'sage.rings.laurent_series_ring_element.LaurentSeries'>
sage: (1-t).inverse()
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + ...
```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, sparse=True, names=('t',)); (t,) = R._first_
↳ngens(1)
>>> t.inverse()
t^-1
>>> type(_)
<class 'sage.rings.laurent_series_ring_element.LaurentSeries'>
>>> (Integer(1)-t).inverse()
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + ...

```

is_dense()

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_dense()
True
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_dense()
False

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> t.is_dense()
True
>>> R = PowerSeriesRing(ZZ, sparse=True, names=('t',)); (t,) = R._first_
↳ngens(1)
>>> t.is_dense()
False

```

is_gen()

Return True if this is the generator (the variable) of the power series ring.

EXAMPLES:

```

sage: R.<t> = QQ[[[]]
sage: t.is_gen()
True
sage: (1 + 2*t).is_gen()
False

```

```

>>> from sage.all import *
>>> R = QQ[['t']]; (t,) = R._first_ngens(1)
>>> t.is_gen()
True
>>> (Integer(1) + Integer(2)*t).is_gen()
False

```

Note that this only returns True on the actual generator, not on something that happens to be equal to it.

```

sage: (1*t).is_gen()
False
sage: 1*t == t
True

```



```
>>> from sage.all import *
>>> (Integer(1)*t).is_gen()
False
>>> Integer(1)*t == t
True
```

is_monomial()

Return True if this element is a monomial. That is, if self is x^n for some nonnegative integer n .

EXAMPLES:

```
sage: k.<z> = PowerSeriesRing(QQ, 'z')
sage: z.is_monomial()
True
sage: k(1).is_monomial()
True
sage: (z+1).is_monomial()
False
sage: (z^2909).is_monomial()
True
sage: (3*z^2909).is_monomial()
False
```

```
>>> from sage.all import *
>>> k = PowerSeriesRing(QQ, 'z', names=('z',)); (z,) = k._first_ngens(1)
>>> z.is_monomial()
True
>>> k(Integer(1)).is_monomial()
True
>>> (z+Integer(1)).is_monomial()
False
>>> (z**Integer(2909)).is_monomial()
True
>>> (Integer(3)*z**Integer(2909)).is_monomial()
False
```

is_sparse()

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: t.is_sparse()
False
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: t.is_sparse()
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> t.is_sparse()
False
>>> R = PowerSeriesRing(ZZ, sparse=True, names=('t',)); (t,) = R._first_
↳ngens(1)
```

(continues on next page)

(continued from previous page)

```
>>> t.is_sparse()
True
```

is_square()

Return True if this function has a square root in this ring, e.g., there is an element y in `self.parent()` such that y^2 equals `self`.

ALGORITHM: If the base ring is a field, this is true whenever the power series has even valuation and the leading coefficient is a perfect square.

For an integral domain, it attempts the square root in the fraction field and tests whether or not the result lies in the original ring.

EXAMPLES:

```
sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: (1+t).is_square()
True
sage: (2+t).is_square()
False
sage: (2+t.change_ring(RR)).is_square()
True
sage: t.is_square()
False
sage: K.<t> = PowerSeriesRing(ZZ, 't', 5)
sage: (1+t).is_square()
False
sage: f = (1+t)^100
sage: f.is_square()
True
```

```
>>> from sage.all import *
>>> K = PowerSeriesRing(QQ, 't', Integer(5), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> (Integer(1)+t).is_square()
True
>>> (Integer(2)+t).is_square()
False
>>> (Integer(2)+t.change_ring(RR)).is_square()
True
>>> t.is_square()
False
>>> K = PowerSeriesRing(ZZ, 't', Integer(5), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> (Integer(1)+t).is_square()
False
>>> f = (Integer(1)+t)**Integer(100)
>>> f.is_square()
True
```

is_unit()

Return True if this power series is invertible.

A power series is invertible precisely when the constant term is invertible.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: (-1 + t - t^5).is_unit()
True
sage: (3 + t - t^5).is_unit()
False
sage: O(t^0).is_unit()
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> (-Integer(1) + t - t**Integer(5)).is_unit()
True
>>> (Integer(3) + t - t**Integer(5)).is_unit()
False
>>> O(t**Integer(0)).is_unit()
False
```

AUTHORS:

- David Harvey (2006-09-03)

jacobi_continued_fraction()

Return the Jacobi continued fraction of `self`.

The J-fraction or Jacobi continued fraction of a power series is a continued fraction expansion with steps of size two. We use the following convention

$$1/(1 + A_0t + B_0t^2/(1 + A_1t + B_1t^2/(1 + \cdots)))$$

OUTPUT:

tuple of pairs (A_n, B_n) for $n \geq 0$

The expansion is done as long as possible given the precision. Whenever the expansion is not well-defined, because it would require to divide by zero, an exception is raised.

See section 2.7 of [Kra1999det] for the close relationship of this kind of expansion with Hankel determinants and orthogonal polynomials.

EXAMPLES:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: s = sum(factorial(k) * t**k for k in range(12)).O(12)
sage: s.jacobi_continued_fraction()
((-1, -1), (-3, -4), (-5, -9), (-7, -16), (-9, -25))
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> s = sum(factorial(k) * t**k for k in range(Integer(12))).O(Integer(12))
>>> s.jacobi_continued_fraction()
((-1, -1), (-3, -4), (-5, -9), (-7, -16), (-9, -25))
```

Another example:

```
sage: (log(1+t)/t).jacobi_continued_fraction()
((1/2, -1/12),
 (1/2, -1/15),
 (1/2, -9/140),
 (1/2, -4/63),
 (1/2, -25/396),
 (1/2, -9/143),
 (1/2, -49/780),
 (1/2, -16/255),
 (1/2, -81/1292))
```

```
>>> from sage.all import *
>>> (log(Integer(1)+t)/t).jacobi_continued_fraction()
((1/2, -1/12),
 (1/2, -1/15),
 (1/2, -9/140),
 (1/2, -4/63),
 (1/2, -25/396),
 (1/2, -9/143),
 (1/2, -49/780),
 (1/2, -16/255),
 (1/2, -81/1292))
```

laurent_series()

Return the Laurent series associated to this power series, i.e., this series considered as a Laurent series.

EXAMPLES:

```
sage: k.<w> = QQ[[]]
sage: f = 1 + 17*w + 15*w^3 + O(w^5)
sage: parent(f)
Power Series Ring in w over Rational Field
sage: g = f.laurent_series(); g
1 + 17*w + 15*w^3 + O(w^5)
```

```
>>> from sage.all import *
>>> k = QQ[['w']]; (w,) = k._first_ngens(1)
>>> f = Integer(1) + Integer(17)*w + Integer(15)*w**Integer(3) + O(w**Integer(5))
>>> parent(f)
Power Series Ring in w over Rational Field
>>> g = f.laurent_series(); g
1 + 17*w + 15*w^3 + O(w^5)
```

lift_to_precision(absprec=None)

Return a congruent power series with absolute precision at least absprec.

INPUT:

- **absprec** – integer or None (default: None); the absolute precision of the result. If None, lifts to an exact element.

EXAMPLES:

```
sage: A.<t> = PowerSeriesRing(GF(5))
sage: x = t + t^2 + O(t^5)
sage: x.lift_to_precision(10)
t + t^2 + O(t^10)
sage: x.lift_to_precision()
t + t^2
```

```
>>> from sage.all import *
>>> A = PowerSeriesRing(GF(Integer(5)), names=('t',)); (t,) = A._first_
    ↪ngens(1)
>>> x = t + t**Integer(2) + O(t**Integer(5))
>>> x.lift_to_precision(Integer(10))
t + t^2 + O(t^10)
>>> x.lift_to_precision()
t + t^2
```

list()

See this method in derived classes:

- `sage.rings.power_series_poly.PowerSeries_poly.list()`,
- `sage.rings.multi_power_series_ring_element.MPowerSeries.list()`

Implementations *MUST* override this in the derived class.

EXAMPLES:

```
sage: from sage.rings.power_series_ring_element import PowerSeries
sage: R.<x> = PowerSeriesRing(ZZ)
sage: PowerSeries.list(1 + x^2)
Traceback (most recent call last):
...
NotImplementedError
```

```
>>> from sage.all import *
>>> from sage.rings.power_series_ring_element import PowerSeries
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> PowerSeries.list(Integer(1) + x**Integer(2))
Traceback (most recent call last):
...
NotImplementedError
```

log(*prec=None*)

Return log of this power series to the indicated precision.

This works only if the constant term of the power series is 1 or the base ring can take the logarithm of the constant coefficient.

INPUT:

- *prec* – integer (default: `self.parent().default_prec()`)

ALGORITHM: See `solve_linear_de()`.

Warning

Screwy things can happen if the coefficient ring is not a field of characteristic zero. See `solve_linear_de()`.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=10)
sage: (1 + t + O(t^10)).log()
t - 1/2*t^2 + 1/3*t^3 - 1/4*t^4 + 1/5*t^5 - 1/6*t^6 + 1/7*t^7
- 1/8*t^8 + 1/9*t^9 + O(t^10)

sage: t.exp().log()
t + O(t^10)

sage: (1 + t).log().exp()
1 + t + O(t^10)

sage: (-1 + t + O(t^10)).log()
Traceback (most recent call last):
...
ArithmeticError: constant term of power series is not 1

sage: # needs sage.rings.real_mpfr
sage: R.<t> = PowerSeriesRing(RR)
sage: (2 + t).log().exp()
2.000000000000000 + 1.000000000000000*t + O(t^20)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(10), names=('t',)); (t,) = R.
↳_first_ngens(1)
>>> (Integer(1) + t + O(t**Integer(10))).log()
t - 1/2*t^2 + 1/3*t^3 - 1/4*t^4 + 1/5*t^5 - 1/6*t^6 + 1/7*t^7
- 1/8*t^8 + 1/9*t^9 + O(t^10)

>>> t.exp().log()
t + O(t^10)

>>> (Integer(1) + t).log().exp()
1 + t + O(t^10)

>>> (-Integer(1) + t + O(t**Integer(10))).log()
Traceback (most recent call last):
...
ArithmeticError: constant term of power series is not 1

>>> # needs sage.rings.real_mpfr
>>> R = PowerSeriesRing(RR, names=('t',)); (t,) = R._first_ngens(1)
>>> (Integer(2) + t).log().exp()
2.000000000000000 + 1.000000000000000*t + O(t^20)
```

`map_coefficients(f, new_base_ring=None)`

Return the series obtained by applying `f` to the nonzero coefficients of `self`.

If `f` is a `sage.categories.map.Map`, then the resulting series will be defined over the codomain of `f`. Otherwise, the resulting polynomial will be over the same ring as `self`. Set `new_base_ring` to override this behaviour.

INPUT:

- `f` – a callable that will be applied to the coefficients of `self`
- `new_base_ring` – (optional) if given, the resulting polynomial will be defined over this ring

EXAMPLES:

```
sage: R.<x> = SR[[]] #_
↪needs sage.symbolic
sage: f = (1+I)*x^2 + 3*x - I #_
↪needs sage.symbolic
sage: f.map_coefficients(lambda z: z.conjugate()) #_
↪needs sage.symbolic
I + 3*x + (-I + 1)*x^2
sage: R.<x> = ZZ[[]]
sage: f = x^2 + 2
sage: f.map_coefficients(lambda a: a + 42)
44 + 43*x^2
```

```
>>> from sage.all import *
>>> R = SR[['x']]; (x,) = R._first_ngens(1) # needs sage.symbolic
>>> f = (Integer(1)+I)*x**Integer(2) + Integer(3)*x - I #_
↪ # needs sage.symbolic
>>> f.map_coefficients(lambda z: z.conjugate()) #_
↪needs sage.symbolic
I + 3*x + (-I + 1)*x^2
>>> R = ZZ[['x']]; (x,) = R._first_ngens(1)
>>> f = x**Integer(2) + Integer(2)
>>> f.map_coefficients(lambda a: a + Integer(42))
44 + 43*x^2
```

Examples with different base ring:

```
sage: R.<x> = ZZ[[]]
sage: k = GF(2)
sage: residue = lambda x: k(x)
sage: f = 4*x^2+x+3
sage: g = f.map_coefficients(residue); g
1 + x
sage: g.parent()
Power Series Ring in x over Integer Ring
sage: g = f.map_coefficients(residue, new_base_ring=k); g
1 + x
sage: g.parent()
Power Series Ring in x over Finite Field of size 2
sage: residue = k.coerce_map_from(ZZ)
sage: g = f.map_coefficients(residue); g
1 + x
```

(continues on next page)

(continued from previous page)

```
sage: g.parent()
Power Series Ring in x over Finite Field of size 2
```

```
>>> from sage.all import *
>>> R = ZZ[['x']]; (x,) = R._first_ngens(1)
>>> k = GF(Integer(2))
>>> residue = lambda x: k(x)
>>> f = Integer(4)*x**Integer(2)+x+Integer(3)
>>> g = f.map_coefficients(residue); g
1 + x
>>> g.parent()
Power Series Ring in x over Integer Ring
>>> g = f.map_coefficients(residue, new_base_ring=k); g
1 + x
>>> g.parent()
Power Series Ring in x over Finite Field of size 2
>>> residue = k.coerce_map_from(ZZ)
>>> g = f.map_coefficients(residue); g
1 + x
>>> g.parent()
Power Series Ring in x over Finite Field of size 2
```

Tests other implementations:

```
sage: # needs sage.libs.pari
sage: R.<q> = PowerSeriesRing(GF(11), implementation='pari')
sage: f = q - q^3 + O(q^10)
sage: f.map_coefficients(lambda c: c - 2)
10*q + 8*q^3 + O(q^10)
```

```
>>> from sage.all import *
>>> # needs sage.libs.pari
>>> R = PowerSeriesRing(GF(Integer(11)), implementation='pari', names=('q',));
↪ (q,) = R._first_ngens(1)
>>> f = q - q**Integer(3) + O(q**Integer(10))
>>> f.map_coefficients(lambda c: c - Integer(2))
10*q + 8*q^3 + O(q^10)
```

nth_root (*n*, *prec*=None)

Return the *n*-th root of this power series.

INPUT:

- *n* – integer
- *prec* – integer (optional); precision of the result. Though, if this series has finite precision, then the result cannot have larger precision.

EXAMPLES:

```
sage: R.<x> = QQ[[[]]]
sage: (1+x).nth_root(5)
1 + 1/5*x - 2/25*x^2 + ... + 12039376311816/2384185791015625*x^19 + O(x^20)
```

(continues on next page)

(continued from previous page)

```
sage: (1 + x + O(x^5)).nth_root(5)
1 + 1/5*x - 2/25*x^2 + 6/125*x^3 - 21/625*x^4 + O(x^5)
```

```
>>> from sage.all import *
>>> R = QQ[['x']]; (x,) = R._first_ngens(1)
>>> (Integer(1)+x).nth_root(Integer(5))
1 + 1/5*x - 2/25*x^2 + ... + 12039376311816/2384185791015625*x^19 + O(x^20)

>>> (Integer(1) + x + O(x**Integer(5))).nth_root(Integer(5))
1 + 1/5*x - 2/25*x^2 + 6/125*x^3 - 21/625*x^4 + O(x^5)
```

Check that the results are consistent with taking log and exponential:

```
sage: R.<x> = PowerSeriesRing(QQ, default_prec=100)
sage: p = (1 + 2*x - x^4)**200
sage: p1 = p.nth_root(1000, prec=100)
sage: p2 = (p.log()/1000).exp()
sage: p1.prec() == p2.prec() == 100
True
sage: p1.polynomial() == p2.polynomial()
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(100), names=('x',)); (x,) = R._first_ngens(1)
>>> p = (Integer(1) + Integer(2)*x - x**Integer(4))**Integer(200)
>>> p1 = p.nth_root(Integer(1000), prec=Integer(100))
>>> p2 = (p.log()/Integer(1000)).exp()
>>> p1.prec() == p2.prec() == Integer(100)
True
>>> p1.polynomial() == p2.polynomial()
True
```

Positive characteristic:

```
sage: R.<u> = GF(3)[[]]
sage: p = 1 + 2 * u^2
sage: p.nth_root(4)
1 + 2*u^2 + u^6 + 2*u^8 + u^12 + 2*u^14 + O(u^20)
sage: p.nth_root(4)**4
1 + 2*u^2 + O(u^20)
```

```
>>> from sage.all import *
>>> R = GF(Integer(3))[['u']]; (u,) = R._first_ngens(1)
>>> p = Integer(1) + Integer(2) * u**Integer(2)
>>> p.nth_root(Integer(4))
1 + 2*u^2 + u^6 + 2*u^8 + u^12 + 2*u^14 + O(u^20)
>>> p.nth_root(Integer(4))**Integer(4)
1 + 2*u^2 + O(u^20)
```

ogf_to_egf()

Return the exponential generating function power series, assuming `self` is an ordinary generating function

power series.

This is a formal Borel transform.

This can also be computed as `serconvol(f, exp(t))` in PARI/GP.

See also

`egf_to_ogf()` for the inverse method.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: f = t + t^2 + 2*t^3
sage: f.ogf_to_egf()
t + 1/2*t^2 + 1/3*t^3
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t + t**Integer(2) + Integer(2)*t**Integer(3)
>>> f.ogf_to_egf()
t + 1/2*t^2 + 1/3*t^3
```

`padded_list` ($n=None$)

Return a list of coefficients of `self` up to (but not including) q^n .

Includes 0s in the list on the right so that the list has length n .

INPUT:

- n – (optional) an integer that is at least 0. If n is not given, it will be taken to be the precision of `self`, unless this is `+Infinity`, in which case we just return `self.list()`.

EXAMPLES:

```
sage: R.<q> = PowerSeriesRing(QQ)
sage: f = 1 - 17*q + 13*q^2 + 10*q^4 + O(q^7)
sage: f.list()
[1, -17, 13, 0, 10]
sage: f.padded_list(7)
[1, -17, 13, 0, 10, 0, 0]
sage: f.padded_list(10)
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
sage: f.padded_list(3)
[1, -17, 13]
sage: f.padded_list()
[1, -17, 13, 0, 10, 0, 0]
sage: g = 1 - 17*q + 13*q^2 + 10*q^4
sage: g.list()
[1, -17, 13, 0, 10]
sage: g.padded_list()
[1, -17, 13, 0, 10]
sage: g.padded_list(10)
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('q',)); (q,) = R._first_ngens(1)
>>> f = Integer(1) - Integer(17)*q + Integer(13)*q**Integer(2) + \
↳ Integer(10)*q**Integer(4) + O(q**Integer(7))
>>> f.list()
[1, -17, 13, 0, 10]
>>> f.padded_list(Integer(7))
[1, -17, 13, 0, 10, 0, 0]
>>> f.padded_list(Integer(10))
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
>>> f.padded_list(Integer(3))
[1, -17, 13]
>>> f.padded_list()
[1, -17, 13, 0, 10, 0, 0]
>>> g = Integer(1) - Integer(17)*q + Integer(13)*q**Integer(2) + \
↳ Integer(10)*q**Integer(4)
>>> g.list()
[1, -17, 13, 0, 10]
>>> g.padded_list()
[1, -17, 13, 0, 10]
>>> g.padded_list(Integer(10))
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]

```

polynomial()

See this method in derived classes:

- `sage.rings.power_series_poly.PowerSeries_poly.polynomial()`,
- `sage.rings.multi_power_series_ring_element.MPowerSeries.polynomial()`

Implementations *MUST* override this in the derived class.

EXAMPLES:

```

sage: from sage.rings.power_series_ring_element import PowerSeries
sage: R.<x> = PowerSeriesRing(ZZ)
sage: PowerSeries.polynomial(1 + x^2)
Traceback (most recent call last):
...
NotImplementedError

```

```

>>> from sage.all import *
>>> from sage.rings.power_series_ring_element import PowerSeries
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> PowerSeries.polynomial(Integer(1) + x**Integer(2))
Traceback (most recent call last):
...
NotImplementedError

```

prec()

The precision of $\dots + O(x^r)$ is by definition r .

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: (t^2 + O(t^3)).prec()
3
sage: (1 - t^2 + O(t^100)).prec()
100
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (t**Integer(2) + O(t**Integer(3))).prec()
3
>>> (Integer(1) - t**Integer(2) + O(t**Integer(100))).prec()
100
```

precision_absolute()

Return the absolute precision of this series.

By definition, the absolute precision of $\dots + O(x^r)$ is r .

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: (t^2 + O(t^3)).precision_absolute()
3
sage: (1 - t^2 + O(t^100)).precision_absolute()
100
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (t**Integer(2) + O(t**Integer(3))).precision_absolute()
3
>>> (Integer(1) - t**Integer(2) + O(t**Integer(100))).precision_absolute()
100
```

precision_relative()

Return the relative precision of this series, that is the difference between its absolute precision and its valuation.

By convention, the relative precision of 0 (or $O(x^r)$ for any r) is 0.

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: (t^2 + O(t^3)).precision_relative()
1
sage: (1 - t^2 + O(t^100)).precision_relative()
100
sage: O(t^4).precision_relative()
0
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (t**Integer(2) + O(t**Integer(3))).precision_relative()
1
>>> (Integer(1) - t**Integer(2) + O(t**Integer(100))).precision_relative()
100
```

(continues on next page)

(continued from previous page)

```
>>> O(t**Integer(4)).precision_relative()
0
```

shift (*n*)

Return this power series multiplied by the power t^n .

If n is negative, terms below t^{-n} are discarded.

This power series is left unchanged.

Note

Despite the fact that higher order terms are printed to the right in a power series, right shifting decreases the powers of t , while left shifting increases them. This is to be consistent with polynomials, integers, etc.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ['y'], 't', 5)
sage: f = ~(1+t); f
1 - t + t^2 - t^3 + t^4 + O(t^5)
sage: f.shift(3)
t^3 - t^4 + t^5 - t^6 + t^7 + O(t^8)
sage: f >> 2
1 - t + t^2 + O(t^3)
sage: f << 10
t^10 - t^11 + t^12 - t^13 + t^14 + O(t^15)
sage: t << 29
t^30
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ['y'], 't', Integer(5), names=('t',)); (t,) = R._
↳first_ngens(1)
>>> f = ~(Integer(1)+t); f
1 - t + t^2 - t^3 + t^4 + O(t^5)
>>> f.shift(Integer(3))
t^3 - t^4 + t^5 - t^6 + t^7 + O(t^8)
>>> f >> Integer(2)
1 - t + t^2 + O(t^3)
>>> f << Integer(10)
t^10 - t^11 + t^12 - t^13 + t^14 + O(t^15)
>>> t << Integer(29)
t^30
```

AUTHORS:

- Robert Bradshaw (2007-04-18)

sin (*prec*='infinity')

Apply sin to the formal power series.

INPUT:

- *prec* – integer or infinity; the degree to truncate the result to

OUTPUT: a new power series

EXAMPLES:

For one variable:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = (t + t**2).O(4)
sage: sin(f)
t + t^2 - 1/6*t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> f = (t + t**Integer(2)).O(Integer(4))
>>> sin(f)
t + t^2 - 1/6*t^3 + O(t^4)
```

For several variables:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: sin(f)
a + b + a*b + O(a, b)^3
sage: f.sin()
a + b + a*b + O(a, b)^3
sage: f.sin(prec=2)
a + b + O(a, b)^2
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> sin(f)
a + b + a*b + O(a, b)^3
>>> f.sin()
a + b + a*b + O(a, b)^3
>>> f.sin(prec=Integer(2))
a + b + O(a, b)^2
```

If the power series has a nonzero constant coefficient c , one raises an error:

```
sage: g = 2+f
sage: sin(g)
Traceback (most recent call last):
...
ValueError: can only apply sin to formal power series with zero constant term
```

```
>>> from sage.all import *
>>> g = Integer(2)+f
>>> sin(g)
Traceback (most recent call last):
...
ValueError: can only apply sin to formal power series with zero constant term
```

If no precision is specified, the default precision is used:

```

sage: T.default_prec()
12
sage: sin(a)
a - 1/6*a^3 + 1/120*a^5 - 1/5040*a^7 + 1/362880*a^9 - 1/39916800*a^11 + O(a,
↪b)^12
sage: a.sin(prec=5)
a - 1/6*a^3 + O(a, b)^5
sage: sin(a + T.O(5))
a - 1/6*a^3 + O(a, b)^5

```

```

>>> from sage.all import *
>>> T.default_prec()
12
>>> sin(a)
a - 1/6*a^3 + 1/120*a^5 - 1/5040*a^7 + 1/362880*a^9 - 1/39916800*a^11 + O(a,
↪b)^12
>>> a.sin(prec=Integer(5))
a - 1/6*a^3 + O(a, b)^5
>>> sin(a + T.O(Integer(5)))
a - 1/6*a^3 + O(a, b)^5

```

sinh (*prec*='infinity')

Apply sinh to the formal power series.

INPUT:

- *prec* – integer or infinity; the degree to truncate the result to

OUTPUT: a new power series

EXAMPLES:

For one variable:

```

sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = (t + t**2).O(4)
sage: sinh(f)
t + t^2 + 1/6*t^3 + O(t^4)

```

```

>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> f = (t + t**Integer(2)).O(Integer(4))
>>> sinh(f)
t + t^2 + 1/6*t^3 + O(t^4)

```

For several variables:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: sinh(f)
a + b + a*b + O(a, b)^3
sage: f.sinh()
a + b + a*b + O(a, b)^3
sage: f.sinh(prec=2)
a + b + O(a, b)^2

```

```

>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> sinh(f)
a + b + a*b + O(a, b)^3
>>> f.sinh()
a + b + a*b + O(a, b)^3
>>> f.sinh(prec=Integer(2))
a + b + O(a, b)^2

```

If the power series has a nonzero constant coefficient c , one raises an error:

```

sage: g = 2 + f
sage: sinh(g)
Traceback (most recent call last):
...
ValueError: can only apply sinh to formal power series with zero
constant term

```

```

>>> from sage.all import *
>>> g = Integer(2) + f
>>> sinh(g)
Traceback (most recent call last):
...
ValueError: can only apply sinh to formal power series with zero
constant term

```

If no precision is specified, the default precision is used:

```

sage: T.default_prec()
12
sage: sinh(a)
a + 1/6*a^3 + 1/120*a^5 + 1/5040*a^7 + 1/362880*a^9 +
1/39916800*a^11 + O(a, b)^12
sage: a.sinh(prec=5)
a + 1/6*a^3 + O(a, b)^5
sage: sinh(a + T.O(5))
a + 1/6*a^3 + O(a, b)^5

```

```

>>> from sage.all import *
>>> T.default_prec()
12
>>> sinh(a)
a + 1/6*a^3 + 1/120*a^5 + 1/5040*a^7 + 1/362880*a^9 +
1/39916800*a^11 + O(a, b)^12
>>> a.sinh(prec=Integer(5))
a + 1/6*a^3 + O(a, b)^5
>>> sinh(a + T.O(Integer(5)))
a + 1/6*a^3 + O(a, b)^5

```

solve_linear_de (*prec='infinity', b=None, f0=None*)

Obtain a power series solution to an inhomogeneous linear differential equation of the form:

$$f'(t) = a(t)f(t) + b(t).$$

INPUT:

- `self` – the power series $a(t)$
- `b` – the power series $b(t)$ (default: zero)
- `f0` – the constant term of f (“initial condition”) (default: 1)
- `prec` – desired precision of result (this will be reduced if either `a` or `b` have less precision available)

OUTPUT: the power series f , to indicated precision

ALGORITHM: A divide-and-conquer strategy; see the source code. Running time is approximately $M(n) \log n$, where $M(n)$ is the time required for a polynomial multiplication of length n over the coefficient ring. (If you’re working over something like $\mathbf{Q}$, running time analysis can be a little complicated because the coefficients tend to explode.)

Note

- If the coefficient ring is a field of characteristic zero, then the solution will exist and is unique.
- For other coefficient rings, things are more complicated. A solution may not exist, and if it does it may not be unique. Generally, by the time the n -th term has been computed, the algorithm will have attempted divisions by $n!$ in the coefficient ring. So if your coefficient ring has enough ‘precision’, and if your coefficient ring can perform divisions even when the answer is not unique, and if you know in advance that a solution exists, then this function will find a solution (otherwise it will probably crash).

AUTHORS:

- David Harvey (2006-09-11): factored functionality out from `exp()` function, cleaned up precision tests a bit

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ, default_prec=10)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(10), names=('t',)); (t,) = R.
↳_first_ngens(1)
```

```
sage: a = 2 - 3*t + 4*t^2 + O(t^10)
sage: b = 3 - 4*t^2 + O(t^7)
sage: f = a.solve_linear_de(prec=5, b=b, f0=3/5)
sage: f
3/5 + 21/5*t + 33/10*t^2 - 38/15*t^3 + 11/24*t^4 + O(t^5)
sage: f.derivative() - a*f - b
O(t^4)
```

```
>>> from sage.all import *
>>> a = Integer(2) - Integer(3)*t + Integer(4)*t**Integer(2) +
↳O(t**Integer(10))
```

(continues on next page)

(continued from previous page)

```
>>> b = Integer(3) - Integer(4)*t**Integer(2) + O(t**Integer(7))
>>> f = a.solve_linear_de(prec=Integer(5), b=b, f0=Integer(3)/Integer(5))
>>> f
3/5 + 21/5*t + 33/10*t^2 - 38/15*t^3 + 11/24*t^4 + O(t^5)
>>> f.derivative() - a*f - b
O(t^4)
```

```
sage: a = 2 - 3*t + 4*t^2
sage: b = b = 3 - 4*t^2
sage: f = a.solve_linear_de(b=b, f0=3/5)
Traceback (most recent call last):
...
ValueError: cannot solve differential equation to infinite precision
```

```
>>> from sage.all import *
>>> a = Integer(2) - Integer(3)*t + Integer(4)*t**Integer(2)
>>> b = b = Integer(3) - Integer(4)*t**Integer(2)
>>> f = a.solve_linear_de(b=b, f0=Integer(3)/Integer(5))
Traceback (most recent call last):
...
ValueError: cannot solve differential equation to infinite precision
```

```
sage: a.solve_linear_de(prec=5, b=b, f0=3/5)
3/5 + 21/5*t + 33/10*t^2 - 38/15*t^3 + 11/24*t^4 + O(t^5)
```

```
>>> from sage.all import *
>>> a.solve_linear_de(prec=Integer(5), b=b, f0=Integer(3)/Integer(5))
3/5 + 21/5*t + 33/10*t^2 - 38/15*t^3 + 11/24*t^4 + O(t^5)
```

sqrt (*prec=None, extend=False, all=False, name=None*)

Return a square root of *self*.

INPUT:

- *prec* – integer (default: *None*); if not *None* and the series has infinite precision, truncates series at precision *prec*
- *extend* – boolean (default: *False*); if *True*, return a square root in an extension ring, if necessary. Otherwise, raise a *ValueError* if the square root is not in the base power series ring. For example, if *extend* is *True*, the square root of a power series with odd degree leading coefficient is defined as an element of a formal extension ring.
- *name* – string; if *extend* is *True*, you must also specify the print name of the formal square root
- *all* – boolean (default: *False*); if *True*, return all square roots of *self*, instead of just one

ALGORITHM: Newton's method

$$x_{i+1} = \frac{1}{2}(x_i + \text{self}/x_i)$$

EXAMPLES:

```
sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: sqrt(t^2)
```

(continues on next page)

(continued from previous page)

```

t
sage: sqrt(1 + t)
1 + 1/2*t - 1/8*t^2 + 1/16*t^3 - 5/128*t^4 + O(t^5)
sage: sqrt(4 + t)
2 + 1/4*t - 1/64*t^2 + 1/512*t^3 - 5/16384*t^4 + O(t^5)
sage: u = sqrt(2 + t, prec=2, extend=True, name = 'alpha'); u
alpha
sage: u^2
2 + t
sage: u.parent()
Univariate Quotient Polynomial Ring in alpha
over Power Series Ring in t over Rational Field
with modulus x^2 - 2 - t
sage: K.<t> = PowerSeriesRing(QQ, 't', 50)
sage: sqrt(1 + 2*t + t^2)
1 + t
sage: sqrt(t^2 + 2*t^4 + t^6)
t + t^3
sage: sqrt(1 + t + t^2 + 7*t^3)^2
1 + t + t^2 + 7*t^3 + O(t^50)
sage: sqrt(K(0))
0
sage: sqrt(t^2)
t

```

```

>>> from sage.all import *
>>> K = PowerSeriesRing(QQ, 't', Integer(5), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> sqrt(t**Integer(2))
t
>>> sqrt(Integer(1) + t)
1 + 1/2*t - 1/8*t^2 + 1/16*t^3 - 5/128*t^4 + O(t^5)
>>> sqrt(Integer(4) + t)
2 + 1/4*t - 1/64*t^2 + 1/512*t^3 - 5/16384*t^4 + O(t^5)
>>> u = sqrt(Integer(2) + t, prec=Integer(2), extend=True, name = 'alpha'); u
alpha
>>> u**Integer(2)
2 + t
>>> u.parent()
Univariate Quotient Polynomial Ring in alpha
over Power Series Ring in t over Rational Field
with modulus x^2 - 2 - t
>>> K = PowerSeriesRing(QQ, 't', Integer(50), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> sqrt(Integer(1) + Integer(2)*t + t**Integer(2))
1 + t
>>> sqrt(t**Integer(2) + Integer(2)*t**Integer(4) + t**Integer(6))
t + t^3
>>> sqrt(Integer(1) + t + t**Integer(2) +
↳Integer(7)*t**Integer(3))**Integer(2)
1 + t + t^2 + 7*t^3 + O(t^50)
>>> sqrt(K(Integer(0)))

```

(continues on next page)

(continued from previous page)

```
0
>>> sqrt(t**Integer(2))
t
```

```
sage: # needs sage.rings.complex_double
sage: K.<t> = PowerSeriesRing(CDF, 5)
sage: v = sqrt(-1 + t + t^3, all=True); v
[1.0*I - 0.5*I*t - 0.125*I*t^2 - 0.5625*I*t^3 - 0.2890625*I*t^4 + O(t^5),
 -1.0*I + 0.5*I*t + 0.125*I*t^2 + 0.5625*I*t^3 + 0.2890625*I*t^4 + O(t^5)]
sage: [a^2 for a in v]
[-1.0 + 1.0*t + 0.0*t^2 + 1.0*t^3 + O(t^5), -1.0 + 1.0*t + 0.0*t^2 + 1.0*t^3_
↪ + O(t^5)]
```

```
>>> from sage.all import *
>>> # needs sage.rings.complex_double
>>> K = PowerSeriesRing(CDF, Integer(5), names=('t',)); (t,) = K._first_
↪ngens(1)
>>> v = sqrt(-Integer(1) + t + t**Integer(3), all=True); v
[1.0*I - 0.5*I*t - 0.125*I*t^2 - 0.5625*I*t^3 - 0.2890625*I*t^4 + O(t^5),
 -1.0*I + 0.5*I*t + 0.125*I*t^2 + 0.5625*I*t^3 + 0.2890625*I*t^4 + O(t^5)]
>>> [a**Integer(2) for a in v]
[-1.0 + 1.0*t + 0.0*t^2 + 1.0*t^3 + O(t^5), -1.0 + 1.0*t + 0.0*t^2 + 1.0*t^3_
↪ + O(t^5)]
```

A formal square root:

```
sage: K.<t> = PowerSeriesRing(QQ, 5)
sage: f = 2*t + t^3 + O(t^4)
sage: s = f.sqrt(extend=True, name='sqrtf'); s
sqrtf
sage: s^2
2*t + t^3 + O(t^4)
sage: parent(s)
Univariate Quotient Polynomial Ring in sqrtf
over Power Series Ring in t over Rational Field
with modulus x^2 - 2*t - t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> K = PowerSeriesRing(QQ, Integer(5), names=('t',)); (t,) = K._first_
↪ngens(1)
>>> f = Integer(2)*t + t**Integer(3) + O(t**Integer(4))
>>> s = f.sqrt(extend=True, name='sqrtf'); s
sqrtf
>>> s**Integer(2)
2*t + t^3 + O(t^4)
>>> parent(s)
Univariate Quotient Polynomial Ring in sqrtf
over Power Series Ring in t over Rational Field
with modulus x^2 - 2*t - t^3 + O(t^4)
```

AUTHORS:

- Robert Bradshaw

- William Stein

`square_root()`

Return the square root of `self` in this ring. If this cannot be done, then an error will be raised.

This function succeeds if and only if `self.is_square()`

EXAMPLES:

```
sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: (1 + t).square_root()
1 + 1/2*t - 1/8*t^2 + 1/16*t^3 - 5/128*t^4 + O(t^5)
sage: (2 + t).square_root()
Traceback (most recent call last):
...
ValueError: Square root does not live in this ring.
sage: (2 + t.change_ring(RR)).square_root()
↳needs sage.rings.real_mpfr
1.41421356237309 + 0.353553390593274*t - 0.0441941738241592*t^2
+ 0.0110485434560398*t^3 - 0.00345266983001244*t^4 + O(t^5)
sage: t.square_root()
Traceback (most recent call last):
...
ValueError: Square root not defined for power series of odd valuation.
sage: K.<t> = PowerSeriesRing(ZZ, 't', 5)
sage: f = (1+t)^20
sage: f.square_root()
1 + 10*t + 45*t^2 + 120*t^3 + 210*t^4 + O(t^5)
sage: f = 1 + t
sage: f.square_root()
Traceback (most recent call last):
...
ValueError: Square root does not live in this ring.
```

```
>>> from sage.all import *
>>> K = PowerSeriesRing(QQ, 't', Integer(5), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> (Integer(1) + t).square_root()
1 + 1/2*t - 1/8*t^2 + 1/16*t^3 - 5/128*t^4 + O(t^5)
>>> (Integer(2) + t).square_root()
Traceback (most recent call last):
...
ValueError: Square root does not live in this ring.
>>> (Integer(2) + t.change_ring(RR)).square_root()
↳ # needs sage.rings.real_mpfr
1.41421356237309 + 0.353553390593274*t - 0.0441941738241592*t^2
+ 0.0110485434560398*t^3 - 0.00345266983001244*t^4 + O(t^5)
>>> t.square_root()
Traceback (most recent call last):
...
ValueError: Square root not defined for power series of odd valuation.
>>> K = PowerSeriesRing(ZZ, 't', Integer(5), names=('t',)); (t,) = K._first_
↳ngens(1)
>>> f = (Integer(1)+t)**Integer(20)
```

(continues on next page)

(continued from previous page)

```
>>> f.square_root()
1 + 10*t + 45*t^2 + 120*t^3 + 210*t^4 + O(t^5)
>>> f = Integer(1) + t
>>> f.square_root()
Traceback (most recent call last):
...
ValueError: Square root does not live in this ring.
```

AUTHORS:

- Robert Bradshaw

stieltjes_continued_fraction()

Return the Stieltjes continued fraction of `self`.

The S-fraction or Stieltjes continued fraction of a power series is a continued fraction expansion with steps of size one. We use the following convention

$$1/(1 - A_1 t / (1 - A_2 t / (1 - A_3 t / (1 - \dots))))$$

OUTPUT: A_n for $n \geq 1$

The expansion is done as long as possible given the precision. Whenever the expansion is not well-defined, because it would require to divide by zero, an exception is raised.

EXAMPLES:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: s = sum(catalan_number(k) * t**k for k in range(12)).O(12)
sage: s.stieltjes_continued_fraction()
(1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1)
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> s = sum(catalan_number(k) * t**k for k in range(Integer(12))).
↳ O(Integer(12))
>>> s.stieltjes_continued_fraction()
(1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1)
```

Another example:

```
sage: (exp(t)).stieltjes_continued_fraction()
(1,
 -1/2,
 1/6,
 -1/6,
 1/10,
 -1/10,
 1/14,
 -1/14,
 1/18,
 -1/18,
 1/22,
 -1/22,
 1/26,
```

(continues on next page)

(continued from previous page)

```
-1/26,
1/30,
-1/30,
1/34,
-1/34,
1/38)
```

```
>>> from sage.all import *
>>> (exp(t)).stieltjes_continued_fraction()
(1,
 -1/2,
 1/6,
 -1/6,
 1/10,
 -1/10,
 1/14,
 -1/14,
 1/18,
 -1/18,
 1/22,
 -1/22,
 1/26,
 -1/26,
 1/30,
 -1/30,
 1/34,
 -1/34,
 1/38)
```

`super_delta_fraction(delta)`

Return the super delta continued fraction of `self`.

This is a continued fraction of the following shape:

$$U_1(x) - \frac{v_0 x^{k_0}}{U_2(x) - \frac{v_1 x^{k_0+k_1+\delta}}{U_3(x) - \frac{v_2 x^{k_0+k_1+k_2+\delta}}{\ddots}}}}$$

where each $U_j(x) = 1 + u_j(x)x$.

INPUT:

- `delta` – positive integer, usually 2

OUTPUT: list of $(v_j, k_j, U_{j+1}(x))_{j \geq 0}$

REFERENCES:

- [Han2016]

EXAMPLES:

```
sage: deg = 30
sage: PS = PowerSeriesRing(QQ, 'q', default_prec=deg+1)
```

(continues on next page)

(continued from previous page)

```

sage: q = PS.gen()
sage: F = prod([(1+q**k).add_bigoh(deg+1) for k in range(1,deg)])
sage: F.super_delta_fraction(2)
[(1, 0, -q + 1),
 (1, 1, q + 1),
 (-1, 2, -q^3 + q^2 - q + 1),
 (1, 1, q^2 + q + 1),
 (-1, 0, -q + 1),
 (-1, 1, q^2 + q + 1),
 (-1, 0, -q + 1),
 (1, 1, 3*q^2 + 2*q + 1),
 (-4, 0, -q + 1)]

```

```

>>> from sage.all import *
>>> deg = Integer(30)
>>> PS = PowerSeriesRing(QQ, 'q', default_prec=deg+Integer(1))
>>> q = PS.gen()
>>> F = prod([(Integer(1)+q**k).add_bigoh(deg+Integer(1)) for k in
↳range(Integer(1),deg)])
>>> F.super_delta_fraction(Integer(2))
[(1, 0, -q + 1),
 (1, 1, q + 1),
 (-1, 2, -q^3 + q^2 - q + 1),
 (1, 1, q^2 + q + 1),
 (-1, 0, -q + 1),
 (-1, 1, q^2 + q + 1),
 (-1, 0, -q + 1),
 (1, 1, 3*q^2 + 2*q + 1),
 (-4, 0, -q + 1)]

```

A Jacobi continued fraction:

```

sage: t = PowerSeriesRing(QQ, 't').gen()
sage: s = sum(factorial(k) * t**k for k in range(12)).O(12)
sage: s.super_delta_fraction(2)
[(1, 0, -t + 1),
 (1, 0, -3*t + 1),
 (4, 0, -5*t + 1),
 (9, 0, -7*t + 1),
 (16, 0, -9*t + 1),
 (25, 0, -11*t + 1)]

```

```

>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> s = sum(factorial(k) * t**k for k in range(Integer(12))).O(Integer(12))
>>> s.super_delta_fraction(Integer(2))
[(1, 0, -t + 1),
 (1, 0, -3*t + 1),
 (4, 0, -5*t + 1),
 (9, 0, -7*t + 1),
 (16, 0, -9*t + 1),
 (25, 0, -11*t + 1)]

```


`tan(prec='infinity')`

Apply `tan` to the formal power series.

INPUT:

- `prec` – integer or `infinity`; the degree to truncate the result to

OUTPUT: a new power series

EXAMPLES:

For one variable:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = (t + t**2).O(4)
sage: tan(f)
t + t^2 + 1/3*t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> f = (t + t**Integer(2)).O(Integer(4))
>>> tan(f)
t + t^2 + 1/3*t^3 + O(t^4)
```

For several variables:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: tan(f)
a + b + a*b + O(a, b)^3
sage: f.tan()
a + b + a*b + O(a, b)^3
sage: f.tan(prec=2)
a + b + O(a, b)^2
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> tan(f)
a + b + a*b + O(a, b)^3
>>> f.tan()
a + b + a*b + O(a, b)^3
>>> f.tan(prec=Integer(2))
a + b + O(a, b)^2
```

If the power series has a nonzero constant coefficient c , one raises an error:

```
sage: g = 2 + f
sage: tan(g)
Traceback (most recent call last):
...
ValueError: can only apply tan to formal power series with zero constant term
```

```
>>> from sage.all import *
>>> g = Integer(2) + f
>>> tan(g)
Traceback (most recent call last):
...
ValueError: can only apply tan to formal power series with zero constant term
```

If no precision is specified, the default precision is used:

```
sage: T.default_prec()
12
sage: tan(a)
a + 1/3*a^3 + 2/15*a^5 + 17/315*a^7 + 62/2835*a^9 + 1382/155925*a^11 + O(a,
↪b)^12
sage: a.tan(prec=5)
a + 1/3*a^3 + O(a, b)^5
sage: tan(a + T.O(5))
a + 1/3*a^3 + O(a, b)^5
```

```
>>> from sage.all import *
>>> T.default_prec()
12
>>> tan(a)
a + 1/3*a^3 + 2/15*a^5 + 17/315*a^7 + 62/2835*a^9 + 1382/155925*a^11 + O(a,
↪b)^12
>>> a.tan(prec=Integer(5))
a + 1/3*a^3 + O(a, b)^5
>>> tan(a + T.O(Integer(5)))
a + 1/3*a^3 + O(a, b)^5
```

tanh (*prec*='infinity')

Apply tanh to the formal power series.

INPUT:

- *prec* – integer or infinity; the degree to truncate the result to

OUTPUT: a new power series

EXAMPLES:

For one variable:

```
sage: t = PowerSeriesRing(QQ, 't').gen()
sage: f = (t + t**2).O(4)
sage: tanh(f)
t + t^2 - 1/3*t^3 + O(t^4)
```

```
>>> from sage.all import *
>>> t = PowerSeriesRing(QQ, 't').gen()
>>> f = (t + t**Integer(2)).O(Integer(4))
>>> tanh(f)
t + t^2 - 1/3*t^3 + O(t^4)
```

For several variables:

```

sage: T.<a,b> = PowerSeriesRing(ZZ,2)
sage: f = a + b + a*b + T.O(3)
sage: tanh(f)
a + b + a*b + O(a, b)^3
sage: f.tanh()
a + b + a*b + O(a, b)^3
sage: f.tanh(prec=2)
a + b + O(a, b)^2

```

```

>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> tanh(f)
a + b + a*b + O(a, b)^3
>>> f.tanh()
a + b + a*b + O(a, b)^3
>>> f.tanh(prec=Integer(2))
a + b + O(a, b)^2

```

If the power series has a nonzero constant coefficient c , one raises an error:

```

sage: g = 2 + f
sage: tanh(g)
Traceback (most recent call last):
...
ValueError: can only apply tanh to formal power series with zero
constant term

```

```

>>> from sage.all import *
>>> g = Integer(2) + f
>>> tanh(g)
Traceback (most recent call last):
...
ValueError: can only apply tanh to formal power series with zero
constant term

```

If no precision is specified, the default precision is used:

```

sage: T.default_prec()
12
sage: tanh(a)
a - 1/3*a^3 + 2/15*a^5 - 17/315*a^7 + 62/2835*a^9 -
1382/155925*a^11 + O(a, b)^12
sage: a.tanh(prec=5)
a - 1/3*a^3 + O(a, b)^5
sage: tanh(a + T.O(5))
a - 1/3*a^3 + O(a, b)^5

```

```

>>> from sage.all import *
>>> T.default_prec()
12

```

(continues on next page)

(continued from previous page)

```
>>> tanh(a)
a - 1/3*a^3 + 2/15*a^5 - 17/315*a^7 + 62/2835*a^9 -
1382/155925*a^11 + O(a, b)^12
>>> a.tanh(prec=Integer(5))
a - 1/3*a^3 + O(a, b)^5
>>> tanh(a + T.O(Integer(5)))
a - 1/3*a^3 + O(a, b)^5
```

truncate (*prec='infinity'*)

The polynomial obtained from power series by truncation.

EXAMPLES:

```
sage: R.<I> = GF(2)[[]]
sage: f = 1/(1+I+O(I^8)); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
sage: f.truncate(5)
I^4 + I^3 + I^2 + I + 1
```

```
>>> from sage.all import *
>>> R = GF(Integer(2))[['I']]; (I,) = R._first_ngens(1)
>>> f = Integer(1)/(Integer(1)+I+O(I**Integer(8))); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
>>> f.truncate(Integer(5))
I^4 + I^3 + I^2 + I + 1
```

valuation ()

Return the valuation of this power series.

This is equal to the valuation of the underlying polynomial.

EXAMPLES:

Sparse examples:

```
sage: R.<t> = PowerSeriesRing(QQ, sparse=True)
sage: f = t^100000 + O(t^1000000)
sage: f.valuation()
100000
sage: R(0).valuation()
+Infinity
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, sparse=True, names=('t',)); (t,) = R._first_
↳ngens(1)
>>> f = t**Integer(100000) + O(t**Integer(1000000))
>>> f.valuation()
100000
>>> R(Integer(0)).valuation()
+Infinity
```

Dense examples:

```
sage: R.<t> = PowerSeriesRing(ZZ)
sage: f = 17*t^100 + O(t^110)
sage: f.valuation()
100
sage: t.valuation()
1
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = Integer(17)*t**Integer(100) + O(t**Integer(110))
>>> f.valuation()
100
>>> t.valuation()
1
```

valuation_zero_part()

Factor self as $q^n \cdot (a_0 + a_1q + \cdots)$ with a_0 nonzero. Then this function returns $a_0 + a_1q + \cdots$.

Note

This valuation zero part need not be a unit if, e.g., a_0 is not invertible in the base ring.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(QQ)
sage: ((1/3)*t^5*(17-2/3*t^3)).valuation_zero_part()
17/3 - 2/9*t^3
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> ((Integer(1)/Integer(3))*t**Integer(5)*(Integer(17)-Integer(2)/
↪ Integer(3)*t**Integer(3))).valuation_zero_part()
17/3 - 2/9*t^3
```

In this example the valuation 0 part is not a unit:

```
sage: R.<t> = PowerSeriesRing(ZZ, sparse=True)
sage: u = (-2*t^5*(17-t^3)).valuation_zero_part(); u
-34 + 2*t^3
sage: u.is_unit()
False
sage: u.valuation()
0
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, sparse=True, names=('t',)); (t,) = R._first_
↪ ngens(1)
>>> u = (-Integer(2)*t**Integer(5)*(Integer(17)-t**Integer(3))).valuation_
↪ zero_part(); u
-34 + 2*t^3
>>> u.is_unit()
```

(continues on next page)

(continued from previous page)

```
False
>>> u.valuation()
0
```

variable()

Return a string with the name of the variable of this power series.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(Rationals())
sage: f = x^2 + 3*x^4 + O(x^7)
sage: f.variable()
'x'
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(Rationals(), names=('x',)); (x,) = R._first_ngens(1)
>>> f = x**Integer(2) + Integer(3)*x**Integer(4) + O(x**Integer(7))
>>> f.variable()
'x'
```

AUTHORS:

- David Harvey (2006-08-08)

`sage.rings.power_series_ring_element.is_PowerSeries(x)`

Return True if x is an instance of a univariate or multivariate power series.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(ZZ)
sage: from sage.rings.power_series_ring_element import is_PowerSeries
sage: is_PowerSeries(1 + x^2)
doctest:warning...
DeprecationWarning: The function is_PowerSeries is deprecated; use 'isinstance(...
↳, PowerSeries)' instead.
See https://github.com/sagemath/sage/issues/38266 for details.
True
sage: is_PowerSeries(x - x)
True
sage: is_PowerSeries(0)
False
sage: var('x') #_
↳needs sage.symbolic
x
sage: is_PowerSeries(1 + x^2) #_
↳needs sage.symbolic
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> from sage.rings.power_series_ring_element import is_PowerSeries
>>> is_PowerSeries(Integer(1) + x**Integer(2))
doctest:warning...
```

(continues on next page)

(continued from previous page)

```

DeprecationWarning: The function is_PowerSeries is deprecated; use 'isinstance(...
↳, PowerSeries)' instead.
See https://github.com/sagemath/sage/issues/38266 for details.
True
>>> is_PowerSeries(x - x)
True
>>> is_PowerSeries(Integer(0))
False
>>> var('x')                                     #↳
↳needs sage.symbolic
x
>>> is_PowerSeries(Integer(1) + x**Integer(2))   ↳
↳                                     # needs sage.symbolic
False

```

sage.rings.power_series_ring_element.**make_element_from_parent_v0**(parent, *args)

sage.rings.power_series_ring_element.**make_powerseries_poly_v0**(parent, f, prec, is_gen)

POWER SERIES METHODS

The class `PowerSeries_poly` provides additional methods for univariate power series.

class `sage.rings.power_series_poly.BaseRingFloorDivAction`

Bases: `Action`

The floor division action of the base ring on a formal power series.

class `sage.rings.power_series_poly.PowerSeries_poly`

Bases: `PowerSeries`

EXAMPLES:

```
sage: R.<q> = PowerSeriesRing(CC); R                                     #_
↳needs sage.rings.real_mpfr
Power Series Ring in q over Complex Field with 53 bits of precision
sage: loads(q.dumps()) == q                                           #_
↳needs sage.rings.real_mpfr
True

sage: R.<t> = QQ[[[]]
sage: f = 3 - t^3 + O(t^5)
sage: a = f^3; a
27 - 27*t^3 + O(t^5)
sage: b = f^-3; b
1/27 + 1/27*t^3 + O(t^5)
sage: a*b
1 + O(t^5)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(CC, names=('q',)); (q,) = R._first_ngens(1); R                                     _
↳                                     # needs sage.rings.real_mpfr
Power Series Ring in q over Complex Field with 53 bits of precision
>>> loads(q.dumps()) == q                                           # needs_
↳sage.rings.real_mpfr
True

>>> R = QQ[['t]]; (t,) = R._first_ngens(1)
>>> f = Integer(3) - t**Integer(3) + O(t**Integer(5))
>>> a = f**Integer(3); a
27 - 27*t^3 + O(t^5)
>>> b = f**-Integer(3); b
1/27 + 1/27*t^3 + O(t^5)
```

(continues on next page)

(continued from previous page)

```
>>> a*b
1 + O(t^5)
```

Check that [Issue #22216](#) is fixed:

```
sage: R.<T> = PowerSeriesRing(QQ)
sage: R(pari('1 + O(T)')) #_
↪needs sage.libs.pari
1 + O(T)
sage: R(pari('1/T + O(T)')) #_
↪needs sage.libs.pari
Traceback (most recent call last):
...
ValueError: series has negative valuation
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('T',)); (T,) = R._first_ngens(1)
>>> R(pari('1 + O(T)')) # needs_
↪sage.libs.pari
1 + O(T)
>>> R(pari('1/T + O(T)')) # needs_
↪sage.libs.pari
Traceback (most recent call last):
...
ValueError: series has negative valuation
```

degree()

Return the degree of the underlying polynomial of `self`.

That is, if `self` is of the form $f(x) + O(x^n)$, we return the degree of $f(x)$. Note that if $f(x)$ is 0, we return -1 , just as with polynomials.

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: (5 + t^3 + O(t^4)).degree()
3
sage: (5 + O(t^4)).degree()
0
sage: O(t^4).degree()
-1
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (Integer(5) + t**Integer(3) + O(t**Integer(4))).degree()
3
>>> (Integer(5) + O(t**Integer(4))).degree()
0
>>> O(t**Integer(4)).degree()
-1
```

dict (*copy=True*)

alias of `monomial_coefficients()`.

integral (*var=None*)

Return the integral of this power series.

By default, the integration variable is the variable of the power series.

Otherwise, the integration variable is the optional parameter *var*.

Note

The integral is always chosen so the constant term is 0.

EXAMPLES:

```
sage: k.<w> = QQ[[[]]]
sage: (1+17*w+15*w^3+O(w^5)).integral()
w + 17/2*w^2 + 15/4*w^4 + O(w^6)
sage: (w^3 + 4*w^4 + O(w^7)).integral()
1/4*w^4 + 4/5*w^5 + O(w^8)
sage: (3*w^2).integral()
w^3
```

```
>>> from sage.all import *
>>> k = QQ[['w']]; (w,) = k._first_ngens(1)
>>> (Integer(1)+Integer(17)*w+Integer(15)*w**Integer(3)+O(w**Integer(5))).
↳integral()
w + 17/2*w^2 + 15/4*w^4 + O(w^6)
>>> (w**Integer(3) + Integer(4)*w**Integer(4) + O(w**Integer(7))).integral()
1/4*w^4 + 4/5*w^5 + O(w^8)
>>> (Integer(3)*w**Integer(2)).integral()
w^3
```

list ()

Return the list of known coefficients for *self*.

This is just the list of coefficients of the underlying polynomial, so in particular, need not have length equal to *self*.prec().

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]]
sage: f = 1 - 5*t^3 + t^5 + O(t^7)
sage: f.list()
[1, 0, 0, -5, 0, 1]
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> f = Integer(1) - Integer(5)*t**Integer(3) + t**Integer(5) +
↳O(t**Integer(7))
>>> f.list()
[1, 0, 0, -5, 0, 1]
```

monomial_coefficients (*copy=True*)

Return a dictionary of coefficients for *self*.

This is simply a dict for the underlying polynomial, so need not have keys corresponding to every number smaller than `self.prec()`.

EXAMPLES:

```
sage: R.<t> = ZZ[[[]]
sage: f = 1 + t^10 + O(t^12)
sage: f.monomial_coefficients()
{0: 1, 10: 1}
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> f = Integer(1) + t**Integer(10) + O(t**Integer(12))
>>> f.monomial_coefficients()
{0: 1, 10: 1}
```

`dict` is an alias:

```
sage: f.dict()
{0: 1, 10: 1}
```

```
>>> from sage.all import *
>>> f.dict()
{0: 1, 10: 1}
```

padé(*m*, *n*)

Return the Padé approximant of `self` of index (m, n) .

The Padé approximant of index (m, n) of a formal power series f is the quotient Q/P of two polynomials Q and P such that $\deg(Q) \leq m$, $\deg(P) \leq n$ and

$$f(z) - Q(z)/P(z) = O(z^{m+n+1}).$$

The formal power series f must be known up to order $n + m$.

See [Wikipedia article Padé approximant](#)

INPUT:

- m, n – integers, describing the degrees of the polynomials

OUTPUT: a ratio of two polynomials

ALGORITHM:

This method uses the formula as a quotient of two determinants.

See also

- `sage.matrix.berlekamp_massey`,
- `sage.rings.polynomial.polynomial_zmod_flint.Polynomial_zmod_flint.rational_reconstruction()`

EXAMPLES:

```

sage: z = PowerSeriesRing(QQ, 'z').gen()
sage: exp(z).pade(4, 0)
1/24*z^4 + 1/6*z^3 + 1/2*z^2 + z + 1
sage: exp(z).pade(1, 1)
(-z - 2)/(z - 2)
sage: exp(z).pade(3, 3)
(-z^3 - 12*z^2 - 60*z - 120)/(z^3 - 12*z^2 + 60*z - 120)
sage: log(1-z).pade(4, 4)
(25/6*z^4 - 130/3*z^3 + 105*z^2 - 70*z)/(z^4 - 20*z^3 + 90*z^2
- 140*z + 70)
sage: sqrt(1+z).pade(3, 2)
(1/6*z^3 + 3*z^2 + 8*z + 16/3)/(z^2 + 16/3*z + 16/3)
sage: exp(2*z).pade(3, 3)
(-z^3 - 6*z^2 - 15*z - 15)/(z^3 - 6*z^2 + 15*z - 15)

```

```

>>> from sage.all import *
>>> z = PowerSeriesRing(QQ, 'z').gen()
>>> exp(z).pade(Integer(4), Integer(0))
1/24*z^4 + 1/6*z^3 + 1/2*z^2 + z + 1
>>> exp(z).pade(Integer(1), Integer(1))
(-z - 2)/(z - 2)
>>> exp(z).pade(Integer(3), Integer(3))
(-z^3 - 12*z^2 - 60*z - 120)/(z^3 - 12*z^2 + 60*z - 120)
>>> log(Integer(1)-z).pade(Integer(4), Integer(4))
(25/6*z^4 - 130/3*z^3 + 105*z^2 - 70*z)/(z^4 - 20*z^3 + 90*z^2
- 140*z + 70)
>>> sqrt(Integer(1)+z).pade(Integer(3), Integer(2))
(1/6*z^3 + 3*z^2 + 8*z + 16/3)/(z^2 + 16/3*z + 16/3)
>>> exp(Integer(2)*z).pade(Integer(3), Integer(3))
(-z^3 - 6*z^2 - 15*z - 15)/(z^3 - 6*z^2 + 15*z - 15)

```

polynomial()

Return the underlying polynomial of `self`.

EXAMPLES:

```

sage: R.<t> = GF(7)[[]]
sage: f = 3 - t^3 + O(t^5)
sage: f.polynomial()
6*t^3 + 3

```

```

>>> from sage.all import *
>>> R = GF(Integer(7))['t']; (t,) = R._first_ngens(1)
>>> f = Integer(3) - t**Integer(3) + O(t**Integer(5))
>>> f.polynomial()
6*t^3 + 3

```

reverse(precision=None)

Return the reverse of f , i.e., the series g such that $g(f(x)) = x$.

Given an optional argument `precision`, return the reverse with given precision (note that the reverse can have precision at most `f.prec()`). If f has infinite precision, and the argument `precision` is not given, then the precision of the reverse defaults to the default precision of `f.parent()`.

Note that this is only possible if the valuation of `self` is exactly 1.

ALGORITHM:

We first attempt to pass the computation to `pari`; if this fails, we use Lagrange inversion. Using `sage: set_verbose(1)` will print a message if passing to `pari` fails.

If the base ring has positive characteristic, then we attempt to lift to a characteristic zero ring and perform the reverse there. If this fails, an error is raised.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(QQ)
sage: f = 2*x + 3*x^2 - x^4 + O(x^5)
sage: g = f.reverse()
sage: g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
sage: f(g)
x + O(x^5)
sage: g(f)
x + O(x^5)

sage: A.<t> = PowerSeriesRing(ZZ)
sage: a = t - t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

sage: B.<b,c> = PolynomialRing(ZZ)
sage: A.<t> = PowerSeriesRing(B)
sage: f = t + b*t^2 + c*t^3 + O(t^4)
sage: g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
sage: g(f)
t + O(t^4)

sage: A.<t> = PowerSeriesRing(ZZ)
sage: B.<s> = A[[]]
sage: f = (1 - 3*t + 4*t^3 + O(t^4))*s + (2 + t + t^2 + O(t^3))*s^2 + O(s^3)
sage: from sage.misc.verbose import set_verbose
sage: set_verbose(1)
sage: g = f.reverse(); g
verbose 1 (<module>) passing to pari failed; trying Lagrange inversion
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*s + (-2 - 19*t - 118*t^2 + O(t^3))*s^2 +
↪ O(s^3)
sage: set_verbose(0)
sage: f(g) == g(f) == s
True
```

```
>>> from sage.all import *
```

(continues on next page)

(continued from previous page)

```

>>> R = PowerSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> f = Integer(2)*x + Integer(3)*x**Integer(2) - x**Integer(4) +
↳O(x**Integer(5))
>>> g = f.reverse()
>>> g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
>>> f(g)
x + O(x^5)
>>> g(f)
x + O(x^5)

>>> A = PowerSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> a = t - t**Integer(2) - Integer(2)*t**Integer(4) + t**Integer(5) +
↳O(t**Integer(6))
>>> b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
>>> a(b)
t + O(t^6)
>>> b(a)
t + O(t^6)

>>> B = PolynomialRing(ZZ, names=('b', 'c',)); (b, c,) = B._first_ngens(2)
>>> A = PowerSeriesRing(B, names=('t',)); (t,) = A._first_ngens(1)
>>> f = t + b*t**Integer(2) + c*t**Integer(3) + O(t**Integer(4))
>>> g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
>>> f(g)
t + O(t^4)
>>> g(f)
t + O(t^4)

>>> A = PowerSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> B = A[['s']]; (s,) = B._first_ngens(1)
>>> f = (Integer(1) - Integer(3)*t + Integer(4)*t**Integer(3) +
↳O(t**Integer(4)))*s + (Integer(2) + t + t**Integer(2) +
↳O(t**Integer(3)))*s**Integer(2) + O(s**Integer(3))
>>> from sage.misc.verbose import set_verbose
>>> set_verbose(Integer(1))
>>> g = f.reverse(); g
verbose 1 (<module>) passing to pari failed; trying Lagrange inversion
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*s + (-2 - 19*t - 118*t^2 + O(t^3))*s^2 +
↳O(s^3)
>>> set_verbose(Integer(0))
>>> f(g) == g(f) == s
True

```

If the leading coefficient is not a unit, we pass to its fraction field if possible:

```

sage: A.<t> = PowerSeriesRing(ZZ)
sage: a = 2*t - 4*t^2 + t^4 - t^5 + O(t^6)
sage: a.reverse()
1/2*t + 1/2*t^2 + t^3 + 79/32*t^4 + 437/64*t^5 + O(t^6)

```

(continues on next page)

(continued from previous page)

```

sage: B.<b> = PolynomialRing(ZZ)
sage: A.<t> = PowerSeriesRing(B)
sage: f = 2*b*t + b*t^2 + 3*b^2*t^3 + O(t^4)
sage: g = f.reverse(); g
1/(2*b)*t - 1/(8*b^2)*t^2 + ((-3*b + 1)/(16*b^3))*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
sage: g(f)
t + O(t^4)

```

```

>>> from sage.all import *
>>> A = PowerSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> a = Integer(2)*t - Integer(4)*t**Integer(2) + t**Integer(4) -
↳ t**Integer(5) + O(t**Integer(6))
>>> a.reverse()
1/2*t + 1/2*t^2 + t^3 + 79/32*t^4 + 437/64*t^5 + O(t^6)

>>> B = PolynomialRing(ZZ, names=('b',)); (b,) = B._first_ngens(1)
>>> A = PowerSeriesRing(B, names=('t',)); (t,) = A._first_ngens(1)
>>> f = Integer(2)*b*t + b*t**Integer(2) +
↳ Integer(3)*b**Integer(2)*t**Integer(3) + O(t**Integer(4))
>>> g = f.reverse(); g
1/(2*b)*t - 1/(8*b^2)*t^2 + ((-3*b + 1)/(16*b^3))*t^3 + O(t^4)
>>> f(g)
t + O(t^4)
>>> g(f)
t + O(t^4)

```

We can handle some base rings of positive characteristic:

```

sage: A8.<t> = PowerSeriesRing(Zmod(8))
sage: a = t - 15*t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + 7*t^2 + 2*t^3 + 5*t^4 + t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

```

```

>>> from sage.all import *
>>> A8 = PowerSeriesRing(Zmod(Integer(8)), names=('t',)); (t,) = A8._first_
↳ ngens(1)
>>> a = t - Integer(15)*t**Integer(2) - Integer(2)*t**Integer(4) +
↳ t**Integer(5) + O(t**Integer(6))
>>> b = a.reverse(); b
t + 7*t^2 + 2*t^3 + 5*t^4 + t^5 + O(t^6)
>>> a(b)
t + O(t^6)
>>> b(a)
t + O(t^6)

```


The optional argument `precision` sets the precision of the output:

```
sage: R.<x> = PowerSeriesRing(QQ)
sage: f = 2*x + 3*x^2 - 7*x^3 + x^4 + O(x^5)
sage: g = f.reverse(precision=3); g
1/2*x - 3/8*x^2 + O(x^3)
sage: f(g)
x + O(x^3)
sage: g(f)
x + O(x^3)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> f = Integer(2)*x + Integer(3)*x**Integer(2) - Integer(7)*x**Integer(3) +
↳ x**Integer(4) + O(x**Integer(5))
>>> g = f.reverse(precision=Integer(3)); g
1/2*x - 3/8*x^2 + O(x^3)
>>> f(g)
x + O(x^3)
>>> g(f)
x + O(x^3)
```

If the input series has infinite precision, the precision of the output is automatically set to the default precision of the parent ring:

```
sage: R.<x> = PowerSeriesRing(QQ, default_prec=20)
sage: (x - x^2).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8 + 1430*x^9
+ 4862*x^10 + 16796*x^11 + 58786*x^12 + 208012*x^13 + 742900*x^14
+ 2674440*x^15 + 9694845*x^16 + 35357670*x^17 + 129644790*x^18
+ 477638700*x^19 + O(x^20)
sage: (x - x^2).reverse(precision=3)
x + x^2 + O(x^3)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(20), names=('x',)); (x,) = R.
↳ _first_ngens(1)
>>> (x - x**Integer(2)).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8 + 1430*x^9
+ 4862*x^10 + 16796*x^11 + 58786*x^12 + 208012*x^13 + 742900*x^14
+ 2674440*x^15 + 9694845*x^16 + 35357670*x^17 + 129644790*x^18
+ 477638700*x^19 + O(x^20)
>>> (x - x**Integer(2)).reverse(precision=Integer(3))
x + x^2 + O(x^3)
```

truncate (*prec*='infinity')

The polynomial obtained from power series by truncation at precision `prec`.

EXAMPLES:

```
sage: R.<I> = GF(2)[[]]
sage: f = 1/(1+I+O(I^8)); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
```

(continues on next page)

(continued from previous page)

```
sage: f.truncate(5)
I^4 + I^3 + I^2 + I + 1
```

```
>>> from sage.all import *
>>> R = GF(Integer(2))[['I']]; (I,) = R._first_ngens(1)
>>> f = Integer(1)/(Integer(1)+I+O(I**Integer(8))); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
>>> f.truncate(Integer(5))
I^4 + I^3 + I^2 + I + 1
```

truncate_powerseries (*prec*)

Given input `prec = n`, returns the power series of degree $< n$ which is equivalent to `self` modulo x^n .

EXAMPLES:

```
sage: R.<I> = GF(2)[[]]
sage: f = 1/(1+I+O(I^8)); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
sage: f.truncate_powerseries(5)
1 + I + I^2 + I^3 + I^4 + O(I^5)
```

```
>>> from sage.all import *
>>> R = GF(Integer(2))[['I']]; (I,) = R._first_ngens(1)
>>> f = Integer(1)/(Integer(1)+I+O(I**Integer(8))); f
1 + I + I^2 + I^3 + I^4 + I^5 + I^6 + I^7 + O(I^8)
>>> f.truncate_powerseries(Integer(5))
1 + I + I^2 + I^3 + I^4 + O(I^5)
```

valuation ()

Return the valuation of `self`.

EXAMPLES:

```
sage: R.<t> = QQ[[]]
sage: (5 - t^8 + O(t^11)).valuation()
0
sage: (-t^8 + O(t^11)).valuation()
8
sage: O(t^7).valuation()
7
sage: R(0).valuation()
+Infinity
```

```
>>> from sage.all import *
>>> R = QQ[['t']]; (t,) = R._first_ngens(1)
>>> (Integer(5) - t**Integer(8) + O(t**Integer(11))).valuation()
0
>>> (-t**Integer(8) + O(t**Integer(11))).valuation()
8
>>> O(t**Integer(7)).valuation()
7
>>> R(Integer(0)).valuation()
+Infinity
```

`sage.rings.power_series_poly.make_powerseries_poly_v0` (*parent, f, prec, is_gen*)

Return the power series specified by *f*, *prec*, and *is_gen*.

This function exists for the purposes of pickling. Do not delete this function – if you change the internal representation, instead make a new function and make sure that both kinds of objects correctly unpickle as the new type.

EXAMPLES:

```
sage: R.<t> = QQ[[]]
sage: sage.rings.power_series_poly.make_powerseries_poly_v0(R, t, infinity, True)
t
```

```
>>> from sage.all import *
>>> R = QQ[['t']]; (t,) = R._first_ngens(1)
>>> sage.rings.power_series_poly.make_powerseries_poly_v0(R, t, infinity, True)
t
```


POWER SERIES IMPLEMENTED USING PARI

EXAMPLES:

This implementation can be selected for any base ring supported by PARI by passing the keyword `implementation='pari'` to the `PowerSeriesRing()` constructor:

```
sage: R.<q> = PowerSeriesRing(ZZ, implementation='pari'); R
Power Series Ring in q over Integer Ring
sage: S.<t> = PowerSeriesRing(CC, implementation='pari'); S
↳needs sage.rings.real_mpfr
Power Series Ring in t over Complex Field with 53 bits of precision
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, implementation='pari', names=('q',)); (q,) = R._first_
↳ngens(1); R
Power Series Ring in q over Integer Ring
>>> S = PowerSeriesRing(CC, implementation='pari', names=('t',)); (t,) = S._first_
↳ngens(1); S # needs sage.rings.real_mpfr
Power Series Ring in t over Complex Field with 53 bits of precision
```

Note that only the type of the elements depends on the implementation, not the type of the parents:

```
sage: type(R)
<class 'sage.rings.power_series_ring.PowerSeriesRing_domain_with_category'>
sage: type(q)
<class 'sage.rings.power_series_pari.PowerSeries_pari'>
sage: type(S)
↳needs sage.rings.real_mpfr
<class 'sage.rings.power_series_ring.PowerSeriesRing_over_field_with_category'>
sage: type(t)
↳needs sage.rings.real_mpfr
<class 'sage.rings.power_series_pari.PowerSeries_pari'>
```

```
>>> from sage.all import *
>>> type(R)
<class 'sage.rings.power_series_ring.PowerSeriesRing_domain_with_category'>
>>> type(q)
<class 'sage.rings.power_series_pari.PowerSeries_pari'>
>>> type(S)
↳needs sage.rings.real_mpfr
<class 'sage.rings.power_series_ring.PowerSeriesRing_over_field_with_category'>
>>> type(t)
```

(continues on next page)

(continued from previous page)

```
↪needs sage.rings.real_mpfr
<class 'sage.rings.power_series_pari.PowerSeries_pari'>
```

If k is a finite field implemented using PARI, this is the default implementation for power series over k :

```
sage: k.<c> = GF(5^12)
sage: type(c)
<class 'sage.rings.finite_rings.element_pari_ffelt.FiniteFieldElement_pari_ffelt'>
sage: A.<x> = k[[[]]]
sage: type(x)
<class 'sage.rings.power_series_pari.PowerSeries_pari'>
```

```
>>> from sage.all import *
>>> k = GF(Integer(5)**Integer(12), names=('c',)); (c,) = k._first_ngens(1)
>>> type(c)
<class 'sage.rings.finite_rings.element_pari_ffelt.FiniteFieldElement_pari_ffelt'>
>>> A = k[['x']]; (x,) = A._first_ngens(1)
>>> type(x)
<class 'sage.rings.power_series_pari.PowerSeries_pari'>
```

Warning

Because this implementation uses the PARI interface, the PARI variable ordering must be respected in the sense that the variable name of the power series ring must have higher priority than any variable names occurring in the base ring:

```
sage: R.<y> = QQ[]
sage: S.<x> = PowerSeriesRing(R, implementation='pari'); S
Power Series Ring in x over Univariate Polynomial Ring in y over Rational Field
```

```
>>> from sage.all import *
>>> R = QQ['y']; (y,) = R._first_ngens(1)
>>> S = PowerSeriesRing(R, implementation='pari', names=('x',)); (x,) = S._first_
↪ngens(1); S
Power Series Ring in x over Univariate Polynomial Ring in y over Rational Field
```

Reversing the variable ordering leads to errors:

```
sage: R.<x> = QQ[]
sage: S.<y> = PowerSeriesRing(R, implementation='pari')
Traceback (most recent call last):
...
PariError: incorrect priority in gtopoly: variable x <= y
```

```
>>> from sage.all import *
>>> R = QQ['x']; (x,) = R._first_ngens(1)
>>> S = PowerSeriesRing(R, implementation='pari', names=('y',)); (y,) = S._first_
↪ngens(1)
Traceback (most recent call last):
...
PariError: incorrect priority in gtopoly: variable x <= y
```

AUTHORS:

- Peter Bruin (December 2013): initial version

class sage.rings.power_series_pari.**PowerSeries_pari**

Bases: *PowerSeries*

A power series implemented using PARI.

INPUT:

- `parent` – the power series ring to use as the parent
- `f` – object from which to construct a power series
- `prec` – (default: infinity) precision of the element to be constructed
- `check` – ignored, but accepted for compatibility with *PowerSeries_poly*

dict (*copy=None*)

alias of *monomial_coefficients()*.

integral (*var=None*)

Return the formal integral of *self*.

By default, the integration variable is the variable of the power series. Otherwise, the integration variable is the optional parameter *var*.

Note

The integral is always chosen so the constant term is 0.

EXAMPLES:

```
sage: k.<w> = PowerSeriesRing(QQ, implementation='pari')
sage: (1+17*w+15*w^3+O(w^5)).integral()
w + 17/2*w^2 + 15/4*w^4 + O(w^6)
sage: (w^3 + 4*w^4 + O(w^7)).integral()
1/4*w^4 + 4/5*w^5 + O(w^8)
sage: (3*w^2).integral()
w^3
```

```
>>> from sage.all import *
>>> k = PowerSeriesRing(QQ, implementation='pari', names=('w',)); (w,) = k._
↳ first_ngens(1)
>>> (Integer(1)+Integer(17)*w+Integer(15)*w**Integer(3)+O(w**Integer(5))).
↳ integral()
w + 17/2*w^2 + 15/4*w^4 + O(w^6)
>>> (w**Integer(3) + Integer(4)*w**Integer(4) + O(w**Integer(7))).integral()
1/4*w^4 + 4/5*w^5 + O(w^8)
>>> (Integer(3)*w**Integer(2)).integral()
w^3
```

list ()

Return the list of known coefficients for *self*.

This is just the list of coefficients of the underlying polynomial; it need not have length equal to *self.prec()*.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(ZZ, implementation='pari')
sage: f = 1 - 5*t^3 + t^5 + O(t^7)
sage: f.list()
[1, 0, 0, -5, 0, 1]

sage: # needs sage.rings.padic
sage: S.<u> = PowerSeriesRing(pAdicRing(5), implementation='pari')
sage: (2 + u).list()
[2 + O(5^20), 1 + O(5^20)]

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, implementation='pari', names=('t',)); (t,) = R._
↳ first_ngens(1)
>>> f = Integer(1) - Integer(5)*t**Integer(3) + t**Integer(5) +
↳ O(t**Integer(7))
>>> f.list()
[1, 0, 0, -5, 0, 1]

>>> # needs sage.rings.padic
>>> S = PowerSeriesRing(pAdicRing(Integer(5)), implementation='pari', names=(
↳ 'u',)); (u,) = S._first_ngens(1)
>>> (Integer(2) + u).list()
[2 + O(5^20), 1 + O(5^20)]

```

monomial_coefficients (*copy=None*)

Return a dictionary of coefficients for *self*.

This is simply a dict for the underlying polynomial; it need not have keys corresponding to every number smaller than *self*.prec().

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(ZZ, implementation='pari')
sage: f = 1 + t^10 + O(t^12)
sage: f.monomial_coefficients()
{0: 1, 10: 1}

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, implementation='pari', names=('t',)); (t,) = R._
↳ first_ngens(1)
>>> f = Integer(1) + t**Integer(10) + O(t**Integer(12))
>>> f.monomial_coefficients()
{0: 1, 10: 1}

```

dict is an alias:

```

sage: f.dict()
{0: 1, 10: 1}

```

```

>>> from sage.all import *
>>> f.dict()
{0: 1, 10: 1}

```


padded_list (*n=None*)

Return a list of coefficients of *self* up to (but not including) q^n .

The list is padded with zeroes on the right so that it has length *n*.

INPUT:

- *n* – nonnegative integer (optional); if *n* is not given, it will be taken to be the precision of *self*, unless this is +Infinity, in which case we just return *self*.list()

EXAMPLES:

```
sage: R.<q> = PowerSeriesRing(QQ, implementation='pari')
sage: f = 1 - 17*q + 13*q^2 + 10*q^4 + O(q^7)
sage: f.list()
[1, -17, 13, 0, 10]
sage: f.padded_list(7)
[1, -17, 13, 0, 10, 0, 0]
sage: f.padded_list(10)
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
sage: f.padded_list(3)
[1, -17, 13]
sage: f.padded_list()
[1, -17, 13, 0, 10, 0, 0]
sage: g = 1 - 17*q + 13*q^2 + 10*q^4
sage: g.list()
[1, -17, 13, 0, 10]
sage: g.padded_list()
[1, -17, 13, 0, 10]
sage: g.padded_list(10)
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, implementation='pari', names=('q',)); (q,) = R._
↳first_ngens(1)
>>> f = Integer(1) - Integer(17)*q + Integer(13)*q**Integer(2) +
↳Integer(10)*q**Integer(4) + O(q**Integer(7))
>>> f.list()
[1, -17, 13, 0, 10]
>>> f.padded_list(Integer(7))
[1, -17, 13, 0, 10, 0, 0]
>>> f.padded_list(Integer(10))
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
>>> f.padded_list(Integer(3))
[1, -17, 13]
>>> f.padded_list()
[1, -17, 13, 0, 10, 0, 0]
>>> g = Integer(1) - Integer(17)*q + Integer(13)*q**Integer(2) +
↳Integer(10)*q**Integer(4)
>>> g.list()
[1, -17, 13, 0, 10]
>>> g.padded_list()
[1, -17, 13, 0, 10]
>>> g.padded_list(Integer(10))
[1, -17, 13, 0, 10, 0, 0, 0, 0, 0]
```

polynomial()

Convert self to a polynomial.

EXAMPLES:

```
sage: R.<t> = PowerSeriesRing(GF(7), implementation='pari')
sage: f = 3 - t^3 + O(t^5)
sage: f.polynomial()
6*t^3 + 3
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(GF(Integer(7)), implementation='pari', names=('t',));
↳ (t,) = R._first_ngens(1)
>>> f = Integer(3) - t**Integer(3) + O(t**Integer(5))
>>> f.polynomial()
6*t^3 + 3
```

reverse (*precision=None*)

Return the reverse of self.

The reverse of a power series f is the power series g such that $g(f(x)) = x$. This exists if and only if the valuation of self is exactly 1 and the coefficient of x is a unit.

If the optional argument `precision` is given, the reverse is returned with this precision. If f has infinite precision and the argument `precision` is not given, then the reverse is returned with the default precision of `f.parent()`.

EXAMPLES:

```
sage: R.<x> = PowerSeriesRing(QQ, implementation='pari')
sage: f = 2*x + 3*x^2 - x^4 + O(x^5)
sage: g = f.reverse()
sage: g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
sage: f(g)
x + O(x^5)
sage: g(f)
x + O(x^5)

sage: A.<t> = PowerSeriesRing(ZZ, implementation='pari')
sage: a = t - t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

sage: B.<b,c> = PolynomialRing(ZZ)
sage: A.<t> = PowerSeriesRing(B, implementation='pari')
sage: f = t + b*t^2 + c*t^3 + O(t^4)
sage: g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
```

(continues on next page)

(continued from previous page)

```

sage: g(f)
t + O(t^4)

sage: A.<t> = PowerSeriesRing(ZZ, implementation='pari')
sage: B.<x> = PowerSeriesRing(A, implementation='pari')
sage: f = (1 - 3*t + 4*t^3 + O(t^4))*x + (2 + t + t^2 + O(t^3))*x^2 + O(x^3)
sage: g = f.reverse(); g
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*x + (-2 - 19*t - 118*t^2 + O(t^3))*x^2 +
↪ O(x^3)

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, implementation='pari', names=('x',)); (x,) = R._
↪ first_ngens(1)
>>> f = Integer(2)*x + Integer(3)*x**Integer(2) - x**Integer(4) +
↪ O(x**Integer(5))
>>> g = f.reverse()
>>> g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
>>> f(g)
x + O(x^5)
>>> g(f)
x + O(x^5)

>>> A = PowerSeriesRing(ZZ, implementation='pari', names=('t',)); (t,) = A._
↪ first_ngens(1)
>>> a = t - t**Integer(2) - Integer(2)*t**Integer(4) + t**Integer(5) +
↪ O(t**Integer(6))
>>> b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
>>> a(b)
t + O(t^6)
>>> b(a)
t + O(t^6)

>>> B = PolynomialRing(ZZ, names=('b', 'c',)); (b, c,) = B._first_ngens(2)
>>> A = PowerSeriesRing(B, implementation='pari', names=('t',)); (t,) = A._
↪ first_ngens(1)
>>> f = t + b*t**Integer(2) + c*t**Integer(3) + O(t**Integer(4))
>>> g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
>>> f(g)
t + O(t^4)
>>> g(f)
t + O(t^4)

>>> A = PowerSeriesRing(ZZ, implementation='pari', names=('t',)); (t,) = A._
↪ first_ngens(1)
>>> B = PowerSeriesRing(A, implementation='pari', names=('x',)); (x,) = B._
↪ first_ngens(1)
>>> f = (Integer(1) - Integer(3)*t + Integer(4)*t**Integer(3) +
↪ O(t**Integer(4)))*x + (Integer(2) + t + t**Integer(2) +
↪ O(t**Integer(3)))*x**Integer(2) + O(x**Integer(3))

```

(continues on next page)

(continued from previous page)

```
>>> g = f.reverse(); g
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*x + (-2 - 19*t - 118*t^2 + O(t^3))*x^2 +
↪ O(x^3)
```

The optional argument `precision` sets the precision of the output:

```
sage: R.<x> = PowerSeriesRing(QQ, implementation='pari')
sage: f = 2*x + 3*x^2 - 7*x^3 + x^4 + O(x^5)
sage: g = f.reverse(precision=3); g
1/2*x - 3/8*x^2 + O(x^3)
sage: f(g)
x + O(x^3)
sage: g(f)
x + O(x^3)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, implementation='pari', names=('x',)); (x,) = R._
↪ first_ngens(1)
>>> f = Integer(2)*x + Integer(3)*x**Integer(2) - Integer(7)*x**Integer(3) +
↪ x**Integer(4) + O(x**Integer(5))
>>> g = f.reverse(precision=Integer(3)); g
1/2*x - 3/8*x^2 + O(x^3)
>>> f(g)
x + O(x^3)
>>> g(f)
x + O(x^3)
```

If the input series has infinite precision, the precision of the output is automatically set to the default precision of the parent ring:

```
sage: R.<x> = PowerSeriesRing(QQ, default_prec=20, implementation='pari')
sage: (x - x^2).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8
+ 1430*x^9 + 4862*x^10 + 16796*x^11 + 58786*x^12 + 208012*x^13
+ 742900*x^14 + 2674440*x^15 + 9694845*x^16 + 35357670*x^17
+ 129644790*x^18 + 477638700*x^19 + O(x^20)
sage: (x - x^2).reverse(precision=3)
x + x^2 + O(x^3)
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, default_prec=Integer(20), implementation='pari',
↪ names=('x',)); (x,) = R._first_ngens(1)
>>> (x - x**Integer(2)).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8
+ 1430*x^9 + 4862*x^10 + 16796*x^11 + 58786*x^12 + 208012*x^13
+ 742900*x^14 + 2674440*x^15 + 9694845*x^16 + 35357670*x^17
+ 129644790*x^18 + 477638700*x^19 + O(x^20)
>>> (x - x**Integer(2)).reverse(precision=Integer(3))
x + x^2 + O(x^3)
```

valuation()

Return the valuation of `self`.

EXAMPLES:

```

sage: R.<t> = PowerSeriesRing(QQ, implementation='pari')
sage: (5 - t^8 + O(t^11)).valuation()
0
sage: (-t^8 + O(t^11)).valuation()
8
sage: O(t^7).valuation()
7
sage: R(0).valuation()
+Infinity

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, implementation='pari', names=('t',)); (t,) = R._
↳first_ngens(1)
>>> (Integer(5) - t**Integer(8) + O(t**Integer(11))).valuation()
0
>>> (-t**Integer(8) + O(t**Integer(11))).valuation()
8
>>> O(t**Integer(7)).valuation()
7
>>> R(Integer(0)).valuation()
+Infinity

```


MULTIVARIATE POWER SERIES RINGS

Construct a multivariate power series ring (in finitely many variables) over a given (commutative) base ring.

EXAMPLES:

Construct rings and elements:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: TestSuite(R).run()
sage: p = -t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + R.O(6); p
-t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + O(t, u, v)^6
sage: p in R
True

sage: g = 1 + v + 3*u*t^2 - 2*v^2*t^2; g
1 + v + 3*t^2*u - 2*t^2*v^2
sage: g in R
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t', 'u', 'v',)); (t, u, v,) = R._first_ngens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field
>>> TestSuite(R).run()
>>> p = -t + Integer(1)/Integer(2)*t**Integer(3)*u - Integer(1)/
↳Integer(4)*t**Integer(4)*u + Integer(2)/Integer(3)*v**Integer(5) + R.O(Integer(6));
↳p
-t + 1/2*t^3*u - 1/4*t^4*u + 2/3*v^5 + O(t, u, v)^6
>>> p in R
True

>>> g = Integer(1) + v + Integer(3)*u*t**Integer(2) -
↳Integer(2)*v**Integer(2)*t**Integer(2); g
1 + v + 3*t^2*u - 2*t^2*v^2
>>> g in R
True
```

Add big O as with single variable power series:

```
sage: g.add_bigoh(3)
1 + v + O(t, u, v)^3
sage: g = g.O(5); g
1 + v + 3*t^2*u - 2*t^2*v^2 + O(t, u, v)^5
```

```
>>> from sage.all import *
>>> g.add_bigoh(Integer(3))
1 + v + O(t, u, v)^3
>>> g = g.O(Integer(5)); g
1 + v + 3*t^2*u - 2*t^2*v^2 + O(t, u, v)^5
```

Sage keeps track of total-degree precision:

```
sage: f = (g-1)^2 - g + 1; f
-v + v^2 - 3*t^2*u + 6*t^2*u*v + 2*t^2*v^2 + O(t, u, v)^5
sage: f in R
True
sage: f.prec()
5
sage: ((g-1-v)^2).prec()
8
```

```
>>> from sage.all import *
>>> f = (g-Integer(1))**Integer(2) - g + Integer(1); f
-v + v^2 - 3*t^2*u + 6*t^2*u*v + 2*t^2*v^2 + O(t, u, v)^5
>>> f in R
True
>>> f.prec()
5
>>> ((g-Integer(1)-v)**Integer(2)).prec()
8
```

Construct multivariate power series rings over various base rings.

```
sage: M = PowerSeriesRing(QQ, 4, 'k'); M
Multivariate Power Series Ring in k0, k1, k2, k3 over Rational Field
sage: loads(dumps(M)) is M
True
sage: TestSuite(M).run()

sage: H = PowerSeriesRing(PolynomialRing(ZZ, 3, 'z'), 4, 'f'); H
Multivariate Power Series Ring in f0, f1, f2, f3
over Multivariate Polynomial Ring in z0, z1, z2 over Integer Ring
sage: TestSuite(H).run()
sage: loads(dumps(H)) is H
True

sage: z = H.base_ring().gens()
sage: f = H.gens()
sage: h = 4*z[1]^2 + 2*z[0]*z[2] + z[1]*z[2] + z[2]^2 \
.....: + (-z[2]^2 - 2*z[0] + z[2])*f[0]*f[2] \
.....: + (-22*z[0]^2 + 2*z[1]^2 - z[0]*z[2] + z[2]^2 - 1955*z[2])*f[1]*f[2] \
.....: + (-z[0]*z[1] - 2*z[1]^2)*f[2]*f[3] \
.....: + (2*z[0]*z[1] + z[1]*z[2] - z[2]^2 - z[1] + 3*z[2])*f[3]^2 \
.....: + H.O(3)
sage: h in H
True
sage: h
```

(continues on next page)

(continued from previous page)

```

4*z1^2 + 2*z0*z2 + z1*z2 + z2^2 + (-z2^2 - 2*z0 + z2)*f0*f2
+ (-22*z0^2 + 2*z1^2 - z0*z2 + z2^2 - 1955*z2)*f1*f2
+ (-z0*z1 - 2*z1^2)*f2*f3 + (2*z0*z1 + z1*z2 - z2^2 - z1 + 3*z2)*f3^2
+ O(f0, f1, f2, f3)^3
    
```

```

>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 'k'); M
Multivariate Power Series Ring in k0, k1, k2, k3 over Rational Field
>>> loads(dumps(M)) is M
True
>>> TestSuite(M).run()

>>> H = PowerSeriesRing(PolynomialRing(ZZ, Integer(3), 'z'), Integer(4), 'f'); H
Multivariate Power Series Ring in f0, f1, f2, f3
over Multivariate Polynomial Ring in z0, z1, z2 over Integer Ring
>>> TestSuite(H).run()
>>> loads(dumps(H)) is H
True

>>> z = H.base_ring().gens()
>>> f = H.gens()
>>> h = Integer(4)*z[Integer(1)]**Integer(2) + Integer(2)*z[Integer(0)]*z[Integer(2)] -
↳ z[Integer(1)]*z[Integer(2)] + z[Integer(2)]**Integer(2) + (-
↳ z[Integer(2)]**Integer(2) - Integer(2)*z[Integer(0)] +
↳ z[Integer(2)]*f[Integer(0)]*f[Integer(2)] + (-
↳ Integer(22)*z[Integer(0)]**Integer(2) + Integer(2)*z[Integer(1)]**Integer(2) -
↳ z[Integer(0)]*z[Integer(2)] + z[Integer(2)]**Integer(2) -
↳ Integer(1955)*z[Integer(2)]*f[Integer(1)]*f[Integer(2)] + (-
↳ z[Integer(0)]*z[Integer(1)] -
↳ Integer(2)*z[Integer(1)]**Integer(2)*f[Integer(2)]*f[Integer(3)] +
↳ (Integer(2)*z[Integer(0)]*z[Integer(1)] + z[Integer(1)]*z[Integer(2)] -
↳ z[Integer(2)]**Integer(2) - z[Integer(1)] +
↳ Integer(3)*z[Integer(2)]*f[Integer(3)]**Integer(2) + H.O(Integer(3))
>>> h in H
True
>>> h
4*z1^2 + 2*z0*z2 + z1*z2 + z2^2 + (-z2^2 - 2*z0 + z2)*f0*f2
+ (-22*z0^2 + 2*z1^2 - z0*z2 + z2^2 - 1955*z2)*f1*f2
+ (-z0*z1 - 2*z1^2)*f2*f3 + (2*z0*z1 + z1*z2 - z2^2 - z1 + 3*z2)*f3^2
+ O(f0, f1, f2, f3)^3
    
```

- Use angle-bracket notation:

```

sage: # needs sage.rings.finite_rings
sage: S.<x,y> = PowerSeriesRing(GF(65537)); S
Multivariate Power Series Ring in x, y over Finite Field of size 65537
sage: s = -30077*x + 9485*x*y - 6260*y^3 + 12870*x^2*y^2 - 20289*y^4 + S.O(5); s
-30077*x + 9485*x*y - 6260*y^3 + 12870*x^2*y^2 - 20289*y^4 + O(x, y)^5
sage: s in S
True
sage: TestSuite(S).run()
sage: loads(dumps(S)) is S
    
```

(continues on next page)

(continued from previous page)

True

```

>>> from sage.all import *
>>> # needs sage.rings.finite_rings
>>> S = PowerSeriesRing(GF(Integer(65537)), names=('x', 'y')); (x, y) = S._
    ↪ first_ngens(2); S
Multivariate Power Series Ring in x, y over Finite Field of size 65537
>>> s = -Integer(30077)*x + Integer(9485)*x*y - Integer(6260)*y**Integer(3) +
    ↪ Integer(12870)*x**Integer(2)*y**Integer(2) - Integer(20289)*y**Integer(4) + S.
    ↪ O(Integer(5)); s
-30077*x + 9485*x*y - 6260*y^3 + 12870*x^2*y^2 - 20289*y^4 + O(x, y)^5
>>> s in S
True
>>> TestSuite(S).run()
>>> loads(dumps(S)) is S
True

```

- Use double square bracket notation:

```

sage: ZZ[['s,t,u']]
Multivariate Power Series Ring in s, t, u over Integer Ring
sage: GF(127931)[['x,y']]
    ↪ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 127931

```

```

>>> from sage.all import *
>>> ZZ[['s,t,u']]
Multivariate Power Series Ring in s, t, u over Integer Ring
>>> GF(Integer(127931))[['x,y']]
    ↪ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 127931

```

Variable ordering determines how series are displayed.

```

sage: T.<a,b> = PowerSeriesRing(ZZ,order='deglex'); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: TestSuite(T).run()
sage: loads(dumps(T)) is T
True
sage: T.term_order()
Degree lexicographic term order
sage: p = - 2*b^6 + a^5*b^2 + a^7 - b^2 - a*b^3 + T.O(9); p
a^7 + a^5*b^2 - 2*b^6 - a*b^3 - b^2 + O(a, b)^9

sage: U = PowerSeriesRing(ZZ,'a,b',order='negdeglex'); U
Multivariate Power Series Ring in a, b over Integer Ring
sage: U.term_order()
Negative degree lexicographic term order
sage: U(p)
-b^2 - a*b^3 - 2*b^6 + a^7 + a^5*b^2 + O(a, b)^9

```

```

>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, order='deglex', names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2); T
Multivariate Power Series Ring in a, b over Integer Ring
>>> TestSuite(T).run()
>>> loads(dumps(T)) is T
True
>>> T.term_order()
Degree lexicographic term order
>>> p = - Integer(2)*b**Integer(6) + a**Integer(5)*b**Integer(2) + a**Integer(7) -
↳b**Integer(2) - a*b**Integer(3) + T.O(Integer(9)); p
a^7 + a^5*b^2 - 2*b^6 - a*b^3 - b^2 + O(a, b)^9

>>> U = PowerSeriesRing(ZZ, 'a,b', order='negdeglex'); U
Multivariate Power Series Ring in a, b over Integer Ring
>>> U.term_order()
Negative degree lexicographic term order
>>> U(p)
-b^2 - a*b^3 - 2*b^6 + a^7 + a^5*b^2 + O(a, b)^9

```

Change from one base ring to another:

```

sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: R.base_extend(RR) #↳
↳needs sage.rings.real_mpfr
Multivariate Power Series Ring in t, u, v
over Real Field with 53 bits of precision
sage: R.change_ring(IntegerModRing(10))
Multivariate Power Series Ring in t, u, v
over Ring of integers modulo 10

sage: S = PowerSeriesRing(GF(65537), 2, 'x,y'); S #↳
↳needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 65537
sage: S.change_ring(GF(5)) #↳
↳needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 5

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t', 'u', 'v',)); (t, u, v,) = R._first_ngens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field
>>> R.base_extend(RR) #↳
↳needs sage.rings.real_mpfr
Multivariate Power Series Ring in t, u, v
over Real Field with 53 bits of precision
>>> R.change_ring(IntegerModRing(Integer(10)))
Multivariate Power Series Ring in t, u, v
over Ring of integers modulo 10

>>> S = PowerSeriesRing(GF(Integer(65537)), Integer(2), 'x,y'); S #↳
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 65537

```

(continues on next page)

(continued from previous page)

```
>>> S.change_ring(GF(Integer(5)))
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 5
```

Coercion from polynomial ring:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: A = PolynomialRing(ZZ,3,'t,u,v')
sage: g = A.gens()
sage: a = 2*g[0]*g[2] - 2*g[0] - 2; a
2*t*v - 2*t - 2
sage: R(a)
-2 - 2*t + 2*t*v
sage: R(a).O(4)
-2 - 2*t + 2*t*v + O(t, u, v)^4
sage: a.parent()
Multivariate Polynomial Ring in t, u, v over Integer Ring
sage: a in R
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t', 'u', 'v',)); (t, u, v,) = R._first_ngens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field
>>> A = PolynomialRing(ZZ,Integer(3),'t,u,v')
>>> g = A.gens()
>>> a = Integer(2)*g[Integer(0)]*g[Integer(2)] - Integer(2)*g[Integer(0)] -
↳ Integer(2); a
2*t*v - 2*t - 2
>>> R(a)
-2 - 2*t + 2*t*v
>>> R(a).O(Integer(4))
-2 - 2*t + 2*t*v + O(t, u, v)^4
>>> a.parent()
Multivariate Polynomial Ring in t, u, v over Integer Ring
>>> a in R
True
```

Coercion from polynomial ring in subset of variables:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: A = PolynomialRing(QQ,2,'t,v')
sage: g = A.gens()
sage: a = -2*g[0]*g[1] - 1/27*g[1]^2 + g[0] - 1/2*g[1]; a
-2*t*v - 1/27*v^2 + t - 1/2*v
sage: a in R
True
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t', 'u', 'v',)); (t, u, v,) = R._first_ngens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field
```

(continues on next page)

(continued from previous page)

```

>>> A = PolynomialRing(QQ, Integer(2), 't,v')
>>> g = A.gens()
>>> a = -Integer(2)*g[Integer(0)]*g[Integer(1)] - Integer(1)/
↳Integer(27)*g[Integer(1)]**Integer(2) + g[Integer(0)] - Integer(1)/
↳Integer(2)*g[Integer(1)]; a
-2*t*v - 1/27*v^2 + t - 1/2*v
>>> a in R
True

```

Coercion from symbolic ring:

```

sage: # needs sage.symbolic
sage: x,y = var('x,y')
sage: S = PowerSeriesRing(GF(11), 2, 'x,y'); S
Multivariate Power Series Ring in x, y over Finite Field of size 11
sage: type(x)
<class 'sage.symbolic.expression.Expression'>
sage: type(S(x))
<class 'sage.rings.multi_power_series_ring.MPowerSeriesRing_generic_with_category.
↳element_class'>
sage: f = S(2/7 -100*x^2 + 1/3*x*y + y^2).O(3); f
5 - x^2 + 4*x*y + y^2 + O(x, y)^3
sage: f.parent()
Multivariate Power Series Ring in x, y over Finite Field of size 11
sage: f.parent() == S
True

```

```

>>> from sage.all import *
>>> # needs sage.symbolic
>>> x,y = var('x,y')
>>> S = PowerSeriesRing(GF(Integer(11)), Integer(2), 'x,y'); S
Multivariate Power Series Ring in x, y over Finite Field of size 11
>>> type(x)
<class 'sage.symbolic.expression.Expression'>
>>> type(S(x))
<class 'sage.rings.multi_power_series_ring.MPowerSeriesRing_generic_with_category.
↳element_class'>
>>> f = S(Integer(2)/Integer(7) -Integer(100)*x**Integer(2) + Integer(1)/
↳Integer(3)*x*y + y**Integer(2)).O(Integer(3)); f
5 - x^2 + 4*x*y + y^2 + O(x, y)^3
>>> f.parent()
Multivariate Power Series Ring in x, y over Finite Field of size 11
>>> f.parent() == S
True

```

The implementation of the multivariate power series ring uses a combination of multivariate polynomials and univariate power series. Namely, in order to construct the multivariate power series ring $R[[x_1, x_2, \dots, x_n]]$, we consider the univariate power series ring $S[[T]]$ over the multivariate polynomial ring $S := R[x_1, x_2, \dots, x_n]$, and in it we take the subring formed by all power series whose i -th coefficient has degree i for all $i \geq 0$. This subring is isomorphic to $R[[x_1, x_2, \dots, x_n]]$. This is how $R[[x_1, x_2, \dots, x_n]]$ is implemented in this class. The ring S is called the foreground polynomial ring, and the ring $S[[T]]$ is called the background univariate power series ring.

AUTHORS:

- Niles Johnson (2010-07): initial code
- Simon King (2012-08, 2013-02): Use category and coercion framework, [Issue #13412](#) and [Issue #14084](#)

```
class sage.rings.multi_power_series_ring.MPowerSeriesRing_generic(base_ring, num_gens,
                                                                    name_list,
                                                                    order='negdeglex',
                                                                    default_prec=10,
                                                                    sparse=False)
```

Bases: `PowerSeriesRing_generic`, `Nonexact`

A multivariate power series ring.

This class is implemented as a single variable power series ring in the variable `T` over a multivariable polynomial ring in the specified generators. Each generator `g` of the multivariable polynomial ring (called the “foreground ring”) is mapped to `g*T` in the single variable power series ring (called the “background ring”). The background power series ring is used to do arithmetic and track total-degree precision. The foreground polynomial ring is used to display elements.

For usage and examples, see above, and `PowerSeriesRing()`.

Element

alias of `MPowerSeries`

`O(prec)`

Return big oh with precision `prec`.

This function is an alias for `bigoh`.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: T.O(10)
0 + O(a, b)^10
sage: T.bigoh(10)
0 + O(a, b)^10
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ,Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2); T
Multivariate Power Series Ring in a, b over Integer Ring
>>> T.O(Integer(10))
0 + O(a, b)^10
>>> T.bigoh(Integer(10))
0 + O(a, b)^10
```

`bigoh(prec)`

Return big oh with precision `prec`.

The function `O` does the same thing.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ,2); T
Multivariate Power Series Ring in a, b over Integer Ring
sage: T.bigoh(10)
0 + O(a, b)^10
```

(continues on next page)

(continued from previous page)

```
sage: T.O(10)
0 + O(a, b)^10
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, Integer(2), names=('a', 'b',)); (a, b,) = T._first_
↳ngens(2); T
Multivariate Power Series Ring in a, b over Integer Ring
>>> T.bigoh(Integer(10))
0 + O(a, b)^10
>>> T.O(Integer(10))
0 + O(a, b)^10
```

change_ring(*R*)

Return the power series ring over *R* in the same variable as *self*.

This function ignores the question of whether the base ring of *self* is or can extend to the base ring of *R*; for the latter, use *base_extend*.

EXAMPLES:

```
sage: R.<t,u,v> = PowerSeriesRing(QQ); R
Multivariate Power Series Ring in t, u, v over Rational Field
sage: R.base_extend(RR) #_
↳needs sage.rings.real_mpfr
Multivariate Power Series Ring in t, u, v over Real Field with
53 bits of precision
sage: R.change_ring(IntegerModRing(10))
Multivariate Power Series Ring in t, u, v over Ring of integers
modulo 10
sage: R.base_extend(IntegerModRing(10))
Traceback (most recent call last):
...
TypeError: no base extension defined

sage: S = PowerSeriesRing(GF(65537), 2, 'x, y'); S #_
↳needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size
65537
sage: S.change_ring(GF(5)) #_
↳needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 5
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(QQ, names=('t', 'u', 'v',)); (t, u, v,) = R._first_
↳ngens(3); R
Multivariate Power Series Ring in t, u, v over Rational Field
>>> R.base_extend(RR) #_
↳needs sage.rings.real_mpfr
Multivariate Power Series Ring in t, u, v over Real Field with
53 bits of precision
>>> R.change_ring(IntegerModRing(Integer(10)))
```

(continues on next page)

(continued from previous page)

```

Multivariate Power Series Ring in t, u, v over Ring of integers
modulo 10
>>> R.base_extend(IntegerModRing(Integer(10)))
Traceback (most recent call last):
...
TypeError: no base extension defined

>>> S = PowerSeriesRing(GF(Integer(65537)), Integer(2), 'x, y'); S
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size
65537
>>> S.change_ring(GF(Integer(5)))
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in x, y over Finite Field of size 5

```

characteristic()

Return characteristic of base ring, which is characteristic of self.

EXAMPLES:

```

sage: H = PowerSeriesRing(GF(65537), 4, 'f'); H
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in f0, f1, f2, f3 over
Finite Field of size 65537
sage: H.characteristic()
↳ # needs sage.rings.finite_rings
65537

```

```

>>> from sage.all import *
>>> H = PowerSeriesRing(GF(Integer(65537)), Integer(4), 'f'); H
↳ # needs sage.rings.finite_rings
Multivariate Power Series Ring in f0, f1, f2, f3 over
Finite Field of size 65537
>>> H.characteristic()
↳ # needs sage.rings.finite_rings
65537

```

construction()

Return a functor F and base ring R such that $F(R) == \text{self}$.

EXAMPLES:

```

sage: M = PowerSeriesRing(QQ, 4, 'f'); M
Multivariate Power Series Ring in f0, f1, f2, f3 over Rational Field

sage: c, R = M.construction(); R
Multivariate Polynomial Ring in f0, f1, f2, f3 over Rational Field
sage: c
Completion[('f0', 'f1', 'f2', 'f3'), prec=12]
sage: c(R)
Multivariate Power Series Ring in f0, f1, f2, f3 over Rational Field

```

(continues on next page)

(continued from previous page)

```
sage: c(R) == M
True
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 'f'); M
Multivariate Power Series Ring in f0, f1, f2, f3 over Rational Field

>>> c, R = M.construction(); R
Multivariate Polynomial Ring in f0, f1, f2, f3 over Rational Field
>>> c
Completion[('f0', 'f1', 'f2', 'f3'), prec=12]
>>> c(R)
Multivariate Power Series Ring in f0, f1, f2, f3 over Rational Field
>>> c(R) == M
True
```

gen($n=0$)Return the n -th generator of self.

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 10, 'v')
sage: M.gen(6)
v6
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(ZZ, Integer(10), 'v')
>>> M.gen(Integer(6))
v6
```

gens()

Return the generators of this ring.

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 3, 'v')
sage: M.gens()
(v0, v1, v2)
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(ZZ, Integer(3), 'v')
>>> M.gens()
(v0, v1, v2)
```

is_dense()

Is self dense? (opposite of sparse)

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 3, 's,t,u'); M
Multivariate Power Series Ring in s, t, u over Integer Ring
sage: M.is_dense()
```

(continues on next page)

(continued from previous page)

```

True
sage: N = PowerSeriesRing(ZZ, 3, 's,t,u', sparse=True); N
Sparse Multivariate Power Series Ring in s, t, u over Integer Ring
sage: N.is_dense()
False

```

```

>>> from sage.all import *
>>> M = PowerSeriesRing(ZZ, Integer(3), 's,t,u'); M
Multivariate Power Series Ring in s, t, u over Integer Ring
>>> M.is_dense()
True
>>> N = PowerSeriesRing(ZZ, Integer(3), 's,t,u', sparse=True); N
Sparse Multivariate Power Series Ring in s, t, u over Integer Ring
>>> N.is_dense()
False

```

is_noetherian (*proof=False*)

Power series over a Noetherian ring are Noetherian.

EXAMPLES:

```

sage: M = PowerSeriesRing(QQ, 4, 'v'); M
Multivariate Power Series Ring in v0, v1, v2, v3 over Rational Field
sage: M.is_noetherian()
True

sage: W = PowerSeriesRing(InfinitePolynomialRing(ZZ, 'a'), 2, 'x,y')
sage: W.is_noetherian()
False

```

```

>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 'v'); M
Multivariate Power Series Ring in v0, v1, v2, v3 over Rational Field
>>> M.is_noetherian()
True

>>> W = PowerSeriesRing(InfinitePolynomialRing(ZZ, 'a'), Integer(2), 'x,y')
>>> W.is_noetherian()
False

```

is_sparse ()

Check whether self is sparse.

EXAMPLES:

```

sage: M = PowerSeriesRing(ZZ, 3, 's,t,u'); M
Multivariate Power Series Ring in s, t, u over Integer Ring
sage: M.is_sparse()
False

sage: N = PowerSeriesRing(ZZ, 3, 's,t,u', sparse=True); N
Sparse Multivariate Power Series Ring in s, t, u over Integer Ring
sage: N.is_sparse()
True

```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(ZZ, Integer(3), 's,t,u'); M
Multivariate Power Series Ring in s, t, u over Integer Ring
>>> M.is_sparse()
False
>>> N = PowerSeriesRing(ZZ, Integer(3), 's,t,u', sparse=True); N
Sparse Multivariate Power Series Ring in s, t, u over Integer Ring
>>> N.is_sparse()
True
```

laurent_series_ring()

Laurent series not yet implemented for multivariate power series rings.

ngens()

Return number of generators of self.

EXAMPLES:

```
sage: M = PowerSeriesRing(ZZ, 10, 'v')
sage: M.ngens()
10
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(ZZ, Integer(10), 'v')
>>> M.ngens()
10
```

prec_ideal()

Return the ideal which determines precision.

This is the ideal generated by all of the generators of our background polynomial ring.

EXAMPLES:

```
sage: A.<s,t,u> = PowerSeriesRing(ZZ)
sage: A.prec_ideal()
Ideal (s, t, u) of
Multivariate Polynomial Ring in s, t, u over Integer Ring
```

```
>>> from sage.all import *
>>> A = PowerSeriesRing(ZZ, names=('s', 't', 'u',)); (s, t, u,) = A._first_
↳ngens(3)
>>> A.prec_ideal()
Ideal (s, t, u) of
Multivariate Polynomial Ring in s, t, u over Integer Ring
```

remove_var(*var)

Remove given variable or sequence of variables from self.

EXAMPLES:

```
sage: A.<s,t,u> = PowerSeriesRing(ZZ)
sage: A.remove_var(t)
Multivariate Power Series Ring in s, u over Integer Ring
```

(continues on next page)

(continued from previous page)

```
sage: A.remove_var(s,t)
Power Series Ring in u over Integer Ring

sage: M = PowerSeriesRing(GF(5),5,'t'); M
Multivariate Power Series Ring in t0, t1, t2, t3, t4
over Finite Field of size 5
sage: M.remove_var(M.gens()[3])
Multivariate Power Series Ring in t0, t1, t2, t4
over Finite Field of size 5
```

```
>>> from sage.all import *
>>> A = PowerSeriesRing(ZZ, names=('s', 't', 'u',)); (s, t, u,) = A._first_
↳ngens(3)
>>> A.remove_var(t)
Multivariate Power Series Ring in s, u over Integer Ring
>>> A.remove_var(s,t)
Power Series Ring in u over Integer Ring

>>> M = PowerSeriesRing(GF(Integer(5)),Integer(5),'t'); M
Multivariate Power Series Ring in t0, t1, t2, t3, t4
over Finite Field of size 5
>>> M.remove_var(M.gens()[Integer(3)])
Multivariate Power Series Ring in t0, t1, t2, t4
over Finite Field of size 5
```

Removing all variables results in the base ring:

```
sage: M.remove_var(*M.gens())
Finite Field of size 5
```

```
>>> from sage.all import *
>>> M.remove_var(*M.gens())
Finite Field of size 5
```

term_order()

Return the term ordering of self.

Term orderings are implemented by the `TermOrder` class.

EXAMPLES:

```
sage: M.<x,y,z> = PowerSeriesRing(ZZ,3)
sage: M.term_order()
Negative degree lexicographic term order
sage: m = y*z^12 - y^6*z^8 - x^7*y^5*z^2 + x*y^2*z + M.O(15); m
x*y^2*z + y*z^12 - x^7*y^5*z^2 - y^6*z^8 + O(x, y, z)^15

sage: N = PowerSeriesRing(ZZ,3,'x,y,z', order='deglex')
sage: N.term_order()
Degree lexicographic term order
```

(continues on next page)

(continued from previous page)

```
sage: N(m)
-x^7*y^5*z^2 - y^6*z^8 + y*z^12 + x*y^2*z + O(x, y, z)^15
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(ZZ,Integer(3), names=('x', 'y', 'z')); (x, y, z) = M._first_ngens(3)
>>> M.term_order()
Negative degree lexicographic term order
>>> m = y*z**Integer(12) - y**Integer(6)*z**Integer(8) - x**Integer(7)*y**Integer(5)*z**Integer(2) + x*y**Integer(2)*z + M.
O(Integer(15)); m
x*y^2*z + y*z^12 - x^7*y^5*z^2 - y^6*z^8 + O(x, y, z)^15

>>> N = PowerSeriesRing(ZZ,Integer(3),'x,y,z', order='deglex')
>>> N.term_order()
Degree lexicographic term order
>>> N(m)
-x^7*y^5*z^2 - y^6*z^8 + y*z^12 + x*y^2*z + O(x, y, z)^15
```

```
sage.rings.multi_power_series_ring.is_MPowerSeriesRing(x)
```

Return True if input is a multivariate power series ring.

```
sage.rings.multi_power_series_ring.unpickle_multi_power_series_ring_v0(base_ring, num_gens,
                                                                           names, order,
                                                                           default_prec, sparse)
```

Unpickle (deserialize) a multivariate power series ring according to the given inputs.

EXAMPLES:

```
sage: P.<x,y> = PowerSeriesRing(QQ)
sage: loads(dumps(P)) == P # indirect doctest
True
```

```
>>> from sage.all import *
>>> P = PowerSeriesRing(QQ, names=('x', 'y')); (x, y) = P._first_ngens(2)
>>> loads(dumps(P)) == P # indirect doctest
True
```


MULTIVARIATE POWER SERIES

Construct and manipulate multivariate power series (in finitely many variables) over a given commutative ring. Multivariate power series are implemented with total-degree precision.

EXAMPLES:

Power series arithmetic, tracking precision:

```
sage: R.<s,t> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in s, t over Integer Ring

sage: f = 1 + s + 3*s^2; f
1 + s + 3*s^2
sage: g = t^2*s + 3*t^2*s^2 + R.O(5); g
s*t^2 + 3*s^2*t^2 + O(s, t)^5
sage: g = t^2*s + 3*t^2*s^2 + O(s, t)^5; g
s*t^2 + 3*s^2*t^2 + O(s, t)^5
sage: f = f.O(7); f
1 + s + 3*s^2 + O(s, t)^7
sage: f += s; f
1 + 2*s + 3*s^2 + O(s, t)^7
sage: f*g
s*t^2 + 5*s^2*t^2 + O(s, t)^5
sage: (f-1)*g
2*s^2*t^2 + 9*s^3*t^2 + O(s, t)^6
sage: f*g - g
2*s^2*t^2 + O(s, t)^5

sage: f *= s; f
s + 2*s^2 + 3*s^3 + O(s, t)^8
sage: f%2
s + s^3 + O(s, t)^8
sage: (f%2).parent()
Multivariate Power Series Ring in s, t over Ring of integers modulo 2
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('s', 't')); (s, t,) = R._first_ngens(2); R
Multivariate Power Series Ring in s, t over Integer Ring

>>> f = Integer(1) + s + Integer(3)*s**Integer(2); f
1 + s + 3*s^2
>>> g = t**Integer(2)*s + Integer(3)*t**Integer(2)*s**Integer(2) + R.O(Integer(5)); g
```

(continues on next page)

(continued from previous page)

```

s*t^2 + 3*s^2*t^2 + O(s, t)^5
>>> g = t**Integer(2)*s + Integer(3)*t**Integer(2)*s**Integer(2) + O(s, t)
      ↪t)**Integer(5); g
s*t^2 + 3*s^2*t^2 + O(s, t)^5
>>> f = f.O(Integer(7)); f
1 + s + 3*s^2 + O(s, t)^7
>>> f += s; f
1 + 2*s + 3*s^2 + O(s, t)^7
>>> f*g
s*t^2 + 5*s^2*t^2 + O(s, t)^5
>>> (f-Integer(1))*g
2*s^2*t^2 + 9*s^3*t^2 + O(s, t)^6
>>> f*g - g
2*s^2*t^2 + O(s, t)^5

>>> f *= s; f
s + 2*s^2 + 3*s^3 + O(s, t)^8
>>> f%Integer(2)
s + s^3 + O(s, t)^8
>>> (f%Integer(2)).parent()
Multivariate Power Series Ring in s, t over Ring of integers modulo 2

```

As with univariate power series, comparison of f and g is done up to the minimum precision of f and g :

```

sage: f = 1 + t + s + s*t + R.O(3); f
1 + s + t + s*t + O(s, t)^3
sage: g = s^2 + 2*s^4 - s^5 + s^2*t^3 + R.O(6); g
s^2 + 2*s^4 - s^5 + s^2*t^3 + O(s, t)^6
sage: f == g
False
sage: g == g.add_bigoh(3)
True
sage: f < g
False
sage: f > g
True

```

```

>>> from sage.all import *
>>> f = Integer(1) + t + s + s*t + R.O(Integer(3)); f
1 + s + t + s*t + O(s, t)^3
>>> g = s**Integer(2) + Integer(2)*s**Integer(4) - s**Integer(5) +
      ↪s**Integer(2)*t**Integer(3) + R.O(Integer(6)); g
s^2 + 2*s^4 - s^5 + s^2*t^3 + O(s, t)^6
>>> f == g
False
>>> g == g.add_bigoh(Integer(3))
True
>>> f < g
False
>>> f > g
True

```

Calling:


```
sage: f = s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + R.O(5); f
s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + O(s, t)^5
sage: f(t, s)
s*t + t^2 + s*t^2 + t^3 + 3*s*t^3 + 3*t^4 + O(s, t)^5
sage: f(t^2, s^2)
s^2*t^2 + t^4 + s^2*t^4 + t^6 + 3*s^2*t^6 + 3*t^8 + O(s, t)^10
```

```
>>> from sage.all import *
>>> f = s**Integer(2) + s*t + s**Integer(3) + s**Integer(2)*t +
Integer(3)*s**Integer(4) + Integer(3)*s**Integer(3)*t + R.O(Integer(5)); f
s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + O(s, t)^5
>>> f(t, s)
s*t + t^2 + s*t^2 + t^3 + 3*s*t^3 + 3*t^4 + O(s, t)^5
>>> f(t**Integer(2), s**Integer(2))
s^2*t^2 + t^4 + s^2*t^4 + t^6 + 3*s^2*t^6 + 3*t^8 + O(s, t)^10
```

Substitution is defined only for elements of positive valuation, unless f has infinite precision:

```
sage: f(t^2, s^2 + 1)
Traceback (most recent call last):
...
TypeError: Substitution defined only for elements of positive valuation,
unless self has infinite precision.

sage: g = f.truncate()
sage: g(t^2, s^2 + 1)
t^2 + s^2*t^2 + 2*t^4 + s^2*t^4 + 4*t^6 + 3*s^2*t^6 + 3*t^8
sage: g(t^2, (s^2+1).O(3))
t^2 + s^2*t^2 + 2*t^4 + O(s, t)^5
```

```
>>> from sage.all import *
>>> f(t**Integer(2), s**Integer(2) + Integer(1))
Traceback (most recent call last):
...
TypeError: Substitution defined only for elements of positive valuation,
unless self has infinite precision.

>>> g = f.truncate()
>>> g(t**Integer(2), s**Integer(2) + Integer(1))
t^2 + s^2*t^2 + 2*t^4 + s^2*t^4 + 4*t^6 + 3*s^2*t^6 + 3*t^8
>>> g(t**Integer(2), (s**Integer(2)+Integer(1)).O(Integer(3)))
t^2 + s^2*t^2 + 2*t^4 + O(s, t)^5
```

0 has valuation +Infinity:

```
sage: f(t^2, 0)
t^4 + t^6 + 3*t^8 + O(s, t)^10
sage: f(t^2, s^2 + s)
s*t^2 + s^2*t^2 + t^4 + O(s, t)^5
```

```
>>> from sage.all import *
>>> f(t**Integer(2), Integer(0))
```

(continues on next page)

(continued from previous page)

```
t^4 + t^6 + 3*t^8 + O(s, t)^10
>>> f(t**Integer(2), s**Integer(2) + s)
s*t^2 + s^2*t^2 + t^4 + O(s, t)^5
```

Substitution of power series with finite precision works too:

```
sage: f(s.O(2), t)
s^2 + s*t + O(s, t)^3
sage: f(f, f)
2*s^4 + 4*s^3*t + 2*s^2*t^2 + 4*s^5 + 8*s^4*t + 4*s^3*t^2 + 16*s^6 +
34*s^5*t + 20*s^4*t^2 + 2*s^3*t^3 + O(s, t)^7
sage: t(f, f)
s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + O(s, t)^5
sage: t(0, f) == s(f, 0)
True
```

```
>>> from sage.all import *
>>> f(s.O(Integer(2)), t)
s^2 + s*t + O(s, t)^3
>>> f(f, f)
2*s^4 + 4*s^3*t + 2*s^2*t^2 + 4*s^5 + 8*s^4*t + 4*s^3*t^2 + 16*s^6 +
34*s^5*t + 20*s^4*t^2 + 2*s^3*t^3 + O(s, t)^7
>>> t(f, f)
s^2 + s*t + s^3 + s^2*t + 3*s^4 + 3*s^3*t + O(s, t)^5
>>> t(Integer(0), f) == s(f, Integer(0))
True
```

The subs syntax works as expected:

```
sage: r0 = -t^2 - s*t^3 - 2*t^6 + s^7 + s^5*t^2 + R.O(10)
sage: r1 = s^4 - s*t^4 + s^6*t - 4*s^2*t^5 - 6*s^3*t^5 + R.O(10)
sage: r2 = 2*s^3*t^2 - 2*s*t^4 - 2*s^3*t^4 + s*t^7 + R.O(10)
sage: r0.subs({t: r2, s: r1})
-4*s^6*t^4 + 8*s^4*t^6 - 4*s^2*t^8 + 8*s^6*t^6 - 8*s^4*t^8 - 4*s^4*t^9
+ 4*s^2*t^11 - 4*s^6*t^8 + O(s, t)^15
sage: r0.subs({t: r2, s: r1}) == r0(r1, r2)
True
```

```
>>> from sage.all import *
>>> r0 = -t**Integer(2) - s*t**Integer(3) - Integer(2)*t**Integer(6) + s**Integer(7) -
↳ + s**Integer(5)*t**Integer(2) + R.O(Integer(10))
>>> r1 = s**Integer(4) - s*t**Integer(4) + s**Integer(6)*t -
↳ Integer(4)*s**Integer(2)*t**Integer(5) - Integer(6)*s**Integer(3)*t**Integer(5) + R.
↳ O(Integer(10))
>>> r2 = Integer(2)*s**Integer(3)*t**Integer(2) - Integer(2)*s*t**Integer(4) -
↳ Integer(2)*s**Integer(3)*t**Integer(4) + s*t**Integer(7) + R.O(Integer(10))
>>> r0.subs({t: r2, s: r1})
-4*s^6*t^4 + 8*s^4*t^6 - 4*s^2*t^8 + 8*s^6*t^6 - 8*s^4*t^8 - 4*s^4*t^9
+ 4*s^2*t^11 - 4*s^6*t^8 + O(s, t)^15
>>> r0.subs({t: r2, s: r1}) == r0(r1, r2)
True
```

Construct ring homomorphisms from one power series ring to another:

```

sage: A.<a,b> = PowerSeriesRing(QQ)
sage: X.<x,y> = PowerSeriesRing(QQ)

sage: phi = Hom(A,X) ([x,2*y]); phi
Ring morphism:
  From: Multivariate Power Series Ring in a, b over Rational Field
  To:   Multivariate Power Series Ring in x, y over Rational Field
  Defn: a |--> x
        b |--> 2*y

sage: phi(a+b+3*a*b^2 + A.O(5))
x + 2*y + 12*x*y^2 + O(x, y)^5

```

```

>>> from sage.all import *
>>> A = PowerSeriesRing(QQ, names=('a', 'b',)); (a, b,) = A._first_ngens(2)
>>> X = PowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = X._first_ngens(2)

>>> phi = Hom(A,X) ([x,Integer(2)*y]); phi
Ring morphism:
  From: Multivariate Power Series Ring in a, b over Rational Field
  To:   Multivariate Power Series Ring in x, y over Rational Field
  Defn: a |--> x
        b |--> 2*y

>>> phi(a+b+Integer(3)*a*b**Integer(2) + A.O(Integer(5)))
x + 2*y + 12*x*y^2 + O(x, y)^5

```

Multiplicative inversion of power series:

```

sage: h = 1 + s + t + s*t + s^2*t^2 + 3*s^4 + 3*s^3*t + R.O(5)
sage: k = h^-1; k
1 - s - t + s^2 + s*t + t^2 - s^3 - s^2*t - s*t^2 - t^3 - 2*s^4 -
2*s^3*t + s*t^3 + t^4 + O(s, t)^5

sage: h*k
1 + O(s, t)^5

sage: f = 1 - 5*s^29 - 5*s^28*t + 4*s^18*t^35 + \
....: 4*s^17*t^36 - s^45*t^25 - s^44*t^26 + s^7*t^83 + \
....: s^6*t^84 + R.O(101)
sage: h = ~f; h
1 + 5*s^29 + 5*s^28*t - 4*s^18*t^35 - 4*s^17*t^36 + 25*s^58 + 50*s^57*t
+ 25*s^56*t^2 + s^45*t^25 + s^44*t^26 - 40*s^47*t^35 - 80*s^46*t^36
- 40*s^45*t^37 + 125*s^87 + 375*s^86*t + 375*s^85*t^2 + 125*s^84*t^3
- s^7*t^83 - s^6*t^84 + 10*s^74*t^25 + 20*s^73*t^26 + 10*s^72*t^27
+ O(s, t)^101
sage: h*f
1 + O(s, t)^101

```

```

>>> from sage.all import *
>>> h = Integer(1) + s + t + s*t + s**Integer(2)*t**Integer(2) + \
    Integer(3)*s**Integer(4) + Integer(3)*s**Integer(3)*t + R.O(Integer(5))
>>> k = h**-Integer(1); k

```

(continues on next page)

(continued from previous page)

```

1 - s - t + s^2 + s*t + t^2 - s^3 - s^2*t - s*t^2 - t^3 - 2*s^4 -
2*s^3*t + s*t^3 + t^4 + O(s, t)^5
>>> h*k
1 + O(s, t)^5

>>> f = Integer(1) - Integer(5)*s**Integer(29) - Integer(5)*s**Integer(28)*t +
↳Integer(4)*s**Integer(18)*t**Integer(35) + Integer(4)*s**Integer(17)*t**Integer(36)
↳- s**Integer(45)*t**Integer(25) - s**Integer(44)*t**Integer(26) +
↳s**Integer(7)*t**Integer(83) + s**Integer(6)*t**Integer(84) + R.O(Integer(101))
>>> h = ~f; h
1 + 5*s^29 + 5*s^28*t - 4*s^18*t^35 - 4*s^17*t^36 + 25*s^58 + 50*s^57*t
+ 25*s^56*t^2 + s^45*t^25 + s^44*t^26 - 40*s^47*t^35 - 80*s^46*t^36
- 40*s^45*t^37 + 125*s^87 + 375*s^86*t + 375*s^85*t^2 + 125*s^84*t^3
- s^7*t^83 - s^6*t^84 + 10*s^74*t^25 + 20*s^73*t^26 + 10*s^72*t^27
+ O(s, t)^101
>>> h*f
1 + O(s, t)^101

```

AUTHORS:

- Niles Johnson (07/2010): initial code
- Simon King (08/2012): Use category and coercion framework, [Issue #13412](#)

```
class sage.rings.multi_power_series_ring_element.MO(x)
```

Bases: object

Object representing a zero element with given precision.

EXAMPLES:

```

sage: R.<u,v> = QQ[[[]]]
sage: m = O(u, v)
sage: m^4
0 + O(u, v)^4
sage: m^1
0 + O(u, v)^1

sage: T.<a,b,c> = PowerSeriesRing(ZZ, 3)
sage: z = O(a, b, c)
sage: z^1
0 + O(a, b, c)^1
sage: 1 + a + z^1
1 + O(a, b, c)^1

sage: w = 1 + a + O(a, b, c)^2; w
1 + a + O(a, b, c)^2
sage: w^2
1 + 2*a + O(a, b, c)^2

```

```

>>> from sage.all import *
>>> R = QQ[['u', 'v']]; (u, v,) = R._first_ngens(2)
>>> m = O(u, v)
>>> m**Integer(4)

```

(continues on next page)

(continued from previous page)

```

0 + O(u, v)^4
>>> m**Integer(1)
0 + O(u, v)^1

>>> T = PowerSeriesRing(ZZ, Integer(3), names=('a', 'b', 'c',)); (a, b, c,) = T._
↳first_ngens(3)
>>> z = O(a, b, c)
>>> z**Integer(1)
0 + O(a, b, c)^1
>>> Integer(1) + a + z**Integer(1)
1 + O(a, b, c)^1

>>> w = Integer(1) + a + O(a, b, c)**Integer(2); w
1 + a + O(a, b, c)^2
>>> w**Integer(2)
1 + 2*a + O(a, b, c)^2

```

```

class sage.rings.multi_power_series_ring_element.MPowerSeries (parent, x=0, prec=+Infinity,
                                                                is_gen=False, check=False)

```

Bases: *PowerSeries*

Multivariate power series; these are the elements of Multivariate Power Series Rings.

INPUT:

- `parent` – a multivariate power series
- `x` – the element (default: 0). This can be another *MPowerSeries* object, or an element of one of the following:
 - the background univariate power series ring
 - the foreground polynomial ring
 - a ring that coerces to one of the above two
- `prec` – (default: infinity) the precision
- `is_gen` – boolean (default: False); whether this element is one of the generators
- `check` – boolean (default: False); needed by univariate power series class

EXAMPLES:

Construct multivariate power series from generators:

```

sage: S.<s,t> = PowerSeriesRing(ZZ)
sage: f = s + 4*t + 3*s*t
sage: f in S
True
sage: f = f.add_bigoh(4); f
s + 4*t + 3*s*t + O(s, t)^4
sage: g = 1 + s + t - s*t + S.O(5); g
1 + s + t - s*t + O(s, t)^5

sage: T = PowerSeriesRing(GF(3), 5, 't'); T
Multivariate Power Series Ring in t0, t1, t2, t3, t4
over Finite Field of size 3
sage: t = T.gens()

```

(continues on next page)

(continued from previous page)

```

sage: w = t[0] - 2*t[1]*t[3] + 5*t[4]^3 - t[0]^3*t[2]^2; w
t0 + t1*t3 - t4^3 - t0^3*t2^2
sage: w = w.add_bigoh(5); w
t0 + t1*t3 - t4^3 + O(t0, t1, t2, t3, t4)^5
sage: w in T
True
sage: w = t[0] - 2*t[0]*t[2] + 5*t[4]^3 - t[0]^3*t[2]^2 + T.O(6)
sage: w
t0 + t0*t2 - t4^3 - t0^3*t2^2 + O(t0, t1, t2, t3, t4)^6

```

```

>>> from sage.all import *
>>> S = PowerSeriesRing(ZZ, names=('s', 't')); (s, t) = S._first_ngens(2)
>>> f = s + Integer(4)*t + Integer(3)*s*t
>>> f in S
True
>>> f = f.add_bigoh(Integer(4)); f
s + 4*t + 3*s*t + O(s, t)^4
>>> g = Integer(1) + s + t - s*t + S.O(Integer(5)); g
1 + s + t - s*t + O(s, t)^5

>>> T = PowerSeriesRing(GF(Integer(3)), Integer(5), 't'); T
Multivariate Power Series Ring in t0, t1, t2, t3, t4
over Finite Field of size 3
>>> t = T.gens()
>>> w = t[Integer(0)] - Integer(2)*t[Integer(1)]*t[Integer(3)] +
↳ Integer(5)*t[Integer(4)]**Integer(3) -
↳ t[Integer(0)]**Integer(3)*t[Integer(2)]**Integer(2); w
t0 + t1*t3 - t4^3 - t0^3*t2^2
>>> w = w.add_bigoh(Integer(5)); w
t0 + t1*t3 - t4^3 + O(t0, t1, t2, t3, t4)^5
>>> w in T
True

>>> w = t[Integer(0)] - Integer(2)*t[Integer(0)]*t[Integer(2)] +
↳ Integer(5)*t[Integer(4)]**Integer(3) -
↳ t[Integer(0)]**Integer(3)*t[Integer(2)]**Integer(2) + T.O(Integer(6))
>>> w
t0 + t0*t2 - t4^3 - t0^3*t2^2 + O(t0, t1, t2, t3, t4)^6

```

Get random elements:

```

sage: S.random_element(4) # random
-2*t + t^2 - 12*s^3 + O(s, t)^4

sage: T.random_element(10) # random
-t1^2*t3^2*t4^2 + t1^5*t3^3*t4 + O(t0, t1, t2, t3, t4)^10

```

```

>>> from sage.all import *
>>> S.random_element(Integer(4)) # random
-2*t + t^2 - 12*s^3 + O(s, t)^4

```

(continues on next page)

(continued from previous page)

```
>>> T.random_element(Integer(10)) # random
-t1^2*t3^2*t4^2 + t1^5*t3^3*t4 + O(t0, t1, t2, t3, t4)^10
```

Convert elements from polynomial rings:

```
sage: # needs sage.rings.finite_rings
sage: R = PolynomialRing(ZZ, 5, T.variable_names())
sage: t = R.gens()
sage: r = -t[2]*t[3] + t[3]^2 + t[4]^2
sage: T(r)
-t2*t3 + t3^2 + t4^2
sage: r.parent()
Multivariate Polynomial Ring in t0, t1, t2, t3, t4 over Integer Ring
sage: r in T
True
```

```
>>> from sage.all import *
>>> # needs sage.rings.finite_rings
>>> R = PolynomialRing(ZZ, Integer(5), T.variable_names())
>>> t = R.gens()
>>> r = -t[Integer(2)]*t[Integer(3)] + t[Integer(3)]**Integer(2) +
↳ t[Integer(4)]**Integer(2)
>>> T(r)
-t2*t3 + t3^2 + t4^2
>>> r.parent()
Multivariate Polynomial Ring in t0, t1, t2, t3, t4 over Integer Ring
>>> r in T
True
```

O(prec)

Return a multivariate power series of precision `prec` obtained by truncating `self` at precision `prec`.

This is the same as `add_bigoh()`.

EXAMPLES:

```
sage: B.<x,y> = PowerSeriesRing(QQ); B
Multivariate Power Series Ring in x, y over Rational Field
sage: r = 1 - x*y + x^2
sage: r.O(4)
1 + x^2 - x*y + O(x, y)^4
sage: r.O(2)
1 + O(x, y)^2
```

```
>>> from sage.all import *
>>> B = PowerSeriesRing(QQ, names=('x', 'y')); (x, y) = B._first_ngens(2); B
Multivariate Power Series Ring in x, y over Rational Field
>>> r = Integer(1) - x*y + x**Integer(2)
>>> r.O(Integer(4))
1 + x^2 - x*y + O(x, y)^4
>>> r.O(Integer(2))
1 + O(x, y)^2
```

Note that this does not change `self`:

```
sage: r
1 + x^2 - x*y
```

```
>>> from sage.all import *
>>> r
1 + x^2 - x*y
```

$\mathbf{V}(n)$

If

$$f = \sum a_{m_0, \dots, m_k} x_0^{m_0} \cdots x_k^{m_k},$$

then this function returns

$$\sum a_{m_0, \dots, m_k} x_0^{nm_0} \cdots x_k^{nm_k}.$$

The total-degree precision of the output is n times the precision of `self`.

EXAMPLES:

```
sage: H = QQ[['x,y,z']]
sage: (x,y,z) = H.gens()
sage: h = -x*y^4*z^7 - 1/4*y*z^12 + 1/2*x^7*y^5*z^2 \
.....: + 2/3*y^6*z^8 + H.O(15)
sage: h.V(3)
-x^3*y^12*z^21 - 1/4*y^3*z^36 + 1/2*x^21*y^15*z^6 + 2/3*y^18*z^24 + O(x, y, \
↪ z)^45
```

```
>>> from sage.all import *
>>> H = QQ[['x,y,z']]
>>> (x,y,z) = H.gens()
>>> h = -x*y**Integer(4)*z**Integer(7) - Integer(1)/
↪ Integer(4)*y*z**Integer(12) + Integer(1)/
↪ Integer(2)*x**Integer(7)*y**Integer(5)*z**Integer(2) + Integer(2)/
↪ Integer(3)*y**Integer(6)*z**Integer(8) + H.O(Integer(15))
>>> h.V(Integer(3))
-x^3*y^12*z^21 - 1/4*y^3*z^36 + 1/2*x^21*y^15*z^6 + 2/3*y^18*z^24 + O(x, y, \
↪ z)^45
```

`add_bigoh(prec)`

Return a multivariate power series of precision `prec` obtained by truncating `self` at precision `prec`.

This is the same as `O()`.

EXAMPLES:

```
sage: B.<x,y> = PowerSeriesRing(QQ); B
Multivariate Power Series Ring in x, y over Rational Field
sage: r = 1 - x*y + x^2
sage: r.add_bigoh(4)
1 + x^2 - x*y + O(x, y)^4
sage: r.add_bigoh(2)
1 + O(x, y)^2
```



```

>>> from sage.all import *
>>> B = PowerSeriesRing(QQ, names=('x', 'y')); (x, y) = B._first_ngens(2); B
Multivariate Power Series Ring in x, y over Rational Field
>>> r = Integer(1) - x*y + x**Integer(2)
>>> r.add_bigoh(Integer(4))
1 + x^2 - x*y + O(x, y)^4
>>> r.add_bigoh(Integer(2))
1 + O(x, y)^2

```

Note that this does not change self:

```

sage: r
1 + x^2 - x*y

```

```

>>> from sage.all import *
>>> r
1 + x^2 - x*y

```

`coefficients()`

Return a dict of monomials and coefficients.

EXAMPLES:

```

sage: R.<s,t> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in s, t over Integer Ring
sage: f = 1 + t + s + s*t + R.O(3)
sage: f.coefficients()
{s*t: 1, t: 1, s: 1, 1: 1}
sage: (f^2).coefficients()
{t^2: 1, s*t: 4, s^2: 1, t: 2, s: 2, 1: 1}

sage: g = f^2 + f - 2; g
3*s + 3*t + s^2 + 5*s*t + t^2 + O(s, t)^3
sage: cd = g.coefficients()
sage: g2 = sum(k*v for (k,v) in cd.items()); g2
3*s + 3*t + s^2 + 5*s*t + t^2
sage: g2 == g.truncate()
True

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('s', 't')); (s, t) = R._first_ngens(2); R
Multivariate Power Series Ring in s, t over Integer Ring
>>> f = Integer(1) + t + s + s*t + R.O(Integer(3))
>>> f.coefficients()
{s*t: 1, t: 1, s: 1, 1: 1}
>>> (f**Integer(2)).coefficients()
{t^2: 1, s*t: 4, s^2: 1, t: 2, s: 2, 1: 1}

>>> g = f**Integer(2) + f - Integer(2); g
3*s + 3*t + s^2 + 5*s*t + t^2 + O(s, t)^3
>>> cd = g.coefficients()
>>> g2 = sum(k*v for (k,v) in cd.items()); g2
3*s + 3*t + s^2 + 5*s*t + t^2

```

(continues on next page)

(continued from previous page)

```
>>> g2 == g.truncate()
True
```

constant_coefficient()

Return constant coefficient of self.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b, c over Integer Ring
sage: f = 3 + a + b - a*b - b*c - a*c + R.O(4)
sage: f.constant_coefficient()
3
sage: f.constant_coefficient().parent()
Integer Ring
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('a', 'b', 'c')); (a, b, c) = R._first_
↳ngens(3); R
Multivariate Power Series Ring in a, b, c over Integer Ring
>>> f = Integer(3) + a + b - a*b - b*c - a*c + R.O(Integer(4))
>>> f.constant_coefficient()
3
>>> f.constant_coefficient().parent()
Integer Ring
```

degree()

Return degree of underlying polynomial of self.

EXAMPLES:

```
sage: B.<x,y> = PowerSeriesRing(QQ)
sage: B
Multivariate Power Series Ring in x, y over Rational Field
sage: r = 1 - x*y + x^2
sage: r = r.add_bigoh(4); r
1 + x^2 - x*y + O(x, y)^4
sage: r.degree()
2
```

```
>>> from sage.all import *
>>> B = PowerSeriesRing(QQ, names=('x', 'y')); (x, y) = B._first_ngens(2)
>>> B
Multivariate Power Series Ring in x, y over Rational Field
>>> r = Integer(1) - x*y + x**Integer(2)
>>> r = r.add_bigoh(Integer(4)); r
1 + x^2 - x*y + O(x, y)^4
>>> r.degree()
2
```

derivative(*args)

The formal derivative of this power series, with respect to variables supplied in args.

EXAMPLES:

```

sage: T.<a,b> = PowerSeriesRing(ZZ, 2)
sage: f = a + b + a^2*b + T.O(5)
sage: f.derivative(a)
1 + 2*a*b + O(a, b)^4
sage: f.derivative(a,2)
2*b + O(a, b)^3
sage: f.derivative(a,a)
2*b + O(a, b)^3
sage: f.derivative([a,a])
2*b + O(a, b)^3
sage: f.derivative(a,5)
0 + O(a, b)^0
sage: f.derivative(a,6)
0 + O(a, b)^0

```

```

>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, Integer(2), names=('a', 'b',)); (a, b,) = T._
↳first_ngens(2)
>>> f = a + b + a**Integer(2)*b + T.O(Integer(5))
>>> f.derivative(a)
1 + 2*a*b + O(a, b)^4
>>> f.derivative(a,Integer(2))
2*b + O(a, b)^3
>>> f.derivative(a,a)
2*b + O(a, b)^3
>>> f.derivative([a,a])
2*b + O(a, b)^3
>>> f.derivative(a,Integer(5))
0 + O(a, b)^0
>>> f.derivative(a,Integer(6))
0 + O(a, b)^0

```

dict (*copy=None*)

alias of `monomial_coefficients()`.

egf ()

Method from univariate power series not yet implemented.

exp (*prec=+Infinity*)

Exponentiate the formal power series.

INPUT:

- *prec* – integer or infinity; the degree to truncate the result to

OUTPUT:

The exponentiated multivariate power series as a new multivariate power series.

EXAMPLES:

```

sage: T.<a,b> = PowerSeriesRing(ZZ, 2)
sage: f = a + b + a*b + T.O(3)
sage: exp(f)
1 + a + b + 1/2*a^2 + 2*a*b + 1/2*b^2 + O(a, b)^3

```

(continues on next page)

(continued from previous page)

```
sage: f.exp()
1 + a + b + 1/2*a^2 + 2*a*b + 1/2*b^2 + O(a, b)^3
sage: f.exp(prec=2)
1 + a + b + O(a, b)^2
sage: log(exp(f)) - f
0 + O(a, b)^3
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, Integer(2), names=('a', 'b',)); (a, b,) = T._
↳first_ngens(2)
>>> f = a + b + a*b + T.O(Integer(3))
>>> exp(f)
1 + a + b + 1/2*a^2 + 2*a*b + 1/2*b^2 + O(a, b)^3
>>> f.exp()
1 + a + b + 1/2*a^2 + 2*a*b + 1/2*b^2 + O(a, b)^3
>>> f.exp(prec=Integer(2))
1 + a + b + O(a, b)^2
>>> log(exp(f)) - f
0 + O(a, b)^3
```

If the power series has a constant coefficient c and $\exp(c)$ is transcendental, then $\exp(f)$ would have to be a power series over the `SymbolicRing`. These are not yet implemented and therefore such cases raise an error:

```
sage: g = 2 + f
sage: exp(g) #_
↳needs sage.symbolic
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *: 'Symbolic Ring' and
'Power Series Ring in Tbg over Multivariate Polynomial Ring in a, b
over Rational Field'
```

```
>>> from sage.all import *
>>> g = Integer(2) + f
>>> exp(g) #_
↳needs sage.symbolic
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *: 'Symbolic Ring' and
'Power Series Ring in Tbg over Multivariate Polynomial Ring in a, b
over Rational Field'
```

Another workaround for this limitation is to change base ring to one which is closed under exponentiation, such as $\mathbf{R}$ or $\mathbf{C}$:

```
sage: exp(g.change_ring(RDF))
7.38905609... + 7.38905609...*a + 7.38905609...*b + 3.69452804...*a^2 +
14.7781121...*a*b + 3.69452804...*b^2 + O(a, b)^3
```

```
>>> from sage.all import *
>>> exp(g.change_ring(RDF))
```

(continues on next page)

(continued from previous page)

```
7.38905609... + 7.38905609...*a + 7.38905609...*b + 3.69452804...*a^2 +
14.7781121...*a*b + 3.69452804...*b^2 + O(a, b)^3
```

If no precision is specified, the default precision is used:

```
sage: T.default_prec()
12
sage: exp(a)
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + 1/120*a^5 + 1/720*a^6 + 1/5040*a^7 +
1/40320*a^8 + 1/362880*a^9 + 1/3628800*a^10 + 1/39916800*a^11 + O(a, b)^12
sage: a.exp(prec=5)
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + O(a, b)^5
sage: exp(a + T.O(5))
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + O(a, b)^5
```

```
>>> from sage.all import *
>>> T.default_prec()
12
>>> exp(a)
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + 1/120*a^5 + 1/720*a^6 + 1/5040*a^7 +
1/40320*a^8 + 1/362880*a^9 + 1/3628800*a^10 + 1/39916800*a^11 + O(a, b)^12
>>> a.exp(prec=Integer(5))
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + O(a, b)^5
>>> exp(a + T.O(Integer(5)))
1 + a + 1/2*a^2 + 1/6*a^3 + 1/24*a^4 + O(a, b)^5
```

exponents()

Return a list of tuples which hold the exponents of each monomial of `self`.

EXAMPLES:

```
sage: H = QQ[['x,y']]
sage: x, y = H.gens()
sage: h = -y^2 - x*y^3 - 6/5*y^6 - x^7 + 2*x^5*y^2 + H.O(10)
sage: h
-y^2 - x*y^3 - 6/5*y^6 - x^7 + 2*x^5*y^2 + O(x, y)^10
sage: h.exponents()
[(0, 2), (1, 3), (0, 6), (7, 0), (5, 2)]
```

```
>>> from sage.all import *
>>> H = QQ[['x,y']]
>>> x, y = H.gens()
>>> h = -y**Integer(2) - x*y**Integer(3) - Integer(6)/
↳Integer(5)*y**Integer(6) - x**Integer(7) +
↳Integer(2)*x**Integer(5)*y**Integer(2) + H.O(Integer(10))
>>> h
-y^2 - x*y^3 - 6/5*y^6 - x^7 + 2*x^5*y^2 + O(x, y)^10
>>> h.exponents()
[(0, 2), (1, 3), (0, 6), (7, 0), (5, 2)]
```

integral(*args)

The formal integral of this multivariate power series, with respect to variables supplied in `args`.

The variable sequence `args` can contain both variables and counts; for the syntax, see `derivative_parse()`.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(QQ, 2)
sage: f = a + b + a^2*b + T.O(5)
sage: f.integral(a, 2)
1/6*a^3 + 1/2*a^2*b + 1/12*a^4*b + O(a, b)^7
sage: f.integral(a, b)
1/2*a^2*b + 1/2*a*b^2 + 1/6*a^3*b^2 + O(a, b)^7
sage: f.integral(a, 5)
1/720*a^6 + 1/120*a^5*b + 1/2520*a^7*b + O(a, b)^10
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(QQ, Integer(2), names=('a', 'b',)); (a, b,) = T._
↳first_ngens(2)
>>> f = a + b + a**Integer(2)*b + T.O(Integer(5))
>>> f.integral(a, Integer(2))
1/6*a^3 + 1/2*a^2*b + 1/12*a^4*b + O(a, b)^7
>>> f.integral(a, b)
1/2*a^2*b + 1/2*a*b^2 + 1/6*a^3*b^2 + O(a, b)^7
>>> f.integral(a, Integer(5))
1/720*a^6 + 1/120*a^5*b + 1/2520*a^7*b + O(a, b)^10
```

Only integration with respect to variables works:

```
sage: f.integral(a + b)
Traceback (most recent call last):
...
ValueError: a + b is not a variable
```

```
>>> from sage.all import *
>>> f.integral(a + b)
Traceback (most recent call last):
...
ValueError: a + b is not a variable
```

Warning

Coefficient division.

If the base ring is not a field (e.g. $\mathbb{ZZ}$), or if it has a nonzero characteristic, (e.g. $\mathbb{ZZ}/3\mathbb{ZZ}$), integration is not always possible while staying with the same base ring. In the first case, Sage will report that it has not been able to coerce some coefficient to the base ring:

```
sage: T.<a,b> = PowerSeriesRing(ZZ, 2)
sage: f = a + T.O(5)
sage: f.integral(a)
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, Integer(2), names=('a', 'b',)); (a, b,) = T._
↳first_ngens(2)
>>> f = a + T.O(Integer(5))
>>> f.integral(a)
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

One can get the correct result by changing the base ring first:

```
sage: f.change_ring(QQ).integral(a)
1/2*a^2 + O(a, b)^6
```

```
>>> from sage.all import *
>>> f.change_ring(QQ).integral(a)
1/2*a^2 + O(a, b)^6
```

However, a correct result is returned even without base change if the denominator cancels:

```
sage: f = 2*b + T.O(5)
sage: f.integral(b)
b^2 + O(a, b)^6
```

```
>>> from sage.all import *
>>> f = Integer(2)*b + T.O(Integer(5))
>>> f.integral(b)
b^2 + O(a, b)^6
```

In nonzero characteristic, Sage will report that a zero division occurred

```
sage: T.<a,b> = PowerSeriesRing(Zmod(3), 2)
sage: (a^3).integral(a)
a^4
sage: (a^2).integral(a)
Traceback (most recent call last):
...
ZeroDivisionError: inverse of Mod(0, 3) does not exist
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(Zmod(Integer(3)), Integer(2), names=('a', 'b',));
↳(a, b,) = T._first_ngens(2)
>>> (a**Integer(3)).integral(a)
a^4
>>> (a**Integer(2)).integral(a)
Traceback (most recent call last):
...
ZeroDivisionError: inverse of Mod(0, 3) does not exist
```

is_nilpotent()

Return True if self is nilpotent. This occurs if

- self has finite precision and positive valuation, or
- self is constant and nilpotent in base ring.

Otherwise, return `False`.

Warning

This is so far just a sufficient condition, so don't trust a `False` output to be legit!

Todo

What should we do about this method? Is nilpotency of a power series even decidable (assuming a nilpotency oracle in the base ring)? And I am not sure that returning `True` just because the series has finite precision and zero constant term is a good idea.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(Zmod(8)); R
Multivariate Power Series Ring in a, b, c over Ring of integers modulo 8
sage: f = a + b + c + a^2*c
sage: f.is_nilpotent()
False
sage: f = f.O(4); f
a + b + c + a^2*c + O(a, b, c)^4
sage: f.is_nilpotent()
True

sage: g = R(2)
sage: g.is_nilpotent()
True
sage: (g.O(4)).is_nilpotent()
True

sage: S = R.change_ring(QQ)
sage: S(g).is_nilpotent()
False
sage: S(g.O(4)).is_nilpotent()
False
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(Zmod(Integer(8)), names=('a', 'b', 'c')); (a, b, c) = R._first_ngens(3); R
Multivariate Power Series Ring in a, b, c over Ring of integers modulo 8
>>> f = a + b + c + a**Integer(2)*c
>>> f.is_nilpotent()
False
>>> f = f.O(Integer(4)); f
a + b + c + a^2*c + O(a, b, c)^4
>>> f.is_nilpotent()
True

>>> g = R(Integer(2))
>>> g.is_nilpotent()
```

(continues on next page)

(continued from previous page)

```

True
>>> (g.O(Integer(4))).is_nilpotent()
True

>>> S = R.change_ring(QQ)
>>> S(g).is_nilpotent()
False
>>> S(g.O(Integer(4))).is_nilpotent()
False

```

is_square()

Method from univariate power series not yet implemented.

is_unit()

A multivariate power series is a unit if and only if its constant coefficient is a unit.

EXAMPLES:

```

sage: R.<a,b> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b over Integer Ring
sage: f = 2 + a^2 + a*b + a^3 + R.O(9)
sage: f.is_unit()
False
sage: f.base_extend(QQ).is_unit()
True
sage: (O(a,b)^0).is_unit()
False

```

```

>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('a', 'b')); (a, b,) = R._first_ngens(2); R
Multivariate Power Series Ring in a, b over Integer Ring
>>> f = Integer(2) + a**Integer(2) + a*b + a**Integer(3) + R.O(Integer(9))
>>> f.is_unit()
False
>>> f.base_extend(QQ).is_unit()
True
>>> (O(a,b)**Integer(0)).is_unit()
False

```

laurent_series()

Not implemented for multivariate power series.

list()

Doesn't make sense for multivariate power series. Multivariate polynomials don't have list of coefficients either.

log(prec=+Infinity)

Return the logarithm of the formal power series.

INPUT:

- `prec` – integer or infinity; the degree to truncate the result to

OUTPUT:

The logarithm of the multivariate power series as a new multivariate power series.

EXAMPLES:

```
sage: T.<a,b> = PowerSeriesRing(ZZ, 2)
sage: f = 1 + a + b + a*b + T.O(5)
sage: f.log()
a + b - 1/2*a^2 - 1/2*b^2 + 1/3*a^3 + 1/3*b^3 - 1/4*a^4 - 1/4*b^4 + O(a, b)^5
sage: log(f)
a + b - 1/2*a^2 - 1/2*b^2 + 1/3*a^3 + 1/3*b^3 - 1/4*a^4 - 1/4*b^4 + O(a, b)^5
sage: exp(log(f)) - f
0 + O(a, b)^5
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(ZZ, Integer(2), names=('a', 'b',)); (a, b,) = T._
↳first_ngens(2)
>>> f = Integer(1) + a + b + a*b + T.O(Integer(5))
>>> f.log()
a + b - 1/2*a^2 - 1/2*b^2 + 1/3*a^3 + 1/3*b^3 - 1/4*a^4 - 1/4*b^4 + O(a, b)^5
>>> log(f)
a + b - 1/2*a^2 - 1/2*b^2 + 1/3*a^3 + 1/3*b^3 - 1/4*a^4 - 1/4*b^4 + O(a, b)^5
>>> exp(log(f)) - f
0 + O(a, b)^5
```

If the power series has a constant coefficient c and $\exp(c)$ is transcendental, then $\exp(f)$ would have to be a power series over the `SymbolicRing`. These are not yet implemented and therefore such cases raise an error:

```
sage: g = 2 + f
sage: log(g) #_
↳needs sage.symbolic
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for -: 'Symbolic Ring' and 'Power
Series Ring in Tbg over Multivariate Polynomial Ring in a, b over Rational_
↳Field'
```

```
>>> from sage.all import *
>>> g = Integer(2) + f
>>> log(g) #_
↳needs sage.symbolic
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for -: 'Symbolic Ring' and 'Power
Series Ring in Tbg over Multivariate Polynomial Ring in a, b over Rational_
↳Field'
```

Another workaround for this limitation is to change base ring to one which is closed under exponentiation, such as **R** or **C**:

```
sage: log(g.change_ring(RDF))
1.09861228... + 0.333333333...*a + 0.333333333...*b - 0.055555555...*a^2
+ 0.222222222...*a*b - 0.055555555...*b^2 + 0.0123456790...*a^3
- 0.0740740740...*a^2*b - 0.0740740740...*a*b^2 + 0.0123456790...*b^3
- 0.00308641975...*a^4 + 0.0246913580...*a^3*b + 0.0246913580...*a*b^3
- 0.00308641975...*b^4 + O(a, b)^5
```

```
>>> from sage.all import *
>>> log(g.change_ring(RDF))
1.09861228... + 0.333333333...*a + 0.333333333...*b - 0.055555555...*a^2
+ 0.222222222...*a*b - 0.055555555...*b^2 + 0.0123456790...*a^3
- 0.0740740740...*a^2*b - 0.0740740740...*a*b^2 + 0.0123456790...*b^3
- 0.00308641975...*a^4 + 0.0246913580...*a^3*b + 0.0246913580...*a*b^3
- 0.00308641975...*b^4 + O(a, b)^5
```

monomial_coefficients (*copy=None*)

Return underlying dictionary with keys the exponents and values the coefficients of this power series.

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ, 4, 't', sparse=True); M
Sparse Multivariate Power Series Ring in t0, t1, t2, t3 over
Rational Field

sage: M.inject_variables()
Defining t0, t1, t2, t3

sage: m = 2/3*t0*t1^15*t3^48 - t0^15*t1^21*t2^28*t3^5
sage: m2 = 1/2*t0^12*t1^29*t2^46*t3^6 - 1/4*t0^39*t1^5*t2^23*t3^30 + M.O(100)
sage: s = m + m2
sage: s.monomial_coefficients()
{(1, 15, 0, 48): 2/3,
 (12, 29, 46, 6): 1/2,
 (15, 21, 28, 5): -1,
 (39, 5, 23, 30): -1/4}
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 't', sparse=True); M
Sparse Multivariate Power Series Ring in t0, t1, t2, t3 over
Rational Field

>>> M.inject_variables()
Defining t0, t1, t2, t3

>>> m = Integer(2)/Integer(3)*t0*t1**Integer(15)*t3**Integer(48) -
↳ t0**Integer(15)*t1**Integer(21)*t2**Integer(28)*t3**Integer(5)
>>> m2 = Integer(1)/
↳ Integer(2)*t0**Integer(12)*t1**Integer(29)*t2**Integer(46)*t3**Integer(6) -
↳ Integer(1)/
↳ Integer(4)*t0**Integer(39)*t1**Integer(5)*t2**Integer(23)*t3**Integer(30) +
↳ M.O(Integer(100))
>>> s = m + m2
>>> s.monomial_coefficients()
{(1, 15, 0, 48): 2/3,
 (12, 29, 46, 6): 1/2,
 (15, 21, 28, 5): -1,
 (39, 5, 23, 30): -1/4}
```

dict is an alias:

```
sage: s.dict()
{(1, 15, 0, 48): 2/3,
 (12, 29, 46, 6): 1/2,
 (15, 21, 28, 5): -1,
 (39, 5, 23, 30): -1/4}
```

```
>>> from sage.all import *
>>> s.dict()
{(1, 15, 0, 48): 2/3,
 (12, 29, 46, 6): 1/2,
 (15, 21, 28, 5): -1,
 (39, 5, 23, 30): -1/4}
```

monomials()

Return a list of monomials of `self`.

These are the keys of the dict returned by `coefficients()`.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b, c over Integer Ring
sage: f = 1 + a + b - a*b - b*c - a*c + R.O(4)
sage: sorted(f.monomials())
[b*c, a*c, a*b, b, a, 1]
sage: f = 1 + 2*a + 7*b - 2*a*b - 4*b*c - 13*a*c + R.O(4)
sage: sorted(f.monomials())
[b*c, a*c, a*b, b, a, 1]
sage: f = R.zero()
sage: f.monomials()
[]
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('a', 'b', 'c')); (a, b, c) = R._first_
↳ngens(3); R
Multivariate Power Series Ring in a, b, c over Integer Ring
>>> f = Integer(1) + a + b - a*b - b*c - a*c + R.O(Integer(4))
>>> sorted(f.monomials())
[b*c, a*c, a*b, b, a, 1]
>>> f = Integer(1) + Integer(2)*a + Integer(7)*b - Integer(2)*a*b -
↳Integer(4)*b*c - Integer(13)*a*c + R.O(Integer(4))
>>> sorted(f.monomials())
[b*c, a*c, a*b, b, a, 1]
>>> f = R.zero()
>>> f.monomials()
[]
```

ogf()

Method from univariate power series not yet implemented.

padded_list()

Method from univariate power series not yet implemented.

polynomial()

Return the underlying polynomial of `self` as an element of the underlying multivariate polynomial ring (the “foreground polynomial ring”).

EXAMPLES:

```
sage: M = PowerSeriesRing(QQ, 4, 't'); M
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational
Field
sage: t = M.gens()
sage: f = 1/2*t[0]^3*t[1]^3*t[2]^2 + 2/3*t[0]*t[2]^6*t[3]
      ↪ t[0]^3*t[1]^3*t[3]^3 - 1/4*t[0]*t[1]*t[2]^7 + M.O(10)
sage: f
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7 + O(t0, t1, t2, t3)^10

sage: f.polynomial()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7

sage: f.polynomial().parent()
Multivariate Polynomial Ring in t0, t1, t2, t3 over Rational Field
```

```
>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 't'); M
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational
Field
>>> t = M.gens()
>>> f = Integer(1)/Integer(2)*t[Integer(0)]**Integer(3)*t[Integer(1)]**Integer
      ↪ (3)*t[Integer(2)]**Integer(2) + Integer(2)/Integer(3)*t[Integer(0)]*t[Intege
      ↪ r(2)]**Integer(6)*t[Integer(3)]
      Ellipsis.: - t[Integer(0)]**Inte
      ↪ ger(3)*t[Integer(1)]**Integer(3)*t[Integer(3)]**Integer(3) - Integer(1)/Inte
      ↪ ger(4)*t[Integer(0)]*t[Integer(1)]*t[Integer(2)]**Integer(7) + M.O(Integer(1
      ↪ 0))
>>> f
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7 + O(t0, t1, t2, t3)^10

>>> f.polynomial()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7

>>> f.polynomial().parent()
Multivariate Polynomial Ring in t0, t1, t2, t3 over Rational Field
```

Contrast with `truncate()`:

```
sage: f.truncate()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3 - 1/4*t0*t1*t2^7
sage: f.truncate().parent()
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field
```

```
>>> from sage.all import *
```

(continues on next page)

(continued from previous page)

```
>>> f.truncate()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3 - 1/4*t0*t1*t2^7
>>> f.truncate().parent()
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field
```

prec()Return precision of `self`.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(ZZ); R
Multivariate Power Series Ring in a, b, c over Integer Ring
sage: f = 3 + a + b - a*b - b*c - a*c + R.O(4)
sage: f.prec()
4
sage: f.truncate().prec()
+Infinity
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('a', 'b', 'c')); (a, b, c) = R._first_
↳ngens(3); R
Multivariate Power Series Ring in a, b, c over Integer Ring
>>> f = Integer(3) + a + b - a*b - b*c - a*c + R.O(Integer(4))
>>> f.prec()
4
>>> f.truncate().prec()
+Infinity
```

quo_rem(*other*, *precision=None*)Return the pair of quotient and remainder for the increasing power division of `self` by `other`.

If a and b are two elements of a power series ring $R[[x_1, x_2, \dots, x_n]]$ such that the trailing term of b is invertible in R , then the pair of quotient and remainder for the increasing power division of a by b is the unique pair $(u, v) \in R[[x_1, x_2, \dots, x_n]] \times R[[x_1, x_2, \dots, x_n]]$ such that $a = bu + v$ and such that no monomial appearing in v divides the trailing monomial (`trailing_monomial()`) of b . Note that this depends on the order of the variables.

This method returns both quotient and remainder as power series, even though in mathematics, the remainder for the increasing power division of two power series is a polynomial. This is because Sage's power series come with a precision, and that precision is not always sufficient to determine the remainder completely. Disregarding this issue, the `polynomial()` method can be used to recast the remainder as an actual polynomial.

INPUT:

- `other` – an element of the same power series ring as `self` such that the trailing term of `other` is invertible in `self` (this is automatically satisfied if the base ring is a field, unless `other` is zero)
- `precision` – (default: the default precision of the parent of `self`) nonnegative integer, determining the precision to be cast on the resulting quotient and remainder if both `self` and `other` have infinite precision (ignored otherwise); note that the resulting precision might be lower than this integer

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<a,b,c> = PowerSeriesRing(ZZ)
```

(continues on next page)

(continued from previous page)

```

sage: f = 1 + a + b - a*b + R.O(3)
sage: g = 1 + 2*a - 3*a*b + R.O(3)
sage: q, r = f.quo_rem(g); q, r
(1 - a + b + 2*a^2 + O(a, b, c)^3, 0 + O(a, b, c)^3)
sage: f == q*g + r
True
sage: q, r = (a*f).quo_rem(g); q, r
(a - a^2 + a*b + 2*a^3 + O(a, b, c)^4, 0 + O(a, b, c)^4)
sage: a*f == q*g + r
True
sage: q, r = (a*f).quo_rem(a*g); q, r
(1 - a + b + 2*a^2 + O(a, b, c)^3, 0 + O(a, b, c)^4)
sage: a*f == q*(a*g) + r
True
sage: q, r = (a*f).quo_rem(b*g); q, r
(a - 3*a^2 + O(a, b, c)^3, a + a^2 + O(a, b, c)^4)
sage: a*f == q*(b*g) + r
True

```

```

>>> from sage.all import *
>>> # needs sage.libs.singular
>>> R = PowerSeriesRing(ZZ, names=('a', 'b', 'c',)); (a, b, c,) = R._first_
↳ngens(3)
>>> f = Integer(1) + a + b - a*b + R.O(Integer(3))
>>> g = Integer(1) + Integer(2)*a - Integer(3)*a*b + R.O(Integer(3))
>>> q, r = f.quo_rem(g); q, r
(1 - a + b + 2*a^2 + O(a, b, c)^3, 0 + O(a, b, c)^3)
>>> f == q*g + r
True
>>> q, r = (a*f).quo_rem(g); q, r
(a - a^2 + a*b + 2*a^3 + O(a, b, c)^4, 0 + O(a, b, c)^4)
>>> a*f == q*g + r
True
>>> q, r = (a*f).quo_rem(a*g); q, r
(1 - a + b + 2*a^2 + O(a, b, c)^3, 0 + O(a, b, c)^4)
>>> a*f == q*(a*g) + r
True
>>> q, r = (a*f).quo_rem(b*g); q, r
(a - 3*a^2 + O(a, b, c)^3, a + a^2 + O(a, b, c)^4)
>>> a*f == q*(b*g) + r
True

```

Trying to divide two polynomials, we run into the issue that there is no natural setting for the precision of the quotient and remainder (and if we wouldn't set a precision, the algorithm would never terminate). Here, default precision comes to our help:

```

sage: # needs sage.libs.singular
sage: (1 + a^3).quo_rem(a + a^2)
(a^2 - a^3 + a^4 - a^5 + a^6 - a^7 + a^8 - a^9 + a^10 + O(a, b, c)^11,
 1 + O(a, b, c)^12)
sage: (1 + a^3 + a*b).quo_rem(b + c)
(a + O(a, b, c)^11, 1 - a*c + a^3 + O(a, b, c)^12)

```

(continues on next page)

(continued from previous page)

```

sage: (1 + a^3 + a*b).quo_rem(b + c, precision=17)
(a + O(a, b, c)^16, 1 - a*c + a^3 + O(a, b, c)^17)
sage: (a^2 + b^2 + c^2).quo_rem(a + b + c)
(a - b - c + O(a, b, c)^11, 2*b^2 + 2*b*c + 2*c^2 + O(a, b, c)^12)
sage: (a^2 + b^2 + c^2).quo_rem(1/(1+a+b+c))
(a^2 + b^2 + c^2 + a^3 + a^2*b + a^2*c + a*b^2 + a*c^2
+ b^3 + b^2*c + b*c^2 + c^3 + O(a, b, c)^14,
0)
sage: (a^2 + b^2 + c^2).quo_rem(a/(1+a+b+c))
(a + a^2 + a*b + a*c + O(a, b, c)^13, b^2 + c^2)
sage: (1 + a + a^15).quo_rem(a^2)
(0 + O(a, b, c)^10, 1 + a + O(a, b, c)^12)
sage: (1 + a + a^15).quo_rem(a^2, precision=15)
(0 + O(a, b, c)^13, 1 + a + O(a, b, c)^15)
sage: (1 + a + a^15).quo_rem(a^2, precision=16)
(a^13 + O(a, b, c)^14, 1 + a + O(a, b, c)^16)

```

```

>>> from sage.all import *
>>> # needs sage.libs.singular
>>> (Integer(1) + a**Integer(3)).quo_rem(a + a**Integer(2))
(a^2 - a^3 + a^4 - a^5 + a^6 - a^7 + a^8 - a^9 + a^10 + O(a, b, c)^11,
1 + O(a, b, c)^12)
>>> (Integer(1) + a**Integer(3) + a*b).quo_rem(b + c)
(a + O(a, b, c)^11, 1 - a*c + a^3 + O(a, b, c)^12)
>>> (Integer(1) + a**Integer(3) + a*b).quo_rem(b + c, precision=Integer(17))
(a + O(a, b, c)^16, 1 - a*c + a^3 + O(a, b, c)^17)
>>> (a**Integer(2) + b**Integer(2) + c**Integer(2)).quo_rem(a + b + c)
(a - b - c + O(a, b, c)^11, 2*b^2 + 2*b*c + 2*c^2 + O(a, b, c)^12)
>>> (a**Integer(2) + b**Integer(2) + c**Integer(2)).quo_rem(Integer(1)/
↪ (Integer(1)+a+b+c))
(a^2 + b^2 + c^2 + a^3 + a^2*b + a^2*c + a*b^2 + a*c^2
+ b^3 + b^2*c + b*c^2 + c^3 + O(a, b, c)^14,
0)
>>> (a**Integer(2) + b**Integer(2) + c**Integer(2)).quo_rem(a/
↪ (Integer(1)+a+b+c))
(a + a^2 + a*b + a*c + O(a, b, c)^13, b^2 + c^2)
>>> (Integer(1) + a + a**Integer(15)).quo_rem(a**Integer(2))
(0 + O(a, b, c)^10, 1 + a + O(a, b, c)^12)
>>> (Integer(1) + a + a**Integer(15)).quo_rem(a**Integer(2), ↵
↪ precision=Integer(15))
(0 + O(a, b, c)^13, 1 + a + O(a, b, c)^15)
>>> (Integer(1) + a + a**Integer(15)).quo_rem(a**Integer(2), ↵
↪ precision=Integer(16))
(a^13 + O(a, b, c)^14, 1 + a + O(a, b, c)^16)

```

Illustrating the dependency on the ordering of variables:

```

sage: # needs sage.libs.singular
sage: (1 + a + b).quo_rem(b + c)
(1 + O(a, b, c)^11, 1 + a - c + O(a, b, c)^12)
sage: (1 + b + c).quo_rem(c + a)
(0 + O(a, b, c)^11, 1 + b + c + O(a, b, c)^12)

```

(continues on next page)

(continued from previous page)

```
sage: (1 + c + a).quo_rem(a + b)
(1 + O(a, b, c)^11, 1 - b + c + O(a, b, c)^12)
```

```
>>> from sage.all import *
>>> # needs sage.libs.singular
>>> (Integer(1) + a + b).quo_rem(b + c)
(1 + O(a, b, c)^11, 1 + a - c + O(a, b, c)^12)
>>> (Integer(1) + b + c).quo_rem(c + a)
(0 + O(a, b, c)^11, 1 + b + c + O(a, b, c)^12)
>>> (Integer(1) + c + a).quo_rem(a + b)
(1 + O(a, b, c)^11, 1 - b + c + O(a, b, c)^12)
```

shift (*n*)

Doesn't make sense for multivariate power series.

solve_linear_de (*prec=+Infinity, b=None, f0=None*)

Not implemented for multivariate power series.

sqrt ()alias of `square_root()`.**square_root** ()

Method from univariate power series not yet implemented. Depends on square root method for multivariate polynomials.

trailing_monomial ()Return the trailing monomial of `self`.

This is defined here as the lowest term of the underlying polynomial.

EXAMPLES:

```
sage: R.<a,b,c> = PowerSeriesRing(ZZ)
sage: f = 1 + a + b - a*b + R.O(3)
sage: f.trailing_monomial()
1
sage: f = a^2*b^3*f; f
a^2*b^3 + a^3*b^3 + a^2*b^4 - a^3*b^4 + O(a, b, c)^8
sage: f.trailing_monomial()
a^2*b^3
```

```
>>> from sage.all import *
>>> R = PowerSeriesRing(ZZ, names=('a', 'b', 'c')); (a, b, c,) = R._first_
↳ngens(3)
>>> f = Integer(1) + a + b - a*b + R.O(Integer(3))
>>> f.trailing_monomial()
1
>>> f = a**Integer(2)*b**Integer(3)*f; f
a^2*b^3 + a^3*b^3 + a^2*b^4 - a^3*b^4 + O(a, b, c)^8
>>> f.trailing_monomial()
a^2*b^3
```

truncate (*prec=+Infinity*)Return infinite precision multivariate power series formed by truncating `self` at precision `prec`.

EXAMPLES:

```

sage: M = PowerSeriesRing(QQ, 4, 't'); M
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field
sage: t = M.gens()
sage: f = 1/2*t[0]^3*t[1]^3*t[2]^2 + 2/3*t[0]*t[2]^6*t[3]
      ↪ t[0]^3*t[1]^3*t[3]^3 - 1/4*t[0]*t[1]*t[2]^7 + M.O(10)
sage: f
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7 + O(t0, t1, t2, t3)^10

sage: f.truncate()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7
sage: f.truncate().parent()
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field

```

```

>>> from sage.all import *
>>> M = PowerSeriesRing(QQ, Integer(4), 't'); M
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field
>>> t = M.gens()
>>> f = Integer(1)/Integer(2)*t[Integer(0)]**Integer(3)*t[Integer(1)]**Integer
      ↪ (3)*t[Integer(2)]**Integer(2) + Integer(2)/Integer(3)*t[Integer(0)]*t[Intege
      ↪ r(2)]**Integer(6)*t[Integer(3)]
      Ellipsis.: - t[Integer(0)]**Inte
      ↪ ger(3)*t[Integer(1)]**Integer(3)*t[Integer(3)]**Integer(3) - Integer(1)/Inte
      ↪ ger(4)*t[Integer(0)]*t[Integer(1)]*t[Integer(2)]**Integer(7) + M.O(Integer(1
      ↪ 0))
>>> f
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7 + O(t0, t1, t2, t3)^10

>>> f.truncate()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3
- 1/4*t0*t1*t2^7
>>> f.truncate().parent()
Multivariate Power Series Ring in t0, t1, t2, t3 over Rational Field

```

Contrast with polynomial:

```

sage: f.polynomial()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3 - 1/4*t0*t1*t2^7
sage: f.polynomial().parent()
Multivariate Polynomial Ring in t0, t1, t2, t3 over Rational Field

```

```

>>> from sage.all import *
>>> f.polynomial()
1/2*t0^3*t1^3*t2^2 + 2/3*t0*t2^6*t3 - t0^3*t1^3*t3^3 - 1/4*t0*t1*t2^7
>>> f.polynomial().parent()
Multivariate Polynomial Ring in t0, t1, t2, t3 over Rational Field

```

valuation()

Return the valuation of self.

The valuation of a power series f is the highest nonnegative integer k less or equal to the precision of f and

such that the coefficient of f before each term of degree $< k$ is zero. (If such an integer does not exist, then the valuation is the precision of f itself.)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: R.<a,b> = PowerSeriesRing(GF(4949717)); R
Multivariate Power Series Ring in a, b
over Finite Field of size 4949717
sage: f = a^2 + a*b + a^3 + R.O(9)
sage: f.valuation()
2
sage: g = 1 + a + a^3
sage: g.valuation()
0
sage: R.zero().valuation()
+Infinity
```

```
>>> from sage.all import *
>>> # needs sage.rings.finite_rings
>>> R = PowerSeriesRing(GF(Integer(4949717)), names=('a', 'b')); (a, b,) = R.
↳_first_ngens(2); R
Multivariate Power Series Ring in a, b
over Finite Field of size 4949717
>>> f = a**Integer(2) + a*b + a**Integer(3) + R.O(Integer(9))
>>> f.valuation()
2
>>> g = Integer(1) + a + a**Integer(3)
>>> g.valuation()
0
>>> R.zero().valuation()
+Infinity
```

valuation_zero_part()

Doesn't make sense for multivariate power series; valuation zero with respect to which variable?

variable()

Doesn't make sense for multivariate power series.

variables()

Return tuple of variables occurring in self.

EXAMPLES:

```
sage: T = PowerSeriesRing(GF(3), 5, 't'); T
Multivariate Power Series Ring in t0, t1, t2, t3, t4 over
Finite Field of size 3
sage: t = T.gens()
sage: w = t[0] - 2*t[0]*t[2] + 5*t[4]^3 - t[0]^3*t[2]^2 + T.O(6)
sage: w
t0 + t0*t2 - t4^3 - t0^3*t2^2 + O(t0, t1, t2, t3, t4)^6
sage: w.variables()
(t0, t2, t4)
```

```
>>> from sage.all import *
>>> T = PowerSeriesRing(GF(Integer(3)), Integer(5), 't'); T
Multivariate Power Series Ring in t0, t1, t2, t3, t4 over
Finite Field of size 3
>>> t = T.gens()
>>> w = t[Integer(0)] - Integer(2)*t[Integer(0)]*t[Integer(2)] +
↳ Integer(5)*t[Integer(4)]**Integer(3) -
↳ t[Integer(0)]**Integer(3)*t[Integer(2)]**Integer(2) + T.O(Integer(6))
>>> w
t0 + t0*t2 - t4^3 - t0^3*t2^2 + O(t0, t1, t2, t3, t4)^6
>>> w.variables()
(t0, t2, t4)
```

`sage.rings.multi_power_series_ring_element.is_MPowerSeries(f)`

Return True if `f` is a multivariate power series.

LAURENT SERIES RINGS

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.base_ring()
Rational Field
sage: S = LaurentSeriesRing(GF(17)['x'], 'y')
sage: S
Laurent Series Ring in y over
  Univariate Polynomial Ring in x over Finite Field of size 17
sage: S.base_ring()
Univariate Polynomial Ring in x over Finite Field of size 17
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.base_ring()
Rational Field
>>> S = LaurentSeriesRing(GF(Integer(17))['x'], 'y')
>>> S
Laurent Series Ring in y over
  Univariate Polynomial Ring in x over Finite Field of size 17
>>> S.base_ring()
Univariate Polynomial Ring in x over Finite Field of size 17
```

See also

- `sage.misc.defaults.set_series_precision()`

class `sage.rings.laurent_series_ring.LaurentSeriesRing` (*power_series*)

Bases: `UniqueRepresentation`, `Parent`

Univariate Laurent Series Ring.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, 'x'); R
Laurent Series Ring in x over Rational Field
sage: x = R.0
sage: g = 1 - x + x^2 - x^4 + O(x^8); g
1 - x + x^2 - x^4 + O(x^8)
```

(continues on next page)

(continued from previous page)

```
sage: g = 10*x^(-3) + 2006 - 19*x + x^2 - x^4 + O(x^8); g
10*x^-3 + 2006 - 19*x + x^2 - x^4 + O(x^8)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, 'x'); R
Laurent Series Ring in x over Rational Field
>>> x = R.gen(0)
>>> g = Integer(1) - x + x**Integer(2) - x**Integer(4) + O(x**Integer(8)); g
1 - x + x^2 - x^4 + O(x^8)
>>> g = Integer(10)*x**(-Integer(3)) + Integer(2006) - Integer(19)*x +
↳ x**Integer(2) - x**Integer(4) + O(x**Integer(8)); g
10*x^-3 + 2006 - 19*x + x^2 - x^4 + O(x^8)
```

You can also use more mathematical notation when the base is a field:

```
sage: Frac(QQ[['x']])
Laurent Series Ring in x over Rational Field
sage: Frac(GF(5)['y'])
Fraction Field of Univariate Polynomial Ring in y over Finite Field of size 5
```

```
>>> from sage.all import *
>>> Frac(QQ[['x']])
Laurent Series Ring in x over Rational Field
>>> Frac(GF(Integer(5))['y'])
Fraction Field of Univariate Polynomial Ring in y over Finite Field of size 5
```

When the base ring is a domain, the fraction field is the Laurent series ring over the fraction field of the base ring:

```
sage: Frac(ZZ[['t']])
Laurent Series Ring in t over Rational Field
```

```
>>> from sage.all import *
>>> Frac(ZZ[['t']])
Laurent Series Ring in t over Rational Field
```

Laurent series rings are determined by their variable and the base ring, and are globally unique:

```
sage: # needs sage.rings.padics
sage: K = Qp(5, prec=5)
sage: L = Qp(5, prec=200)
sage: R.<x> = LaurentSeriesRing(K)
sage: S.<y> = LaurentSeriesRing(L)
sage: R is S
False
sage: T.<y> = LaurentSeriesRing(Qp(5, prec=200))
sage: S is T
True
sage: W.<y> = LaurentSeriesRing(Qp(5, prec=199))
sage: W is T
False

sage: K = LaurentSeriesRing(CC, 'q'); K
```

(continues on next page)

(continued from previous page)

```

↪needs sage.rings.real_mpfr
Laurent Series Ring in q over Complex Field with 53 bits of precision
sage: loads(K.dumps()) == K                                     #_
↪needs sage.rings.real_mpfr
True
sage: P = QQ[['x']]
sage: F = Frac(P)
sage: TestSuite(F).run()

```

```

>>> from sage.all import *
>>> # needs sage.rings.padics
>>> K = Qp(Integer(5), prec=Integer(5))
>>> L = Qp(Integer(5), prec=Integer(200))
>>> R = LaurentSeriesRing(K, names=('x',)); (x,) = R._first_ngens(1)
>>> S = LaurentSeriesRing(L, names=('y',)); (y,) = S._first_ngens(1)
>>> R is S
False
>>> T = LaurentSeriesRing(Qp(Integer(5), prec=Integer(200)), names=('y',)); (y,) = T._first_ngens(1)
>>> S is T
True
>>> W = LaurentSeriesRing(Qp(Integer(5), prec=Integer(199)), names=('y',)); (y,) = W._first_ngens(1)
>>> W is T
False

>>> K = LaurentSeriesRing(CC, 'q'); K                             #_
↪needs sage.rings.real_mpfr
Laurent Series Ring in q over Complex Field with 53 bits of precision
>>> loads(K.dumps()) == K                                     #_
↪needs sage.rings.real_mpfr
True
>>> P = QQ[['x']]
>>> F = Frac(P)
>>> TestSuite(F).run()

```

When the base ring k is a field, the ring $k((x))$ is a CDVF, that is a field equipped with a discrete valuation for which it is complete. The appropriate (sub)category is automatically set in this case:

```

sage: k = GF(11)
sage: R.<x> = k[[x]]
sage: F = Frac(R)
sage: F.category()
Join of
  Category of complete discrete valuation fields and
  Category of commutative algebras over (finite enumerated fields and
  subquotients of monoids and quotients of semigroups) and
  Category of infinite sets
sage: TestSuite(F).run()

```

```

>>> from sage.all import *
>>> k = GF(Integer(11))

```

(continues on next page)

(continued from previous page)

```

>>> R = k[['x']]; (x,) = R._first_ngens(1)
>>> F = Frac(R)
>>> F.category()
Join of
Category of complete discrete valuation fields and
Category of commutative algebras over (finite enumerated fields and
subquotients of monoids and quotients of semigroups) and
Category of infinite sets
>>> TestSuite(F).run()

```

Elementalias of *LaurentSeries***base_extend(R)**

Return the Laurent series ring over R in the same variable as `self`, assuming there is a canonical coerce map from the base ring of `self` to R.

EXAMPLES:

```

sage: K.<x> = LaurentSeriesRing(QQ, default_prec=4)
sage: K.base_extend(QQ['t'])
Laurent Series Ring in x over Univariate Polynomial Ring in t over Rational_
↪Field

```

```

>>> from sage.all import *
>>> K = LaurentSeriesRing(QQ, default_prec=Integer(4), names=('x',)); (x,) = _
↪K._first_ngens(1)
>>> K.base_extend(QQ['t'])
Laurent Series Ring in x over Univariate Polynomial Ring in t over Rational_
↪Field

```

change_ring(R)

EXAMPLES:

```

sage: K.<x> = LaurentSeriesRing(QQ, default_prec=4)
sage: R = K.change_ring(ZZ); R
Laurent Series Ring in x over Integer Ring
sage: R.default_prec()
4

```

```

>>> from sage.all import *
>>> K = LaurentSeriesRing(QQ, default_prec=Integer(4), names=('x',)); (x,) = _
↪K._first_ngens(1)
>>> R = K.change_ring(ZZ); R
Laurent Series Ring in x over Integer Ring
>>> R.default_prec()
4

```

characteristic()

EXAMPLES:


```
sage: R.<x> = LaurentSeriesRing(GF(17))
sage: R.characteristic()
17
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(GF(Integer(17)), names=('x',)); (x,) = R._first_
↳ngens(1)
>>> R.characteristic()
17
```

construction()

Return the functorial construction of this Laurent power series ring.

The construction is given as the completion of the Laurent polynomials.

EXAMPLES:

```
sage: L.<t> = LaurentSeriesRing(ZZ, default_prec=42)
sage: phi, arg = L.construction()
sage: phi
Completion[t, prec=42]
sage: arg
Univariate Laurent Polynomial Ring in t over Integer Ring
sage: phi(arg) is L
True
```

```
>>> from sage.all import *
>>> L = LaurentSeriesRing(ZZ, default_prec=Integer(42), names=('t',)); (t,) = L
↳L._first_ngens(1)
>>> phi, arg = L.construction()
>>> phi
Completion[t, prec=42]
>>> arg
Univariate Laurent Polynomial Ring in t over Integer Ring
>>> phi(arg) is L
True
```

Because of this construction, pushout is automatically available:

```
sage: 1/2 * t
1/2*t
sage: parent(1/2 * t)
Laurent Series Ring in t over Rational Field

sage: QQbar.gen() * t                                     #_
↳needs sage.rings.number_field
I*t
sage: parent(QQbar.gen() * t)                             #_
↳needs sage.rings.number_field
Laurent Series Ring in t over Algebraic Field
```

```
>>> from sage.all import *
>>> Integer(1)/Integer(2) * t
```

(continues on next page)

(continued from previous page)

```

1/2*t
>>> parent(Integer(1)/Integer(2) * t)
Laurent Series Ring in t over Rational Field

>>> QQbar.gen() * t                                     #_
↪needs sage.rings.number_field
I*t
>>> parent(QQbar.gen() * t)                             #_
↪needs sage.rings.number_field
Laurent Series Ring in t over Algebraic Field

```

default_prec()

Get the precision to which exact elements are truncated when necessary (most frequently when inverting).

EXAMPLES:

```

sage: R.<x> = LaurentSeriesRing(QQ, default_prec=5)
sage: R.default_prec()
5

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, default_prec=Integer(5), names=('x',)); (x,) =_
↪R._first_ngens(1)
>>> R.default_prec()
5

```

fraction_field()

Return the fraction field of this ring of Laurent series.

If the base ring is a field, then Laurent series are already a field. If the base ring is a domain, then the Laurent series over its fraction field is returned. Otherwise, raise a `ValueError`.

EXAMPLES:

```

sage: R = LaurentSeriesRing(ZZ, 't', 30).fraction_field()
sage: R
Laurent Series Ring in t over Rational Field
sage: R.default_prec()
30

```

```

sage: LaurentSeriesRing(Zmod(4), 't').fraction_field()
Traceback (most recent call last):
...
ValueError: must be an integral domain

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(ZZ, 't', Integer(30)).fraction_field()
>>> R
Laurent Series Ring in t over Rational Field
>>> R.default_prec()
30

>>> LaurentSeriesRing(Zmod(Integer(4)), 't').fraction_field()

```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
ValueError: must be an integral domain
```

gen($n=0$)

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.gen()
x
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.gen()
x
```

gens()

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.gens()
(x,)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.gens()
(x,)
```

is_dense()

EXAMPLES:

```
sage: K.<x> = LaurentSeriesRing(QQ, sparse=True)
sage: K.is_dense()
False
```

```
>>> from sage.all import *
>>> K = LaurentSeriesRing(QQ, sparse=True, names=('x',)); (x,) = K._first_
↳ngens(1)
>>> K.is_dense()
False
```

is_exact()

Laurent series rings are inexact.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.is_exact()
False
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.is_exact()
False
```

is_field(*proof=True*)

A Laurent series ring is a field if and only if the base ring is a field.

is_sparse()

Return if *self* is a sparse implementation.

EXAMPLES:

```
sage: K.<x> = LaurentSeriesRing(QQ, sparse=True)
sage: K.is_sparse()
True
```

```
>>> from sage.all import *
>>> K = LaurentSeriesRing(QQ, sparse=True, names=('x',)); (x,) = K._first_
↳ngens(1)
>>> K.is_sparse()
True
```

laurent_polynomial_ring()

If this is the Laurent series ring $R((t))$, return the Laurent polynomial ring $R[t, 1/t]$.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.laurent_polynomial_ring()
Univariate Laurent Polynomial Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.laurent_polynomial_ring()
Univariate Laurent Polynomial Ring in x over Rational Field
```

ngens()

Laurent series rings are univariate.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.ngens()
1
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.ngens()
1
```

polynomial_ring()

If this is the Laurent series ring $R((t))$, return the polynomial ring $R[t]$.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.polynomial_ring()
Univariate Polynomial Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.polynomial_ring()
Univariate Polynomial Ring in x over Rational Field
```

power_series_ring()

If this is the Laurent series ring $R((t))$, return the power series ring $R[[t]]$.

EXAMPLES:

```
sage: R = LaurentSeriesRing(QQ, "x")
sage: R.power_series_ring()
Power Series Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, "x")
>>> R.power_series_ring()
Power Series Ring in x over Rational Field
```

random_element (algorithm='default')

Return a random element of this Laurent series ring.

The optional `algorithm` parameter decides how elements are generated. Algorithms currently implemented:

- 'default': Choose an integer shift using the standard distribution on the integers. Then choose a list of coefficients using the `random_element` function of the base ring, and construct a new element based on those coefficients, so that the i -th coefficient corresponds to the $(i+\text{shift})$ -th power of the uniformizer. The amount of coefficients is determined by the `default_prec` of the ring. Note that this method only creates non-exact elements.

EXAMPLES:

```
sage: S.<s> = LaurentSeriesRing(GF(3))
sage: S.random_element() # random
s^-8 + s^-7 + s^-6 + s^-5 + s^-1 + s + s^3 + s^4
+ s^5 + 2*s^6 + s^7 + s^11 + O(s^12)
```

```
>>> from sage.all import *
>>> S = LaurentSeriesRing(GF(Integer(3)), names=('s',)); (s,) = S._first_
    ↪ngens(1)
>>> S.random_element() # random
s^-8 + s^-7 + s^-6 + s^-5 + s^-1 + s + s^3 + s^4
+ s^5 + 2*s^6 + s^7 + s^11 + O(s^12)
```

residue_field()

Return the residue field of this Laurent series field if it is a complete discrete valuation field (i.e. if the base ring is a field, in which case it is also the residue field).

EXAMPLES:

```

sage: R.<x> = LaurentSeriesRing(GF(17))
sage: R.residue_field()
Finite Field of size 17

sage: R.<x> = LaurentSeriesRing(ZZ)
sage: R.residue_field()
Traceback (most recent call last):
...
TypeError: the base ring is not a field

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(GF(Integer(17)), names=('x',)); (x,) = R._first_
↳ngens(1)
>>> R.residue_field()
Finite Field of size 17

>>> R = LaurentSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> R.residue_field()
Traceback (most recent call last):
...
TypeError: the base ring is not a field

```

uniformizer()

Return a uniformizer of this Laurent series field if it is a discrete valuation field (i.e. if the base ring is actually a field). Otherwise, an error is raised.

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(QQ)
sage: R.uniformizer()
t

sage: R.<t> = LaurentSeriesRing(ZZ)
sage: R.uniformizer()
Traceback (most recent call last):
...
TypeError: the base ring is not a field

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.uniformizer()
t

>>> R = LaurentSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.uniformizer()
Traceback (most recent call last):
...
TypeError: the base ring is not a field

```

`sage.rings.laurent_series_ring.is_LaurentSeriesRing(x)`

Return True if this is a *univariate* Laurent series ring.

This is in keeping with the behavior of `is_PolynomialRing` versus `is_MPolynomialRing`.

LAURENT SERIES

Laurent series in Sage are represented internally as a power of the variable times the power series part. If a Laurent series f is represented as $f = t^n \cdot u$ where t is the variable and u has nonzero constant term, u can be accessed through `valuation_zero_part()` and n can be accessed through `valuation()`.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(GF(7), 't'); R
Laurent Series Ring in t over Finite Field of size 7
sage: f = 1/(1-t+O(t^10)); f
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + t^9 + O(t^10)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(GF(Integer(7)), 't', names=('t',)); (t,) = R._first_
    ↪ngens(1); R
Laurent Series Ring in t over Finite Field of size 7
>>> f = Integer(1)/(Integer(1)-t+O(t**Integer(10))); f
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + t^9 + O(t^10)
```

Laurent series are immutable:

```
sage: f[2]
1
sage: f[2] = 5
Traceback (most recent call last):
...
IndexError: Laurent series are immutable
```

```
>>> from sage.all import *
>>> f[Integer(2)]
1
>>> f[Integer(2)] = Integer(5)
Traceback (most recent call last):
...
IndexError: Laurent series are immutable
```

We compute with a Laurent series over the complex mpfr numbers.

```
sage: K.<q> = Frac(CC[['q']]); K #_
    ↪needs sage.rings.real_mpfr
Laurent Series Ring in q over Complex Field with 53 bits of precision
sage: q #_
```

(continues on next page)

(continued from previous page)

```
↪needs sage.rings.real_mpfr
1.0000000000000000*q
```

```
>>> from sage.all import *
>>> K = Frac(CC[['q']], names=('q',)); (q,) = K._first_ngens(1); K
↪ # needs sage.rings.real_mpfr
Laurent Series Ring in q over Complex Field with 53 bits of precision
>>> q
↪ #
↪needs sage.rings.real_mpfr
1.0000000000000000*q
```

Saving and loading.

```
sage: loads(q.dumps()) == q
↪needs sage.rings.real_mpfr
True
sage: loads(K.dumps()) == K
↪needs sage.rings.real_mpfr
True
```

```
>>> from sage.all import *
>>> loads(q.dumps()) == q
↪needs sage.rings.real_mpfr
True
>>> loads(K.dumps()) == K
↪needs sage.rings.real_mpfr
True
```

AUTHORS:

- William Stein: original version
- David Joyner (2006-01-22): added examples
- Robert Bradshaw (2007-04): optimizations, shifting
- Robert Bradshaw: Cython version

class sage.rings.laurent_series_ring_element.**LaurentSeries**

Bases: [AlgebraElement](#)

A Laurent Series.

We consider a Laurent series of the form $f = t^n \cdot u$ where u is a power series with nonzero constant term.

INPUT:

- parent – a Laurent series ring
- f – a power series (or something can be coerced to one); note that f does *not* have to be a unit
- n – (default: 0) integer

o(prec)

Return the Laurent series of precision at most prec obtained by adding $O(q^{\text{prec}})$, where q is the variable.

The precision of `self` and the integer `prec` can be arbitrary. The resulting Laurent series will have precision equal to the minimum of the precision of `self` and `prec`. The term $O(q^{\text{prec}})$ is the zero series with precision `prec`.

See also `add_bigoh()`.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = t^-5 + t^-4 + t^3 + O(t^10); f
t^-5 + t^-4 + t^3 + O(t^10)
sage: f.O(-4)
t^-5 + O(t^-4)
sage: f.O(15)
t^-5 + t^-4 + t^3 + O(t^10)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t**Integer(5) + t**Integer(4) + t**Integer(3) + O(t**Integer(10)); f
t^-5 + t^-4 + t^3 + O(t^10)
>>> f.O(Integer(4))
t^-5 + O(t^-4)
>>> f.O(Integer(15))
t^-5 + t^-4 + t^3 + O(t^10)
```

V(*n*)

alias of `verschiebung()`.

add_bigoh(*prec*)

Return the truncated series at chosen precision *prec*.

See also `O()`.

INPUT:

- *prec* – the precision of the series as an integer

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = t^2 + t^3 + O(t^10); f
t^2 + t^3 + O(t^10)
sage: f.add_bigoh(5)
t^2 + t^3 + O(t^5)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t**Integer(2) + t**Integer(3) + O(t**Integer(10)); f
t^2 + t^3 + O(t^10)
>>> f.add_bigoh(Integer(5))
t^2 + t^3 + O(t^5)
```

change_ring(*R*)

Change the base ring of `self`.

EXAMPLES:

```
sage: R.<q> = LaurentSeriesRing(ZZ)
sage: p = R([1,2,3]); p
1 + 2*q + 3*q^2
```

(continues on next page)

(continued from previous page)

```
sage: p.change_ring(GF(2))
1 + q^2
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(ZZ, names=('q',)); (q,) = R._first_ngens(1)
>>> p = R([Integer(1), Integer(2), Integer(3)]); p
1 + 2*q + 3*q^2
>>> p.change_ring(GF(Integer(2)))
1 + q^2
```

coefficients()

Return the nonzero coefficients of self.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = -5/t^(2) + t + t^2 - 10/3*t^3
sage: f.coefficients()
[-5, 1, 1, -10/3]
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = -Integer(5)/t**(Integer(2)) + t + t**Integer(2) - Integer(10)/
↳ Integer(3)*t**Integer(3)
>>> f.coefficients()
[-5, 1, 1, -10/3]
```

common_prec(other)

Return the minimum precision of self and other.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
```

```
sage: f = t^(-1) + t + t^2 + O(t^3)
sage: g = t + t^3 + t^4 + O(t^4)
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3
```

```
>>> from sage.all import *
>>> f = t**(-Integer(1)) + t + t**Integer(2) + O(t**Integer(3))
>>> g = t + t**Integer(3) + t**Integer(4) + O(t**Integer(4))
>>> f.common_prec(g)
3
>>> g.common_prec(f)
3
```

```
sage: f = t + t^2 + O(t^3)
sage: g = t^(-3) + t^2
sage: f.common_prec(g)
3
sage: g.common_prec(f)
3
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2) + O(t**Integer(3))
>>> g = t**(-Integer(3)) + t**Integer(2)
>>> f.common_prec(g)
3
>>> g.common_prec(f)
3
```

```
sage: f = t + t^2
sage: g = t^2
sage: f.common_prec(g)
+Infinity
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2)
>>> g = t**Integer(2)
>>> f.common_prec(g)
+Infinity
```

```
sage: f = t^(-3) + O(t^(-2))
sage: g = t^(-5) + O(t^(-1))
sage: f.common_prec(g)
-2
```

```
>>> from sage.all import *
>>> f = t**(-Integer(3)) + O(t**(-Integer(2)))
>>> g = t**(-Integer(5)) + O(t**(-Integer(1)))
>>> f.common_prec(g)
-2
```

```
sage: f = O(t^2)
sage: g = O(t^5)
sage: f.common_prec(g)
2
```

```
>>> from sage.all import *
>>> f = O(t**Integer(2))
>>> g = O(t**Integer(5))
>>> f.common_prec(g)
2
```

common_valuation (*other*)

Return the minimum valuation of *self* and *other*.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
```

```
sage: f = t^(-1) + t + t^2 + O(t^3)
sage: g = t + t^3 + t^4 + O(t^4)
sage: f.common_valuation(g)
-1
sage: g.common_valuation(f)
-1
```

```
>>> from sage.all import *
>>> f = t**(-Integer(1)) + t + t**Integer(2) + O(t**Integer(3))
>>> g = t + t**Integer(3) + t**Integer(4) + O(t**Integer(4))
>>> f.common_valuation(g)
-1
>>> g.common_valuation(f)
-1
```

```
sage: f = t + t^2 + O(t^3)
sage: g = t^(-3) + t^2
sage: f.common_valuation(g)
-3
sage: g.common_valuation(f)
-3
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2) + O(t**Integer(3))
>>> g = t**(-Integer(3)) + t**Integer(2)
>>> f.common_valuation(g)
-3
>>> g.common_valuation(f)
-3
```

```
sage: f = t + t^2
sage: g = t^2
sage: f.common_valuation(g)
1
```

```
>>> from sage.all import *
>>> f = t + t**Integer(2)
>>> g = t**Integer(2)
>>> f.common_valuation(g)
1
```

```
sage: f = t^(-3) + O(t^(-2))
sage: g = t^(-5) + O(t^(-1))
sage: f.common_valuation(g)
-5
```

```
>>> from sage.all import *
>>> f = t**(-Integer(3)) + O(t**(-Integer(2)))
>>> g = t**(-Integer(5)) + O(t**(-Integer(1)))
>>> f.common_valuation(g)
-5
```

```
sage: f = O(t^2)
sage: g = O(t^5)
sage: f.common_valuation(g)
+Infinity
```

```
>>> from sage.all import *
>>> f = O(t**Integer(2))
>>> g = O(t**Integer(5))
>>> f.common_valuation(g)
+Infinity
```

degree()

Return the degree of a polynomial equivalent to this power series modulo big oh of the precision.

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: g = x^2 - x^4 + O(x^8)
sage: g.degree()
4
sage: g = -10/x^5 + x^2 - x^4 + O(x^8)
sage: g.degree()
4
sage: (x^-2 + O(x^0)).degree()
-2
```

```
>>> from sage.all import *
>>> x = Frac(QQ[['x']]).gen(0)
>>> g = x**Integer(2) - x**Integer(4) + O(x**Integer(8))
>>> g.degree()
4
>>> g = -Integer(10)/x**Integer(5) + x**Integer(2) - x**Integer(4) + O(x**Integer(8))
>>> g.degree()
4
>>> (x**(-Integer(2)) + O(x**Integer(0))).degree()
-2
```

derivative(*args)

The formal derivative of this Laurent series, with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the global derivative() function for more details.

 See also

`_derivative()`

EXAMPLES:

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: g = 1/x^10 - x + x^2 - x^4 + O(x^8)
sage: g.derivative()
-10*x^-11 - 1 + 2*x - 4*x^3 + O(x^7)
sage: g.derivative(x)
-10*x^-11 - 1 + 2*x - 4*x^3 + O(x^7)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> g = Integer(1)/x**Integer(10) - x + x**Integer(2) - x**Integer(4) + \
↳ O(x**Integer(8))
>>> g.derivative()
-10*x^-11 - 1 + 2*x - 4*x^3 + O(x^7)
>>> g.derivative(x)
-10*x^-11 - 1 + 2*x - 4*x^3 + O(x^7)
```

```
sage: R.<t> = PolynomialRing(ZZ)
sage: S.<x> = LaurentSeriesRing(R)
sage: f = 2*t/x + (3*t^2 + 6*t)*x + O(x^2)
sage: f.derivative()
-2*t*x^-2 + (3*t^2 + 6*t) + O(x)
sage: f.derivative(x)
-2*t*x^-2 + (3*t^2 + 6*t) + O(x)
sage: f.derivative(t)
2*x^-1 + (6*t + 6)*x + O(x^2)
```

```
>>> from sage.all import *
>>> R = PolynomialRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> S = LaurentSeriesRing(R, names=('x',)); (x,) = S._first_ngens(1)
>>> f = Integer(2)*t/x + (Integer(3)*t**Integer(2) + Integer(6)*t)*x + \
↳ O(x**Integer(2))
>>> f.derivative()
-2*t*x^-2 + (3*t^2 + 6*t) + O(x)
>>> f.derivative(x)
-2*t*x^-2 + (3*t^2 + 6*t) + O(x)
>>> f.derivative(t)
2*x^-1 + (6*t + 6)*x + O(x^2)
```

exponents()

Return the exponents appearing in *self* with nonzero coefficients.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = -5/t^2 + t + t^2 - 10/3*t^3
sage: f.exponents()
[-2, 1, 2, 3]
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = -Integer(5)/t**(Integer(2)) + t + t**Integer(2) - Integer(10)/
```

(continues on next page)

(continued from previous page)

```

↪Integer(3)*t**Integer(3)
>>> f.exponents()
[-2, 1, 2, 3]

```

integral()

The formal integral of this Laurent series with 0 constant term.

EXAMPLES: The integral may or may not be defined if the base ring is not a field.

```

sage: t = LaurentSeriesRing(ZZ, 't').0
sage: f = 2*t^-3 + 3*t^2 + O(t^4)
sage: f.integral()
-t^-2 + t^3 + O(t^5)

```

```

>>> from sage.all import *
>>> t = LaurentSeriesRing(ZZ, 't').gen(0)
>>> f = Integer(2)*t**Integer(-3) + Integer(3)*t**Integer(2) +
↪O(t**Integer(4))
>>> f.integral()
-t^-2 + t^3 + O(t^5)

```

```

sage: f = t^3
sage: f.integral()
Traceback (most recent call last):
...
ArithmeticError: Coefficients of integral cannot be coerced into the base ring

```

```

>>> from sage.all import *
>>> f = t**Integer(3)
>>> f.integral()
Traceback (most recent call last):
...
ArithmeticError: Coefficients of integral cannot be coerced into the base ring

```

The integral of $1/t$ is $\log(t)$, which is not given by a Laurent series:

```

sage: t = Frac(QQ[['t']]).0
sage: f = -1/t^3 - 31/t + O(t^3)
sage: f.integral()
Traceback (most recent call last):
...
ArithmeticError: The integral of is not a Laurent series, since t^-1 has
↪nonzero coefficient.

```

```

>>> from sage.all import *
>>> t = Frac(QQ[['t']]).gen(0)
>>> f = -Integer(1)/t**Integer(3) - Integer(31)/t + O(t**Integer(3))
>>> f.integral()
Traceback (most recent call last):
...
ArithmeticError: The integral of is not a Laurent series, since t^-1 has
↪nonzero coefficient.

```

Another example with just one negative coefficient:

```
sage: A.<t> = QQ[[]]
sage: f = -2*t^(-4) + O(t^8)
sage: f.integral()
2/3*t^-3 + O(t^9)
sage: f.integral().derivative() == f
True
```

```
>>> from sage.all import *
>>> A = QQ[['t']]; (t,) = A._first_ngens(1)
>>> f = -Integer(2)*t**(-Integer(4)) + O(t**Integer(8))
>>> f.integral()
2/3*t^-3 + O(t^9)
>>> f.integral().derivative() == f
True
```

inverse()

Return the inverse of self, i.e., self^{-1} .

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(ZZ)
sage: t.inverse()
t^-1
sage: (1-t).inverse()
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + ...
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> t.inverse()
t^-1
>>> (Integer(1)-t).inverse()
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + ...
```

is_monomial()

Return True if this element is a monomial. That is, if self is x^n for some integer n .

EXAMPLES:

```
sage: k.<z> = LaurentSeriesRing(QQ, 'z')
sage: (30*z).is_monomial()
False
sage: k(1).is_monomial()
True
sage: (z+1).is_monomial()
False
sage: (z^-2909).is_monomial()
True
sage: (3*z^-2909).is_monomial()
False
```

```
>>> from sage.all import *
>>> k = LaurentSeriesRing(QQ, 'z', names=('z',)); (z,) = k._first_ngens(1)
```

(continues on next page)

(continued from previous page)

```

>>> (Integer(30)*z).is_monomial()
False
>>> k(Integer(1)).is_monomial()
True
>>> (z+Integer(1)).is_monomial()
False
>>> (z**Integer(2909)).is_monomial()
True
>>> (Integer(3)*z**Integer(2909)).is_monomial()
False

```

is_unit()

Return True if this is Laurent series is a unit in this ring.

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(QQ)
sage: (2 + t).is_unit()
True
sage: f = 2 + t^2 + O(t^10); f.is_unit()
True
sage: 1/f
1/2 - 1/4*t^2 + 1/8*t^4 - 1/16*t^6 + 1/32*t^8 + O(t^10)
sage: R(0).is_unit()
False
sage: R.<s> = LaurentSeriesRing(ZZ)
sage: f = 2 + s^2 + O(s^10)
sage: f.is_unit()
False
sage: 1/f
Traceback (most recent call last):
...
ValueError: constant term 2 is not a unit

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> (Integer(2) + t).is_unit()
True
>>> f = Integer(2) + t**Integer(2) + O(t**Integer(10)); f.is_unit()
True
>>> Integer(1)/f
1/2 - 1/4*t^2 + 1/8*t^4 - 1/16*t^6 + 1/32*t^8 + O(t^10)
>>> R(Integer(0)).is_unit()
False
>>> R = LaurentSeriesRing(ZZ, names=('s',)); (s,) = R._first_ngens(1)
>>> f = Integer(2) + s**Integer(2) + O(s**Integer(10))
>>> f.is_unit()
False
>>> Integer(1)/f
Traceback (most recent call last):
...
ValueError: constant term 2 is not a unit

```

ALGORITHM: A Laurent series is a unit if and only if its “unit part” is a unit.

`is_zero()`

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = 1/x + x + x^2 + 3*x^4 + O(x^7)
sage: f.is_zero()
0
sage: z = 0*f
sage: z.is_zero()
1
```

```
>>> from sage.all import *
>>> x = Frac(QQ[['x']]).gen(0)
>>> f = Integer(1)/x + x + x**Integer(2) + Integer(3)*x**Integer(4) + \
↳ O(x**Integer(7))
>>> f.is_zero()
0
>>> z = Integer(0)*f
>>> z.is_zero()
1
```

`laurent_polynomial()`

Return the corresponding Laurent polynomial.

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = t^-3 + t + 7*t^2 + O(t^5)
sage: g = f.laurent_polynomial(); g
t^-3 + t + 7*t^2
sage: g.parent()
Univariate Laurent Polynomial Ring in t over Rational Field
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = t**Integer(-3) + t + Integer(7)*t**Integer(2) + O(t**Integer(5))
>>> g = f.laurent_polynomial(); g
t^-3 + t + 7*t^2
>>> g.parent()
Univariate Laurent Polynomial Ring in t over Rational Field
```

`lift_to_precision(absprec=None)`

Return a congruent Laurent series with absolute precision at least `absprec`.

INPUT:

- `absprec` – integer or `None` (default: `None`); the absolute precision of the result. If `None`, lifts to an exact element.

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: A.<t> = LaurentSeriesRing(GF(5))
```

(continues on next page)

(continued from previous page)

```
sage: x = t^(-1) + t^2 + O(t^5)
sage: x.lift_to_precision(10)
t^-1 + t^2 + O(t^10)
sage: x.lift_to_precision()
t^-1 + t^2
```

```
>>> from sage.all import *
>>> # needs sage.rings.finite_rings
>>> A = LaurentSeriesRing(GF(Integer(5)), names=('t',)); (t,) = A._first_
↳ngens(1)
>>> x = t**(-Integer(1)) + t**Integer(2) + O(t**Integer(5))
>>> x.lift_to_precision(Integer(10))
t^-1 + t^2 + O(t^10)
>>> x.lift_to_precision()
t^-1 + t^2
```

list()

EXAMPLES:

```
sage: R.<t> = LaurentSeriesRing(QQ)
sage: f = -5/t^(2) + t + t^2 - 10/3*t^3
sage: f.list()
[-5, 0, 0, 1, 1, -10/3]
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = -Integer(5)/t**(Integer(2)) + t + t**Integer(2) - Integer(10)/
↳Integer(3)*t**Integer(3)
>>> f.list()
[-5, 0, 0, 1, 1, -10/3]
```

nth_root (*n*, *prec*=None)Return the *n*-th root of this Laurent power series.

INPUT:

- *n* – integer
- *prec* – integer (optional); precision of the result. Though, if this series has finite precision, then the result cannot have larger precision.

EXAMPLES:

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: (x^-2 + 1 + x).nth_root(2)
x^-1 + 1/2*x + 1/2*x^2 - ... - 19437/65536*x^18 + O(x^19)
sage: (x^-2 + 1 + x).nth_root(2)**2
x^-2 + 1 + x + O(x^18)

sage: # needs sage.modular
sage: j = j_invariant_qexp()
sage: q = j.parent().gen()
sage: j(q^3).nth_root(3)
```

(continues on next page)

(continued from previous page)

```

q^-1 + 248*q^2 + 4124*q^5 + ... + O(q^29)
sage: (j(q^2) - 1728).nth_root(2)
q^-1 - 492*q - 22590*q^3 - ... + O(q^19)

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> (x**Integer(2) + Integer(1) + x).nth_root(Integer(2))
x^-1 + 1/2*x + 1/2*x^2 - ... - 19437/65536*x^18 + O(x^19)
>>> (x**Integer(2) + Integer(1) + x).nth_root(Integer(2))**Integer(2)
x^-2 + 1 + x + O(x^18)

>>> # needs sage.modular
>>> j = j_invariant_qexp()
>>> q = j.parent().gen()
>>> j(q**Integer(3)).nth_root(Integer(3))
q^-1 + 248*q^2 + 4124*q^5 + ... + O(q^29)
>>> (j(q**Integer(2)) - Integer(1728)).nth_root(Integer(2))
q^-1 - 492*q - 22590*q^3 - ... + O(q^19)

```

power_series()

Convert this Laurent series to a power series.

An error is raised if the Laurent series has a term (or an error term $O(x^k)$) whose exponent is negative.

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-t+O(t^10)); f.parent()
Laurent Series Ring in t over Integer Ring
sage: g = f.power_series(); g
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + t^9 + O(t^10)
sage: parent(g)
Power Series Ring in t over Integer Ring
sage: f = 3/t^2 + t^2 + t^3 + O(t^10)
sage: f.power_series()
Traceback (most recent call last):
...
TypeError: self is not a power series

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> f = Integer(1)/(Integer(1)-t+O(t**Integer(10))); f.parent()
Laurent Series Ring in t over Integer Ring
>>> g = f.power_series(); g
1 + t + t^2 + t^3 + t^4 + t^5 + t^6 + t^7 + t^8 + t^9 + O(t^10)
>>> parent(g)
Power Series Ring in t over Integer Ring
>>> f = Integer(3)/t**Integer(2) + t**Integer(2) + t**Integer(3) +
↳ O(t**Integer(10))
>>> f.power_series()
Traceback (most recent call last):
...
TypeError: self is not a power series

```

prec()

This function returns the n so that the Laurent series is of the form (stuff) + $O(t^n)$. It doesn't matter how many negative powers appear in the expansion. In particular, `prec` could be negative.

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = x^2 + 3*x^4 + O(x^7)
sage: f.prec()
7
sage: g = 1/x^10 - x + x^2 - x^4 + O(x^8)
sage: g.prec()
8
```

```
>>> from sage.all import *
>>> x = Frac(QQ[['x']]).gen(0)
>>> f = x**Integer(2) + Integer(3)*x**Integer(4) + O(x**Integer(7))
>>> f.prec()
7
>>> g = Integer(1)/x**Integer(10) - x + x**Integer(2) - x**Integer(4) +
↪ O(x**Integer(8))
>>> g.prec()
8
```

precision_absolute()

Return the absolute precision of this series.

By definition, the absolute precision of $\dots + O(x^r)$ is r .

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: (t^2 + O(t^3)).precision_absolute()
3
sage: (1 - t^2 + O(t^100)).precision_absolute()
100
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (t**Integer(2) + O(t**Integer(3))).precision_absolute()
3
>>> (Integer(1) - t**Integer(2) + O(t**Integer(100))).precision_absolute()
100
```

precision_relative()

Return the relative precision of this series, that is the difference between its absolute precision and its valuation.

By convention, the relative precision of 0 (or $O(x^r)$ for any r) is 0.

EXAMPLES:

```
sage: R.<t> = ZZ[[t]]
sage: (t^2 + O(t^3)).precision_relative()
1
sage: (1 - t^2 + O(t^100)).precision_relative()
```

(continues on next page)

(continued from previous page)

```
100
sage: O(t^4).precision_relative()
0
```

```
>>> from sage.all import *
>>> R = ZZ[['t']]; (t,) = R._first_ngens(1)
>>> (t**Integer(2) + O(t**Integer(3))).precision_relative()
1
>>> (Integer(1) - t**Integer(2) + O(t**Integer(100))).precision_relative()
100
>>> O(t**Integer(4)).precision_relative()
0
```

residue()Return the residue of `self`.

Consider the Laurent series

$$f = \sum_{n \in \mathbb{Z}} a_n t^n = \cdots + \frac{a_{-2}}{t^2} + \frac{a_{-1}}{t} + a_0 + a_1 t + a_2 t^2 + \cdots,$$

then the residue of f is a_{-1} . Alternatively this is the coefficient of $1/t$.

EXAMPLES:

```
sage: t = LaurentSeriesRing(ZZ, 't').gen()
sage: f = 1/t**2 + 2/t + 3 + 4*t
sage: f.residue()
2
sage: f = t + t**2
sage: f.residue()
0
sage: f.residue().parent()
Integer Ring
```

```
>>> from sage.all import *
>>> t = LaurentSeriesRing(ZZ, 't').gen()
>>> f = Integer(1)/t**Integer(2) + Integer(2)/t + Integer(3) + Integer(4)*t
>>> f.residue()
2
>>> f = t + t**Integer(2)
>>> f.residue()
0
>>> f.residue().parent()
Integer Ring
```

reverse (*precision=None*)Return the reverse of f , i.e., the series g such that $g(f(x)) = x$. Given an optional argument `precision`, return the reverse with given precision (note that the reverse can have precision at most `f.prec()`). If f has infinite precision, and the argument `precision` is not given, then the precision of the reverse defaults to the default precision of `f.parent()`.Note that this is only possible if the valuation of `self` is exactly 1.

The implementation depends on the underlying power series element implementing a reverse method.

EXAMPLES:

```

sage: R.<x> = Frac(QQ[['x']])
sage: f = 2*x + 3*x^2 - x^4 + O(x^5)
sage: g = f.reverse()
sage: g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
sage: f(g)
x + O(x^5)
sage: g(f)
x + O(x^5)

sage: A.<t> = LaurentSeriesRing(ZZ)
sage: a = t - t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

sage: B.<b,c> = ZZ[ ]
sage: A.<t> = LaurentSeriesRing(B)
sage: f = t + b*t^2 + c*t^3 + O(t^4)
sage: g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
sage: g(f)
t + O(t^4)

sage: A.<t> = PowerSeriesRing(ZZ)
sage: B.<s> = LaurentSeriesRing(A)
sage: f = (1 - 3*t + 4*t^3 + O(t^4))*s + (2 + t + t^2 + O(t^3))*s^2 + O(s^3)
sage: set_verbose(1)
sage: g = f.reverse(); g
verbose 1 (<module>) passing to pari failed; trying Lagrange inversion
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*s + (-2 - 19*t - 118*t^2 + O(t^3))*s^2 +
↳O(s^3)
sage: set_verbose(0)
sage: f(g) == g(f) == s
True

```

```

>>> from sage.all import *
>>> R = Frac(QQ[['x']], names=('x',)); (x,) = R._first_ngens(1)
>>> f = Integer(2)*x + Integer(3)*x**Integer(2) - x**Integer(4) +
↳O(x**Integer(5))
>>> g = f.reverse()
>>> g
1/2*x - 3/8*x^2 + 9/16*x^3 - 131/128*x^4 + O(x^5)
>>> f(g)
x + O(x^5)
>>> g(f)

```

(continues on next page)

(continued from previous page)

```

x + O(x^5)

>>> A = LaurentSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> a = t - t**Integer(2) - Integer(2)*t**Integer(4) + t**Integer(5) +
↳O(t**Integer(6))
>>> b = a.reverse(); b
t + t^2 + 2*t^3 + 7*t^4 + 25*t^5 + O(t^6)
>>> a(b)
t + O(t^6)
>>> b(a)
t + O(t^6)

>>> B = ZZ['b, c']; (b, c,) = B._first_ngens(2)
>>> A = LaurentSeriesRing(B, names=('t',)); (t,) = A._first_ngens(1)
>>> f = t + b*t**Integer(2) + c*t**Integer(3) + O(t**Integer(4))
>>> g = f.reverse(); g
t - b*t^2 + (2*b^2 - c)*t^3 + O(t^4)
>>> f(g)
t + O(t^4)
>>> g(f)
t + O(t^4)

>>> A = PowerSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> B = LaurentSeriesRing(A, names=('s',)); (s,) = B._first_ngens(1)
>>> f = (Integer(1) - Integer(3)*t + Integer(4)*t**Integer(3) +
↳O(t**Integer(4)))*s + (Integer(2) + t + t**Integer(2) +
↳O(t**Integer(3)))*s**Integer(2) + O(s**Integer(3))
>>> set_verbose(Integer(1))
>>> g = f.reverse(); g
verbose 1 (<module>) passing to pari failed; trying Lagrange inversion
(1 + 3*t + 9*t^2 + 23*t^3 + O(t^4))*s + (-2 - 19*t - 118*t^2 + O(t^3))*s^2 +
↳O(s^3)
>>> set_verbose(Integer(0))
>>> f(g) == g(f) == s
True

```

If the leading coefficient is not a unit, we pass to its fraction field if possible:

```

sage: A.<t> = LaurentSeriesRing(ZZ)
sage: a = 2*t - 4*t^2 + t^4 - t^5 + O(t^6)
sage: a.reverse()
1/2*t + 1/2*t^2 + t^3 + 79/32*t^4 + 437/64*t^5 + O(t^6)

sage: B.<b> = PolynomialRing(ZZ)
sage: A.<t> = LaurentSeriesRing(B)
sage: f = 2*b*t + b*t^2 + 3*b^2*t^3 + O(t^4)
sage: g = f.reverse(); g
1/(2*b)*t - 1/(8*b^2)*t^2 + ((-3*b + 1)/(16*b^3))*t^3 + O(t^4)
sage: f(g)
t + O(t^4)
sage: g(f)
t + O(t^4)

```



```

>>> from sage.all import *
>>> A = LaurentSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> a = Integer(2)*t - Integer(4)*t**Integer(2) + t**Integer(4) -
↳ t**Integer(5) + O(t**Integer(6))
>>> a.reverse()
1/2*t + 1/2*t^2 + t^3 + 79/32*t^4 + 437/64*t^5 + O(t^6)

>>> B = PolynomialRing(ZZ, names=('b',)); (b,) = B._first_ngens(1)
>>> A = LaurentSeriesRing(B, names=('t',)); (t,) = A._first_ngens(1)
>>> f = Integer(2)*b*t + b*t**Integer(2) +
↳ Integer(3)*b**Integer(2)*t**Integer(3) + O(t**Integer(4))
>>> g = f.reverse(); g
1/(2*b)*t - 1/(8*b^2)*t^2 + ((-3*b + 1)/(16*b^3))*t^3 + O(t^4)
>>> f(g)
t + O(t^4)
>>> g(f)
t + O(t^4)

```

We can handle some base rings of positive characteristic:

```

sage: A8.<t> = LaurentSeriesRing(Zmod(8))
sage: a = t - 15*t^2 - 2*t^4 + t^5 + O(t^6)
sage: b = a.reverse(); b
t + 7*t^2 + 2*t^3 + 5*t^4 + t^5 + O(t^6)
sage: a(b)
t + O(t^6)
sage: b(a)
t + O(t^6)

```

```

>>> from sage.all import *
>>> A8 = LaurentSeriesRing(Zmod(Integer(8)), names=('t',)); (t,) = A8._first_
↳ ngens(1)
>>> a = t - Integer(15)*t**Integer(2) - Integer(2)*t**Integer(4) +
↳ t**Integer(5) + O(t**Integer(6))
>>> b = a.reverse(); b
t + 7*t^2 + 2*t^3 + 5*t^4 + t^5 + O(t^6)
>>> a(b)
t + O(t^6)
>>> b(a)
t + O(t^6)

```

The optional argument `precision` sets the precision of the output:

```

sage: R.<x> = LaurentSeriesRing(QQ)
sage: f = 2*x + 3*x^2 - 7*x^3 + x^4 + O(x^5)
sage: g = f.reverse(precision=3); g
1/2*x - 3/8*x^2 + O(x^3)
sage: f(g)
x + O(x^3)
sage: g(f)
x + O(x^3)

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> f = Integer(2)*x + Integer(3)*x**Integer(2) - Integer(7)*x**Integer(3) +
  ↪ x**Integer(4) + O(x**Integer(5))
>>> g = f.reverse(precision=Integer(3)); g
1/2*x - 3/8*x^2 + O(x^3)
>>> f(g)
x + O(x^3)
>>> g(f)
x + O(x^3)

```

If the input series has infinite precision, the precision of the output is automatically set to the default precision of the parent ring:

```

sage: R.<x> = LaurentSeriesRing(QQ, default_prec=20)
sage: (x - x^2).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8 + 1430*x^9
+ 4862*x^10 + 16796*x^11 + 58786*x^12 + 208012*x^13 + 742900*x^14
+ 2674440*x^15 + 9694845*x^16 + 35357670*x^17 + 129644790*x^18
+ 477638700*x^19 + O(x^20)
sage: (x - x^2).reverse(precision=3)
x + x^2 + O(x^3)

```

```

>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, default_prec=Integer(20), names=('x',)); (x,) =
  ↪ R._first_ngens(1)
>>> (x - x**Integer(2)).reverse() # get some Catalan numbers
x + x^2 + 2*x^3 + 5*x^4 + 14*x^5 + 42*x^6 + 132*x^7 + 429*x^8 + 1430*x^9
+ 4862*x^10 + 16796*x^11 + 58786*x^12 + 208012*x^13 + 742900*x^14
+ 2674440*x^15 + 9694845*x^16 + 35357670*x^17 + 129644790*x^18
+ 477638700*x^19 + O(x^20)
>>> (x - x**Integer(2)).reverse(precision=Integer(3))
x + x^2 + O(x^3)

```

shift(*k*)

Return this Laurent series multiplied by the power t^n . Does not change this series.

Note

Despite the fact that higher order terms are printed to the right in a power series, right shifting decreases the powers of t , while left shifting increases them. This is to be consistent with polynomials, integers, etc.

EXAMPLES:

```

sage: R.<t> = LaurentSeriesRing(QQ['y'])
sage: f = (t+t^-1)^4; f
t^-4 + 4*t^-2 + 6 + 4*t^2 + t^4
sage: f.shift(10)
t^6 + 4*t^8 + 6*t^10 + 4*t^12 + t^14
sage: f >> 10
t^-14 + 4*t^-12 + 6*t^-10 + 4*t^-8 + t^-6
sage: t << 4

```

(continues on next page)

(continued from previous page)

```
t^5
sage: t + O(t^3) >> 4
t^-3 + O(t^-1)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ['y'], names=('t',)); (t,) = R._first_ngens(1)
>>> f = (t+t**Integer(1))**Integer(4); f
t^-4 + 4*t^-2 + 6 + 4*t^2 + t^4
>>> f.shift(Integer(10))
t^6 + 4*t^8 + 6*t^10 + 4*t^12 + t^14
>>> f >> Integer(10)
t^-14 + 4*t^-12 + 6*t^-10 + 4*t^-8 + t^-6
>>> t << Integer(4)
t^5
>>> t + O(t**Integer(3)) >> Integer(4)
t^-3 + O(t^-1)
```

AUTHORS:

- Robert Bradshaw (2007-04-18)

truncate(n)

Return the Laurent series of degree $< n$ which is equivalent to `self` modulo x^n .

EXAMPLES:

```
sage: A.<x> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-x)
sage: f
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + x^10 + x^11
+ x^12 + x^13 + x^14 + x^15 + x^16 + x^17 + x^18 + x^19 + O(x^20)
sage: f.truncate(10)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9
```

```
>>> from sage.all import *
>>> A = LaurentSeriesRing(ZZ, names=('x',)); (x,) = A._first_ngens(1)
>>> f = Integer(1)/(Integer(1)-x)
>>> f
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + x^10 + x^11
+ x^12 + x^13 + x^14 + x^15 + x^16 + x^17 + x^18 + x^19 + O(x^20)
>>> f.truncate(Integer(10))
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9
```

truncate_laurentseries(n)

Replace any terms of degree $\geq n$ by big oh.

EXAMPLES:

```
sage: A.<x> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-x)
sage: f
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + x^10 + x^11
+ x^12 + x^13 + x^14 + x^15 + x^16 + x^17 + x^18 + x^19 + O(x^20)
```

(continues on next page)

(continued from previous page)

```
sage: f.truncate_laurentseries(10)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + O(x^10)
```

```
>>> from sage.all import *
>>> A = LaurentSeriesRing(ZZ, names=('x',)); (x,) = A._first_ngens(1)
>>> f = Integer(1)/(Integer(1)-x)
>>> f
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + x^10 + x^11
+ x^12 + x^13 + x^14 + x^15 + x^16 + x^17 + x^18 + x^19 + O(x^20)
>>> f.truncate_laurentseries(Integer(10))
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + x^7 + x^8 + x^9 + O(x^10)
```

truncate_neg(*n*)

Return the Laurent series equivalent to `self` except without any degree *n* terms.

This is equivalent to:

```
``self - self.truncate(n)``
```

EXAMPLES:

```
sage: A.<t> = LaurentSeriesRing(ZZ)
sage: f = 1/(1-t)
sage: f.truncate_neg(15)
t^15 + t^16 + t^17 + t^18 + t^19 + O(t^20)
```

```
>>> from sage.all import *
>>> A = LaurentSeriesRing(ZZ, names=('t',)); (t,) = A._first_ngens(1)
>>> f = Integer(1)/(Integer(1)-t)
>>> f.truncate_neg(Integer(15))
t^15 + t^16 + t^17 + t^18 + t^19 + O(t^20)
```

valuation()**EXAMPLES:**

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: f = 1/x + x^2 + 3*x^4 + O(x^7)
sage: g = 1 - x + x^2 - x^4 + O(x^8)
sage: f.valuation()
-1
sage: g.valuation()
0
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> f = Integer(1)/x + x**Integer(2) + Integer(3)*x**Integer(4) +_
↳O(x**Integer(7))
>>> g = Integer(1) - x + x**Integer(2) - x**Integer(4) + O(x**Integer(8))
>>> f.valuation()
-1
>>> g.valuation()
0
```

Note that the valuation of an element indistinguishable from zero is infinite:

```
sage: h = f - f; h
O(x^7)
sage: h.valuation()
+Infinity
```

```
>>> from sage.all import *
>>> h = f - f; h
O(x^7)
>>> h.valuation()
+Infinity
```

valuation_zero_part()

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = x + x^2 + 3*x^4 + O(x^7)
sage: f/x
1 + x + 3*x^3 + O(x^6)
sage: f.valuation_zero_part()
1 + x + 3*x^3 + O(x^6)
sage: g = 1/x^7 - x + x^2 - x^4 + O(x^8)
sage: g.valuation_zero_part()
1 - x^8 + x^9 - x^11 + O(x^15)
```

```
>>> from sage.all import *
>>> x = Frac(QQ[['x']]).gen(0)
>>> f = x + x**Integer(2) + Integer(3)*x**Integer(4) + O(x**Integer(7))
>>> f/x
1 + x + 3*x^3 + O(x^6)
>>> f.valuation_zero_part()
1 + x + 3*x^3 + O(x^6)
>>> g = Integer(1)/x**Integer(7) - x + x**Integer(2) - x**Integer(4) + O(x**Integer(8))
>>> g.valuation_zero_part()
1 - x^8 + x^9 - x^11 + O(x^15)
```

variable()

EXAMPLES:

```
sage: x = Frac(QQ[['x']]).0
sage: f = 1/x + x^2 + 3*x^4 + O(x^7)
sage: f.variable()
'x'
```

```
>>> from sage.all import *
>>> x = Frac(QQ[['x']]).gen(0)
>>> f = Integer(1)/x + x**Integer(2) + Integer(3)*x**Integer(4) + O(x**Integer(7))
>>> f.variable()
'x'
```

verschiebung (*n*)

Return the *n*-th Verschiebung of *self*.

If $f = \sum a_m x^m$ then this function returns $\sum a_m x^{mn}$.

EXAMPLES:

```
sage: R.<x> = LaurentSeriesRing(QQ)
sage: f = -1/x + 1 + 2*x^2 + 5*x^5
sage: f.V(2)
-x^-2 + 1 + 2*x^4 + 5*x^10
sage: f.V(-1)
5*x^-5 + 2*x^-2 + 1 - x
sage: h = f.add_bigoh(7)
sage: h.V(2)
-x^-2 + 1 + 2*x^4 + 5*x^10 + O(x^14)
sage: h.V(-2)
Traceback (most recent call last):
...
ValueError: For finite precision only positive arguments allowed
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> f = -Integer(1)/x + Integer(1) + Integer(2)*x**Integer(2) + \
Integer(5)*x**Integer(5)
>>> f.V(Integer(2))
-x^-2 + 1 + 2*x^4 + 5*x^10
>>> f.V(-Integer(1))
5*x^-5 + 2*x^-2 + 1 - x
>>> h = f.add_bigoh(Integer(7))
>>> h.V(Integer(2))
-x^-2 + 1 + 2*x^4 + 5*x^10 + O(x^14)
>>> h.V(-Integer(2))
Traceback (most recent call last):
...
ValueError: For finite precision only positive arguments allowed
```

`sage.rings.laurent_series_ring_element.is_LaurentSeries` (*x*)

LAZY SERIES

Coefficients of lazy series are computed on demand. They have infinite precision, although equality can only be decided in special cases.

AUTHORS:

- Kwankyu Lee (2019-02-24): initial version
- Tejasvi Chebrolu, Martin Rubey, Travis Scrimshaw (2021-08): refactored and expanded functionality

EXAMPLES:

Laurent series over the integer ring are particularly useful as generating functions for sequences arising in combinatorics.

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
```

The generating function of the Fibonacci sequence is:

```
sage: f = 1 / (1 - z - z^2)
sage: f
1 + z + 2*z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> f = Integer(1) / (Integer(1) - z - z**Integer(2))
>>> f
1 + z + 2*z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
```

In principle, we can now compute any coefficient of f :

```
sage: f.coefficient(100)
573147844013817084101
```

```
>>> from sage.all import *
>>> f.coefficient(Integer(100))
573147844013817084101
```

Which coefficients are actually computed depends on the type of implementation. For the sparse implementation, only the coefficients which are needed are computed.

```
sage: s = L(lambda n: n, valuation=0); s
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: s.coefficient(10)
10
sage: s._coeff_stream._cache
{1: 1, 2: 2, 3: 3, 4: 4, 5: 5, 6: 6, 10: 10}
```

```
>>> from sage.all import *
>>> s = L(lambda n: n, valuation=Integer(0)); s
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> s.coefficient(Integer(10))
10
>>> s._coeff_stream._cache
{1: 1, 2: 2, 3: 3, 4: 4, 5: 5, 6: 6, 10: 10}
```

Using the dense implementation, all coefficients up to the required coefficient are computed.

```
sage: L.<x> = LazyLaurentSeriesRing(ZZ, sparse=False)
sage: s = L(lambda n: n, valuation=0); s
x + 2*x^2 + 3*x^3 + 4*x^4 + 5*x^5 + 6*x^6 + O(x^7)
sage: s.coefficient(10)
10
sage: s._coeff_stream._cache
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, sparse=False, names=('x',)); (x,) = L._first_
↳ngens(1)
>>> s = L(lambda n: n, valuation=Integer(0)); s
x + 2*x^2 + 3*x^3 + 4*x^4 + 5*x^5 + 6*x^6 + O(x^7)
>>> s.coefficient(Integer(10))
10
>>> s._coeff_stream._cache
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

We can do arithmetic with lazy power series:

```
sage: f
1 + z + 2*z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
sage: f^-1
1 - z - z^2 + O(z^7)
sage: f + f^-1
2 + z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
sage: g = (f + f^-1)*(f - f^-1); g
4*z + 6*z^2 + 8*z^3 + 19*z^4 + 38*z^5 + 71*z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> f
1 + z + 2*z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
>>> f**-Integer(1)
1 - z - z^2 + O(z^7)
>>> f + f**-Integer(1)
```

(continues on next page)

(continued from previous page)

```

2 + z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
>>> g = (f + f**Integer(1))*(f - f**Integer(1)); g
4*z + 6*z^2 + 8*z^3 + 19*z^4 + 38*z^5 + 71*z^6 + O(z^7)

```

We call lazy power series whose coefficients are known to be eventually constant ‘exact’. In some cases, computations with such series are much faster. Moreover, these are the series where equality can be decided. For example:

```

sage: L.<z> = LazyPowerSeriesRing(ZZ)
sage: f = 1 + 2*z^2 / (1 - z)
sage: f - 2 / (1 - z) + 1 + 2*z
0

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = Integer(1) + Integer(2)*z**Integer(2) / (Integer(1) - z)
>>> f - Integer(2) / (Integer(1) - z) + Integer(1) + Integer(2)*z
0

```

However, multivariate Taylor series are actually represented as streams of multivariate polynomials. Therefore, the only exact series in this case are polynomials:

```

sage: L.<x,y> = LazyPowerSeriesRing(ZZ)
sage: 1 / (1-x)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + O(x,y)^7

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('x', 'y',)); (x, y,) = L._first_ngens(2)
>>> Integer(1) / (Integer(1)-x)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + O(x,y)^7

```

A similar statement is true for lazy symmetric functions:

```

sage: h = SymmetricFunctions(QQ).h() #_
↳needs sage.combinat
sage: L = LazySymmetricFunctions(h) #_
↳needs sage.combinat
sage: 1 / (1-L(h[1])) #_
↳needs sage.combinat
h[] + h[1] + (h[1,1]) + (h[1,1,1]) + (h[1,1,1,1]) + (h[1,1,1,1,1]) + (h[1,1,1,1,1,1]) #_
↳+ O^7

```

```

>>> from sage.all import *
>>> h = SymmetricFunctions(QQ).h() #_
↳needs sage.combinat
>>> L = LazySymmetricFunctions(h) #_
↳needs sage.combinat
>>> Integer(1) / (Integer(1)-L(h[Integer(1)])) #_
↳ # needs sage.combinat
h[] + h[1] + (h[1,1]) + (h[1,1,1]) + (h[1,1,1,1]) + (h[1,1,1,1,1]) + (h[1,1,1,1,1,1]) #_
↳+ O^7

```

We can change the base ring:

```
sage: h = g.change_ring(QQ)
sage: h.parent()
↳needs sage.combinat
Lazy Laurent Series Ring in z over Rational Field
sage: h
↳needs sage.combinat
4*z + 6*z^2 + 8*z^3 + 19*z^4 + 38*z^5 + 71*z^6 + 130*z^7 + O(z^8)
sage: hinv = h^-1; hinv
↳needs sage.combinat
1/4*z^-1 - 3/8 + 1/16*z - 17/32*z^2 + 5/64*z^3 - 29/128*z^4 + 165/256*z^5 + O(z^6)
sage: hinv.valuation()
↳needs sage.combinat
-1
```

```
>>> from sage.all import *
>>> h = g.change_ring(QQ)
>>> h.parent()
↳needs sage.combinat
Lazy Laurent Series Ring in z over Rational Field
>>> h
↳needs sage.combinat
4*z + 6*z^2 + 8*z^3 + 19*z^4 + 38*z^5 + 71*z^6 + 130*z^7 + O(z^8)
>>> hinv = h**Integer(1); hinv
↳ # needs sage.combinat
1/4*z^-1 - 3/8 + 1/16*z - 17/32*z^2 + 5/64*z^3 - 29/128*z^4 + 165/256*z^5 + O(z^6)
>>> hinv.valuation()
↳needs sage.combinat
-1
```

class sage.rings.lazy_series.LazyCauchyProductSeries (parent, coeff_stream)

Bases: *LazyModuleElement*

A class for series where multiplication is the Cauchy product.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: f = 1 / (1 - z)
sage: f
1 + z + z^2 + O(z^3)
sage: f * (1 - z)
1

sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=True)
sage: f = 1 / (1 - z)
sage: f
1 + z + z^2 + O(z^3)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = Integer(1) / (Integer(1) - z)
>>> f
1 + z + z^2 + O(z^3)
```

(continues on next page)

(continued from previous page)

```
>>> f * (Integer(1) - z)
1

>>> L = LazyLaurentSeriesRing(ZZ, sparse=True, names=('z',)); (z,) = L._first_
↳ngens(1)
>>> f = Integer(1) / (Integer(1) - z)
>>> f
1 + z + z^2 + O(z^3)
```

exp()Return the exponential series of `self`.

We use the identity

$$\exp(s) = 1 + \int s' \exp(s).$$

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: exp(z)
1 + z + 1/2*z^2 + 1/6*z^3 + 1/24*z^4 + 1/120*z^5 + 1/720*z^6 + O(z^7)
sage: exp(z + z^2)
1 + z + 3/2*z^2 + 7/6*z^3 + 25/24*z^4 + 27/40*z^5 + 331/720*z^6 + O(z^7)
sage: exp(0) #_
↳needs sage.symbolic
1
sage: exp(1 + z)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: exp(x+y)[4].factor()
(1/24) * (x + y)^4
sage: exp(x/(1-y)).polynomial(3)
1/6*x^3 + x^2*y + x*y^2 + 1/2*x^2 + x*y + x + 1
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_
>>> exp(z)
1 + z + 1/2*z^2 + 1/6*z^3 + 1/24*z^4 + 1/120*z^5 + 1/720*z^6 + O(z^7)
>>> exp(z + z**Integer(2))
1 + z + 3/2*z^2 + 7/6*z^3 + 25/24*z^4 + 27/40*z^5 + 331/720*z^6 + O(z^7)
>>> exp(Integer(0))
↳ # needs sage.symbolic
1
>>> exp(Integer(1) + z)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y')); (x, y) = L._first_
```

(continues on next page)

(continued from previous page)

```

↪ngens(2)
>>> exp(x+y)[Integer(4)].factor()
(1/24) * (x + y)^4
>>> exp(x/(Integer(1)-y)).polynomial(Integer(3))
1/6*x^3 + x^2*y + x*y^2 + 1/2*x^2 + x*y + x + 1

```

log()Return the series for the natural logarithm of `self`.

We use the identity

$$\log(s) = \int s'/s.$$

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: log(1/(1-z))
z + 1/2*z^2 + 1/3*z^3 + 1/4*z^4 + 1/5*z^5 + 1/6*z^6 + 1/7*z^7 + O(z^8)

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: log((1 + x/(1-y))).polynomial(3)
1/3*x^3 - x^2*y + x*y^2 - 1/2*x^2 + x*y + x

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> log(Integer(1)/(Integer(1)-z))
z + 1/2*z^2 + 1/3*z^3 + 1/4*z^4 + 1/5*z^5 + 1/6*z^6 + 1/7*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↪ngens(2)
>>> log((Integer(1) + x/(Integer(1)-y))).polynomial(Integer(3))
1/3*x^3 - x^2*y + x*y^2 - 1/2*x^2 + x*y + x

```

valuation()Return the valuation of `self`.

This method determines the valuation of the series by looking for a nonzero coefficient. Hence if the series happens to be zero, then it may run forever.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: s = 1/(1 - z) - 1/(1 - 2*z)
sage: s.valuation()
1
sage: t = z - z
sage: t.valuation()
+Infinity
sage: M = L(lambda n: n^2, 0)
sage: M.valuation()
1
sage: (M - M).valuation()
+Infinity

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> s = Integer(1)/(Integer(1) - z) - Integer(1)/(Integer(1) - Integer(2)*z)
>>> s.valuation()
1
>>> t = z - z
>>> t.valuation()
+Infinity
>>> M = L(lambda n: n**Integer(2), Integer(0))
>>> M.valuation()
1
>>> (M - M).valuation()
+Infinity

```

class sage.rings.lazy_series.LazyCompletionGradedAlgebraElement (parent, coeff_stream)

Bases: *LazyCauchyProductSeries*

An element of a completion of a graded algebra that is computed lazily.

class sage.rings.lazy_series.LazyDirichletSeries (parent, coeff_stream)

Bases: *LazyModuleElement*

A Dirichlet series where the coefficients are computed lazily.

EXAMPLES:

```

sage: L = LazyDirichletSeriesRing(ZZ, "z")
sage: f = L(constant=1)^2
sage: f
↪needs sage.symbolic #_
1 + 2/2^z + 2/3^z + 3/4^z + 2/5^z + 4/6^z + 2/7^z + O(1/(8^z))
sage: f.coefficient(100) == number_of_divisors(100) #_
↪needs sage.libs.pari
True

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, "z")
>>> f = L(constant=Integer(1))**Integer(2)
>>> f
↪needs sage.symbolic #_
1 + 2/2^z + 2/3^z + 3/4^z + 2/5^z + 4/6^z + 2/7^z + O(1/(8^z))
>>> f.coefficient(Integer(100)) == number_of_divisors(Integer(100))
↪ # needs sage.libs.pari
True

```

Lazy Dirichlet series is picklable:

```

sage: g = loads(dumps(f))
sage: g
↪needs sage.symbolic #_
1 + 2/2^z + 2/3^z + 3/4^z + 2/5^z + 4/6^z + 2/7^z + O(1/(8^z))
sage: g == f
True

```

```

>>> from sage.all import *
>>> g = loads(dumps(f))
>>> g
↪needs sage.symbolic
1 + 2/2^z + 2/3^z + 3/4^z + 2/5^z + 4/6^z + 2/7^z + O(1/(8^z))
>>> g == f
True

```

is_unit()

Return whether this element is a unit in the ring.

EXAMPLES:

```

sage: D = LazyDirichletSeriesRing(ZZ, "s")
sage: D([0, 2]).is_unit()
False

sage: D([-1, 2]).is_unit()
True

sage: D([3, 2]).is_unit()
False

sage: D = LazyDirichletSeriesRing(QQ, "s")
sage: D([3, 2]).is_unit()
True

```

```

>>> from sage.all import *
>>> D = LazyDirichletSeriesRing(ZZ, "s")
>>> D([Integer(0), Integer(2)]).is_unit()
False

>>> D([-Integer(1), Integer(2)]).is_unit()
True

>>> D([Integer(3), Integer(2)]).is_unit()
False

>>> D = LazyDirichletSeriesRing(QQ, "s")
>>> D([Integer(3), Integer(2)]).is_unit()
True

```

valuation()

Return the valuation of `self`.

This method determines the valuation of the series by looking for a nonzero coefficient. Hence if the series happens to be zero, then it may run forever.

EXAMPLES:

```

sage: L = LazyDirichletSeriesRing(ZZ, "z")
sage: mu = L(moebius); mu.valuation()
↪needs sage.libs.pari
0

```

(continues on next page)

(continued from previous page)

```

sage: (mu - mu).valuation()
↳needs sage.libs.pari
+Infinity
sage: g = L(constant=1, valuation=2)
sage: g.valuation()
↳needs sage.symbolic
log(2)
sage: (g*g).valuation()
↳needs sage.symbolic
2*log(2)

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, "z")
>>> mu = L(moebius); mu.valuation()
↳needs sage.libs.pari
0
>>> (mu - mu).valuation()
↳needs sage.libs.pari
+Infinity
>>> g = L(constant=Integer(1), valuation=Integer(2))
>>> g.valuation()
↳needs sage.symbolic
log(2)
>>> (g*g).valuation()
↳needs sage.symbolic
2*log(2)

```

class sage.rings.lazy_series.LazyLaurentSeries (parent, coeff_stream)

Bases: *LazyCauchyProductSeries*

A Laurent series where the coefficients are computed lazily.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)

```

We can build a series from a function and specify if the series eventually takes a constant value:

```

sage: f = L(lambda i: i, valuation=-3, constant=-1, degree=3)
sage: f
-3*z^-3 - 2*z^-2 - z^-1 + z + 2*z^2 - z^3 - z^4 - z^5 + O(z^6)
sage: f[-2]
-2
sage: f[10]
-1
sage: f[-5]
0

sage: f = L(lambda i: i, valuation=-3)
sage: f

```

(continues on next page)

(continued from previous page)

```

-3*z^-3 - 2*z^-2 - z^-1 + z + 2*z^2 + 3*z^3 + O(z^4)
sage: f[20]
20

```

```

>>> from sage.all import *
>>> f = L(lambda i: i, valuation=-Integer(3), constant=-Integer(1),
↳degree=Integer(3))
>>> f
-3*z^-3 - 2*z^-2 - z^-1 + z + 2*z^2 - z^3 - z^4 - z^5 + O(z^6)
>>> f[-Integer(2)]
-2
>>> f[Integer(10)]
-1
>>> f[-Integer(5)]
0

>>> f = L(lambda i: i, valuation=-Integer(3))
>>> f
-3*z^-3 - 2*z^-2 - z^-1 + z + 2*z^2 + 3*z^3 + O(z^4)
>>> f[Integer(20)]
20

```

Anything that converts into a polynomial can be input, where we can also specify the valuation or if the series eventually takes a constant value:

```

sage: L([-5,2,0,5])
-5 + 2*z + 5*z^3
sage: L([-5,2,0,5], constant=6)
-5 + 2*z + 5*z^3 + 6*z^4 + 6*z^5 + 6*z^6 + O(z^7)
sage: L([-5,2,0,5], degree=6, constant=6)
-5 + 2*z + 5*z^3 + 6*z^6 + 6*z^7 + 6*z^8 + O(z^9)
sage: L([-5,2,0,5], valuation=-2, degree=3, constant=6)
-5*z^-2 + 2*z^-1 + 5*z + 6*z^3 + 6*z^4 + 6*z^5 + O(z^6)
sage: L([-5,2,0,5], valuation=5)
-5*z^5 + 2*z^6 + 5*z^8
sage: L({-2:9, 3:4}, constant=2, degree=5)
9*z^-2 + 4*z^3 + 2*z^5 + 2*z^6 + 2*z^7 + O(z^8)

```

```

>>> from sage.all import *
>>> L([-Integer(5), Integer(2), Integer(0), Integer(5)])
-5 + 2*z + 5*z^3
>>> L([-Integer(5), Integer(2), Integer(0), Integer(5)], constant=Integer(6))
-5 + 2*z + 5*z^3 + 6*z^4 + 6*z^5 + 6*z^6 + O(z^7)
>>> L([-Integer(5), Integer(2), Integer(0), Integer(5)], degree=Integer(6),
↳constant=Integer(6))
-5 + 2*z + 5*z^3 + 6*z^6 + 6*z^7 + 6*z^8 + O(z^9)
>>> L([-Integer(5), Integer(2), Integer(0), Integer(5)], valuation=-Integer(2),
↳degree=Integer(3), constant=Integer(6))
-5*z^-2 + 2*z^-1 + 5*z + 6*z^3 + 6*z^4 + 6*z^5 + O(z^6)
>>> L([-Integer(5), Integer(2), Integer(0), Integer(5)], valuation=Integer(5))
-5*z^5 + 2*z^6 + 5*z^8
>>> L({-Integer(2):Integer(9), Integer(3):Integer(4)}, constant=Integer(2),
↳

```

(continues on next page)

(continued from previous page)

```

↪degree=Integer(5))
9*z^-2 + 4*z^3 + 2*z^5 + 2*z^6 + 2*z^7 + O(z^8)

```

We can also perform arithmetic:

```

sage: f = 1 / (1 - z - z^2)
sage: f
1 + z + 2*z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
sage: f.coefficient(100)
573147844013817084101
sage: f = (z^-2 - 1 + 2*z) / (z^-1 - z + 3*z^2)
sage: f
z^-1 - z^2 - z^4 + 3*z^5 + O(z^6)

```

```

>>> from sage.all import *
>>> f = Integer(1) / (Integer(1) - z - z**Integer(2))
>>> f
1 + z + 2*z^2 + 3*z^3 + 5*z^4 + 8*z^5 + 13*z^6 + O(z^7)
>>> f.coefficient(Integer(100))
573147844013817084101
>>> f = (z**-Integer(2) - Integer(1) + Integer(2)*z) / (z**-Integer(1) - z + ↪
↪Integer(3)*z**Integer(2))
>>> f
z^-1 - z^2 - z^4 + 3*z^5 + O(z^6)

```

However, we may not always be able to know when a result is exactly a polynomial:

```

sage: f * (z^-1 - z + 3*z^2)
z^-2 - 1 + 2*z + O(z^5)

```

```

>>> from sage.all import *
>>> f * (z**-Integer(2) - z + Integer(3)*z**Integer(2))
z^-2 - 1 + 2*z + O(z^5)

```

`O(prec, name=None)`

alias of `approximate_series()`.

`add_bigoh(prec, name=None)`

alias of `approximate_series()`.

`approximate_series(prec, name=None)`

Return the Laurent series with absolute precision `prec` approximated from this series.

INPUT:

- `prec` – integer
- `name` – name of the variable; if it is `None`, the name of the variable of the series is used

OUTPUT: a Laurent series with absolute precision `prec`

EXAMPLES:

```

sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: z = L.gen()

```

(continues on next page)

(continued from previous page)

```

sage: f = (z - 2*z^3)^5/(1 - 2*z)
sage: f
z^5 + 2*z^6 - 6*z^7 - 12*z^8 + 16*z^9 + 32*z^10 - 16*z^11 + O(z^12)
sage: g = f.approximate_series(10)
sage: g
z^5 + 2*z^6 - 6*z^7 - 12*z^8 + 16*z^9 + O(z^10)
sage: g.parent()
Power Series Ring in z over Integer Ring
sage: h = (f^-1).approximate_series(3)
sage: h
z^-5 - 2*z^-4 + 10*z^-3 - 20*z^-2 + 60*z^-1 - 120 + 280*z - 560*z^2 + O(z^3)
sage: h.parent()
Laurent Series Ring in z over Integer Ring

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> z = L.gen()
>>> f = (z - Integer(2)*z**Integer(3))**Integer(5)/(Integer(1) - Integer(2)*z)
>>> f
z^5 + 2*z^6 - 6*z^7 - 12*z^8 + 16*z^9 + 32*z^10 - 16*z^11 + O(z^12)
>>> g = f.approximate_series(Integer(10))
>>> g
z^5 + 2*z^6 - 6*z^7 - 12*z^8 + 16*z^9 + O(z^10)
>>> g.parent()
Power Series Ring in z over Integer Ring
>>> h = (f**-Integer(1)).approximate_series(Integer(3))
>>> h
z^-5 - 2*z^-4 + 10*z^-3 - 20*z^-2 + 60*z^-1 - 120 + 280*z - 560*z^2 + O(z^3)
>>> h.parent()
Laurent Series Ring in z over Integer Ring

```

compose(g)

Return the composition of self with g.

Given two Laurent series f and g over the same base ring, the composition $(f \circ g)(z) = f(g(z))$ is defined if and only if:

- $g = 0$ and $\text{val}(f) \geq 0$,
- g is nonzero and f has only finitely many nonzero coefficients,
- g is nonzero and $\text{val}(g) > 0$.

INPUT:

- g – other series

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: f = z^2 + 1 + z
sage: f(0)
1
sage: f(L(0))
1

```

(continues on next page)

(continued from previous page)

```

sage: f(f)
3 + 3*z + 4*z^2 + 2*z^3 + z^4
sage: g = z^-3/(1-2*z); g
z^-3 + 2*z^-2 + 4*z^-1 + 8 + 16*z + 32*z^2 + 64*z^3 + O(z^4)
sage: f(g)
z^-6 + 4*z^-5 + 12*z^-4 + 33*z^-3 + 82*z^-2 + 196*z^-1 + 457 + O(z)
sage: g^2 + 1 + g
z^-6 + 4*z^-5 + 12*z^-4 + 33*z^-3 + 82*z^-2 + 196*z^-1 + 457 + O(z)
sage: f(int(2))
7

sage: f = z^-2 + z + 4*z^3
sage: f(f)
4*z^-6 + 12*z^-3 + z^-2 + 48*z^-1 + 12 + O(z)
sage: f^-2 + f + 4*f^3
4*z^-6 + 12*z^-3 + z^-2 + 48*z^-1 + 12 + O(z)
sage: f(g)
4*z^-9 + 24*z^-8 + 96*z^-7 + 320*z^-6 + 960*z^-5 + 2688*z^-4 + 7169*z^-3 +
↳ O(z^-2)
sage: g^-2 + g + 4*g^3
4*z^-9 + 24*z^-8 + 96*z^-7 + 320*z^-6 + 960*z^-5 + 2688*z^-4 + 7169*z^-3 +
↳ O(z^-2)

sage: f = z^-3 + z^-2 + 1 / (1 + z^2); f
z^-3 + z^-2 + 1 - z^2 + O(z^4)
sage: g = z^3 / (1 + z - z^3); g
z^3 - z^4 + z^5 - z^7 + 2*z^8 - 2*z^9 + O(z^10)
sage: f(g)
z^-9 + 3*z^-8 + 3*z^-7 - z^-6 - 4*z^-5 - 2*z^-4 + z^-3 + O(z^-2)
sage: g^-3 + g^-2 + 1 / (1 + g^2)
z^-9 + 3*z^-8 + 3*z^-7 - z^-6 - 4*z^-5 - 2*z^-4 + z^-3 + O(z^-2)

sage: f = z^-3
sage: g = z^-2 + z^-1
sage: g^(-3)
z^6 - 3*z^7 + 6*z^8 - 10*z^9 + 15*z^10 - 21*z^11 + 28*z^12 + O(z^13)
sage: f(g)
z^6 - 3*z^7 + 6*z^8 - 10*z^9 + 15*z^10 - 21*z^11 + 28*z^12 + O(z^13)

sage: f = z^2 + z^3
sage: g = z^-3 + z^-2
sage: f^-3 + f^-2
z^-6 - 3*z^-5 + 7*z^-4 - 12*z^-3 + 18*z^-2 - 25*z^-1 + 33 + O(z)
sage: g(f)
z^-6 - 3*z^-5 + 7*z^-4 - 12*z^-3 + 18*z^-2 - 25*z^-1 + 33 + O(z)
sage: g^2 + g^3
z^-9 + 3*z^-8 + 3*z^-7 + 2*z^-6 + 2*z^-5 + z^-4
sage: f(g)
z^-9 + 3*z^-8 + 3*z^-7 + 2*z^-6 + 2*z^-5 + z^-4

sage: f = L(lambda n: n, valuation=0); f
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)

```

(continues on next page)

(continued from previous page)

```

sage: f(z^2)
z^2 + 2*z^4 + 3*z^6 + 4*z^8 + O(z^9)

sage: f = L(lambd n: n, valuation=-2); f
-2*z^-2 - z^-1 + z + 2*z^2 + 3*z^3 + 4*z^4 + O(z^5)

sage: f3 = f(z^3); f3
-2*z^-6 - z^-3 + O(z)

sage: [f3[i] for i in range(-6,13)]
[-2, 0, 0, -1, 0, 0, 0, 0, 0, 1, 0, 0, 2, 0, 0, 3, 0, 0, 4]

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = z**Integer(2) + Integer(1) + z
>>> f(Integer(0))
1
>>> f(L(Integer(0)))
1
>>> f(f)
3 + 3*z + 4*z^2 + 2*z^3 + z^4
>>> g = z**(-Integer(3))/(Integer(1)-Integer(2)*z); g
z^-3 + 2*z^-2 + 4*z^-1 + 8 + 16*z + 32*z^2 + 64*z^3 + O(z^4)
>>> f(g)
z^-6 + 4*z^-5 + 12*z^-4 + 33*z^-3 + 82*z^-2 + 196*z^-1 + 457 + O(z)
>>> g**Integer(2) + g
z^-6 + 4*z^-5 + 12*z^-4 + 33*z^-3 + 82*z^-2 + 196*z^-1 + 457 + O(z)
>>> f(int(Integer(2)))
7

>>> f = z**(-Integer(2)) + z + Integer(4)*z**Integer(3)
>>> f(f)
4*z^-6 + 12*z^-3 + z^-2 + 48*z^-1 + 12 + O(z)
>>> f**(-Integer(2)) + f + Integer(4)*f**Integer(3)
4*z^-6 + 12*z^-3 + z^-2 + 48*z^-1 + 12 + O(z)
>>> f(g)
4*z^-9 + 24*z^-8 + 96*z^-7 + 320*z^-6 + 960*z^-5 + 2688*z^-4 + 7169*z^-3 +
↳ O(z^-2)
>>> g**(-Integer(2)) + g + Integer(4)*g**Integer(3)
4*z^-9 + 24*z^-8 + 96*z^-7 + 320*z^-6 + 960*z^-5 + 2688*z^-4 + 7169*z^-3 +
↳ O(z^-2)

>>> f = z**(-Integer(3)) + z**(-Integer(2)) + Integer(1) / (Integer(1) +
↳ z**Integer(2)); f
z^-3 + z^-2 + 1 - z^2 + O(z^4)
>>> g = z**Integer(3) / (Integer(1) + z - z**Integer(3)); g
z^3 - z^4 + z^5 - z^7 + 2*z^8 - 2*z^9 + O(z^10)
>>> f(g)
z^-9 + 3*z^-8 + 3*z^-7 - z^-6 - 4*z^-5 - 2*z^-4 + z^-3 + O(z^-2)
>>> g**(-Integer(3)) + g**(-Integer(2)) + Integer(1) / (Integer(1) +
↳ g**Integer(2))
z^-9 + 3*z^-8 + 3*z^-7 - z^-6 - 4*z^-5 - 2*z^-4 + z^-3 + O(z^-2)

>>> f = z**(-Integer(3))

```

(continues on next page)

(continued from previous page)

```

>>> g = z**Integer(2) + z**Integer(1)
>>> g**(-Integer(3))
z^6 - 3*z^7 + 6*z^8 - 10*z^9 + 15*z^10 - 21*z^11 + 28*z^12 + O(z^13)
>>> f(g)
z^6 - 3*z^7 + 6*z^8 - 10*z^9 + 15*z^10 - 21*z^11 + 28*z^12 + O(z^13)

>>> f = z**Integer(2) + z**Integer(3)
>>> g = z**Integer(3) + z**Integer(2)
>>> f**Integer(3) + f**Integer(2)
z^-6 - 3*z^-5 + 7*z^-4 - 12*z^-3 + 18*z^-2 - 25*z^-1 + 33 + O(z)
>>> g(f)
z^-6 - 3*z^-5 + 7*z^-4 - 12*z^-3 + 18*z^-2 - 25*z^-1 + 33 + O(z)
>>> g**Integer(2) + g**Integer(3)
z^-9 + 3*z^-8 + 3*z^-7 + 2*z^-6 + 2*z^-5 + z^-4
>>> f(g)
z^-9 + 3*z^-8 + 3*z^-7 + 2*z^-6 + 2*z^-5 + z^-4

>>> f = L(lambda n: n, valuation=Integer(0)); f
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> f(z**Integer(2))
z^2 + 2*z^4 + 3*z^6 + 4*z^8 + O(z^9)

>>> f = L(lambda n: n, valuation=-Integer(2)); f
-2*z^-2 - z^-1 + z + 2*z^2 + 3*z^3 + 4*z^4 + O(z^5)
>>> f3 = f(z**Integer(3)); f3
-2*z^-6 - z^-3 + O(z)
>>> [f3[i] for i in range(-Integer(6), Integer(13))]
[-2, 0, 0, -1, 0, 0, 0, 0, 0, 1, 0, 0, 2, 0, 0, 3, 0, 0, 4]

```

We compose a Laurent polynomial with a generic element:

```

sage: R.<x> = QQ[]
sage: f = z^2 + 1 + z^-1
sage: g = x^2 + x + 3
sage: f(g)
(x^6 + 3*x^5 + 12*x^4 + 19*x^3 + 37*x^2 + 28*x + 31)/(x^2 + x + 3)
sage: f(g) == g^2 + 1 + g^-1
True

```

```

>>> from sage.all import *
>>> R = QQ['x']; (x,) = R._first_ngens(1)
>>> f = z**Integer(2) + Integer(1) + z**Integer(1)
>>> g = x**Integer(2) + x + Integer(3)
>>> f(g)
(x^6 + 3*x^5 + 12*x^4 + 19*x^3 + 37*x^2 + 28*x + 31)/(x^2 + x + 3)
>>> f(g) == g**Integer(2) + Integer(1) + g**Integer(1)
True

```

We compose with another lazy Laurent series:

```

sage: LS.<y> = LazyLaurentSeriesRing(QQ)
sage: f = z^2 + 1 + z^-1

```

(continues on next page)

(continued from previous page)

```

sage: fy = f(y); fy
y^-1 + 1 + y^2
sage: fy.parent() is LS
True
sage: g = y - y
sage: f(g)
Traceback (most recent call last):
...
ZeroDivisionError: the valuation of the series must be nonnegative

sage: g = 1 - y
sage: f(g)
3 - y + 2*y^2 + y^3 + y^4 + y^5 + O(y^6)
sage: g^2 + 1 + g^-1
3 - y + 2*y^2 + y^3 + y^4 + y^5 + O(y^6)

sage: f = L(lambda n: n, valuation=0); f
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: f(0)
0
sage: f(y)
y + 2*y^2 + 3*y^3 + 4*y^4 + 5*y^5 + 6*y^6 + 7*y^7 + O(y^8)
sage: fp = f(y - y)
sage: fp == 0
True
sage: fp.parent() is LS
True

sage: f = z^2 + 3 + z
sage: f(y - y)
3

```

```

>>> from sage.all import *
>>> LS = LazyLaurentSeriesRing(QQ, names=('y',)); (y,) = LS._first_ngens(1)
>>> f = z**Integer(2) + Integer(1) + z**Integer(1)
>>> fy = f(y); fy
y^-1 + 1 + y^2
>>> fy.parent() is LS
True
>>> g = y - y
>>> f(g)
Traceback (most recent call last):
...
ZeroDivisionError: the valuation of the series must be nonnegative

>>> g = Integer(1) - y
>>> f(g)
3 - y + 2*y^2 + y^3 + y^4 + y^5 + O(y^6)
>>> g**Integer(2) + Integer(1) + g**Integer(1)
3 - y + 2*y^2 + y^3 + y^4 + y^5 + O(y^6)

>>> f = L(lambda n: n, valuation=Integer(0)); f

```

(continues on next page)

(continued from previous page)

```

z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> f(Integer(0))
0
>>> f(y)
y + 2*y^2 + 3*y^3 + 4*y^4 + 5*y^5 + 6*y^6 + 7*y^7 + O(y^8)
>>> fp = f(y - y)
>>> fp == Integer(0)
True
>>> fp.parent() is LS
True

>>> f = z**Integer(2) + Integer(3) + z
>>> f(y - y)
3

```

With both of them sparse:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ, sparse=True)
sage: LS.<y> = LazyLaurentSeriesRing(QQ, sparse=True)
sage: f = L(lambda n: 1, valuation=0); f
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
sage: f(y^2)
1 + y^2 + y^4 + y^6 + O(y^7)

sage: fp = f - 1 + z^-2; fp
z^-2 + z + z^2 + z^3 + z^4 + O(z^5)
sage: fpy = fp(y^2); fpy
y^-4 + y^2 + O(y^3)
sage: fpy.parent() is LS
True
sage: [fpy[i] for i in range(-4,11)]
[1, 0, 0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1]

sage: g = LS(valuation=2, constant=1); g
y^2 + y^3 + y^4 + O(y^5)
sage: fg = f(g); fg
1 + y^2 + y^3 + 2*y^4 + 3*y^5 + 5*y^6 + O(y^7)
sage: 1 + g + g^2 + g^3 + g^4 + g^5 + g^6
1 + y^2 + y^3 + 2*y^4 + 3*y^5 + 5*y^6 + O(y^7)

sage: h = LS(lambda n: 1 if n % 2 else 0, valuation=2); h
y^3 + y^5 + y^7 + O(y^9)
sage: fgh = fg(h); fgh
1 + y^6 + O(y^7)
sage: [fgh[i] for i in range(0, 15)]
[1, 0, 0, 0, 0, 0, 1, 0, 2, 1, 3, 3, 6, 6, 13]
sage: t = 1 + h^2 + h^3 + 2*h^4 + 3*h^5 + 5*h^6
sage: [t[i] for i in range(0, 15)]
[1, 0, 0, 0, 0, 0, 1, 0, 2, 1, 3, 3, 6, 6, 13]

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, sparse=True, names=('z',)); (z,) = L._first_

```

(continues on next page)

(continued from previous page)

```

↪ngens(1)
>>> LS = LazyLaurentSeriesRing(QQ, sparse=True, names=('y',)); (y,) = LS._
↪first_ngens(1)
>>> f = L(lambda n: Integer(1), valuation=Integer(0)); f
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
>>> f(y**Integer(2))
1 + y^2 + y^4 + y^6 + O(y^7)

>>> fp = f - Integer(1) + z**Integer(-2); fp
z^-2 + z + z^2 + z^3 + z^4 + O(z^5)
>>> fpy = fp(y**Integer(2)); fpy
y^-4 + y^2 + O(y^3)
>>> fpy.parent() is LS
True
>>> [fpy[i] for i in range(-Integer(4), Integer(11))]
[1, 0, 0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1]

>>> g = LS(valuation=Integer(2), constant=Integer(1)); g
y^2 + y^3 + y^4 + O(y^5)
>>> fg = f(g); fg
1 + y^2 + y^3 + 2*y^4 + 3*y^5 + 5*y^6 + O(y^7)
>>> Integer(1) + g + g**Integer(2) + g**Integer(3) + g**Integer(4) +
↪g**Integer(5) + g**Integer(6)
1 + y^2 + y^3 + 2*y^4 + 3*y^5 + 5*y^6 + O(y^7)

>>> h = LS(lambda n: Integer(1) if n % Integer(2) else Integer(0),
↪valuation=Integer(2)); h
y^3 + y^5 + y^7 + O(y^9)
>>> fgh = fg(h); fgh
1 + y^6 + O(y^7)
>>> [fgh[i] for i in range(Integer(0), Integer(15))]
[1, 0, 0, 0, 0, 0, 1, 0, 2, 1, 3, 3, 6, 6, 13]
>>> t = Integer(1) + h**Integer(2) + h**Integer(3) + Integer(2)*h**Integer(4)
↪+ Integer(3)*h**Integer(5) + Integer(5)*h**Integer(6)
>>> [t[i] for i in range(Integer(0), Integer(15))]
[1, 0, 0, 0, 0, 0, 1, 0, 2, 1, 3, 3, 6, 6, 13]

```

We look at mixing the sparse and the dense:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: f = L(lambda n: 1, valuation=0); f
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
sage: g = LS(lambda n: 1, valuation=1); g
y + y^2 + y^3 + y^4 + y^5 + y^6 + y^7 + O(y^8)
sage: f(g)
1 + y + 2*y^2 + 4*y^3 + 8*y^4 + 16*y^5 + 32*y^6 + O(y^7)

sage: f = z^-2 + 1 + z
sage: g = 1/(y*(1-y)); g
y^-1 + 1 + y + O(y^2)
sage: f(g)
y^-1 + 2 + y + 2*y^2 - y^3 + 2*y^4 + y^5 + y^6 + y^7 + O(y^8)

```

(continues on next page)

(continued from previous page)

```

sage: g^-2 + 1 + g == f(g)
True

sage: f = z^-3 + z^-2 + 1
sage: g = 1/(y^2*(1-y)); g
y^-2 + y^-1 + 1 + O(y)
sage: f(g)
1 + y^4 - 2*y^5 + 2*y^6 - 3*y^7 + 3*y^8 - y^9
sage: g^-3 + g^-2 + 1 == f(g)
True
sage: z(y)
y

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L(lambda n: Integer(1), valuation=Integer(0)); f
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
>>> g = LS(lambda n: Integer(1), valuation=Integer(1)); g
y + y^2 + y^3 + y^4 + y^5 + y^6 + y^7 + O(y^8)
>>> f(g)
1 + y + 2*y^2 + 4*y^3 + 8*y^4 + 16*y^5 + 32*y^6 + O(y^7)

>>> f = z**Integer(2) + Integer(1) + z
>>> g = Integer(1)/(y*(Integer(1)-y)); g
y^-1 + 1 + y + O(y^2)
>>> f(g)
y^-1 + 2 + y + 2*y^2 - y^3 + 2*y^4 + y^5 + y^6 + y^7 + O(y^8)
>>> g**Integer(2) + Integer(1) + g == f(g)
True

>>> f = z**Integer(3) + z**Integer(2) + Integer(1)
>>> g = Integer(1)/(y**Integer(2)*(Integer(1)-y)); g
y^-2 + y^-1 + 1 + O(y)
>>> f(g)
1 + y^4 - 2*y^5 + 2*y^6 - 3*y^7 + 3*y^8 - y^9
>>> g**Integer(3) + g**Integer(2) + Integer(1) == f(g)
True
>>> z(y)
y

```

We look at cases where the composition does not exist. $g = 0$ and $\text{val}(f) < 0$:

```

sage: g = L(0)
sage: f = z^-1 + z^-2
sage: f.valuation() < 0
True
sage: f(g)
Traceback (most recent call last):
...
ZeroDivisionError: the valuation of the series must be nonnegative

```

```

>>> from sage.all import *
>>> g = L(Integer(0))
>>> f = z**Integer(1) + z**Integer(2)
>>> f.valuation() < Integer(0)
True
>>> f(g)
Traceback (most recent call last):
...
ZeroDivisionError: the valuation of the series must be nonnegative

```

$g \neq 0$ and $\text{val}(g) \leq 0$ and f has infinitely many nonzero coefficients:

```

sage: g = z^-1 + z^-2
sage: g.valuation() <= 0
True
sage: f = L(lambda n: n, valuation=0)
sage: f(g)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

sage: f = L(lambda n: n, valuation=1)
sage: f(1 + z)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

```

```

>>> from sage.all import *
>>> g = z**Integer(1) + z**Integer(2)
>>> g.valuation() <= Integer(0)
True
>>> f = L(lambda n: n, valuation=Integer(0))
>>> f(g)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

>>> f = L(lambda n: n, valuation=Integer(1))
>>> f(Integer(1) + z)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

```

We compose the exponential with a Dirichlet series:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: e = L(lambda n: 1/factorial(n), 0)
sage: D = LazyDirichletSeriesRing(QQ, "s")
sage: g = D(constant=1)-1
sage: g
↪needs sage.symbolic
1/(2^s) + 1/(3^s) + 1/(4^s) + O(1/(5^s))

```

#

(continues on next page)

(continued from previous page)

```

sage: e(g)[0:10]
[0, 1, 1, 1, 3/2, 1, 2, 1, 13/6, 3/2]

sage: sum(g^k/factorial(k) for k in range(10))[0:10]
[0, 1, 1, 1, 3/2, 1, 2, 1, 13/6, 3/2]

sage: g = D([0,1,0,1,1,2])
sage: g
↳needs sage.symbolic
1/(2^s) + 1/(4^s) + 1/(5^s) + 2/6^s
sage: e(g)[0:10]
[0, 1, 1, 0, 3/2, 1, 2, 0, 7/6, 0]
sage: sum(g^k/factorial(k) for k in range(10))[0:10]
[0, 1, 1, 0, 3/2, 1, 2, 0, 7/6, 0]

sage: e(D([1,0,1]))
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

sage: e5 = L(e, degree=5)
sage: e5
1 + z + 1/2*z^2 + 1/6*z^3 + 1/24*z^4
sage: e5(g)
↳needs sage.symbolic
1 + 1/(2^s) + 3/2/4^s + 1/(5^s) + 2/6^s + O(1/(8^s))
sage: sum(e5[k] * g^k for k in range(5))
↳needs sage.symbolic
1 + 1/(2^s) + 3/2/4^s + 1/(5^s) + 2/6^s + O(1/(8^s))

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> e = L(lambda n: Integer(1)/factorial(n), Integer(0))
>>> D = LazyDirichletSeriesRing(QQ, "s")
>>> g = D(constant=Integer(1))-Integer(1)
>>> g
↳needs sage.symbolic
1/(2^s) + 1/(3^s) + 1/(4^s) + O(1/(5^s))

>>> e(g)[Integer(0):Integer(10)]
[0, 1, 1, 1, 3/2, 1, 2, 1, 13/6, 3/2]

>>> sum(g**k/factorial(k) for k in range(Integer(10)))[Integer(0):Integer(10)]
[0, 1, 1, 1, 3/2, 1, 2, 1, 13/6, 3/2]

>>> g = D([Integer(0),Integer(1),Integer(0),Integer(1),Integer(1),Integer(2)])
>>> g
↳needs sage.symbolic
1/(2^s) + 1/(4^s) + 1/(5^s) + 2/6^s
>>> e(g)[Integer(0):Integer(10)]
[0, 1, 1, 0, 3/2, 1, 2, 0, 7/6, 0]
>>> sum(g**k/factorial(k) for k in range(Integer(10)))[Integer(0):Integer(10)]

```

(continues on next page)

(continued from previous page)

```
[0, 1, 1, 0, 3/2, 1, 2, 0, 7/6, 0]

>>> e(D([Integer(1), Integer(0), Integer(1)]))
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

>>> e5 = L(e, degree=Integer(5))
>>> e5
1 + z + 1/2*z^2 + 1/6*z^3 + 1/24*z^4
>>> e5(g) #_
↳ needs sage.symbolic
1 + 1/(2^s) + 3/2/4^s + 1/(5^s) + 2/6^s + O(1/(8^s))
>>> sum(e5[k] * g**k for k in range(Integer(5))) _
↳ # needs sage.symbolic
1 + 1/(2^s) + 3/2/4^s + 1/(5^s) + 2/6^s + O(1/(8^s))
```

The output parent is always the common parent between the base ring of f and the parent of g or extended to the corresponding lazy series:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: R.<x> = ZZ[]
sage: parent(z(x))
Univariate Polynomial Ring in x over Rational Field
sage: parent(z(R.zero()))
Univariate Polynomial Ring in x over Rational Field
sage: parent(z(0))
Rational Field
sage: f = 1 / (1 - z)
sage: f(x)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + O(x^7)
sage: three = L(3)(x^2); three
3
sage: parent(three)
Univariate Polynomial Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> R = ZZ['x']; (x,) = R._first_ngens(1)
>>> parent(z(x))
Univariate Polynomial Ring in x over Rational Field
>>> parent(z(R.zero()))
Univariate Polynomial Ring in x over Rational Field
>>> parent(z(Integer(0)))
Rational Field
>>> f = Integer(1) / (Integer(1) - z)
>>> f(x)
1 + x + x^2 + x^3 + x^4 + x^5 + x^6 + O(x^7)
>>> three = L(Integer(3))(x**Integer(2)); three
3
>>> parent(three)
Univariate Polynomial Ring in x over Rational Field
```

Consistency check when g is an uninitialized series between a polynomial f as both a polynomial and a lazy series:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: f = 1 + z
sage: g = L.undefined(valuation=0)
sage: f(g) == f.polynomial()(g)
True
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = Integer(1) + z
>>> g = L.undefined(valuation=Integer(0))
>>> f(g) == f.polynomial()(g)
True
```

compositional_inverse()

alias of `revert()`.

derivative(*args)

Return the derivative of the Laurent series.

Multiple variables and iteration counts may be supplied; see the documentation of `sage.calculus.functional.derivative()` function for details.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: z.derivative()
1
sage: (1+z+z^2).derivative(3)
0
sage: (1/z).derivative()
-z^-2
sage: (1/(1-z)).derivative(z)
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> z.derivative()
1
>>> (Integer(1)+z+z**Integer(2)).derivative(Integer(3))
0
>>> (Integer(1)/z).derivative()
-z^-2
>>> (Integer(1)/(Integer(1)-z)).derivative(z)
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
```

integral(variable, constants=None)

Return the integral of `self` with respect to `variable`.

INPUT:

- `variable` – (optional) the variable to integrate

- `constants` – (optional; keyword-only) list of integration constants for the integrals of `self` (the last constant corresponds to the first integral)

If the first argument is a list, then this method interprets it as integration constants. If it is a positive integer, the method interprets it as the number of times to integrate the function. If `variable` is not the variable of the Laurent series, then the coefficients are integrated with respect to `variable`.

If the integration constants are not specified, they are considered to be 0.

EXAMPLES:

```
sage: L.<t> = LazyLaurentSeriesRing(QQ)
sage: f = t^-3 + 2 + 3*t + t^5
sage: f.integral()
-1/2*t^-2 + 2*t + 3/2*t^2 + 1/6*t^6
sage: f.integral([-2, -2])
1/2*t^-1 - 2 - 2*t + t^2 + 1/2*t^3 + 1/42*t^7
sage: f.integral(t)
-1/2*t^-2 + 2*t + 3/2*t^2 + 1/6*t^6
sage: f.integral(2)
1/2*t^-1 + t^2 + 1/2*t^3 + 1/42*t^7
sage: L.zero().integral()
0
sage: L.zero().integral([0, 1, 2, 3])
t + t^2 + 1/2*t^3
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('t',)); (t,) = L._first_ngens(1)
>>> f = t**Integer(3) + Integer(2) + Integer(3)*t + t**Integer(5)
>>> f.integral()
-1/2*t^-2 + 2*t + 3/2*t^2 + 1/6*t^6
>>> f.integral([-Integer(2), -Integer(2)])
1/2*t^-1 - 2 - 2*t + t^2 + 1/2*t^3 + 1/42*t^7
>>> f.integral(t)
-1/2*t^-2 + 2*t + 3/2*t^2 + 1/6*t^6
>>> f.integral(Integer(2))
1/2*t^-1 + t^2 + 1/2*t^3 + 1/42*t^7
>>> L.zero().integral()
0
>>> L.zero().integral([Integer(0), Integer(1), Integer(2), Integer(3)])
t + t^2 + 1/2*t^3
```

We solve the ODE $f' = af$ by integrating both sides and the recursive definition:

```
sage: R.<a, C> = QQ[]
sage: L.<x> = LazyLaurentSeriesRing(R)
sage: f = L.undefined(0)
sage: f.define((a*f).integral(constants=[C]))
sage: f
C + a*C*x + 1/2*a^2*C*x^2 + 1/6*a^3*C*x^3 + 1/24*a^4*C*x^4
+ 1/120*a^5*C*x^5 + 1/720*a^6*C*x^6 + O(x^7)
sage: C * exp(a*x)
C + a*C*x + 1/2*a^2*C*x^2 + 1/6*a^3*C*x^3 + 1/24*a^4*C*x^4
+ 1/120*a^5*C*x^5 + 1/720*a^6*C*x^6 + O(x^7)
```

```

>>> from sage.all import *
>>> R = QQ['a, C']; (a, C,) = R._first_ngens(2)
>>> L = LazyLaurentSeriesRing(R, names=('x',)); (x,) = L._first_ngens(1)
>>> f = L.undefine(Integer(0))
>>> f.define((a*f).integral(constants=[C]))
>>> f
C + a*C*x + 1/2*a^2*C*x^2 + 1/6*a^3*C*x^3 + 1/24*a^4*C*x^4
+ 1/120*a^5*C*x^5 + 1/720*a^6*C*x^6 + O(x^7)
>>> C * exp(a*x)
C + a*C*x + 1/2*a^2*C*x^2 + 1/6*a^3*C*x^3 + 1/24*a^4*C*x^4
+ 1/120*a^5*C*x^5 + 1/720*a^6*C*x^6 + O(x^7)

```

We can integrate both the series and coefficients:

```

sage: R.<x,y,z> = QQ[]
sage: L.<t> = LazyLaurentSeriesRing(R)
sage: f = (x*t^2 + y*t^-2 + z)^2; f
y^2*t^-4 + 2*y*z*t^-2 + (2*x*y + z^2) + 2*x*z*t^2 + x^2*t^4
sage: f.integral(x)
x*y^2*t^-4 + 2*x*y*z*t^-2 + (x^2*y + x*z^2) + x^2*z*t^2 + 1/3*x^3*t^4
sage: f.integral(t)
-1/3*y^2*t^-3 - 2*y*z*t^-1 + (2*x*y + z^2)*t + 2/3*x*z*t^3 + 1/5*x^2*t^5
sage: f.integral(y, constants=[x*y*z])
-1/9*y^3*t^-3 - y^2*z*t^-1 + x*y*z + (x*y^2 + y*z^2)*t + 2/3*x*y*z*t^3 + 1/
↪ 5*x^2*y*t^5

```

```

>>> from sage.all import *
>>> R = QQ['x, y, z']; (x, y, z,) = R._first_ngens(3)
>>> L = LazyLaurentSeriesRing(R, names=('t',)); (t,) = L._first_ngens(1)
>>> f = (x*t**Integer(2) + y*t**-Integer(2) + z)**Integer(2); f
y^2*t^-4 + 2*y*z*t^-2 + (2*x*y + z^2) + 2*x*z*t^2 + x^2*t^4
>>> f.integral(x)
x*y^2*t^-4 + 2*x*y*z*t^-2 + (x^2*y + x*z^2) + x^2*z*t^2 + 1/3*x^3*t^4
>>> f.integral(t)
-1/3*y^2*t^-3 - 2*y*z*t^-1 + (2*x*y + z^2)*t + 2/3*x*z*t^3 + 1/5*x^2*t^5
>>> f.integral(y, constants=[x*y*z])
-1/9*y^3*t^-3 - y^2*z*t^-1 + x*y*z + (x*y^2 + y*z^2)*t + 2/3*x*y*z*t^3 + 1/
↪ 5*x^2*y*t^5

```

is_unit()

Return whether this element is a unit in the ring.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: (2*z).is_unit()
False

sage: (1 + 2*z).is_unit()
True

sage: (1 + 2*z^-1).is_unit()
False

```

(continues on next page)

(continued from previous page)

```
sage: (z^3 + 4 - z^-2).is_unit()
True
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> (Integer(2)*z).is_unit()
False

>>> (Integer(1) + Integer(2)*z).is_unit()
True

>>> (Integer(1) + Integer(2)*z**Integer(1)).is_unit()
False

>>> (z**Integer(3) + Integer(4) - z**Integer(2)).is_unit()
True
```

polynomial (*degree=None, name=None*)

Return `self` as a Laurent polynomial if `self` is actually so.

INPUT:

- `degree` – `None` or an integer
- `name` – name of the variable; if it is `None`, the name of the variable of the series is used

OUTPUT:

A Laurent polynomial if the valuation of the series is negative or a polynomial otherwise.

If `degree` is not `None`, the terms of the series of degree greater than `degree` are first truncated. If `degree` is `None` and the series is not a polynomial or a Laurent polynomial, a `ValueError` is raised.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: f = L([1,0,0,2,0,0,0,3], valuation=5); f
z^5 + 2*z^8 + 3*z^12
sage: f.polynomial()
3*z^12 + 2*z^8 + z^5
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L([Integer(1), Integer(0), Integer(0), Integer(2), Integer(0), Integer(0),
↪ Integer(0), Integer(3)], valuation=Integer(5)); f
z^5 + 2*z^8 + 3*z^12
>>> f.polynomial()
3*z^12 + 2*z^8 + z^5
```

revert ()

Return the compositional inverse of `self`.

Given a Laurent series f , the compositional inverse is a Laurent series g over the same base ring, such that $(f \circ g)(z) = f(g(z)) = z$.

The compositional inverse exists if and only if:

- $\text{val}(f) = 1$, or
- $f = a + bz$ with $a, b \neq 0$, or
- $f = a/z$ with $a \neq 0$.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: (2*z).revert()
1/2*z
sage: (2/z).revert()
2*z^-1
sage: (z-z^2).revert()
z + z^2 + 2*z^3 + 5*z^4 + 14*z^5 + 42*z^6 + 132*z^7 + O(z^8)

sage: s = L(degree=1, constant=-1)
sage: s.revert()
-z - z^2 - z^3 + O(z^4)

sage: s = L(degree=1, constant=1)
sage: s.revert()
z - z^2 + z^3 - z^4 + z^5 - z^6 + z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> (Integer(2)*z).revert()
1/2*z
>>> (Integer(2)/z).revert()
2*z^-1
>>> (z-z**Integer(2)).revert()
z + z^2 + 2*z^3 + 5*z^4 + 14*z^5 + 42*z^6 + 132*z^7 + O(z^8)

>>> s = L(degree=Integer(1), constant=-Integer(1))
>>> s.revert()
-z - z^2 - z^3 + O(z^4)

>>> s = L(degree=Integer(1), constant=Integer(1))
>>> s.revert()
z - z^2 + z^3 - z^4 + z^5 - z^6 + z^7 + O(z^8)
```

Warning

For series not known to be eventually constant (e.g., being defined by a function) with approximate valuation ≤ 1 (but not necessarily its true valuation), this assumes that this is the actual valuation:

```
sage: f = L(lambda n: n if n > 2 else 0, valuation=1)
sage: f.revert()
<repr(... failed: ValueError: inverse does not exist>
```

```
>>> from sage.all import *
>>> f = L(lambda n: n if n > Integer(2) else Integer(0), valuation=Integer(1))
>>> f.revert()
<repr(... failed: ValueError: inverse does not exist>
```

```
class sage.rings.lazy_series.LazyModuleElement (parent, coeff_stream)
```

Bases: `Element`

A lazy sequence with a module structure given by term-wise addition and scalar multiplication.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: M = L(lambda n: n, valuation=0)
sage: N = L(lambda n: 1, valuation=0)
sage: M[0:10]
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
sage: N[0:10]
[1, 1, 1, 1, 1, 1, 1, 1, 1, 1]
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> M = L(lambda n: n, valuation=Integer(0))
>>> N = L(lambda n: Integer(1), valuation=Integer(0))
>>> M[Integer(0):Integer(10)]
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
>>> N[Integer(0):Integer(10)]
[1, 1, 1, 1, 1, 1, 1, 1, 1, 1]
```

Two sequences can be added:

```
sage: O = M + N
sage: O[0:10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

```
>>> from sage.all import *
>>> O = M + N
>>> O[Integer(0):Integer(10)]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

Two sequences can be subtracted:

```
sage: P = M - N
sage: P[0:10]
[-1, 0, 1, 2, 3, 4, 5, 6, 7, 8]
```

```
>>> from sage.all import *
>>> P = M - N
>>> P[Integer(0):Integer(10)]
[-1, 0, 1, 2, 3, 4, 5, 6, 7, 8]
```

A sequence can be multiplied by a scalar:

```
sage: Q = 2 * M
sage: Q[0:10]
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
```

```
>>> from sage.all import *
>>> Q = Integer(2) * M
>>> Q[Integer(0):Integer(10)]
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
```

The negation of a sequence can also be found:

```
sage: R = -M
sage: R[0:10]
[0, -1, -2, -3, -4, -5, -6, -7, -8, -9]
```

```
>>> from sage.all import *
>>> R = -M
>>> R[Integer(0):Integer(10)]
[0, -1, -2, -3, -4, -5, -6, -7, -8, -9]
```

arccos()

Return the arccosine of self.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(RR)
sage: arccos(z) #_
↳needs sage.symbolic
1.57079632679490 - 1.000000000000000*z + 0.000000000000000*z^2
- 0.166666666666667*z^3 + 0.000000000000000*z^4
- 0.0750000000000000*z^5 + O(1.000000000000000*z^7)

sage: L.<z> = LazyLaurentSeriesRing(SR) #_
↳needs sage.symbolic
sage: arccos(z/(1-z)) #_
↳needs sage.symbolic
1/2*pi - z - z^2 - 7/6*z^3 - 3/2*z^4 - 83/40*z^5 - 73/24*z^6 + O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(SR) #_
↳needs sage.symbolic
sage: arccos(x/(1-y)) #_
↳needs sage.symbolic
1/2*pi + (-x) + (-x*y) + ((-1/6)*x^3-x*y^2) + ((-1/2)*x^3*y-x*y^3)
+ ((-3/40)*x^5-x^3*y^2-x*y^4) + ((-3/8)*x^5*y+(-5/3)*x^3*y^3-x*y^5) + O(x,y)^
↳7
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(RR, names=('z',)); (z,) = L._first_ngens(1)
>>> arccos(z) #_
↳needs sage.symbolic
1.57079632679490 - 1.000000000000000*z + 0.000000000000000*z^2
- 0.166666666666667*z^3 + 0.000000000000000*z^4
- 0.0750000000000000*z^5 + O(1.000000000000000*z^7)

>>> L = LazyLaurentSeriesRing(SR, names=('z',)); (z,) = L._first_ngens(1) #_
↳needs sage.symbolic
>>> arccos(z/(Integer(1)-z)) #_
↳needs sage.symbolic
```

(continues on next page)

(continued from previous page)

```

↪ # needs sage.symbolic
1/2*pi - z - z^2 - 7/6*z^3 - 3/2*z^4 - 83/40*z^5 - 73/24*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(SR, names=('x', 'y',)); (x, y) = L._first_
↪ ngens(2) # needs sage.symbolic
>>> arccos(x/(Integer(1)-y))
↪ # needs sage.symbolic
1/2*pi + (-x) + (-x*y) + ((-1/6)*x^3-x*y^2) + ((-1/2)*x^3*y-x*y^3)
+ ((-3/40)*x^5-x^3*y^2-x*y^4) + ((-3/8)*x^5*y+(-5/3)*x^3*y^3-x*y^5) + O(x,y)^
↪ 7

```

arccot()

Return the arctangent of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(RR)
sage: arccot(z)
↪ needs sage.symbolic
1.57079632679490 - 1.000000000000000*z + 0.000000000000000*z^2
+ 0.333333333333333*z^3 + 0.000000000000000*z^4
- 0.200000000000000*z^5 + O(1.000000000000000*z^7)

sage: L.<z> = LazyLaurentSeriesRing(SR)
↪ needs sage.symbolic
sage: arccot(z/(1-z))
↪ needs sage.symbolic
1/2*pi - z - z^2 - 2/3*z^3 + 4/5*z^5 + 4/3*z^6 + O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(SR)
↪ needs sage.symbolic
sage: acot(x/(1-y))
↪ needs sage.symbolic
1/2*pi + (-x) + (-x*y) + (1/3*x^3-x*y^2) + (x^3*y-x*y^3)
+ ((-1/5)*x^5+2*x^3*y^2-x*y^4) + (-x^5*y+10/3*x^3*y^3-x*y^5) + O(x,y)^7

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(RR, names=('z',)); (z,) = L._first_ngens(1)
>>> arccot(z)
↪ needs sage.symbolic
1.57079632679490 - 1.000000000000000*z + 0.000000000000000*z^2
+ 0.333333333333333*z^3 + 0.000000000000000*z^4
- 0.200000000000000*z^5 + O(1.000000000000000*z^7)

>>> L = LazyLaurentSeriesRing(SR, names=('z',)); (z,) = L._first_ngens(1)
↪ needs sage.symbolic
>>> arccot(z/(Integer(1)-z))
↪ # needs sage.symbolic
1/2*pi - z - z^2 - 2/3*z^3 + 4/5*z^5 + 4/3*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(SR, names=('x', 'y',)); (x, y) = L._first_
↪ ngens(2) # needs sage.symbolic

```

(continues on next page)

(continued from previous page)

```
>>> acot(x/(Integer(1)-y))
↪      # needs sage.symbolic
1/2*pi + (-x) + (-x*y) + (1/3*x^3-x*y^2) + (x^3*y-x*y^3)
+ ((-1/5)*x^5+2*x^3*y^2-x*y^4) + (-x^5*y+10/3*x^3*y^3-x*y^5) + O(x,y)^7
```

arcsin()

Return the arcsine of self.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: arcsin(z)
z + 1/6*z^3 + 3/40*z^5 + 5/112*z^7 + O(z^8)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: asin(x/(1-y))
x + x*y + (1/6*x^3+x*y^2) + (1/2*x^3*y+x*y^3)
+ (3/40*x^5+x^3*y^2+x*y^4) + (3/8*x^5*y+5/3*x^3*y^3+x*y^5)
+ (5/112*x^7+9/8*x^5*y^2+5/2*x^3*y^4+x*y^6) + O(x,y)^8
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> arcsin(z)
z + 1/6*z^3 + 3/40*z^5 + 5/112*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↪ngens(2)
>>> asin(x/(Integer(1)-y))
x + x*y + (1/6*x^3+x*y^2) + (1/2*x^3*y+x*y^3)
+ (3/40*x^5+x^3*y^2+x*y^4) + (3/8*x^5*y+5/3*x^3*y^3+x*y^5)
+ (5/112*x^7+9/8*x^5*y^2+5/2*x^3*y^4+x*y^6) + O(x,y)^8
```

arcsinh()

Return the inverse of the hyperbolic sine of self.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: asinh(z)
z - 1/6*z^3 + 3/40*z^5 - 5/112*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> asinh(z)
z - 1/6*z^3 + 3/40*z^5 - 5/112*z^7 + O(z^8)
```

arcsinh is an alias:

```
sage: arcsinh(z)
z - 1/6*z^3 + 3/40*z^5 - 5/112*z^7 + O(z^8)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: asinh(x/(1-y))
```

(continues on next page)

(continued from previous page)

```
x + x*y - (1/6*x^3-x*y^2) - (1/2*x^3*y-x*y^3) + (3/40*x^5-x^3*y^2+x*y^4)
+ (3/8*x^5*y-5/3*x^3*y^3+x*y^5) - (5/112*x^7-9/8*x^5*y^2+5/2*x^3*y^4-x*y^6) +
↪ O(x,y)^8
```

```
>>> from sage.all import *
>>> arcsinh(z)
z - 1/6*z^3 + 3/40*z^5 - 5/112*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y')); (x, y) = L._first_
↪ngens(2)
>>> asinh(x/(Integer(1)-y))
x + x*y - (1/6*x^3-x*y^2) - (1/2*x^3*y-x*y^3) + (3/40*x^5-x^3*y^2+x*y^4)
+ (3/8*x^5*y-5/3*x^3*y^3+x*y^5) - (5/112*x^7-9/8*x^5*y^2+5/2*x^3*y^4-x*y^6) +
↪ O(x,y)^8
```

arctan()

Return the arctangent of self.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: arctan(z)
z - 1/3*z^3 + 1/5*z^5 - 1/7*z^7 + O(z^8)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: atan(x/(1-y))
x + x*y - (1/3*x^3-x*y^2) - (x^3*y-x*y^3) + (1/5*x^5-2*x^3*y^2+x*y^4)
+ (x^5*y-10/3*x^3*y^3+x*y^5) - (1/7*x^7-3*x^5*y^2+5*x^3*y^4-x*y^6) + O(x,y)^8
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> arctan(z)
z - 1/3*z^3 + 1/5*z^5 - 1/7*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y')); (x, y) = L._first_
↪ngens(2)
>>> atan(x/(Integer(1)-y))
x + x*y - (1/3*x^3-x*y^2) - (x^3*y-x*y^3) + (1/5*x^5-2*x^3*y^2+x*y^4)
+ (x^5*y-10/3*x^3*y^3+x*y^5) - (1/7*x^7-3*x^5*y^2+5*x^3*y^4-x*y^6) + O(x,y)^8
```

arctanh()

Return the inverse of the hyperbolic tangent of self.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: atanh(z)
z + 1/3*z^3 + 1/5*z^5 + 1/7*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> atanh(z)
z + 1/3*z^3 + 1/5*z^5 + 1/7*z^7 + O(z^8)
```

`arctanh` is an alias:

```
sage: arctanh(z)
z + 1/3*z^3 + 1/5*z^5 + 1/7*z^7 + O(z^8)

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: atanh(x/(1-y))
x + x*y + (1/3*x^3+x*y^2) + (x^3*y+x*y^3) + (1/5*x^5+2*x^3*y^2+x*y^4)
+ (x^5*y+10/3*x^3*y^3+x*y^5) + (1/7*x^7+3*x^5*y^2+5*x^3*y^4+x*y^6) + O(x,y)^8
```

```
>>> from sage.all import *
>>> arctanh(z)
z + 1/3*z^3 + 1/5*z^5 + 1/7*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> atanh(x/(Integer(1)-y))
x + x*y + (1/3*x^3+x*y^2) + (x^3*y+x*y^3) + (1/5*x^5+2*x^3*y^2+x*y^4)
+ (x^5*y+10/3*x^3*y^3+x*y^5) + (1/7*x^7+3*x^5*y^2+5*x^3*y^4+x*y^6) + O(x,y)^8
```

`change_ring(ring)`

Return self with coefficients converted to elements of ring.

INPUT:

- `ring` – a ring

EXAMPLES:

Dense Implementation:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=False)
sage: s = 2 + z
sage: t = s.change_ring(QQ)
sage: t^-1
1/2 - 1/4*z + 1/8*z^2 - 1/16*z^3 + 1/32*z^4 - 1/64*z^5 + 1/128*z^6 + O(z^7)
sage: M = L(lambda n: n, valuation=0); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: N = M.change_ring(QQ)
sage: N.parent()
Lazy Laurent Series Ring in z over Rational Field
sage: M.parent()
Lazy Laurent Series Ring in z over Integer Ring
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, sparse=False, names=('z',)); (z,) = L._
↳first_ngens(1)
>>> s = Integer(2) + z
>>> t = s.change_ring(QQ)
>>> t**-Integer(1)
1/2 - 1/4*z + 1/8*z^2 - 1/16*z^3 + 1/32*z^4 - 1/64*z^5 + 1/128*z^6 + O(z^7)
>>> M = L(lambda n: n, valuation=Integer(0)); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> N = M.change_ring(QQ)
>>> N.parent()
```

(continues on next page)

(continued from previous page)

```

Lazy Laurent Series Ring in z over Rational Field
>>> M.parent()
Lazy Laurent Series Ring in z over Integer Ring

```

Sparse Implementation:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=True)
sage: M = L(lambda n: n, valuation=0); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: M.parent()
Lazy Laurent Series Ring in z over Integer Ring
sage: N = M.change_ring(QQ)
sage: N.parent()
Lazy Laurent Series Ring in z over Rational Field
sage: M^-1
z^-1 - 2 + z + O(z^6)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, sparse=True, names=('z',)); (z,) = L._first_
↳ngens(1)
>>> M = L(lambda n: n, valuation=Integer(0)); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> M.parent()
Lazy Laurent Series Ring in z over Integer Ring
>>> N = M.change_ring(QQ)
>>> N.parent()
Lazy Laurent Series Ring in z over Rational Field
>>> M**Integer(1)
z^-1 - 2 + z + O(z^6)

```

A Dirichlet series example:

```

sage: L = LazyDirichletSeriesRing(ZZ, 'z')
sage: s = L(constant=2)
sage: t = s.change_ring(QQ)
sage: t.parent()
Lazy Dirichlet Series Ring in z over Rational Field
sage: it = t^-1
sage: it
↳needs sage.symbolic
1/2 - 1/2/2^z - 1/2/3^z - 1/2/5^z + 1/2/6^z - 1/2/7^z + O(1/(8^z))

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, 'z')
>>> s = L(constant=Integer(2))
>>> t = s.change_ring(QQ)
>>> t.parent()
Lazy Dirichlet Series Ring in z over Rational Field
>>> it = t**Integer(1)
>>> it
↳needs sage.symbolic
1/2 - 1/2/2^z - 1/2/3^z - 1/2/5^z + 1/2/6^z - 1/2/7^z + O(1/(8^z))

```


A Taylor series example:

```
sage: L.<z> = LazyPowerSeriesRing(ZZ)
sage: s = 2 + z
sage: t = s.change_ring(QQ)
sage: t^-1
1/2 - 1/4*z + 1/8*z^2 - 1/16*z^3 + 1/32*z^4 - 1/64*z^5 + 1/128*z^6 + O(z^7)
sage: t.parent()
Lazy Taylor Series Ring in z over Rational Field
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> s = Integer(2) + z
>>> t = s.change_ring(QQ)
>>> t**Integer(1)
1/2 - 1/4*z + 1/8*z^2 - 1/16*z^3 + 1/32*z^4 - 1/64*z^5 + 1/128*z^6 + O(z^7)
>>> t.parent()
Lazy Taylor Series Ring in z over Rational Field
```

coefficient(*n*)

Return the homogeneous degree *n* part of the series.

INPUT:

- *n* – integer; the degree

For a series *f*, the slice *f*[*start*:*stop*] produces the following:

- if *start* and *stop* are integers, return the list of terms with given degrees
- if *start* is None, return the list of terms beginning with the valuation
- if *stop* is None, return a `lazy_list_generic` instead.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: f = z / (1 - 2*z^3)
sage: [f[n] for n in range(20)]
[0, 1, 0, 0, 2, 0, 0, 4, 0, 0, 8, 0, 0, 16, 0, 0, 32, 0, 0, 64]
sage: f[0:20]
[0, 1, 0, 0, 2, 0, 0, 4, 0, 0, 8, 0, 0, 16, 0, 0, 32, 0, 0, 64]
sage: f[:20]
[1, 0, 0, 2, 0, 0, 4, 0, 0, 8, 0, 0, 16, 0, 0, 32, 0, 0, 64]
sage: f[:3]
lazy list [1, 2, 4, ...]

sage: M = L(lambda n: n, valuation=0)
sage: [M[n] for n in range(20)]
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19]

sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=True)
sage: M = L(lambda n: n, valuation=0)
sage: [M[n] for n in range(20)]
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19]
```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = z / (Integer(1) - Integer(2)*z**Integer(3))
>>> [f[n] for n in range(Integer(20))]
[0, 1, 0, 0, 2, 0, 0, 4, 0, 0, 8, 0, 0, 16, 0, 0, 32, 0, 0, 64]
>>> f[Integer(0):Integer(20)]
[0, 1, 0, 0, 2, 0, 0, 4, 0, 0, 8, 0, 0, 16, 0, 0, 32, 0, 0, 64]
>>> f[:Integer(20)]
[1, 0, 0, 2, 0, 0, 4, 0, 0, 8, 0, 0, 16, 0, 0, 32, 0, 0, 64]
>>> f[::Integer(3)]
lazy list [1, 2, 4, ...]

>>> M = L(lambda n: n, valuation=Integer(0))
>>> [M[n] for n in range(Integer(20))]
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19]

>>> L = LazyLaurentSeriesRing(ZZ, sparse=True, names=('z',)); (z,) = L._first_
↳ngens(1)
>>> M = L(lambda n: n, valuation=Integer(0))
>>> [M[n] for n in range(Integer(20))]
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19]

```

Similarly for multivariate series:

```

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: sin(x*y)[:11]
[x*y, 0, 0, 0, -1/6*x^3*y^3, 0, 0, 0, 1/120*x^5*y^5]
sage: sin(x*y)[2::4]
lazy list [x*y, -1/6*x^3*y^3, 1/120*x^5*y^5, ...]

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↳ngens(2)
>>> sin(x*y)[:Integer(11)]
[x*y, 0, 0, 0, -1/6*x^3*y^3, 0, 0, 0, 1/120*x^5*y^5]
>>> sin(x*y)[Integer(2)::Integer(4)]
lazy list [x*y, -1/6*x^3*y^3, 1/120*x^5*y^5, ...]

```

Similarly for Dirichlet series:

```

sage: L = LazyDirichletSeriesRing(ZZ, "z")
sage: L(lambda n: n)[1:11]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, "z")
>>> L(lambda n: n)[Integer(1):Integer(11)]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

```

coefficients ($n=None$)

Return the first n nonzero coefficients of `self`.

INPUT:

- n – (optional) the number of nonzero coefficients to return

If the series has fewer than n nonzero coefficients, only these are returned.

If n is None, a `lazy_list_generic` with all nonzero coefficients is returned instead.

Warning

If there are fewer than n nonzero coefficients, but this cannot be detected, this method will not return.

EXAMPLES:

```
sage: L.<x> = LazyPowerSeriesRing(QQ)
sage: f = L([1,2,3])
sage: f.coefficients(5)
doctest:...: DeprecationWarning: the method coefficients now only returns the_
↪nonzero coefficients. Use __getitem__ instead.
See https://github.com/sagemath/sage/issues/32367 for details.
[1, 2, 3]

sage: f = sin(x)
sage: f.coefficients(5)
[1, -1/6, 1/120, -1/5040, 1/362880]

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: f = sin(x^2+y^2)
sage: f.coefficients(5)
[1, 1, -1/6, -1/2, -1/2]

sage: f.coefficients()
lazy list [1, 1, -1/6, ...]

sage: L.<x> = LazyPowerSeriesRing(GF(2))
sage: f = L(lambda n: n)
sage: f.coefficients(5)
[1, 1, 1, 1, 1]
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> f = L([Integer(1), Integer(2), Integer(3)])
>>> f.coefficients(Integer(5))
doctest:...: DeprecationWarning: the method coefficients now only returns the_
↪nonzero coefficients. Use __getitem__ instead.
See https://github.com/sagemath/sage/issues/32367 for details.
[1, 2, 3]

>>> f = sin(x)
>>> f.coefficients(Integer(5))
[1, -1/6, 1/120, -1/5040, 1/362880]

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↪ngens(2)
>>> f = sin(x**Integer(2)+y**Integer(2))
```

(continues on next page)

(continued from previous page)

```

>>> f.coefficients(Integer(5))
[1, 1, -1/6, -1/2, -1/2]

>>> f.coefficients()
lazy list [1, 1, -1/6, ...]

>>> L = LazyPowerSeriesRing(GF(Integer(2)), names=('x',)); (x,) = L._first_
↳ngens(1)
>>> f = L(lambda n: n)
>>> f.coefficients(Integer(5))
[1, 1, 1, 1, 1]

```

cos()Return the cosine of `self`.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: cos(z)
1 - 1/2*z^2 + 1/24*z^4 - 1/720*z^6 + O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: cos(x/(1-y)).polynomial(4)
1/24*x^4 - 3/2*x^2*y^2 - x^2*y - 1/2*x^2 + 1

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> cos(z)
1 - 1/2*z^2 + 1/24*z^4 - 1/720*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> cos(x/(Integer(1)-y)).polynomial(Integer(4))
1/24*x^4 - 3/2*x^2*y^2 - x^2*y - 1/2*x^2 + 1

```

cosh()Return the hyperbolic cosine of `self`.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: cosh(z)
1 + 1/2*z^2 + 1/24*z^4 + 1/720*z^6 + O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: cosh(x/(1-y))
1 + 1/2*x^2 + x^2*y + (1/24*x^4+3/2*x^2*y^2) + (1/6*x^4*y+2*x^2*y^3)
+ (1/720*x^6+5/12*x^4*y^2+5/2*x^2*y^4) + O(x,y)^7

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> cosh(z)

```

(continues on next page)

(continued from previous page)

```

1 + 1/2*z^2 + 1/24*z^4 + 1/720*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> cosh(x/(Integer(1)-y))
1 + 1/2*x^2 + x^2*y + (1/24*x^4+3/2*x^2*y^2) + (1/6*x^4*y+2*x^2*y^3)
+ (1/720*x^6+5/12*x^4*y^2+5/2*x^2*y^4) + O(x,y)^7

```

cot()Return the cotangent of `self`.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: cot(z)
z^-1 - 1/3*z - 1/45*z^3 - 2/945*z^5 + O(z^6)

sage: L.<x> = LazyLaurentSeriesRing(QQ)
sage: cot(x/(1-x)).polynomial(4)
x^-1 - 1 - 1/3*x - 1/3*x^2 - 16/45*x^3 - 2/5*x^4

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> cot(z)
z^-1 - 1/3*z - 1/45*z^3 - 2/945*z^5 + O(z^6)

>>> L = LazyLaurentSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> cot(x/(Integer(1)-x)).polynomial(Integer(4))
x^-1 - 1 - 1/3*x - 1/3*x^2 - 16/45*x^3 - 2/5*x^4

```

coth()Return the hyperbolic cotangent of `self`.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: coth(z) #_
↳needs sage.libs.flint
z^-1 + 1/3*z - 1/45*z^3 + 2/945*z^5 + O(z^6)

sage: coth(z + z^2) #_
↳needs sage.libs.flint
z^-1 - 1 + 4/3*z - 2/3*z^2 + 44/45*z^3 - 16/15*z^4 + 884/945*z^5 + O(z^6)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> coth(z) #_
↳needs sage.libs.flint
z^-1 + 1/3*z - 1/45*z^3 + 2/945*z^5 + O(z^6)

>>> coth(z + z**Integer(2)) #_
↳ # needs sage.libs.flint
z^-1 - 1 + 4/3*z - 2/3*z^2 + 44/45*z^3 - 16/15*z^4 + 884/945*z^5 + O(z^6)

```

csc()Return the cosecant of `self`.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: csc(z)
z^-1 + 1/6*z + 7/360*z^3 + 31/15120*z^5 + O(z^6)

sage: L.<x> = LazyLaurentSeriesRing(QQ)
sage: csc(x/(1-x)).polynomial(4)
x^-1 - 1 + 1/6*x + 1/6*x^2 + 67/360*x^3 + 9/40*x^4
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> csc(z)
z^-1 + 1/6*z + 7/360*z^3 + 31/15120*z^5 + O(z^6)

>>> L = LazyLaurentSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> csc(x/(Integer(1)-x)).polynomial(Integer(4))
x^-1 - 1 + 1/6*x + 1/6*x^2 + 67/360*x^3 + 9/40*x^4
```

csch()Return the hyperbolic cosecant of `self`.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: csch(z) #_
↪needs sage.libs.flint
z^-1 - 1/6*z + 7/360*z^3 - 31/15120*z^5 + O(z^6)

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: csch(z/(1-z)) #_
↪needs sage.libs.flint
z^-1 - 1 - 1/6*z - 1/6*z^2 - 53/360*z^3 - 13/120*z^4 - 787/15120*z^5 + O(z^6)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> csch(z) #_
↪needs sage.libs.flint
z^-1 - 1/6*z + 7/360*z^3 - 31/15120*z^5 + O(z^6)

>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> csch(z/(Integer(1)-z)) #_
↪ # needs sage.libs.flint
z^-1 - 1 - 1/6*z - 1/6*z^2 - 53/360*z^3 - 13/120*z^4 - 787/15120*z^5 + O(z^6)
```

define(s)Define an equation by `self = s`.

INPUT:

- `s` – a lazy series

EXAMPLES:

We begin by constructing the Catalan numbers:

```
sage: L.<z> = LazyPowerSeriesRing(ZZ)
sage: C = L.undefined()
sage: C.define(1 + z*C^2)
sage: C
1 + z + 2*z^2 + 5*z^3 + 14*z^4 + 42*z^5 + 132*z^6 + O(z^7)
sage: binomial(2000, 1000) / C[1000] #_
↪needs sage.symbolic
1001
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> C = L.undefined()
>>> C.define(Integer(1) + z*C**Integer(2))
>>> C
1 + z + 2*z^2 + 5*z^3 + 14*z^4 + 42*z^5 + 132*z^6 + O(z^7)
>>> binomial(Integer(2000), Integer(1000)) / C[Integer(1000)]
↪ # needs sage.symbolic
1001
```

The Catalan numbers but with a valuation 1:

```
sage: B = L.undefined(valuation=1)
sage: B.define(z + B^2)
sage: B
z + z^2 + 2*z^3 + 5*z^4 + 14*z^5 + 42*z^6 + 132*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> B = L.undefined(valuation=Integer(1))
>>> B.define(z + B**Integer(2))
>>> B
z + z^2 + 2*z^3 + 5*z^4 + 14*z^5 + 42*z^6 + 132*z^7 + O(z^8)
```

We can define multiple series that are linked:

```
sage: s = L.undefined()
sage: t = L.undefined()
sage: s.define(1 + z*t^3)
sage: t.define(1 + z*s^2)
sage: s[0:9]
[1, 1, 3, 9, 34, 132, 546, 2327, 10191]
sage: t[0:9]
[1, 1, 2, 7, 24, 95, 386, 1641, 7150]
```

```
>>> from sage.all import *
>>> s = L.undefined()
>>> t = L.undefined()
>>> s.define(Integer(1) + z*t**Integer(3))
>>> t.define(Integer(1) + z*s**Integer(2))
>>> s[Integer(0):Integer(9)]
[1, 1, 3, 9, 34, 132, 546, 2327, 10191]
>>> t[Integer(0):Integer(9)]
```

(continues on next page)

(continued from previous page)

```
[1, 1, 2, 7, 24, 95, 386, 1641, 7150]
```

A bigger example:

```
sage: L.<z> = LazyPowerSeriesRing(ZZ)
sage: A = L.undefined(valuation=5)
sage: B = L.undefined()
sage: C = L.undefined(valuation=2)
sage: A.define(z^5 + B^2)
sage: B.define(z^5 + C^2)
sage: C.define(z^2 + C^2 + A^2)
sage: A[0:15]
[0, 0, 0, 0, 0, 1, 0, 0, 1, 2, 5, 4, 14, 10, 48]
sage: B[0:15]
[0, 0, 0, 0, 1, 1, 2, 0, 5, 0, 14, 0, 44, 0, 138]
sage: C[0:15]
[0, 0, 1, 0, 1, 0, 2, 0, 5, 0, 15, 0, 44, 2, 142]
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> A = L.undefined(valuation=Integer(5))
>>> B = L.undefined()
>>> C = L.undefined(valuation=Integer(2))
>>> A.define(z**Integer(5) + B**Integer(2))
>>> B.define(z**Integer(5) + C**Integer(2))
>>> C.define(z**Integer(2) + C**Integer(2) + A**Integer(2))
>>> A[Integer(0):Integer(15)]
[0, 0, 0, 0, 0, 1, 0, 0, 1, 2, 5, 4, 14, 10, 48]
>>> B[Integer(0):Integer(15)]
[0, 0, 0, 0, 1, 1, 2, 0, 5, 0, 14, 0, 44, 0, 138]
>>> C[Integer(0):Integer(15)]
[0, 0, 1, 0, 1, 0, 2, 0, 5, 0, 15, 0, 44, 2, 142]
```

Counting binary trees:

```
sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: s = L.undefined(valuation=1)
sage: s.define(z + (s^2+s(z^2))/2)
sage: s[0:9]
[0, 1, 1, 1, 2, 3, 6, 11, 23]
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> s = L.undefined(valuation=Integer(1))
>>> s.define(z + (s**Integer(2)+s(z**Integer(2)))/Integer(2))
>>> s[Integer(0):Integer(9)]
[0, 1, 1, 1, 2, 3, 6, 11, 23]
```

The q -Catalan numbers:

```
sage: R.<q> = ZZ[]
sage: L.<z> = LazyLaurentSeriesRing(R)
```

(continues on next page)

(continued from previous page)

```

sage: s = L.undefined(valuation=0)
sage: s.define(1+z*s*s(q*z))
sage: s
1 + z + (q + 1)*z^2 + (q^3 + q^2 + 2*q + 1)*z^3
+ (q^6 + q^5 + 2*q^4 + 3*q^3 + 3*q^2 + 3*q + 1)*z^4
+ (q^10 + q^9 + 2*q^8 + 3*q^7 + 5*q^6 + 5*q^5 + 7*q^4 + 7*q^3 + 6*q^2 + 4*q
↪ + 1)*z^5
+ (q^15 + q^14 + 2*q^13 + 3*q^12 + 5*q^11 + 7*q^10 + 9*q^9 + 11*q^8
+ 14*q^7 + 16*q^6 + 16*q^5 + 17*q^4 + 14*q^3 + 10*q^2 + 5*q + 1)*z^6 +
↪ O(z^7)

```

```

>>> from sage.all import *
>>> R = ZZ['q']; (q,) = R._first_ngens(1)
>>> L = LazyLaurentSeriesRing(R, names=('z',)); (z,) = L._first_ngens(1)
>>> s = L.undefined(valuation=Integer(0))
>>> s.define(Integer(1)+z*s*s(q*z))
>>> s
1 + z + (q + 1)*z^2 + (q^3 + q^2 + 2*q + 1)*z^3
+ (q^6 + q^5 + 2*q^4 + 3*q^3 + 3*q^2 + 3*q + 1)*z^4
+ (q^10 + q^9 + 2*q^8 + 3*q^7 + 5*q^6 + 5*q^5 + 7*q^4 + 7*q^3 + 6*q^2 + 4*q
↪ + 1)*z^5
+ (q^15 + q^14 + 2*q^13 + 3*q^12 + 5*q^11 + 7*q^10 + 9*q^9 + 11*q^8
+ 14*q^7 + 16*q^6 + 16*q^5 + 17*q^4 + 14*q^3 + 10*q^2 + 5*q + 1)*z^6 +
↪ O(z^7)

```

We count unlabeled ordered trees by total number of nodes and number of internal nodes:

```

sage: R.<q> = QQ[]
sage: Q.<z> = LazyPowerSeriesRing(R)
sage: leaf = z
sage: internal_node = q * z
sage: L = Q(constant=1, degree=1)
sage: T = Q.undefined(valuation=1)
sage: T.define(leaf + internal_node * L(T))
sage: T[0:6]
[0, 1, q, q^2 + q, q^3 + 3*q^2 + q, q^4 + 6*q^3 + 6*q^2 + q]

```

```

>>> from sage.all import *
>>> R = QQ['q']; (q,) = R._first_ngens(1)
>>> Q = LazyPowerSeriesRing(R, names=('z',)); (z,) = Q._first_ngens(1)
>>> leaf = z
>>> internal_node = q * z
>>> L = Q(constant=Integer(1), degree=Integer(1))
>>> T = Q.undefined(valuation=Integer(1))
>>> T.define(leaf + internal_node * L(T))
>>> T[Integer(0):Integer(6)]
[0, 1, q, q^2 + q, q^3 + 3*q^2 + q, q^4 + 6*q^3 + 6*q^2 + q]

```

Similarly for Dirichlet series:

```

sage: L = LazyDirichletSeriesRing(ZZ, "z")
sage: g = L(constant=1, valuation=2)

```

(continues on next page)

(continued from previous page)

```

sage: F = L.undefined()
sage: F.define(1 + g*F)
sage: F[:16]
[1, 1, 1, 2, 1, 3, 1, 4, 2, 3, 1, 8, 1, 3, 3]
sage: oeis(_)                                     #_
↪ optional - internet
0: A002033: Number of perfect partitions of n.
1: A074206: Kalmár's [Kalmar's] problem: number of ordered factorizations of_
↪ n.
...

sage: F = L.undefined()
sage: F.define(1 + g*F*F)
sage: F[:16]
[1, 1, 1, 3, 1, 5, 1, 10, 3, 5, 1, 24, 1, 5, 5]

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, "z")
>>> g = L(constant=Integer(1), valuation=Integer(2))
>>> F = L.undefined()
>>> F.define(Integer(1) + g*F)
>>> F[:Integer(16)]
[1, 1, 1, 2, 1, 3, 1, 4, 2, 3, 1, 8, 1, 3, 3]
>>> oeis(_)                                     # optional -
↪ internet
0: A002033: Number of perfect partitions of n.
1: A074206: Kalmár's [Kalmar's] problem: number of ordered factorizations of_
↪ n.
...

>>> F = L.undefined()
>>> F.define(Integer(1) + g*F*F)
>>> F[:Integer(16)]
[1, 1, 1, 3, 1, 5, 1, 10, 3, 5, 1, 24, 1, 5, 5]

```

We can compute the Frobenius character of unlabeled trees:

```

sage: # needs sage.combinat
sage: m = SymmetricFunctions(QQ).m()
sage: s = SymmetricFunctions(QQ).s()
sage: L = LazySymmetricFunctions(m)
sage: E = L(lambda n: s[n], valuation=0)
sage: X = L(s[1])
sage: A = L.undefined()
sage: A.define(X*E(A))
sage: A[:6]
[m[1],
 2*m[1, 1] + m[2],
 9*m[1, 1, 1] + 5*m[2, 1] + 2*m[3],
 64*m[1, 1, 1, 1] + 34*m[2, 1, 1] + 18*m[2, 2] + 13*m[3, 1] + 4*m[4],
 625*m[1, 1, 1, 1, 1] + 326*m[2, 1, 1, 1] + 171*m[2, 2, 1] + 119*m[3, 1, 1] +_
↪ 63*m[3, 2] + 35*m[4, 1] + 9*m[5]]

```

```

>>> from sage.all import *
>>> # needs sage.combinat
>>> m = SymmetricFunctions(QQ).m()
>>> s = SymmetricFunctions(QQ).s()
>>> L = LazySymmetricFunctions(m)
>>> E = L(lambda n: s[n], valuation=Integer(0))
>>> X = L(s[Integer(1)])
>>> A = L.undefined()
>>> A.define(X*E(A))
>>> A[:Integer(6)]
[m[1],
 2*m[1, 1] + m[2],
 9*m[1, 1, 1] + 5*m[2, 1] + 2*m[3],
 64*m[1, 1, 1, 1] + 34*m[2, 1, 1] + 18*m[2, 2] + 13*m[3, 1] + 4*m[4],
 625*m[1, 1, 1, 1, 1] + 326*m[2, 1, 1, 1] + 171*m[2, 2, 1] + 119*m[3, 1, 1] +
↪ 63*m[3, 2] + 35*m[4, 1] + 9*m[5]]

```

dilog()

Return the dilogarithm evaluated at self.

EXAMPLES:

```

sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: z.dilog()
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
sage: dilog(z)
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> z.dilog()
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
>>> dilog(z)
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)

```

We check some dilogarithm identities:

```

sage: dilog(z) + dilog(-z)
1/2*z^2 + 1/8*z^4 + 1/18*z^6 + O(z^8)
sage: dilog(z^2) / 2
1/2*z^2 + 1/8*z^4 + 1/18*z^6 + 1/32*z^8 + O(z^9)

sage: dilog(z) + dilog(z/(z-1))
-1/2*z^2 - 1/2*z^3 - 11/24*z^4 - 5/12*z^5 - 137/360*z^6 - 7/20*z^7 + O(z^8)
sage: -1/2 * log(1 - z)^2
-1/2*z^2 - 1/2*z^3 - 11/24*z^4 - 5/12*z^5 - 137/360*z^6 - 7/20*z^7 - 363/
↪ 1120*z^8 + O(z^9)

```

```

>>> from sage.all import *
>>> dilog(z) + dilog(-z)
1/2*z^2 + 1/8*z^4 + 1/18*z^6 + O(z^8)
>>> dilog(z**Integer(2)) / Integer(2)
1/2*z^2 + 1/8*z^4 + 1/18*z^6 + 1/32*z^8 + O(z^9)

```

(continues on next page)

(continued from previous page)

```

>>> dilog(z) + dilog(z/(z-Integer(1)))
-1/2*z^2 - 1/2*z^3 - 11/24*z^4 - 5/12*z^5 - 137/360*z^6 - 7/20*z^7 + O(z^8)
>>> -Integer(1)/Integer(2) * log(Integer(1) - z)**Integer(2)
-1/2*z^2 - 1/2*z^3 - 11/24*z^4 - 5/12*z^5 - 137/360*z^6 - 7/20*z^7 - 363/
↪1120*z^8 + O(z^9)

```

REFERENCES:

- [Wikipedia article Dilogarithm](#)

euler()

Return the Euler function evaluated at `self`.

The *Euler function* is defined as

$$\phi(z) = (z; z)_{\infty} = \sum_{n=0}^{\infty} (-1)^n q^{(3n^2-n)/2}.$$

 See also

`sage.rings.lazy_series_ring.LazyLaurentSeriesRing.euler()`

EXAMPLES:

```

sage: L.<q> = LazyLaurentSeriesRing(ZZ)
sage: phi = L.euler()
sage: (q + q^2).euler() - phi(q + q^2)
O(q^7)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('q',)); (q,) = L._first_ngens(1)
>>> phi = L.euler()
>>> (q + q**Integer(2)).euler() - phi(q + q**Integer(2))
O(q^7)

```

exp()

Return the exponential series of `self`.

EXAMPLES:

```

sage: L = LazyDirichletSeriesRing(QQ, "s")
sage: Z = L(constant=1, valuation=2)
sage: exp(Z)
↪needs sage.symbolic
1 + 1/(2^s) + 1/(3^s) + 3/2/4^s + 1/(5^s) + 2/6^s + 1/(7^s) + O(1/(8^s))

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(QQ, "s")
>>> Z = L(constant=Integer(1), valuation=Integer(2))
>>> exp(Z)
↪needs sage.symbolic
1 + 1/(2^s) + 1/(3^s) + 3/2/4^s + 1/(5^s) + 2/6^s + 1/(7^s) + O(1/(8^s))

```

hypergeometric(a, b)

Return the ${}_pF_q$ -hypergeometric function ${}_pF_q$ where (p, q) is the parameterization of `self`.

INPUT:

- a – the first parameter of the hypergeometric function
- b – the second parameter of the hypergeometric function

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: z.hypergeometric([1, 1], [1])
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
sage: z.hypergeometric([], []) - exp(z)
O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: (x+y).hypergeometric([1, 1], [1]).polynomial(4)
x^4 + 4*x^3*y + 6*x^2*y^2 + 4*x*y^3 + y^4 + x^3 + 3*x^2*y
+ 3*x*y^2 + y^3 + x^2 + 2*x*y + y^2 + x + y + 1
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> z.hypergeometric([Integer(1), Integer(1)], [Integer(1)])
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
>>> z.hypergeometric([], []) - exp(z)
O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↳ngens(2)
>>> (x+y).hypergeometric([Integer(1), Integer(1)], [Integer(1)]).
↳polynomial(Integer(4))
x^4 + 4*x^3*y + 6*x^2*y^2 + 4*x*y^3 + y^4 + x^3 + 3*x^2*y
+ 3*x*y^2 + y^3 + x^2 + 2*x*y + y^2 + x + y + 1
```

is_nonzero(*proof=False*)

Return True if `self` is *known* to be nonzero.

INPUT:

- *proof* – boolean (default: False); if True, this will also return an index such that `self` has a nonzero coefficient

Warning

If the stream is exactly zero, this will run forever.

EXAMPLES:

A series that it not known to be nonzero with no halting precision:

```
sage: L.<z> = LazyLaurentSeriesRing(GF(2))
sage: f = L(lambda n: 0, valuation=0)
sage: f.is_nonzero()
```

(continues on next page)

(continued from previous page)

```
False
sage: bool(f)
True
sage: g = L(lambd n: 0 if n < 50 else 1, valuation=2)
sage: g.is_nonzero()
False
sage: g[60]
1
sage: g.is_nonzero()
True
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(GF(Integer(2)), names=('z',)); (z,) = L._first_
↳ngens(1)
>>> f = L(lambd n: Integer(0), valuation=Integer(0))
>>> f.is_nonzero()
False
>>> bool(f)
True
>>> g = L(lambd n: Integer(0) if n < Integer(50) else Integer(1),
↳valuation=Integer(2))
>>> g.is_nonzero()
False
>>> g[Integer(60)]
1
>>> g.is_nonzero()
True
```

With finite halting precision, it can be considered to be indistinguishable from zero until possibly enough coefficients are computed:

```
sage: L.options.halting_precision = 20
sage: f = L(lambd n: 0, valuation=0)
sage: f.is_zero()
True

sage: g = L(lambd n: 0 if n < 50 else 1, valuation=2)
sage: g.is_nonzero() # checks up to degree 22 = 2 + 20
False
sage: g.is_nonzero() # checks up to degree 42 = 22 + 20
False
sage: g.is_nonzero() # checks up to degree 62 = 42 + 20
True
sage: L.options._reset()
```

```
>>> from sage.all import *
>>> L.options.halting_precision = Integer(20)
>>> f = L(lambd n: Integer(0), valuation=Integer(0))
>>> f.is_zero()
True

>>> g = L(lambd n: Integer(0) if n < Integer(50) else Integer(1),
↳
```

(continues on next page)

(continued from previous page)

```

↪valuation=Integer(2))
>>> g.is_nonzero() # checks up to degree 22 = 2 + 20
False
>>> g.is_nonzero() # checks up to degree 42 = 22 + 20
False
>>> g.is_nonzero() # checks up to degree 62 = 42 + 20
True
>>> L.options._reset()

```

With a proof:

```

sage: L.<z> = LazyLaurentSeriesRing(GF(5))
sage: g = L(lambda n: 5 if n < 50 else 1, valuation=2)
sage: g.is_nonzero(proof=True)
(True, 50)

sage: L.zero().is_nonzero(proof=True)
(False, None)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(GF(Integer(5)), names=('z',)); (z,) = L._first_
↪ngens(1)
>>> g = L(lambda n: Integer(5) if n < Integer(50) else Integer(1), ↪
↪valuation=Integer(2))
>>> g.is_nonzero(proof=True)
(True, 50)

>>> L.zero().is_nonzero(proof=True)
(False, None)

```

is_trivial_zero()

Return whether `self` is known to be trivially zero.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: f = L(lambda n: 0, valuation=2)
sage: f.is_trivial_zero()
False

sage: L.zero().is_trivial_zero()
True

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L(lambda n: Integer(0), valuation=Integer(2))
>>> f.is_trivial_zero()
False

>>> L.zero().is_trivial_zero()
True

```

jacobi_theta($w, a=0, b=0$)

Return the Jacobi theta function $\vartheta_{ab}(w; q)$ evaluated with the nome q at `self`.

 See also

`sage.rings.lazy_series_ring.LazyLaurentSeriesRing.jacobi_theta()`

EXAMPLES:

```
sage: R.<w> = LaurentSeriesRing(QQ)
sage: L.<q> = LazyLaurentSeriesRing(R)
sage: theta = L.jacobi_theta(w)
sage: (q + q^2).jacobi_theta(w) - theta(q + q^2)
O(q^7)
```

```
>>> from sage.all import *
>>> R = LaurentSeriesRing(QQ, names=('w',)); (w,) = R._first_ngens(1)
>>> L = LazyLaurentSeriesRing(R, names=('q',)); (q,) = L._first_ngens(1)
>>> theta = L.jacobi_theta(w)
>>> (q + q**Integer(2)).jacobi_theta(w) - theta(q + q**Integer(2))
O(q^7)
```

lift_to_precision (*absprec=None*)

Return another element of the same parent with absolute precision at least *absprec*, congruent to this element modulo the precision of this element.

Since the precision of a lazy series is infinity, this method returns the series itself, and the argument is ignored.

EXAMPLES:

```
sage: P.<t> = PowerSeriesRing(QQ, default_prec=2)
sage: R.<z> = LazyPowerSeriesRing(P)
sage: f = R(lambda n: 1/(1-t)^n)
sage: f
1 + ((1+t+O(t^2))*z) + ((1+2*t+O(t^2))*z^2)
+ ((1+3*t+O(t^2))*z^3)
+ ((1+4*t+O(t^2))*z^4)
+ ((1+5*t+O(t^2))*z^5)
+ ((1+6*t+O(t^2))*z^6) + O(z^7)
sage: f.lift_to_precision()
1 + ((1+t+O(t^2))*z) + ((1+2*t+O(t^2))*z^2)
+ ((1+3*t+O(t^2))*z^3)
+ ((1+4*t+O(t^2))*z^4)
+ ((1+5*t+O(t^2))*z^5)
+ ((1+6*t+O(t^2))*z^6) + O(z^7)
```

```
>>> from sage.all import *
>>> P = PowerSeriesRing(QQ, default_prec=Integer(2), names=('t',)); (t,) = P._
↳ first_ngens(1)
>>> R = LazyPowerSeriesRing(P, names=('z',)); (z,) = R._first_ngens(1)
>>> f = R(lambda n: Integer(1)/(Integer(1)-t)**n)
>>> f
1 + ((1+t+O(t^2))*z) + ((1+2*t+O(t^2))*z^2)
```

(continues on next page)

(continued from previous page)

```

+ ((1+3*t+O(t^2))*z^3)
+ ((1+4*t+O(t^2))*z^4)
+ ((1+5*t+O(t^2))*z^5)
+ ((1+6*t+O(t^2))*z^6) + O(z^7)
>>> f.lift_to_precision()
1 + ((1+t+O(t^2))*z) + ((1+2*t+O(t^2))*z^2)
+ ((1+3*t+O(t^2))*z^3)
+ ((1+4*t+O(t^2))*z^4)
+ ((1+5*t+O(t^2))*z^5)
+ ((1+6*t+O(t^2))*z^6) + O(z^7)

```

log()

Return the series for the natural logarithm of `self`.

EXAMPLES:

```

sage: L = LazyDirichletSeriesRing(QQ, "s")
sage: Z = L(constant=1)
sage: log(Z)
↪needs sage.symbolic
1/(2^s) + 1/(3^s) + 1/2/4^s + 1/(5^s) + 1/(7^s) + O(1/(8^s))

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(QQ, "s")
>>> Z = L(constant=Integer(1))
>>> log(Z)
↪needs sage.symbolic
1/(2^s) + 1/(3^s) + 1/2/4^s + 1/(5^s) + 1/(7^s) + O(1/(8^s))

```

map_coefficients(f)

Return the series with `f` applied to each nonzero coefficient of `self`.

INPUT:

- `func` – function that takes in a coefficient and returns a new coefficient

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: m = L(lambda n: n, valuation=0); m
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: m.map_coefficients(lambda c: c + 1)
2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + 8*z^7 + O(z^8)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> m = L(lambda n: n, valuation=Integer(0)); m
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> m.map_coefficients(lambda c: c + Integer(1))
2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + 8*z^7 + O(z^8)

```

Similarly for Dirichlet series:

```

sage: L = LazyDirichletSeriesRing(ZZ, "z")
sage: s = L(lambd n: n-1)
sage: s
↪needs sage.symbolic
1/(2^z) + 2/3^z + 3/4^z + 4/5^z + 5/6^z + 6/7^z + O(1/(8^z))
sage: ms = s.map_coefficients(lambd c: c + 1)
↪needs sage.symbolic
sage: ms
↪needs sage.symbolic
2/2^z + 3/3^z + 4/4^z + 5/5^z + 6/6^z + 7/7^z + 8/8^z + O(1/(9^z))

```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, "z")
>>> s = L(lambd n: n-Integer(1))
>>> s
↪needs sage.symbolic
1/(2^z) + 2/3^z + 3/4^z + 4/5^z + 5/6^z + 6/7^z + O(1/(8^z))
>>> ms = s.map_coefficients(lambd c: c + Integer(1))
↪ # needs sage.symbolic
>>> ms
↪needs sage.symbolic
2/2^z + 3/3^z + 4/4^z + 5/5^z + 6/6^z + 7/7^z + 8/8^z + O(1/(9^z))

```

Similarly for multivariate power series:

```

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: f = 1/(1-(x+y)); f
1 + (x+y) + (x^2+2*x*y+y^2) + (x^3+3*x^2*y+3*x*y^2+y^3)
+ (x^4+4*x^3*y+6*x^2*y^2+4*x*y^3+y^4)
+ (x^5+5*x^4*y+10*x^3*y^2+10*x^2*y^3+5*x*y^4+y^5)
+ (x^6+6*x^5*y+15*x^4*y^2+20*x^3*y^3+15*x^2*y^4+6*x*y^5+y^6)
+ O(x, y)^7
sage: f.map_coefficients(lambd c: c^2)
1 + (x+y) + (x^2+4*x*y+y^2) + (x^3+9*x^2*y+9*x*y^2+y^3)
+ (x^4+16*x^3*y+36*x^2*y^2+16*x*y^3+y^4)
+ (x^5+25*x^4*y+100*x^3*y^2+100*x^2*y^3+25*x*y^4+y^5)
+ (x^6+36*x^5*y+225*x^4*y^2+400*x^3*y^3+225*x^2*y^4+36*x*y^5+y^6)
+ O(x, y)^7

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y')); (x, y) = L._first_
↪ngens(2)
>>> f = Integer(1)/(Integer(1)-(x+y)); f
1 + (x+y) + (x^2+2*x*y+y^2) + (x^3+3*x^2*y+3*x*y^2+y^3)
+ (x^4+4*x^3*y+6*x^2*y^2+4*x*y^3+y^4)
+ (x^5+5*x^4*y+10*x^3*y^2+10*x^2*y^3+5*x*y^4+y^5)
+ (x^6+6*x^5*y+15*x^4*y^2+20*x^3*y^3+15*x^2*y^4+6*x*y^5+y^6)
+ O(x, y)^7
>>> f.map_coefficients(lambd c: c**Integer(2))
1 + (x+y) + (x^2+4*x*y+y^2) + (x^3+9*x^2*y+9*x*y^2+y^3)
+ (x^4+16*x^3*y+36*x^2*y^2+16*x*y^3+y^4)
+ (x^5+25*x^4*y+100*x^3*y^2+100*x^2*y^3+25*x*y^4+y^5)

```

(continues on next page)

(continued from previous page)

```
+ (x^6+36*x^5*y+225*x^4*y^2+400*x^3*y^3+225*x^2*y^4+36*x*y^5+y^6)
+ O(x,y)^7
```

Similarly for lazy symmetric functions:

```
sage: # needs sage.combinat
sage: p = SymmetricFunctions(QQ).p()
sage: L = LazySymmetricFunctions(p)
sage: f = 1/(1-2*L(p[1])); f
p[] + 2*p[1] + (4*p[1,1]) + (8*p[1,1,1]) + (16*p[1,1,1,1])
+ (32*p[1,1,1,1,1]) + (64*p[1,1,1,1,1,1]) + O^7
sage: f.map_coefficients(lambda c: log(c, 2))
p[1] + (2*p[1,1]) + (3*p[1,1,1]) + (4*p[1,1,1,1])
+ (5*p[1,1,1,1,1]) + (6*p[1,1,1,1,1,1]) + O^7
```

```
>>> from sage.all import *
>>> # needs sage.combinat
>>> p = SymmetricFunctions(QQ).p()
>>> L = LazySymmetricFunctions(p)
>>> f = Integer(1)/(Integer(1)-Integer(2)*L(p[Integer(1)])); f
p[] + 2*p[1] + (4*p[1,1]) + (8*p[1,1,1]) + (16*p[1,1,1,1])
+ (32*p[1,1,1,1,1]) + (64*p[1,1,1,1,1,1]) + O^7
>>> f.map_coefficients(lambda c: log(c, Integer(2)))
p[1] + (2*p[1,1]) + (3*p[1,1,1]) + (4*p[1,1,1,1])
+ (5*p[1,1,1,1,1]) + (6*p[1,1,1,1,1,1]) + O^7
```

polylog(*s*)

Return the polylogarithm in *s* evaluated at *self*.

EXAMPLES:

```
sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: z.polylog(-2)
z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + 49*z^7 + O(z^8)
sage: (z + z^2).polylog(3)
z + 9/8*z^2 + 31/108*z^3 + 145/576*z^4 + 3269/18000*z^5 + 421/2400*z^6
+ 213859/1234800*z^7 + O(z^8)
sage: polylog(3, z)
z + 1/8*z^2 + 1/27*z^3 + 1/64*z^4 + 1/125*z^5 + 1/216*z^6 + 1/343*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> z.polylog(-Integer(2))
z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + 49*z^7 + O(z^8)
>>> (z + z**Integer(2)).polylog(Integer(3))
z + 9/8*z^2 + 31/108*z^3 + 145/576*z^4 + 3269/18000*z^5 + 421/2400*z^6
+ 213859/1234800*z^7 + O(z^8)
>>> polylog(Integer(3), z)
z + 1/8*z^2 + 1/27*z^3 + 1/64*z^4 + 1/125*z^5 + 1/216*z^6 + 1/343*z^7 + O(z^8)
```

We verify an identity due to D.C. Wood (1992):

```
sage: n = 5
sage: polylog(-n, z)
z + 32*z^2 + 243*z^3 + 1024*z^4 + 3125*z^5 + 7776*z^6 + 16807*z^7 + O(z^8)
sage: (-1)^(n+1) * sum(factorial(k) * stirling_number2(n+1,k+1)
....:                  * (-1/(1-z))^(k+1) for k in range(n+1))
z + 32*z^2 + 243*z^3 + 1024*z^4 + 3125*z^5 + 7776*z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> n = Integer(5)
>>> polylog(-n, z)
z + 32*z^2 + 243*z^3 + 1024*z^4 + 3125*z^5 + 7776*z^6 + 16807*z^7 + O(z^8)
>>> (-Integer(1))**(n+Integer(1)) * sum(factorial(k) * stirling_
↳number2(n+Integer(1),k+Integer(1))
...      * (-Integer(1)/(Integer(1)-z))**(k+Integer(1)) for k in_
↳range(n+Integer(1)))
z + 32*z^2 + 243*z^3 + 1024*z^4 + 3125*z^5 + 7776*z^6 + O(z^7)
```

We can pass more general values:

```
sage: L.<z> = LazyPowerSeriesRing(SR)
sage: s = SR.var('s')
sage: z.polylog(s)
z + 1/(2^s)*z^2 + 1/(3^s)*z^3 + 1/(4^s)*z^4 + 1/(5^s)*z^5
+ 1/(6^s)*z^6 + 1/(7^s)*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(SR, names=('z',)); (z,) = L._first_ngens(1)
>>> s = SR.var('s')
>>> z.polylog(s)
z + 1/(2^s)*z^2 + 1/(3^s)*z^3 + 1/(4^s)*z^4 + 1/(5^s)*z^5
+ 1/(6^s)*z^6 + 1/(7^s)*z^7 + O(z^8)
```

REFERENCES:

- [Wikipedia article Polylogarithm](#)

`prec()`

Return the precision of the series, which is infinity.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: f = 1/(1 - z)
sage: f.prec()
+Infinity
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = Integer(1)/(Integer(1) - z)
>>> f.prec()
+Infinity
```

`q_pochhammer(q=None)`

Return the infinite q -Pochhammer symbol $(a; q)_{\infty}$, where a is `self`.

This is also one version of the quantum dilogarithm or the q -Exponential function.

See also

`sage.rings.lazy_series_ring.LazyLaurentSeriesRing.q_pochhammer()`

INPUT:

- q – (default: $q \in \mathbb{Q}(q)$) the parameter q

EXAMPLES:

```
sage: q = ZZ['q'].fraction_field().gen()
sage: L.<z> = LazyLaurentSeriesRing(q.parent())
sage: qp = L.q_pochhammer(q)
sage: (z + z^2).q_pochhammer(q) - qp(z + z^2)
O(z^7)
```

```
>>> from sage.all import *
>>> q = ZZ['q'].fraction_field().gen()
>>> L = LazyLaurentSeriesRing(q.parent(), names=('z',)); (z,) = L._first_
↳ngens(1)
>>> qp = L.q_pochhammer(q)
>>> (z + z**Integer(2)).q_pochhammer(q) - qp(z + z**Integer(2))
O(z^7)
```

restrict (*min_degree=None, max_degree=None*)

Return the series obtained by keeping only terms of degree between *min_degree* and *max_degree*.

INPUT:

- *min_degree, max_degree* – (optional) integers indicating which degrees to keep

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: alpha = z + 2*z^2 + 3*z^3 + z^4/(1-z)
sage: alpha
z + 2*z^2 + 3*z^3 + z^4 + z^5 + z^6 + O(z^7)
sage: alpha.restrict(2)
2*z^2 + 3*z^3 + z^4 + z^5 + z^6 + O(z^7)
sage: alpha.restrict(3)
3*z^3 + z^4 + z^5 + z^6 + O(z^7)
sage: alpha.restrict(3, 6)
3*z^3 + z^4 + z^5 + z^6
sage: alpha.restrict(max_degree=6)
z + 2*z^2 + 3*z^3 + z^4 + z^5 + z^6

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: exp(z).restrict(3)
1/6*z^3 + 1/24*z^4 + 1/120*z^5 + 1/720*z^6 + 1/5040*z^7 + 1/40320*z^8 + 1/
↳362880*z^9 + O(z^10)
```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> alpha = z + Integer(2)*z**Integer(2) + Integer(3)*z**Integer(3) +
↳ z**Integer(4)/(Integer(1)-z)
>>> alpha
z + 2*z^2 + 3*z^3 + z^4 + z^5 + z^6 + O(z^7)
>>> alpha.restrict(Integer(2))
2*z^2 + 3*z^3 + z^4 + z^5 + z^6 + O(z^7)
>>> alpha.restrict(Integer(3))
3*z^3 + z^4 + z^5 + z^6 + O(z^7)
>>> alpha.restrict(Integer(3), Integer(6))
3*z^3 + z^4 + z^5 + z^6
>>> alpha.restrict(max_degree=Integer(6))
z + 2*z^2 + 3*z^3 + z^4 + z^5 + z^6

>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> exp(z).restrict(Integer(3))
1/6*z^3 + 1/24*z^4 + 1/120*z^5 + 1/720*z^6 + 1/5040*z^7 + 1/40320*z^8 + 1/
↳ 362880*z^9 + O(z^10)

```

sec()

Return the secant of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: sec(z)
1 + 1/2*z^2 + 5/24*z^4 + 61/720*z^6 + O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: sec(x/(1-y)).polynomial(4)
5/24*x^4 + 3/2*x^2*y^2 + x^2*y + 1/2*x^2 + 1

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> sec(z)
1 + 1/2*z^2 + 5/24*z^4 + 61/720*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↳ ngens(2)
>>> sec(x/(Integer(1)-y)).polynomial(Integer(4))
5/24*x^4 + 3/2*x^2*y^2 + x^2*y + 1/2*x^2 + 1

```

sech()

Return the hyperbolic secant of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: sech(z)
↳ needs sage.libs.flint
1 - 1/2*z^2 + 5/24*z^4 - 61/720*z^6 + O(z^7)

```

(continues on next page)

(continued from previous page)

```

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: sech(x/(1-y))
↪needs sage.libs.flint
1 - 1/2*x^2 - x^2*y + (5/24*x^4-3/2*x^2*y^2) + (5/6*x^4*y-2*x^2*y^3)
- (61/720*x^6-25/12*x^4*y^2+5/2*x^2*y^4) + O(x,y)^7
#_

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> sech(z)
↪needs sage.libs.flint
1 - 1/2*z^2 + 5/24*z^4 - 61/720*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↪ngens(2)
>>> sech(x/(Integer(1)-y))
↪# needs sage.libs.flint
1 - 1/2*x^2 - x^2*y + (5/24*x^4-3/2*x^2*y^2) + (5/6*x^4*y-2*x^2*y^3)
- (61/720*x^6-25/12*x^4*y^2+5/2*x^2*y^4) + O(x,y)^7
_

```

set (*s*)alias of `define()`.**shift** (*n*)Return `self` with the indices shifted by *n*.

For example, a Laurent series is multiplied by the power z^n , where z is the variable of `self`. For series with a fixed minimal valuation (e.g., power series), this removes any terms that are less than the minimal valuation.

INPUT:

- *n* – the amount to shift

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: f = 1 / (1 + 2*z)
sage: f
1 - 2*z + 4*z^2 - 8*z^3 + 16*z^4 - 32*z^5 + 64*z^6 + O(z^7)
sage: f.shift(3)
z^3 - 2*z^4 + 4*z^5 - 8*z^6 + 16*z^7 - 32*z^8 + 64*z^9 + O(z^10)
sage: f << -3 # shorthand
z^-3 - 2*z^-2 + 4*z^-1 - 8 + 16*z - 32*z^2 + 64*z^3 + O(z^4)
sage: g = z^-3 + 3 + z^2
sage: g.shift(5)
z^2 + 3*z^5 + z^7
sage: L([2,0,3], valuation=2, degree=7, constant=1) << -2
2 + 3*z^2 + z^5 + z^6 + z^7 + O(z^8)

sage: D = LazyDirichletSeriesRing(QQ, 't')
sage: f = D([0,1,2])
sage: f
↪needs sage.symbolic
1/(2^t) + 2/3^t
sage: sf = f.shift(3)

```

(continues on next page)

(continued from previous page)

```

sage: sf
↪needs sage.symbolic
1/(5^t) + 2/6^t
#_

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = Integer(1) / (Integer(1) + Integer(2)*z)
>>> f
1 - 2*z + 4*z^2 - 8*z^3 + 16*z^4 - 32*z^5 + 64*z^6 + O(z^7)
>>> f.shift(Integer(3))
z^3 - 2*z^4 + 4*z^5 - 8*z^6 + 16*z^7 - 32*z^8 + 64*z^9 + O(z^10)
>>> f << -Integer(3) # shorthand
z^-3 - 2*z^-2 + 4*z^-1 - 8 + 16*z - 32*z^2 + 64*z^3 + O(z^4)
>>> g = z**Integer(3) + Integer(3) + z**Integer(2)
>>> g.shift(Integer(5))
z^2 + 3*z^5 + z^7
>>> L([Integer(2), Integer(0), Integer(3)], valuation=Integer(2),
↪degree=Integer(7), constant=Integer(1)) << -Integer(2)
2 + 3*z^2 + z^5 + z^6 + z^7 + O(z^8)

>>> D = LazyDirichletSeriesRing(QQ, 't')
>>> f = D([Integer(0), Integer(1), Integer(2)])
>>> f
↪needs sage.symbolic
1/(2^t) + 2/3^t
>>> sf = f.shift(Integer(3))
>>> sf
↪needs sage.symbolic
1/(5^t) + 2/6^t
#_

```

Examples with power series (where the minimal valuation is 0):

```

sage: L.<x> = LazyPowerSeriesRing(QQ)
sage: f = 1 / (1 - x)
sage: f.shift(2)
x^2 + x^3 + x^4 + O(x^5)
sage: g = f.shift(-1); g
1 + x + x^2 + O(x^3)
sage: f == g
True
sage: g[-1]
0
sage: h = L(lambda n: 1)
sage: LazyPowerSeriesRing.options.halting_precision(20) # verify up to
↪degree 20
sage: f == h
True
sage: h == f
True
sage: h.shift(-1) == h
True
sage: LazyPowerSeriesRing.options._reset()

```

(continues on next page)

(continued from previous page)

```

sage: fp = L([3,3,3], constant=1)
sage: fp.shift(2)
3*x^2 + 3*x^3 + 3*x^4 + x^5 + x^6 + x^7 + O(x^8)
sage: fp.shift(-2)
3 + x + x^2 + x^3 + O(x^4)
sage: fp.shift(-7)
1 + x + x^2 + O(x^3)
sage: fp.shift(-5) == g
True

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> f = Integer(1) / (Integer(1) - x)
>>> f.shift(Integer(2))
x^2 + x^3 + x^4 + O(x^5)
>>> g = f.shift(-Integer(1)); g
1 + x + x^2 + O(x^3)
>>> f == g
True
>>> g[-Integer(1)]
0
>>> h = L(lambda n: Integer(1))
>>> LazyPowerSeriesRing.options.halting_precision(Integer(20)) # verify up
↳to degree 20
>>> f == h
True
>>> h == f
True
>>> h.shift(-Integer(1)) == h
True
>>> LazyPowerSeriesRing.options._reset()

>>> fp = L([Integer(3), Integer(3), Integer(3)], constant=Integer(1))
>>> fp.shift(Integer(2))
3*x^2 + 3*x^3 + 3*x^4 + x^5 + x^6 + x^7 + O(x^8)
>>> fp.shift(-Integer(2))
3 + x + x^2 + x^3 + O(x^4)
>>> fp.shift(-Integer(7))
1 + x + x^2 + O(x^3)
>>> fp.shift(-Integer(5)) == g
True

```

We compare the shifting with converting to the fraction field (see also [Issue #35293](#)):

```

sage: M = L.fraction_field()
sage: f = L([1,2,3,4]); f
1 + 2*x + 3*x^2 + 4*x^3
sage: f.shift(-3)
4
sage: M(f).shift(-3)
x^-3 + 2*x^-2 + 3*x^-1 + 4

```

```

>>> from sage.all import *
>>> M = L.fraction_field()
>>> f = L([Integer(1), Integer(2), Integer(3), Integer(4)]); f
1 + 2*x + 3*x^2 + 4*x^3
>>> f.shift(-Integer(3))
4
>>> M(f).shift(-Integer(3))
x^-3 + 2*x^-2 + 3*x^-1 + 4

```

An example with a more general function:

```

sage: fun = lambda n: 1 if ZZ(n).is_power_of(2) else 0
sage: f = L(fun); f
x + x^2 + x^4 + O(x^7)
sage: fs = f.shift(-4)
sage: fs
1 + x^4 + O(x^7)
sage: fs.shift(4)
x^4 + x^8 + O(x^11)
sage: M(f).shift(-4)
x^-3 + x^-2 + 1 + O(x^4)

```

```

>>> from sage.all import *
>>> fun = lambda n: Integer(1) if ZZ(n).is_power_of(Integer(2)) else_
↳ Integer(0)
>>> f = L(fun); f
x + x^2 + x^4 + O(x^7)
>>> fs = f.shift(-Integer(4))
>>> fs
1 + x^4 + O(x^7)
>>> fs.shift(Integer(4))
x^4 + x^8 + O(x^11)
>>> M(f).shift(-Integer(4))
x^-3 + x^-2 + 1 + O(x^4)

```

sin()

Return the sine of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: sin(z)
z - 1/6*z^3 + 1/120*z^5 - 1/5040*z^7 + O(z^8)

sage: sin(1 + z)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: sin(x/(1-y)).polynomial(3)
-1/6*x^3 + x*y^2 + x*y + x

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> sin(z)
z - 1/6*z^3 + 1/120*z^5 - 1/5040*z^7 + O(z^8)

>>> sin(Integer(1) + z)
Traceback (most recent call last):
...
ValueError: can only compose with a positive valuation series

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> sin(x/(Integer(1)-y)).polynomial(Integer(3))
-1/6*x^3 + x*y^2 + x*y + x

```

sinh()

Return the hyperbolic sine of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: sinh(z)
z + 1/6*z^3 + 1/120*z^5 + 1/5040*z^7 + O(z^8)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: sinh(x/(1-y))
x + x*y + (1/6*x^3+x*y^2) + (1/2*x^3*y+x*y^3)
+ (1/120*x^5+x^3*y^2+x*y^4) + (1/24*x^5*y+5/3*x^3*y^3+x*y^5)
+ (1/5040*x^7+1/8*x^5*y^2+5/2*x^3*y^4+x*y^6) + O(x,y)^8

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> sinh(z)
z + 1/6*z^3 + 1/120*z^5 + 1/5040*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> sinh(x/(Integer(1)-y))
x + x*y + (1/6*x^3+x*y^2) + (1/2*x^3*y+x*y^3)
+ (1/120*x^5+x^3*y^2+x*y^4) + (1/24*x^5*y+5/3*x^3*y^3+x*y^5)
+ (1/5040*x^7+1/8*x^5*y^2+5/2*x^3*y^4+x*y^6) + O(x,y)^8

```

sqrt()

Return $\text{self}^{(1/2)}$.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: sqrt(1+z)
1 + 1/2*z - 1/8*z^2 + 1/16*z^3 - 5/128*z^4 + 7/256*z^5 - 21/1024*z^6 + O(z^7)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: sqrt(1+x/(1-y))

```

(continues on next page)

(continued from previous page)

```

1 + 1/2*x - (1/8*x^2-1/2*x*y) + (1/16*x^3-1/4*x^2*y+1/2*x*y^2)
- (5/128*x^4-3/16*x^3*y+3/8*x^2*y^2-1/2*x*y^3)
+ (7/256*x^5-5/32*x^4*y+3/8*x^3*y^2-1/2*x^2*y^3+1/2*x*y^4)
- (21/1024*x^6-35/256*x^5*y+25/64*x^4*y^2-5/8*x^3*y^3+5/8*x^2*y^4-1/2*x*y^5)
+ O(x,y)^7

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> sqrt(Integer(1)+z)
1 + 1/2*z - 1/8*z^2 + 1/16*z^3 - 5/128*z^4 + 7/256*z^5 - 21/1024*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↳ngens(2)
>>> sqrt(Integer(1)+x/(Integer(1)-y))
1 + 1/2*x - (1/8*x^2-1/2*x*y) + (1/16*x^3-1/4*x^2*y+1/2*x*y^2)
- (5/128*x^4-3/16*x^3*y+3/8*x^2*y^2-1/2*x*y^3)
+ (7/256*x^5-5/32*x^4*y+3/8*x^3*y^2-1/2*x^2*y^3+1/2*x*y^4)
- (21/1024*x^6-35/256*x^5*y+25/64*x^4*y^2-5/8*x^3*y^3+5/8*x^2*y^4-1/2*x*y^5)
+ O(x,y)^7

```

This also works for Dirichlet series:

```

sage: # needs sage.symbolic
sage: D = LazyDirichletSeriesRing(SR, "s")
sage: Z = D(constant=1)
sage: f = sqrt(Z); f
1 + 1/2/2^s + 1/2/3^s + 3/8/4^s + 1/2/5^s + 1/4/6^s + 1/2/7^s + O(1/(8^s))
sage: f*f - Z
O(1/(8^s))

```

```

>>> from sage.all import *
>>> # needs sage.symbolic
>>> D = LazyDirichletSeriesRing(SR, "s")
>>> Z = D(constant=Integer(1))
>>> f = sqrt(Z); f
1 + 1/2/2^s + 1/2/3^s + 3/8/4^s + 1/2/5^s + 1/4/6^s + 1/2/7^s + O(1/(8^s))
>>> f*f - Z
O(1/(8^s))

```

tan()

Return the tangent of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: tan(z)
z + 1/3*z^3 + 2/15*z^5 + 17/315*z^7 + O(z^8)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: tan(x/(1-y)).polynomial(5)
2/15*x^5 + 2*x^3*y^2 + x*y^4 + x^3*y + x*y^3 + 1/3*x^3 + x*y^2 + x*y + x

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> tan(z)
z + 1/3*z^3 + 2/15*z^5 + 17/315*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> tan(x/(Integer(1)-y)).polynomial(Integer(5))
2/15*x^5 + 2*x^3*y^2 + x*y^4 + x^3*y + x*y^3 + 1/3*x^3 + x*y^2 + x*y + x

```

tanh()

Return the hyperbolic tangent of self.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: tanh(z)
↳needs sage.libs.flint
z - 1/3*z^3 + 2/15*z^5 - 17/315*z^7 + O(z^8)

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: tanh(x/(1-y))
↳needs sage.libs.flint
x + x*y - (1/3*x^3-x*y^2) - (x^3*y-x*y^3) + (2/15*x^5-2*x^3*y^2+x*y^4)
+ (2/3*x^5*y-10/3*x^3*y^3+x*y^5) - (17/315*x^7-2*x^5*y^2+5*x^3*y^4-x*y^6) +
↳O(x,y)^8

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> tanh(z)
↳needs sage.libs.flint
z - 1/3*z^3 + 2/15*z^5 - 17/315*z^7 + O(z^8)

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> tanh(x/(Integer(1)-y))
↳ # needs sage.libs.flint
x + x*y - (1/3*x^3-x*y^2) - (x^3*y-x*y^3) + (2/15*x^5-2*x^3*y^2+x*y^4)
+ (2/3*x^5*y-10/3*x^3*y^3+x*y^5) - (17/315*x^7-2*x^5*y^2+5*x^3*y^4-x*y^6) +
↳O(x,y)^8

```

truncate(d)

Return the series obtained by removing all terms of degree at least d.

INPUT:

- d – integer; the degree from which the series is truncated

EXAMPLES:

Dense implementation:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=False)
sage: alpha = 1/(1-z)
sage: alpha

```

(continues on next page)

(continued from previous page)

```

1 + z + z^2 + O(z^3)
sage: beta = alpha.truncate(5)
sage: beta
1 + z + z^2 + z^3 + z^4
sage: alpha - beta
z^5 + z^6 + z^7 + O(z^8)
sage: M = L(lambda n: n, valuation=0); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: M.truncate(4)
z + 2*z^2 + 3*z^3

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, sparse=False, names=('z',)); (z,) = L._
↳first_ngens(1)
>>> alpha = Integer(1)/(Integer(1)-z)
>>> alpha
1 + z + z^2 + O(z^3)
>>> beta = alpha.truncate(Integer(5))
>>> beta
1 + z + z^2 + z^3 + z^4
>>> alpha - beta
z^5 + z^6 + z^7 + O(z^8)
>>> M = L(lambda n: n, valuation=Integer(0)); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> M.truncate(Integer(4))
z + 2*z^2 + 3*z^3

```

Sparse Implementation:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=True)
sage: M = L(lambda n: n, valuation=0); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
sage: M.truncate(4)
z + 2*z^2 + 3*z^3

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, sparse=True, names=('z',)); (z,) = L._first_
↳ngens(1)
>>> M = L(lambda n: n, valuation=Integer(0)); M
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + O(z^7)
>>> M.truncate(Integer(4))
z + 2*z^2 + 3*z^3

```

Series which are known to be exact can also be truncated:

```

sage: M = z + z^2 + z^3 + z^4
sage: M.truncate(4)
z + z^2 + z^3

```

```

>>> from sage.all import *
>>> M = z + z**Integer(2) + z**Integer(3) + z**Integer(4)

```

(continues on next page)

(continued from previous page)

```
>>> M.truncate(Integer(4))
z + z^2 + z^3
```

class sage.rings.lazy_series.**LazyPowerSeries** (*parent, coeff_stream*)

Bases: [LazyCauchyProductSeries](#)

A Taylor series where the coefficients are computed lazily.

EXAMPLES:

```
sage: L.<x, y> = LazyPowerSeriesRing(ZZ)
sage: f = 1 / (1 - x^2 + y^3); f
1 + x^2 - y^3 + x^4 - 2*x^2*y^3 + (x^6+y^6) + O(x,y)^7
sage: P.<x, y> = PowerSeriesRing(ZZ, default_prec=101)
sage: g = 1 / (1 - x^2 + y^3); f[100] - g[100]
0
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('x', 'y',)); (x, y,) = L._first_ngens(2)
>>> f = Integer(1) / (Integer(1) - x**Integer(2) + y**Integer(3)); f
1 + x^2 - y^3 + x^4 - 2*x^2*y^3 + (x^6+y^6) + O(x,y)^7
>>> P = PowerSeriesRing(ZZ, default_prec=Integer(101), names=('x', 'y',)); (x, y,
↪) = P._first_ngens(2)
>>> g = Integer(1) / (Integer(1) - x**Integer(2) + y**Integer(3)); ↪
↪f[Integer(100)] - g[Integer(100)]
0
```

Lazy Taylor series is picklable:

```
sage: g = loads(dumps(f))
sage: g
1 + x^2 - y^3 + x^4 - 2*x^2*y^3 + (x^6+y^6) + O(x,y)^7
sage: g == f
True
```

```
>>> from sage.all import *
>>> g = loads(dumps(f))
>>> g
1 + x^2 - y^3 + x^4 - 2*x^2*y^3 + (x^6+y^6) + O(x,y)^7
>>> g == f
True
```

O(*prec*)

alias of [add_bigoh\(\)](#).

adams_operator(*p*)

Return the image of *self* under the Adams operator of index *p*.

This raises all variables to the power *p*, both the power series variables and the variables inside the coefficient ring.

INPUT:

- *p* – positive integer

EXAMPLES:

With no variables in the base ring:

```
sage: A = LazyPowerSeriesRing(QQ, 't')
sage: f = A([1, 2, 3, 4]); f
1 + 2*t + 3*t^2 + 4*t^3
sage: f.adams_operator(2)
1 + 2*t^2 + 3*t^4 + 4*t^6
```

```
>>> from sage.all import *
>>> A = LazyPowerSeriesRing(QQ, 't')
>>> f = A([Integer(1), Integer(2), Integer(3), Integer(4)]); f
1 + 2*t + 3*t^2 + 4*t^3
>>> f.adams_operator(Integer(2))
1 + 2*t^2 + 3*t^4 + 4*t^6
```

With variables in the base ring:

```
sage: q = polygen(QQ, 'q')
sage: A = LazyPowerSeriesRing(q.parent(), 't')
sage: f = A([0, 1+q, 2, 3+q**2]); f
((q+1)*t) + 2*t^2 + ((q^2+3)*t^3)
sage: f.adams_operator(2)
((q^2+1)*t^2) + 2*t^4 + ((q^4+3)*t^6)
```

```
>>> from sage.all import *
>>> q = polygen(QQ, 'q')
>>> A = LazyPowerSeriesRing(q.parent(), 't')
>>> f = A([Integer(0), Integer(1)+q, Integer(2), Integer(3)+q**Integer(2)]); f
((q+1)*t) + 2*t^2 + ((q^2+3)*t^3)
>>> f.adams_operator(Integer(2))
((q^2+1)*t^2) + 2*t^4 + ((q^4+3)*t^6)
```

In the multivariate case:

```
sage: A = LazyPowerSeriesRing(ZZ, 't,u')
sage: f = A({(1,2):4, (2,3):6}); f
4*t*u^2 + 6*t^2*u^3
sage: f.adams_operator(3)
4*t^3*u^6 + 6*t^6*u^9
```

```
>>> from sage.all import *
>>> A = LazyPowerSeriesRing(ZZ, 't,u')
>>> f = A({(Integer(1), Integer(2)):Integer(4), (Integer(2),
↳ Integer(3)):Integer(6)}); f
4*t*u^2 + 6*t^2*u^3
>>> f.adams_operator(Integer(3))
4*t^3*u^6 + 6*t^6*u^9
```

add_bigoh(prec)

Return the power series of precision at most `prec` obtained by adding $O(q^{\text{prec}})$ to f , where q is the (tuple of) variable(s).

EXAMPLES:


```

sage: L.<x,y> = LazyPowerSeriesRing(QQ)
sage: f = 1 / (1 - x + y)
sage: f
1 + (x-y) + (x^2-2*x*y+y^2) + (x^3-3*x^2*y+3*x*y^2-y^3)
+ (x^4-4*x^3*y+6*x^2*y^2-4*x*y^3+y^4)
+ (x^5-5*x^4*y+10*x^3*y^2-10*x^2*y^3+5*x*y^4-y^5)
+ (x^6-6*x^5*y+15*x^4*y^2-20*x^3*y^3+15*x^2*y^4-6*x*y^5+y^6)
+ O(x,y)^7
sage: f3 = f.add_bigoh(3); f3
1 + x - y + x^2 - 2*x*y + y^2 + O(x, y)^3
sage: f3.parent()
Multivariate Power Series Ring in x, y over Rational Field

sage: R.<t> = QQ[]
sage: L.<x> = LazyPowerSeriesRing(R)
sage: f = 1 / (1 - t^3*x)
sage: f
1 + t^3*x + t^6*x^2 + t^9*x^3 + t^12*x^4 + t^15*x^5 + t^18*x^6 + O(x^7)
sage: f3 = f.add_bigoh(3); f3
1 + t^3*x + t^6*x^2 + O(x^3)
sage: f3.parent()
Power Series Ring in x over Univariate Polynomial Ring in t
over Rational Field

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y')); (x, y) = L._first_
↳ngens(2)
>>> f = Integer(1) / (Integer(1) - x + y)
>>> f
1 + (x-y) + (x^2-2*x*y+y^2) + (x^3-3*x^2*y+3*x*y^2-y^3)
+ (x^4-4*x^3*y+6*x^2*y^2-4*x*y^3+y^4)
+ (x^5-5*x^4*y+10*x^3*y^2-10*x^2*y^3+5*x*y^4-y^5)
+ (x^6-6*x^5*y+15*x^4*y^2-20*x^3*y^3+15*x^2*y^4-6*x*y^5+y^6)
+ O(x,y)^7
>>> f3 = f.add_bigoh(Integer(3)); f3
1 + x - y + x^2 - 2*x*y + y^2 + O(x, y)^3
>>> f3.parent()
Multivariate Power Series Ring in x, y over Rational Field

>>> R = QQ['t']; (t,) = R._first_ngens(1)
>>> L = LazyPowerSeriesRing(R, names=('x',)); (x,) = L._first_ngens(1)
>>> f = Integer(1) / (Integer(1) - t**Integer(3)*x)
>>> f
1 + t^3*x + t^6*x^2 + t^9*x^3 + t^12*x^4 + t^15*x^5 + t^18*x^6 + O(x^7)
>>> f3 = f.add_bigoh(Integer(3)); f3
1 + t^3*x + t^6*x^2 + O(x^3)
>>> f3.parent()
Power Series Ring in x over Univariate Polynomial Ring in t
over Rational Field

```

compose(*g)

Return the composition of self with g.

The arity of `self` must be equal to the number of arguments provided.

Given a Taylor series f of arity n and a tuple of Taylor series $g = (g_1, \dots, g_n)$ over the same base ring, the composition $f \circ g$ is defined if and only if for each $1 \leq i \leq n$:

- g_i is zero, or
- setting all variables except the i -th in f to zero yields a polynomial, or
- $\text{val}(g_i) > 0$.

If f is a univariate ‘exact’ series, we can check whether f is actually a polynomial. However, if f is a multivariate series, we have no way to test whether setting all but one variable of f to zero yields a polynomial, except if f itself is ‘exact’ and therefore a polynomial.

INPUT:

- g – other series, all can be coerced into the same parent

EXAMPLES:

```
sage: L.<x, y, z> = LazyPowerSeriesRing(QQ)
sage: M.<a, b> = LazyPowerSeriesRing(ZZ)
sage: g1 = 1 / (1 - x)
sage: g2 = x + y^2
sage: p = a^2 + b + 1
sage: p(g1, g2) - g1^2 - g2 - 1
O(x,y,z)^7
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y', 'z')); (x, y, z) = L._
↳first_ngens(3)
>>> M = LazyPowerSeriesRing(ZZ, names=('a', 'b')); (a, b) = M._first_
↳ngens(2)
>>> g1 = Integer(1) / (Integer(1) - x)
>>> g2 = x + y**Integer(2)
>>> p = a**Integer(2) + b + Integer(1)
>>> p(g1, g2) - g1**Integer(2) - g2 - Integer(1)
O(x,y,z)^7
```

The number of mappings from a set with m elements to a set with n elements:

```
sage: M.<a> = LazyPowerSeriesRing(QQ)
sage: Ea = M(lambda n: 1/factorial(n))
sage: Ex = L(lambda n: 1/factorial(n)*x^n)
sage: Ea(Ex*y)[5]
1/24*x^4*y + 2/3*x^3*y^2 + 3/4*x^2*y^3 + 1/6*x*y^4 + 1/120*y^5
```

```
>>> from sage.all import *
>>> M = LazyPowerSeriesRing(QQ, names=('a',)); (a,) = M._first_ngens(1)
>>> Ea = M(lambda n: Integer(1)/factorial(n))
>>> Ex = L(lambda n: Integer(1)/factorial(n)*x**n)
>>> Ea(Ex*y)[Integer(5)]
1/24*x^4*y + 2/3*x^3*y^2 + 3/4*x^2*y^3 + 1/6*x*y^4 + 1/120*y^5
```

So, there are $3!2!2/3 = 8$ mappings from a three element set to a two element set.

We perform the composition with a lazy Laurent series:

```

sage: N.<w> = LazyLaurentSeriesRing(QQ)
sage: f1 = 1 / (1 - w)
sage: f2 = cot(w / (1 - w))
sage: p(f1, f2)
w^-1 + 1 + 5/3*w + 8/3*w^2 + 164/45*w^3 + 23/5*w^4 + 5227/945*w^5 + O(w^6)

```

```

>>> from sage.all import *
>>> N = LazyLaurentSeriesRing(QQ, names=('w',)); (w,) = N._first_ngens(1)
>>> f1 = Integer(1) / (Integer(1) - w)
>>> f2 = cot(w / (Integer(1) - w))
>>> p(f1, f2)
w^-1 + 1 + 5/3*w + 8/3*w^2 + 164/45*w^3 + 23/5*w^4 + 5227/945*w^5 + O(w^6)

```

We perform the composition with a lazy Dirichlet series:

```

sage: # needs sage.symbolic
sage: D = LazyDirichletSeriesRing(QQ, "s")
sage: g = D(constant=1)-1
sage: g
1/(2^s) + 1/(3^s) + 1/(4^s) + O(1/(5^s))
sage: f = 1 / (1 - x - y*z); f
1 + x + (x^2+y*z) + (x^3+2*x*y*z) + (x^4+3*x^2*y*z+y^2*z^2)
+ (x^5+4*x^3*y*z+3*x*y^2*z^2)
+ (x^6+5*x^4*y*z+6*x^2*y^2*z^2+y^3*z^3)
+ O(x,y,z)^7
sage: fog = f(g, g, g)
sage: fog
1 + 1/(2^s) + 1/(3^s) + 3/4^s + 1/(5^s) + 5/6^s + O(1/(7^s))
sage: fg = 1 / (1 - g - g*g)
sage: fg
1 + 1/(2^s) + 1/(3^s) + 3/4^s + 1/(5^s) + 5/6^s + 1/(7^s) + O(1/(8^s))
sage: fog - fg
O(1/(8^s))

sage: f = 1 / (1 - 2*a)
sage: f(g)
↪needs sage.symbolic
1 + 2/2^s + 2/3^s + 6/4^s + 2/5^s + 10/6^s + 2/7^s + O(1/(8^s))
sage: 1 / (1 - 2*g)
↪needs sage.symbolic
1 + 2/2^s + 2/3^s + 6/4^s + 2/5^s + 10/6^s + 2/7^s + O(1/(8^s))

```

```

>>> from sage.all import *
>>> # needs sage.symbolic
>>> D = LazyDirichletSeriesRing(QQ, "s")
>>> g = D(constant=Integer(1))-Integer(1)
>>> g
1/(2^s) + 1/(3^s) + 1/(4^s) + O(1/(5^s))
>>> f = Integer(1) / (Integer(1) - x - y*z); f
1 + x + (x^2+y*z) + (x^3+2*x*y*z) + (x^4+3*x^2*y*z+y^2*z^2)
+ (x^5+4*x^3*y*z+3*x*y^2*z^2)
+ (x^6+5*x^4*y*z+6*x^2*y^2*z^2+y^3*z^3)

```

(continues on next page)

(continued from previous page)

```

+ O(x,y,z)^7
>>> fog = f(g, g, g)
>>> fog
1 + 1/(2^s) + 1/(3^s) + 3/4^s + 1/(5^s) + 5/6^s + O(1/(7^s))
>>> fg = Integer(1) / (Integer(1) - g - g*g)
>>> fg
1 + 1/(2^s) + 1/(3^s) + 3/4^s + 1/(5^s) + 5/6^s + 1/(7^s) + O(1/(8^s))
>>> fog - fg
O(1/(8^s))

>>> f = Integer(1) / (Integer(1) - Integer(2)*a)
>>> f(g)                                     #
↳needs sage.symbolic
1 + 2/2^s + 2/3^s + 6/4^s + 2/5^s + 10/6^s + 2/7^s + O(1/(8^s))
>>> Integer(1) / (Integer(1) - Integer(2)*g)
↳                                     # needs sage.symbolic
1 + 2/2^s + 2/3^s + 6/4^s + 2/5^s + 10/6^s + 2/7^s + O(1/(8^s))

```

The output parent is always the common parent between the base ring of f and the parent of g or extended to the corresponding lazy series:

```

sage: T.<x,y> = LazyPowerSeriesRing(QQ)
sage: R.<a,b,c> = ZZ[]
sage: S.<v> = R[]
sage: L.<z> = LaurentPolynomialRing(ZZ)
sage: parent(x(a, b))
Multivariate Polynomial Ring in a, b, c over Rational Field
sage: parent(x(CC(2), a))
Multivariate Polynomial Ring in a, b, c over Complex Field with 53 bits of
↳precision
sage: parent(x(0, 0))
Rational Field
sage: f = 1 / (1 - x - y); f
1 + (x+y) + (x^2+2*x*y+y^2) + (x^3+3*x^2*y+3*x*y^2+y^3)
+ (x^4+4*x^3*y+6*x^2*y^2+4*x*y^3+y^4)
+ (x^5+5*x^4*y+10*x^3*y^2+10*x^2*y^3+5*x*y^4+y^5)
+ (x^6+6*x^5*y+15*x^4*y^2+20*x^3*y^3+15*x^2*y^4+6*x*y^5+y^6)
+ O(x,y)^7
sage: f(a^2, b*c)
1 + (a^2+b*c) + (a^4+2*a^2*b*c+b^2*c^2) + (a^6+3*a^4*b*c+3*a^2*b^2*c^2+b^3*c^
↳3) + O(a,b,c)^7
sage: f(v, v^2)
1 + v + 2*v^2 + 3*v^3 + 5*v^4 + 8*v^5 + 13*v^6 + O(v^7)
sage: f(z, z^2 + z)
1 + 2*z + 5*z^2 + 12*z^3 + 29*z^4 + 70*z^5 + 169*z^6 + O(z^7)
sage: three = T(3)(a^2, b); three
3
sage: parent(three)
Multivariate Polynomial Ring in a, b, c over Rational Field

```

```

>>> from sage.all import *
>>> T = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = T._first_

```

(continues on next page)

(continued from previous page)

```

↪ngens(2)
>>> R = ZZ['a, b, c']; (a, b, c) = R._first_ngens(3)
>>> S = R['v']; (v,) = S._first_ngens(1)
>>> L = LaurentPolynomialRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> parent(x(a, b))
Multivariate Polynomial Ring in a, b, c over Rational Field
>>> parent(x(CC(Integer(2)), a))
Multivariate Polynomial Ring in a, b, c over Complex Field with 53 bits of
↪precision
>>> parent(x(Integer(0), Integer(0)))
Rational Field
>>> f = Integer(1) / (Integer(1) - x - y); f
1 + (x+y) + (x^2+2*x*y+y^2) + (x^3+3*x^2*y+3*x*y^2+y^3)
+ (x^4+4*x^3*y+6*x^2*y^2+4*x*y^3+y^4)
+ (x^5+5*x^4*y+10*x^3*y^2+10*x^2*y^3+5*x*y^4+y^5)
+ (x^6+6*x^5*y+15*x^4*y^2+20*x^3*y^3+15*x^2*y^4+6*x*y^5+y^6)
+ O(x,y)^7
>>> f(a**Integer(2), b*c)
1 + (a^2+b*c) + (a^4+2*a^2*b*c+b^2*c^2) + (a^6+3*a^4*b*c+3*a^2*b^2*c^2+b^3*c^
↪3) + O(a,b,c)^7
>>> f(v, v**Integer(2))
1 + v + 2*v^2 + 3*v^3 + 5*v^4 + 8*v^5 + 13*v^6 + O(v^7)
>>> f(z, z**Integer(2) + z)
1 + 2*z + 5*z^2 + 12*z^3 + 29*z^4 + 70*z^5 + 169*z^6 + O(z^7)
>>> three = T(Integer(3))(a**Integer(2), b); three
3
>>> parent(three)
Multivariate Polynomial Ring in a, b, c over Rational Field

```

compositional_inverse()alias of `revert()`.**compute_coefficients(i)**Compute all the coefficients of `self` up to `i`.

This method is deprecated, it has no effect anymore.

derivative(*args)

Return the derivative of the Taylor series.

Multiple variables and iteration counts may be supplied; see the documentation of `sage.calculus.functional.derivative()` function for details.

EXAMPLES:

```

sage: T.<z> = LazyPowerSeriesRing(ZZ)
sage: z.derivative()
1
sage: (1 + z + z^2).derivative(3)
0
sage: (z^2 + z^4 + z^10).derivative(3)
24*z + 720*z^7
sage: (1 / (1-z)).derivative()
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)

```

(continues on next page)

(continued from previous page)

```

sage: T([1, 1, 1], constant=4).derivative()
1 + 2*z + 12*z^2 + 16*z^3 + 20*z^4 + 24*z^5 + 28*z^6 + O(z^7)

sage: R.<q> = QQ[]
sage: L.<x, y> = LazyPowerSeriesRing(R)
sage: f = 1 / (1-q*x+y); f
1 + (q*x-y) + (q^2*x^2+(-2*q)*x*y+y^2)
+ (q^3*x^3+(-3*q^2)*x^2*y+3*q*x*y^2-y^3)
+ (q^4*x^4+(-4*q^3)*x^3*y+6*q^2*x^2*y^2+(-4*q)*x*y^3+y^4)
+ (q^5*x^5+(-5*q^4)*x^4*y+10*q^3*x^3*y^2+(-10*q^2)*x^2*y^3+5*q*x*y^4-y^5)
+ (q^6*x^6+(-6*q^5)*x^5*y+15*q^4*x^4*y^2+(-20*q^3)*x^3*y^3+15*q^2*x^2*y^4+(-
↪ 6*q)*x*y^5+y^6)
+ O(x, y)^7
sage: f.derivative(q)
x + (2*q*x^2+(-2)*x*y) + (3*q^2*x^3+(-6*q)*x^2*y+3*x*y^2)
+ (4*q^3*x^4+(-12*q^2)*x^3*y+12*q*x^2*y^2+(-4)*x*y^3)
+ (5*q^4*x^5+(-20*q^3)*x^4*y+30*q^2*x^3*y^2+(-20*q)*x^2*y^3+5*x*y^4)
+ (6*q^5*x^6+(-30*q^4)*x^5*y+60*q^3*x^4*y^2+(-60*q^2)*x^3*y^3+30*q*x^2*y^4+(-
↪ 6)*x*y^5)
+ O(x, y)^7

```

```

>>> from sage.all import *
>>> T = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = T._first_ngens(1)
>>> z.derivative()
1
>>> (Integer(1) + z + z**Integer(2)).derivative(Integer(3))
0
>>> (z**Integer(2) + z**Integer(4) + z**Integer(10)).derivative(Integer(3))
24*z + 720*z^7
>>> (Integer(1) / (Integer(1)-z)).derivative()
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
>>> T([Integer(1), Integer(1), Integer(1)], constant=Integer(4)).derivative()
1 + 2*z + 12*z^2 + 16*z^3 + 20*z^4 + 24*z^5 + 28*z^6 + O(z^7)

>>> R = QQ['q']; (q,) = R._first_ngens(1)
>>> L = LazyPowerSeriesRing(R, names=('x', 'y',)); (x, y,) = L._first_ngens(2)
>>> f = Integer(1) / (Integer(1)-q*x+y); f
1 + (q*x-y) + (q^2*x^2+(-2*q)*x*y+y^2)
+ (q^3*x^3+(-3*q^2)*x^2*y+3*q*x*y^2-y^3)
+ (q^4*x^4+(-4*q^3)*x^3*y+6*q^2*x^2*y^2+(-4*q)*x*y^3+y^4)
+ (q^5*x^5+(-5*q^4)*x^4*y+10*q^3*x^3*y^2+(-10*q^2)*x^2*y^3+5*q*x*y^4-y^5)
+ (q^6*x^6+(-6*q^5)*x^5*y+15*q^4*x^4*y^2+(-20*q^3)*x^3*y^3+15*q^2*x^2*y^4+(-
↪ 6*q)*x*y^5+y^6)
+ O(x, y)^7
>>> f.derivative(q)
x + (2*q*x^2+(-2)*x*y) + (3*q^2*x^3+(-6*q)*x^2*y+3*x*y^2)
+ (4*q^3*x^4+(-12*q^2)*x^3*y+12*q*x^2*y^2+(-4)*x*y^3)
+ (5*q^4*x^5+(-20*q^3)*x^4*y+30*q^2*x^3*y^2+(-20*q)*x^2*y^3+5*x*y^4)
+ (6*q^5*x^6+(-30*q^4)*x^5*y+60*q^3*x^4*y^2+(-60*q^2)*x^3*y^3+30*q*x^2*y^4+(-
↪ 6)*x*y^5)
+ O(x, y)^7

```

Multivariate:

```

sage: L.<x,y,z> = LazyPowerSeriesRing(QQ)
sage: f = (x + y^2 + z)^3; f
(x^3+3*x^2*z+3*x*z^2+z^3) + (3*x^2*y^2+6*x*y^2*z+3*y^2*z^2) + (3*x*y^4+3*y^
↪4*z) + y^6
sage: f.derivative(x)
(3*x^2+6*x*z+3*z^2) + (6*x*y^2+6*y^2*z) + 3*y^4
sage: f.derivative(y, 5)
720*y
sage: f.derivative(z, 5)
0
sage: f.derivative(x, y, z)
12*y

sage: f = (1 + x + y^2 + z)^-1
sage: f.derivative(x)
-1 + (2*x+2*z) - (3*x^2-2*y^2+6*x*z+3*z^2) + ... + O(x,y,z)^6
sage: f.derivative(y, 2)
-2 + (4*x+4*z) - (6*x^2-12*y^2+12*x*z+6*z^2) + ... + O(x,y,z)^5
sage: f.derivative(x, y)
4*y - (12*x*y+12*y*z) + (24*x^2*y-12*y^3+48*x*y*z+24*y*z^2)
- (40*x^3*y-48*x*y^3+120*x^2*y*z-48*y^3*z+120*x*y*z^2+40*y*z^3) + O(x,y,z)^5
sage: f.derivative(x, y, z)
-12*y + (48*x*y+48*y*z) - (120*x^2*y-48*y^3+240*x*y*z+120*y*z^2) + O(x,y,z)^4

sage: R.<t> = QQ[]
sage: L.<x,y,z> = LazyPowerSeriesRing(R)
sage: f = ((t^2-3)*x + t*y^2 - t*z)^2
sage: f.derivative(t,x,t,y)
24*t*y
sage: f.derivative(t, 2)
(12*t^2-12)*x^2+(-12*t)*x*z+2*z^2 + (12*t*x*y^2+(-4)*y^2*z) + 2*y^4
sage: f.derivative(z, t)
((-6*t^2+6)*x+4*t*z) + ((-4*t)*y^2)
sage: f.derivative(t, 10)
0

sage: f = (1 + t*(x + y + z))^-1
sage: f.derivative(x, t, y)
4*t + ((-18*t^2)*x+(-18*t^2)*y+(-18*t^2)*z)
+ (48*t^3*x^2+96*t^3*x*y+48*t^3*y^2+96*t^3*x*z+96*t^3*y*z+48*t^3*z^2)
+ ... + O(x,y,z)^5
sage: f.derivative(t, 2)
(2*x^2+4*x*y+2*y^2+4*x*z+4*y*z+2*z^2) + ... + O(x,y,z)^7
sage: f.derivative(x, y, z, t)
(-18*t^2) + (96*t^3*x+96*t^3*y+96*t^3*z) + ... + O(x,y,z)^4

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y', 'z')); (x, y, z,) = L._
↪first_ngens(3)
>>> f = (x + y**Integer(2) + z)**Integer(3); f
(x^3+3*x^2*z+3*x*z^2+z^3) + (3*x^2*y^2+6*x*y^2*z+3*y^2*z^2) + (3*x*y^4+3*y^

```

(continues on next page)

(continued from previous page)

```

↪ 4*z) + y^6
>>> f.derivative(x)
(3*x^2+6*x*z+3*z^2) + (6*x*y^2+6*y^2*z) + 3*y^4
>>> f.derivative(y, Integer(5))
720*y
>>> f.derivative(z, Integer(5))
0
>>> f.derivative(x, y, z)
12*y

>>> f = (Integer(1) + x + y**Integer(2) + z)**-Integer(1)
>>> f.derivative(x)
-1 + (2*x+2*z) - (3*x^2-2*y^2+6*x*z+3*z^2) + ... + O(x,y,z)^6
>>> f.derivative(y, Integer(2))
-2 + (4*x+4*z) - (6*x^2-12*y^2+12*x*z+6*z^2) + ... + O(x,y,z)^5
>>> f.derivative(x, y)
4*y - (12*x*y+12*y*z) + (24*x^2*y-12*y^3+48*x*y*z+24*y*z^2)
- (40*x^3*y-48*x*y^3+120*x^2*y*z-48*y^3*z+120*x*y*z^2+40*y*z^3) + O(x,y,z)^5
>>> f.derivative(x, y, z)
-12*y + (48*x*y+48*y*z) - (120*x^2*y-48*y^3+240*x*y*z+120*y*z^2) + O(x,y,z)^4

>>> R = QQ['t']; (t,) = R._first_ngens(1)
>>> L = LazyPowerSeriesRing(R, names=('x', 'y', 'z',)); (x, y, z,) = L._first_
↪ ngens(3)
>>> f = ((t**Integer(2)-Integer(3))*x + t*y**Integer(2) - t*z)**Integer(2)
>>> f.derivative(t,x,t,y)
24*t*y
>>> f.derivative(t, Integer(2))
((12*t^2-12)*x^2+(-12*t)*x*z+2*z^2) + (12*t*x*y^2+(-4)*y^2*z) + 2*y^4
>>> f.derivative(z, t)
((-6*t^2+6)*x+4*t*z) + ((-4*t)*y^2)
>>> f.derivative(t, Integer(10))
0

>>> f = (Integer(1) + t*(x + y + z))**-Integer(1)
>>> f.derivative(x, t, y)
4*t + ((-18*t^2)*x+(-18*t^2)*y+(-18*t^2)*z)
+ (48*t^3*x^2+96*t^3*x*y+48*t^3*y^2+96*t^3*x*z+96*t^3*y*z+48*t^3*z^2)
+ ... + O(x,y,z)^5
>>> f.derivative(t, Integer(2))
(2*x^2+4*x*y+2*y^2+4*x*z+4*y*z+2*z^2) + ... + O(x,y,z)^7
>>> f.derivative(x, y, z, t)
(-18*t^2) + (96*t^3*x+96*t^3*y+96*t^3*z) + ... + O(x,y,z)^4

```

exponential()Return the exponential series of `self`.This method is deprecated, use `exp()` instead.**integral** (*variable*, *constants=None*)Return the integral of `self` with respect to `variable`.

INPUT:

- `variable` – (optional) the variable to integrate
- `constants` – (optional; keyword-only) list of integration constants for the integrals of `self` (the last constant corresponds to the first integral)

For multivariable series, only `variable` should be specified; the integration constant is taken to be 0.

Now we assume the series is univariate. If the first argument is a list, then this method interprets it as integration constants. If it is a positive integer, the method interprets it as the number of times to integrate the function. If `variable` is not the variable of the power series, then the coefficients are integrated with respect to `variable`. If the integration constants are not specified, they are considered to be 0.

EXAMPLES:

```
sage: L.<t> = LazyPowerSeriesRing(QQ)
sage: f = 2 + 3*t + t^5
sage: f.integral()
2*t + 3/2*t^2 + 1/6*t^6
sage: f.integral([-2, -2])
-2 - 2*t + t^2 + 1/2*t^3 + 1/42*t^7
sage: f.integral(t)
2*t + 3/2*t^2 + 1/6*t^6
sage: f.integral(2)
t^2 + 1/2*t^3 + 1/42*t^7
sage: (t^3 + t^5).integral()
1/4*t^4 + 1/6*t^6
sage: L.zero().integral()
0
sage: L.zero().integral([0, 1, 2, 3])
t + t^2 + 1/2*t^3
sage: L([1, 2, 3], constant=4).integral()
t + t^2 + t^3 + t^4 + 4/5*t^5 + 2/3*t^6 + O(t^7)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('t',)); (t,) = L._first_ngens(1)
>>> f = Integer(2) + Integer(3)*t + t**Integer(5)
>>> f.integral()
2*t + 3/2*t^2 + 1/6*t^6
>>> f.integral([-Integer(2), -Integer(2)])
-2 - 2*t + t^2 + 1/2*t^3 + 1/42*t^7
>>> f.integral(t)
2*t + 3/2*t^2 + 1/6*t^6
>>> f.integral(Integer(2))
t^2 + 1/2*t^3 + 1/42*t^7
>>> (t**Integer(3) + t**Integer(5)).integral()
1/4*t^4 + 1/6*t^6
>>> L.zero().integral()
0
>>> L.zero().integral([Integer(0), Integer(1), Integer(2), Integer(3)])
t + t^2 + 1/2*t^3
>>> L([Integer(1), Integer(2), Integer(3)], constant=Integer(4)).integral()
t + t^2 + t^3 + t^4 + 4/5*t^5 + 2/3*t^6 + O(t^7)
```

We solve the ODE $f'' - f' - 2f = 0$ by solving for f'' , then integrating and applying a recursive definition:

```

sage: R.<C, D> = QQ[]
sage: L.<x> = LazyPowerSeriesRing(R)
sage: f = L.undefined()
sage: f.define((f.derivative() + 2*f).integral(constants=[C, D]))
sage: f
C + D*x + ((C+1/2*D)*x^2) + ((1/3*C+1/2*D)*x^3)
+ ((1/4*C+5/24*D)*x^4) + ((1/12*C+11/120*D)*x^5)
+ ((11/360*C+7/240*D)*x^6) + O(x^7)
sage: f.derivative(2) - f.derivative() - 2*f
O(x^7)

```

```

>>> from sage.all import *
>>> R = QQ['C, D']; (C, D,) = R._first_ngens(2)
>>> L = LazyPowerSeriesRing(R, names=('x',)); (x,) = L._first_ngens(1)
>>> f = L.undefined()
>>> f.define((f.derivative() + Integer(2)*f).integral(constants=[C, D]))
>>> f
C + D*x + ((C+1/2*D)*x^2) + ((1/3*C+1/2*D)*x^3)
+ ((1/4*C+5/24*D)*x^4) + ((1/12*C+11/120*D)*x^5)
+ ((11/360*C+7/240*D)*x^6) + O(x^7)
>>> f.derivative(Integer(2)) - f.derivative() - Integer(2)*f
O(x^7)

```

We compare this with the answer we get from the characteristic polynomial:

```

sage: g = C * exp(-x) + D * exp(2*x); g
(C+D) + ((-C+2*D)*x) + ((1/2*C+2*D)*x^2) + ((-1/6*C+4/3*D)*x^3)
+ ((1/24*C+2/3*D)*x^4) + ((-1/120*C+4/15*D)*x^5)
+ ((1/720*C+4/45*D)*x^6) + O(x^7)
sage: g.derivative(2) - g.derivative() - 2*g
O(x^7)

```

```

>>> from sage.all import *
>>> g = C * exp(-x) + D * exp(Integer(2)*x); g
(C+D) + ((-C+2*D)*x) + ((1/2*C+2*D)*x^2) + ((-1/6*C+4/3*D)*x^3)
+ ((1/24*C+2/3*D)*x^4) + ((-1/120*C+4/15*D)*x^5)
+ ((1/720*C+4/45*D)*x^6) + O(x^7)
>>> g.derivative(Integer(2)) - g.derivative() - Integer(2)*g
O(x^7)

```

Note that C and D are playing different roles, so we need to perform a substitution to the coefficients of f to recover the solution g :

```

sage: fp = f.map_coefficients(lambda c: c(C=C+D, D=2*D-C)); fp
(C+D) + ((-C+2*D)*x) + ((1/2*C+2*D)*x^2) + ((-1/6*C+4/3*D)*x^3)
+ ((1/24*C+2/3*D)*x^4) + ((-1/120*C+4/15*D)*x^5)
+ ((1/720*C+4/45*D)*x^6) + O(x^7)
sage: fp - g
O(x^7)

```

```

>>> from sage.all import *
>>> fp = f.map_coefficients(lambda c: c(C=C+D, D=Integer(2)*D-C)); fp

```

(continues on next page)

(continued from previous page)

```
(C+D) + ((-C+2*D)*x) + ((1/2*C+2*D)*x^2) + ((-1/6*C+4/3*D)*x^3)
+ ((1/24*C+2/3*D)*x^4) + ((-1/120*C+4/15*D)*x^5)
+ ((1/720*C+4/45*D)*x^6) + O(x^7)
>>> fp - g
O(x^7)
```

We can integrate both the series and coefficients:

```
sage: R.<x,y,z> = QQ[]
sage: L.<t> = LazyPowerSeriesRing(R)
sage: f = (x*t^2 + y*t + z)^2; f
z^2 + 2*y*z*t + ((y^2+2*x*z)*t^2) + 2*x*y*t^3 + x^2*t^4
sage: f.integral(x)
x*z^2 + 2*x*y*z*t + ((x*y^2+x^2*z)*t^2) + x^2*y*t^3 + 1/3*x^3*t^4
sage: f.integral(t)
z^2*t + y*z*t^2 + ((1/3*y^2+2/3*x*z)*t^3) + 1/2*x*y*t^4 + 1/5*x^2*t^5
sage: f.integral(y, constants=[x*y*z])
x*y*z + y*z^2*t + 1/2*y^2*z*t^2 + ((1/9*y^3+2/3*x*y*z)*t^3) + 1/4*x*y^2*t^4 +
↪ 1/5*x^2*y*t^5
```

```
>>> from sage.all import *
>>> R = QQ['x, y, z']; (x, y, z) = R._first_ngens(3)
>>> L = LazyPowerSeriesRing(R, names=('t',)); (t,) = L._first_ngens(1)
>>> f = (x**Integer(2) + y*t + z)**Integer(2); f
z^2 + 2*y*z*t + ((y^2+2*x*z)*t^2) + 2*x*y*t^3 + x^2*t^4
>>> f.integral(x)
x*z^2 + 2*x*y*z*t + ((x*y^2+x^2*z)*t^2) + x^2*y*t^3 + 1/3*x^3*t^4
>>> f.integral(t)
z^2*t + y*z*t^2 + ((1/3*y^2+2/3*x*z)*t^3) + 1/2*x*y*t^4 + 1/5*x^2*t^5
>>> f.integral(y, constants=[x*y*z])
x*y*z + y*z^2*t + 1/2*y^2*z*t^2 + ((1/9*y^3+2/3*x*y*z)*t^3) + 1/4*x*y^2*t^4 +
↪ 1/5*x^2*y*t^5
```

We can integrate multivariate power series:

```
sage: R.<t> = QQ[]
sage: L.<x,y,z> = LazyPowerSeriesRing(R)
sage: f = ((t^2 + t) - t * y^2 + t^2 * (y + z))^2; f
(t^4+2*t^3+t^2) + ((2*t^4+2*t^3)*y + (2*t^4+2*t^3)*z)
+ ((t^4-2*t^3-2*t^2)*y^2+2*t^4*y*z+t^4*z^2)
+ ((-2*t^3)*y^3+(-2*t^3)*y^2*z) + t^2*y^4
sage: g = f.integral(x); g
((t^4+2*t^3+t^2)*x) + ((2*t^4+2*t^3)*x*y + (2*t^4+2*t^3)*x*z)
+ ((t^4-2*t^3-2*t^2)*x*y^2+2*t^4*x*y*z+t^4*x*z^2)
+ ((-2*t^3)*x*y^3+(-2*t^3)*x*y^2*z) + t^2*x*y^4
sage: g[0]
0
sage: g[1]
(t^4 + 2*t^3 + t^2)*x
sage: g[2]
(2*t^4 + 2*t^3)*x*y + (2*t^4 + 2*t^3)*x*z
sage: f.integral(z)
```

(continues on next page)

(continued from previous page)

```

((t^4+2*t^3+t^2)*z) + ((2*t^4+2*t^3)*y*z+(t^4+t^3)*z^2)
+ ((t^4-2*t^3-2*t^2)*y^2*z+t^4*y*z^2+1/3*t^4*z^3)
+ ((-2*t^3)*y^3*z+(-t^3)*y^2*z^2) + t^2*y^4*z
sage: f.integral(t)
(1/5*t^5+1/2*t^4+1/3*t^3) + ((2/5*t^5+1/2*t^4)*y+(2/5*t^5+1/2*t^4)*z)
+ ((1/5*t^5-1/2*t^4-2/3*t^3)*y^2+2/5*t^5*y*z+1/5*t^5*z^2)
+ ((-1/2*t^4)*y^3+(-1/2*t^4)*y^2*z) + 1/3*t^3*y^4
sage: L.<x,y,z> = LazyPowerSeriesRing(QQ)
sage: (x + y - z^2).integral(z)
(x*z+y*z) - 1/3*z^3

```

```

>>> from sage.all import *
>>> R = QQ['t']; (t,) = R._first_ngens(1)
>>> L = LazyPowerSeriesRing(R, names=('x', 'y', 'z',)); (x, y, z,) = L._first_
↳ngens(3)
>>> f = ((t**Integer(2) + t) - t * y**Integer(2) + t**Integer(2) * (y +
↳z))**Integer(2); f
(t^4+2*t^3+t^2) + ((2*t^4+2*t^3)*y+(2*t^4+2*t^3)*z)
+ ((t^4-2*t^3-2*t^2)*y^2+2*t^4*y*z+t^4*z^2)
+ ((-2*t^3)*y^3+(-2*t^3)*y^2*z) + t^2*y^4
>>> g = f.integral(x); g
((t^4+2*t^3+t^2)*x) + ((2*t^4+2*t^3)*x*y+(2*t^4+2*t^3)*x*z)
+ ((t^4-2*t^3-2*t^2)*x*y^2+2*t^4*x*y*z+t^4*x*z^2)
+ ((-2*t^3)*x*y^3+(-2*t^3)*x*y^2*z) + t^2*x*y^4
>>> g[Integer(0)]
0
>>> g[Integer(1)]
(t^4 + 2*t^3 + t^2)*x
>>> g[Integer(2)]
(2*t^4 + 2*t^3)*x*y + (2*t^4 + 2*t^3)*x*z
>>> f.integral(z)
((t^4+2*t^3+t^2)*z) + ((2*t^4+2*t^3)*y*z+(t^4+t^3)*z^2)
+ ((t^4-2*t^3-2*t^2)*y^2*z+t^4*y*z^2+1/3*t^4*z^3)
+ ((-2*t^3)*y^3*z+(-t^3)*y^2*z^2) + t^2*y^4*z
>>> f.integral(t)
(1/5*t^5+1/2*t^4+1/3*t^3) + ((2/5*t^5+1/2*t^4)*y+(2/5*t^5+1/2*t^4)*z)
+ ((1/5*t^5-1/2*t^4-2/3*t^3)*y^2+2/5*t^5*y*z+1/5*t^5*z^2)
+ ((-1/2*t^4)*y^3+(-1/2*t^4)*y^2*z) + 1/3*t^3*y^4

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y', 'z',)); (x, y, z,) = L._
↳first_ngens(3)
>>> (x + y - z**Integer(2)).integral(z)
(x*z+y*z) - 1/3*z^3

```

is_unit()

Return whether this element is a unit in the ring.

EXAMPLES:

```

sage: L.<z> = LazyPowerSeriesRing(ZZ)
sage: (2*z).is_unit()

```

(continues on next page)

(continued from previous page)

```
False

sage: (1 + 2*z).is_unit()
True

sage: (3 + 2*z).is_unit()
False

sage: L.<x,y> = LazyPowerSeriesRing(ZZ)
sage: (-1 + 2*x + 3*x*y).is_unit()
True
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> (Integer(2)*z).is_unit()
False

>>> (Integer(1) + Integer(2)*z).is_unit()
True

>>> (Integer(3) + Integer(2)*z).is_unit()
False

>>> L = LazyPowerSeriesRing(ZZ, names=('x', 'y',)); (x, y,) = L._first_
↳ngens(2)
>>> (-Integer(1) + Integer(2)*x + Integer(3)*x*y).is_unit()
True
```

polynomial (*degree=None, names=None*)

Return self as a polynomial if self is actually so.

INPUT:

- degree – None or an integer
- names – names of the variables; if it is None, the name of the variables of the series is used

OUTPUT:

If degree is not None, the terms of the series of degree greater than degree are first truncated. If degree is None and the series is not a polynomial, a `ValueError` is raised.

EXAMPLES:

```
sage: L.<x,y> = LazyPowerSeriesRing(ZZ)
sage: f = x^2 + y*x - x + 2; f
2 - x + (x^2+x*y)
sage: f.polynomial()
x^2 + x*y - x + 2
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('x', 'y',)); (x, y,) = L._first_
↳ngens(2)
>>> f = x**Integer(2) + y*x - x + Integer(2); f
```

(continues on next page)

(continued from previous page)

```

2 - x + (x^2+x*y)
>>> f.polynomial()
x^2 + x*y - x + 2

```

revert()

Return the compositional inverse of `self`.

Given a Taylor series f in one variable, the compositional inverse is a power series g over the same base ring, such that $(f \circ g)(z) = f(g(z)) = z$.

The compositional inverse exists if and only if:

- $\text{val}(f) = 1$, or
- $f = a + bz$ with $a, b \neq 0$.

EXAMPLES:

```

sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: (2*z).revert()
1/2*z
sage: (z-z^2).revert()
z + z^2 + 2*z^3 + 5*z^4 + 14*z^5 + 42*z^6 + 132*z^7 + O(z^8)

sage: s = L(degree=1, constant=-1)
sage: s.revert()
-z - z^2 - z^3 + O(z^4)

sage: s = L(degree=1, constant=1)
sage: s.revert()
z - z^2 + z^3 - z^4 + z^5 - z^6 + z^7 + O(z^8)

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> (Integer(2)*z).revert()
1/2*z
>>> (z-z**Integer(2)).revert()
z + z^2 + 2*z^3 + 5*z^4 + 14*z^5 + 42*z^6 + 132*z^7 + O(z^8)

>>> s = L(degree=Integer(1), constant=-Integer(1))
>>> s.revert()
-z - z^2 - z^3 + O(z^4)

>>> s = L(degree=Integer(1), constant=Integer(1))
>>> s.revert()
z - z^2 + z^3 - z^4 + z^5 - z^6 + z^7 + O(z^8)

```

Warning

For series not known to be eventually constant (e.g., being defined by a function) with approximate valuation ≤ 1 (but not necessarily its true valuation), this assumes that this is the actual valuation:

```

sage: f = L(lambda n: n if n > 2 else 0)
sage: f.revert()
<repr(... failed: ValueError: generator already executing>

```

```
>>> from sage.all import *
>>> f = L(lambda n: n if n > Integer(2) else Integer(0))
>>> f.revert()
<repr(... failed: ValueError: generator already executing>
```

class sage.rings.lazy_series.LazyPowerSeries_gcd_mixin

Bases: object

A lazy power series that also implements the GCD algorithm.

gcd(other)

Return the greatest common divisor of *self* and *other*.

EXAMPLES:

```
sage: L.<x> = LazyPowerSeriesRing(QQ)
sage: a = 16*x^5 / (1 - 5*x)
sage: b = (22*x^2 + x^8) / (1 - 4*x^2)
sage: a.gcd(b)
x^2
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> a = Integer(16)*x**Integer(5) / (Integer(1) - Integer(5)*x)
>>> b = (Integer(22)*x**Integer(2) + x**Integer(8)) / (Integer(1) -
↳ Integer(4)*x**Integer(2))
>>> a.gcd(b)
x^2
```

xgcd(f)

Return the extended gcd of *self* and *f*.

OUTPUT:

A triple (*g*, *s*, *t*) such that *g* is the gcd of *self* and *f*, and *s* and *t* are cofactors satisfying the Bezout identity

$$g = s \cdot \text{self} + t \cdot f.$$

EXAMPLES:

```
sage: L.<x> = LazyPowerSeriesRing(QQ)
sage: a = 16*x^5 / (1 - 2*x)
sage: b = (22*x^3 + x^8) / (1 - 3*x^2)
sage: g, s, t = a.xgcd(b)
sage: g
x^3
sage: s
1/22 - 41/242*x^2 - 8/121*x^3 + 120/1331*x^4 + 1205/5324*x^5 + 316/14641*x^6...
↳ + O(x^7)
sage: t
1/22 - 41/242*x^2 - 8/121*x^3 + 120/1331*x^4 + 1205/5324*x^5 + 316/14641*x^6...
↳ + O(x^7)
```

(continues on next page)

(continued from previous page)

```

sage: LazyPowerSeriesRing.options.halting_precision(20) # verify up to
↪degree 20

sage: g == s * a + t * b
True

sage: a = 16*x^5 / (1 - 2*x)
sage: b = (-16*x^5 + x^8) / (1 - 3*x^2)
sage: g, s, t = a.xgcd(b)
sage: g
x^5
sage: s
1/16 - 1/16*x - 3/16*x^2 + 1/8*x^3 - 17/256*x^4 + 9/128*x^5 + 1/128*x^6 + O(x^
↪7)
sage: t
1/16*x - 1/16*x^2 - 3/16*x^3 + 1/8*x^4 - 17/256*x^5 + 9/128*x^6 + 1/128*x^7 +
↪O(x^8)
sage: g == s * a + t * b
True

sage: # needs sage.rings.finite_rings
sage: L.<x> = LazyPowerSeriesRing(GF(2))
sage: a = L(lambdify n: n % 2, valuation=3); a
x^3 + x^5 + x^7 + x^9 + O(x^10)
sage: b = L(lambdify n: binomial(n,2) % 2, valuation=3); b
x^3 + x^6 + x^7 + O(x^10)
sage: g, s, t = a.xgcd(b)
sage: g
x^3
sage: s
1 + x + x^3 + x^4 + x^5 + O(x^7)
sage: t
x + x^2 + x^4 + x^5 + x^6 + O(x^8)
sage: g == s * a + t * b
True

sage: LazyPowerSeriesRing.options._reset() # reset the options

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> a = Integer(16)*x**Integer(5) / (Integer(1) - Integer(2)*x)
>>> b = (Integer(22)*x**Integer(3) + x**Integer(8)) / (Integer(1) -
↪Integer(3)*x**Integer(2))
>>> g, s, t = a.xgcd(b)
>>> g
x^3
>>> s
1/22 - 41/242*x^2 - 8/121*x^3 + 120/1331*x^4 + 1205/5324*x^5 + 316/14641*x^6
↪+ O(x^7)
>>> t
1/22 - 41/242*x^2 - 8/121*x^3 + 120/1331*x^4 + 1205/5324*x^5 + 316/14641*x^6
↪

```

(continues on next page)

(continued from previous page)

```

↪ + O(x^7)

>>> LazyPowerSeriesRing.options.halting_precision(Integer(20)) # verify up
↪ to degree 20

>>> g == s * a + t * b
True

>>> a = Integer(16)*x**Integer(5) / (Integer(1) - Integer(2)*x)
>>> b = (-Integer(16)*x**Integer(5) + x**Integer(8)) / (Integer(1) -
↪ Integer(3)*x**Integer(2))
>>> g, s, t = a.xgcd(b)
>>> g
x^5
>>> s
1/16 - 1/16*x - 3/16*x^2 + 1/8*x^3 - 17/256*x^4 + 9/128*x^5 + 1/128*x^6 + O(x^
↪ 7)
>>> t
1/16*x - 1/16*x^2 - 3/16*x^3 + 1/8*x^4 - 17/256*x^5 + 9/128*x^6 + 1/128*x^7 +
↪ O(x^8)
>>> g == s * a + t * b
True

>>> # needs sage.rings.finite_rings
>>> L = LazyPowerSeriesRing(GF(Integer(2)), names=('x',)); (x,) = L._first_
↪ ngens(1)
>>> a = L(lambda n: n % Integer(2), valuation=Integer(3)); a
x^3 + x^5 + x^7 + x^9 + O(x^10)
>>> b = L(lambda n: binomial(n,Integer(2)) % Integer(2),
↪ valuation=Integer(3)); b
x^3 + x^6 + x^7 + O(x^10)
>>> g, s, t = a.xgcd(b)
>>> g
x^3
>>> s
1 + x + x^3 + x^4 + x^5 + O(x^7)
>>> t
x + x^2 + x^4 + x^5 + x^6 + O(x^8)
>>> g == s * a + t * b
True

>>> LazyPowerSeriesRing.options._reset() # reset the options

```

class sage.rings.lazy_series.LazySymmetricFunction(parent, coeff_stream)

Bases: *LazyCompletionGradedAlgebraElement*

A symmetric function where each degree is computed lazily.

EXAMPLES:

```

sage: s = SymmetricFunctions(ZZ).s() #
↪ needs sage.modules
sage: L = LazySymmetricFunctions(s) #

```

(continues on next page)

(continued from previous page)

`↪needs sage.modules`

```

>>> from sage.all import *
>>> s = SymmetricFunctions(ZZ).s() #_
↪needs sage.modules
>>> L = LazySymmetricFunctions(s) #_
↪needs sage.modules

```

arithmetic_product (*args)Return the arithmetic product of `self` with `g`.

The arithmetic product is a binary operation $\square$ on the ring of symmetric functions which is bilinear in its two arguments and satisfies

$$p_\lambda \square p_\mu = \prod_{i \geq 1, j \geq 1} p_{\text{lcm}(\lambda_i, \mu_j)}^{\gcd(\lambda_i, \mu_j)}$$

for any two partitions $\lambda = (\lambda_1, \lambda_2, \lambda_3, \dots)$ and $\mu = (\mu_1, \mu_2, \mu_3, \dots)$ (where p_ν denotes the power-sum symmetric function indexed by the partition ν , and p_i denotes the i -th power-sum symmetric function). This is enough to define the arithmetic product if the base ring is torsion-free as a $\mathbf{Z}$ -module; for all other cases the arithmetic product is uniquely determined by requiring it to be functorial in the base ring. See <http://mathoverflow.net/questions/138148/> for a discussion of this arithmetic product.

Warning

The operation $f \square g$ was originally defined only for symmetric functions f and g without constant term. We extend this definition using the convention that the least common multiple of any integer with 0 is 0.

If f and g are two symmetric functions which are homogeneous of degrees a and b , respectively, then $f \square g$ is homogeneous of degree ab .

The arithmetic product is commutative and associative and has unity $e_1 = p_1 = h_1$.

For species M and N such that $M[\emptyset] = N[\emptyset] = \emptyset$, their arithmetic product is the species $M \square N$ of “ M -assemblies of cloned N -structures”. This operation is defined and several examples are given in [MM2008].

INPUT:

- `g` – a cycle index series having the same parent as `self`

OUTPUT: the arithmetic product of `self` with `g`**See also**

```

sage.combinat.sf.sfa.SymmetricFunctionAlgebra_generic_Element.
arithmetic_product()

```

EXAMPLES:

For C the species of (oriented) cycles and L_+ the species of nonempty linear orders, $C \square L_+$ corresponds to the species of “regular octopuses”; a $(C \square L_+)$ -structure is a cycle of some length, each of whose elements is an ordered list of a length which is consistent for all the lists in the structure.

```

sage: R.<q> = QQ[]
sage: p = SymmetricFunctions(R).p() #_
↳needs sage.modules
sage: m = SymmetricFunctions(R).m() #_
↳needs sage.modules
sage: L = LazySymmetricFunctions(m) #_
↳needs sage.modules

sage: # needs sage.modules
sage: c = LazyCombinatorialSpecies(QQ, "X").Cycles().cycle_index_series()
sage: Lplus = L(lambda n: p([1]*n), valuation=1)
sage: r = c.arithmetic_product(Lplus); r #_
↳needs sage.libs.pari
m[1] + (3*m[1,1]+2*m[2])
+ (8*m[1,1,1]+4*m[2,1]+2*m[3])
+ (42*m[1,1,1,1]+21*m[2,1,1]+12*m[2,2]+7*m[3,1]+3*m[4])
+ (144*m[1,1,1,1,1]+72*m[2,1,1,1]+36*m[2,2,1]+24*m[3,1,1]+12*m[3,2]+6*m[4,
↳1]+2*m[5])
+ ...
+ O^7

```

```

>>> from sage.all import *
>>> R = QQ['q']; (q,) = R._first_ngens(1)
>>> p = SymmetricFunctions(R).p() #_
↳needs sage.modules
>>> m = SymmetricFunctions(R).m() #_
↳needs sage.modules
>>> L = LazySymmetricFunctions(m) #_
↳needs sage.modules

>>> # needs sage.modules
>>> c = LazyCombinatorialSpecies(QQ, "X").Cycles().cycle_index_series()
>>> Lplus = L(lambda n: p([Integer(1)]*n), valuation=Integer(1))
>>> r = c.arithmetic_product(Lplus); r #_
↳needs sage.libs.pari
m[1] + (3*m[1,1]+2*m[2])
+ (8*m[1,1,1]+4*m[2,1]+2*m[3])
+ (42*m[1,1,1,1]+21*m[2,1,1]+12*m[2,2]+7*m[3,1]+3*m[4])
+ (144*m[1,1,1,1,1]+72*m[2,1,1,1]+36*m[2,2,1]+24*m[3,1,1]+12*m[3,2]+6*m[4,
↳1]+2*m[5])
+ ...
+ O^7

```

In particular, the number of regular octopuses is:

```

sage: [r[n].coefficient([1]*n) for n in range(8)] #_
↳needs sage.libs.pari sage.modules
[0, 1, 3, 8, 42, 144, 1440, 5760]

```

```

>>> from sage.all import *
>>> [r[n].coefficient([Integer(1)]*n) for n in range(Integer(8))] #_
↳ # needs sage.libs.pari sage.modules
[0, 1, 3, 8, 42, 144, 1440, 5760]

```

It is shown in [MM2008] that the exponential generating function for regular octopuses satisfies $(C \boxplus L_+)(x) = \sum_{n \geq 1} \sigma(n)(n-1)! \frac{x^n}{n!}$ (where $\sigma(n)$ is the sum of the divisors of n).

```
sage: [sum(divisors(i))*factorial(i-1) for i in range(1,8)] #_
↪needs sage.modules
[1, 3, 8, 42, 144, 1440, 5760]
```

```
>>> from sage.all import *
>>> [sum(divisors(i))*factorial(i-Integer(1)) for i in range(Integer(1),
↪Integer(8))] # needs sage.modules
[1, 3, 8, 42, 144, 1440, 5760]
```

AUTHORS:

- Andrew Gainer-Dewar (2013)

REFERENCES:

- [MM2008]

compositional_inverse()

alias of `revert()`.

derivative_with_respect_to_p1(n=1)

Return the symmetric function obtained by taking the derivative of `self` with respect to the power-sum symmetric function p_1 when the expansion of `self` in the power-sum basis is considered as a polynomial in p_k 's (with $k \geq 1$).

This is the same as skewing `self` by the first power-sum symmetric function p_1 .

INPUT:

- n – (default: 1) nonnegative integer which determines which power of the derivative is taken

EXAMPLES:

The species E of sets satisfies the relationship $E' = E$:

```
sage: # needs sage.modules
sage: h = SymmetricFunctions(QQ).h()
sage: T = LazySymmetricFunctions(h)
sage: E = T(lambda n: h[n])
sage: E - E.derivative_with_respect_to_p1()
O^6
```

```
>>> from sage.all import *
>>> # needs sage.modules
>>> h = SymmetricFunctions(QQ).h()
>>> T = LazySymmetricFunctions(h)
>>> E = T(lambda n: h[n])
>>> E - E.derivative_with_respect_to_p1()
O^6
```

The species C of cyclic orderings and the species L of linear orderings satisfy the relationship $C' = L$:

```
sage: # needs sage.modules
sage: p = SymmetricFunctions(QQ).p()
sage: C = T(lambda n: (sum(euler_phi(k)*p([k])** (n//k)
```

(continues on next page)

(continued from previous page)

```

.....:               for k in divisors(n)) / n if n > 0 else 0))
sage: L = T(lambda n: p([1]*n))
sage: L - C.derivative_with_respect_to_p1() #_
↪needs sage.libs.pari
O^6
    
```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> p = SymmetricFunctions(QQ).p()
>>> C = T(lambda n: (sum(euler_phi(k)*p([k])** (n//k)
...               for k in divisors(n)) / n if n > Integer(0) else_
↪Integer(0)))
>>> L = T(lambda n: p([Integer(1)]*n))
>>> L - C.derivative_with_respect_to_p1() #_
↪needs sage.libs.pari
O^6
    
```

functorial_composition(*args)

Return the functorial composition of `self` and `g`.

Let X be a finite set of cardinality m . For a group action of the symmetric group $g : S_n \rightarrow S_X$ and a (possibly virtual) representation of the symmetric group on X , $f : S_X \rightarrow GL(V)$, the functorial composition is the (virtual) representation of the symmetric group $f \square g : S_n \rightarrow GL(V)$ given by $\sigma \mapsto f(g(\sigma))$.

This is more naturally phrased in the language of combinatorial species. Let F and G be species, then their functorial composition is the species $F \square G$ with $(F \square G)[A] = F[G[A]]$. In other words, an $(F \square G)$ -structure on a set A of labels is an F -structure whose labels are the set of all G -structures on A .

The Frobenius character (or cycle index series) of $F \square G$ can be computed as follows, see section 2.2 of [BLL1998]:

$$\sum_{n \geq 0} \frac{1}{n!} \sum_{\sigma \in \mathfrak{S}_n} \text{fix } F[(G[\sigma])_1, (G[\sigma])_2, \dots] p_1^{\sigma_1} p_2^{\sigma_2} \dots$$

Warning

The operation $f \square g$ only makes sense when g corresponds to a permutation representation, i.e., a group action.

EXAMPLES:

The species G of simple graphs can be expressed in terms of a functorial composition: $G = p \square p_2$, where p is the `SubsetSpecies`..

```

sage: # needs sage.modules
sage: R.<q> = QQ[]
sage: h = SymmetricFunctions(R).h()
sage: m = SymmetricFunctions(R).m()
sage: L = LazySymmetricFunctions(m)
sage: P = L(lambda n: sum(q^k*h[n-k]*h[k] for k in range(n+1)))
sage: P2 = L(lambda n: h[2]*h[n-2], valuation=2)
sage: P.functorial_composition(P2)[:4] #_
    
```

(continues on next page)

(continued from previous page)

```

↪needs sage.libs.pari
[m[],
 m[1],
 (q+1)*m[1, 1] + (q+1)*m[2],
 (q^3+3*q^2+3*q+1)*m[1, 1, 1] + (q^3+2*q^2+2*q+1)*m[2, 1] + (q^3+q^
↪2+q+1)*m[3]]

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> R = QQ['q']; (q,) = R._first_ngens(1)
>>> h = SymmetricFunctions(R).h()
>>> m = SymmetricFunctions(R).m()
>>> L = LazySymmetricFunctions(m)
>>> P = L(lambda n: sum(q**k*h[n-k]*h[k] for k in range(n+Integer(1))))
>>> P2 = L(lambda n: h[Integer(2)]*h[n-Integer(2)], valuation=Integer(2))
>>> P.functorial_composition(P2)[Integer(4)]
↪ # needs sage.libs.pari
[m[],
 m[1],
 (q+1)*m[1, 1] + (q+1)*m[2],
 (q^3+3*q^2+3*q+1)*m[1, 1, 1] + (q^3+2*q^2+2*q+1)*m[2, 1] + (q^3+q^
↪2+q+1)*m[3]]

```

For example, there are:

```

sage: P.functorial_composition(P2)[4].coefficient([4])[3]
↪needs sage.libs.pari sage.modules
3

```

```

>>> from sage.all import *
>>> P.functorial_composition(P2)[Integer(4)].
↪coefficient([Integer(4)])[Integer(3)] # needs sage.libs.
↪pari sage.modules
3

```

unlabelled graphs on 4 vertices and 3 edges, and:

```

sage: P.functorial_composition(P2)[4].coefficient([2,2])[3]
↪needs sage.libs.pari sage.modules
8

```

```

>>> from sage.all import *
>>> P.functorial_composition(P2)[Integer(4)].coefficient([Integer(2),
↪Integer(2)])[Integer(3)] # needs sage.libs.pari sage.modules
8

```

labellings of their vertices with two 1s and two 2s.

The symmetric function $h_1 \sum_n h_n$ is the neutral element with respect to functorial composition:

```

sage: # needs sage.modules
sage: p = SymmetricFunctions(QQ).p()

```

(continues on next page)

(continued from previous page)

```

sage: h = SymmetricFunctions(QQ).h()
sage: e = SymmetricFunctions(QQ).e()
sage: L = LazySymmetricFunctions(h)
sage: H = L(lambda n: h[n])
sage: Ep = p[1]*H.derivative_with_respect_to_p1(); Ep
h[1] + (h[1,1]) + (h[2,1]) + (h[3,1]) + (h[4,1]) + (h[5,1]) + O^7
sage: f = L(lambda n: h[n-n//2, n//2])
sage: f - Ep.functorial_composition(f) #_
↪needs sage.libs.pari
O^7

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> p = SymmetricFunctions(QQ).p()
>>> h = SymmetricFunctions(QQ).h()
>>> e = SymmetricFunctions(QQ).e()
>>> L = LazySymmetricFunctions(h)
>>> H = L(lambda n: h[n])
>>> Ep = p[Integer(1)]*H.derivative_with_respect_to_p1(); Ep
h[1] + (h[1,1]) + (h[2,1]) + (h[3,1]) + (h[4,1]) + (h[5,1]) + O^7
>>> f = L(lambda n: h[n-n//Integer(2), n//Integer(2)])
>>> f - Ep.functorial_composition(f) #_
↪needs sage.libs.pari
O^7

```

The symmetric function $\sum_n h_n$ is a left absorbing element:

```

sage: # needs sage.modules
sage: H.functorial_composition(f) - H
O^7

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> H.functorial_composition(f) - H
O^7

```

The functorial composition distributes over the sum:

```

sage: # needs sage.modules
sage: F1 = L(lambda n: h[n])
sage: F2 = L(lambda n: e[n])
sage: f1 = F1.functorial_composition(f)
sage: f2 = F2.functorial_composition(f)
sage: (F1 + F2).functorial_composition(f) - f1 - f2 # long time
O^7

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> F1 = L(lambda n: h[n])
>>> F2 = L(lambda n: e[n])
>>> f1 = F1.functorial_composition(f)
>>> f2 = F2.functorial_composition(f)

```

(continues on next page)

(continued from previous page)

```
>>> (F1 + F2).functorial_composition(f) - f1 - f2      # long time
0^7
```

is_unit()

Return whether this element is a unit in the ring.

EXAMPLES:

```
sage: # needs sage.modules
sage: m = SymmetricFunctions(ZZ).m()
sage: L = LazySymmetricFunctions(m)
sage: L(2*m[1]).is_unit()
False
sage: L(-1 + 2*m[1]).is_unit()
True
sage: L(2 + m[1]).is_unit()
False
sage: m = SymmetricFunctions(QQ).m()
sage: L = LazySymmetricFunctions(m)
sage: L(2 + 3*m[1]).is_unit()
True
```

```
>>> from sage.all import *
>>> # needs sage.modules
>>> m = SymmetricFunctions(ZZ).m()
>>> L = LazySymmetricFunctions(m)
>>> L(Integer(2)*m[Integer(1)]).is_unit()
False
>>> L(-Integer(1) + Integer(2)*m[Integer(1)]).is_unit()
True
>>> L(Integer(2) + m[Integer(1)]).is_unit()
False
>>> m = SymmetricFunctions(QQ).m()
>>> L = LazySymmetricFunctions(m)
>>> L(Integer(2) + Integer(3)*m[Integer(1)]).is_unit()
True
```

legendre_transform()Return the Legendre transform of `self`.

Given a symmetric function f of valuation 2, the Legendre transform of f is the unique symmetric function g of valuation 2 over the same base ring, such that

$$g \circ \partial_{p_1} f + f = p_1 \partial_{p_1} f.$$

This implies that the derivatives of f and g with respect to p_1 are inverses of each other with respect to plethystic substitution.

The Legendre transform is an involution.

 **See also**

```
revert()
```


EXAMPLES:

```

sage: p = SymmetricFunctions(QQ).p()
sage: s = SymmetricFunctions(QQ).s()
sage: lp = LazySymmetricFunctions(p)
sage: A = lp(s([2]))
sage: A.legendre_transform()
(1/2*p[1,1]-1/2*p[2]) + O^9

sage: def asso(n):
....:     return p.sum_of_terms((Partition([d] * (n // d)),
....:         euler_phi(d) / n) for d in divisors(n))

sage: A = lp(asso, valuation=2)
sage: A.legendre_transform()[:5]
[1/2*p[1, 1] - 1/2*p[2],
-1/3*p[1, 1, 1] - 2/3*p[3],
1/4*p[1, 1, 1, 1] + 1/4*p[2, 2] - 1/2*p[4]]

```

```

>>> from sage.all import *
>>> p = SymmetricFunctions(QQ).p()
>>> s = SymmetricFunctions(QQ).s()
>>> lp = LazySymmetricFunctions(p)
>>> A = lp(s([Integer(2)]))
>>> A.legendre_transform()
(1/2*p[1,1]-1/2*p[2]) + O^9

>>> def asso(n):
...     return p.sum_of_terms((Partition([d] * (n // d)),
...         euler_phi(d) / n) for d in divisors(n))

>>> A = lp(asso, valuation=Integer(2))
>>> A.legendre_transform()[:Integer(5)]
[1/2*p[1, 1] - 1/2*p[2],
-1/3*p[1, 1, 1] - 2/3*p[3],
1/4*p[1, 1, 1, 1] + 1/4*p[2, 2] - 1/2*p[4]]

```

plethysm(*args)

Return the composition of `self` with `g`.

The arity of `self` must be equal to the number of arguments provided.

Given a lazy symmetric function f of arity n and a tuple of lazy symmetric functions $g = (g_1, \dots, g_n)$ over the same base ring, the composition (or plethysm) $(f \circ g)$ is defined if and only if for each $1 \leq i \leq n$:

- $g_i = 0$, or
- setting all alphabets except the i -th in f to zero yields a symmetric function with only finitely many nonzero coefficients, or
- $\text{val}(g) > 0$.

If f is a univariate ‘exact’ lazy symmetric function, we can check whether f has only finitely many nonzero coefficients. However, if f has larger arity, we have no way to test whether setting all but one alphabets of f to zero yields a polynomial, except if f itself is ‘exact’ and therefore a symmetric function with only finitely many nonzero coefficients.

INPUT:

- g – other (lazy) symmetric functions

Todo

Allow specification of degree one elements.

EXAMPLES:

```
sage: # needs sage.modules
sage: P.<q> = QQ[]
sage: s = SymmetricFunctions(P).s()
sage: L = LazySymmetricFunctions(s)
sage: f = s[2]
sage: g = s[3]
sage: L(f)(L(g)) - L(f(g))
0
sage: f = s[2] + s[2,1]
sage: g = s[1] + s[2,2]
sage: L(f)(L(g)) - L(f(g))
0
sage: L(f)(g) - L(f(g))
0
sage: f = s[2] + s[2,1]
sage: g = s[1] + s[2,2]
sage: L(f)(L(q*g)) - L(f(q*g))
0
```

```
>>> from sage.all import *
>>> # needs sage.modules
>>> P = QQ['q']; (q,) = P._first_ngens(1)
>>> s = SymmetricFunctions(P).s()
>>> L = LazySymmetricFunctions(s)
>>> f = s[Integer(2)]
>>> g = s[Integer(3)]
>>> L(f)(L(g)) - L(f(g))
0
>>> f = s[Integer(2)] + s[Integer(2), Integer(1)]
>>> g = s[Integer(1)] + s[Integer(2), Integer(2)]
>>> L(f)(L(g)) - L(f(g))
0
>>> L(f)(g) - L(f(g))
0
>>> f = s[Integer(2)] + s[Integer(2), Integer(1)]
>>> g = s[Integer(1)] + s[Integer(2), Integer(2)]
>>> L(f)(L(q*g)) - L(f(q*g))
0
```

The Frobenius character of the permutation action on set partitions is a plethysm:

```
sage: # needs sage.modules
sage: s = SymmetricFunctions(QQ).s()
```

(continues on next page)

(continued from previous page)

```

sage: S = LazySymmetricFunctions(s)
sage: E1 = S(lambd n: s[n], valuation=1)
sage: E = 1 + E1
sage: P = E(E1)
sage: P[:5]
[s[], s[1], 2*s[2], s[2, 1] + 3*s[3], 2*s[2, 2] + 2*s[3, 1] + 5*s[4]]

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> s = SymmetricFunctions(QQ).s()
>>> S = LazySymmetricFunctions(s)
>>> E1 = S(lambd n: s[n], valuation=Integer(1))
>>> E = Integer(1) + E1
>>> P = E(E1)
>>> P[:Integer(5)]
[s[], s[1], 2*s[2], s[2, 1] + 3*s[3], 2*s[2, 2] + 2*s[3, 1] + 5*s[4]]

```

The plethysm with a tensor product is also implemented:

```

sage: # needs sage.modules
sage: s = SymmetricFunctions(QQ).s()
sage: X = tensor([s[1],s[[]]])
sage: Y = tensor([s[[]],s[1]])
sage: S = LazySymmetricFunctions(s)
sage: S2 = LazySymmetricFunctions(tensor([s, s]))
sage: A = S(s[1,1,1])
sage: B = S2(X+Y)
sage: A(B) #_
↪needs lrcalc_python
(s[]#s[1,1,1]+s[1]#s[1,1]+s[1,1]#s[1]+s[1,1,1]#s[])

sage: H = S(lambd n: s[n]) #_
↪needs sage.modules
sage: H(S2(X*Y)) #_
↪needs lrcalc_python sage.modules
(s[]#s[]) + (s[1]#s[1]) + (s[1,1]#s[1,1]+s[2]#s[2])
+ (s[1,1,1]#s[1,1,1]+s[2,1]#s[2,1]+s[3]#s[3]) + O^7
sage: H(S2(X+Y)) #_
↪needs sage.modules
(s[]#s[]) + (s[]#s[1]+s[1]#s[]) + (s[]#s[2]+s[1]#s[1]+s[2]#s[])
+ (s[]#s[3]+s[1]#s[2]+s[2]#s[1]+s[3]#s[])
+ (s[]#s[4]+s[1]#s[3]+s[2]#s[2]+s[3]#s[1]+s[4]#s[])
+ (s[]#s[5]+s[1]#s[4]+s[2]#s[3]+s[3]#s[2]+s[4]#s[1]+s[5]#s[])
+ (s[]#s[6]+s[1]#s[5]+s[2]#s[4]+s[3]#s[3]+s[4]#s[2]+s[5]#s[1]+s[6]#s[])
+ O^7

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> s = SymmetricFunctions(QQ).s()
>>> X = tensor([s[Integer(1)],s[[]]])
>>> Y = tensor([s[[]],s[Integer(1)]])
>>> S = LazySymmetricFunctions(s)

```

(continues on next page)

(continued from previous page)

```

>>> S2 = LazySymmetricFunctions(tensor([s, s]))
>>> A = S(s[Integer(1), Integer(1), Integer(1)])
>>> B = S2(X+Y)
>>> A(B) #_
↳needs lrcalc_python
(s[]#s[1,1,1]+s[1]#s[1,1]+s[1,1]#s[1]+s[1,1,1]#s[])

>>> H = S(lambda n: s[n]) #_
↳needs sage.modules
>>> H(S2(X*Y)) #_
↳needs lrcalc_python sage.modules
(s[]#s[]) + (s[1]#s[1]) + (s[1,1]#s[1,1]+s[2]#s[2])
+ (s[1,1,1]#s[1,1,1]+s[2,1]#s[2,1]+s[3]#s[3]) + O^7
>>> H(S2(X+Y)) #_
↳needs sage.modules
(s[]#s[]) + (s[]#s[1]+s[1]#s[]) + (s[]#s[2]+s[1]#s[1]+s[2]#s[])
+ (s[]#s[3]+s[1]#s[2]+s[2]#s[1]+s[3]#s[])
+ (s[]#s[4]+s[1]#s[3]+s[2]#s[2]+s[3]#s[1]+s[4]#s[])
+ (s[]#s[5]+s[1]#s[4]+s[2]#s[3]+s[3]#s[2]+s[4]#s[1]+s[5]#s[])
+ (s[]#s[6]+s[1]#s[5]+s[2]#s[4]+s[3]#s[3]+s[4]#s[2]+s[5]#s[1]+s[6]#s[])
+ O^7

```

plethystic_inverse()alias of `revert()`.**revert()**Return the compositional inverse of `self`.

Given a symmetric function f , the compositional inverse is a symmetric function g over the same base ring, such that $f \circ g = p_1$. Thus, it is the inverse with respect to plethystic substitution.

The compositional inverse exists if and only if:

- $\text{val}(f) = 1$, or
- $f = a + bp_1$ with $a, b \neq 0$.

See also`legendre_transform()`**EXAMPLES:**

```

sage: # needs sage.modules
sage: h = SymmetricFunctions(QQ).h()
sage: L = LazySymmetricFunctions(h)
sage: f = L(lambda n: h[n]) - 1
sage: f(f.revert())
h[1] + O^8

```

```

>>> from sage.all import *
>>> # needs sage.modules
>>> h = SymmetricFunctions(QQ).h()

```

(continues on next page)

(continued from previous page)

```

>>> L = LazySymmetricFunctions(h)
>>> f = L(lambda n: h[n]) - Integer(1)
>>> f(f.revert())
h[1] + O^8

```

ALGORITHM:

Let F be a symmetric function with valuation 1, i.e., whose constant term vanishes and whose degree one term equals bp_1 . Then

$$(F - bp_1) \circ G = F \circ G - bp_1 \circ G = p_1 - bG,$$

and therefore $G = (p_1 - (F - bp_1) \circ G)/b$, which allows recursive computation of G .

 See also

The compositional inverse Ω of the symmetric function $h_1 + h_2 + \dots$ can be handled much more efficiently using specialized methods. See `LogarithmCycleIndexSeries()`

AUTHORS:

- Andrew Gainer-Dewar
- Martin Rubey

suspension()

Return the suspension of `self`.

This is an involution, that maps the homogeneous component f_n of degree n to $(-1)^{n-1}\omega(f_n)$, where *omega* is the usual involution of symmetric functions.

EXAMPLES:

```

sage: s = SymmetricFunctions(QQ).s()
sage: ls = LazySymmetricFunctions(s)
sage: f = ls(lambda n: s([n]), valuation=1)
sage: g = f.revert().suspension(); g
s[1] + (s[1,1]) + (s[2,1]) + (s[2,1,1]+s[3,1]) + ...
sage: g.revert().suspension()
s[1] + s[2] + s[3] + s[4] + s[5] + ...

```

```

>>> from sage.all import *
>>> s = SymmetricFunctions(QQ).s()
>>> ls = LazySymmetricFunctions(s)
>>> f = ls(lambda n: s([n]), valuation=Integer(1))
>>> g = f.revert().suspension(); g
s[1] + (s[1,1]) + (s[2,1]) + (s[2,1,1]+s[3,1]) + ...
>>> g.revert().suspension()
s[1] + s[2] + s[3] + s[4] + s[5] + ...

```

symmetric_function (*degree=None*)

Return `self` as a symmetric function if `self` is actually so.

INPUT:

- `degree` – None or an integer

OUTPUT:

If `degree` is not `None`, the terms of the series of degree greater than `degree` are first truncated. If `degree` is `None` and the series is not a polynomial polynomial, a `ValueError` is raised.

EXAMPLES:

```
sage: # needs sage.modules
sage: s = SymmetricFunctions(QQ).s()
sage: S = LazySymmetricFunctions(s)
sage: elt = S[s[2]]
sage: elt.symmetric_function()
s[2]
```

```
>>> from sage.all import *
>>> # needs sage.modules
>>> s = SymmetricFunctions(QQ).s()
>>> S = LazySymmetricFunctions(s)
>>> elt = S[s[Integer(2)]]
>>> elt.symmetric_function()
s[2]
```

LAZY SERIES RINGS

We provide lazy implementations for various $\mathbb{N}$ -graded rings.

<code>LazyLaurentSeriesRing</code>	The ring of lazy Laurent series.
<code>LazyPowerSeriesRing</code>	The ring of (possibly multivariate) lazy Taylor series.
<code>LazyCompletionGradedAlgebra</code>	The completion of a graded algebra consisting of formal series.
<code>LazySymmetricFunctions</code>	The ring of (possibly multivariate) lazy symmetric functions.
<code>LazyDirichletSeriesRing</code>	The ring of lazy Dirichlet series.

➡ See also

`sage.rings.padics.generic_nodes.pAdicRelaxedGeneric`, `sage.rings.padics.factory.ZpER()`

⚠ Warning

When the halting precision is infinite, the default for `bool(f)` is `True` for any lazy series `f` that is not known to be zero. This could end up resulting in infinite loops:

```
sage: L.<x> = LazyPowerSeriesRing(ZZ)
sage: f = L(lambda n: 0, valuation=0)
sage: 1 / f # not tested - infinite loop
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('x',)); (x,) = L._first_ngens(1)
>>> f = L(lambda n: Integer(0), valuation=Integer(0))
>>> Integer(1) / f # not tested - infinite loop
```

➡ See also

The examples of `LazyLaurentSeriesRing` contain a discussion about the different methods of comparisons the lazy series can use.

AUTHORS:

- Kwankyu Lee (2019-02-24): initial version
- Tejasvi Chebrolu, Martin Rubey, Travis Scrimshaw (2021-08): refactored and expanded functionality

```
class sage.rings.lazy_series_ring.LazyCompletionGradedAlgebra(basis, sparse=True,
                                                             category=None)
```

Bases: *LazySeriesRing*

The completion of a graded algebra consisting of formal series.

For a graded algebra A , we can form a completion of A consisting of all formal series of A such that each homogeneous component is a finite linear combination of basis elements of A .

INPUT:

- `basis` – a graded algebra
- `names` – name(s) of the alphabets
- `sparse` – boolean (default: `True`); whether we use a sparse or a dense representation

EXAMPLES:

```
sage: # needs sage.modules
sage: NCSF = NonCommutativeSymmetricFunctions(QQ)
sage: S = NCSF.Complete()
sage: L = S.formal_series_ring(); L
Lazy completion of Non-Commutative Symmetric Functions
over the Rational Field in the Complete basis
sage: f = 1 / (1 - L(S[1])); f
S[] + S[1] + (S[1,1]) + (S[1,1,1]) + (S[1,1,1,1]) + (S[1,1,1,1,1])
+ (S[1,1,1,1,1,1]) + O^7
sage: g = 1 / (1 - L(S[2])); g
S[] + S[2] + (S[2,2]) + (S[2,2,2]) + O^7
sage: f * g
S[] + S[1] + (S[1,1]+S[2]) + (S[1,1,1]+S[1,2])
+ (S[1,1,1,1]+S[1,1,2]+S[2,2]) + (S[1,1,1,1,1]+S[1,1,1,2]+S[1,2,2])
+ (S[1,1,1,1,1,1]+S[1,1,1,1,2]+S[1,1,2,2]+S[2,2,2]) + O^7
sage: g * f
S[] + S[1] + (S[1,1]+S[2]) + (S[1,1,1]+S[2,1])
+ (S[1,1,1,1]+S[2,1,1]+S[2,2]) + (S[1,1,1,1,1]+S[2,1,1,1]+S[2,2,1])
+ (S[1,1,1,1,1,1]+S[2,1,1,1,1]+S[2,2,1,1]+S[2,2,2]) + O^7
sage: f * g - g * f
(S[1,2]-S[2,1]) + (S[1,1,2]-S[2,1,1])
+ (S[1,1,1,2]+S[1,2,2]-S[2,1,1,1]-S[2,2,1])
+ (S[1,1,1,1,2]+S[1,1,2,2]-S[2,1,1,1,1]-S[2,2,1,1]) + O^7
```

```
>>> from sage.all import *
>>> # needs sage.modules
>>> NCSF = NonCommutativeSymmetricFunctions(QQ)
>>> S = NCSF.Complete()
>>> L = S.formal_series_ring(); L
Lazy completion of Non-Commutative Symmetric Functions
over the Rational Field in the Complete basis
>>> f = Integer(1) / (Integer(1) - L(S[Integer(1)])); f
S[] + S[1] + (S[1,1]) + (S[1,1,1]) + (S[1,1,1,1]) + (S[1,1,1,1,1])
+ (S[1,1,1,1,1,1]) + O^7
>>> g = Integer(1) / (Integer(1) - L(S[Integer(2)])); g
S[] + S[2] + (S[2,2]) + (S[2,2,2]) + O^7
>>> f * g
```

(continues on next page)

(continued from previous page)

```

S[] + S[1] + (S[1,1]+S[2]) + (S[1,1,1]+S[1,2])
+ (S[1,1,1,1]+S[1,1,2]+S[2,2]) + (S[1,1,1,1,1]+S[1,1,1,2]+S[1,2,2])
+ (S[1,1,1,1,1,1]+S[1,1,1,1,2]+S[1,1,2,2]+S[2,2,2]) + O^7
>>> g * f
S[] + S[1] + (S[1,1]+S[2]) + (S[1,1,1]+S[2,1])
+ (S[1,1,1,1]+S[2,1,1]+S[2,2]) + (S[1,1,1,1,1]+S[2,1,1,1]+S[2,2,1])
+ (S[1,1,1,1,1,1]+S[2,1,1,1,1]+S[2,2,1,1]+S[2,2,2]) + O^7
>>> f * g - g * f
(S[1,2]-S[2,1]) + (S[1,1,2]-S[2,1,1])
+ (S[1,1,1,2]+S[1,2,2]-S[2,1,1,1]-S[2,2,1])
+ (S[1,1,1,1,2]+S[1,1,2,2]-S[2,1,1,1,1]-S[2,2,1,1]) + O^7

```

Elementalias of *LazyCompletionGradedAlgebraElement***some_elements()**

Return a list of elements of self.

EXAMPLES:

```

sage: m = SymmetricFunctions(GF(5)).m() #_
↪ needs sage.modules
sage: L = LazySymmetricFunctions(m) #_
↪ needs sage.modules
sage: L.some_elements()[:5] #_
↪ needs sage.modules
[0, m[], 2*m[] + 2*m[1] + 3*m[2], 2*m[1] + 3*m[2],
 3*m[] + 2*m[1] + (m[1,1]+m[2])
  + (2*m[1,1,1]+m[3])
  + (2*m[1,1,1,1]+4*m[2,1,1]+2*m[2,2])
  + (3*m[2,1,1,1]+3*m[3,1,1]+4*m[3,2]+m[5])
  + (2*m[2,2,1,1]+m[2,2,2]+2*m[3,2,1]+2*m[3,3]+m[4,1,1]+3*m[4,2]+4*m[5,
↪ 1]+4*m[6])
  + O^7]

sage: # needs sage.modules
sage: NCSF = NonCommutativeSymmetricFunctions(QQ)
sage: S = NCSF.Complete()
sage: L = S.formal_series_ring()
sage: L.some_elements()[:4]
[0, S[], 2*S[] + 2*S[1] + (3*S[1,1]), 2*S[1] + (3*S[1,1])]

```

```

>>> from sage.all import *
>>> m = SymmetricFunctions(GF(Integer(5))).m() #_
↪ # needs sage.modules
>>> L = LazySymmetricFunctions(m) #_
↪ needs sage.modules
>>> L.some_elements()[:Integer(5)] #_
↪ # needs sage.modules
[0, m[], 2*m[] + 2*m[1] + 3*m[2], 2*m[1] + 3*m[2],
 3*m[] + 2*m[1] + (m[1,1]+m[2])
  + (2*m[1,1,1]+m[3])

```

(continues on next page)

(continued from previous page)

```

+ (2*m[1,1,1,1]+4*m[2,1,1]+2*m[2,2])
+ (3*m[2,1,1,1]+3*m[3,1,1]+4*m[3,2]+m[5])
+ (2*m[2,2,1,1]+m[2,2,2]+2*m[3,2,1]+2*m[3,3]+m[4,1,1]+3*m[4,2]+4*m[5,
↪1]+4*m[6])
+ O^7]

>>> # needs sage.modules
>>> NCSF = NonCommutativeSymmetricFunctions(QQ)
>>> S = NCSF.Complete()
>>> L = S.formal_series_ring()
>>> L.some_elements()[:Integer(4)]
[0, S[], 2*S[] + 2*S[1] + (3*S[1,1]), 2*S[1] + (3*S[1,1])]

```

```
class sage.rings.lazy_series_ring.LazyDirichletSeriesRing(base_ring, names, sparse=True,
                                                         category=None)
```

Bases: [LazySeriesRing](#)

The ring of lazy Dirichlet series.

INPUT:

- `base_ring` – base ring of this Dirichlet series ring
- `names` – name of the generator of this Dirichlet series ring
- `sparse` – boolean (default: `True`); whether this series is sparse or not

Unlike formal univariate Laurent/power series (over a field), the ring of formal Dirichlet series is not a [Wikipedia article discrete_valuation_ring](#). On the other hand, it is a [Wikipedia article local_ring](#). The unique maximal ideal consists of all non-invertible series, i.e., series with vanishing constant term.

Todo

According to the answers in <https://mathoverflow.net/questions/5522/dirichlet-series-with-integer-coefficients-as-a-ufd>, (which, in particular, references [arXiv math/0105219](#)) the ring of formal Dirichlet series is actually a [Wikipedia article Unique_factorization_domain](#) over $\mathbf{Z}$.

Note

An interesting valuation is described in Emil Daniel Schwab; Gheorghe Silberberg *A note on some discrete valuation rings of arithmetical functions*, Archivum Mathematicum, Vol. 36 (2000), No. 2, 103-109, <http://dml.cz/dmlcz/107723>. Let J_k be the ideal of Dirichlet series whose coefficient $f[n]$ of n^s vanishes if n has less than k prime factors, counting multiplicities. For any Dirichlet series f , let $D(f)$ be the largest integer k such that f is in J_k . Then D is surjective, $D(fg) = D(f) + D(g)$ for nonzero f and g , and $D(f + g) \geq \min(D(f), D(g))$ provided that $f + g$ is nonzero.

For example, J_1 are series with no constant term, and J_2 are series such that $f[1]$ and $f[p]$ for prime p vanish. Since this is a chain of increasing ideals, the ring of formal Dirichlet series is not a [Wikipedia article Noetherian_ring](#).

Evidently, this valuation cannot be computed for a given series.

EXAMPLES:

```
sage: LazyDirichletSeriesRing(ZZ, 't')
Lazy Dirichlet Series Ring in t over Integer Ring
```

```
>>> from sage.all import *
>>> LazyDirichletSeriesRing(ZZ, 't')
Lazy Dirichlet Series Ring in t over Integer Ring
```

The ideal generated by 2^{-s} and 3^{-s} is not principal:

```
sage: L = LazyDirichletSeriesRing(QQ, 's')
sage: L in PrincipalIdealDomains
False
```

```
>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(QQ, 's')
>>> L in PrincipalIdealDomains
False
```

Element

alias of *LazyDirichletSeries*

one()

Return the constant series 1.

EXAMPLES:

```
sage: L = LazyDirichletSeriesRing(ZZ, 'z')
sage: L.one() #_
↪needs sage.symbolic
1
sage: ~L.one() #_
↪needs sage.symbolic
1 + O(1/(8^z))
```

```
>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, 'z')
>>> L.one() #_
↪needs sage.symbolic
1
>>> ~L.one() #_
↪needs sage.symbolic
1 + O(1/(8^z))
```

polylog(z)

alias of *polylogarithm()*.

polylogarithm(z)

Return the polylogarithm at z considered as a Dirichlet series in `self`.

The *polylogarithm* at z is the Dirichlet series

$$\mathrm{Li}_s(z) = \sum_{k=1}^{\infty} \frac{z^k}{k^s}.$$

EXAMPLES:

```
sage: R.<z> = ZZ[]
sage: L = LazyDirichletSeriesRing(R, 's')
sage: L.polylogarithm(z)
z + z^2/2^s + z^3/3^s + z^4/4^s + z^5/5^s + z^6/6^s + z^7/7^s + O(1/(8^s))
```

```
>>> from sage.all import *
>>> R = ZZ['z']; (z,) = R._first_ngens(1)
>>> L = LazyDirichletSeriesRing(R, 's')
>>> L.polylogarithm(z)
z + z^2/2^s + z^3/3^s + z^4/4^s + z^5/5^s + z^6/6^s + z^7/7^s + O(1/(8^s))
```

At $z = 1$, this is the Riemann zeta function:

```
sage: L.polylogarithm(1)
1 + 1/(2^s) + 1/(3^s) + 1/(4^s) + 1/(5^s) + 1/(6^s) + 1/(7^s) + O(1/(8^s))
```

```
>>> from sage.all import *
>>> L.polylogarithm(Integer(1))
1 + 1/(2^s) + 1/(3^s) + 1/(4^s) + 1/(5^s) + 1/(6^s) + 1/(7^s) + O(1/(8^s))
```

At $z = -1$, this is the negative of the Dirichlet eta function:

```
sage: -L.polylogarithm(-1)
1 - 1/(2^s) + 1/(3^s) - 1/(4^s) + 1/(5^s) - 1/(6^s) + 1/(7^s) + O(1/(8^s))
```

```
>>> from sage.all import *
>>> -L.polylogarithm(-Integer(1))
1 - 1/(2^s) + 1/(3^s) - 1/(4^s) + 1/(5^s) - 1/(6^s) + 1/(7^s) + O(1/(8^s))
```

REFERENCES:

- [Wikipedia article Polylogarithm](#)

`some_elements()`

Return a list of elements of `self`.

EXAMPLES:

```
sage: L = LazyDirichletSeriesRing(ZZ, 'z')
sage: l = L.some_elements()
sage: l
↳needs sage.symbolic
[0, 1,
 1/(4^z) + 1/(5^z) + 1/(6^z) + O(1/(7^z)),
 1/(2^z) - 1/(3^z) + 2/4^z - 2/5^z + 3/6^z - 3/7^z + 4/8^z - 4/9^z,
 1/(2^z) - 1/(3^z) + 2/4^z - 2/5^z + 3/6^z - 3/7^z + 4/8^z - 4/9^z + 1/(10^z)
↳ + 1/(11^z) + 1/(12^z) + O(1/(13^z)),
 1 + 4/2^z + 9/3^z + 16/4^z + 25/5^z + 36/6^z + 49/7^z + O(1/(8^z))]
```

```
sage: L = LazyDirichletSeriesRing(QQ, 'z')
sage: l = L.some_elements()
sage: l
↳needs sage.symbolic
[0, 1,
```

(continues on next page)

(continued from previous page)

```

1/2/4^z + 1/2/5^z + 1/2/6^z + O(1/(7^z)),
1/2 - 1/2/2^z + 2/3^z - 2/4^z + 1/(6^z) - 1/(7^z) + 42/8^z + 2/3/9^z,
1/2 - 1/2/2^z + 2/3^z - 2/4^z + 1/(6^z) - 1/(7^z) + 42/8^z + 2/3/9^z + 1/2/
↪10^z + 1/2/11^z + 1/2/12^z + O(1/(13^z)),
1 + 4/2^z + 9/3^z + 16/4^z + 25/5^z + 36/6^z + 49/7^z + O(1/(8^z))]
```

```

>>> from sage.all import *
>>> L = LazyDirichletSeriesRing(ZZ, 'z')
>>> l = L.some_elements()
>>> l
↪needs sage.symbolic
[0, 1,
 1/(4^z) + 1/(5^z) + 1/(6^z) + O(1/(7^z)),
 1/(2^z) - 1/(3^z) + 2/4^z - 2/5^z + 3/6^z - 3/7^z + 4/8^z - 4/9^z,
 1/(2^z) - 1/(3^z) + 2/4^z - 2/5^z + 3/6^z - 3/7^z + 4/8^z - 4/9^z + 1/(10^z) ↪
↪+ 1/(11^z) + 1/(12^z) + O(1/(13^z)),
 1 + 4/2^z + 9/3^z + 16/4^z + 25/5^z + 36/6^z + 49/7^z + O(1/(8^z))]
```

```

>>> L = LazyDirichletSeriesRing(QQ, 'z')
>>> l = L.some_elements()
>>> l
↪needs sage.symbolic
[0, 1,
 1/2/4^z + 1/2/5^z + 1/2/6^z + O(1/(7^z)),
 1/2 - 1/2/2^z + 2/3^z - 2/4^z + 1/(6^z) - 1/(7^z) + 42/8^z + 2/3/9^z,
 1/2 - 1/2/2^z + 2/3^z - 2/4^z + 1/(6^z) - 1/(7^z) + 42/8^z + 2/3/9^z + 1/2/
↪10^z + 1/2/11^z + 1/2/12^z + O(1/(13^z)),
 1 + 4/2^z + 9/3^z + 16/4^z + 25/5^z + 36/6^z + 49/7^z + O(1/(8^z))]
```

```

class sage.rings.lazy_series_ring.LazyLaurentSeriesRing (base_ring, names, sparse=True,
                                                         category=None)
```

Bases: *LazySeriesRing*

The ring of lazy Laurent series.

The ring of Laurent series over a ring with the usual arithmetic where the coefficients are computed lazily.

INPUT:

- `base_ring` – base ring
- `names` – name of the generator
- `sparse` – boolean (default: `True`); whether the implementation of the series is sparse or not

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: 1 / (1 - z)
1 + z + z^2 + O(z^3)
sage: 1 / (1 - z) == 1 / (1 - z)
True
sage: L in Fields
True
```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> Integer(1) / (Integer(1) - z)
1 + z + z^2 + O(z^3)
>>> Integer(1) / (Integer(1) - z) == Integer(1) / (Integer(1) - z)
True
>>> L in Fields
True

```

Lazy Laurent series ring over a finite field:

```

sage: # needs sage.rings.finite_rings
sage: L.<z> = LazyLaurentSeriesRing(GF(3)); L
Lazy Laurent Series Ring in z over Finite Field of size 3
sage: e = 1 / (1 + z)
sage: e.coefficient(100)
1
sage: e.coefficient(100).parent()
Finite Field of size 3

```

```

>>> from sage.all import *
>>> # needs sage.rings.finite_rings
>>> L = LazyLaurentSeriesRing(GF(Integer(3)), names=('z',)); (z,) = L._first_
↳ngens(1); L
Lazy Laurent Series Ring in z over Finite Field of size 3
>>> e = Integer(1) / (Integer(1) + z)
>>> e.coefficient(Integer(100))
1
>>> e.coefficient(Integer(100)).parent()
Finite Field of size 3

```

Series can be defined by specifying a coefficient function and a valuation:

```

sage: R.<x,y> = QQ[]
sage: L.<z> = LazyLaurentSeriesRing(R)
sage: def coeff(n):
....:     if n < 0:
....:         return -2 + n
....:     if n == 0:
....:         return 6
....:     return x + y^n
sage: f = L(coeff, valuation=-5)
sage: f
-7*z^-5 - 6*z^-4 - 5*z^-3 - 4*z^-2 - 3*z^-1 + 6 + (x + y)*z + O(z^2)
sage: 1 / (1 - f)
1/7*z^5 - 6/49*z^6 + 1/343*z^7 + 8/2401*z^8 + 64/16807*z^9
+ 17319/117649*z^10 + (1/49*x + 1/49*y - 180781/823543)*z^11 + O(z^12)
sage: L(coeff, valuation=-3, degree=3, constant=x)
-5*z^-3 - 4*z^-2 - 3*z^-1 + 6 + (x + y)*z + (y^2 + x)*z^2
+ x*z^3 + x*z^4 + x*z^5 + O(z^6)

```

```

>>> from sage.all import *
>>> R = QQ['x, y']; (x, y,) = R._first_ngens(2)

```

(continues on next page)

(continued from previous page)

```

>>> L = LazyLaurentSeriesRing(R, names=('z',)); (z,) = L._first_ngens(1)
>>> def coeff(n):
...     if n < Integer(0):
...         return -Integer(2) + n
...     if n == Integer(0):
...         return Integer(6)
...     return x + y**n
>>> f = L(coeff, valuation=-Integer(5))
>>> f
-7*z^-5 - 6*z^-4 - 5*z^-3 - 4*z^-2 - 3*z^-1 + 6 + (x + y)*z + O(z^2)
>>> Integer(1) / (Integer(1) - f)
1/7*z^5 - 6/49*z^6 + 1/343*z^7 + 8/2401*z^8 + 64/16807*z^9
+ 17319/117649*z^10 + (1/49*x + 1/49*y - 180781/823543)*z^11 + O(z^12)
>>> L(coeff, valuation=-Integer(3), degree=Integer(3), constant=x)
-5*z^-3 - 4*z^-2 - 3*z^-1 + 6 + (x + y)*z + (y^2 + x)*z^2
+ x*z^3 + x*z^4 + x*z^5 + O(z^6)

```

We can also specify a polynomial or the initial coefficients. Additionally, we may specify that all coefficients are equal to a given constant, beginning at a given degree:

```

sage: L([1, x, y, 0, x+y])
1 + x*z + y*z^2 + (x + y)*z^4
sage: L([1, x, y, 0, x+y], constant=2)
1 + x*z + y*z^2 + (x + y)*z^4 + 2*z^5 + 2*z^6 + 2*z^7 + O(z^8)
sage: L([1, x, y, 0, x+y], degree=7, constant=2)
1 + x*z + y*z^2 + (x + y)*z^4 + 2*z^7 + 2*z^8 + 2*z^9 + O(z^10)
sage: L([1, x, y, 0, x+y], valuation=-2)
z^-2 + x*z^-1 + y + (x + y)*z^2
sage: L([1, x, y, 0, x+y], valuation=-2, constant=3)
z^-2 + x*z^-1 + y + (x + y)*z^2 + 3*z^3 + 3*z^4 + 3*z^5 + O(z^6)
sage: L([1, x, y, 0, x+y], valuation=-2, degree=4, constant=3)
z^-2 + x*z^-1 + y + (x + y)*z^2 + 3*z^4 + 3*z^5 + 3*z^6 + O(z^7)

```

```

>>> from sage.all import *
>>> L([Integer(1), x, y, Integer(0), x+y])
1 + x*z + y*z^2 + (x + y)*z^4
>>> L([Integer(1), x, y, Integer(0), x+y], constant=Integer(2))
1 + x*z + y*z^2 + (x + y)*z^4 + 2*z^5 + 2*z^6 + 2*z^7 + O(z^8)
>>> L([Integer(1), x, y, Integer(0), x+y], degree=Integer(7), constant=Integer(2))
1 + x*z + y*z^2 + (x + y)*z^4 + 2*z^7 + 2*z^8 + 2*z^9 + O(z^10)
>>> L([Integer(1), x, y, Integer(0), x+y], valuation=-Integer(2))
z^-2 + x*z^-1 + y + (x + y)*z^2
>>> L([Integer(1), x, y, Integer(0), x+y], valuation=-Integer(2), ↵
↵constant=Integer(3))
z^-2 + x*z^-1 + y + (x + y)*z^2 + 3*z^3 + 3*z^4 + 3*z^5 + O(z^6)
>>> L([Integer(1), x, y, Integer(0), x+y], valuation=-Integer(2), ↵
↵degree=Integer(4), constant=Integer(3))
z^-2 + x*z^-1 + y + (x + y)*z^2 + 3*z^4 + 3*z^5 + 3*z^6 + O(z^7)

```

Some additional examples over the integer ring:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)

```

(continues on next page)

(continued from previous page)

```

sage: L in Fields
False
sage: 1 / (1 - 2*z)^3
1 + 6*z + 24*z^2 + 80*z^3 + 240*z^4 + 672*z^5 + 1792*z^6 + O(z^7)

sage: R.<x> = LaurentPolynomialRing(ZZ)
sage: L(x^-2 + 3 + x)
z^-2 + 3 + z
sage: L(x^-2 + 3 + x, valuation=-5, constant=2)
z^-5 + 3*z^-3 + z^-2 + 2*z^-1 + 2 + 2*z + O(z^2)
sage: L(x^-2 + 3 + x, valuation=-5, degree=0, constant=2)
z^-5 + 3*z^-3 + z^-2 + 2 + 2*z + 2*z^2 + O(z^3)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> L in Fields
False
>>> Integer(1) / (Integer(1) - Integer(2)*z)**Integer(3)
1 + 6*z + 24*z^2 + 80*z^3 + 240*z^4 + 672*z^5 + 1792*z^6 + O(z^7)

>>> R = LaurentPolynomialRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> L(x**Integer(2) + Integer(3) + x)
z^-2 + 3 + z
>>> L(x**Integer(2) + Integer(3) + x, valuation=-Integer(5), constant=Integer(2))
z^-5 + 3*z^-3 + z^-2 + 2*z^-1 + 2 + 2*z + O(z^2)
>>> L(x**Integer(2) + Integer(3) + x, valuation=-Integer(5), degree=Integer(0),
↪constant=Integer(2))
z^-5 + 3*z^-3 + z^-2 + 2 + 2*z + 2*z^2 + O(z^3)

```

We can truncate a series, shift its coefficients, or replace all coefficients beginning with a given degree by a constant:

```

sage: f = 1 / (z + z^2)
sage: f
z^-1 - 1 + z - z^2 + z^3 - z^4 + z^5 + O(z^6)
sage: L(f, valuation=2)
z^2 - z^3 + z^4 - z^5 + z^6 - z^7 + z^8 + O(z^9)
sage: L(f, degree=3)
z^-1 - 1 + z - z^2
sage: L(f, degree=3, constant=2)
z^-1 - 1 + z - z^2 + 2*z^3 + 2*z^4 + 2*z^5 + O(z^6)
sage: L(f, valuation=1, degree=4)
z - z^2 + z^3
sage: L(f, valuation=1, degree=4, constant=5)
z - z^2 + z^3 + 5*z^4 + 5*z^5 + 5*z^6 + O(z^7)

```

```

>>> from sage.all import *
>>> f = Integer(1) / (z + z**Integer(2))
>>> f
z^-1 - 1 + z - z^2 + z^3 - z^4 + z^5 + O(z^6)
>>> L(f, valuation=Integer(2))
z^2 - z^3 + z^4 - z^5 + z^6 - z^7 + z^8 + O(z^9)
>>> L(f, degree=Integer(3))

```

(continues on next page)

(continued from previous page)

```

z^-1 - 1 + z - z^2
>>> L(f, degree=Integer(3), constant=Integer(2))
z^-1 - 1 + z - z^2 + 2*z^3 + 2*z^4 + 2*z^5 + O(z^6)
>>> L(f, valuation=Integer(1), degree=Integer(4))
z - z^2 + z^3
>>> L(f, valuation=Integer(1), degree=Integer(4), constant=Integer(5))
z - z^2 + z^3 + 5*z^4 + 5*z^5 + 5*z^6 + O(z^7)

```

Power series can be defined recursively (see `sage.rings.lazy_series.LazyModuleElement.define()` for more examples):

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: s = L.undefined(valuation=0)
sage: s.define(1 + z*s^2)
sage: s
1 + z + 2*z^2 + 5*z^3 + 14*z^4 + 42*z^5 + 132*z^6 + O(z^7)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> s = L.undefined(valuation=Integer(0))
>>> s.define(Integer(1) + z*s**Integer(2))
>>> s
1 + z + 2*z^2 + 5*z^3 + 14*z^4 + 42*z^5 + 132*z^6 + O(z^7)

```

By default, any two series f and g that are not known to be equal are considered to be different:

```

sage: f = L(lambda n: 0, valuation=0)
sage: f == 0
False

sage: f = L(constant=1, valuation=0).derivative(); f
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
sage: g = L(lambda n: (n+1), valuation=0); g
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
sage: f == g
False

```

```

>>> from sage.all import *
>>> f = L(lambda n: Integer(0), valuation=Integer(0))
>>> f == Integer(0)
False

>>> f = L(constant=Integer(1), valuation=Integer(0)).derivative(); f
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
>>> g = L(lambda n: (n+Integer(1)), valuation=Integer(0)); g
1 + 2*z + 3*z^2 + 4*z^3 + 5*z^4 + 6*z^5 + 7*z^6 + O(z^7)
>>> f == g
False

```

**Warning**

We have imposed that $(f == g) == \text{not } (f != g)$, and so $f != g$ returning `True` might not mean that the two series are actually different:

```
sage: f = L(lambda n: 0, valuation=0)
sage: g = L.zero()
sage: f != g
True

>>> from sage.all import *
>>> f = L(lambda n: Integer(0), valuation=Integer(0))
>>> g = L.zero()
>>> f != g
True
```

This can be verified by `is_nonzero()`, which only returns `True` if the series is known to be nonzero:

```
sage: (f - g).is_nonzero()
False

>>> from sage.all import *
>>> (f - g).is_nonzero()
False
```

The implementation of the ring can be either be a sparse or a dense one. The default is a sparse implementation:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: L.is_sparse()
True
sage: L.<z> = LazyLaurentSeriesRing(ZZ, sparse=False)
sage: L.is_sparse()
False
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> L.is_sparse()
True
>>> L = LazyLaurentSeriesRing(ZZ, sparse=False, names=('z',)); (z,) = L._first_
↳ngens(1)
>>> L.is_sparse()
False
```

We additionally provide two other methods of performing comparisons. The first is raising a `ValueError` and the second uses a check up to a (user set) finite precision. These behaviors are set using the options `secure` and `halting_precision`. In particular, this applies to series that are not specified by a finite number of initial coefficients and a constant for the remaining coefficients. Equality checking will depend on the coefficients which have already been computed. If this information is not enough to check that two series are different, then if `L.options.secure` is set to `True`, then we raise a `ValueError`:

```
sage: L.options.secure = True
sage: f = 1 / (z + z^2); f
z^-1 - 1 + z - z^2 + z^3 - z^4 + z^5 + O(z^6)
sage: f2 = f * 2 # currently no coefficients computed
sage: f3 = f * 3 # currently no coefficients computed
sage: f2 == f3
Traceback (most recent call last):
...
```

(continues on next page)

(continued from previous page)

```

ValueError: undecidable
sage: f2 # computes some of the coefficients of f2
2*z^-1 - 2 + 2*z - 2*z^2 + 2*z^3 - 2*z^4 + 2*z^5 + O(z^6)
sage: f3 # computes some of the coefficients of f3
3*z^-1 - 3 + 3*z - 3*z^2 + 3*z^3 - 3*z^4 + 3*z^5 + O(z^6)
sage: f2 == f3
False
sage: f2a = f + f
sage: f2 == f2a
Traceback (most recent call last):
...
ValueError: undecidable
sage: zf = L(lambda n: 0, valuation=0)
sage: zf == 0
Traceback (most recent call last):
...
ValueError: undecidable

```

```

>>> from sage.all import *
>>> L.options.secure = True
>>> f = Integer(1) / (z + z**Integer(2)); f
z^-1 - 1 + z - z^2 + z^3 - z^4 + z^5 + O(z^6)
>>> f2 = f * Integer(2) # currently no coefficients computed
>>> f3 = f * Integer(3) # currently no coefficients computed
>>> f2 == f3
Traceback (most recent call last):
...
ValueError: undecidable
>>> f2 # computes some of the coefficients of f2
2*z^-1 - 2 + 2*z - 2*z^2 + 2*z^3 - 2*z^4 + 2*z^5 + O(z^6)
>>> f3 # computes some of the coefficients of f3
3*z^-1 - 3 + 3*z - 3*z^2 + 3*z^3 - 3*z^4 + 3*z^5 + O(z^6)
>>> f2 == f3
False
>>> f2a = f + f
>>> f2 == f2a
Traceback (most recent call last):
...
ValueError: undecidable
>>> zf = L(lambda n: Integer(0), valuation=Integer(0))
>>> zf == Integer(0)
Traceback (most recent call last):
...
ValueError: undecidable

```

For boolean checks, an error is raised when it is not known to be nonzero:

```

sage: bool(zf)
Traceback (most recent call last):
...
ValueError: undecidable

```

```
>>> from sage.all import *
>>> bool(zf)
Traceback (most recent call last):
...
ValueError: undecidable
```

If the halting precision is set to a finite number p (for unlimited precision, it is set to `None`), then it will check up to p values from the current position:

```
sage: L.options.halting_precision = 20
sage: f2 = f * 2 # currently no coefficients computed
sage: f3 = f * 3 # currently no coefficients computed
sage: f2 == f3
False
sage: f2a = f + f
sage: f2 == f2a
True
sage: zf = L(lambda n: 0, valuation=0)
sage: zf == 0
True
```

```
>>> from sage.all import *
>>> L.options.halting_precision = Integer(20)
>>> f2 = f * Integer(2) # currently no coefficients computed
>>> f3 = f * Integer(3) # currently no coefficients computed
>>> f2 == f3
False
>>> f2a = f + f
>>> f2 == f2a
True
>>> zf = L(lambda n: Integer(0), valuation=Integer(0))
>>> zf == Integer(0)
True
```

Element

alias of `LazyLaurentSeries`

dilog()

Return the dilogarithm as an element in `self`.

See also

`polylog()`

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: L.dilog()
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
sage: L.polylog(2)
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
```

(continues on next page)

(continued from previous page)

```
sage: L.<x> = LazyLaurentSeriesRing(SR)
sage: L.dilog()
x + 1/4*x^2 + 1/9*x^3 + 1/16*x^4 + 1/25*x^5 + 1/36*x^6 + 1/49*x^7 + O(x^8)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> L.dilog()
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
>>> L.polylog(Integer(2))
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)

>>> L = LazyLaurentSeriesRing(SR, names=('x',)); (x,) = L._first_ngens(1)
>>> L.dilog()
x + 1/4*x^2 + 1/9*x^3 + 1/16*x^4 + 1/25*x^5 + 1/36*x^6 + 1/49*x^7 + O(x^8)
```

REFERENCES:

- [Wikipedia article Dilogarithm](#)

euler()

Return the Euler function as an element of `self`.

The *Euler function* is defined as

$$\phi(z) = (z; z)_{\infty} = \sum_{n=0}^{\infty} (-1)^n q^{(3n^2-n)/2}.$$

EXAMPLES:

```
sage: L.<q> = LazyLaurentSeriesRing(ZZ)
sage: phi = q.euler()
sage: phi
1 - q - q^2 + q^5 + O(q^7)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('q',)); (q,) = L._first_ngens(1)
>>> phi = q.euler()
>>> phi
1 - q - q^2 + q^5 + O(q^7)
```

We verify that $1/\phi$ gives the generating function for all partitions:

```
sage: P = 1 / phi; P
1 + q + 2*q^2 + 3*q^3 + 5*q^4 + 7*q^5 + 11*q^6 + O(q^7)
sage: P[:20] == [Partitions(n).cardinality() for n in range(20)] #_
↪needs sage.libs.flint
True
```

```
>>> from sage.all import *
>>> P = Integer(1) / phi; P
1 + q + 2*q^2 + 3*q^3 + 5*q^4 + 7*q^5 + 11*q^6 + O(q^7)
>>> P[:Integer(20)] == [Partitions(n).cardinality() for n in_
↪range(Integer(20))] # needs sage.libs.flint
True
```

REFERENCES:

- [Wikipedia article Euler_function](#)

gen($n=0$)Return the n -th generator of `self`.

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: L.gen()
z
sage: L.gen(3)
Traceback (most recent call last):
...
IndexError: there is only one generator
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> L.gen()
z
>>> L.gen(Integer(3))
Traceback (most recent call last):
...
IndexError: there is only one generator
```

gens()Return the generators of `self`.

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: L.gens()
(z,)
sage: 1/(1 - z)
1 + z + z^2 + O(z^3)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> L.gens()
(z,)
>>> Integer(1)/(Integer(1) - z)
1 + z + z^2 + O(z^3)
```

jacobi_theta($w, a=0, b=0$)Return the Jacobi function $\vartheta_{ab}(w; q)$ as an element of `self`.The *Jacobi theta functions* with nome $q = \exp(\pi i \tau)$ for $z \in \mathbf{C}$ and $\tau \in \mathbf{R} + \mathbf{R}_{>0}i$, are defined as

$$\begin{aligned}\vartheta_{00}(z; \tau) &= \sum_{n=0}^{\infty} (w^{2n} + w^{-2n}) q^{n^2}, \quad \vartheta_{01}(z; \tau) = \sum_{n=0}^{\infty} (-1)^n (w^{2n} + w^{-2n}) q^{n^2}, \\ \vartheta_{10}(z; \tau) &= \sum_{n=0}^{\infty} (w^{2n+1} + w^{-2n+1}) q^{n^2+n}, \\ \vartheta_{11}(z; \tau) &= \sum_{n=0}^{\infty} (-1)^n (w^{2n+1} + w^{-2n+1}) q^{n^2+n},\end{aligned}$$

where $w = \exp(\pi iz)$. We consider them as formal power series in q with the coefficients in the Laurent polynomial ring $R[w, w^{-1}]$ (for a commutative ring R). Here, we deviate from the standard definition of θ_{10} and θ_{11} by removing the overall factor of $q^{1/4}$ and $iq^{1/4}$, respectively.

EXAMPLES:

```
sage: R.<w> = LaurentPolynomialRing(QQ)
sage: L.<q> = LazyPowerSeriesRing(R)
sage: L.options.display_length = 17 # to display more coefficients
sage: theta = q.jacobi_theta(w)
sage: theta
1 + ((w^-2+w^2)*q) + ((w^-4+w^4)*q^4) + ((w^-6+w^6)*q^9)
+ ((w^-8+w^8)*q^16) + O(q^17)

sage: th3 = q.jacobi_theta(1, 0, 0); th3
1 + 2*q + 2*q^4 + 2*q^9 + 2*q^16 + O(q^17)
sage: th2 = q.jacobi_theta(1, 1, 0); th2
2 + 2*q^2 + 2*q^6 + 2*q^12 + O(q^17)
sage: th4 = q.jacobi_theta(1, 0, 1); th4
1 + (-2*q) + 2*q^4 + (-2*q^9) + 2*q^16 + O(q^17)
sage: th1 = -q.jacobi_theta(1, 1, 1); th1
-2 + 2*q^2 + (-2*q^6) + 2*q^12 + O(q^17)
```

```
>>> from sage.all import *
>>> R = LaurentPolynomialRing(QQ, names=('w',)); (w,) = R._first_ngens(1)
>>> L = LazyPowerSeriesRing(R, names=('q',)); (q,) = L._first_ngens(1)
>>> L.options.display_length = Integer(17) # to display more coefficients
>>> theta = q.jacobi_theta(w)
>>> theta
1 + ((w^-2+w^2)*q) + ((w^-4+w^4)*q^4) + ((w^-6+w^6)*q^9)
+ ((w^-8+w^8)*q^16) + O(q^17)

>>> th3 = q.jacobi_theta(Integer(1), Integer(0), Integer(0)); th3
1 + 2*q + 2*q^4 + 2*q^9 + 2*q^16 + O(q^17)
>>> th2 = q.jacobi_theta(Integer(1), Integer(1), Integer(0)); th2
2 + 2*q^2 + 2*q^6 + 2*q^12 + O(q^17)
>>> th4 = q.jacobi_theta(Integer(1), Integer(0), Integer(1)); th4
1 + (-2*q) + 2*q^4 + (-2*q^9) + 2*q^16 + O(q^17)
>>> th1 = -q.jacobi_theta(Integer(1), Integer(1), Integer(1)); th1
-2 + 2*q^2 + (-2*q^6) + 2*q^12 + O(q^17)
```

We verify the Jacobi triple product formula:

```
sage: JTP = L.prod(lambda n: ((1 - q^(2*n)) * (1 + w^2*q^(2*n-1))
....:                        * (1 + w^-2*q^(2*n-1))), 1, oo)
sage: JTP
1 + ((w^-2+w^2)*q) + ((w^-4+w^4)*q^4) + ((w^-6+w^6)*q^9)
+ ((w^-8+w^8)*q^16) + O(q^17)
sage: JTP[:30] == theta[:30]
True
```

```
>>> from sage.all import *
>>> JTP = L.prod(lambda n: ((Integer(1) - q**(Integer(2)*n)) * (Integer(1) +
↪ w**Integer(2)*q**(Integer(2)*n-Integer(1))))
```

(continues on next page)

(continued from previous page)

```

...
    * (Integer(1) + w**Integer(2)*q**(Integer(2)*n-
    ↪Integer(1))), Integer(1), oo)
>>> JTP
1 + ((w^-2+w^2)*q) + ((w^-4+w^4)*q^4) + ((w^-6+w^6)*q^9)
  + ((w^-8+w^8)*q^16) + O(q^17)
>>> JTP[:Integer(30)] == theta[:Integer(30)]
True

```

We verify the Jacobi identity:

```

sage: LHS = q.jacobi_theta(1, 0, 1)^4 + q*q.jacobi_theta(1, 1, 0)^4
sage: LHS
1 + 8*q + 24*q^2 + 32*q^3 + 24*q^4 + 48*q^5 + 96*q^6 + 64*q^7
  + 24*q^8 + 104*q^9 + 144*q^10 + 96*q^11 + 96*q^12 + 112*q^13
  + 192*q^14 + 192*q^15 + 24*q^16 + O(q^17)
sage: RHS = q.jacobi_theta(1, 0, 0)^4
sage: RHS
1 + 8*q + 24*q^2 + 32*q^3 + 24*q^4 + 48*q^5 + 96*q^6 + 64*q^7
  + 24*q^8 + 104*q^9 + 144*q^10 + 96*q^11 + 96*q^12 + 112*q^13
  + 192*q^14 + 192*q^15 + 24*q^16 + O(q^17)
sage: LHS[:20] == RHS[:20]
True

```

```

>>> from sage.all import *
>>> LHS = q.jacobi_theta(Integer(1), Integer(0), Integer(1))**Integer(4) +
    ↪q*q.jacobi_theta(Integer(1), Integer(1), Integer(0))**Integer(4)
>>> LHS
1 + 8*q + 24*q^2 + 32*q^3 + 24*q^4 + 48*q^5 + 96*q^6 + 64*q^7
  + 24*q^8 + 104*q^9 + 144*q^10 + 96*q^11 + 96*q^12 + 112*q^13
  + 192*q^14 + 192*q^15 + 24*q^16 + O(q^17)
>>> RHS = q.jacobi_theta(Integer(1), Integer(0), Integer(0))**Integer(4)
>>> RHS
1 + 8*q + 24*q^2 + 32*q^3 + 24*q^4 + 48*q^5 + 96*q^6 + 64*q^7
  + 24*q^8 + 104*q^9 + 144*q^10 + 96*q^11 + 96*q^12 + 112*q^13
  + 192*q^14 + 192*q^15 + 24*q^16 + O(q^17)
>>> LHS[:Integer(20)] == RHS[:Integer(20)]
True

```

We verify some relationships to the (rescaled) Dedekind eta function:

```

sage: eta = q.euler()
sage: RHS = 2 * eta(q^4)^2 / eta(q^2); RHS
2 + 2*q^2 + 2*q^6 + 2*q^12 + O(q^17)
sage: th2[:30] == RHS[:30]
True

sage: RHS = eta(q^2)^5 / (eta^2 * eta(q^4)^2); RHS
1 + 2*q + 2*q^4 + 2*q^9 + 2*q^16 + O(q^17)
sage: th3[:30] == RHS[:30]
True

sage: RHS = eta^2 / eta(q^2); RHS

```

(continues on next page)

(continued from previous page)

$$1 + (-2*q) + 2*q^4 + (-2*q^9) + 2*q^{16} + O(q^{17})$$

```
sage: th4[:30] == RHS[:30]
```

```
True
```

```
sage: LHS = th2 * th3 * th4; LHS
```

$$2 + (-6*q^2) + 10*q^6 + (-14*q^{12}) + O(q^{17})$$

```
sage: RHS = 2 * eta(q^2)^3; RHS
```

$$2 + (-6*q^2) + 10*q^6 + (-14*q^{12}) + O(q^{17})$$

```
sage: LHS[:30] == RHS[:30]
```

```
True
```

```
>>> from sage.all import *
```

```
>>> eta = q.euler()
```

```
>>> RHS = Integer(2) * eta(q**Integer(4))**Integer(2) / eta(q**Integer(2));
```

```
↳RHS
```

$$2 + 2*q^2 + 2*q^6 + 2*q^{12} + O(q^{17})$$

```
>>> th2[:Integer(30)] == RHS[:Integer(30)]
```

```
True
```

```
>>> RHS = eta(q**Integer(2))**Integer(5) / (eta**Integer(2) *
```

```
↳eta(q**Integer(4))**Integer(2)); RHS
```

$$1 + 2*q + 2*q^4 + 2*q^9 + 2*q^{16} + O(q^{17})$$

```
>>> th3[:Integer(30)] == RHS[:Integer(30)]
```

```
True
```

```
>>> RHS = eta**Integer(2) / eta(q**Integer(2)); RHS
```

$$1 + (-2*q) + 2*q^4 + (-2*q^9) + 2*q^{16} + O(q^{17})$$

```
>>> th4[:Integer(30)] == RHS[:Integer(30)]
```

```
True
```

```
>>> LHS = th2 * th3 * th4; LHS
```

$$2 + (-6*q^2) + 10*q^6 + (-14*q^{12}) + O(q^{17})$$

```
>>> RHS = Integer(2) * eta(q**Integer(2))**Integer(3); RHS
```

$$2 + (-6*q^2) + 10*q^6 + (-14*q^{12}) + O(q^{17})$$

```
>>> LHS[:Integer(30)] == RHS[:Integer(30)]
```

```
True
```

We verify some derivative formulas (recall our conventions):

```
sage: LHS = th4 * th3.derivative() - th3 * th4.derivative(); LHS
```

$$4 + (-24*q^4) + 36*q^8 + 40*q^{12} + (-120*q^{16}) + O(q^{17})$$

```
sage: RHS = th3 * th4 * (th3^4 - th4^4) / (4*q); RHS
```

$$4 + (-24*q^4) + 36*q^8 + 40*q^{12} + O(q^{16})$$

```
sage: LHS[:30] == RHS[:30]
```

```
True
```

```
sage: LHS = (th2 / th3) / (4*q) + (th2 / th3).derivative(); LHS
```

$$\begin{aligned} &1/2/q - 5 + 45/2*q + (-65*q^2) + 153*q^3 + (-336*q^4) + 1375/2*q^5 \\ &+ (-1305*q^6) + 2376*q^7 + (-4181*q^8) + 7093*q^9 + (-11745*q^{10}) \\ &+ 38073/2*q^{11} + (-30157*q^{12}) + 46968*q^{13} + (-72041*q^{14}) \\ &+ 108810*q^{15} + O(q^{16}) \end{aligned}$$

```
sage: RHS = th2 * th4^4 / (4 * q * th3); RHS
```

(continues on next page)

(continued from previous page)

```

1/2/q - 5 + 45/2*q + (-65*q^2) + 153*q^3 + (-336*q^4) + 1375/2*q^5
+ (-1305*q^6) + 2376*q^7 + (-4181*q^8) + 7093*q^9 + (-11745*q^10)
+ 38073/2*q^11 + (-30157*q^12) + 46968*q^13 + (-72041*q^14)
+ 108810*q^15 + O(q^16)
sage: LHS[:30] == RHS[:30]
True

sage: LHS = (th2 / th4) / (4*q) + (th2 / th4).derivative(); LHS
1/2/q + 5 + 45/2*q + 65*q^2 + 153*q^3 + 336*q^4 + 1375/2*q^5
+ 1305*q^6 + 2376*q^7 + 4181*q^8 + 7093*q^9 + 11745*q^10
+ 38073/2*q^11 + 30157*q^12 + 46968*q^13 + 72041*q^14
+ 108810*q^15 + O(q^16)
sage: RHS = th2 * th3^4 / (4 * q * th4); RHS
1/2/q + 5 + 45/2*q + 65*q^2 + 153*q^3 + 336*q^4 + 1375/2*q^5
+ 1305*q^6 + 2376*q^7 + 4181*q^8 + 7093*q^9 + 11745*q^10
+ 38073/2*q^11 + 30157*q^12 + 46968*q^13 + 72041*q^14
+ 108810*q^15 + O(q^16)
sage: LHS[:30] == RHS[:30]
True

sage: LHS = (th3 / th4).derivative(); LHS
4 + 16*q + 48*q^2 + 128*q^3 + 280*q^4 + 576*q^5 + 1120*q^6 + 2048*q^7
+ 3636*q^8 + 6240*q^9 + 10384*q^10 + 16896*q^11 + 26936*q^12
+ 42112*q^13 + 64800*q^14 + 98304*q^15 + 147016*q^16 + O(q^17)
sage: RHS = (th3^5 - th3 * th4^4) / (4 * q * th4); RHS
4 + 16*q + 48*q^2 + 128*q^3 + 280*q^4 + 576*q^5 + 1120*q^6 + 2048*q^7
+ 3636*q^8 + 6240*q^9 + 10384*q^10 + 16896*q^11 + 26936*q^12
+ 42112*q^13 + 64800*q^14 + 98304*q^15 + O(q^16)
sage: LHS[:30] == RHS[:30]
True

```

```

>>> from sage.all import *
>>> LHS = th4 * th3.derivative() - th3 * th4.derivative(); LHS
4 + (-24*q^4) + 36*q^8 + 40*q^12 + (-120*q^16) + O(q^17)
>>> RHS = th3 * th4 * (th3**Integer(4) - th4**Integer(4)) / (Integer(4)*q);
↪RHS
4 + (-24*q^4) + 36*q^8 + 40*q^12 + O(q^16)
>>> LHS[:Integer(30)] == RHS[:Integer(30)]
True

>>> LHS = (th2 / th3) / (Integer(4)*q) + (th2 / th3).derivative(); LHS
1/2/q - 5 + 45/2*q + (-65*q^2) + 153*q^3 + (-336*q^4) + 1375/2*q^5
+ (-1305*q^6) + 2376*q^7 + (-4181*q^8) + 7093*q^9 + (-11745*q^10)
+ 38073/2*q^11 + (-30157*q^12) + 46968*q^13 + (-72041*q^14)
+ 108810*q^15 + O(q^16)
>>> RHS = th2 * th4**Integer(4) / (Integer(4) * q * th3); RHS
1/2/q - 5 + 45/2*q + (-65*q^2) + 153*q^3 + (-336*q^4) + 1375/2*q^5
+ (-1305*q^6) + 2376*q^7 + (-4181*q^8) + 7093*q^9 + (-11745*q^10)
+ 38073/2*q^11 + (-30157*q^12) + 46968*q^13 + (-72041*q^14)
+ 108810*q^15 + O(q^16)
>>> LHS[:Integer(30)] == RHS[:Integer(30)]
True

```

(continues on next page)

(continued from previous page)

```

>>> LHS = (th2 / th4) / (Integer(4)*q) + (th2 / th4).derivative(); LHS
1/2/q + 5 + 45/2*q + 65*q^2 + 153*q^3 + 336*q^4 + 1375/2*q^5
+ 1305*q^6 + 2376*q^7 + 4181*q^8 + 7093*q^9 + 11745*q^10
+ 38073/2*q^11 + 30157*q^12 + 46968*q^13 + 72041*q^14
+ 108810*q^15 + O(q^16)
>>> RHS = th2 * th3**Integer(4) / (Integer(4) * q * th4); RHS
1/2/q + 5 + 45/2*q + 65*q^2 + 153*q^3 + 336*q^4 + 1375/2*q^5
+ 1305*q^6 + 2376*q^7 + 4181*q^8 + 7093*q^9 + 11745*q^10
+ 38073/2*q^11 + 30157*q^12 + 46968*q^13 + 72041*q^14
+ 108810*q^15 + O(q^16)
>>> LHS[:Integer(30)] == RHS[:Integer(30)]
True

>>> LHS = (th3 / th4).derivative(); LHS
4 + 16*q + 48*q^2 + 128*q^3 + 280*q^4 + 576*q^5 + 1120*q^6 + 2048*q^7
+ 3636*q^8 + 6240*q^9 + 10384*q^10 + 16896*q^11 + 26936*q^12
+ 42112*q^13 + 64800*q^14 + 98304*q^15 + 147016*q^16 + O(q^17)
>>> RHS = (th3**Integer(5) - th3 * th4**Integer(4)) / (Integer(4) * q * th4);
↪RHS
4 + 16*q + 48*q^2 + 128*q^3 + 280*q^4 + 576*q^5 + 1120*q^6 + 2048*q^7
+ 3636*q^8 + 6240*q^9 + 10384*q^10 + 16896*q^11 + 26936*q^12
+ 42112*q^13 + 64800*q^14 + 98304*q^15 + O(q^16)
>>> LHS[:Integer(30)] == RHS[:Integer(30)]
True

```

We have the partition generating function:

```

sage: P = th3^(-1/6) * th4^(-2/3) * ((th3^4 - th4^4)/(16*q))^(-1/24); P
1 + q + 2*q^2 + 3*q^3 + 5*q^4 + 7*q^5 + 11*q^6 + 15*q^7 + 22*q^8
+ 30*q^9 + 42*q^10 + 56*q^11 + 77*q^12 + 101*q^13 + 135*q^14
+ 176*q^15 + 231*q^16 + O(q^17)
sage: 1 / q.euler()
1 + q + 2*q^2 + 3*q^3 + 5*q^4 + 7*q^5 + 11*q^6 + 15*q^7 + 22*q^8
+ 30*q^9 + 42*q^10 + 56*q^11 + 77*q^12 + 101*q^13 + 135*q^14
+ 176*q^15 + 231*q^16 + O(q^17)
sage: oeis(P[:30]) # optional - internet
0: A000041: a(n) is the number of partitions of n (the partition numbers).
...

```

```

>>> from sage.all import *
>>> P = th3**(-Integer(1)/Integer(6)) * th4**(-Integer(2)/Integer(3)) *
↪((th3**Integer(4) - th4**Integer(4))/(Integer(16)*q))**(-Integer(1)/
↪Integer(24)); P
1 + q + 2*q^2 + 3*q^3 + 5*q^4 + 7*q^5 + 11*q^6 + 15*q^7 + 22*q^8
+ 30*q^9 + 42*q^10 + 56*q^11 + 77*q^12 + 101*q^13 + 135*q^14
+ 176*q^15 + 231*q^16 + O(q^17)
>>> Integer(1) / q.euler()
1 + q + 2*q^2 + 3*q^3 + 5*q^4 + 7*q^5 + 11*q^6 + 15*q^7 + 22*q^8
+ 30*q^9 + 42*q^10 + 56*q^11 + 77*q^12 + 101*q^13 + 135*q^14
+ 176*q^15 + 231*q^16 + O(q^17)
>>> oeis(P[:Integer(30)]) # optional - internet

```

(continues on next page)

(continued from previous page)

```
0: A000041: a(n) is the number of partitions of n (the partition numbers).
...
```

We have the strict partition generating function:

```
sage: SP = th3^(1/6) * th4^(-1/3) * ((th3^4 - th4^4)/(16*q))^(1/24); SP
1 + q + q^2 + 2*q^3 + 2*q^4 + 3*q^5 + 4*q^6 + 5*q^7 + 6*q^8 + 8*q^9
+ 10*q^10 + 12*q^11 + 15*q^12 + 18*q^13 + 22*q^14 + 27*q^15
+ 32*q^16 + O(q^17)
sage: oeis(SP[:30]) # optional - internet
0: A000009: Expansion of Product_{m >= 1} (1 + x^m);
number of partitions of n into distinct parts;
number of partitions of n into odd parts.
1: A081360: Expansion of q^(-1/24) (m (1-m) / 16)^(1/24) in
powers of q, where m = k^2 is the parameter and q is the nome
for Jacobian elliptic functions.
```

```
>>> from sage.all import *
>>> SP = th3**(Integer(1)/Integer(6)) * th4**(-Integer(1)/Integer(3)) *
↳ ((th3**Integer(4) - th4**Integer(4))/(Integer(16)*q))**(Integer(1)/
↳ Integer(24)); SP
1 + q + q^2 + 2*q^3 + 2*q^4 + 3*q^5 + 4*q^6 + 5*q^7 + 6*q^8 + 8*q^9
+ 10*q^10 + 12*q^11 + 15*q^12 + 18*q^13 + 22*q^14 + 27*q^15
+ 32*q^16 + O(q^17)
>>> oeis(SP[:Integer(30)]) # optional - internet
0: A000009: Expansion of Product_{m >= 1} (1 + x^m);
number of partitions of n into distinct parts;
number of partitions of n into odd parts.
1: A081360: Expansion of q^(-1/24) (m (1-m) / 16)^(1/24) in
powers of q, where m = k^2 is the parameter and q is the nome
for Jacobian elliptic functions.
```

We have the overpartition generating function:

```
sage: ~th4
1 + 2*q + 4*q^2 + 8*q^3 + 14*q^4 + 24*q^5 + 40*q^6 + 64*q^7 + 100*q^8
+ 154*q^9 + 232*q^10 + 344*q^11 + 504*q^12 + 728*q^13 + 1040*q^14
+ 1472*q^15 + 2062*q^16 + O(q^17)
sage: oeis((~th4)[:20]) # optional - internet
0: A015128: Number of overpartitions of n: ... overlined.
1: A004402: Expansion of 1 / Sum_{n=-oo..oo} x^(n^2).
```

```
>>> from sage.all import *
>>> ~th4
1 + 2*q + 4*q^2 + 8*q^3 + 14*q^4 + 24*q^5 + 40*q^6 + 64*q^7 + 100*q^8
+ 154*q^9 + 232*q^10 + 344*q^11 + 504*q^12 + 728*q^13 + 1040*q^14
+ 1472*q^15 + 2062*q^16 + O(q^17)
>>> oeis((~th4)[:Integer(20)]) # optional - internet
0: A015128: Number of overpartitions of n: ... overlined.
1: A004402: Expansion of 1 / Sum_{n=-oo..oo} x^(n^2).
```

We give an example over the SymbolicRing with the input $w = e^{\pi iz}$ and verify the periodicity:

```

sage: L.<q> = LazyLaurentSeriesRing(SR)
sage: z = SR.var('z')
sage: theta = L.jacobi_theta(exp(pi*I*z))
sage: theta
1 + (e^(2*I*pi*z) + e^(-2*I*pi*z))*q
  + (e^(4*I*pi*z) + e^(-4*I*pi*z))*q^4
  + (e^(6*I*pi*z) + e^(-6*I*pi*z))*q^9
  + (e^(8*I*pi*z) + e^(-8*I*pi*z))*q^16 + O(q^17)

sage: theta.map_coefficients(lambda c: c(z=z+1))
1 + (e^(2*I*pi*z) + e^(-2*I*pi*z))*q
  + (e^(4*I*pi*z) + e^(-4*I*pi*z))*q^4
  + (e^(6*I*pi*z) + e^(-6*I*pi*z))*q^9
  + (e^(8*I*pi*z) + e^(-8*I*pi*z))*q^16 + O(q^17)

sage: L.options._reset() # reset options

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(SR, names=('q',)); (q,) = L._first_ngens(1)
>>> z = SR.var('z')
>>> theta = L.jacobi_theta(exp(pi*I*z))
>>> theta
1 + (e^(2*I*pi*z) + e^(-2*I*pi*z))*q
  + (e^(4*I*pi*z) + e^(-4*I*pi*z))*q^4
  + (e^(6*I*pi*z) + e^(-6*I*pi*z))*q^9
  + (e^(8*I*pi*z) + e^(-8*I*pi*z))*q^16 + O(q^17)

>>> theta.map_coefficients(lambda c: c(z=z+Integer(1)))
1 + (e^(2*I*pi*z) + e^(-2*I*pi*z))*q
  + (e^(4*I*pi*z) + e^(-4*I*pi*z))*q^4
  + (e^(6*I*pi*z) + e^(-6*I*pi*z))*q^9
  + (e^(8*I*pi*z) + e^(-8*I*pi*z))*q^16 + O(q^17)

>>> L.options._reset() # reset options

```

REFERENCES:

- [Wikipedia article Theta_function](#)

ngens()

Return the number of generators of `self`.

This is always 1.

EXAMPLES:

```

sage: L.<z> = LazyLaurentSeriesRing(ZZ)
sage: L.ngens()
1

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> L.ngens()
1

```

polylog(s)

Return the polylogarithm at s as an element in `self`.

The *polylogarithm* at s is the power series in z

$$\mathrm{Li}_s(z) = \sum_{k=1}^{\infty} \frac{z^k}{k^s}.$$

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: L.polylog(1)
z + 1/2*z^2 + 1/3*z^3 + 1/4*z^4 + 1/5*z^5 + 1/6*z^6 + 1/7*z^7 + O(z^8)
sage: -log(1 - z)
z + 1/2*z^2 + 1/3*z^3 + 1/4*z^4 + 1/5*z^5 + 1/6*z^6 + 1/7*z^7 + O(z^8)
sage: L.polylog(2)
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
sage: (-log(1-z) / z).integral()
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + O(z^7)
sage: L.polylog(0)
z + z^2 + z^3 + O(z^4)
sage: L.polylog(-1)
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + 7*z^7 + O(z^8)
sage: z / (1-z)^2
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + 7*z^7 + O(z^8)
sage: L.polylog(-2)
z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + 49*z^7 + O(z^8)
sage: z * (1 + z) / (1 - z)^3
z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + 49*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> L.polylog(Integer(1))
z + 1/2*z^2 + 1/3*z^3 + 1/4*z^4 + 1/5*z^5 + 1/6*z^6 + 1/7*z^7 + O(z^8)
>>> -log(Integer(1) - z)
z + 1/2*z^2 + 1/3*z^3 + 1/4*z^4 + 1/5*z^5 + 1/6*z^6 + 1/7*z^7 + O(z^8)
>>> L.polylog(Integer(2))
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + 1/49*z^7 + O(z^8)
>>> (-log(Integer(1)-z) / z).integral()
z + 1/4*z^2 + 1/9*z^3 + 1/16*z^4 + 1/25*z^5 + 1/36*z^6 + O(z^7)
>>> L.polylog(Integer(0))
z + z^2 + z^3 + O(z^4)
>>> L.polylog(-Integer(1))
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + 7*z^7 + O(z^8)
>>> z / (Integer(1)-z)**Integer(2)
z + 2*z^2 + 3*z^3 + 4*z^4 + 5*z^5 + 6*z^6 + 7*z^7 + O(z^8)
>>> L.polylog(-Integer(2))
z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + 49*z^7 + O(z^8)
>>> z * (Integer(1) + z) / (Integer(1) - z)**Integer(3)
z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + 49*z^7 + O(z^8)
```

We can compute the Eulerian numbers:

```
sage: [L.polylog(-n) * (1-z)^(n+1) for n in range(1, 6)]
[z + O(z^8),
 z + z^2 + O(z^8),
 z + 4*z^2 + z^3 + O(z^8),
 z + 11*z^2 + 11*z^3 + z^4 + O(z^8),
 z + 26*z^2 + 66*z^3 + 26*z^4 + z^5 + O(z^8)]
```

```
>>> from sage.all import *
>>> [L.polylog(-n) * (Integer(1)-z)**(n+Integer(1)) for n in range(Integer(1),
↪ Integer(6))]
[z + O(z^8),
 z + z^2 + O(z^8),
 z + 4*z^2 + z^3 + O(z^8),
 z + 11*z^2 + 11*z^3 + z^4 + O(z^8),
 z + 26*z^2 + 66*z^3 + 26*z^4 + z^5 + O(z^8)]
```

REFERENCES:

- [Wikipedia article Polylogarithm](#)

q_pochhammer ($q=None$)

Return the infinite q -Pochhammer symbol $(a; q)_{\infty}$, where a is the variable of `self`.

This is also one version of the quantum dilogarithm or the q -Exponential function.

INPUT:

- q – (default: $q \in \mathbf{Q}(q)$) the parameter q

EXAMPLES:

```
sage: q = ZZ['q'].fraction_field().gen()
sage: L.<z> = LazyLaurentSeriesRing(q.parent())
sage: qpoch = L.q_pochhammer(q)
sage: qpoch
1
+ (-1/(-q + 1))*z
+ (q/(q^3 - q^2 - q + 1))*z^2
+ (-q^3/(-q^6 + q^5 + q^4 - q^2 - q + 1))*z^3
+ (q^6/(q^10 - q^9 - q^8 + 2*q^5 - q^2 - q + 1))*z^4
+ (-q^10/(-q^15 + q^14 + q^13 - q^10 - q^9 - q^8 + q^7 + q^6 + q^5 - q^2 - q
↪ + 1))*z^5
+ (q^15/(q^21 - q^20 - q^19 + q^16 + 2*q^14 - q^12 - q^11 - q^10 - q^9 + 2*q^
↪ 7 + q^5 - q^2 - q + 1))*z^6
+ O(z^7)
```

```
>>> from sage.all import *
>>> q = ZZ['q'].fraction_field().gen()
>>> L = LazyLaurentSeriesRing(q.parent(), names=('z',)); (z,) = L._first_
↪ ngens(1)
>>> qpoch = L.q_pochhammer(q)
>>> qpoch
1
+ (-1/(-q + 1))*z
+ (q/(q^3 - q^2 - q + 1))*z^2
```

(continues on next page)

(continued from previous page)

```

+ (-q^3/(-q^6 + q^5 + q^4 - q^2 - q + 1))*z^3
+ (q^6/(q^10 - q^9 - q^8 + 2*q^5 - q^2 - q + 1))*z^4
+ (-q^10/(-q^15 + q^14 + q^13 - q^10 - q^9 - q^8 + q^7 + q^6 + q^5 - q^2 - q
↪ + 1))*z^5
+ (q^15/(q^21 - q^20 - q^19 + q^16 + 2*q^14 - q^12 - q^11 - q^10 - q^9 + 2*q^
↪ 7 + q^5 - q^2 - q + 1))*z^6
+ O(z^7)

```

We show that $(z; q)_n = \frac{(z; q)_\infty}{(q^n z; q)_\infty}$:

```

sage: qpoch / qpoch(q*z)
1 - z + O(z^7)
sage: qpoch / qpoch(q^2*z)
1 + (-q - 1)*z + q*z^2 + O(z^7)
sage: qpoch / qpoch(q^3*z)
1 + (-q^2 - q - 1)*z + (q^3 + q^2 + q)*z^2 - q^3*z^3 + O(z^7)
sage: qpoch / qpoch(q^4*z)
1 + (-q^3 - q^2 - q - 1)*z + (q^5 + q^4 + 2*q^3 + q^2 + q)*z^2
+ (-q^6 - q^5 - q^4 - q^3)*z^3 + q^6*z^4 + O(z^7)

```

```

>>> from sage.all import *
>>> qpoch / qpoch(q*z)
1 - z + O(z^7)
>>> qpoch / qpoch(q**Integer(2)*z)
1 + (-q - 1)*z + q*z^2 + O(z^7)
>>> qpoch / qpoch(q**Integer(3)*z)
1 + (-q^2 - q - 1)*z + (q^3 + q^2 + q)*z^2 - q^3*z^3 + O(z^7)
>>> qpoch / qpoch(q**Integer(4)*z)
1 + (-q^3 - q^2 - q - 1)*z + (q^5 + q^4 + 2*q^3 + q^2 + q)*z^2
+ (-q^6 - q^5 - q^4 - q^3)*z^3 + q^6*z^4 + O(z^7)

```

We can also construct part of Euler's function:

```

sage: M.<a> = LazyLaurentSeriesRing(QQ)
sage: phi = sum(qpoch[i](q=a)*a^i for i in range(10))
sage: phi[:20] == M.euler()[:20]
True

```

```

>>> from sage.all import *
>>> M = LazyLaurentSeriesRing(QQ, names=('a',)); (a,) = M._first_ngens(1)
>>> phi = sum(qpoch[i](q=a)*a**i for i in range(Integer(10)))
>>> phi[:Integer(20)] == M.euler()[:Integer(20)]
True

```

REFERENCES:

- [Wikipedia article Q-Pochhammer_symbol](#)
- [Wikipedia article Quantum_dilogarithm](#)
- [Wikipedia article Q-exponential](#)

residue_field()

Return the residue field of the ring of integers of `self`.

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(QQ, 'z')
sage: L.residue_field()
Rational Field
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, 'z')
>>> L.residue_field()
Rational Field
```

series (*coefficient*, *valuation*, *degree=None*, *constant=None*)

Return a lazy Laurent series.

INPUT:

- *coefficient* – Python function that computes coefficients or a list
- *valuation* – integer; approximate valuation of the series
- *degree* – (optional) integer
- *constant* – (optional) an element of the base ring

Let the coefficient of index i mean the coefficient of the term of the series with exponent i .

Python function `coefficient` returns the value of the coefficient of index i from input s and i where s is the series itself.

Let *valuation* be n . All coefficients of index below n are zero. If *constant* is not specified, then the *coefficient* function is responsible to compute the values of all coefficients of index $\geq n$. If *degree* or *constant* is a pair (c, m) , then the *coefficient* function is responsible to compute the values of all coefficients of index $\geq n$ and $< m$ and all the coefficients of index $\geq m$ is the constant c .

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: L.series(lambda s, i: i, 5, (1,10))
5*z^5 + 6*z^6 + 7*z^7 + 8*z^8 + 9*z^9 + z^10 + z^11 + z^12 + O(z^13)

sage: def g(s, i):
....:     if i < 0:
....:         return 1
....:     else:
....:         return s.coefficient(i - 1) + i
sage: e = L.series(g, -5); e
z^-5 + z^-4 + z^-3 + z^-2 + z^-1 + 1 + 2*z + O(z^2)
sage: f = e^-1; f
z^5 - z^6 - z^11 + O(z^12)
sage: f.coefficient(10)
0
sage: f.coefficient(20)
9
sage: f.coefficient(30)
-219
```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> L.series(lambda s, i: i, Integer(5), (Integer(1), Integer(10)))
5*z^5 + 6*z^6 + 7*z^7 + 8*z^8 + 9*z^9 + z^10 + z^11 + z^12 + O(z^13)

>>> def g(s, i):
...     if i < Integer(0):
...         return Integer(1)
...     else:
...         return s.coefficient(i - Integer(1)) + i
>>> e = L.series(g, -Integer(5)); e
z^-5 + z^-4 + z^-3 + z^-2 + z^-1 + 1 + 2*z + O(z^2)
>>> f = e**Integer(1); f
z^5 - z^6 - z^11 + O(z^12)
>>> f.coefficient(Integer(10))
0
>>> f.coefficient(Integer(20))
9
>>> f.coefficient(Integer(30))
-219

```

Alternatively, the `coefficient` can be a list of elements of the base ring. Then these elements are read as coefficients of the terms of degrees starting from the valuation. In this case, `constant` may be just an element of the base ring instead of a tuple or can be simply omitted if it is zero.

```

sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: f = L.series([1,2,3,4], -5); f
z^-5 + 2*z^-4 + 3*z^-3 + 4*z^-2
sage: g = L.series([1,3,5,7,9], 5, constant=-1); g
z^5 + 3*z^6 + 5*z^7 + 7*z^8 + 9*z^9 - z^10 - z^11 - z^12 + O(z^13)

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> f = L.series([Integer(1), Integer(2), Integer(3), Integer(4)], -Integer(5));
↪ f
z^-5 + 2*z^-4 + 3*z^-3 + 4*z^-2
>>> g = L.series([Integer(1), Integer(3), Integer(5), Integer(7), Integer(9)],
↪ Integer(5), constant=-Integer(1)); g
z^5 + 3*z^6 + 5*z^7 + 7*z^8 + 9*z^9 - z^10 - z^11 - z^12 + O(z^13)

```

some_elements()

Return a list of elements of `self`.

EXAMPLES:

```

sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: L.some_elements()[:7]
[0, 1, z,
 -3*z^-4 + z^-3 - 12*z^-2 - 2*z^-1 - 10 - 8*z + z^2 + z^3,
 z^-2 + z^3 + z^4 + z^5 + O(z^6),
 -2*z^-3 - 2*z^-2 + 4*z^-1 + 11 - z - 34*z^2 - 31*z^3 + O(z^4),
 4*z^-2 + z^-1 + z + 4*z^2 + 9*z^3 + 16*z^4 + O(z^5)]

```

(continues on next page)

(continued from previous page)

```

sage: L = LazyLaurentSeriesRing(GF(2), 'z')
sage: L.some_elements()[:7]
[0, 1, z,
 z^-4 + z^-3 + z^2 + z^3,
 z^-2,
 1 + z + z^3 + z^4 + z^6 + O(z^7),
 z^-1 + z + z^3 + O(z^5)]

sage: L = LazyLaurentSeriesRing(GF(3), 'z')
sage: L.some_elements()[:7]
[0, 1, z,
 z^-3 + z^-1 + 2 + z + z^2 + z^3,
 z^-2,
 z^-3 + z^-2 + z^-1 + 2 + 2*z + 2*z^2 + O(z^3),
 z^-2 + z^-1 + z + z^2 + z^4 + O(z^5)]

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> L.some_elements()[:Integer(7)]
[0, 1, z,
 -3*z^-4 + z^-3 - 12*z^-2 - 2*z^-1 - 10 - 8*z + z^2 + z^3,
 z^-2 + z^3 + z^4 + z^5 + O(z^6),
 -2*z^-3 - 2*z^-2 + 4*z^-1 + 11 - z - 34*z^2 - 31*z^3 + O(z^4),
 4*z^-2 + z^-1 + z + 4*z^2 + 9*z^3 + 16*z^4 + O(z^5)]

>>> L = LazyLaurentSeriesRing(GF(Integer(2)), 'z')
>>> L.some_elements()[:Integer(7)]
[0, 1, z,
 z^-4 + z^-3 + z^2 + z^3,
 z^-2,
 1 + z + z^3 + z^4 + z^6 + O(z^7),
 z^-1 + z + z^3 + O(z^5)]

>>> L = LazyLaurentSeriesRing(GF(Integer(3)), 'z')
>>> L.some_elements()[:Integer(7)]
[0, 1, z,
 z^-3 + z^-1 + 2 + z + z^2 + z^3,
 z^-2,
 z^-3 + z^-2 + z^-1 + 2 + 2*z + 2*z^2 + O(z^3),
 z^-2 + z^-1 + z + z^2 + z^4 + O(z^5)]

```

taylor(*f*)Return the Taylor expansion around 0 of the function *f*.

INPUT:

- *f* – a function such that one of the following works:
 - the substitution $f(z)$, where z is a generator of `self`
 - f is a function of a single variable with no poles at 0 and has a `derivative` method

EXAMPLES:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: x = SR.var('x')
sage: f(x) = (1 + x) / (1 - x^2)
sage: L.taylor(f)
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> x = SR.var('x')
>>> __tmp__=var("x"); f = symbolic_expression((Integer(1) + x) / (Integer(1) -
↪ x**Integer(2))).function(x)
>>> L.taylor(f)
1 + z + z^2 + z^3 + z^4 + z^5 + z^6 + O(z^7)
```

For inputs as symbolic functions/expressions, the function must not have any poles at 0:

```
sage: f(x) = (1 + x^2) / sin(x^2)
sage: L.taylor(f)
<repr(...) failed: ValueError: power::eval(): division by zero>
sage: def g(a): return (1 + a^2) / sin(a^2)
sage: L.taylor(g)
z^-2 + 1 + 1/6*z^2 + 1/6*z^4 + O(z^5)
```

```
>>> from sage.all import *
>>> __tmp__=var("x"); f = symbolic_expression((Integer(1) + x**Integer(2)) /
↪ sin(x**Integer(2))).function(x)
>>> L.taylor(f)
<repr(...) failed: ValueError: power::eval(): division by zero>
>>> def g(a): return (Integer(1) + a**Integer(2)) / sin(a**Integer(2))
>>> L.taylor(g)
z^-2 + 1 + 1/6*z^2 + 1/6*z^4 + O(z^5)
```

uniformizer()

Return a uniformizer of self..

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(QQ, 'z')
sage: L.uniformizer()
z
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, 'z')
>>> L.uniformizer()
z
```

```
class sage.rings.lazy_series_ring.LazyPowerSeriesRing(base_ring, names, sparse=True,
                                                         category=None)
```

Bases: *LazySeriesRing*

The ring of (possibly multivariate) lazy Taylor series.

INPUT:

- *base_ring* – base ring of this Taylor series ring

- `names` – name(s) of the generator of this Taylor series ring
- `sparse` – boolean (default: `True`); whether this series is sparse or not

EXAMPLES:

```
sage: LazyPowerSeriesRing(ZZ, 't')
Lazy Taylor Series Ring in t over Integer Ring

sage: L.<x, y> = LazyPowerSeriesRing(QQ); L
Multivariate Lazy Taylor Series Ring in x, y over Rational Field
```

```
>>> from sage.all import *
>>> LazyPowerSeriesRing(ZZ, 't')
Lazy Taylor Series Ring in t over Integer Ring

>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y')); (x, y) = L._first_ngens(2); L
Multivariate Lazy Taylor Series Ring in x, y over Rational Field
```

Element

alias of *LazyPowerSeries*

construction()

Return a pair (F, R) , where F is a CompletionFunctor and R is a ring, such that $F(R)$ returns `self`.

EXAMPLES:

```
sage: L = LazyPowerSeriesRing(ZZ, 't')
sage: L.construction()
(Completion[t, prec=+Infinity],
 Sparse Univariate Polynomial Ring in t over Integer Ring)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, 't')
>>> L.construction()
(Completion[t, prec=+Infinity],
 Sparse Univariate Polynomial Ring in t over Integer Ring)
```

fraction_field()

Return the fraction field of `self`.

If this is with a single variable over a field, then the fraction field is the field of (lazy) formal Laurent series.

Todo

Implement other fraction fields.

EXAMPLES:

```
sage: L.<x> = LazyPowerSeriesRing(QQ)
sage: L.fraction_field()
Lazy Laurent Series Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x',)); (x,) = L._first_ngens(1)
>>> L.fraction_field()
Lazy Laurent Series Ring in x over Rational Field
```

gen ($n=0$)

Return the n -th generator of self.

EXAMPLES:

```
sage: L = LazyPowerSeriesRing(ZZ, 'z')
sage: L.gen()
z
sage: L.gen(3)
Traceback (most recent call last):
...
IndexError: there is only one generator
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, 'z')
>>> L.gen()
z
>>> L.gen(Integer(3))
Traceback (most recent call last):
...
IndexError: there is only one generator
```

gens ()

Return the generators of self.

EXAMPLES:

```
sage: L = LazyPowerSeriesRing(ZZ, 'x,y')
sage: L.gens()
(x, y)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, 'x,y')
>>> L.gens()
(x, y)
```

ngens ()

Return the number of generators of self.

EXAMPLES:

```
sage: L.<z> = LazyPowerSeriesRing(ZZ)
sage: L.ngens()
1
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, names=('z',)); (z,) = L._first_ngens(1)
>>> L.ngens()
1
```

residue_field()

Return the residue field of the ring of integers of `self`.

EXAMPLES:

```
sage: L = LazyPowerSeriesRing(QQ, 'x')
sage: L.residue_field()
Rational Field
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, 'x')
>>> L.residue_field()
Rational Field
```

some_elements()

Return a list of elements of `self`.

EXAMPLES:

```
sage: L = LazyPowerSeriesRing(ZZ, 'z')
sage: L.some_elements()[:6]
[0, 1, z + z^2 + z^3 + O(z^4),
 -12 - 8*z + z^2 + z^3,
 1 + z - 2*z^2 - 7*z^3 - z^4 + 20*z^5 + 23*z^6 + O(z^7),
 z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + O(z^7)]
```

```
sage: L = LazyPowerSeriesRing(GF(3) ["q"], 'z')
sage: L.some_elements()[:6]
[0, 1, z + q*z^2 + q*z^3 + q*z^4 + O(z^5),
 z + z^2 + z^3,
 1 + z + z^2 + 2*z^3 + 2*z^4 + 2*z^5 + O(z^6),
 z + z^2 + z^4 + z^5 + O(z^7)]
```

```
sage: L = LazyPowerSeriesRing(GF(3), 'q, t')
sage: L.some_elements()[:6]
[0, 1, q,
 q + q^2 + q^3,
 1 + q + q^2 - q^3 - q^4 - q^5 - q^6 + O(q,t)^7,
 1 + (q+t) + (q^2-q*t+t^2) + (q^3+t^3) + (q^4+q^3*t+q*t^3+t^4)
 + (q^5-q^4*t+q^3*t^2+q^2*t^3-q*t^4+t^5) + (q^6-q^3*t^3+t^6) + O(q,t)^7]
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(ZZ, 'z')
>>> L.some_elements()[:Integer(6)]
[0, 1, z + z^2 + z^3 + O(z^4),
 -12 - 8*z + z^2 + z^3,
 1 + z - 2*z^2 - 7*z^3 - z^4 + 20*z^5 + 23*z^6 + O(z^7),
 z + 4*z^2 + 9*z^3 + 16*z^4 + 25*z^5 + 36*z^6 + O(z^7)]

>>> L = LazyPowerSeriesRing(GF(Integer(3)) ["q"], 'z')
>>> L.some_elements()[:Integer(6)]
[0, 1, z + q*z^2 + q*z^3 + q*z^4 + O(z^5),
 z + z^2 + z^3,
 1 + z + z^2 + 2*z^3 + 2*z^4 + 2*z^5 + O(z^6),
```

(continues on next page)

(continued from previous page)

```

z + z^2 + z^4 + z^5 + O(z^7)]

>>> L = LazyPowerSeriesRing(GF(Integer(3)), 'q, t')
>>> L.some_elements():Integer(6)]
[0, 1, q,
 q + q^2 + q^3,
 1 + q + q^2 - q^3 - q^4 - q^5 - q^6 + O(q,t)^7,
 1 + (q+t) + (q^2-q*t+t^2) + (q^3+t^3) + (q^4+q^3*t+q*t^3+t^4)
 + (q^5-q^4*t+q^3*t^2+q^2*t^3-q*t^4+t^5) + (q^6-q^3*t^3+t^6) + O(q,t)^7]

```

taylor(*f*)Return the Taylor expansion around 0 of the function *f*.

INPUT:

- *f* – a function such that one of the following works:
 - the substitution $f(z_1, \dots, z_n)$, where $(z_1, \dots, z_n)$ are the generators of *self*
 - *f* is a function with no poles at 0 and has a `derivative` method

Warning

For inputs as symbolic functions/expressions, this does not check that the function does not have poles at 0.

EXAMPLES:

```

sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: x = SR.var('x')
sage: f(x) = (1 + x) / (1 - x^3)
sage: L.taylor(f)
1 + z + z^3 + z^4 + z^6 + O(z^7)
sage: (1 + z) / (1 - z^3)
1 + z + z^3 + z^4 + z^6 + O(z^7)
sage: f(x) = cos(x + pi/2)
sage: L.taylor(f)
-z + 1/6*z^3 - 1/120*z^5 + O(z^7)

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> x = SR.var('x')
>>> __tmp__=var("x"); f = symbolic_expression((Integer(1) + x) / (Integer(1) -
↪ x**Integer(3))).function(x)
>>> L.taylor(f)
1 + z + z^3 + z^4 + z^6 + O(z^7)
>>> (Integer(1) + z) / (Integer(1) - z**Integer(3))
1 + z + z^3 + z^4 + z^6 + O(z^7)
>>> __tmp__=var("x"); f = symbolic_expression(cos(x + pi/Integer(2))).
↪function(x)
>>> L.taylor(f)
-z + 1/6*z^3 - 1/120*z^5 + O(z^7)

```

For inputs as symbolic functions/expressions, the function must not have any poles at 0:


```
sage: L.<z> = LazyPowerSeriesRing(QQ, sparse=True)
sage: f = 1 / sin(x)
sage: L.taylor(f)
<repr(...) failed: ValueError: power::eval(): division by zero>
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, sparse=True, names=('z',)); (z,) = L._first_
↳ngens(1)
>>> f = Integer(1) / sin(x)
>>> L.taylor(f)
<repr(...) failed: ValueError: power::eval(): division by zero>
```

Different multivariate inputs:

```
sage: L.<a,b> = LazyPowerSeriesRing(QQ)
sage: def f(x, y): return (1 + x) / (1 + y)
sage: L.taylor(f)
1 + (a-b) - (a*b-b^2) + (a*b^2-b^3) - (a*b^3-b^4) + (a*b^4-b^5) - (a*b^5-b^6) ↵
↳+ O(a,b)^7
sage: g(w, z) = (1 + w) / (1 + z)
sage: L.taylor(g)
1 + (a-b) - (a*b-b^2) + (a*b^2-b^3) - (a*b^3-b^4) + (a*b^4-b^5) - (a*b^5-b^6) ↵
↳+ O(a,b)^7
sage: y = SR.var('y')
sage: h = (1 + x) / (1 + y)
sage: L.taylor(h)
1 + (a-b) - (a*b-b^2) + (a*b^2-b^3) - (a*b^3-b^4) + (a*b^4-b^5) - (a*b^5-b^6) ↵
↳+ O(a,b)^7
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('a', 'b',)); (a, b,) = L._first_
↳ngens(2)
>>> def f(x, y): return (Integer(1) + x) / (Integer(1) + y)
>>> L.taylor(f)
1 + (a-b) - (a*b-b^2) + (a*b^2-b^3) - (a*b^3-b^4) + (a*b^4-b^5) - (a*b^5-b^6) ↵
↳+ O(a,b)^7
>>> __tmp__=var("w,z"); g = symbolic_expression((Integer(1) + w) / ↵
↳(Integer(1) + z)).function(w,z)
>>> L.taylor(g)
1 + (a-b) - (a*b-b^2) + (a*b^2-b^3) - (a*b^3-b^4) + (a*b^4-b^5) - (a*b^5-b^6) ↵
↳+ O(a,b)^7
>>> y = SR.var('y')
>>> h = (Integer(1) + x) / (Integer(1) + y)
>>> L.taylor(h)
1 + (a-b) - (a*b-b^2) + (a*b^2-b^3) - (a*b^3-b^4) + (a*b^4-b^5) - (a*b^5-b^6) ↵
↳+ O(a,b)^7
```

uniformizer()

Return a uniformizer of `self`.

EXAMPLES:

```
sage: L = LazyPowerSeriesRing(QQ, 'x')
sage: L.uniformizer()
x
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, 'x')
>>> L.uniformizer()
x
```

class sage.rings.lazy_series_ring.**LazySeriesRing**

Bases: UniqueRepresentation, Parent

Abstract base class for lazy series.

characteristic()

Return the characteristic of this lazy power series ring, which is the same as the characteristic of its base ring.

EXAMPLES:

```
sage: L.<t> = LazyLaurentSeriesRing(ZZ)
sage: L.characteristic()
0

sage: R.<w> = LazyLaurentSeriesRing(GF(11)); R
Lazy Laurent Series Ring in w over Finite Field of size 11
sage: R.characteristic()
11

sage: R.<x, y> = LazyPowerSeriesRing(GF(7)); R
Multivariate Lazy Taylor Series Ring in x, y over Finite Field of size 7
sage: R.characteristic()
7

sage: L = LazyDirichletSeriesRing(ZZ, "s")
sage: L.characteristic()
0
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, names=('t',)); (t,) = L._first_ngens(1)
>>> L.characteristic()
0

>>> R = LazyLaurentSeriesRing(GF(Integer(11)), names=('w',)); (w,) = R._first_
↳ngens(1); R
Lazy Laurent Series Ring in w over Finite Field of size 11
>>> R.characteristic()
11

>>> R = LazyPowerSeriesRing(GF(Integer(7)), names=('x', 'y',)); (x, y,) = R._
↳first_ngens(2); R
Multivariate Lazy Taylor Series Ring in x, y over Finite Field of size 7
>>> R.characteristic()
7
```

(continues on next page)

(continued from previous page)

```
>>> L = LazyDirichletSeriesRing(ZZ, "s")
>>> L.characteristic()
0
```

define_implicitly(*series, equations, max_lookahead=1*)

Define series by solving functional equations.

INPUT:

- *series* – list of undefined series or pairs each consisting of a series and its initial values
- *equations* – list of equations defining the series
- *max_lookahead*– (default: 1); a positive integer specifying how many elements beyond the currently known (i.e., approximate) order of each equation to extract linear equations from

EXAMPLES:

```
sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: f = L.undefined(0)
sage: F = diff(f, 2)
sage: L.define_implicitly([(f, [1, 0])], [F + f])
sage: f
1 - 1/2*z^2 + 1/24*z^4 - 1/720*z^6 + O(z^7)
sage: cos(z)
1 - 1/2*z^2 + 1/24*z^4 - 1/720*z^6 + O(z^7)
sage: F
-1 + 1/2*z^2 - 1/24*z^4 + 1/720*z^6 + O(z^7)

sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: f = L.undefined(0)
sage: L.define_implicitly([f], [2*z*f(z^3) + z*f^3 - 3*f + 3])
sage: f
1 + z + z^2 + 2*z^3 + 5*z^4 + 11*z^5 + 28*z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L.undefined(Integer(0))
>>> F = diff(f, Integer(2))
>>> L.define_implicitly([(f, [Integer(1), Integer(0)])], [F + f])
>>> f
1 - 1/2*z^2 + 1/24*z^4 - 1/720*z^6 + O(z^7)
>>> cos(z)
1 - 1/2*z^2 + 1/24*z^4 - 1/720*z^6 + O(z^7)
>>> F
-1 + 1/2*z^2 - 1/24*z^4 + 1/720*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L.undefined(Integer(0))
>>> L.define_implicitly([f], [Integer(2)*z*f(z**Integer(3)) + z*f**Integer(3) -
↳ Integer(3)*f + Integer(3)])
>>> f
1 + z + z^2 + 2*z^3 + 5*z^4 + 11*z^5 + 28*z^6 + O(z^7)
```

From Exercise 6.63b in [EnumComb2]:

```
sage: g = L.undefined()
sage: z1 = z*diff(g, z)
sage: z2 = z1 + z^2 * diff(g, z, 2)
sage: z3 = z1 + 3 * z^2 * diff(g, z, 2) + z^3 * diff(g, z, 3)
sage: e1 = g^2 * z3 - 15*g*z1*z2 + 30*z1^3
sage: e2 = g * z2 - 3 * z1^2
sage: e3 = g * z2 - 3 * z1^2
sage: e = e1^2 + 32 * e2^3 - g^10 * e3^2
sage: L.define_implicitly([(g, [1, 2])], [e])

sage: sol = L(lambda n: 1 if not n else (2 if is_square(n) else 0)); sol
1 + 2*z + 2*z^4 + O(z^7)
sage: all(g[i] == sol[i] for i in range(50))
True
```

```
>>> from sage.all import *
>>> g = L.undefined()
>>> z1 = z*diff(g, z)
>>> z2 = z1 + z**Integer(2) * diff(g, z, Integer(2))
>>> z3 = z1 + Integer(3) * z**Integer(2) * diff(g, z, Integer(2)) +
↳ z**Integer(3) * diff(g, z, Integer(3))
>>> e1 = g**Integer(2) * z3 - Integer(15)*g*z1*z2 + Integer(30)*z1**Integer(3)
>>> e2 = g * z2 - Integer(3) * z1**Integer(2)
>>> e3 = g * z2 - Integer(3) * z1**Integer(2)
>>> e = e1**Integer(2) + Integer(32) * e2**Integer(3) - g**Integer(10) *
↳ e3**Integer(2)
>>> L.define_implicitly([(g, [Integer(1), Integer(2)])], [e])

>>> sol = L(lambda n: Integer(1) if not n else (Integer(2) if is_square(n)
↳ else Integer(0))); sol
1 + 2*z + 2*z^4 + O(z^7)
>>> all(g[i] == sol[i] for i in range(Integer(50)))
True
```

Some more examples over different rings:

```
sage: # needs sage.symbolic
sage: L.<z> = LazyPowerSeriesRing(SR)
sage: G = L.undefined(0)
sage: L.define_implicitly([(G, [ln(2)])], [diff(G) - exp(-G(-z))])
sage: G
log(2) + z + 1/2*z^2 + (-1/12*z^4) + 1/45*z^6 + O(z^7)

sage: L.<z> = LazyPowerSeriesRing(RR)
sage: G = L.undefined(0)
sage: L.define_implicitly([(G, [log(2)])], [diff(G) - exp(-G(-z))])
sage: G
0.693147180559945 + 1.000000000000000*z + 0.500000000000000*z^2
- 0.0833333333333333*z^4 + 0.0222222222222222*z^6 + O(1.000000000000000*z^7)
```

```
>>> from sage.all import *
```

(continues on next page)

(continued from previous page)

```

>>> # needs sage.symbolic
>>> L = LazyPowerSeriesRing(SR, names=('z',)); (z,) = L._first_ngens(1)
>>> G = L.undefined(Integer(0))
>>> L.define_implicitly([(G, [ln(Integer(2))])], [diff(G) - exp(-G(-z))])
>>> G
log(2) + z + 1/2*z^2 + (-1/12*z^4) + 1/45*z^6 + O(z^7)

>>> L = LazyPowerSeriesRing(RR, names=('z',)); (z,) = L._first_ngens(1)
>>> G = L.undefined(Integer(0))
>>> L.define_implicitly([(G, [log(Integer(2))])], [diff(G) - exp(-G(-z))])
>>> G
0.693147180559945 + 1.0000000000000000*z + 0.5000000000000000*z^2
- 0.08333333333333333*z^4 + 0.02222222222222222*z^6 + O(1.0000000000000000*z^7)

```

We solve the recurrence relation in (3.12) of Prellberg and Brak doi:10.1007/BF02183685:

```

sage: q, y = QQ['q,y'].fraction_field().gens()
sage: L.<x> = LazyPowerSeriesRing(q.parent())
sage: R = L.undefined()
sage: L.define_implicitly([(R, [0])], [(1-q*x)*R - (y*q*x+y)*R(q*x) -
↪ q*x*R*R(q*x) - x*y*q])
sage: R[0]
0
sage: R[1]
(-q*y)/(q*y - 1)
sage: R[2]
(q^3*y^2 + q^2*y)/(q^3*y^2 - q^2*y - q*y + 1)
sage: R[3].factor()
(-1) * y * q^3 * (q*y - 1)^-2 * (q^2*y - 1)^-1 * (q^3*y - 1)^-1
* (q^4*y^3 + q^3*y^2 + q^2*y^2 - q^2*y - q*y - 1)

sage: Rp = L.undefined(1)
sage: L.define_implicitly([Rp], [(y*q*x+y)*Rp(q*x) + q*x*Rp*Rp(q*x) + x*y*q -
↪ (1-q*x)*Rp])
sage: all(R[n] == Rp[n] for n in range(7))
True

```

```

>>> from sage.all import *
>>> q, y = QQ['q,y'].fraction_field().gens()
>>> L = LazyPowerSeriesRing(q.parent(), names=('x',)); (x,) = L._first_
↪ ngens(1)
>>> R = L.undefined()
>>> L.define_implicitly([(R, [Integer(0)])], [(Integer(1)-q*x)*R -
↪ (y*q*x+y)*R(q*x) - q*x*R*R(q*x) - x*y*q])
>>> R[Integer(0)]
0
>>> R[Integer(1)]
(-q*y)/(q*y - 1)
>>> R[Integer(2)]
(q^3*y^2 + q^2*y)/(q^3*y^2 - q^2*y - q*y + 1)
>>> R[Integer(3)].factor()
(-1) * y * q^3 * (q*y - 1)^-2 * (q^2*y - 1)^-1 * (q^3*y - 1)^-1

```

(continues on next page)

(continued from previous page)

```

* (q^4*y^3 + q^3*y^2 + q^2*y^2 - q^2*y - q*y - 1)

>>> Rp = L.undefined(Integer(1))
>>> L.define_implicitly([Rp], [(y*q*x+y)*Rp(q*x) + q*x*Rp*Rp(q*x) + x*y*q -
↳ (Integer(1)-q*x)*Rp])
>>> all(R[n] == Rp[n] for n in range(Integer(7)))
True

```

Another example:

```

sage: L.<z> = LazyPowerSeriesRing(QQ["x,y,f1,f2"].fraction_field())
sage: L.base_ring().inject_variables()
Defining x, y, f1, f2
sage: F = L.undefined()
sage: L.define_implicitly([(F, [0, f1, f2])], [F(2*z) -
↳ (1+exp(x*z)+exp(y*z))*F - exp((x+y)*z)*F(-z)])
sage: F
f1*z + f2*z^2 + ((-1/6*x*y*f1+1/3*x*f2+1/3*y*f2)*z^3)
+ ((-1/24*x^2*y*f1-1/24*x*y^2*f1+1/12*x^2*f2+1/12*x*y*f2+1/12*y^2*f2)*z^4)
+ ... + O(z^8)
sage: sol = 1/(x-y)*((2*f2-y*f1)*(exp(x*z)-1)/x - (2*f2-x*f1)*(exp(y*z)-1)/y)
sage: F - sol
O(z^7)

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ["x,y,f1,f2"].fraction_field(), names=('z',));
↳ (z,) = L._first_ngens(1)
>>> L.base_ring().inject_variables()
Defining x, y, f1, f2
>>> F = L.undefined()
>>> L.define_implicitly([(F, [Integer(0), f1, f2])], [F(Integer(2)*z) -
↳ (Integer(1)+exp(x*z)+exp(y*z))*F - exp((x+y)*z)*F(-z)])
>>> F
f1*z + f2*z^2 + ((-1/6*x*y*f1+1/3*x*f2+1/3*y*f2)*z^3)
+ ((-1/24*x^2*y*f1-1/24*x*y^2*f1+1/12*x^2*f2+1/12*x*y*f2+1/12*y^2*f2)*z^4)
+ ... + O(z^8)
>>> sol = Integer(1)/(x-y)*((Integer(2)*f2-y*f1)*(exp(x*z)-Integer(1))/x -
↳ (Integer(2)*f2-x*f1)*(exp(y*z)-Integer(1))/y)
>>> F - sol
O(z^7)

```

We need to specify the initial values for the degree 1 and 2 components to get a unique solution in the previous example:

```

sage: L.<z> = LazyPowerSeriesRing(QQ['x','y','f1'].fraction_field())
sage: L.base_ring().inject_variables()
Defining x, y, f1
sage: F = L.undefined()
sage: L.define_implicitly([F], [F(2*z) - (1+exp(x*z)+exp(y*z))*F -
↳ exp((x+y)*z)*F(-z)])
sage: F
<repr(...) failed: ValueError: could not determine any coefficients:

```

(continues on next page)

(continued from previous page)

```
coefficient [3]: 6*series[3] + (-2*x - 2*y)*series[2] + (x*y)*series[1]
↳ == 0>
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ['x', 'y', 'f1'].fraction_field(), names=('z',));
↳ (z,) = L._first_ngens(1)
>>> L.base_ring().inject_variables()
Defining x, y, f1
>>> F = L.undefined()
>>> L.define_implicitly([F], [F(Integer(2)*z) -
↳ (Integer(1)+exp(x*z)+exp(y*z))*F - exp((x+y)*z)*F(-z)])
>>> F
<repr(...) failed: ValueError: could not determine any coefficients:
coefficient [3]: 6*series[3] + (-2*x - 2*y)*series[2] + (x*y)*series[1]
↳ == 0>
```

Let us now try to only specify the degree 0 and degree 1 components. We will see that this is still not enough to remove the ambiguity, so an error is raised. However, we will see that the dependence on `series[1]` disappears. The equation which has no unique solution is now $6*\text{series}[3] + (-2*x - 2*y)*\text{series}[2] + (x*y*f1) == 0$:

```
sage: F = L.undefined()
sage: L.define_implicitly([(F, [0, f1])], [F(2*z) - (1+exp(x*z)+exp(y*z))*F -
↳ exp((x+y)*z)*F(-z)])
sage: F
<repr(...) failed: ValueError: could not determine any coefficients:
coefficient [3]: ... == 0>
```

```
>>> from sage.all import *
>>> F = L.undefined()
>>> L.define_implicitly([(F, [Integer(0), f1])], [F(Integer(2)*z) -
↳ (Integer(1)+exp(x*z)+exp(y*z))*F - exp((x+y)*z)*F(-z)])
>>> F
<repr(...) failed: ValueError: could not determine any coefficients:
coefficient [3]: ... == 0>
```

(Note that the order of summands of the equation in the error message is not deterministic.)

Laurent series examples:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: f = L.undefined(-1)
sage: L.define_implicitly([(f, [5])], [2+z*f(z^2) - f])
sage: f
5*z^-1 + 2 + 2*z + 2*z^3 + O(z^6)
sage: 2 + z*f(z^2) - f
O(z^6)

sage: g = L.undefined(-2)
sage: L.define_implicitly([(g, [5])], [2+z*g(z^2) - g])
sage: g
<repr(...) failed: ValueError: no solution as the coefficient in degree -3 of
↳ the equation is 5 != 0>
```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L.undefine(Integer(1))
>>> L.define_implicitly([(f, [Integer(5)])], [Integer(2)+z*f(z**Integer(2)) -
↳ f])
>>> f
5*z^-1 + 2 + 2*z + 2*z^3 + O(z^6)
>>> Integer(2) + z*f(z**Integer(2)) - f
O(z^6)

>>> g = L.undefine(Integer(2))
>>> L.define_implicitly([(g, [Integer(5)])], [Integer(2)+z*g(z**Integer(2)) -
↳ g])
>>> g
<repr(...) failed: ValueError: no solution as the coefficient in degree -3 of
↳ the equation is 5 != 0>

```

A bivariate example:

```

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: B = L.undefine()
sage: eq = y*B^2 + 1 - B(x, x-y)
sage: L.define_implicitly([B], [eq])
sage: B
1 + (x-y) + (2*x*y-2*y^2) + (4*x^2*y-7*x*y^2+3*y^3)
+ (2*x^3*y+6*x^2*y^2-18*x*y^3+10*y^4)
+ (30*x^3*y^2-78*x^2*y^3+66*x*y^4-18*y^5)
+ (28*x^4*y^2-12*x^3*y^3-128*x^2*y^4+180*x*y^5-68*y^6) + O(x,y)^7

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y,) = L._first_
↳ ngens(2)
>>> B = L.undefine()
>>> eq = y*B**Integer(2) + Integer(1) - B(x, x-y)
>>> L.define_implicitly([B], [eq])
>>> B
1 + (x-y) + (2*x*y-2*y^2) + (4*x^2*y-7*x*y^2+3*y^3)
+ (2*x^3*y+6*x^2*y^2-18*x*y^3+10*y^4)
+ (30*x^3*y^2-78*x^2*y^3+66*x*y^4-18*y^5)
+ (28*x^4*y^2-12*x^3*y^3-128*x^2*y^4+180*x*y^5-68*y^6) + O(x,y)^7

```

Knödel walks:

```

sage: L.<z, x> = LazyPowerSeriesRing(QQ)
sage: F = L.undefine()
sage: eq = F(z, x)*(x^2*z-x+z) - (z - x*z^2 - x^2*z^2)*F(z, 0) + x
sage: L.define_implicitly([F], [eq])
sage: F
1 + (2*z^2+z*x) + (z^3+z^2*x) + (5*z^4+3*z^3*x+z^2*x^2)
+ (5*z^5+4*z^4*x+z^3*x^2) + (15*z^6+10*z^5*x+4*z^4*x^2+z^3*x^3)
+ O(z,x)^7

```



```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z', 'x',)); (z, x) = L._first_
↳ngens(2)
>>> F = L.undefined()
>>> eq = F(z, x)*(x**Integer(2)*z-x+z) - (z - x*z**Integer(2) -
↳x**Integer(2)*z**Integer(2))*F(z, Integer(0)) + x
>>> L.define_implicitly([F], [eq])
>>> F
1 + (2*z^2+z*x) + (z^3+z^2*x) + (5*z^4+3*z^3*x+z^2*x^2)
+ (5*z^5+4*z^4*x+z^3*x^2) + (15*z^6+10*z^5*x+4*z^4*x^2+z^3*x^3)
+ O(z, x)^7

```

Bicolored rooted trees with black and white roots:

```

sage: L.<x, y> = LazyPowerSeriesRing(QQ)
sage: A = L.undefined()
sage: B = L.undefined()
sage: L.define_implicitly([A, B], [A - x*exp(B), B - y*exp(A)])
sage: A
x + x*y + (x^2*y+1/2*x*y^2) + (1/2*x^3*y+2*x^2*y^2+1/6*x*y^3)
+ (1/6*x^4*y+3*x^3*y^2+2*x^2*y^3+1/24*x*y^4)
+ (1/24*x^5*y+8/3*x^4*y^2+27/4*x^3*y^3+4/3*x^2*y^4+1/120*x*y^5)
+ O(x, y)^7

sage: h = SymmetricFunctions(QQ).h()
sage: S = LazySymmetricFunctions(h)
sage: E = S(lambda n: h[n])
sage: T = LazySymmetricFunctions(tensor([h, h]))
sage: X = tensor([h[1], h[[]]])
sage: Y = tensor([h[[]], h[1]])
sage: A = T.undefined()
sage: B = T.undefined()
sage: T.define_implicitly([A, B], [A - X*E(B), B - Y*E(A)])
sage: A[:3]
[h[1] # h[], h[1] # h[1]]

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('x', 'y',)); (x, y) = L._first_
↳ngens(2)
>>> A = L.undefined()
>>> B = L.undefined()
>>> L.define_implicitly([A, B], [A - x*exp(B), B - y*exp(A)])
>>> A
x + x*y + (x^2*y+1/2*x*y^2) + (1/2*x^3*y+2*x^2*y^2+1/6*x*y^3)
+ (1/6*x^4*y+3*x^3*y^2+2*x^2*y^3+1/24*x*y^4)
+ (1/24*x^5*y+8/3*x^4*y^2+27/4*x^3*y^3+4/3*x^2*y^4+1/120*x*y^5)
+ O(x, y)^7

>>> h = SymmetricFunctions(QQ).h()
>>> S = LazySymmetricFunctions(h)
>>> E = S(lambda n: h[n])
>>> T = LazySymmetricFunctions(tensor([h, h]))
>>> X = tensor([h[Integer(1)], h[[]]])

```

(continues on next page)

(continued from previous page)

```

>>> Y = tensor([h[[]],h[Integer(1)]])
>>> A = T.undefine()
>>> B = T.undefine()
>>> T.define_implicitly([A, B], [A - X*E(B), B - Y*E(A)])
>>> A[:Integer(3)]
[h[1] # h[], h[1] # h[1]]

```

Permutations with two kinds of labels such that each cycle contains at least one element of each kind (defined implicitly to have a test):

```

sage: p = SymmetricFunctions(QQ).p()
sage: S = LazySymmetricFunctions(p)
sage: P = S(lambda n: sum(p[la] for la in Partitions(n)))
sage: T = LazySymmetricFunctions(tensor([p, p]))
sage: X = tensor([p[1],p[[]]])
sage: Y = tensor([p[[]],p[1]])
sage: A = T.undefine()
sage: T.define_implicitly([A], [P(X)*P(Y)*A - P(X+Y)])
sage: A[:4]
[p[] # p[], 0, p[1] # p[1], p[1] # p[1, 1] + p[1, 1] # p[1]]

```

```

>>> from sage.all import *
>>> p = SymmetricFunctions(QQ).p()
>>> S = LazySymmetricFunctions(p)
>>> P = S(lambda n: sum(p[la] for la in Partitions(n)))
>>> T = LazySymmetricFunctions(tensor([p, p]))
>>> X = tensor([p[Integer(1)],p[[]]])
>>> Y = tensor([p[[]],p[Integer(1)]])
>>> A = T.undefine()
>>> T.define_implicitly([A], [P(X)*P(Y)*A - P(X+Y)])
>>> A[:Integer(4)]
[p[] # p[], 0, p[1] # p[1], p[1] # p[1, 1] + p[1, 1] # p[1]]

```

The Frobenius character of labelled Dyck words:

```

sage: h = SymmetricFunctions(QQ).h()
sage: L.<t, u> = LazyPowerSeriesRing(h.fraction_field())
sage: D = L.undefine()
sage: s1 = L.sum(lambda n: h[n]*t^(n+1)*u^(n-1), 1)
sage: L.define_implicitly([D], [u*D - u - u*s1*D - t*(D - D(t, 0))])
sage: D
h[] + h[1]*t^2 + ((h[1,1]+h[2])*t^4+h[2]*t^3*u)
+ ((h[1,1,1]+3*h[2,1]+h[3])*t^6+(2*h[2,1]+h[3])*t^5*u+h[3]*t^4*u^2)
+ O(t,u)^7

```

```

>>> from sage.all import *
>>> h = SymmetricFunctions(QQ).h()
>>> L = LazyPowerSeriesRing(h.fraction_field(), names=('t', 'u')); (t, u) = L
↳ L._first_ngens(2)
>>> D = L.undefine()
>>> s1 = L.sum(lambda n: h[n]*t**(n+Integer(1))*u**(n-Integer(1)), Integer(1))
>>> L.define_implicitly([D], [u*D - u - u*s1*D - t*(D - D(t, Integer(0)))]])

```

(continues on next page)

(continued from previous page)

```
>>> D
h[] + h[1]*t^2 + ((h[1,1]+h[2])*t^4+h[2]*t^3*u)
+ ((h[1,1,1]+3*h[2,1]+h[3])*t^6+(2*h[2,1]+h[3])*t^5*u+h[3]*t^4*u^2)
+ O(t,u)^7
```

is_exact()

Return if self is exact or not.

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: L.is_exact()
True
sage: L = LazyLaurentSeriesRing(RR, 'z')
sage: L.is_exact()
False
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> L.is_exact()
True
>>> L = LazyLaurentSeriesRing(RR, 'z')
>>> L.is_exact()
False
```

is_sparse()

Return whether self is sparse or not.

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(ZZ, 'z', sparse=False)
sage: L.is_sparse()
False

sage: L = LazyLaurentSeriesRing(ZZ, 'z', sparse=True)
sage: L.is_sparse()
True
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z', sparse=False)
>>> L.is_sparse()
False

>>> L = LazyLaurentSeriesRing(ZZ, 'z', sparse=True)
>>> L.is_sparse()
True
```

one()

Return the constant series 1.

EXAMPLES:

```

sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: L.one()
1

sage: L = LazyPowerSeriesRing(ZZ, 'z')
sage: L.one()
1

sage: m = SymmetricFunctions(ZZ).m() #_
↪needs sage.modules
sage: L = LazySymmetricFunctions(m) #_
↪needs sage.modules
sage: L.one() #_
↪needs sage.modules
m[]

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> L.one()
1

>>> L = LazyPowerSeriesRing(ZZ, 'z')
>>> L.one()
1

>>> m = SymmetricFunctions(ZZ).m() #_
↪needs sage.modules
>>> L = LazySymmetricFunctions(m) #_
↪needs sage.modules
>>> L.one() #_
↪needs sage.modules
m[]

```

**options = Current options for lazy series rings - constant_length: 3 -
display_length: 7 - halting_precision: None - secure: False**

prod(*f*, *a*=None, *b*=+Infinity, *add_one*=False)

The product of elements of *self*.

INPUT:

- *f* – list (or iterable) of elements of *self*
- *a*, *b* – optional arguments
- *add_one* – (default: False) if True, then converts a lazy series p_i from *args* into $1 + p_i$ for the product

If *a* and *b* are both integers, then this returns the product $\prod_{i=a}^b f(i)$, where $f(i) = p_i$ if *add_one*=False or $f(i) = 1 + p_i$ otherwise. If *b* is not specified, then we consider $b = \infty$. Note this corresponds to the Python `range(a, b+1)`.

If *a* is any other iterable, then this returns the product $\prod_{i \in a} f(i)$, where $f(i) = p_i$ if *add_one*=False or $f(i) = 1 + p_i$.

Note

For infinite products, it is faster to use `add_one=True` since the implementation is based on p_i in $\prod_i (1 + p_i)$.

Warning

When f is an infinite generator, then the first argument `a` must be `True`. Otherwise this will loop forever.

Warning

For an *infinite* product of the form $\prod_i (1 + p_i)$, if $p_i = 0$, then this will loop forever.

EXAMPLES:

```
sage: L.<t> = LazyLaurentSeriesRing(QQ)
sage: euler = L.prod(lambda n: 1 - t^n, PositiveIntegers())
sage: euler
1 - t - t^2 + t^5 + O(t^7)
sage: 1 / euler
1 + t + 2*t^2 + 3*t^3 + 5*t^4 + 7*t^5 + 11*t^6 + O(t^7)
sage: euler - L.euler()
O(t^7)
sage: L.prod(lambda n: -t^n, 1, add_one=True)
1 - t - t^2 + t^5 + O(t^7)

sage: L.prod((1 - t^n for n in PositiveIntegers()), True)
1 - t - t^2 + t^5 + O(t^7)
sage: L.prod((-t^n for n in PositiveIntegers()), True, add_one=True)
1 - t - t^2 + t^5 + O(t^7)

sage: L.prod((1 + t^(n-3) for n in PositiveIntegers()), True)
2*t^-3 + 4*t^-2 + 4*t^-1 + 4 + 6*t + 10*t^2 + 16*t^3 + O(t^4)

sage: L.prod(lambda n: 2 + t^n, -3, 5)
96*t^-6 + 240*t^-5 + 336*t^-4 + 840*t^-3 + 984*t^-2 + 1248*t^-1
+ 1980 + 1668*t + 1824*t^2 + 1872*t^3 + 1782*t^4 + 1710*t^5
+ 1314*t^6 + 1122*t^7 + 858*t^8 + 711*t^9 + 438*t^10 + 282*t^11
+ 210*t^12 + 84*t^13 + 60*t^14 + 24*t^15
sage: L.prod(lambda n: t^n / (1 + abs(n)), -2, 2, add_one=True)
1/3*t^-3 + 5/6*t^-2 + 13/9*t^-1 + 25/9 + 13/9*t + 5/6*t^2 + 1/3*t^3
sage: L.prod(lambda n: t^-2 + t^n / n, -4, -2)
1/24*t^-9 - 1/8*t^-8 - 1/6*t^-7 + 1/2*t^-6

sage: D = LazyDirichletSeriesRing(QQ, "s")
sage: D.prod(lambda p: (1+D(1, valuation=p)).inverse(), Primes())
1 - 1/(2^s) - 1/(3^s) + 1/(4^s) - 1/(5^s) + 1/(6^s) - 1/(7^s) + O(1/(8^s))

sage: D.prod(lambda p: D(1, valuation=p), Primes(), add_one=True)
```

(continues on next page)

(continued from previous page)

```

1 + 1/(2^s) + 1/(3^s) + 1/(5^s) + 1/(6^s) + 1/(7^s) + O(1/(8^s))

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('t',)); (t,) = L._first_ngens(1)
>>> euler = L.prod(lambda n: Integer(1) - t**n, PositiveIntegers())
>>> euler
1 - t - t^2 + t^5 + O(t^7)
>>> Integer(1) / euler
1 + t + 2*t^2 + 3*t^3 + 5*t^4 + 7*t^5 + 11*t^6 + O(t^7)
>>> euler - L.euler()
O(t^7)
>>> L.prod(lambda n: -t**n, Integer(1), add_one=True)
1 - t - t^2 + t^5 + O(t^7)

>>> L.prod((Integer(1) - t**n for n in PositiveIntegers()), True)
1 - t - t^2 + t^5 + O(t^7)
>>> L.prod((-t**n for n in PositiveIntegers()), True, add_one=True)
1 - t - t^2 + t^5 + O(t^7)

>>> L.prod((Integer(1) + t**(n-Integer(3)) for n in PositiveIntegers()), True)
2*t^-3 + 4*t^-2 + 4*t^-1 + 4 + 6*t + 10*t^2 + 16*t^3 + O(t^4)

>>> L.prod(lambda n: Integer(2) + t**n, -Integer(3), Integer(5))
96*t^-6 + 240*t^-5 + 336*t^-4 + 840*t^-3 + 984*t^-2 + 1248*t^-1
+ 1980 + 1668*t + 1824*t^2 + 1872*t^3 + 1782*t^4 + 1710*t^5
+ 1314*t^6 + 1122*t^7 + 858*t^8 + 711*t^9 + 438*t^10 + 282*t^11
+ 210*t^12 + 84*t^13 + 60*t^14 + 24*t^15
>>> L.prod(lambda n: t**n / (Integer(1) + abs(n)), -Integer(2), Integer(2),
↪add_one=True)
1/3*t^-3 + 5/6*t^-2 + 13/9*t^-1 + 25/9 + 13/9*t + 5/6*t^2 + 1/3*t^3
>>> L.prod(lambda n: t**(-Integer(2) + t**n / n, -Integer(4), -Integer(2))
1/24*t^-9 - 1/8*t^-8 - 1/6*t^-7 + 1/2*t^-6

>>> D = LazyDirichletSeriesRing(QQ, "s")
>>> D.prod(lambda p: (Integer(1)+D(Integer(1), valuation=p)).inverse(),
↪Primes())
1 - 1/(2^s) - 1/(3^s) + 1/(4^s) - 1/(5^s) + 1/(6^s) - 1/(7^s) + O(1/(8^s))

>>> D.prod(lambda p: D(Integer(1), valuation=p), Primes(), add_one=True)
1 + 1/(2^s) + 1/(3^s) + 1/(5^s) + 1/(6^s) + 1/(7^s) + O(1/(8^s))

```

sum(*f*, *a*=None, *b*=+Infinity)

The sum of elements of *self*.

INPUT:

- *f* – list (or iterable or function) of elements of *self*
- *a*, *b* – optional arguments

If *a* and *b* are both integers, then this returns the sum $\sum_{i=a}^b f(i)$. If *b* is not specified, then we consider $b = \infty$. Note this corresponds to the Python range(*a*, *b*+1).

If *a* is any other iterable, then this returns the sum $\sum_{i \in a} f(i)$.

Warning

When `f` is an infinite generator, then the first argument `a` must be `True`. Otherwise this will loop forever.

Warning

For an *infinite* sum of the form $\sum_i s_i$, if $s_i = 0$, then this will loop forever.

EXAMPLES:

```
sage: L.<t> = LazyLaurentSeriesRing(QQ)
sage: L.sum(lambda n: t^n / (n+1), PositiveIntegers())
1/2*t + 1/3*t^2 + 1/4*t^3 + 1/5*t^4 + 1/6*t^5 + 1/7*t^6 + 1/8*t^7 + O(t^8)

sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: T = L.undefine(1)
sage: D = L.undefine(0)
sage: H = L.sum(lambda k: T(z^k)/k, 2)
sage: T.define(z*exp(T)*D)
sage: D.define(exp(H))
sage: T
z + z^2 + 2*z^3 + 4*z^4 + 9*z^5 + 20*z^6 + 48*z^7 + O(z^8)
sage: D
1 + 1/2*z^2 + 1/3*z^3 + 7/8*z^4 + 11/30*z^5 + 281/144*z^6 + O(z^7)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('t',)); (t,) = L._first_ngens(1)
>>> L.sum(lambda n: t**n / (n+Integer(1)), PositiveIntegers())
1/2*t + 1/3*t^2 + 1/4*t^3 + 1/5*t^4 + 1/6*t^5 + 1/7*t^6 + 1/8*t^7 + O(t^8)

>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> T = L.undefine(Integer(1))
>>> D = L.undefine(Integer(0))
>>> H = L.sum(lambda k: T(z**k)/k, Integer(2))
>>> T.define(z*exp(T)*D)
>>> D.define(exp(H))
>>> T
z + z^2 + 2*z^3 + 4*z^4 + 9*z^5 + 20*z^6 + 48*z^7 + O(z^8)
>>> D
1 + 1/2*z^2 + 1/3*z^3 + 7/8*z^4 + 11/30*z^5 + 281/144*z^6 + O(z^7)
```

We verify the Rogers-Ramanujan identities up to degree 100:

```
sage: L.<q> = LazyPowerSeriesRing(QQ)
sage: Gpi = L.prod(lambda k: -q^(1+5*k), 0, oo, add_one=True)
sage: Gpi *= L.prod(lambda k: -q^(4+5*k), 0, oo, add_one=True)
sage: Gp = 1 / Gpi
sage: G = L.sum(lambda n: q^(n^2) / prod(1 - q^(k+1) for k in range(n)), 0, oo)
sage: G - Gp
O(q^7)
```

(continues on next page)

(continued from previous page)

```

sage: all(G[k] == Gp[k] for k in range(100))
True

sage: Hpi = L.prod(lambda k: -q^(2+5*k), 0, oo, add_one=True)
sage: Hpi *= L.prod(lambda k: -q^(3+5*k), 0, oo, add_one=True)
sage: Hp = 1 / Hpi
sage: H = L.sum(lambda n: q^(n^2+n) / prod(1 - q^(k+1) for k in range(n)), 0, oo)
O(q^7)
sage: all(H[k] == Hp[k] for k in range(100))
True

```

```

>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('q',)); (q,) = L._first_ngens(1)
>>> Gpi = L.prod(lambda k: -q**(Integer(1)+Integer(5)*k), Integer(0), oo, add_
    ↪ one=True)
>>> Gpi *= L.prod(lambda k: -q**(Integer(4)+Integer(5)*k), Integer(0), oo,
    ↪ add_one=True)
>>> Gp = Integer(1) / Gpi
>>> G = L.sum(lambda n: q**(n**Integer(2)) / prod(Integer(1) -
    ↪ q**(k+Integer(1)) for k in range(n)), Integer(0), oo)
>>> G - Gp
O(q^7)
>>> all(G[k] == Gp[k] for k in range(Integer(100)))
True

>>> Hpi = L.prod(lambda k: -q**(Integer(2)+Integer(5)*k), Integer(0), oo, add_
    ↪ one=True)
>>> Hpi *= L.prod(lambda k: -q**(Integer(3)+Integer(5)*k), Integer(0), oo,
    ↪ add_one=True)
>>> Hp = Integer(1) / Hpi
>>> H = L.sum(lambda n: q**(n**Integer(2)+n) / prod(Integer(1) -
    ↪ q**(k+Integer(1)) for k in range(n)), Integer(0), oo)
>>> H - Hp
O(q^7)
>>> all(H[k] == Hp[k] for k in range(Integer(100)))
True

```

```

sage: D = LazyDirichletSeriesRing(QQ, "s")
sage: D.sum(lambda p: D(1, valuation=p), Primes())
1/(2^s) + 1/(3^s) + 1/(5^s) + 1/(7^s) + O(1/(9^s))

```

```

>>> from sage.all import *
>>> D = LazyDirichletSeriesRing(QQ, "s")
>>> D.sum(lambda p: D(Integer(1), valuation=p), Primes())
1/(2^s) + 1/(3^s) + 1/(5^s) + 1/(7^s) + O(1/(9^s))

```

undefined (*valuation=None, name=None*)

Return an uninitialized series.

INPUT:

- `valuation` – integer; a lower bound for the valuation of the series
- `name` – string; a name that refers to the undefined stream in error messages

Power series can be defined recursively (see `sage.rings.lazy_series.LazyModuleElement.define()` for more examples).

See also

`sage.rings.padics.generic_nodes.pAdicRelaxedGeneric.unknown()`

EXAMPLES:

```
sage: L.<z> = LazyPowerSeriesRing(QQ)
sage: s = L.undefined(1)
sage: s.define(z + (s^2+s(z^2))/2)
sage: s
z + z^2 + z^3 + 2*z^4 + 3*z^5 + 6*z^6 + 11*z^7 + O(z^8)
```

```
>>> from sage.all import *
>>> L = LazyPowerSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> s = L.undefined(Integer(1))
>>> s.define(z + (s**Integer(2)+s(z**Integer(2)))/Integer(2))
>>> s
z + z^2 + z^3 + 2*z^4 + 3*z^5 + 6*z^6 + 11*z^7 + O(z^8)
```

Alternatively:

```
sage: L.<z> = LazyLaurentSeriesRing(QQ)
sage: f = L(None, valuation=-1)
sage: f.define(z^-1 + z^2*f^2)
sage: f
z^-1 + 1 + 2*z + 5*z^2 + 14*z^3 + 42*z^4 + 132*z^5 + O(z^6)
```

```
>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(QQ, names=('z',)); (z,) = L._first_ngens(1)
>>> f = L(None, valuation=-Integer(1))
>>> f.define(z**-Integer(1) + z**Integer(2)*f**Integer(2))
>>> f
z^-1 + 1 + 2*z + 5*z^2 + 14*z^3 + 42*z^4 + 132*z^5 + O(z^6)
```

unknown (*valuation=None, name=None*)

alias of `undefined()`.

zero ()

Return the zero series.

EXAMPLES:

```
sage: L = LazyLaurentSeriesRing(ZZ, 'z')
sage: L.zero()
0
sage: s = SymmetricFunctions(ZZ).s()
```

#

(continues on next page)

(continued from previous page)

```

↪needs sage.modules
sage: L = LazySymmetricFunctions(s) #_
↪needs sage.modules
sage: L.zero() #_
↪needs sage.modules
0

sage: L = LazyDirichletSeriesRing(ZZ, 'z')
sage: L.zero()
0

sage: L = LazyPowerSeriesRing(ZZ, 'z')
sage: L.zero()
0

```

```

>>> from sage.all import *
>>> L = LazyLaurentSeriesRing(ZZ, 'z')
>>> L.zero()
0

>>> s = SymmetricFunctions(ZZ).s() #_
↪needs sage.modules
>>> L = LazySymmetricFunctions(s) #_
↪needs sage.modules
>>> L.zero() #_
↪needs sage.modules
0

>>> L = LazyDirichletSeriesRing(ZZ, 'z')
>>> L.zero()
0

>>> L = LazyPowerSeriesRing(ZZ, 'z')
>>> L.zero()
0

```

class sage.rings.lazy_series_ring.**LazySymmetricFunctions** (*basis, sparse=True, category=None*)

Bases: *LazyCompletionGradedAlgebra*

The ring of lazy symmetric functions.

INPUT:

- *basis* – the ring of symmetric functions
- *names* – name(s) of the alphabets
- *sparse* – boolean (default: `True`); whether we use a sparse or a dense representation

EXAMPLES:

```

sage: s = SymmetricFunctions(ZZ).s() #_
↪needs sage.modules
sage: LazySymmetricFunctions(s) #_
↪needs sage.modules

```

(continues on next page)

(continued from previous page)

```
Lazy completion of Symmetric Functions over Integer Ring in the Schur basis
```

```
sage: m = SymmetricFunctions(ZZ).m() #_
```

```
↳needs sage.modules
```

```
sage: LazySymmetricFunctions(tensor([s, m])) #_
```

```
↳needs sage.modules
```

```
Lazy completion of
```

```
Symmetric Functions over Integer Ring in the Schur basis
```

```
# Symmetric Functions over Integer Ring in the monomial basis
```

```
>>> from sage.all import *
```

```
>>> s = SymmetricFunctions(ZZ).s() #_
```

```
↳needs sage.modules
```

```
>>> LazySymmetricFunctions(s) #_
```

```
↳needs sage.modules
```

```
Lazy completion of Symmetric Functions over Integer Ring in the Schur basis
```

```
>>> m = SymmetricFunctions(ZZ).m() #_
```

```
↳needs sage.modules
```

```
>>> LazySymmetricFunctions(tensor([s, m])) #_
```

```
↳needs sage.modules
```

```
Lazy completion of
```

```
Symmetric Functions over Integer Ring in the Schur basis
```

```
# Symmetric Functions over Integer Ring in the monomial basis
```

Element

alias of *LazySymmetricFunction*

PUISEUX SERIES RING

The ring of Puiseux series.

AUTHORS:

- Chris Swierczewski 2016: initial version on <https://github.com/abelfunctions/abelfunctions/tree/master/abelfunctions>
- Frédéric Chapoton 2016: integration of code
- Travis Scrimshaw, Sebastian Oehms 2019-2020: basic improvements and completions

REFERENCES:

- [Wikipedia article Puiseux_series](#)

class sage.rings.puiseux_series_ring.**PuiseuxSeriesRing**(*laurent_series*)

Bases: `UniqueRepresentation`, `Parent`

Rings of Puiseux series.

EXAMPLES:

```
sage: P = PuiseuxSeriesRing(QQ, 'y')
sage: y = P.gen()
sage: f = y**(4/3) + y**(-5/6); f
y^(-5/6) + y^(4/3)
sage: f.add_bigoh(2)
y^(-5/6) + y^(4/3) + O(y^2)
sage: f.add_bigoh(1)
y^(-5/6) + O(y)
```

```
>>> from sage.all import *
>>> P = PuiseuxSeriesRing(QQ, 'y')
>>> y = P.gen()
>>> f = y**(Integer(4)/Integer(3)) + y**(-Integer(5)/Integer(6)); f
y^(-5/6) + y^(4/3)
>>> f.add_bigoh(Integer(2))
y^(-5/6) + y^(4/3) + O(y^2)
>>> f.add_bigoh(Integer(1))
y^(-5/6) + O(y)
```

Element

alias of `PuiseuxSeries`

base_extend(*R*)

Extend the coefficients.

INPUT:

- *R* – a ring

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(ZZ, 'y')
sage: A.base_extend(QQ)
Puisseux Series Ring in y over Rational Field
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(ZZ, 'y')
>>> A.base_extend(QQ)
Puisseux Series Ring in y over Rational Field
```

change_ring(*R*)

Return a Puiseux series ring over another ring.

INPUT:

- *R* – a ring

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(ZZ, 'y')
sage: A.change_ring(QQ)
Puisseux Series Ring in y over Rational Field
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(ZZ, 'y')
>>> A.change_ring(QQ)
Puisseux Series Ring in y over Rational Field
```

default_prec()

Return the default precision of self.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
sage: A.default_prec() #_
↪needs sage.rings.number_field
20
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
>>> A.default_prec() #_
↪needs sage.rings.number_field
20
```

fraction_field()

Return the fraction field of this ring of Laurent series.

If the base ring is a field, then Puiseux series are already a field. If the base ring is a domain, then the Puiseux series over its fraction field is returned. Otherwise, raise a `ValueError`.

EXAMPLES:

```
sage: R = PuiseuxSeriesRing(ZZ, 't', 30).fraction_field()
sage: R
Puisseux Series Ring in t over Rational Field
sage: R.default_prec()
30

sage: PuiseuxSeriesRing(Zmod(4), 't').fraction_field()
Traceback (most recent call last):
...
ValueError: must be an integral domain
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, 't', Integer(30)).fraction_field()
>>> R
Puisseux Series Ring in t over Rational Field
>>> R.default_prec()
30

>>> PuiseuxSeriesRing(Zmod(Integer(4)), 't').fraction_field()
Traceback (most recent call last):
...
ValueError: must be an integral domain
```

gen($n=0$)

Return the generator of self.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
sage: A.gen() #_
↪needs sage.rings.number_field
z
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
>>> A.gen() #_
↪needs sage.rings.number_field
z
```

gens()

Return the tuple of generators.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(QQ, 'z')
sage: A.gens()
(z, )
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(QQ, 'z')
>>> A.gens()
(z,)
```

is_dense()

Return whether `self` is dense.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(ZZ, 'y')
sage: A.is_dense()
True
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(ZZ, 'y')
>>> A.is_dense()
True
```

is_field(*proof=True*)

Return whether `self` is a field.

A Puiseux series ring is a field if and only its base ring is a field.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(ZZ, 'y')
sage: A.is_field()
False
sage: A in Fields()
False
sage: B = A.change_ring(QQ); B.is_field()
True
sage: B in Fields()
True
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(ZZ, 'y')
>>> A.is_field()
False
>>> A in Fields()
False
>>> B = A.change_ring(QQ); B.is_field()
True
>>> B in Fields()
True
```

is_sparse()

Return whether `self` is sparse.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(ZZ, 'y')
sage: A.is_sparse()
False
```



```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(ZZ, 'y')
>>> A.is_sparse()
False
```

laurent_series_ring()

Return the underlying Laurent series ring.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
sage: A.laurent_series_ring() #_
↪needs sage.rings.number_field
Laurent Series Ring in z over Algebraic Real Field
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
>>> A.laurent_series_ring() #_
↪needs sage.rings.number_field
Laurent Series Ring in z over Algebraic Real Field
```

ngens()

Return the number of generators of `self`, namely 1.

EXAMPLES:

```
sage: A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
sage: A.ngens() #_
↪needs sage.rings.number_field
1
```

```
>>> from sage.all import *
>>> A = PuiseuxSeriesRing(AA, 'z') #_
↪needs sage.rings.number_field
>>> A.ngens() #_
↪needs sage.rings.number_field
1
```

residue_field()

Return the residue field of this Puiseux series field if it is a complete discrete valuation field (i.e. if the base ring is a field, in which case it is also the residue field).

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(GF(17))
sage: R.residue_field()
Finite Field of size 17

sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: R.residue_field()
```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
TypeError: the base ring is not a field
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(GF(Integer(17)), names=('x',)); (x,) = R._first_
↳ngens(1)
>>> R.residue_field()
Finite Field of size 17

>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> R.residue_field()
Traceback (most recent call last):
...
TypeError: the base ring is not a field
```

uniformizer()

Return a uniformizer of this Puiseux series field if it is a discrete valuation field (i.e. if the base ring is actually a field). Otherwise, an error is raised.

EXAMPLES:

```
sage: R.<t> = PuiseuxSeriesRing(QQ)
sage: R.uniformizer()
t

sage: R.<t> = PuiseuxSeriesRing(ZZ)
sage: R.uniformizer()
Traceback (most recent call last):
...
TypeError: the base ring is not a field
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.uniformizer()
t

>>> R = PuiseuxSeriesRing(ZZ, names=('t',)); (t,) = R._first_ngens(1)
>>> R.uniformizer()
Traceback (most recent call last):
...
TypeError: the base ring is not a field
```

PUISEUX SERIES RING ELEMENT

A Puiseux series is a series of the form

$$p(x) = \sum_{n=N}^{\infty} a_n (x - a)^{n/e},$$

where the integer e is called the *ramification index* of the series and the number a is the *center*. A Puiseux series is essentially a Laurent series but with fractional exponents.

EXAMPLES:

We begin by constructing the ring of Puiseux series in x with coefficients in the rationals:

```
sage: R.<x> = PuiseuxSeriesRing(QQ)
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
```

This command also defines x as the generator of this ring.

When constructing a Puiseux series, the ramification index is automatically determined from the greatest common divisor of the exponents:

```
sage: p = x^(1/2); p
x^(1/2)
sage: p.ramification_index()
2
sage: q = x^(1/2) + x**(1/3); q
x^(1/3) + x^(1/2)
sage: q.ramification_index()
6
```

```
>>> from sage.all import *
>>> p = x**(Integer(1)/Integer(2)); p
x^(1/2)
>>> p.ramification_index()
2
>>> q = x**(Integer(1)/Integer(2)) + x**(Integer(1)/Integer(3)); q
x^(1/3) + x^(1/2)
>>> q.ramification_index()
6
```

Other arithmetic can be performed with Puiseux Series:

```
sage: p + q
x^(1/3) + 2*x^(1/2)
sage: p - q
-x^(1/3)
sage: p * q
x^(5/6) + x
sage: (p / q).add_bigoh(4/3)
x^(1/6) - x^(1/3) + x^(1/2) - x^(2/3) + x^(5/6) - x + x^(7/6) + O(x^(4/3))
```

```
>>> from sage.all import *
>>> p + q
x^(1/3) + 2*x^(1/2)
>>> p - q
-x^(1/3)
>>> p * q
x^(5/6) + x
>>> (p / q).add_bigoh(Integer(4)/Integer(3))
x^(1/6) - x^(1/3) + x^(1/2) - x^(2/3) + x^(5/6) - x + x^(7/6) + O(x^(4/3))
```

Mind the base ring. However, the base ring can be changed:

```
sage: I*q
↳needs sage.rings.number_field
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *:
'Number Field in I with defining polynomial x^2 + 1 with I = 1*I' and
'Puisseux Series Ring in x over Rational Field'
sage: qz = q.change_ring(ZZ); qz
x^(1/3) + x^(1/2)
sage: qz.parent()
Puisseux Series Ring in x over Integer Ring
```

```
>>> from sage.all import *
>>> I*q
↳needs sage.rings.number_field
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *:
'Number Field in I with defining polynomial x^2 + 1 with I = 1*I' and
'Puisseux Series Ring in x over Rational Field'
>>> qz = q.change_ring(ZZ); qz
x^(1/3) + x^(1/2)
>>> qz.parent()
Puisseux Series Ring in x over Integer Ring
```

Other properties of the Puiseux series can be easily obtained:

```
sage: r = (3*x^(-1/5) + 7*x^(2/5) + (1/2)*x).add_bigoh(6/5); r
3*x^(-1/5) + 7*x^(2/5) + 1/2*x + O(x^(6/5))
sage: r.valuation()
-1/5
sage: r.prec()
```

(continues on next page)

(continued from previous page)

```

6/5
sage: r.precision_absolute()
6/5
sage: r.precision_relative()
7/5
sage: r.exponents()
[-1/5, 2/5, 1]
sage: r.coefficients()
[3, 7, 1/2]

```

```

>>> from sage.all import *
>>> r = (Integer(3)*x**(-Integer(1)/Integer(5)) + Integer(7)*x**(Integer(2)/
↳ Integer(5)) + (Integer(1)/Integer(2))*x).add_bigoh(Integer(6)/Integer(5)); r
3*x^(-1/5) + 7*x^(2/5) + 1/2*x + O(x^(6/5))
>>> r.valuation()
-1/5
>>> r.prec()
6/5
>>> r.precision_absolute()
6/5
>>> r.precision_relative()
7/5
>>> r.exponents()
[-1/5, 2/5, 1]
>>> r.coefficients()
[3, 7, 1/2]

```

Finally, Puiseux series are compatible with other objects in Sage. For example, you can perform arithmetic with Laurent series:

```

sage: L.<x> = LaurentSeriesRing(ZZ)
sage: l = 3*x^(-2) + x^(-1) + 2 + x**3
sage: r + l
3*x^-2 + x^-1 + 3*x^(-1/5) + 2 + 7*x^(2/5) + 1/2*x + O(x^(6/5))

```

```

>>> from sage.all import *
>>> L = LaurentSeriesRing(ZZ, names=('x',)); (x,) = L._first_ngens(1)
>>> l = Integer(3)*x**(-Integer(2)) + x**(-Integer(1)) + Integer(2) + x**Integer(3)
>>> r + l
3*x^-2 + x^-1 + 3*x^(-1/5) + 2 + 7*x^(2/5) + 1/2*x + O(x^(6/5))

```

AUTHORS:

- Chris Swierczewski 2016: initial version on <https://github.com/abelfunctions/abelfunctions/tree/master/abelfunctions>
- Frédéric Chapoton 2016: integration of code
- Travis Scrimshaw, Sebastian Oehms 2019-2020: basic improvements and completions

REFERENCES:

- [Wikipedia article Puiseux_series](#)

class sage.rings.puiseux_series_ring_element.**PuiseuxSeries**

Bases: `AlgebraElement`

A Puiseux series.

$$\sum_{n=-N}^{\infty} a_n x^{n/e}$$

It is stored as a Laurent series:

$$\sum_{n=-N}^{\infty} a_n t^n$$

where $t = x^{1/e}$.

INPUT:

- `parent` – the parent ring
- `f` – one of the following types of inputs:
 - instance of `PuiseuxSeries`
 - instance that can be coerced into the Laurent series ring of the parent
- `e` – integer (default: 1); the ramification index

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(1/2) + x**3; p
x^(1/2) + x^3
sage: q = x**(1/2) - x**(-1/2)
sage: r = q.add_bigoh(7/2); r
-x^(-1/2) + x^(1/2) + O(x^(7/2))
sage: r**2
x^-1 - 2 + x + O(x^3)
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(1)/Integer(2)) + x**Integer(3); p
x^(1/2) + x^3
>>> q = x**(Integer(1)/Integer(2)) - x**(-Integer(1)/Integer(2))
>>> r = q.add_bigoh(Integer(7)/Integer(2)); r
-x^(-1/2) + x^(1/2) + O(x^(7/2))
>>> r**Integer(2)
x^-1 - 2 + x + O(x^3)
```

add_bigoh(*prec*)

Return the truncated series at chosen precision *prec*.

INPUT:

- `prec` – the precision of the series as a rational number

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(-7/2) + 3 + 5*x^(1/2) - 7*x**3
sage: p.add_bigoh(2)
x^(-7/2) + 3 + 5*x^(1/2) + O(x^2)
sage: p.add_bigoh(0)
x^(-7/2) + O(1)
sage: p.add_bigoh(-1)
x^(-7/2) + O(x^-1)

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(7)/Integer(2)) + Integer(3) + Integer(5)*x**(Integer(1)/
↪Integer(2)) - Integer(7)*x**Integer(3)
>>> p.add_bigoh(Integer(2))
x^(-7/2) + 3 + 5*x^(1/2) + O(x^2)
>>> p.add_bigoh(Integer(0))
x^(-7/2) + O(1)
>>> p.add_bigoh(-Integer(1))
x^(-7/2) + O(x^-1)

```

Note

The precision passed to the method is adapted to the common ramification index:

```

sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x**(-1/3) + 2*x**(1/5)
sage: p.add_bigoh(1/2)
x^(-1/3) + 2*x^(1/5) + O(x^(7/15))

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(1)/Integer(3)) + Integer(2)*x**(Integer(1)/Integer(5))
>>> p.add_bigoh(Integer(1)/Integer(2))
x^(-1/3) + 2*x^(1/5) + O(x^(7/15))

```

`change_ring(R)`

Return self over a the new ring R.

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x^(-7/2) + 3 + 5*x^(1/2) - 7*x**3
sage: q = p.change_ring(QQ); q
x^(-7/2) + 3 + 5*x^(1/2) - 7*x^3
sage: q.parent()
Puisseux Series Ring in x over Rational Field

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(7)/Integer(2)) + Integer(3) + Integer(5)*x**(Integer(1)/
↪Integer(2)) - Integer(7)*x**Integer(3)

```

(continues on next page)

(continued from previous page)

```
>>> q = p.change_ring(QQ); q
x^(-7/2) + 3 + 5*x^(1/2) - 7*x^3
>>> q.parent()
Puiseux Series Ring in x over Rational Field
```

coefficients()

Return the list of coefficients.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x^(3/4) + 2*x^(4/5) + 3*x^(5/6)
sage: p.coefficients()
[1, 2, 3]
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(3)/Integer(4)) + Integer(2)*x**(Integer(4)/Integer(5)) +
Integer(3)*x**(Integer(5)/Integer(6))
>>> p.coefficients()
[1, 2, 3]
```

common_prec(p)Return the minimum precision of p and self.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = (x**(-1/3) + 2*x**3)**2
sage: q5 = p.add_bigoh(5); q5
x^(-2/3) + 4*x^(8/3) + O(x^5)
sage: q7 = p.add_bigoh(7); q7
x^(-2/3) + 4*x^(8/3) + 4*x^6 + O(x^7)
sage: q5.common_prec(q7)
5
sage: q7.common_prec(q5)
5
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = (x**(-Integer(1)/Integer(3)) + Integer(2)*x**Integer(3))**Integer(2)
>>> q5 = p.add_bigoh(Integer(5)); q5
x^(-2/3) + 4*x^(8/3) + O(x^5)
>>> q7 = p.add_bigoh(Integer(7)); q7
x^(-2/3) + 4*x^(8/3) + 4*x^6 + O(x^7)
>>> q5.common_prec(q7)
5
>>> q7.common_prec(q5)
5
```

degree()

Return the degree of self.

EXAMPLES:


```

sage: P.<y> = PolynomialRing(GF(5))
sage: R.<x> = PuiseuxSeriesRing(P)
sage: p = 3*y*x**(-2/3) + 2*y**2*x**(1/5); p
3*y*x^(-2/3) + 2*y^2*x^(1/5)
sage: p.degree()
1/5

```

```

>>> from sage.all import *
>>> P = PolynomialRing(GF(Integer(5)), names=('y',)); (y,) = P._first_ngens(1)
>>> R = PuiseuxSeriesRing(P, names=('x',)); (x,) = R._first_ngens(1)
>>> p = Integer(3)*y*x**(-Integer(2)/Integer(3)) + \
↳ Integer(2)*y**Integer(2)*x**(Integer(1)/Integer(5)); p
3*y*x^(-2/3) + 2*y^2*x^(1/5)
>>> p.degree()
1/5

```

exponents()

Return the list of exponents.

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x^(3/4) + 2*x^(4/5) + 3*x^(5/6)
sage: p.exponents()
[3/4, 4/5, 5/6]

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(3)/Integer(4)) + Integer(2)*x**(Integer(4)/Integer(5)) + \
↳ Integer(3)*x**(Integer(5)/Integer(6))
>>> p.exponents()
[3/4, 4/5, 5/6]

```

inverse()

Return the inverse of self.

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(-7/2) + 3 + 5*x^(1/2) - 7*x**3
sage: 1/p
x^(7/2) - 3*x^7 - 5*x^(15/2) + 7*x^10 + 9*x^(21/2) + 30*x^11 +
25*x^(23/2) + O(x^(27/2))

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(7)/Integer(2)) + Integer(3) + Integer(5)*x**(Integer(1)/
↳ Integer(2)) - Integer(7)*x**Integer(3)
>>> Integer(1)/p
x^(7/2) - 3*x^7 - 5*x^(15/2) + 7*x^10 + 9*x^(21/2) + 30*x^11 +
25*x^(23/2) + O(x^(27/2))

```

is_monomial()

Return whether `self` is a monomial.

This is `True` if and only if `self` is x^p for some rational p .

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(1/2) + 3/4 * x^(2/3)
sage: p.is_monomial()
False
sage: q = x**(11/13)
sage: q.is_monomial()
True
sage: q = 4*x**(11/13)
sage: q.is_monomial()
False
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(1)/Integer(2)) + Integer(3)/Integer(4) * x**(Integer(2)/
↳ Integer(3))
>>> p.is_monomial()
False
>>> q = x**(Integer(11)/Integer(13))
>>> q.is_monomial()
True
>>> q = Integer(4)*x**(Integer(11)/Integer(13))
>>> q.is_monomial()
False
```

is_unit()

Return whether `self` is a unit.

A Puiseux series is a unit if and only if its leading coefficient is.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x^(-7/2) + 3 + 5*x^(1/2) - 7*x**3
sage: p.is_unit()
True
sage: q = 4 * x^(-7/2) + 3 * x**4
sage: q.is_unit()
False
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(7)/Integer(2)) + Integer(3) + Integer(5)*x**(Integer(1)/
↳ Integer(2)) - Integer(7)*x**Integer(3)
>>> p.is_unit()
True
>>> q = Integer(4) * x**(-Integer(7)/Integer(2)) + Integer(3) * x**Integer(4)
>>> q.is_unit()
False
```

is_zero()

Return whether self is zero.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(1/2) + 3/4 * x^(2/3)
sage: p.is_zero()
False
sage: R.zero().is_zero()
True
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(1)/Integer(2)) + Integer(3)/Integer(4) * x**(Integer(2)/
↳Integer(3))
>>> p.is_zero()
False
>>> R.zero().is_zero()
True
```

laurent_part()

Return the underlying Laurent series.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(1/2) + 3/4 * x^(2/3)
sage: p.laurent_part()
x^3 + 3/4*x^4
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(1)/Integer(2)) + Integer(3)/Integer(4) * x**(Integer(2)/
↳Integer(3))
>>> p.laurent_part()
x^3 + 3/4*x^4
```

laurent_series()

If self is a Laurent series, return it as a Laurent series.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x**(1/2) - x**(-1/2)
sage: p.laurent_series()
Traceback (most recent call last):
...
ArithmeticError: self is not a Laurent series
sage: q = p**2
sage: q.laurent_series()
x^-1 - 2 + x
```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(1)/Integer(2)) - x**(-Integer(1)/Integer(2))
>>> p.laurent_series()
Traceback (most recent call last):
...
ArithmeticError: self is not a Laurent series
>>> q = p**Integer(2)
>>> q.laurent_series()
x^-1 - 2 + x

```

list()

Return the list of coefficients indexed by the exponents of the the corresponding Laurent series.

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = x^(3/4) + 2*x^(4/5) + 3* x^(5/6)
sage: p.list()
[1, 0, 0, 2, 0, 3]

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(3)/Integer(4)) + Integer(2)*x**(Integer(4)/Integer(5)) +
Integer(3)* x**(Integer(5)/Integer(6))
>>> p.list()
[1, 0, 0, 2, 0, 3]

```

power_series()

If self is a power series, return it as a power series.

EXAMPLES:

```

sage: # needs sage.rings.number_field
sage: R.<x> = PuiseuxSeriesRing(QQbar)
sage: p = x**(3/2) - QQbar(1)*x**(1/2)
sage: p.power_series()
Traceback (most recent call last):
...
ArithmeticError: self is not a power series
sage: q = p**2
sage: q.power_series()
-x - 2*I*x^2 + x^3

```

```

>>> from sage.all import *
>>> # needs sage.rings.number_field
>>> R = PuiseuxSeriesRing(QQbar, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(3)/Integer(2)) - QQbar(1)*x**(Integer(1)/Integer(2))
>>> p.power_series()
Traceback (most recent call last):
...
ArithmeticError: self is not a power series
>>> q = p**Integer(2)

```

(continues on next page)

(continued from previous page)

```
>>> q.power_series()
-x - 2*I*x^2 + x^3
```

prec()Return the precision of `self`.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = (x**(-1/3) + 2*x**3)**2; p
x^(-2/3) + 4*x^(8/3) + 4*x^6
sage: q = p.add_bigoh(5); q
x^(-2/3) + 4*x^(8/3) + O(x^5)
sage: q.prec()
5
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = (x**(-Integer(1)/Integer(3)) + Integer(2)*x**Integer(3))**Integer(2);
↪p
x^(-2/3) + 4*x^(8/3) + 4*x^6
>>> q = p.add_bigoh(Integer(5)); q
x^(-2/3) + 4*x^(8/3) + O(x^5)
>>> q.prec()
5
```

precision_absolute()alias of `prec()`.**precision_relative()**

Return the relative precision of the series.

The relative precision of the Puiseux series is the difference between its absolute precision and its valuation.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(GF(3))
sage: p = (x**(-1/3) + 2*x**3)**2; p
x^(-2/3) + x^(8/3) + x^6
sage: q = p.add_bigoh(7); q
x^(-2/3) + x^(8/3) + x^6 + O(x^7)
sage: q.precision_relative()
23/3
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(GF(Integer(3)), names=('x',)); (x,) = R._first_
↪ngens(1)
>>> p = (x**(-Integer(1)/Integer(3)) + Integer(2)*x**Integer(3))**Integer(2);
↪p
x^(-2/3) + x^(8/3) + x^6
>>> q = p.add_bigoh(Integer(7)); q
x^(-2/3) + x^(8/3) + x^6 + O(x^7)
>>> q.precision_relative()
23/3
```

ramification_index()

Return the ramification index.

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(1/2) + 3/4 * x^(2/3)
sage: p.ramification_index()
6
```

```
>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(Integer(1)/Integer(2)) + Integer(3)/Integer(4) * x**(Integer(2)/
↳ Integer(3))
>>> p.ramification_index()
6
```

shift(r)Return this Puiseux series multiplied by x^r .

EXAMPLES:

```
sage: P.<y> = LaurentPolynomialRing(ZZ)
sage: R.<x> = PuiseuxSeriesRing(P)
sage: p = y*x**(-1/3) + 2*y^(-2)*x**(1/2); p
y*x^(-1/3) + (2*y^-2)*x^(1/2)
sage: p.shift(3)
y*x^(8/3) + (2*y^-2)*x^(7/2)
```

```
>>> from sage.all import *
>>> P = LaurentPolynomialRing(ZZ, names=('y',)); (y,) = P._first_ngens(1)
>>> R = PuiseuxSeriesRing(P, names=('x',)); (x,) = R._first_ngens(1)
>>> p = y*x**(-Integer(1)/Integer(3)) + Integer(2)*y**(-
↳ Integer(2))*x**(Integer(1)/Integer(2)); p
y*x^(-1/3) + (2*y^-2)*x^(1/2)
>>> p.shift(Integer(3))
y*x^(8/3) + (2*y^-2)*x^(7/2)
```

truncate(r)Return the Puiseux series of degree $< r$.This is equivalent to `self modulo  $x^r$` .

EXAMPLES:

```
sage: R.<x> = PuiseuxSeriesRing(ZZ)
sage: p = (x**(-1/3) + 2*x**3)**2; p
x^(-2/3) + 4*x^(8/3) + 4*x^6
sage: q = p.truncate(5); q
x^(-2/3) + 4*x^(8/3)
sage: q == p.add_bigoh(5)
True
```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(ZZ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = (x**(-Integer(1)/Integer(3)) + Integer(2)*x**Integer(3))**Integer(2);
↪p
x^(-2/3) + 4*x^(8/3) + 4*x^6
>>> q = p.truncate(Integer(5)); q
x^(-2/3) + 4*x^(8/3)
>>> q == p.add_bigoh(Integer(5))
True

```

valuation()

Return the valuation of self.

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(-7/2) + 3 + 5*x^(1/2) - 7*x**3
sage: p.valuation()
-7/2

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(7)/Integer(2)) + Integer(3) + Integer(5)*x**(Integer(1)/
↪Integer(2)) - Integer(7)*x**Integer(3)
>>> p.valuation()
-7/2

```

variable()

Return the variable of self.

EXAMPLES:

```

sage: R.<x> = PuiseuxSeriesRing(QQ)
sage: p = x^(-7/2) + 3 + 5*x^(1/2) - 7*x**3
sage: p.variable()
'x'

```

```

>>> from sage.all import *
>>> R = PuiseuxSeriesRing(QQ, names=('x',)); (x,) = R._first_ngens(1)
>>> p = x**(-Integer(7)/Integer(2)) + Integer(3) + Integer(5)*x**(Integer(1)/
↪Integer(2)) - Integer(7)*x**Integer(3)
>>> p.variable()
'x'

```


TATE ALGEBRAS

Let K be a finite extension of $\mathbf{Q}_p$ for some prime number p and let $(v_1, \dots, v_n)$ be a tuple of real numbers.

The associated Tate algebra consists of series of the form

$$\sum_{i_1, \dots, i_n \in \mathbf{N}} a_{i_1, \dots, i_n} x_1^{i_1} \cdots x_n^{i_n}$$

for which the quantity

$$\text{val}(a_{i_1, \dots, i_n}) - (v_1 i_1 + \cdots + v_n i_n)$$

goes to infinity when the multi-index $(i_1, \dots, i_n)$ goes to infinity.

These series converge on the closed disc defined by the inequalities $\text{val}(x_i) \geq -v_i$ for all $i \in \{1, \dots, n\}$. The v_i 's are then the logarithms of the radii of convergence of the series in the above Tate algebra; they will be called the log radii of convergence.

We can create Tate algebras using the constructor `sage.rings.tate_algebra.TateAlgebra()`:

```
sage: K = Qp(2, 5, print_mode='digits')
sage: A.<x,y> = TateAlgebra(K); A
Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 5
```

```
>>> from sage.all import *
>>> K = Qp(Integer(2), Integer(5), print_mode='digits')
>>> A = TateAlgebra(K, names=('x', 'y')); (x, y) = A._first_ngens(2); A
Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 5
```

As we observe, the default value for the log radii of convergence is 0 (the series then converge on the closed unit disc).

We can specify different log radii using the following syntax:

```
sage: B.<u,v> = TateAlgebra(K, log_radii=[1,2]); B
Tate Algebra in u (val >= -1), v (val >= -2)
over 2-adic Field with capped relative precision 5
```

```
>>> from sage.all import *
>>> B = TateAlgebra(K, log_radii=[Integer(1),Integer(2)], names=('u', 'v')); (u, v) = B._first_ngens(2); B
Tate Algebra in u (val >= -1), v (val >= -2)
over 2-adic Field with capped relative precision 5
```

Note that if we pass in the ring of integers of p -adic field, the same Tate algebra is returned:

```
sage: A1.<x,y> = TateAlgebra(K.integer_ring()); A1
Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 5
sage: A is A1
True
```

```
>>> from sage.all import *
>>> A1 = TateAlgebra(K.integer_ring(), names=('x', 'y')); (x, y) = A1._first_
    ↪ngens(2); A1
Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 5
>>> A is A1
True
```

However the method `integer_ring()` constructs the integer ring of a Tate algebra, that is the subring consisting of series bounded by 1 on the domain of convergence:

```
sage: Ao = A.integer_ring(); Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 5
```

```
>>> from sage.all import *
>>> Ao = A.integer_ring(); Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 5
```

Now we can build elements:

```
sage: f = 5 + 2*x*y^3 + 4*x^2*y^2; f
...00101 + ...000010*x*y^3 + ...0000100*x^2*y^2
sage: g = x^3*y + 2*x*y; g
...00001*x^3*y + ...000010*x*y
```

```
>>> from sage.all import *
>>> f = Integer(5) + Integer(2)*x*y**Integer(3) +
    ↪Integer(4)*x**Integer(2)*y**Integer(2); f
...00101 + ...000010*x*y^3 + ...0000100*x^2*y^2
>>> g = x**Integer(3)*y + Integer(2)*x*y; g
...00001*x^3*y + ...000010*x*y
```

and perform all usual arithmetic operations on them:

```
sage: f + g
...00001*x^3*y + ...00101 + ...000010*x*y^3 + ...000010*x*y + ...0000100*x^2*y^2
sage: f * g
...00101*x^3*y + ...000010*x^4*y^4 + ...001010*x*x*y
+ ...0000100*x^5*y^3 + ...0000100*x^2*y^4 + ...00001000*x^3*y^3
```

```
>>> from sage.all import *
>>> f + g
...00001*x^3*y + ...00101 + ...000010*x*y^3 + ...000010*x*y + ...0000100*x^2*y^2
```

(continues on next page)

(continued from previous page)

```
>>> f * g
...00101*x^3*y + ...000010*x^4*y^4 + ...001010*x*y
+ ...0000100*x^5*y^3 + ...0000100*x^2*y^4 + ...00001000*x^3*y^3
```

An element in the integer ring is invertible if and only if its reduction modulo p is a nonzero constant. In our example, f is invertible (its reduction modulo 2 is 1) but g is not:

```
sage: f.inverse_of_unit()
...01101 + ...01110*x*y^3 + ...10100*x^2*y^6 + ... + O(2^5 * <x, y>)
sage: g.inverse_of_unit()
Traceback (most recent call last):
...
ValueError: this series is not invertible
```

```
>>> from sage.all import *
>>> f.inverse_of_unit()
...01101 + ...01110*x*y^3 + ...10100*x^2*y^6 + ... + O(2^5 * <x, y>)
>>> g.inverse_of_unit()
Traceback (most recent call last):
...
ValueError: this series is not invertible
```

The notation $O(2^5)$ in the result above hides a series which lies in 2^5 times the integer ring of A , that is a series which is bounded by $|2^5|$ (2-adic norm) on the domain of convergence.

We can also evaluate series in a point of the domain of convergence (in the base field or in an extension):

```
sage: L.<a> = QQ(2^3, 5)
sage: f(a^2, 2*a)
1 + 2^2 + a*2^4 + O(2^5)

sage: u = polygen(ZZ, 'u')
sage: L.<pi> = K.change(print_mode='series').extension(u^3 - 2)
sage: g(pi, 2*pi)
pi^7 + pi^8 + pi^19 + pi^20 + O(pi^21)
```

```
>>> from sage.all import *
>>> L = QQ(Integer(2)**Integer(3), Integer(5), names=('a',)); (a,) = L._first_ngens(1)
>>> f(a**Integer(2), Integer(2)*a)
1 + 2^2 + a*2^4 + O(2^5)

>>> u = polygen(ZZ, 'u')
>>> L = K.change(print_mode='series').extension(u**Integer(3) - Integer(2), names=('pi',)); (pi,) = L._first_ngens(1)
>>> g(pi, Integer(2)*pi)
pi^7 + pi^8 + pi^19 + pi^20 + O(pi^21)
```

Computations with ideals in Tate algebras are also supported:

```
sage: f = 7*x^3*y + 2*x*y - x*y^2 - 6*y^5
sage: g = x*y^4 + 8*x^3 - 3*y^3 + 1
sage: I = A.ideal([f, g])
sage: I.groebner_basis()
```

(continues on next page)

(continued from previous page)

```
[...00001*x^2*y^3 + ...00001*y^4 + ...10001*x^2 + ... + O(2^5 * <x, y>),
...00001*x*y^4 + ...11101*y^3 + ...00001 + ... + O(2^5 * <x, y>),
...00001*y^5 + ...11111*x*y^3 + ...01001*x^2*y + ... + O(2^5 * <x, y>),
...00001*x^3 + ...01001*x*y + ...10110*y^4 + ...01110*x + O(2^5 * <x, y>)]
```

```
sage: (x^2 + 3*y)*f + 1/2*(x^3*y + x*y)*g in I
True
```

```
>>> from sage.all import *
>>> f = Integer(7)*x**Integer(3)*y + Integer(2)*x*y - x*y**Integer(2) -
↳Integer(6)*y**Integer(5)
>>> g = x*y**Integer(4) + Integer(8)*x**Integer(3) - Integer(3)*y**Integer(3) +
↳Integer(1)
>>> I = A.ideal([f, g])
>>> I.groebner_basis()
[...00001*x^2*y^3 + ...00001*y^4 + ...10001*x^2 + ... + O(2^5 * <x, y>),
...00001*x*y^4 + ...11101*y^3 + ...00001 + ... + O(2^5 * <x, y>),
...00001*y^5 + ...11111*x*y^3 + ...01001*x^2*y + ... + O(2^5 * <x, y>),
...00001*x^3 + ...01001*x*y + ...10110*y^4 + ...01110*x + O(2^5 * <x, y>)]

>>> (x**Integer(2) + Integer(3)*y)*f + Integer(1)/Integer(2)*(x**Integer(3)*y +
↳x*y)*g in I
True
```

AUTHORS:

- Xavier Caruso, Thibaut Verron (2018-09)

class sage.rings.tate_algebra.TateAlgebraFactory

Bases: UniqueFactory

Construct a Tate algebra over a p -adic field.

Given a p -adic field K , variables $X_1, \dots, X_k$ and convergence log radii $v_1, \dots, v_n$ in $\mathbf{R}$, the corresponding Tate algebra $KX_1, \dots, X_k$ consists of power series with coefficients $a_{i_1, \dots, i_n}$ in K such that

$$\text{val}(a_{i_1, \dots, i_n}) - (i_1 v_1 + \dots + i_n v_n)$$

tends to infinity as $i_1, \dots, i_n$ go towards infinity.

INPUT:

- `base` – a p -adic ring or field; if a ring is given, the Tate algebra over its fraction field will be constructed
- `prec` – integer or `None` (default: `None`); the precision cap. It is used if an exact object must be truncated in order to do an arithmetic operation. If left as `None`, it will be set to the precision cap of the base field.
- `log_radii` – integer or a list or a tuple of integers (default: 0); the value(s) v_i . If an integer is given, this will be the common value for all v_i .
- `names` – names of the indeterminates
- `order` – the monomial ordering (default: `degrevlex`) used to break ties when comparing terms with the same coefficient valuation

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits'); R
2-adic Ring with capped relative precision 10
sage: A.<x,y> = TateAlgebra(R, order='lex'); A
Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 10
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits'); R
2-adic Ring with capped relative precision 10
>>> A = TateAlgebra(R, order='lex', names=('x', 'y',)); (x, y) = A._first_
->ngens(2); A
Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 10
```

We observe that the result is the Tate algebra over the fraction field of R and not R itself:

```
sage: A.base_ring()
2-adic Field with capped relative precision 10
sage: A.base_ring() is R.fraction_field()
True
```

```
>>> from sage.all import *
>>> A.base_ring()
2-adic Field with capped relative precision 10
>>> A.base_ring() is R.fraction_field()
True
```

If we want to construct the ring of integers of the Tate algebra, we must use the method `integer_ring()`:

```
sage: Ao = A.integer_ring(); Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 10
sage: Ao.base_ring()
2-adic Ring with capped relative precision 10
sage: Ao.base_ring() is R
True
```

```
>>> from sage.all import *
>>> Ao = A.integer_ring(); Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0)
over 2-adic Field with capped relative precision 10
>>> Ao.base_ring()
2-adic Ring with capped relative precision 10
>>> Ao.base_ring() is R
True
```

The term ordering is used (in particular) to determine how series are displayed. Terms are compared first according to the valuation of their coefficient, and ties are broken using the monomial ordering:

```
sage: A.term_order()
Lexicographic term order
sage: f = 2 + y^5 + x^2; f
```

(continues on next page)

(continued from previous page)

```

...0000000001*x^2 + ...0000000001*y^5 + ...00000000010
sage: B.<x,y> = TateAlgebra(R); B
Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic Field with capped relative_
↳precision 10
sage: B.term_order()
Degree reverse lexicographic term order
sage: B(f)
...0000000001*y^5 + ...0000000001*x^2 + ...00000000010

```

```

>>> from sage.all import *
>>> A.term_order()
Lexicographic term order
>>> f = Integer(2) + y**Integer(5) + x**Integer(2); f
...0000000001*x^2 + ...0000000001*y^5 + ...00000000010
>>> B = TateAlgebra(R, names=('x', 'y')); (x, y) = B._first_ngens(2); B
Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic Field with capped relative_
↳precision 10
>>> B.term_order()
Degree reverse lexicographic term order
>>> B(f)
...0000000001*y^5 + ...0000000001*x^2 + ...00000000010

```

Here are examples of Tate algebra with smaller radii of convergence:

```

sage: B.<x,y> = TateAlgebra(R, log_radii=-1); B
Tate Algebra in x (val >= 1), y (val >= 1) over 2-adic Field with capped relative_
↳precision 10
sage: C.<x,y> = TateAlgebra(R, log_radii=[-1,-2]); C
Tate Algebra in x (val >= 1), y (val >= 2) over 2-adic Field with capped relative_
↳precision 10

```

```

>>> from sage.all import *
>>> B = TateAlgebra(R, log_radii=-Integer(1), names=('x', 'y')); (x, y) = B._
↳first_ngens(2); B
Tate Algebra in x (val >= 1), y (val >= 1) over 2-adic Field with capped relative_
↳precision 10
>>> C = TateAlgebra(R, log_radii=[-Integer(1),-Integer(2)], names=('x', 'y'));
↳(x, y) = C._first_ngens(2); C
Tate Algebra in x (val >= 1), y (val >= 2) over 2-adic Field with capped relative_
↳precision 10

```

AUTHORS:

- Xavier Caruso, Thibaut Verron (2018-09)

create_key (*base, prec=None, log_radii=0, names=None, order='degrevlex'*)

Create a key from the input parameters.

INPUT:

- *base* – a p -adic ring or field
- *prec* – integer or None (default: None)
- *log_radii* – integer or a list or a tuple of integers (default: 0)

- `names` – names of the indeterminates
- `order` – a monomial ordering (default: `degrevlex`)

EXAMPLES:

```
sage: TateAlgebra.create_key(Zp(2), names=['x', 'y'])
(2-adic Field with capped relative precision 20,
 20,
 (0, 0),
 ('x', 'y'),
 Degree reverse lexicographic term order)
```

```
>>> from sage.all import *
>>> TateAlgebra.create_key(Zp(Integer(2)), names=['x', 'y'])
(2-adic Field with capped relative precision 20,
 20,
 (0, 0),
 ('x', 'y'),
 Degree reverse lexicographic term order)
```

create_object (*version*, *key*)

Create an object using the given key.

class `sage.rings.tate_algebra.TateAlgebra_generic` (*field*, *prec*, *log_radII*, *names*, *order*,
integral=False)

Bases: `Parent`

Initialize the Tate algebra.

absolute_e ()

Return the absolute index of ramification of this Tate algebra.

It is equal to the absolute index of ramification of the field of coefficients.

EXAMPLES:

```
sage: R = Zp(2)
sage: A.<u,v> = TateAlgebra(R)
sage: A.absolute_e()
1

sage: R.<a> = Zq(2^3)
sage: A.<u,v> = TateAlgebra(R)
sage: A.absolute_e()
1

sage: x = polygen(ZZ, 'x')
sage: S.<a> = R.extension(x^2 - 2)
sage: A.<u,v> = TateAlgebra(S)
sage: A.absolute_e()
2
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2))
>>> A = TateAlgebra(R, names=('u', 'v')); (u, v) = A._first_ngens(2)
```

(continues on next page)

(continued from previous page)

```

>>> A.absolute_e()
1

>>> R = Zq(Integer(2)**Integer(3), names=('a',)); (a,) = R._first_ngens(1)
>>> A = TateAlgebra(R, names=('u', 'v',)); (u, v,) = A._first_ngens(2)
>>> A.absolute_e()
1

>>> x = polygen(ZZ, 'x')
>>> S = R.extension(x**Integer(2) - Integer(2), names=('a',)); (a,) = S._
↳first_ngens(1)
>>> A = TateAlgebra(S, names=('u', 'v',)); (u, v,) = A._first_ngens(2)
>>> A.absolute_e()
2

```

characteristic()

Return the characteristic of this algebra.

EXAMPLES:

```

sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.characteristic()
0

```

```

>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y,) = A._first_ngens(2)
>>> A.characteristic()
0

```

gen($n=0$)

Return the n -th generator of this Tate algebra.

INPUT:

- n – integer (default: 0); the index of the requested generator

EXAMPLES:

```

sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.gen()
...0000000001*x
sage: A.gen(0)
...0000000001*x
sage: A.gen(1)
...0000000001*y
sage: A.gen(2)
Traceback (most recent call last):
...
ValueError: generator not defined

```



```

>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y) = A._first_ngens(2)
>>> A.gen()
...0000000001*x
>>> A.gen(Integer(0))
...0000000001*x
>>> A.gen(Integer(1))
...0000000001*y
>>> A.gen(Integer(2))
Traceback (most recent call last):
...
ValueError: generator not defined

```

gens()

Return the generators of this Tate algebra.

EXAMPLES:

```

sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.gens()
(...0000000001*x, ...0000000001*y)

```

```

>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y) = A._first_ngens(2)
>>> A.gens()
(...0000000001*x, ...0000000001*y)

```

integer_ring()

Return the ring of integers (consisting of series bounded by 1 in the domain of convergence) of this Tate algebra.

EXAMPLES:

```

sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: Ao = A.integer_ring()
sage: Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic_
↪Field with capped relative precision 10

sage: x in Ao
True
sage: x/2 in Ao
False

```

```

>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y) = A._first_ngens(2)
>>> Ao = A.integer_ring()
>>> Ao

```

(continues on next page)

(continued from previous page)

```
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic
↪Field with capped relative precision 10

>>> x in Ao
True
>>> x/Integer(2) in Ao
False
```

is_integral_domain(*proof=True*)

Return True since any Tate algebra is an integral domain.

EXAMPLES:

```
sage: A.<x,y> = TateAlgebra(Zp(3))
sage: A.is_integral_domain()
True
```

```
>>> from sage.all import *
>>> A = TateAlgebra(Zp(Integer(3)), names=('x', 'y')); (x, y) = A._first_
↪ngens(2)
>>> A.is_integral_domain()
True
```

log_radII()

Return the list of the log-radii of convergence radii defining this Tate algebra.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: A.log_radII()
(0, 0)

sage: B.<x,y> = TateAlgebra(R, log_radII=1)
sage: B.log_radII()
(1, 1)

sage: C.<x,y> = TateAlgebra(R, log_radII=(1,-1))
sage: C.log_radII()
(1, -1)
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> A.log_radII()
(0, 0)

>>> B = TateAlgebra(R, log_radII=Integer(1), names=('x', 'y')); (x, y) = B._
↪first_ngens(2)
>>> B.log_radII()
(1, 1)
```

(continues on next page)

(continued from previous page)

```
>>> C = TateAlgebra(R, log_radII=(Integer(1), -Integer(1)), names=('x', 'y'));
↪ (x, y,) = C._first_ngens(2)
>>> C.log_radII()
(1, -1)
```

monoid_of_terms()

Return the monoid of terms of this Tate algebra.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: A.monoid_of_terms()
Monoid of terms in x (val >= 0), y (val >= 0) over 2-adic Field with capped_
↪ relative precision 10
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y,) = A._first_ngens(2)
>>> A.monoid_of_terms()
Monoid of terms in x (val >= 0), y (val >= 0) over 2-adic Field with capped_
↪ relative precision 10
```

ngens()

Return the number of generators of this algebra.

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.ngens()
2
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y,) = A._first_ngens(2)
>>> A.ngens()
2
```

precision_cap()

Return the precision cap of this Tate algebra.

Note

The precision cap is the truncation precision used for arithmetic operations computed by successive approximations (as inversion).

EXAMPLES:

By default the precision cap is the precision cap of the field of coefficients:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: A.precision_cap()
10
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> A.precision_cap()
10
```

But it could be different (either smaller or larger) if we ask to:

```
sage: A.<x,y> = TateAlgebra(R, prec=5)
sage: A.precision_cap()
5

sage: A.<x,y> = TateAlgebra(R, prec=20)
sage: A.precision_cap()
20
```

```
>>> from sage.all import *
>>> A = TateAlgebra(R, prec=Integer(5), names=('x', 'y')); (x, y) = A._
↳first_ngens(2)
>>> A.precision_cap()
5

>>> A = TateAlgebra(R, prec=Integer(20), names=('x', 'y')); (x, y) = A._
↳first_ngens(2)
>>> A.precision_cap()
20
```

prime()

Return the prime, that is the characteristic of the residue field.

EXAMPLES:

```
sage: R = Zp(3)
sage: A.<x,y> = TateAlgebra(R)
sage: A.prime()
3
```

```
>>> from sage.all import *
>>> R = Zp(Integer(3))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> A.prime()
3
```

random_element (*degree=2, terms=5, integral=False, prec=None*)

Return a random element of this Tate algebra.

INPUT:

- *degree* – integer (default: 2); an upper bound on the total degree of the result

- `terms` – integer (default: 5); the maximal number of terms of the result
- `integral` – boolean (default: `False`); if `True` the result will be in the ring of integers
- `prec` – (optional) an integer, the precision of the result

EXAMPLES:

```
sage: R = Zp(2, prec=10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.random_element() # random
(...00101000.01)*y + ...111101111*x^2 + ...0010010001*x*y
+ ...110000011 + ...010100100*y^2

sage: A.random_element(degree=5, terms=3) # random
(...0101100.01)*x^2*y + (...01000011.11)*y^2 + ...00111011*x*y

sage: A.random_element(integral=True) # random
...0001111101*x + ...1101110101 + ...00010010110*y
+ ...101110001100*x*y + ...000001100100*y^2
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), prec=Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y,) = A._first_ngens(2)
>>> A.random_element() # random
(...00101000.01)*y + ...111101111*x^2 + ...0010010001*x*y
+ ...110000011 + ...010100100*y^2

>>> A.random_element(degree=Integer(5), terms=Integer(3)) # random
(...0101100.01)*x^2*y + (...01000011.11)*y^2 + ...00111011*x*y

>>> A.random_element(integral=True) # random
...0001111101*x + ...1101110101 + ...00010010110*y
+ ...101110001100*x*y + ...000001100100*y^2
```

Note that if we are already working on the ring of integers, specifying `integral=False` has no effect:

```
sage: Ao = A.integer_ring()
sage: f = Ao.random_element(integral=False); f # random
...1100111011*x^2 + ...1110100101*x + ...1100001101*y
+ ...1110110001 + ...01011010110*y^2
sage: f in Ao
True
```

```
>>> from sage.all import *
>>> Ao = A.integer_ring()
>>> f = Ao.random_element(integral=False); f # random
...1100111011*x^2 + ...1110100101*x + ...1100001101*y
+ ...1110110001 + ...01011010110*y^2
>>> f in Ao
True
```

When the log radii are negative, integral series may have non integral coefficients:

```
sage: B.<x,y> = TateAlgebra(R, log_radII=[-1,-2])
sage: B.random_element(integral=True) # random
(...1111111.001)*x*y + (...111000101.1)*x + (...11010111.01)*y^2
+ ...0010011011*y + ...0010100011000
```

```
>>> from sage.all import *
>>> B = TateAlgebra(R, log_radII=[-Integer(1),-Integer(2)], names=('x', 'y',
↵)); (x, y,) = B._first_ngens(2)
>>> B.random_element(integral=True) # random
(...1111111.001)*x*y + (...111000101.1)*x + (...11010111.01)*y^2
+ ...0010011011*y + ...0010100011000
```

some_elements()

Return a list of elements in this Tate algebra.

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.some_elements()
[0,
 ...00000000010,
 ...0000000001*x,
 ...0000000001*y,
 ...00000000010*x*y,
 ...00000000100,
 ...0000000001*x + ...00000000010,
 ...0000000001*y + ...00000000010,
 ...00000000010*x*y + ...00000000010,
 ...0000000010*x,
 ...0000000001*x + ...0000000001*y,
 ...0000000001*x + ...00000000010*x*y,
 ...0000000010*y,
 ...0000000001*y + ...00000000010*x*y,
 ...00000000100*x*y]
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y,) = A._first_ngens(2)
>>> A.some_elements()
[0,
 ...00000000010,
 ...0000000001*x,
 ...0000000001*y,
 ...00000000010*x*y,
 ...00000000100,
 ...0000000001*x + ...00000000010,
 ...0000000001*y + ...00000000010,
 ...00000000010*x*y + ...00000000010,
 ...0000000010*x,
 ...0000000001*x + ...0000000001*y,
 ...0000000001*x + ...00000000010*x*y,
 ...0000000010*y,
 ...00000000010*y,
```

(continues on next page)

(continued from previous page)

```
...0000000001*y + ...00000000010*x*y,
...00000000100*x*y]
```

term_order()

Return the monomial order used in this algebra.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: A.term_order()
Degree reverse lexicographic term order

sage: A.<x,y> = TateAlgebra(R, order='lex')
sage: A.term_order()
Lexicographic term order
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> A.term_order()
Degree reverse lexicographic term order

>>> A = TateAlgebra(R, order='lex', names=('x', 'y')); (x, y) = A._first_
↳ngens(2)
>>> A.term_order()
Lexicographic term order
```

variable_names()

Return the names of the variables of this algebra.

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: A.variable_names()
('x', 'y')
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> A.variable_names()
('x', 'y')
```

class sage.rings.tate_algebra.**TateTermMonoid**(A)Bases: `Monoid_class`, `UniqueRepresentation`

A base class for Tate algebra terms.

A term in a Tate algebra $K\{X_1, \dots, X_n\}$ (resp. in its ring of integers) is a monomial in this ring.

Those terms form a pre-ordered monoid, with term multiplication and the term order of the parent Tate algebra.

Elementalias of `TateAlgebraTerm`

algebra_of_series()

Return the Tate algebra corresponding to this Tate term monoid.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.algebra_of_series()
Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic Field with capped_
↳relative precision 10
sage: T.algebra_of_series() is A
True
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y,) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.algebra_of_series()
Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic Field with capped_
↳relative precision 10
>>> T.algebra_of_series() is A
True
```

base_ring()

Return the base ring of this Tate term monoid.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.base_ring()
2-adic Field with capped relative precision 10
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y,) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.base_ring()
2-adic Field with capped relative precision 10
```

We observe that the base field is not $\mathbb{R}$ but its fraction field:

```
sage: T.base_ring() is R
False
sage: T.base_ring() is R.fraction_field()
True
```

```
>>> from sage.all import *
>>> T.base_ring() is R
False
>>> T.base_ring() is R.fraction_field()
True
```


If we really want to create an integral Tate algebra, we have to invoke the method `integer_ring()`:

```
sage: Ao = A.integer_ring(); Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic
Field with capped relative precision 10
sage: Ao.base_ring()
2-adic Ring with capped relative precision 10
sage: Ao.base_ring() is R
True
```

```
>>> from sage.all import *
>>> Ao = A.integer_ring(); Ao
Integer ring of the Tate Algebra in x (val >= 0), y (val >= 0) over 2-adic
Field with capped relative precision 10
>>> Ao.base_ring()
2-adic Ring with capped relative precision 10
>>> Ao.base_ring() is R
True
```

gen($n=0$)

Return the n -th generator of this monoid of terms.

INPUT:

- n – integer (default: 0); the index of the requested generator

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.gen()
...0000000001*x
sage: T.gen(0)
...0000000001*x
sage: T.gen(1)
...0000000001*y
sage: T.gen(2)
Traceback (most recent call last):
...
ValueError: generator not defined
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y',)); (x, y,) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.gen()
...0000000001*x
>>> T.gen(Integer(0))
...0000000001*x
>>> T.gen(Integer(1))
...0000000001*y
>>> T.gen(Integer(2))
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: generator not defined
```

gens()

Return the generators of this monoid of terms.

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.gens()
(...0000000001*x, ...0000000001*y)
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.gens()
(...0000000001*x, ...0000000001*y)
```

log_radII()

Return the log radii of convergence of this Tate term monoid.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.log_radII()
(0, 0)

sage: B.<x,y> = TateAlgebra(R, log_radII=[1,2])
sage: B.monoid_of_terms().log_radII()
(1, 2)
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.log_radII()
(0, 0)

>>> B = TateAlgebra(R, log_radII=[Integer(1),Integer(2)], names=('x', 'y'));
↪ (x, y) = B._first_ngens(2)
>>> B.monoid_of_terms().log_radII()
(1, 2)
```

ngens()

Return the number of variables in the Tate term monoid.

EXAMPLES:

```
sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.ngens()
2
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.ngens()
2
```

prime()

Return the prime, that is the characteristic of the residue field.

EXAMPLES:

```
sage: R = Zp(3)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.prime()
3
```

```
>>> from sage.all import *
>>> R = Zp(Integer(3))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.prime()
3
```

some_elements()

Return a list of elements in this monoid of terms.

EXAMPLES:

```
sage: R = Zp(2, 10, print_mode='digits')
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.some_elements()
[...00000000010, ...0000000001*x, ...0000000001*y, ...00000000010*x*y]
```

```
>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10), print_mode='digits')
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.some_elements()
[...00000000010, ...0000000001*x, ...0000000001*y, ...00000000010*x*y]
```

term_order()

Return the term order on this Tate term monoid.

EXAMPLES:

```

sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.term_order() # default term order is grevlex
Degree reverse lexicographic term order

sage: A.<x,y> = TateAlgebra(R, order='lex')
sage: T = A.monoid_of_terms()
sage: T.term_order()
Lexicographic term order

```

```

>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.term_order() # default term order is grevlex
Degree reverse lexicographic term order

>>> A = TateAlgebra(R, order='lex', names=('x', 'y')); (x, y) = A._first_
↪ngens(2)
>>> T = A.monoid_of_terms()
>>> T.term_order()
Lexicographic term order

```

variable_names()

Return the names of the variables of this Tate term monoid.

EXAMPLES:

```

sage: R = Zp(2, 10)
sage: A.<x,y> = TateAlgebra(R)
sage: T = A.monoid_of_terms()
sage: T.variable_names()
('x', 'y')

```

```

>>> from sage.all import *
>>> R = Zp(Integer(2), Integer(10))
>>> A = TateAlgebra(R, names=('x', 'y')); (x, y) = A._first_ngens(2)
>>> T = A.monoid_of_terms()
>>> T.variable_names()
('x', 'y')

```

INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

r

- `sage.rings.laurent_series_ring`, [137](#)
- `sage.rings.laurent_series_ring_element`, [147](#)
- `sage.rings.lazy_series`, [171](#)
- `sage.rings.lazy_series_ring`, [267](#)
- `sage.rings.multi_power_series_ring`, [91](#)
- `sage.rings.multi_power_series_ring_element`,
[107](#)
- `sage.rings.power_series_pari`, [81](#)
- `sage.rings.power_series_poly`, [69](#)
- `sage.rings.power_series_ring`, [1](#)
- `sage.rings.power_series_ring_element`, [21](#)
- `sage.rings.puiseux_series_ring`, [321](#)
- `sage.rings.puiseux_series_ring_element`, [327](#)
- `sage.rings.tate_algebra`, [341](#)

A

absolute_e() (sage.rings.tate_algebra.TateAlgebra_generic method), 347

adams_operator() (sage.rings.lazy_series.LazyPowerSeries method), 235

add_bigoh() (sage.rings.laurent_series_ring_element.LaurentSeries method), 149

add_bigoh() (sage.rings.lazy_series.LazyLaurentSeries method), 181

add_bigoh() (sage.rings.lazy_series.LazyPowerSeries method), 236

add_bigoh() (sage.rings.multi_power_series_ring_element.MPowerSeries method), 116

add_bigoh() (sage.rings.power_series_ring_element.PowerSeries method), 24

add_bigoh() (sage.rings.puiseux_series_ring_element.PuiseuxSeries method), 330

algebra_of_series() (sage.rings.tate_algebra.TateTermMonoid method), 356

approximate_series() (sage.rings.lazy_series.LazyLaurentSeries method), 181

arccos() (sage.rings.lazy_series.LazyModuleElement method), 199

arccot() (sage.rings.lazy_series.LazyModuleElement method), 200

arcsin() (sage.rings.lazy_series.LazyModuleElement method), 201

arcsinh() (sage.rings.lazy_series.LazyModuleElement method), 201

arctan() (sage.rings.lazy_series.LazyModuleElement method), 202

arctanh() (sage.rings.lazy_series.LazyModuleElement method), 202

arithmetic_product() (sage.rings.lazy_series.LazySymmetricFunction method), 254

B

base_extend() (sage.rings.laurent_series_ring.LaurentSeriesRing method), 140

base_extend() (sage.rings.power_series_ring_element.PowerSeries method), 24

base_extend() (sage.rings.power_series_ring.PowerSeriesRing_generic method), 9

base_extend() (sage.rings.puiseux_series_ring.PuiseuxSeriesRing method), 321

base_ring() (sage.rings.power_series_ring_element.PowerSeries method), 25

base_ring() (sage.rings.tate_algebra.TateTermMonoid method), 356

BaseRingFloorDivAction (class in sage.rings.power_series_poly), 69

bigoh() (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 98

C

change_ring() (sage.rings.laurent_series_ring_element.LaurentSeries method), 149

change_ring() (sage.rings.laurent_series_ring.LaurentSeriesRing method), 140

change_ring() (sage.rings.lazy_series.LazyModuleElement method), 203

change_ring() (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 99

change_ring() (sage.rings.power_series_ring_element.PowerSeries method), 25

change_ring() (sage.rings.power_series_ring.PowerSeriesRing_generic method), 9

change_ring() (sage.rings.puiseux_series_ring_element.PuiseuxSeries method), 331

change_ring() (sage.rings.puiseux_series_ring.PuiseuxSeriesRing method), 322

change_var() (sage.rings.power_series_ring.PowerSeriesRing_generic method), 10

characteristic() (sage.rings.laurent_series_ring.LaurentSeriesRing method), 140

characteristic() (sage.rings.lazy_series_ring.LazySeriesRing method), 302

characteristic() (sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method), 100

characteristic() (sage.rings.power_series_ring.PowerSeriesRing_generic method), 10

`characteristic()` (*sage.rings.tate_algebra.TateAlgebra_generic method*), 348
`coefficient()` (*sage.rings.lazy_series.LazyModuleElement method*), 205
`coefficients()` (*sage.rings.laurent_series_ring_element.LaurentSeries method*), 150
`coefficients()` (*sage.rings.lazy_series.LazyModuleElement method*), 206
`coefficients()` (*sage.rings.multi_power_series_ring_element.MPowerSeries method*), 117
`coefficients()` (*sage.rings.power_series_ring_element.PowerSeries method*), 26
`coefficients()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries method*), 332
`common_prec()` (*sage.rings.laurent_series_ring_element.LaurentSeries method*), 150
`common_prec()` (*sage.rings.power_series_ring_element.PowerSeries method*), 27
`common_prec()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries method*), 332
`common_valuation()` (*sage.rings.laurent_series_ring_element.LaurentSeries method*), 151
`compose()` (*sage.rings.lazy_series.LazyLaurentSeries method*), 182
`compose()` (*sage.rings.lazy_series.LazyPowerSeries method*), 237
`compositional_inverse()` (*sage.rings.lazy_series.LazyLaurentSeries method*), 193
`compositional_inverse()` (*sage.rings.lazy_series.LazyPowerSeries method*), 241
`compositional_inverse()` (*sage.rings.lazy_series.LazySymmetricFunction method*), 256
`compute_coefficients()` (*sage.rings.lazy_series.LazyPowerSeries method*), 241
`constant_coefficient()` (*sage.rings.multi_power_series_ring_element.MPowerSeries method*), 118
`construction()` (*sage.rings.laurent_series_ring.LaurentSeriesRing method*), 141
`construction()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing method*), 297
`construction()` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic method*), 100
`construction()` (*sage.rings.power_series_ring.PowerSeriesRing_generic method*), 11
`cos()` (*sage.rings.lazy_series.LazyModuleElement method*), 208
`cos()` (*sage.rings.power_series_ring_element.PowerSeries method*), 28
`cosh()` (*sage.rings.lazy_series.LazyModuleElement method*), 208
`cosh()` (*sage.rings.power_series_ring_element.Pow-*

erSeries method), 29

`cot()` (*sage.rings.lazy_series.LazyModuleElement method*), 209
`coth()` (*sage.rings.lazy_series.LazyModuleElement method*), 209
`create_key()` (*sage.rings.tate_algebra.TateAlgebraFactory method*), 346
`create_object()` (*sage.rings.tate_algebra.TateAlgebraFactory method*), 347
`csc()` (*sage.rings.lazy_series.LazyModuleElement method*), 209
`csch()` (*sage.rings.lazy_series.LazyModuleElement method*), 210

D

`default_prec()` (*sage.rings.laurent_series_ring.LaurentSeriesRing method*), 142
`default_prec()` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing method*), 322
`define()` (*sage.rings.lazy_series.LazyModuleElement method*), 210
`define_implicitly()` (*sage.rings.lazy_series_ring.LazySeriesRing method*), 303
`degree()` (*sage.rings.laurent_series_ring_element.LaurentSeries method*), 153
`degree()` (*sage.rings.multi_power_series_ring_element.MPowerSeries method*), 118
`degree()` (*sage.rings.power_series_poly.PowerSeries_poly method*), 70
`degree()` (*sage.rings.power_series_ring_element.PowerSeries method*), 31
`degree()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries method*), 332
`derivative()` (*sage.rings.laurent_series_ring_element.LaurentSeries method*), 153
`derivative()` (*sage.rings.lazy_series.LazyLaurentSeries method*), 193
`derivative()` (*sage.rings.lazy_series.LazyPowerSeries method*), 241
`derivative()` (*sage.rings.multi_power_series_ring_element.MPowerSeries method*), 118
`derivative()` (*sage.rings.power_series_ring_element.PowerSeries method*), 31
`derivative_with_respect_to_p1()` (*sage.rings.lazy_series.LazySymmetricFunction method*), 256
`dict()` (*sage.rings.multi_power_series_ring_element.MPowerSeries method*), 119
`dict()` (*sage.rings.power_series_pari.PowerSeries_pari method*), 83
`dict()` (*sage.rings.power_series_poly.PowerSeries_poly method*), 70
`dilog()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing method*), 280

`dilog()` (*sage.rings.lazy_series.LazyModuleElement* method), 215

E

`egf()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 119

`egf_to_ogf()` (*sage.rings.power_series_ring_element.PowerSeries* method), 32

`Element` (*sage.rings.laurent_series_ring.LaurentSeriesRing* attribute), 140

`Element` (*sage.rings.lazy_series_ring.LazyCompletionGradedAlgebra* attribute), 269

`Element` (*sage.rings.lazy_series_ring.LazyDirichletSeriesRing* attribute), 271

`Element` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* attribute), 280

`Element` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* attribute), 297

`Element` (*sage.rings.lazy_series_ring.LazySymmetricFunctions* attribute), 319

`Element` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* attribute), 98

`Element` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* attribute), 321

`Element` (*sage.rings.tate_algebra.TateTermMonoid* attribute), 355

`euler()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 281

`euler()` (*sage.rings.lazy_series.LazyModuleElement* method), 216

`exp()` (*sage.rings.lazy_series.LazyCauchyProductSeries* method), 175

`exp()` (*sage.rings.lazy_series.LazyModuleElement* method), 216

`exp()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 119

`exp()` (*sage.rings.power_series_ring_element.PowerSeries* method), 32

`exponential()` (*sage.rings.lazy_series.LazyPowerSeries* method), 244

`exponents()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 154

`exponents()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 121

`exponents()` (*sage.rings.power_series_ring_element.PowerSeries* method), 35

`exponents()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 333

F

`fraction_field()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 142

`fraction_field()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 297

`fraction_field()` (*sage.rings.power_series_ring.PowerSeriesRing_domain* method), 9

`fraction_field()` (*sage.rings.power_series_ring.PowerSeriesRing_over_field* method), 17

`fraction_field()` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 322

`functorial_composition()` (*sage.rings.lazy_series.LazySymmetricFunction* method), 257

G

`gcd()` (*sage.rings.lazy_series.LazyPowerSeries_gcd_mixin* method), 251

`gen()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 143

`gen()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 282

`gen()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 298

`gen()` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 101

`gen()` (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 11

`gen()` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 323

`gen()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 348

`gen()` (*sage.rings.tate_algebra.TateTermMonoid* method), 357

`gens()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 143

`gens()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 282

`gens()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 298

`gens()` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 101

`gens()` (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 12

`gens()` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 323

`gens()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 349

`gens()` (*sage.rings.tate_algebra.TateTermMonoid* method), 358

H

`hypergeometric()` (*sage.rings.lazy_series.LazyModuleElement* method), 216

I

`integer_ring()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 349

`integral()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 155

```

integral() (sage.rings.lazy_series.LazyLaurentSeries
            method), 193
integral() (sage.rings.lazy_series.LazyPowerSeries
            method), 244
integral() (sage.rings.multi_power_series_ring_ele-
            ment.MPowerSeries method), 121
integral() (sage.rings.power_series_pari.Pow-
            erSeries_pari method), 83
integral() (sage.rings.power_series_poly.Pow-
            erSeries_poly method), 70
inverse() (sage.rings.laurent_series_ring_element.Lau-
            rentSeries method), 156
inverse() (sage.rings.power_series_ring_element.Pow-
            erSeries method), 35
inverse() (sage.rings.puiseux_series_ring_ele-
            ment.PuiseuxSeries method), 333
is_dense() (sage.rings.laurent_series_ring.Lau-
            rentSeriesRing method), 143
is_dense() (sage.rings.multi_power_series_ring.MPow-
            erSeriesRing_generic method), 101
is_dense() (sage.rings.power_series_ring_element.Pow-
            erSeries method), 36
is_dense() (sage.rings.power_series_ring.PowerSeries-
            Ring_generic method), 12
is_dense() (sage.rings.puiseux_se-
            ries_ring.PuiseuxSeriesRing method), 324
is_exact() (sage.rings.laurent_series_ring.Lau-
            rentSeriesRing method), 143
is_exact() (sage.rings.lazy_series_ring.LazySeriesRing
            method), 311
is_exact() (sage.rings.power_series_ring.PowerSeries-
            Ring_generic method), 12
is_field() (sage.rings.laurent_series_ring.Lau-
            rentSeriesRing method), 144
is_field() (sage.rings.power_series_ring.PowerSeries-
            Ring_generic method), 13
is_field() (sage.rings.puiseux_se-
            ries_ring.PuiseuxSeriesRing method), 324
is_finite() (sage.rings.power_series_ring.PowerSeries-
            Ring_generic method), 13
is_gen() (sage.rings.power_series_ring_element.Pow-
            erSeries method), 36
is_integral_domain() (sage.rings.tate_alge-
            bra.TateAlgebra_generic method), 350
is_LaurentSeries() (in module sage.rings.laurent_se-
            ries_ring_element), 170
is_LaurentSeriesRing() (in module sage.rings.lau-
            rent_series_ring), 146
is_monomial() (sage.rings.laurent_series_ring_ele-
            ment.LaurentSeries method), 156
is_monomial() (sage.rings.power_series_ring_ele-
            ment.PowerSeries method), 37
is_monomial() (sage.rings.puiseux_series_ring_ele-
            ment.PuiseuxSeries method), 333
is_MPowerSeries() (in module
            sage.rings.multi_power_series_ring_element),
            136
is_MPowerSeriesRing() (in module
            sage.rings.multi_power_series_ring), 105
is_nilpotent() (sage.rings.multi_power_se-
            ries_ring_element.MPowerSeries method),
            123
is_noetherian() (sage.rings.multi_power_se-
            ries_ring.MPowerSeriesRing_generic method),
            102
is_nonzero() (sage.rings.lazy_series.LazyModuleEle-
            ment method), 217
is_PowerSeries() (in module sage.rings.power_se-
            ries_ring_element), 66
is_PowerSeriesRing() (in module
            sage.rings.power_series_ring), 18
is_sparse() (sage.rings.laurent_series_ring.Lau-
            rentSeriesRing method), 144
is_sparse() (sage.rings.lazy_series_ring.LazySeriesRing
            method), 311
is_sparse() (sage.rings.multi_power_series_ring.MPow-
            erSeriesRing_generic method), 102
is_sparse() (sage.rings.power_series_ring_ele-
            ment.PowerSeries method), 37
is_sparse() (sage.rings.power_series_ring.PowerSeries-
            Ring_generic method), 13
is_sparse() (sage.rings.puiseux_se-
            ries_ring.PuiseuxSeriesRing method), 324
is_square() (sage.rings.multi_power_series_ring_ele-
            ment.MPowerSeries method), 125
is_square() (sage.rings.power_series_ring_ele-
            ment.PowerSeries method), 38
is_trivial_zero() (sage.rings.lazy_series.LazyMod-
            uleElement method), 219
is_unit() (sage.rings.laurent_series_ring_element.Lau-
            rentSeries method), 157
is_unit() (sage.rings.lazy_series.LazyDirichletSeries
            method), 178
is_unit() (sage.rings.lazy_series.LazyLaurentSeries
            method), 195
is_unit() (sage.rings.lazy_series.LazyPowerSeries
            method), 248
is_unit() (sage.rings.lazy_series.LazySymmetricFunc-
            tion method), 260
is_unit() (sage.rings.multi_power_series_ring_ele-
            ment.MPowerSeries method), 125
is_unit() (sage.rings.power_series_ring_element.Pow-
            erSeries method), 38
is_unit() (sage.rings.puiseux_series_ring_ele-
            ment.PuiseuxSeries method), 334
is_zero() (sage.rings.laurent_series_ring_element.Lau-
            rentSeries method), 158
is_zero() (sage.rings.puiseux_series_ring_ele-

```

ment.PuiseuxSeries method), 334

J

jacobi_continued_fraction() (*sage.rings.power_series_ring_element.PowerSeries* method), 39
jacobi_theta() (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 282
jacobi_theta() (*sage.rings.lazy_series.LazyModuleElement* method), 219

L

laurent_part() (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 335
laurent_polynomial() (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 158
laurent_polynomial_ring() (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 144
laurent_series() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 125
laurent_series() (*sage.rings.power_series_ring_element.PowerSeries* method), 40
laurent_series() (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 335
laurent_series_ring() (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 103
laurent_series_ring() (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 14
laurent_series_ring() (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 325
LaurentSeries (class in *sage.rings.laurent_series_ring_element*), 148
LaurentSeriesRing (class in *sage.rings.laurent_series_ring*), 137
LazyCauchyProductSeries (class in *sage.rings.lazy_series*), 174
LazyCompletionGradedAlgebra (class in *sage.rings.lazy_series_ring*), 267
LazyCompletionGradedAlgebraElement (class in *sage.rings.lazy_series*), 177
LazyDirichletSeries (class in *sage.rings.lazy_series*), 177
LazyDirichletSeriesRing (class in *sage.rings.lazy_series_ring*), 270
LazyLaurentSeries (class in *sage.rings.lazy_series*), 179
LazyLaurentSeriesRing (class in *sage.rings.lazy_series_ring*), 273
LazyModuleElement (class in *sage.rings.lazy_series*), 198

LazyPowerSeries (class in *sage.rings.lazy_series*), 235
LazyPowerSeries_gcd_mixin (class in *sage.rings.lazy_series*), 251
LazyPowerSeriesRing (class in *sage.rings.lazy_series_ring*), 296
LazySeriesRing (class in *sage.rings.lazy_series_ring*), 302
LazySymmetricFunction (class in *sage.rings.lazy_series*), 253
LazySymmetricFunctions (class in *sage.rings.lazy_series_ring*), 318
legendre_transform() (*sage.rings.lazy_series.LazySymmetricFunction* method), 260
lift_to_precision() (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 158
lift_to_precision() (*sage.rings.lazy_series.LazyModuleElement* method), 220
lift_to_precision() (*sage.rings.power_series_ring_element.PowerSeries* method), 40
list() (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 159
list() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 125
list() (*sage.rings.power_series_pari.PowerSeries_pari* method), 83
list() (*sage.rings.power_series_poly.PowerSeries_poly* method), 71
list() (*sage.rings.power_series_ring_element.PowerSeries* method), 41
list() (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 336
log() (*sage.rings.lazy_series.LazyCauchyProductSeries* method), 176
log() (*sage.rings.lazy_series.LazyModuleElement* method), 221
log() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 125
log() (*sage.rings.power_series_ring_element.PowerSeries* method), 41
log_radII() (*sage.rings.tate_algebra.TateAlgebra_generic* method), 350
log_radII() (*sage.rings.tate_algebra.TateTermMonoid* method), 358

M

make_element_from_parent_v0() (in module *sage.rings.power_series_ring_element*), 67
make_powerseries_poly_v0() (in module *sage.rings.power_series_poly*), 78
make_powerseries_poly_v0() (in module *sage.rings.power_series_ring_element*), 67
map_coefficients() (*sage.rings.lazy_series.LazyModuleElement* method), 221

map_coefficients() (*sage.rings.power_series_ring_element.PowerSeries* method), 42

MO (*class in sage.rings.multi_power_series_ring_element*), 112

module

- sage.rings.laurent_series_ring, 137
- sage.rings.laurent_series_ring_element, 147
- sage.rings.lazy_series, 171
- sage.rings.lazy_series_ring, 267
- sage.rings.multi_power_series_ring, 91
- sage.rings.multi_power_series_ring_element, 107
- sage.rings.power_series_pari, 81
- sage.rings.power_series_poly, 69
- sage.rings.power_series_ring, 1
- sage.rings.power_series_ring_element, 21
- sage.rings.puiseux_series_ring, 321
- sage.rings.puiseux_series_ring_element, 327
- sage.rings.tate_algebra, 341

monoid_of_terms() (*sage.rings.tate_algebra.TateAlgebra_generic* method), 351

monomial_coefficients() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 127

monomial_coefficients() (*sage.rings.power_series_pari.PowerSeries_pari* method), 84

monomial_coefficients() (*sage.rings.power_series_poly.PowerSeries_poly* method), 71

monomials() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 128

MPowerSeries (*class in sage.rings.multi_power_series_ring_element*), 113

MPowerSeriesRing_generic (*class in sage.rings.multi_power_series_ring*), 98

N

ngens() (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 144

ngens() (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 289

ngens() (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 298

ngens() (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 103

ngens() (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 14

ngens() (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 325

ngens() (*sage.rings.tate_algebra.TateAlgebra_generic* method), 351

ngens() (*sage.rings.tate_algebra.TateTermMonoid* method), 358

nth_root() (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 159

nth_root() (*sage.rings.power_series_ring_element.PowerSeries* method), 44

O

O() (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 148

O() (*sage.rings.lazy_series.LazyLaurentSeries* method), 181

O() (*sage.rings.lazy_series.LazyPowerSeries* method), 235

O() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 115

O() (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 98

O() (*sage.rings.power_series_ring_element.PowerSeries* method), 23

ogf() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 128

ogf_to_egf() (*sage.rings.power_series_ring_element.PowerSeries* method), 45

one() (*sage.rings.lazy_series_ring.LazyDirichletSeriesRing* method), 271

one() (*sage.rings.lazy_series_ring.LazySeriesRing* method), 311

options (*sage.rings.lazy_series_ring.LazySeriesRing* attribute), 312

P

padded_list() (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 128

padded_list() (*sage.rings.power_series_pari.PowerSeries_pari* method), 84

padded_list() (*sage.rings.power_series_ring_element.PowerSeries* method), 46

pade() (*sage.rings.power_series_poly.PowerSeries_poly* method), 72

plethysm() (*sage.rings.lazy_series.LazySymmetricFunction* method), 261

plethystic_inverse() (*sage.rings.lazy_series.LazySymmetricFunction* method), 264

polylog() (*sage.rings.lazy_series_ring.LazyDirichletSeriesRing* method), 271

polylog() (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 289

polylog() (*sage.rings.lazy_series.LazyModuleElement* method), 223

polylogarithm() (*sage.rings.lazy_series_ring.LazyDirichletSeriesRing* method), 271

polynomial() (*sage.rings.lazy_series.LazyLaurentSeries* method), 196

polynomial() (*sage.rings.lazy_series.LazyPowerSeries* method), 249

`polynomial()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 128
`polynomial()` (*sage.rings.power_series_pari.PowerSeries_pari* method), 85
`polynomial()` (*sage.rings.power_series_poly.PowerSeries_poly* method), 73
`polynomial()` (*sage.rings.power_series_ring_element.PowerSeries* method), 47
`polynomial_ring()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 144
`power_series()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 160
`power_series()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 336
`power_series_ring()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 145
`PowerSeries` (class in *sage.rings.power_series_ring_element*), 23
`PowerSeries_pari` (class in *sage.rings.power_series_pari*), 83
`PowerSeries_poly` (class in *sage.rings.power_series_poly*), 69
`PowerSeriesRing()` (in module *sage.rings.power_series_ring*), 4
`PowerSeriesRing_domain` (class in *sage.rings.power_series_ring*), 8
`PowerSeriesRing_generic` (class in *sage.rings.power_series_ring*), 9
`PowerSeriesRing_over_field` (class in *sage.rings.power_series_ring*), 17
`prec()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 160
`prec()` (*sage.rings.lazy_series.LazyModuleElement* method), 224
`prec()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 130
`prec()` (*sage.rings.power_series_ring_element.PowerSeries* method), 47
`prec()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 337
`prec_ideal()` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 103
`precision_absolute()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 161
`precision_absolute()` (*sage.rings.power_series_ring_element.PowerSeries* method), 48
`precision_absolute()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 337
`precision_cap()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 351
`precision_relative()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method),

161

`precision_relative()` (*sage.rings.power_series_ring_element.PowerSeries* method), 48
`precision_relative()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 337
`prime()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 352
`prime()` (*sage.rings.tate_algebra.TateTermMonoid* method), 359
`prod()` (*sage.rings.lazy_series_ring.LazySeriesRing* method), 312
`PuiseuxSeries` (class in *sage.rings.puiseux_series_ring_element*), 329
`PuiseuxSeriesRing` (class in *sage.rings.puiseux_series_ring*), 321

Q

`q_pochhammer()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 291
`q_pochhammer()` (*sage.rings.lazy_series.LazyModuleElement* method), 224
`quo_rem()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 130

R

`ramification_index()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 337
`random_element()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 145
`random_element()` (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 14
`random_element()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 352
`remove_var()` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 103
`residue()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 162
`residue_field()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 145
`residue_field()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 292
`residue_field()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 298
`residue_field()` (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 16
`residue_field()` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 325
`restrict()` (*sage.rings.lazy_series.LazyModuleElement* method), 225
`reverse()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 162
`reverse()` (*sage.rings.power_series_pari.PowerSeries_pari* method), 86

`reverse()` (*sage.rings.power_series_poly.PowerSeries_poly* method), 73

`revert()` (*sage.rings.lazy_series.LazyLaurentSeries* method), 196

`revert()` (*sage.rings.lazy_series.LazyPowerSeries* method), 250

`revert()` (*sage.rings.lazy_series.LazySymmetricFunction* method), 264

S

`sage.rings.laurent_series_ring`
module, 137

`sage.rings.laurent_series_ring_element`
module, 147

`sage.rings.lazy_series`
module, 171

`sage.rings.lazy_series_ring`
module, 267

`sage.rings.multi_power_series_ring`
module, 91

`sage.rings.multi_power_series_ring_element`
module, 107

`sage.rings.power_series_pari`
module, 81

`sage.rings.power_series_poly`
module, 69

`sage.rings.power_series_ring`
module, 1

`sage.rings.power_series_ring_element`
module, 21

`sage.rings.puiseux_series_ring`
module, 321

`sage.rings.puiseux_series_ring_element`
module, 327

`sage.rings.tate_algebra`
module, 341

`sec()` (*sage.rings.lazy_series.LazyModuleElement* method), 226

`sech()` (*sage.rings.lazy_series.LazyModuleElement* method), 226

`series()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 293

`set()` (*sage.rings.lazy_series.LazyModuleElement* method), 227

`shift()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 166

`shift()` (*sage.rings.lazy_series.LazyModuleElement* method), 227

`shift()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 133

`shift()` (*sage.rings.power_series_ring_element.PowerSeries* method), 49

`shift()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 338

`sin()` (*sage.rings.lazy_series.LazyModuleElement* method), 230

`sin()` (*sage.rings.power_series_ring_element.PowerSeries* method), 49

`sinh()` (*sage.rings.lazy_series.LazyModuleElement* method), 231

`sinh()` (*sage.rings.power_series_ring_element.PowerSeries* method), 51

`solve_linear_de()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 133

`solve_linear_de()` (*sage.rings.power_series_ring_element.PowerSeries* method), 52

`some_elements()` (*sage.rings.lazy_series_ring.LazyCompletionGradedAlgebra* method), 269

`some_elements()` (*sage.rings.lazy_series_ring.LazyDirichletSeriesRing* method), 272

`some_elements()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 294

`some_elements()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 299

`some_elements()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 354

`some_elements()` (*sage.rings.tate_algebra.TateTermMonoid* method), 359

`sqrt()` (*sage.rings.lazy_series.LazyModuleElement* method), 231

`sqrt()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 133

`sqrt()` (*sage.rings.power_series_ring_element.PowerSeries* method), 54

`square_root()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 133

`square_root()` (*sage.rings.power_series_ring_element.PowerSeries* method), 57

`stieltjes_continued_fraction()`
(*sage.rings.power_series_ring_element.PowerSeries* method), 58

`sum()` (*sage.rings.lazy_series_ring.LazySeriesRing* method), 314

`super_delta_fraction()` (*sage.rings.power_series_ring_element.PowerSeries* method), 59

`suspension()` (*sage.rings.lazy_series.LazySymmetricFunction* method), 265

`symmetric_function()` (*sage.rings.lazy_series.LazySymmetricFunction* method), 265

T

`tan()` (*sage.rings.lazy_series.LazyModuleElement* method), 232

`tan()` (*sage.rings.power_series_ring_element.PowerSeries* method), 60

`tanh()` (*sage.rings.lazy_series.LazyModuleElement* method), 233

`tanh()` (*sage.rings.power_series_ring_element.PowerSeries* method), 62
`TateAlgebra_generic` (class in *sage.rings.tate_algebra*), 347
`TateAlgebraFactory` (class in *sage.rings.tate_algebra*), 344
`TateTermMonoid` (class in *sage.rings.tate_algebra*), 355
`taylor()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 295
`taylor()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 300
`term_order()` (*sage.rings.multi_power_series_ring.MPowerSeriesRing_generic* method), 104
`term_order()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 355
`term_order()` (*sage.rings.tate_algebra.TateTermMonoid* method), 359
`trailing_monomial()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 133
`truncate()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 167
`truncate()` (*sage.rings.lazy_series.LazyModuleElement* method), 233
`truncate()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 133
`truncate()` (*sage.rings.power_series_poly.PowerSeries_poly* method), 77
`truncate()` (*sage.rings.power_series_ring_element.PowerSeries* method), 64
`truncate()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 338
`truncate_laurentseries()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 167
`truncate_neg()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 168
`truncate_powerseries()` (*sage.rings.power_series_poly.PowerSeries_poly* method), 78

U

`undefined()` (*sage.rings.lazy_series_ring.LazySeriesRing* method), 316
`uniformizer()` (*sage.rings.laurent_series_ring.LaurentSeriesRing* method), 146
`uniformizer()` (*sage.rings.lazy_series_ring.LazyLaurentSeriesRing* method), 296
`uniformizer()` (*sage.rings.lazy_series_ring.LazyPowerSeriesRing* method), 301
`uniformizer()` (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 16
`uniformizer()` (*sage.rings.puiseux_series_ring.PuiseuxSeriesRing* method), 326
`unknown()` (*sage.rings.lazy_series_ring.LazySeriesRing* method), 317

`unpickle_multi_power_series_ring_v0()` (in module *sage.rings.multi_power_series_ring*), 105
`unpickle_power_series_ring_v0()` (in module *sage.rings.power_series_ring*), 18

V

`V()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 149
`V()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 116
`V()` (*sage.rings.power_series_ring_element.PowerSeries* method), 24
`valuation()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 168
`valuation()` (*sage.rings.lazy_series.LazyCauchyProductSeries* method), 176
`valuation()` (*sage.rings.lazy_series.LazyDirichletSeries* method), 178
`valuation()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 134
`valuation()` (*sage.rings.power_series_pari.PowerSeries_pari* method), 88
`valuation()` (*sage.rings.power_series_poly.PowerSeries_poly* method), 78
`valuation()` (*sage.rings.power_series_ring_element.PowerSeries* method), 64
`valuation()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 339
`valuation_zero_part()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 169
`valuation_zero_part()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 135
`valuation_zero_part()` (*sage.rings.power_series_ring_element.PowerSeries* method), 65
`variable()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 169
`variable()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 135
`variable()` (*sage.rings.power_series_ring_element.PowerSeries* method), 66
`variable()` (*sage.rings.puiseux_series_ring_element.PuiseuxSeries* method), 339
`variable_names()` (*sage.rings.tate_algebra.TateAlgebra_generic* method), 355
`variable_names()` (*sage.rings.tate_algebra.TateTermMonoid* method), 360
`variable_names_recursive()` (*sage.rings.power_series_ring.PowerSeriesRing_generic* method), 17
`variables()` (*sage.rings.multi_power_series_ring_element.MPowerSeries* method), 135
`verschiebung()` (*sage.rings.laurent_series_ring_element.LaurentSeries* method), 169

X

`xgcd()` (*sage.rings.lazy_series.LazyPowerSeries_gcd_mixin method*), [251](#)

Z

`zero()` (*sage.rings.lazy_series_ring.LazySeriesRing method*), [317](#)