
Quivers

Release 10.8

The Sage Development Team

Dec 23, 2025

CONTENTS

1	Path Algebras	1
2	Path algebra elements	13
3	Auslander-Reiten Quivers	27
4	Quiver Homspace	39
5	Quiver Morphisms	45
6	Path Semigroups	61
7	Quiver Paths	75
8	Quiver Representations	83
9	Indices and Tables	125
	Python Module Index	127
	Index	129

PATH ALGEBRAS

class sage.quivers.algebra.**PathAlgebra**(*k*, *P*, *order*='negdegrevlex')

Bases: `CombinatorialFreeModule`

Create the path algebra of a `quiver` over a given field.

Given a quiver Q and a field k , the path algebra kQ is defined as follows. As a vector space it has basis the set of all paths in Q . Multiplication is defined on this basis and extended bilinearly. If p is a path with terminal vertex t and q is a path with initial vertex i then the product $p * q$ is defined to be the composition of the paths p and q if $t = i$ and 0 otherwise.

INPUT:

- k – field (or commutative ring), the base field of the path algebra
- P – the path semigroup of a quiver Q
- *order* – string; one of 'negdegrevlex' (default), 'degrevlex', 'negdeglex' or 'deglex', defining the monomial order to be used

OUTPUT: the path algebra kP with the given monomial order

Note

Monomial orders that are not degree orders are not supported.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a']}, 2:{3:['b']}}).path_semigroup()
sage: A = P.algebra(GF(7))
sage: A
Path algebra of Multi-digraph on 3 vertices over Finite Field of size 7
sage: A.variable_names()
('e_1', 'e_2', 'e_3', 'a', 'b')
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b']}}).
↳path_semigroup()
>>> A = P.algebra(GF(Integer(7)))
>>> A
Path algebra of Multi-digraph on 3 vertices over Finite Field of size 7
>>> A.variable_names()
('e_1', 'e_2', 'e_3', 'a', 'b')
```

Note that path algebras are uniquely defined by their quiver, field and monomial order:

```
sage: A is P.algebra(GF(7))
True
sage: A is P.algebra(GF(7), order='degrevlex')
False
sage: A is P.algebra(RR)
False
sage: A is DiGraph({1:{2:['a']}}).path_semigroup().algebra(GF(7))
False
```

```
>>> from sage.all import *
>>> A is P.algebra(GF(Integer(7)))
True
>>> A is P.algebra(GF(Integer(7)), order='degrevlex')
False
>>> A is P.algebra(RR)
False
>>> A is DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup().
↪ algebra(GF(Integer(7)))
False
```

The path algebra of an acyclic quiver has a finite basis:

```
sage: A.dimension()
6
sage: list(A.basis())
[e_1, e_2, e_3, a, b, a*b]
```

```
>>> from sage.all import *
>>> A.dimension()
6
>>> list(A.basis())
[e_1, e_2, e_3, a, b, a*b]
```

The path algebra can create elements from paths or from elements of the base ring:

```
sage: A(5)
5*e_1 + 5*e_2 + 5*e_3
sage: S = A.semigroup()
sage: S
Partial semigroup formed by the directed paths of Multi-digraph on 3 vertices
sage: p = S([(1, 2, 'a')])
sage: r = S([(2, 3, 'b')])
sage: e2 = S([(2, 2)])
sage: x = A(p) + A(e2)
sage: x
a + e_2
sage: y = A(p) + A(r)
sage: y
a + b
```

```

>>> from sage.all import *
>>> A(Integer(5))
5*e_1 + 5*e_2 + 5*e_3
>>> S = A.semigroup()
>>> S
Partial semigroup formed by the directed paths of Multi-digraph on 3 vertices
>>> p = S([(Integer(1), Integer(2), 'a')])
>>> r = S([(Integer(2), Integer(3), 'b')])
>>> e2 = S([(Integer(2), Integer(2))])
>>> x = A(p) + A(e2)
>>> x
a + e_2
>>> y = A(p) + A(r)
>>> y
a + b
    
```

Path algebras are graded algebras. The grading is given by assigning to each basis element the length of the path corresponding to that basis element:

```

sage: x.is_homogeneous()
False
sage: x.degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
sage: y.is_homogeneous()
True
sage: y.degree()
1
sage: A[1]
Free module spanned by [a, b] over Finite Field of size 7
sage: A[2]
Free module spanned by [a*b] over Finite Field of size 7
    
```

```

>>> from sage.all import *
>>> x.is_homogeneous()
False
>>> x.degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
>>> y.is_homogeneous()
True
>>> y.degree()
1
>>> A[Integer(1)]
Free module spanned by [a, b] over Finite Field of size 7
>>> A[Integer(2)]
Free module spanned by [a*b] over Finite Field of size 7
    
```

Element

alias of *PathAlgebraElement*

arrows ()

Return the arrows of this algebra (corresponding to edges of the underlying quiver).

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a']}, 2:{3:['b', 'c']}, 4:{}}).path_semigroup()
sage: A = P.algebra(GF(5))
sage: A.arrows()
(a, b, c)
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b',
↪ 'c']}, Integer(4):{}}).path_semigroup()
>>> A = P.algebra(GF(Integer(5)))
>>> A.arrows()
(a, b, c)
```

degree_on_basis(x)

Return `x.degree()`.

This function is here to make some methods work that are inherited from `CombinatorialFreeModule`.

EXAMPLES:

```
sage: A = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}).path_semigroup().algebra(ZZ)
sage: A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: X = a+2*b+3*c*e-a*d+5*e_0+3*e_2
sage: X
5*e_0 + a - a*d + 2*b + 3*e_2
sage: X.homogeneous_component(0) # indirect doctest
5*e_0 + 3*e_2
sage: X.homogeneous_component(1)
a + 2*b
sage: X.homogeneous_component(2)
-a*d
sage: X.homogeneous_component(3)
0
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):
↪ {Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'],
↪ Integer(2):['f']}}).path_semigroup().algebra(ZZ)
>>> A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> X = a+Integer(2)*b+Integer(3)*c*e-a*d+Integer(5)*e_0+Integer(3)*e_2
>>> X
5*e_0 + a - a*d + 2*b + 3*e_2
>>> X.homogeneous_component(Integer(0)) # indirect doctest
5*e_0 + 3*e_2
>>> X.homogeneous_component(Integer(1))
a + 2*b
>>> X.homogeneous_component(Integer(2))
```

(continues on next page)

(continued from previous page)

```
-a*d
>>> X.homogeneous_component(Integer(3))
0
```

gen(*i*)

Return the *i*-th generator of this algebra.

This is an idempotent (corresponding to a trivial path at a vertex) if $i < n$ (where n is the number of vertices of the quiver), and a single-edge path otherwise.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a']}, 2:{3:['b', 'c']}, 4:{}}).path_semigroup()
sage: A = P.algebra(GF(5))
sage: A.gens()
(e_1, e_2, e_3, e_4, a, b, c)
sage: A.gen(2)
e_3
sage: A.gen(5)
b
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b',
↪ 'c']}, Integer(4):{}}).path_semigroup()
>>> A = P.algebra(GF(Integer(5)))
>>> A.gens()
(e_1, e_2, e_3, e_4, a, b, c)
>>> A.gen(Integer(2))
e_3
>>> A.gen(Integer(5))
b
```

gens()

Return the generators of this algebra (idempotents and arrows).

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a']}, 2:{3:['b', 'c']}, 4:{}}).path_semigroup()
sage: A = P.algebra(GF(5))
sage: A.variable_names()
('e_1', 'e_2', 'e_3', 'e_4', 'a', 'b', 'c')
sage: A.gens()
(e_1, e_2, e_3, e_4, a, b, c)
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b',
↪ 'c']}, Integer(4):{}}).path_semigroup()
>>> A = P.algebra(GF(Integer(5)))
>>> A.variable_names()
('e_1', 'e_2', 'e_3', 'e_4', 'a', 'b', 'c')
>>> A.gens()
(e_1, e_2, e_3, e_4, a, b, c)
```

homogeneous_component (*n*)

Return the *n*-th homogeneous piece of the path algebra.

INPUT:

- *n* – integer

OUTPUT:

- `CombinatorialFreeModule`, module spanned by the paths of length *n* in the quiver

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a'], 3:['b']}, 2:{4:['c']}, 3:{4:['d']}}).path_
↪semigroup()
sage: A = P.algebra(GF(7))
sage: A.homogeneous_component(2)
Free module spanned by [a*c, b*d] over Finite Field of size 7

sage: D = DiGraph({1: {2: 'a'}, 2: {3: 'b'}, 3: {1: 'c'}})
sage: P = D.path_semigroup()
sage: A = P.algebra(ZZ)
sage: A.homogeneous_component(3)
Free module spanned by [a*b*c, b*c*a, c*a*b] over Integer Ring
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↪{Integer(4):['c']}, Integer(3):{Integer(4):['d']}}).path_semigroup()
>>> A = P.algebra(GF(Integer(7)))
>>> A.homogeneous_component(Integer(2))
Free module spanned by [a*c, b*d] over Finite Field of size 7

>>> D = DiGraph({Integer(1): {Integer(2): 'a'}, Integer(2): {Integer(3): 'b'},
↪ Integer(3): {Integer(1): 'c'}})
>>> P = D.path_semigroup()
>>> A = P.algebra(ZZ)
>>> A.homogeneous_component(Integer(3))
Free module spanned by [a*b*c, b*c*a, c*a*b] over Integer Ring
```

homogeneous_components ()

Return the nonzero homogeneous components of self.

EXAMPLES:

```
sage: Q = DiGraph([[1,2,'a'],[2,3,'b'],[3,4,'c']])
sage: PQ = Q.path_semigroup()
sage: A = PQ.algebra(GF(7))
sage: A.homogeneous_components()
[Free module spanned by [e_1, e_2, e_3, e_4] over Finite Field of size 7,
Free module spanned by [a, b, c] over Finite Field of size 7,
Free module spanned by [a*b, b*c] over Finite Field of size 7,
Free module spanned by [a*b*c] over Finite Field of size 7]
```

```
>>> from sage.all import *
>>> Q = DiGraph([[Integer(1),Integer(2),'a'],[Integer(2),Integer(3),'b'],
↪[Integer(3),Integer(4),'c']])
```

(continues on next page)

(continued from previous page)

```
>>> PQ = Q.path_semigroup()
>>> A = PQ.algebra(GF(Integer(7)))
>>> A.homogeneous_components()
[Free module spanned by [e_1, e_2, e_3, e_4] over Finite Field of size 7,
Free module spanned by [a, b, c] over Finite Field of size 7,
Free module spanned by [a*b, b*c] over Finite Field of size 7,
Free module spanned by [a*b*c] over Finite Field of size 7]
```

Warning

Backward incompatible change: since [Issue #12630](#) and until [Issue #8678](#), this feature was implemented under the syntax `list(A)` by means of `A.__iter__`. This was incorrect since `A.__iter__`, when defined for a parent, should iterate through the elements of `A`.

`idempotents()`

Return the idempotents of this algebra (corresponding to vertices of the underlying quiver).

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a']}, 2:{3:['b', 'c']}, 4:{}}).path_semigroup()
sage: A = P.algebra(GF(5))
sage: A.idempotents()
(e_1, e_2, e_3, e_4)
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b',
↳ 'c']}, Integer(4):{}}).path_semigroup()
>>> A = P.algebra(GF(Integer(5)))
>>> A.idempotents()
(e_1, e_2, e_3, e_4)
```

`linear_combination(iter_of_elements_coeff, factor_on_left=True)`

Return the linear combination $\lambda_1 v_1 + \cdots + \lambda_k v_k$ (resp. the linear combination $v_1 \lambda_1 + \cdots + v_k \lambda_k$) where `iter_of_elements_coeff` iterates through the sequence $((v_1, \lambda_1), \dots, (v_k, \lambda_k))$.

INPUT:

- `iter_of_elements_coeff` – iterator of pairs (element, coeff) with element in self and coeff in self.base_ring()
- `factor_on_left` – (optional) if True, the coefficients are multiplied from the left if False, the coefficients are multiplied from the right

Note

It overrides a method inherited from `CombinatorialFreeModule`, which relies on a private attribute of elements—an implementation detail that is simply not available for `PathAlgebraElement`.

EXAMPLES:

```
sage: A = DiGraph({0: {1: ['a'], 2: ['b']},
.....:           1: {0: ['c'], 1: ['d']},
.....:           2: {0: ['e'], 2: ['f']}}).path_semigroup().algebra(ZZ)
sage: A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: A.linear_combination([(a, 1), (b, 2), (c*e, 3),
.....:                    (a*d, -1), (e_0, 5), (e_2, 3)])
5*e_0 + a - a*d + 2*b + 3*e_2
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(0): {Integer(1): ['a'], Integer(2): ['b']},
...              Integer(1): {Integer(0): ['c'], Integer(1): ['d']},
...              Integer(2): {Integer(0): ['e'], Integer(2): ['f']}}).path_
↳semigroup().algebra(ZZ)
>>> A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> A.linear_combination([(a, Integer(1)), (b, Integer(2)), (c*e, Integer(3)),
...                      (a*d, -Integer(1)), (e_0, Integer(5)), (e_2,
↳Integer(3))])
5*e_0 + a - a*d + 2*b + 3*e_2
```

ngens()

Number of generators of this algebra.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a']}, 2:{3:['b', 'c']}, 4:{}}).path_semigroup()
sage: A = P.algebra(GF(5))
sage: A.ngens()
7
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b',
↳'c']}, Integer(4):{}}).path_semigroup()
>>> A = P.algebra(GF(Integer(5)))
>>> A.ngens()
7
```

one()

Return the multiplicative identity element.

The multiplicative identity of a path algebra is the sum of the basis elements corresponding to the trivial paths at each vertex.

EXAMPLES:

```
sage: A = DiGraph({1:{2:['a']}, 2:{3:['b']}}).path_semigroup().algebra(QQ)
sage: A.one()
e_1 + e_2 + e_3
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b']}}
↳).path_semigroup().algebra(QQ)
```

(continues on next page)

(continued from previous page)

```
>>> A.one()
e_1 + e_2 + e_3
```

order_string()

Return the string that defines the monomial order of this algebra.

EXAMPLES:

```
sage: P1 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'))
sage: P2 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳ order='degrevlex')
sage: P3 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳ order='negdeglex')
sage: P4 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳ order='deglex')
sage: P1.order_string()
'negdegrevlex'
sage: P2.order_string()
'degrevlex'
sage: P3.order_string()
'negdeglex'
sage: P4.order_string()
'deglex'
```

```
>>> from sage.all import *
>>> P1 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'))
>>> P2 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P3 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'), order='negdeglex')
>>> P4 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'), order='deglex')
>>> P1.order_string()
'negdegrevlex'
>>> P2.order_string()
'degrevlex'
>>> P3.order_string()
'negdeglex'
>>> P4.order_string()
'deglex'
```

quiver()

Return the quiver from which the algebra `self` was formed.

OUTPUT: `DiGraph`; the quiver of the algebra

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a','b']}}).path_semigroup()
sage: A = P.algebra(GF(3))
sage: A.quiver() is P.quiver()
True
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> A = P.algebra(GF(Integer(3)))
>>> A.quiver() is P.quiver()
True
```

semigroup()

Return the (partial) semigroup from which the algebra `self` was constructed.

Note

The partial semigroup is formed by the paths of a quiver, multiplied by concatenation. If the quiver has more than a single vertex, then multiplication in the path semigroup is not always defined.

OUTPUT:

- the path semigroup from which `self` was formed (a partial semigroup)

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: A = P.algebra(GF(3))
sage: A.semigroup() is P
True
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> A = P.algebra(GF(Integer(3)))
>>> A.semigroup() is P
True
```

sum(iter_of_elements)

Return the sum of all elements in `iter_of_elements`.

INPUT:

- `iter_of_elements` – iterator of elements of `self`

Note

It overrides a method inherited from `CombinatorialFreeModule`, which relies on a private attribute of elements—an implementation detail that is simply not available for `PathAlgebraElement`.

EXAMPLES:

```
sage: A = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}).path_semigroup().algebra(ZZ)
sage: A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: A.sum((a, 2*b, 3*c*e, -a*d, 5*e_0, 3*e_2))
5*e_0 + a - a*d + 2*b + 3*e_2
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):
↳{Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'],
↳Integer(2):['f']}}).path_semigroup().algebra(ZZ)
>>> A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> A.sum((a, Integer(2)*b, Integer(3)*c*e, -a*d, Integer(5)*e_0,
↳Integer(3)*e_2))
5*e_0 + a - a*d + 2*b + 3*e_2
```


PATH ALGEBRA ELEMENTS

AUTHORS:

- Simon King (2015-08)

class sage.quivers.algebra_elements.**PathAlgebraElement**

Bases: `RingElement`

Elements of a *PathAlgebra*.

Note

Upon creation of a path algebra, one can choose among several monomial orders, which are all positive or negative degree orders. Monomial orders that are not degree orders are not supported.

EXAMPLES:

After creating a path algebra and getting hold of its generators, one can create elements just as usual:

```
sage: A = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'],2:['f']}}
↪).path_semigroup().algebra(ZZ)
sage: A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: x = a+2*b+3*c+5*e_0+3*e_2
sage: x
5*e_0 + a + 2*b + 3*c + 3*e_2
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):
↪{Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'],Integer(2):[
↪'f']}}).path_semigroup().algebra(ZZ)
>>> A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> x = a+Integer(2)*b+Integer(3)*c+Integer(5)*e_0+Integer(3)*e_2
>>> x
5*e_0 + a + 2*b + 3*c + 3*e_2
```

The path algebra decomposes as a direct sum according to start- and endpoints:

```
sage: x.sort_by_vertices()
[(5*e_0, 0, 0),
 (a, 0, 1),
```

(continues on next page)

(continued from previous page)

```
(2*b, 0, 2),
(3*c, 1, 0),
(3*e_2, 2, 2)]
sage: (x^3+x^2).sort_by_vertices()
[(150*e_0 + 33*a*c, 0, 0),
(30*a + 3*a*c*a, 0, 1),
(114*b + 6*a*c*b, 0, 2),
(90*c + 9*c*a*c, 1, 0),
(18*c*a, 1, 1),
(54*c*b, 1, 2),
(36*e_2, 2, 2)]
```

```
>>> from sage.all import *
>>> x.sort_by_vertices()
[(5*e_0, 0, 0),
(a, 0, 1),
(2*b, 0, 2),
(3*c, 1, 0),
(3*e_2, 2, 2)]
>>> (x**Integer(3)+x**Integer(2)).sort_by_vertices()
[(150*e_0 + 33*a*c, 0, 0),
(30*a + 3*a*c*a, 0, 1),
(114*b + 6*a*c*b, 0, 2),
(90*c + 9*c*a*c, 1, 0),
(18*c*a, 1, 1),
(54*c*b, 1, 2),
(36*e_2, 2, 2)]
```

For a consistency test, we create a path algebra that is isomorphic to a free associative algebra, and compare arithmetic with two other implementations of free algebras (note that the letterplace implementation only allows weighted homogeneous elements):

```
sage: F.<x,y,z> = FreeAlgebra(GF(25,'t'))
sage: pF = x+y*z*x+2*y-z+1
sage: pF2 = x^4+x*y*x*z+2*z^2*x*y
sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'))
sage: pP = sage_eval('x+y*z*x+2*y-z+1', P.gens_dict())
sage: pP^5+3*pP^3 == sage_eval(repr(pF^5+3*pF^3), P.gens_dict())
True
sage: L.<x,y,z> = FreeAlgebra(GF(25,'t'), implementation='letterplace')
sage: pL2 = x^4+x*y*x*z+2*z^2*x*y
sage: pP2 = sage_eval('x^4+x*y*x*z+2*z^2*x*y', P.gens_dict())
sage: pP2^7 == sage_eval(repr(pF2^7), P.gens_dict())
True
sage: pP2^7 == sage_eval(repr(pL2^7), P.gens_dict())
True
```

```
>>> from sage.all import *
>>> F = FreeAlgebra(GF(Integer(25),'t'), names=('x', 'y', 'z')); (x, y, z) = F._
    ↪first_gens(3)
>>> pF = x+y*z*x+Integer(2)*y-z+Integer(1)
>>> pF2 = x**Integer(4)+x*y*x*z+Integer(2)*z**Integer(2)*x*y
```

(continues on next page)

(continued from previous page)

```

>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'))
>>> pP = sage_eval('x+y*z*x+2*y-z+1', P.gens_dict())
>>> pP**Integer(5)+Integer(3)*pP**Integer(3) == sage_
↳ eval(repr(pF**Integer(5)+Integer(3)*pF**Integer(3)), P.gens_dict())
True
>>> L = FreeAlgebra(GF(Integer(25),'t'), implementation='letterplace', names=('x',
↳ 'y', 'z',)); (x, y, z) = L._first_ngens(3)
>>> pL2 = x**Integer(4)+x*y*x*z+Integer(2)*z**Integer(2)*x*y
>>> pP2 = sage_eval('x^4+x*y*x*z+2*z^2*x*y', P.gens_dict())
>>> pP2**Integer(7) == sage_eval(repr(pF2**Integer(7)), P.gens_dict())
True
>>> pP2**Integer(7) == sage_eval(repr(pL2**Integer(7)), P.gens_dict())
True

```

When the Cython implementation of path algebra elements was introduced, it was faster than both the default implementation and the letterplace implementation of free algebras. The following timings were obtained with a 32-bit operating system; using 64-bit on the same machine, the letterplace implementation has not become faster, but the timing for path algebra elements has improved by about 20%:

```

sage: # not tested
sage: timeit('pF^5+3*pF^3')
1 loops, best of 3: 338 ms per loop
sage: timeit('pP^5+3*pP^3')
100 loops, best of 3: 2.55 ms per loop
sage: timeit('pF2^7')
10000 loops, best of 3: 513 ms per loop
sage: timeit('pL2^7')
125 loops, best of 3: 1.99 ms per loop
sage: timeit('pP2^7')
10000 loops, best of 3: 1.54 ms per loop

```

```

>>> from sage.all import *
>>> # not tested
>>> timeit('pF^5+3*pF^3')
1 loops, best of 3: 338 ms per loop
>>> timeit('pP^5+3*pP^3')
100 loops, best of 3: 2.55 ms per loop
>>> timeit('pF2^7')
10000 loops, best of 3: 513 ms per loop
>>> timeit('pL2^7')
125 loops, best of 3: 1.99 ms per loop
>>> timeit('pP2^7')
10000 loops, best of 3: 1.54 ms per loop

```

So, if one is merely interested in basic arithmetic operations for free associative algebras, it could make sense to model the free associative algebra as a path algebra. However, standard basis computations are not available for path algebras, yet. Hence, to implement computations in graded quotients of free algebras, the letterplace implementation currently is the only option.

coefficient(P)

Return the coefficient of a monomial.

INPUT:

- p – an element of the underlying partial semigroup

OUTPUT:

The coefficient of the given semigroup element in `self`, or zero if it does not appear.

EXAMPLES:

```
sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳order='degrevlex')
sage: P.inject_variables()
Defining e_1, x, y, z
sage: p = (x+2*z+1)^3
sage: p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
sage: p.coefficient(sage_eval('x*x*z', P.semigroup().gens_dict()))
2
sage: p.coefficient(sage_eval('z*x*x*x', P.semigroup().gens_dict()))
0
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P.inject_variables()
Defining e_1, x, y, z
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
>>> p.coefficient(sage_eval('x*x*z', P.semigroup().gens_dict()))
2
>>> p.coefficient(sage_eval('z*x*x*x', P.semigroup().gens_dict()))
0
```

coefficients()

Return the list of coefficients.

Note

The order in which the coefficients are returned corresponds to the order in which the terms are printed. That is *not* the same as the order given by the monomial order, since the terms are first ordered according to initial and terminal vertices, before applying the monomial order of the path algebra.

EXAMPLES:

```
sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳order='degrevlex')
sage: P.inject_variables()
Defining e_1, x, y, z
sage: p = (x+2*z+1)^3
sage: p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
```

(continues on next page)

(continued from previous page)

```
sage: p.coefficients()
[3, 4, 4, 2, 4, 2, 2, 1, 2, 1, 1, 3, 1, 3, 1]
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P.inject_variables()
Defining e_1, x, y, z
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
>>> p.coefficients()
[3, 4, 4, 2, 4, 2, 2, 1, 2, 1, 1, 3, 1, 3, 1]
```

degree()

Return the degree, provided the element is homogeneous.

An error is raised if the element is not homogeneous.

EXAMPLES:

```
sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'))
sage: P.inject_variables()
Defining e_1, x, y, z
sage: q = (x+y+2*z)^3
sage: q.degree()
3
sage: p = (x+2*z+1)^3
sage: p.degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'))
>>> P.inject_variables()
Defining e_1, x, y, z
>>> q = (x+y+Integer(2)*z)**Integer(3)
>>> q.degree()
3
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p.degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
```

is_homogeneous()

Tell whether this element is homogeneous.

EXAMPLES:

```
sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'))
sage: P.inject_variables()
Defining e_1, x, y, z
sage: q = (x+y+2*z)^3
sage: q.is_homogeneous()
True
sage: p = (x+2*z+1)^3
sage: p.is_homogeneous()
False
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'))
>>> P.inject_variables()
Defining e_1, x, y, z
>>> q = (x+y+Integer(2)*z)**Integer(3)
>>> q.is_homogeneous()
True
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p.is_homogeneous()
False
```

monomial_coefficients()

Return the dictionary keyed by the monomials appearing in this element, the values being the coefficients.

EXAMPLES:

```
sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳ order='degrevlex')
sage: P.inject_variables()
Defining e_1, x, y, z
sage: p = (x+2*z+1)^3
sage: sorted(p.monomial_coefficients().items())
[(x*x*x, 1),
 (z*x*x, 2),
 (x*z*x, 2),
 (z*z*x, 4),
 (x*x*z, 2),
 (z*x*z, 4),
 (x*z*z, 4),
 (z*z*z, 3),
 (x*x, 3),
 (z*x, 1),
 (x*z, 1),
 (z*z, 2),
 (x, 3),
 (z, 1),
 (e_1, 1)]
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P.inject_variables()
```

(continues on next page)

(continued from previous page)

```

Defining e_1, x, y, z
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> sorted(p.monomial_coefficients().items())
[(x*x*x, 1),
 (z*x*x, 2),
 (x*z*x, 2),
 (z*z*x, 4),
 (x*x*z, 2),
 (z*x*z, 4),
 (x*z*z, 4),
 (z*z*z, 3),
 (x*x, 3),
 (z*x, 1),
 (x*z, 1),
 (z*z, 2),
 (x, 3),
 (z, 1),
 (e_1, 1)]
    
```

Note that the dictionary can be fed to the algebra, to reconstruct the element:

```

sage: P(p.monomial_coefficients()) == p
True
    
```

```

>>> from sage.all import *
>>> P(p.monomial_coefficients()) == p
True
    
```

monomials()

Return the list of monomials appearing in this element.

Note

The order in which the monomials are returned corresponds to the order in which the element's terms are printed. That is *not* the same as the order given by the monomial order, since the terms are first ordered according to initial and terminal vertices, before applying the monomial order of the path algebra.

The monomials are not elements of the underlying partial semigroup, but of the algebra.

See also

[*support\(\)*](#)

EXAMPLES:

```

sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳order='degrevlex')
sage: P.inject_variables()
Defining e_1, x, y, z
sage: p = (x+2*z+1)^3
    
```

(continues on next page)

(continued from previous page)

```

sage: p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↪ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
sage: p.monomials()
[z*z*z,
 x*z*z,
 z*x*z,
 x*x*z,
 z*z*x,
 x*z*x,
 z*x*x,
 x*x*x,
 z*z,
 x*z,
 z*x,
 x*x,
 z,
 x,
 e_1]
sage: p.monomials()[1].parent() is P
True

```

```

>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↪ algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P.inject_variables()
Defining e_1, x, y, z
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↪ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
>>> p.monomials()
[z*z*z,
 x*z*z,
 z*x*z,
 x*x*z,
 z*z*x,
 x*z*x,
 z*x*x,
 x*x*x,
 z*z,
 x*z,
 z*x,
 x*x,
 z,
 x,
 e_1]
>>> p.monomials()[Integer(1)].parent() is P
True

```

sort_by_vertices()

Return a list of triples (element, v1, v2), where element is an element whose monomials all have

initial vertex `v1` and terminal vertex `v2`, so that the sum of elements is `self`.

EXAMPLES:

```
sage: A1 = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}).path_semigroup().algebra(ZZ.quo(15))
sage: A1.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: x = (b*e*b*e+4*b+e_0)^2
sage: y = (a*c*b+1)^3
sage: x.sort_by_vertices()
[(e_0 + 2*b*e*b*e + b*e*b*e*b*e*b*e, 0, 0), (4*b + 4*b*e*b*e*b, 0, 2)]
sage: sum(c[0] for c in x.sort_by_vertices()) == x
True
sage: y.sort_by_vertices()
[(e_0, 0, 0), (3*a*c*b, 0, 2), (e_1, 1, 1), (e_2, 2, 2)]
sage: sum(c[0] for c in y.sort_by_vertices()) == y
True
```

```
>>> from sage.all import *
>>> A1 = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):{Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'], Integer(2):['f']}}).path_semigroup().algebra(ZZ.quo(Integer(15)))
>>> A1.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> x = (b*e*b*e+Integer(4)*b+e_0)**Integer(2)
>>> y = (a*c*b+Integer(1))**Integer(3)
>>> x.sort_by_vertices()
[(e_0 + 2*b*e*b*e + b*e*b*e*b*e*b*e, 0, 0), (4*b + 4*b*e*b*e*b, 0, 2)]
>>> sum(c[Integer(0)] for c in x.sort_by_vertices()) == x
True
>>> y.sort_by_vertices()
[(e_0, 0, 0), (3*a*c*b, 0, 2), (e_1, 1, 1), (e_2, 2, 2)]
>>> sum(c[Integer(0)] for c in y.sort_by_vertices()) == y
True
```

support()

Return the list of monomials, as elements of the underlying partial semigroup.

Note

The order in which the monomials are returned corresponds to the order in which the element's terms are printed. That is *not* the same as the order given by the monomial order, since the terms are first ordered according to initial and terminal vertices, before applying the monomial order of the path algebra.

See also

`monomials()`

EXAMPLES:

```

sage: P = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↳order='degrevlex')
sage: P.inject_variables()
Defining e_1, x, y, z
sage: p = (x+2*z+1)^3
sage: p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
sage: p.support()
[z*z*z,
 x*z*z,
 z*x*z,
 x*x*z,
 z*z*x,
 x*z*x,
 z*x*x,
 x*x*x,
 z*z,
 x*z,
 z*x,
 x*x,
 z,
 x,
 e_1]
sage: p.support()[1].parent() is P.semigroup()
True

```

```

>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P.inject_variables()
Defining e_1, x, y, z
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
>>> p.support()
[z*z*z,
 x*z*z,
 z*x*z,
 x*x*z,
 z*z*x,
 x*z*x,
 z*x*x,
 x*x*x,
 z*z,
 x*z,
 z*x,
 x*x,
 z,
 x,
 e_1]

```

(continues on next page)

(continued from previous page)

```
>>> p.support()[Integer(1)].parent() is P.semigroup()
True
```

support_of_term()

If self consists of a single term, return the corresponding element of the underlying path semigroup.

EXAMPLES:

```
sage: A = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}).path_semigroup().algebra(ZZ)
sage: A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: x = 4*a*d*c*b*e
sage: x.support_of_term()
a*d*c*b*e
sage: x.support_of_term().parent() is A.semigroup()
True
sage: (x + f).support_of_term()
Traceback (most recent call last):
...
ValueError: 4*a*d*c*b*e + f is not a single term
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):{Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'], Integer(2):['f']}}).path_semigroup().algebra(ZZ)
>>> A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> x = Integer(4)*a*d*c*b*e
>>> x.support_of_term()
a*d*c*b*e
>>> x.support_of_term().parent() is A.semigroup()
True
>>> (x + f).support_of_term()
Traceback (most recent call last):
...
ValueError: 4*a*d*c*b*e + f is not a single term
```

terms()

Return the list of terms.

Note

The order in which the terms are returned corresponds to the order in which they are printed. That is *not* the same as the order given by the monomial order, since the terms are first ordered according to initial and terminal vertices, before applying the monomial order of the path algebra.

EXAMPLES:

```
sage: P = DiGraph({1:{1:['x', 'y', 'z']}}).path_semigroup().algebra(GF(25, 't'), order='degrevlex')
```

(continues on next page)

(continued from previous page)

```
sage: P.inject_variables()
Defining e_1, x, y, z
sage: p = (x+2*z+1)^3
sage: p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↪ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
sage: p.terms()
[3*z*z*z,
 4*x*z*z,
 4*z*x*z,
 2*x*x*z,
 4*z*z*x,
 2*x*z*x,
 2*z*x*x,
 x*x*x,
 2*z*z,
 x*z,
 z*x,
 3*x*x,
 z,
 3*x,
 e_1]
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↪ algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P.inject_variables()
Defining e_1, x, y, z
>>> p = (x+Integer(2)*z+Integer(1))**Integer(3)
>>> p
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↪ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
>>> p.terms()
[3*z*z*z,
 4*x*z*z,
 4*z*x*z,
 2*x*x*z,
 4*z*z*x,
 2*x*z*x,
 2*z*x*x,
 x*x*x,
 2*z*z,
 x*z,
 z*x,
 3*x*x,
 z,
 3*x,
 e_1]
```

`sage.quivers.algebra_elements.path_algebra_element_unpickle(P, data)`

Auxiliary function for unpickling.

EXAMPLES:

```
sage: A = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}
↪).path_semigroup().algebra(ZZ.quo(15), order='negdeglex')
sage: A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: X = a+2*b+3*c+5*e_0+3*e_2
sage: loads(dumps(X)) == X      # indirect doctest
True
```

```
>>> from sage.all import *
>>> A = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):
↪{Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'], Integer(2):[
↪'f']}}).path_semigroup().algebra(ZZ.quo(Integer(15)), order='negdeglex')
>>> A.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> X = a+Integer(2)*b+Integer(3)*c+Integer(5)*e_0+Integer(3)*e_2
>>> loads(dumps(X)) == X      # indirect doctest
True
```


AUSLANDER-REITEN QUIVERS

```
class sage.quivers.ar_quiver.AuslanderReitenQuiver(quiver)
```

Bases: UniqueRepresentation, Parent

The Auslander-Reiten quiver.

Let $Q = (Q_0, Q_1)$ be a finite acyclic quiver. The *Auslander-Reiten quiver* (AR quiver) Γ_Q is the quiver whose vertices correspond to the indecomposable modules of Q (equivalently its path algebra over an algebraically closed field) and edges are irreducible morphisms.

In this implementation, we denote the vertices of Γ_Q as certain pairs $\langle v, k \rangle$, where $v \in Q_0$ and $k \in \mathbb{Z} \setminus \{0\}$ is called the *level*. When $k > 0$ (resp. $k < 0$), then it corresponds to a preprojective (resp. postinjective) module. When the quiver is a finite type Dynkin quiver, we consider all modules to be preprojectives and denoted by a positive level.

Note

We use the terminology *postinjective* instead of *preinjective* given that they follow from injectives by AR translation.

ALGORITHM:

We compute the dimension vectors of a projective $\langle v, 1 \rangle$ by counting the number of (directed) paths $u \rightarrow v$ in Q . We then proceed inductively to compute all of the dimension vectors of level k by using the translation equation

$$\dim \langle v, k-1 \rangle + \dim \langle v, k \rangle = \sum_{u, k'} \dim \langle u, k' \rangle,$$

where the sum is over all paths from $\langle v, k-1 \rangle$ to $\langle v, k \rangle$ in Γ_Q . More specifically, for each edge $(u, v, \ell) \in Q_1$ (resp. $(v, u, \ell) \in Q_1$), we have $\langle u, k-1 \rangle$ (resp. $\langle u, k \rangle$) in the sum (assuming the node is in the AR quiver).

The algorithm for postinjectives is dual to the above.

Todo

This only is implemented for the preprojectives and postinjectives when the quiver is not a finite type Dynkin quiver.

Todo

Implement this for general Artinian algebras.

EXAMPLES:

We create the AR quivers for finite type A_3 Dynkin quivers:

```
sage: DA = DiGraph([[1, 2], [2, 3]])
sage: AR = DA.auslander_reiten_quiver()
sage: AR.digraph().edges(labels=False)
[(<1, 1>, <2, 2>), (<2, 1>, <1, 1>), (<2, 1>, <3, 2>), (<3, 1>, <2, 1>),
 (<2, 2>, <3, 3>), (<3, 2>, <2, 2>)]

sage: DA = DiGraph([[1, 2], [3, 2]])
sage: AR = DA.auslander_reiten_quiver()
sage: AR.digraph().edges(labels=False)
[(<1, 1>, <2, 2>), (<2, 1>, <1, 1>), (<2, 1>, <3, 1>), (<3, 1>, <2, 2>),
 (<2, 2>, <1, 2>), (<2, 2>, <3, 2>)]

sage: DA = DiGraph([[2, 1], [2, 3]])
sage: AR = DA.auslander_reiten_quiver()
sage: AR.digraph().edges(labels=False)
[(<1, 1>, <2, 1>), (<2, 1>, <1, 2>), (<2, 1>, <3, 2>), (<3, 1>, <2, 1>),
 (<1, 2>, <2, 2>), (<3, 2>, <2, 2>)]

sage: DA = DiGraph([[2, 1], [3, 2]])
sage: AR = DA.auslander_reiten_quiver()
sage: AR.digraph().edges(labels=False)
[(<1, 1>, <2, 1>), (<2, 1>, <3, 1>), (<2, 1>, <1, 2>), (<3, 1>, <2, 2>),
 (<1, 2>, <2, 2>), (<2, 2>, <1, 3>)]
```

```
>>> from sage.all import *
>>> DA = DiGraph([[Integer(1), Integer(2)], [Integer(2), Integer(3)]])
>>> AR = DA.auslander_reiten_quiver()
>>> AR.digraph().edges(labels=False)
[(<1, 1>, <2, 2>), (<2, 1>, <1, 1>), (<2, 1>, <3, 2>), (<3, 1>, <2, 1>),
 (<2, 2>, <3, 3>), (<3, 2>, <2, 2>)]

>>> DA = DiGraph([[Integer(1), Integer(2)], [Integer(3), Integer(2)]])
>>> AR = DA.auslander_reiten_quiver()
>>> AR.digraph().edges(labels=False)
[(<1, 1>, <2, 2>), (<2, 1>, <1, 1>), (<2, 1>, <3, 1>), (<3, 1>, <2, 2>),
 (<2, 2>, <1, 2>), (<2, 2>, <3, 2>)]

>>> DA = DiGraph([[Integer(2), Integer(1)], [Integer(2), Integer(3)]])
>>> AR = DA.auslander_reiten_quiver()
>>> AR.digraph().edges(labels=False)
[(<1, 1>, <2, 1>), (<2, 1>, <1, 2>), (<2, 1>, <3, 2>), (<3, 1>, <2, 1>),
 (<1, 2>, <2, 2>), (<3, 2>, <2, 2>)]

>>> DA = DiGraph([[Integer(2), Integer(1)], [Integer(3), Integer(2)]])
>>> AR = DA.auslander_reiten_quiver()
>>> AR.digraph().edges(labels=False)
[(<1, 1>, <2, 1>), (<2, 1>, <3, 1>), (<2, 1>, <1, 2>), (<3, 1>, <2, 2>),
 (<1, 2>, <2, 2>), (<2, 2>, <1, 3>)]
```

An example for the type D_5 Dynkin quiver:

```
sage: DD = DiGraph([[5,3], [4,3], [3,2], [2,1]])
sage: AR = DD.auslander_reiten_quiver()
sage: AR
Auslander-Reiten quiver of a ['D', 5] Dynkin quiver
sage: len(list(DD))
5
```

```
>>> from sage.all import *
>>> DD = DiGraph([[Integer(5),Integer(3)], [Integer(4),Integer(3)], [Integer(3),
↪Integer(2)], [Integer(2),Integer(1)]])
>>> AR = DD.auslander_reiten_quiver()
>>> AR
Auslander-Reiten quiver of a ['D', 5] Dynkin quiver
>>> len(list(DD))
5
```

An E_8 Dynkin quiver:

```
sage: DE = DiGraph([[8,7], [7,6], [5,6], [5,3], [3,4], [3,2], [2,1]])
sage: AR = DE.auslander_reiten_quiver()
sage: AR
Auslander-Reiten quiver of a ['E', 8] Dynkin quiver
sage: len(list(AR))
120
sage: len(list(RootSystem(['E', 8]).root_lattice().positive_roots()))
120
```

```
>>> from sage.all import *
>>> DE = DiGraph([[Integer(8),Integer(7)], [Integer(7),Integer(6)], [Integer(5),
↪Integer(6)], [Integer(5),Integer(3)], [Integer(3),Integer(4)], [Integer(3),
↪Integer(2)], [Integer(2),Integer(1)]])
>>> AR = DE.auslander_reiten_quiver()
>>> AR
Auslander-Reiten quiver of a ['E', 8] Dynkin quiver
>>> len(list(AR))
120
>>> len(list(RootSystem(['E', Integer(8)]).root_lattice().positive_roots()))
120
```

The Kronecker quiver:

```
sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: for i in range(1, 5):
.....:     for v in D.vertices():
.....:         pp = AR(v, i)
.....:         pi = AR(v, -i)
.....:         print(pp, pp.dimension_vector(), " ", pi, pi.dimension_vector())
<1, 1> v1 + 2*v2      <1, -1> v1
<2, 1> v2             <2, -1> 2*v1 + v2
<1, 2> 3*v1 + 4*v2    <1, -2> 3*v1 + 2*v2
<2, 2> 2*v1 + 3*v2    <2, -2> 4*v1 + 3*v2
<1, 3> 5*v1 + 6*v2    <1, -3> 5*v1 + 4*v2
```

(continues on next page)

(continued from previous page)

```
<2, 3> 4*v1 + 5*v2    <2, -3> 6*v1 + 5*v2
<1, 4> 7*v1 + 8*v2    <1, -4> 7*v1 + 6*v2
<2, 4> 6*v1 + 7*v2    <2, -4> 8*v1 + 7*v2
```

```
>>> from sage.all import *
>>> D = DiGraph([[Integer(1), Integer(2), 'a'], [Integer(1), Integer(2), 'b']],
↳ multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> for i in range(Integer(1), Integer(5)):
...     for v in D.vertices():
...         pp = AR(v, i)
...         pi = AR(v, -i)
...         print(pp, pp.dimension_vector(), " ", pi, pi.dimension_vector())
<1, 1> v1 + 2*v2      <1, -1> v1
<2, 1> v2             <2, -1> 2*v1 + v2
<1, 2> 3*v1 + 4*v2    <1, -2> 3*v1 + 2*v2
<2, 2> 2*v1 + 3*v2    <2, -2> 4*v1 + 3*v2
<1, 3> 5*v1 + 6*v2    <1, -3> 5*v1 + 4*v2
<2, 3> 4*v1 + 5*v2    <2, -3> 6*v1 + 5*v2
<1, 4> 7*v1 + 8*v2    <1, -4> 7*v1 + 6*v2
<2, 4> 6*v1 + 7*v2    <2, -4> 8*v1 + 7*v2
```

class Element (*parent, vertex, level*)

Bases: `Element`

A node in the AR quiver.

dimension_vector()

Return the dimension vector of `self`.

EXAMPLES:

```
sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: node = AR(2, -4)
sage: node.dimension_vector()
8*v1 + 7*v2
```

```
>>> from sage.all import *
>>> D = DiGraph([[Integer(1), Integer(2), 'a'], [Integer(1), Integer(2), 'b'
↳ '']], multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> node = AR(Integer(2), -Integer(4))
>>> node.dimension_vector()
8*v1 + 7*v2
```

inverse_translation()

Return the inverse AR translation of `self`.

EXAMPLES:

```
sage: DA = DiGraph([[2,3], [2,1]])
sage: AR = DA.auslander_reiten_quiver()
```

(continues on next page)

(continued from previous page)

```
sage: node = AR(1, 1)
sage: node.inverse_translation()
<1, 2>
sage: node = AR(1, 2)
sage: node.inverse_translation() is None
True

sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: AR(2, -1).inverse_translation() is None
True
```

```
>>> from sage.all import *
>>> DA = DiGraph([[Integer(2), Integer(3)], [Integer(2), Integer(1)]])
>>> AR = DA.auslander_reiten_quiver()
>>> node = AR(Integer(1), Integer(1))
>>> node.inverse_translation()
<1, 2>
>>> node = AR(Integer(1), Integer(2))
>>> node.inverse_translation() is None
True

>>> D = DiGraph([[Integer(1), Integer(2), 'a'], [Integer(1), Integer(2), 'b
↪']], multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> AR(Integer(2), -Integer(1)).inverse_translation() is None
True
```

level()

Return the level of self.

EXAMPLES:

```
sage: DA = DiGraph([[2,3], [2,1]])
sage: AR = DA.auslander_reiten_quiver()
sage: node = AR(1, 2)
sage: node.level()
2
```

```
>>> from sage.all import *
>>> DA = DiGraph([[Integer(2), Integer(3)], [Integer(2), Integer(1)]])
>>> AR = DA.auslander_reiten_quiver()
>>> node = AR(Integer(1), Integer(2))
>>> node.level()
2
```

translation()

Return the AR translation of self.

EXAMPLES:

```
sage: DA = DiGraph([[4,3], [3,2], [2,1]])
sage: AR = DA.auslander_reiten_quiver()
```

(continues on next page)

(continued from previous page)

```
sage: node = AR(1, 1)
sage: node.translation() is None
True
sage: node = AR(1, 2)
sage: node.translation()
<1, 1>
```

```
>>> from sage.all import *
>>> DA = DiGraph([[Integer(4), Integer(3)], [Integer(3), Integer(2)],
↳ [Integer(2), Integer(1)]])
>>> AR = DA.auslander_reiten_quiver()
>>> node = AR(Integer(1), Integer(1))
>>> node.translation() is None
True
>>> node = AR(Integer(1), Integer(2))
>>> node.translation()
<1, 1>
```

vertex()

Return the vertex of the quiver corresponding to `self`.

EXAMPLES:

```
sage: DA = DiGraph([[2, 3], [2, 1]])
sage: AR = DA.auslander_reiten_quiver()
sage: node = AR(1, 2)
sage: node.vertex()
1
```

```
>>> from sage.all import *
>>> DA = DiGraph([[Integer(2), Integer(3)], [Integer(2), Integer(1)]])
>>> AR = DA.auslander_reiten_quiver()
>>> node = AR(Integer(1), Integer(2))
>>> node.vertex()
1
```

digraph (*with_translations=False*)

Return the digraph of `self`.

INPUT:

- `with_translations` – boolean (default: `False`); if `True`, then include the arrows corresponding to the translations

EXAMPLES:

```
sage: DA = DiGraph([[1, 2]])
sage: AR = DA.auslander_reiten_quiver()
sage: G = AR.digraph(); G
Digraph on 3 vertices
sage: G.edges()
[(<1, 1>, <2, 2>, None), (<2, 1>, <1, 1>, None)]
sage: GT = AR.digraph(with_translations=True)
```

(continues on next page)

(continued from previous page)

```
sage: GT.edges()
[(<1, 1>, <2, 2>, None), (<2, 1>, <1, 1>, None), (<2, 2>, <2, 1>, 'ART')]
```

```
>>> from sage.all import *
>>> DA = DiGraph([[Integer(1), Integer(2)]])
>>> AR = DA.auslander_reiten_quiver()
>>> G = AR.digraph(); G
Digraph on 3 vertices
>>> G.edges()
[(<1, 1>, <2, 2>, None), (<2, 1>, <1, 1>, None)]
>>> GT = AR.digraph(with_translations=True)
>>> GT.edges()
[(<1, 1>, <2, 2>, None), (<2, 1>, <1, 1>, None), (<2, 2>, <2, 1>, 'ART')]
```

digraph_postinjectives (*max_depth*, *with_translations=False*)

Return the digraph of postinjectives of self up to *max_depth*.

EXAMPLES:

```
sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: G = AR.digraph_postinjectives(3)
sage: [node.dimension_vector() for node in G]
[5*v1 + 4*v2, 6*v1 + 5*v2, 3*v1 + 2*v2, 4*v1 + 3*v2, v1, 2*v1 + v2]
sage: AR.digraph_postinjectives(0)
Digraph on 0 vertices
```

```
>>> from sage.all import *
>>> D = DiGraph([[Integer(1), Integer(2), 'a'], [Integer(1), Integer(2), 'b']],
↳ multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> G = AR.digraph_postinjectives(Integer(3))
>>> [node.dimension_vector() for node in G]
[5*v1 + 4*v2, 6*v1 + 5*v2, 3*v1 + 2*v2, 4*v1 + 3*v2, v1, 2*v1 + v2]
>>> AR.digraph_postinjectives(Integer(0))
Digraph on 0 vertices
```

digraph_preprojectives (*max_depth*, *with_translations=False*)

Return the digraph of preprojectives of self up to *max_depth*.

EXAMPLES:

```
sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: G = AR.digraph_preprojectives(3)
sage: [node.dimension_vector() for node in G]
[v1 + 2*v2, v2, 3*v1 + 4*v2, 2*v1 + 3*v2, 5*v1 + 6*v2, 4*v1 + 5*v2]
sage: AR.digraph_preprojectives(0)
Digraph on 0 vertices
```

```
>>> from sage.all import *
>>> D = DiGraph([[Integer(1), Integer(2), 'a'], [Integer(1), Integer(2), 'b']],
```

(continues on next page)

(continued from previous page)

```

↪multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> G = AR.digraph_preprojectives(Integer(3))
>>> [node.dimension_vector() for node in G]
[v1 + 2*v2, v2, 3*v1 + 4*v2, 2*v1 + 3*v2, 5*v1 + 6*v2, 4*v1 + 5*v2]
>>> AR.digraph_preprojectives(Integer(0))
Digraph on 0 vertices

```

`dimension_vectors_of_level(k)`

Return a Family of dimension vectors of level k .

EXAMPLES:

```

sage: DA = DiGraph([[4,3], [2,3], [2,1]])
sage: AR = DA.auslander_reiten_quiver()
sage: AR.dimension_vectors_of_level(1)
{1: v1, 2: v1 + v2 + v3, 3: v3, 4: v3 + v4}
sage: AR.dimension_vectors_of_level(3)
{1: v4, 3: v2}
sage: AR.dimension_vectors_of_level(10)
{}
sage: AR.dimension_vectors_of_level(-1)
{1: v1 + v2, 2: v2, 3: v2 + v3 + v4, 4: v4}
sage: AR.dimension_vectors_of_level(-2)
{1: v3 + v4, 2: v1 + v2 + v3 + v4, 3: v1 + v2 + v3, 4: v2 + v3}

sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: AR.dimension_vectors_of_level(1)
{1: v1 + 2*v2, 2: v2}
sage: AR.dimension_vectors_of_level(3)
{1: 5*v1 + 6*v2, 2: 4*v1 + 5*v2}
sage: AR.dimension_vectors_of_level(-1)
{1: v1, 2: 2*v1 + v2}
sage: AR.dimension_vectors_of_level(-3)
{1: 5*v1 + 4*v2, 2: 6*v1 + 5*v2}

```

```

>>> from sage.all import *
>>> DA = DiGraph([[Integer(4),Integer(3)], [Integer(2),Integer(3)],
↪[Integer(2),Integer(1)]])
>>> AR = DA.auslander_reiten_quiver()
>>> AR.dimension_vectors_of_level(Integer(1))
{1: v1, 2: v1 + v2 + v3, 3: v3, 4: v3 + v4}
>>> AR.dimension_vectors_of_level(Integer(3))
{1: v4, 3: v2}
>>> AR.dimension_vectors_of_level(Integer(10))
{}
>>> AR.dimension_vectors_of_level(-Integer(1))
{1: v1 + v2, 2: v2, 3: v2 + v3 + v4, 4: v4}
>>> AR.dimension_vectors_of_level(-Integer(2))
{1: v3 + v4, 2: v1 + v2 + v3 + v4, 3: v1 + v2 + v3, 4: v2 + v3}

```

(continues on next page)

(continued from previous page)

```
>>> D = DiGraph([[Integer(1),Integer(2),'a'], [Integer(1),Integer(2),'b']],
↳multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> AR.dimension_vectors_of_level(Integer(1))
{1: v1 + 2*v2, 2: v2}
>>> AR.dimension_vectors_of_level(Integer(3))
{1: 5*v1 + 6*v2, 2: 4*v1 + 5*v2}
>>> AR.dimension_vectors_of_level(-Integer(1))
{1: v1, 2: 2*v1 + v2}
>>> AR.dimension_vectors_of_level(-Integer(3))
{1: 5*v1 + 4*v2, 2: 6*v1 + 5*v2}
```

injectives()

Return the injectives of self.

EXAMPLES:

```
sage: DE = DiGraph([[7,6], [6,5], [5,3], [4,3], [2,3], [1,2]])
sage: AR = DE.auslander_reiten_quiver()
sage: AR.injectives()
Finite family {1: <1, 9>, 2: <2, 9>, 3: <3, 9>, 4: <4, 9>,
               5: <5, 9>, 6: <6, 9>, 7: <7, 9>}
```

```
>>> from sage.all import *
>>> DE = DiGraph([[Integer(7),Integer(6)], [Integer(6),Integer(5)],
↳[Integer(5),Integer(3)], [Integer(4),Integer(3)], [Integer(2),Integer(3)],
↳[Integer(1),Integer(2)]])
>>> AR = DE.auslander_reiten_quiver()
>>> AR.injectives()
Finite family {1: <1, 9>, 2: <2, 9>, 3: <3, 9>, 4: <4, 9>,
               5: <5, 9>, 6: <6, 9>, 7: <7, 9>}
```

options = Current options for AuslanderReitenQuiver - latex: node

projectives()

Return the projectives of self.

EXAMPLES:

```
sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: AR = D.auslander_reiten_quiver()
sage: AR.projectives()
Finite family {1: <1, 1>, 2: <2, 1>}
```

```
>>> from sage.all import *
>>> D = DiGraph([[Integer(1),Integer(2),'a'], [Integer(1),Integer(2),'b']],
↳multiedges=True)
>>> AR = D.auslander_reiten_quiver()
>>> AR.projectives()
Finite family {1: <1, 1>, 2: <2, 1>}
```

quiver()

Return the quiver defining self.

EXAMPLES:

```
sage: DE = DiGraph([[7,8], [7,6], [5,6], [3,5], [4,3], [2,3], [1,2]])
sage: AR = DE.auslander_reiten_quiver()
sage: AR.quiver() == DE
True
```

```
>>> from sage.all import *
>>> DE = DiGraph([[Integer(7),Integer(8)], [Integer(7),Integer(6)],
↳[Integer(5),Integer(6)], [Integer(3),Integer(5)], [Integer(4),Integer(3)],
↳[Integer(2),Integer(3)], [Integer(1),Integer(2)]])
>>> AR = DE.auslander_reiten_quiver()
>>> AR.quiver() == DE
True
```

simples()

Return the simples of self.

EXAMPLES:

```
sage: DE = DiGraph([[7,8], [7,6], [5,6], [3,5], [4,3], [2,3], [1,2]])
sage: AR = DE.auslander_reiten_quiver()
sage: AR.simples()
Finite family {1: <1, 15>, 2: <1, 14>, 3: <8, 4>, 4: <4, 15>,
5: <8, 3>, 6: <6, 1>, 7: <7, 15>, 8: <8, 1>}
```

```
>>> from sage.all import *
>>> DE = DiGraph([[Integer(7),Integer(8)], [Integer(7),Integer(6)],
↳[Integer(5),Integer(6)], [Integer(3),Integer(5)], [Integer(4),Integer(3)],
↳[Integer(2),Integer(3)], [Integer(1),Integer(2)]])
>>> AR = DE.auslander_reiten_quiver()
>>> AR.simples()
Finite family {1: <1, 15>, 2: <1, 14>, 3: <8, 4>, 4: <4, 15>,
5: <8, 3>, 6: <6, 1>, 7: <7, 15>, 8: <8, 1>}
```

`sage.quivers.ar_quiver.detect_dynkin_quiver(quiver)`

Determine if quiver is a finite type Dynkin quiver.

EXAMPLES:

```
sage: from sage.quivers.ar_quiver import detect_dynkin_quiver
sage: D = DiGraph([[1,2], [2,3], [3,4], [4,0], ['a','b'], ['b','c'], ['c','d'],
↳['c','e']])
sage: detect_dynkin_quiver(D)
D5xA5

sage: D = DiGraph([[1,2,'a'], [1,2,'b']], multiedges=True)
sage: detect_dynkin_quiver(D) is None
True
sage: D = DiGraph([[1,2], [2,3], [1,3]])
sage: detect_dynkin_quiver(D) is None
True
sage: D = DiGraph([[1,2], [1,3], [1,4], [1,5]])
sage: detect_dynkin_quiver(D) is None
```

(continues on next page)

(continued from previous page)

```

True
sage: D = DiGraph([[1,2], [2,3], [2,4], [4,5], [6,4]])
sage: detect_dynkin_quiver(D) is None
True
sage: D = DiGraph([[1,2], [2,3], [3,4], [4,5], [5,6], [6,7], [7,8], [8,9], [0,3]])
sage: detect_dynkin_quiver(D) is None
True
sage: D = DiGraph([[1,2], [2,3], [3,4], [4,5], [5,6], [6,7], [0,4]])
sage: detect_dynkin_quiver(D) is None
True

```

```

>>> from sage.all import *
>>> from sage.quivers.ar_quiver import detect_dynkin_quiver
>>> D = DiGraph([[Integer(1),Integer(2)], [Integer(2),Integer(3)], [Integer(3),
↪Integer(4)], [Integer(4),Integer(0)], ['a','b'], ['b','c'], ['c','d'], ['c','e
↪']]
>>> detect_dynkin_quiver(D)
D5xA5

>>> D = DiGraph([[Integer(1),Integer(2),'a'], [Integer(1),Integer(2),'b']],
↪multiedges=True)
>>> detect_dynkin_quiver(D) is None
True
>>> D = DiGraph([[Integer(1), Integer(2)], [Integer(2), Integer(3)], [Integer(1),
↪Integer(3)]]
>>> detect_dynkin_quiver(D) is None
True
>>> D = DiGraph([[Integer(1),Integer(2)], [Integer(1),Integer(3)], [Integer(1),
↪Integer(4)], [Integer(1),Integer(5)]]
>>> detect_dynkin_quiver(D) is None
True
>>> D = DiGraph([[Integer(1),Integer(2)], [Integer(2),Integer(3)], [Integer(2),
↪Integer(4)], [Integer(4),Integer(5)], [Integer(6),Integer(4)]]
>>> detect_dynkin_quiver(D) is None
True
>>> D = DiGraph([[Integer(1),Integer(2)], [Integer(2),Integer(3)], [Integer(3),
↪Integer(4)], [Integer(4),Integer(5)], [Integer(5),Integer(6)], [Integer(6),
↪Integer(7)], [Integer(7),Integer(8)], [Integer(8),Integer(9)], [Integer(0),
↪Integer(3)]]
>>> detect_dynkin_quiver(D) is None
True
>>> D = DiGraph([[Integer(1),Integer(2)], [Integer(2),Integer(3)], [Integer(3),
↪Integer(4)], [Integer(4),Integer(5)], [Integer(5),Integer(6)], [Integer(6),
↪Integer(7)], [Integer(0),Integer(4)]]
>>> detect_dynkin_quiver(D) is None
True

```


QUIVER HOMSPACE

class sage.quivers.homspace.**QuiverHomSpace** (domain, codomain, category=None)

Bases: Homset

A homomorphism of quiver representations (of one and the same quiver) is given by specifying, for each vertex of the quiver, a homomorphism of the spaces assigned to this vertex such that these homomorphisms commute with the edge maps. This class handles the set of all such maps, $\text{Hom}_Q(M, N)$.

INPUT:

- domain – the domain of the homomorphism space
- codomain – the codomain of the homomorphism space

OUTPUT:

- *QuiverHomSpace*, the homomorphism space $\text{Hom}_Q(\text{domain}, \text{codomain})$

Note

The quivers of the domain and codomain must be equal or a `ValueError` is raised.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: H = Q.S(QQ, 2).Hom(Q.P(QQ, 1))
sage: H.dimension()
2
sage: H.gens()
(Homomorphism of representations of Multi-digraph on 2 vertices,
 Homomorphism of representations of Multi-digraph on 2 vertices)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> H = Q.S(QQ, Integer(2)).Hom(Q.P(QQ, Integer(1)))
>>> H.dimension()
2
>>> H.gens()
(Homomorphism of representations of Multi-digraph on 2 vertices,
 Homomorphism of representations of Multi-digraph on 2 vertices)
```

Element

alias of *QuiverRepHom*

`base_ring()`

Return the base ring of the representations.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: H = Q.S(QQ, 2).Hom(Q.P(QQ, 1))
sage: H.base_ring()
Rational Field
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> H = Q.S(QQ, Integer(2)).Hom(Q.P(QQ, Integer(1)))
>>> H.base_ring()
Rational Field
```

`codomain()`

Return the codomain of the hom space.

OUTPUT: `QuiverRep`; the codomain of the Hom space

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: H = Q.S(QQ, 2).Hom(P)
sage: H.codomain() is P
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> H = Q.S(QQ, Integer(2)).Hom(P)
>>> H.codomain() is P
True
```

`coordinates(hom)`

Return the coordinates of the map when expressed in terms of the generators (i. e., the output of the `gens` method) of the hom space.

INPUT:

- `hom` – [`QuiverRepHom`](#)

OUTPUT:

- list, the coordinates of the given map when written in terms of the generators of the [`QuiverHomSpace`](#)

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: S = Q.S(QQ, 2)
sage: P = Q.P(QQ, 1)
sage: H = S.Hom(P)
sage: f = S.hom({2: [[1, -1]]}, P)
sage: H.coordinates(f)
[1, -1]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> S = Q.S(QQ, Integer(2))
>>> P = Q.P(QQ, Integer(1))
>>> H = S.Hom(P)
>>> f = S.hom({Integer(2): [[Integer(1), -Integer(1)]]}, P)
>>> H.coordinates(f)
[1, -1]
```

dimension()

Return the dimension of the hom space.

OUTPUT: integer; the dimension

EXAMPLES:

```
sage: Q = DiGraph({1:2:['a', 'b']}).path_semigroup()
sage: H = Q.S(QQ, 2).Hom(Q.P(QQ, 1))
sage: H.dimension()
2
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> H = Q.S(QQ, Integer(2)).Hom(Q.P(QQ, Integer(1)))
>>> H.dimension()
2
```

domain()

Return the domain of the hom space.

OUTPUT: *QuiverRep*; the domain of the Hom space

EXAMPLES:

```
sage: Q = DiGraph({1:2:['a', 'b']}).path_semigroup()
sage: S = Q.S(QQ, 2)
sage: H = S.Hom(Q.P(QQ, 1))
sage: H.domain() is S
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> S = Q.S(QQ, Integer(2))
>>> H = S.Hom(Q.P(QQ, Integer(1)))
>>> H.domain() is S
True
```

gens()

Return a tuple of generators of the hom space (as a k -vector space).

OUTPUT: tuple of *QuiverRepHom* objects; the generators

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: H = Q.S(QQ, 2).Hom(Q.P(QQ, 1))
sage: H.gens()
(Homomorphism of representations of Multi-digraph on 2 vertices,
Homomorphism of representations of Multi-digraph on 2 vertices)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> H = Q.S(QQ, Integer(2)).Hom(Q.P(QQ, Integer(1)))
>>> H.gens()
(Homomorphism of representations of Multi-digraph on 2 vertices,
Homomorphism of representations of Multi-digraph on 2 vertices)
```

left_module (*basis=False*)

Create the QuiverRep of `self` as a module over the opposite quiver.

INPUT:

- `basis` – boolean; if `False`, then only the module is returned. If `True`, then a tuple is returned. The first element is the QuiverRep and the second element is a dictionary which associates to each vertex a list. The elements of this list are the homomorphisms which correspond to the basis elements of that vertex in the module.

OUTPUT: QuiverRep or tuple

Warning

The codomain of the Hom space must be a left module.

Note

The left action of a path e on a map f is given by $(ef)(m) = ef(m)$. This gives the Hom space its structure as a left module over the path algebra. This is then converted to a right module over the path algebra of the opposite quiver `Q.reverse()` and returned.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b'], 3: ['c', 'd']}, 2:{3:['e']}}).path_
↪semigroup()
sage: P = Q.P(GF(3), 3)
sage: A = Q.free_module(GF(3))
sage: H = P.Hom(A)
sage: H.dimension()
6
sage: M, basis_dict = H.left_module(true)
sage: M.dimension_vector()
(4, 1, 1)
sage: Q.reverse().P(GF(3), 3).dimension_vector()
(4, 1, 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b'], Integer(3): ['c', 'd']},
↳Integer(2):{Integer(3):['e']}}).path_semigroup()
>>> P = Q.P(GF(Integer(3)), Integer(3))
>>> A = Q.free_module(GF(Integer(3)))
>>> H = P.Hom(A)
>>> H.dimension()
6
>>> M, basis_dict = H.left_module(true)
>>> M.dimension_vector()
(4, 1, 1)
>>> Q.reverse().P(GF(Integer(3)), Integer(3)).dimension_vector()
(4, 1, 1)
```

As lists start indexing at 0 the i -th vertex corresponds to the $(i - 1)$ -th entry of the dimension vector:

```
sage: len(basis_dict[2]) == M.dimension_vector()[1]
True
```

```
>>> from sage.all import *
>>> len(basis_dict[Integer(2)]) == M.dimension_vector()[Integer(1)]
True
```

natural_map()

The natural map from domain to codomain.

This is the zero map.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3:QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]],
↳(2, 3, 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: spaces2 = {2: QQ^1, 3: QQ^1}
sage: S = Q.representation(QQ, spaces2)
sage: S.hom(M) # indirect doctest
Homomorphism of representations of Multi-digraph on 3 vertices
sage: S.hom(M) == S.Hom(M).natural_map()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b'], Integer(2):{Integer(3):[
↳'c']}}}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↳Integer(3):QQ**Integer(1)}
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)],
↳[Integer(0), Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0),
↳Integer(0)], [Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'):
↳[[Integer(1)], [Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
>>> spaces2 = {Integer(2): QQ**Integer(1), Integer(3): QQ**Integer(1)}
```

(continues on next page)

(continued from previous page)

```
>>> S = Q.representation(QQ, spaces2)
>>> S.hom(M)          # indirect doctest
Homomorphism of representations of Multi-digraph on 3 vertices
>>> S.hom(M) == S.Hom(M).natural_map()
True
```

quiver()

Return the quiver of the representations.

OUTPUT: `DiGraph`; the quiver of the representations

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: H = P.S(QQ, 2).Hom(P.P(QQ, 1))
sage: H.quiver() is P.quiver()
True
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> H = P.S(QQ, Integer(2)).Hom(P.P(QQ, Integer(1)))
>>> H.quiver() is P.quiver()
True
```

zero()

Return the zero morphism.

Note

It is needed to override the method inherited from the category of modules, because it would create a morphism that is of the wrong type and does not comply with `QuiverRepHom`.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: H = Q.S(QQ, 2).Hom(Q.P(QQ, 1))
sage: H.zero() + H.an_element() == H.an_element()
True
sage: isinstance(H.zero(), H.element_class)
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> H = Q.S(QQ, Integer(2)).Hom(Q.P(QQ, Integer(1)))
>>> H.zero() + H.an_element() == H.an_element()
True
>>> isinstance(H.zero(), H.element_class)
True
```

QUIVER MORPHISMS

```
class sage.quivers.morphism.QuiverRepHom(domain, codomain, data={})
```

Bases: `CallMorphism`

A homomorphism of quiver representations (of one and the same quiver) is given by specifying, for each vertex of the quiver, a homomorphism of the spaces assigned to this vertex such that these homomorphisms commute with the edge maps. The domain and codomain of the homomorphism are required to be representations of the same quiver over the same base ring.

INPUT:

- `domain` – `QuiverRep`, the domain of the homomorphism
- `codomain` – `QuiverRep`, the codomain of the homomorphism
- `data` – dict, list, or `QuiverRepElement` (default: empty dict), with the following meaning:
 - list: `data` can be a list of images for the generators of the domain. “Generators” means the output of the `gens()` method. An error will be generated if the map so defined is not equivariant with respect to the action of the quiver.
 - dictionary: `data` can be a dictionary associating to each vertex of the quiver either a homomorphism with domain and codomain the spaces associated to this vertex in the domain and codomain modules respectively, or a matrix defining such a homomorphism, or an object that sage can construct such a matrix from. Not all vertices must be specified, unspecified vertices are assigned the zero map, and keys not corresponding to vertices of the quiver are ignored. An error will be generated if these maps do not commute with the edge maps of the domain and codomain.
 - `QuiverRepElement`: if the domain is a `QuiverRep_with_path_basis` then `data` can be a single `QuiverRepElement` belonging to the codomain. The map is then defined by sending each path, `p`, in the basis to `data*p`. If `data` is not an element of the codomain or the domain is not a `QuiverRep_with_path_basis` then an error will be generated.
 - `QuiverRepHom`: the input can also be a map $f : D \rightarrow C$ such that there is a coercion from the domain of `self` to `D` and from `C` to the codomain of `self`. The composition of these maps is the result.

OUTPUT: `QuiverRepHom`

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3: QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]], (2, 3,
↪ 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: spaces2 = {2: QQ^1, 3: QQ^1}
sage: S = Q.representation(QQ, spaces2)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):['c']}}
↳}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↳Integer(3):QQ**Integer(1)}
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)], [Integer(0),
↳Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0), Integer(0)],
↳[Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'): [[Integer(1)],
↳[Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
>>> spaces2 = {Integer(2): QQ**Integer(1), Integer(3): QQ**Integer(1)}
>>> S = Q.representation(QQ, spaces2)
```

With no additional data this creates the zero map:

```
sage: f = S.hom(M)
sage: f.is_zero()
True
```

```
>>> from sage.all import *
>>> f = S.hom(M)
>>> f.is_zero()
True
```

We must specify maps at the vertices to get a nonzero homomorphism. Note that if the dimensions of the spaces assigned to the domain and codomain of a vertex are equal then Sage will construct the identity matrix from 1:

```
sage: maps2 = {2:[1, -1], 3:1}
sage: g = S.hom(maps2, M)
```

```
>>> from sage.all import *
>>> maps2 = {Integer(2):[Integer(1), -Integer(1)], Integer(3):Integer(1)}
>>> g = S.hom(maps2, M)
```

Here we create the same map by specifying images for the generators:

```
sage: x = M({2: (1, -1)})
sage: y = M({3: (1,)})
sage: h = S.hom([x, y], M)
sage: g == h
True
```

```
>>> from sage.all import *
>>> x = M({Integer(2): (Integer(1), -Integer(1))})
>>> y = M({Integer(3): (Integer(1),)})
>>> h = S.hom([x, y], M)
>>> g == h
True
```

If the domain is a module of type `QuiverRep_with_path_basis` (for example, the indecomposable projectives) we can create maps by specifying a single image:

```
sage: Proj = Q.P(GF(7), 3)
sage: Simp = Q.S(GF(7), 3)
sage: im = Simp({3: (1,)})
sage: Proj.hom(im, Simp).is_surjective()
True
```

```
>>> from sage.all import *
>>> Proj = Q.P(GF(Integer(7)), Integer(3))
>>> Simp = Q.S(GF(Integer(7)), Integer(3))
>>> im = Simp({Integer(3): (Integer(1),)})
>>> Proj.hom(im, Simp).is_surjective()
True
```

algebraic_dual()

Compute the algebraic dual $f^t : N^t \rightarrow M^t$ of $\text{self} = f : M \rightarrow N$ where $(-)^t = \text{Hom}_Q(-, kQ)$.

OUTPUT: *QuiverRepHom*; the map $f^t : N^t \rightarrow M^t$

Note

If e is an edge of the quiver Q and g is an element of $\text{Hom}_Q(N, kQ)$ then we let $(ge)(m) = eg(m)$. This gives $\text{Hom}_Q(N, kQ)$ its structure as a module over the opposite quiver $Q.\text{reverse}()$. The map $\text{Hom}_Q(N, kQ) \rightarrow \text{Hom}_Q(M, kQ)$ returned sends g to gf .

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b','c','d']}, 2:{4:['e','f']}, 3:{4:['g']},
↪ 5:{2:['h','i']}}).path_semigroup()
sage: P1 = Q.P(QQ, 4)
sage: P1.algebraic_dual()
Representation with dimension vector (5, 2, 1, 1, 4)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b','c','d']},
↪ Integer(2):{Integer(4):['e','f']}, Integer(3):{Integer(4):['g']},
↪ Integer(5):{Integer(2):['h','i']}}).path_semigroup()
>>> P1 = Q.P(QQ, Integer(4))
>>> P1.algebraic_dual()
Representation with dimension vector (5, 2, 1, 1, 4)
```

The algebraic dual of an indecomposable projective is the indecomposable projective of the same vertex in the opposite quiver.

```
sage: Q.reverse().P(QQ, 4)
Representation with dimension vector (5, 2, 1, 1, 4)
```

```
>>> from sage.all import *
>>> Q.reverse().P(QQ, Integer(4))
Representation with dimension vector (5, 2, 1, 1, 4)
```

base_ring()

Return the base ring of the representation in the codomain.

OUTPUT: the base ring of the codomain

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
sage: f.base_ring() is QQ
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3):
↪ Integer(1)}, P)
>>> f.base_ring() is QQ
True
```

codomain()

Return the codomain of the homomorphism.

OUTPUT: QuiverRep; the codomain

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3: QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]],
↪ (2, 3, 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: S = Q.representation(QQ)
sage: g = S.hom(M)
sage: g.codomain() is M
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↪ Integer(3): QQ**Integer(1)}
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)],
↪ [Integer(0), Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0),
↪ Integer(0)], [Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'):
↪ [[Integer(1)], [Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
>>> S = Q.representation(QQ)
>>> g = S.hom(M)
>>> g.codomain() is M
True
```

cokernel()

Return the cokernel of self.

OUTPUT: QuiverRep; the cokernel

Note

To get the factor map of the codomain, D , onto the cokernel, C , use `C.coerce_map_from(D)`.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3: QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]],
↪ (2, 3, 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: spaces2 = {2: QQ^2, 3: QQ^1}
sage: N = Q.representation(QQ, spaces2, {(2, 3, 'c'): [[1], [0]]})
sage: maps2 = {2: [[1, 0], [0, 0]], 3: 1}
sage: g = N.hom(maps2, M)
sage: g.cokernel().dimension_vector()
(2, 1, 0)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↪ Integer(3): QQ**Integer(1)}
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)],
↪ [Integer(0), Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0),
↪ Integer(0)], [Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'):
↪ [[Integer(1)], [Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
>>> spaces2 = {Integer(2): QQ**Integer(2), Integer(3): QQ**Integer(1)}
>>> N = Q.representation(QQ, spaces2, {(Integer(2), Integer(3), 'c'):
↪ [[Integer(1)], [Integer(0)]]})
>>> maps2 = {Integer(2): [[Integer(1), Integer(0)], [Integer(0), Integer(0)]],
↪ Integer(3): Integer(1)}
>>> g = N.hom(maps2, M)
>>> g.cokernel().dimension_vector()
(2, 1, 0)
```

direct_sum(*maps*, *return_maps=False*, *pinch=None*)

Return the direct sum of *self* with the maps in the list *maps*.

INPUT:

- *maps* – *QuiverRepHom* or list of *QuiverRepHom*'s
- *return_maps* – boolean (default: `False`); if `False`, then the return value is a *QuiverRepHom* which is the direct sum of *self* with the *QuiverRepHom*s in *maps*. If `True`, then the return value is a tuple of length either 3 or 5. The first entry of the tuple is the *QuiverRepHom* giving the direct sum. If *pinch* is either `None` or `'codomain'` then the next two entries in the tuple are lists giving respectively the inclusion and the projection maps for the factors of the direct sum. Summands are ordered as given in *maps* with *self* as the zeroth summand. If *pinch* is either `None` or `'domain'` then the next two entries in the tuple are the inclusion and projection maps for the codomain. Thus if *pinch* is `None` then the tuple will have length 5. If *pinch* is either `'domain'` or `'codomain'` then the tuple will have length 3.
- *pinch* – string or `None` (default: `None`); if this is equal to `'domain'`, then the domains of *self* and

the given maps must be equal. The direct sum of $f : A \rightarrow B$ and $g : A \rightarrow C$ returned is then the map $A \rightarrow B \oplus C$ defined by sending x to $(f(x), g(x))$. If `pinch` equals 'codomain', then the codomains of `self` and the given maps must be equal. The direct sum of $f : A \rightarrow C$ and $g : B \rightarrow C$ returned is then the map $A \oplus B \rightarrow C$ defined by sending (x, y) to $f(x) + g(y)$. Finally, if `pinch` is anything other than 'domain' or 'codomain', then the direct sum of $f : A \rightarrow B$ and $g : C \rightarrow D$ returned is the map $A \oplus C \rightarrow B \oplus D$ defined by sending (x, y) to $(f(x), g(y))$.

OUTPUT: *QuiverRepHom* or tuple

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: P1 = Q.P(GF(3), 1)
sage: P2 = Q.P(GF(3), 2)
sage: S1 = P1/P1.radical()
sage: S2 = P2/P2.radical()
sage: pi1 = S1.coerce_map_from(P1)
sage: pi2 = S2.coerce_map_from(P2)
sage: f = pi1.direct_sum(pi2)
sage: f.domain().dimension_vector() == Q.free_module(GF(3)).dimension_vector()
True
sage: f.is_surjective()
True
sage: id = P1.Hom(P1).identity()
sage: g = pi1.direct_sum(id, pinch='domain')
sage: g.is_surjective()
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> P1 = Q.P(GF(Integer(3)), Integer(1))
>>> P2 = Q.P(GF(Integer(3)), Integer(2))
>>> S1 = P1/P1.radical()
>>> S2 = P2/P2.radical()
>>> pi1 = S1.coerce_map_from(P1)
>>> pi2 = S2.coerce_map_from(P2)
>>> f = pi1.direct_sum(pi2)
>>> f.domain().dimension_vector() == Q.free_module(GF(Integer(3))).dimension_
↳vector()
True
>>> f.is_surjective()
True
>>> id = P1.Hom(P1).identity()
>>> g = pi1.direct_sum(id, pinch='domain')
>>> g.is_surjective()
False
```

domain()

Return the domain of the homomorphism.

OUTPUT: *QuiverRep*; the domain

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3: QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]],
↪ (2, 3, 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: S = Q.representation(QQ)
sage: g = M.hom(S)
sage: g.domain() is M
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↪ Integer(3): QQ**Integer(1)}
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)],
↪ [Integer(0), Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0),
↪ Integer(0)], [Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'):
↪ [[Integer(1)], [Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
>>> S = Q.representation(QQ)
>>> g = M.hom(S)
>>> g.domain() is M
True
```

get_map(vertex)

Return the homomorphism at the given vertex vertex.

INPUT:

- vertex – integer; a vertex of the quiver

OUTPUT: the homomorphism associated to the given vertex

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: S = P/P.radical()
sage: f = S.coerce_map_from(P)
sage: f.get_map(1).is_bijective()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> S = P/P.radical()
>>> f = S.coerce_map_from(P)
>>> f.get_map(Integer(1)).is_bijective()
True
```

get_matrix(vertex)

Return the matrix of the homomorphism attached to vertex vertex.

INPUT:

- vertex – integer; a vertex of the quiver

OUTPUT: the matrix representing the homomorphism associated to the given vertex

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: I = Q.I(QQ, 3)
sage: M = I/I.radical()
sage: f = M.coerce_map_from(I)
sage: f.get_matrix(1)
[1 0]
[0 1]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> I = Q.I(QQ, Integer(3))
>>> M = I/I.radical()
>>> f = M.coerce_map_from(I)
>>> f.get_matrix(Integer(1))
[1 0]
[0 1]
```

`image()`

Return the image of self.

OUTPUT: QuiverRep; the image

Note

To get the inclusion map of the image, I , into the codomain, C , use `C.coerce_map_from(I)`.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3: QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]],
↪ (2, 3, 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: spaces2 = {2: QQ^2, 3: QQ^1}
sage: N = Q.representation(QQ, spaces2, {(2, 3, 'c'): [[1], [0]]})
sage: maps2 = {2: [[1, 0], [0, 0]], 3: 1}
sage: g = N.hom(maps2, M)
sage: g.image().dimension_vector()
(0, 1, 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↪ Integer(3): QQ**Integer(1)}
```

(continues on next page)

(continued from previous page)

```
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)],
↪[Integer(0), Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0),
↪Integer(0)], [Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'):
↪[[Integer(1)], [Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
>>> spaces2 = {Integer(2): QQ**Integer(2), Integer(3): QQ**Integer(1)}
>>> N = Q.representation(QQ, spaces2, {(Integer(2), Integer(3), 'c'):
↪[[Integer(1)], [Integer(0)]]})
>>> maps2 = {Integer(2):[[Integer(1), Integer(0)], [Integer(0), Integer(0)]],
↪Integer(3):Integer(1)}
>>> g = N.hom(maps2, M)
>>> g.image().dimension_vector()
(0, 1, 1)
```

`is_endomorphism()`

Test whether the homomorphism is an endomorphism.

OUTPUT: boolean; True if the domain equals the codomain, False otherwise

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
sage: f.is_endomorphism()
True
sage: S = P/P.radical()
sage: g = S.coerce_map_from(P)
sage: g.is_endomorphism()
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3):
↪Integer(1)}, P)
>>> f.is_endomorphism()
True
>>> S = P/P.radical()
>>> g = S.coerce_map_from(P)
>>> g.is_endomorphism()
False
```

`is_injective()`

Test whether the homomorphism is injective.

OUTPUT: boolean; True if the homomorphism is injective, False otherwise

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
```

(continues on next page)

(continued from previous page)

```
sage: f.is_injective()
True
sage: g = P.hom(P)
sage: g.is_injective()
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3): ↪
↪ Integer(1)}, P)
>>> f.is_injective()
True
>>> g = P.hom(P)
>>> g.is_injective()
False
```

`is_isomorphism()`

Test whether the homomorphism is an isomorphism.

OUTPUT: boolean; True if the homomorphism is bijective, False otherwise

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
sage: f.is_isomorphism()
True
sage: g = P.hom(P)
sage: g.is_isomorphism()
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3): ↪
↪ Integer(1)}, P)
>>> f.is_isomorphism()
True
>>> g = P.hom(P)
>>> g.is_isomorphism()
False
```

`is_surjective()`

Test whether the homomorphism is surjective.

OUTPUT: boolean; True if the homomorphism is surjective, False otherwise

EXAMPLES:

```

sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
sage: f.is_surjective()
True
sage: g = P.hom(P)
sage: g.is_surjective()
False
    
```

```

>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3):↪
↪Integer(1)}, P)
>>> f.is_surjective()
True
>>> g = P.hom(P)
>>> g.is_surjective()
False
    
```

is_zero()

Test whether the homomorphism is the zero homomorphism.

OUTPUT: boolean; True if the homomorphism is zero, False otherwise

EXAMPLES:

```

sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
sage: f.is_zero()
False
sage: g = P.hom(P)
sage: g.is_zero()
True
    
```

```

>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↪'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3):↪
↪Integer(1)}, P)
>>> f.is_zero()
False
>>> g = P.hom(P)
>>> g.is_zero()
True
    
```

iscalar_mult(*scalar*)

Multiply self by scalar in place.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: f = M.Hom(M).an_element()
sage: x = M.an_element()
sage: y = f(x)
sage: f.iscalar_mult(6)
sage: f(x) == 6*y
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> f = M.Hom(M).an_element()
>>> x = M.an_element()
>>> y = f(x)
>>> f.iscalar_mult(Integer(6))
>>> f(x) == Integer(6)*y
True
```

kernel()

Return the kernel of self.

OUTPUT: QuiverRep; the kernel

Note

To get the inclusion map of the kernel, K, into the domain, D, use `D.coerce_map_from(K)`.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^2, 3: QQ^1}
sage: maps = {(1, 2, 'a'): [[1, 0], [0, 0]], (1, 2, 'b'): [[0, 0], [0, 1]],
↳ (2, 3, 'c'): [[1], [1]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: spaces2 = {2: QQ^2, 3: QQ^1}
sage: N = Q.representation(QQ, spaces2, {(2, 3, 'c'): [[1], [0]]})
sage: maps2 = {2: [[1, 0], [0, 0]], 3: 1}
sage: g = N.hom(maps2, M)
sage: g.kernel().dimension_vector()
(0, 1, 0)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):[
↳ 'c']}}).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(2),
↳ Integer(3): QQ**Integer(1)}
>>> maps = {(Integer(1), Integer(2), 'a'): [[Integer(1), Integer(0)],
↳ [Integer(0), Integer(0)]], (Integer(1), Integer(2), 'b'): [[Integer(0),
↳ Integer(0)], [Integer(0), Integer(1)]], (Integer(2), Integer(3), 'c'):
↳ [[Integer(1)], [Integer(1)]]}
>>> M = Q.representation(QQ, spaces, maps)
```

(continues on next page)

(continued from previous page)

```
>>> spaces2 = {Integer(2): QQ**Integer(2), Integer(3): QQ**Integer(1)}
>>> N = Q.representation(QQ, spaces2, {(Integer(2), Integer(3), 'c'):
↳ [[Integer(1)], [Integer(0)]]})
>>> maps2 = {Integer(2): [[Integer(1), Integer(0)], [Integer(0), Integer(0)]],
↳ Integer(3): Integer(1)}
>>> g = N.hom(maps2, M)
>>> g.kernel().dimension_vector()
(0, 1, 0)
```

lift(x)

Given an element x of the image, return an element of the domain that maps onto it under `self`.

INPUT:

- x – `QuiverRepElement`

OUTPUT: `QuiverRepElement`

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c','d']}}).path_semigroup()
sage: P = Q.P(QQ, 3)
sage: S = P/P.radical()
sage: proj = S.coerce_map_from(P)
sage: x = S.an_element()
sage: y = proj.lift(x)
sage: proj(y) == x
True
sage: zero = S.hom(S, {})
sage: zero.lift(x)
Traceback (most recent call last):
...
ValueError: element is not in the image
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c
↳ ','d']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(3))
>>> S = P/P.radical()
>>> proj = S.coerce_map_from(P)
>>> x = S.an_element()
>>> y = proj.lift(x)
>>> proj(y) == x
True
>>> zero = S.hom(S, {})
>>> zero.lift(x)
Traceback (most recent call last):
...
ValueError: element is not in the image
```

linear_dual()

Compute the linear dual $Df : DN \rightarrow DM$ of `self` = $f : M \rightarrow N$ where $D(-) = \text{Hom}_k(-, k)$.

OUTPUT: `QuiverRepHom`; the map $Df : DN \rightarrow DM$

Note

If e is an edge of the quiver Q and g is an element of $\text{Hom}_k(N, k)$ then we let $(ga)(m) = g(ma)$. This gives $\text{Hom}_k(N, k)$ its structure as a module over the opposite quiver $Q.\text{reverse}()$. The map $\text{Hom}_k(N, k) \rightarrow \text{Hom}_k(M, k)$ returned sends g to gf .

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: S = P/P.radical()
sage: f = S.coerce_map_from(P)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↳ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> S = P/P.radical()
>>> f = S.coerce_map_from(P)
```

The dual of a surjective map is injective and vice versa:

```
sage: f.is_surjective()
True
sage: g = f.linear_dual()
sage: g.is_injective()
True
```

```
>>> from sage.all import *
>>> f.is_surjective()
True
>>> g = f.linear_dual()
>>> g.is_injective()
True
```

The dual of a right module is a left module for the same quiver, Sage represents this as a right module for the opposite quiver:

```
sage: g.quiver().path_semigroup() is Q.reverse()
True
```

```
>>> from sage.all import *
>>> g.quiver().path_semigroup() is Q.reverse()
True
```

The double dual of a map is the original representation:

```
sage: g.linear_dual() == f
True
```

```
>>> from sage.all import *
>>> g.linear_dual() == f
```

(continues on next page)

(continued from previous page)

```
True
```

quiver()

Return the quiver of the representations in the domain/codomain.

OUTPUT:

- `DiGraph`, the quiver of the representations in the domain and codomain

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: f = P.hom({1: 1, 2: 1, 3: 1}, P)
sage: f.quiver() is Q.quiver()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↳ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> f = P.hom({Integer(1): Integer(1), Integer(2): Integer(1), Integer(3):
↳ Integer(1)}, P)
>>> f.quiver() is Q.quiver()
True
```

rank()

Return the rank of the homomorphism `self` (as a k -linear map).

OUTPUT: integer; the rank

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: S = P/P.radical()
sage: f = S.coerce_map_from(P)
sage: assert(f.rank() == 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):[
↳ 'c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> S = P/P.radical()
>>> f = S.coerce_map_from(P)
>>> assert(f.rank() == Integer(1))
```

scalar_mult (*scalar*)

Return the result of the scalar multiplication `scalar * self`, where `scalar` is an element of the base ring k .

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: f = M.Hom(M).an_element()
sage: x = M.an_element()
sage: g = f.scalar_mult(6)
sage: g(x) == 6*f(x)
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> f = M.Hom(M).an_element()
>>> x = M.an_element()
>>> g = f.scalar_mult(Integer(6))
>>> g(x) == Integer(6)*f(x)
True
```

PATH SEMIGROUPS

```
class sage.quivers.path_semigroup.PathSemigroup(Q)
```

Bases: UniqueRepresentation, Parent

The partial semigroup that is given by the directed paths of a quiver, subject to concatenation.

See [representation](#) for a definition of this semigroup and of the notion of a path in a quiver.

Note that a *partial semigroup* here is defined as a set G with a partial binary operation $G \times G \rightarrow G \cup \{\text{None}\}$, which is written infix as a $*$ sign and satisfies associativity in the following sense: If a , b and c are three elements of G , and if one of the products $(a * b) * c$ and $a * (b * c)$ exists, then so does the other and the two products are equal. A partial semigroup is not required to have a neutral element (and this one usually has no such element).

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 2:{3:['d']}})
sage: S = Q.path_semigroup()
sage: S
Partial semigroup formed by the directed paths of Multi-digraph on 3 vertices
sage: S.variable_names()
('e_1', 'e_2', 'e_3', 'a', 'b', 'c', 'd')
sage: S.gens()
(e_1, e_2, e_3, a, b, c, d)
sage: S.category()
Category of finite enumerated semigroups
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']}, Integer(2):
↳ {Integer(3):['d']}})
>>> S = Q.path_semigroup()
>>> S
Partial semigroup formed by the directed paths of Multi-digraph on 3 vertices
>>> S.variable_names()
('e_1', 'e_2', 'e_3', 'a', 'b', 'c', 'd')
>>> S.gens()
(e_1, e_2, e_3, a, b, c, d)
>>> S.category()
Category of finite enumerated semigroups
```

In the test suite, we skip the associativity test, as in this example the paths used for testing cannot be concatenated:

```
sage: TestSuite(S).run(skip=['_test_associativity'])
```

```
>>> from sage.all import *
>>> TestSuite(S).run(skip=['_test_associativity'])
```

If there is only a single vertex, the partial semigroup is a monoid. If the underlying quiver has cycles or loops, then the (partial) semigroup only is an infinite enumerated set. This time, there is no need to skip tests:

```
sage: Q = DiGraph({1:{1:['a', 'b', 'c', 'd']}})
sage: M = Q.path_semigroup()
sage: M
Monoid formed by the directed paths of Looped multi-digraph on 1 vertex
sage: M.category()
Category of infinite enumerated monoids
sage: TestSuite(M).run()
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(1):['a', 'b', 'c', 'd']}})
>>> M = Q.path_semigroup()
>>> M
Monoid formed by the directed paths of Looped multi-digraph on 1 vertex
>>> M.category()
Category of infinite enumerated monoids
>>> TestSuite(M).run()
```

Element

alias of *QuiverPath*

I (*k*, *vertex*)

Return the indecomposable injective module over *k* at the given vertex *vertex*.

This module is literally indecomposable only when *k* is a field.

INPUT:

- *k* – the base ring of the representation
- *vertex* – integer; a vertex of the quiver

OUTPUT:

- *QuiverRep*, the indecomposable injective module at vertex *vertex* with base ring *k*

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c', 'd']}}).path_semigroup()
sage: I2 = Q.I(GF(3), 2)
sage: Q.I(ZZ, 3).dimension_vector()
(4, 2, 1)
sage: Q.I(ZZ, 1).dimension_vector()
(1, 0, 0)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):['c', 'd']}}).path_semigroup()
>>> I2 = Q.I(GF(Integer(3)), Integer(2))
>>> Q.I(ZZ, Integer(3)).dimension_vector()
(4, 2, 1)
```

(continues on next page)

(continued from previous page)

```
>>> Q.I(ZZ, Integer(1)).dimension_vector()
(1, 0, 0)
```

The vertex given must be a vertex of the quiver:

```
sage: Q.I(QQ, 4)
Traceback (most recent call last):
...
ValueError: must specify a valid vertex of the quiver
```

```
>>> from sage.all import *
>>> Q.I(QQ, Integer(4))
Traceback (most recent call last):
...
ValueError: must specify a valid vertex of the quiver
```

$\mathbf{P}(k, \text{vertex})$

Return the indecomposable projective module over k at the given vertex `vertex`.

This module is literally indecomposable only when k is a field.

INPUT:

- k – the base ring of the representation
- `vertex` – integer; a vertex of the quiver

OUTPUT: `QuiverRep`, the indecomposable projective module at `vertex` with base ring k

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c','d']}}).path_semigroup()
sage: P2 = Q.P(GF(3), 2)
sage: Q.P(ZZ, 3).dimension_vector()
(0, 0, 1)
sage: Q.P(ZZ, 1).dimension_vector()
(1, 2, 4)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↪','d']}}).path_semigroup()
>>> P2 = Q.P(GF(Integer(3)), Integer(2))
>>> Q.P(ZZ, Integer(3)).dimension_vector()
(0, 0, 1)
>>> Q.P(ZZ, Integer(1)).dimension_vector()
(1, 2, 4)
```

The vertex given must be a vertex of the quiver:

```
sage: Q.P(QQ, 4)
Traceback (most recent call last):
...
ValueError: must specify a valid vertex of the quiver
```

```
>>> from sage.all import *
>>> Q.P(QQ, Integer(4))
Traceback (most recent call last):
...
ValueError: must specify a valid vertex of the quiver
```

s(k , *vertex*)

Return the simple module over k at the given vertex *vertex*.

This module is literally simple only when k is a field.

INPUT:

- k – the base ring of the representation
- *vertex* – integer; a vertex of the quiver

OUTPUT: QuiverRep; the simple module at *vertex* with base ring k

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a','b']}, 2:{3:['c','d']}}).path_semigroup()
sage: S1 = P.S(GF(3), 1)
sage: P.S(ZZ, 3).dimension_vector()
(0, 0, 1)
sage: P.S(ZZ, 1).dimension_vector()
(1, 0, 0)
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↪ 'd']}}).path_semigroup()
>>> S1 = P.S(GF(Integer(3)), Integer(1))
>>> P.S(ZZ, Integer(3)).dimension_vector()
(0, 0, 1)
>>> P.S(ZZ, Integer(1)).dimension_vector()
(1, 0, 0)
```

The vertex given must be a vertex of the quiver:

```
sage: P.S(QQ, 4)
Traceback (most recent call last):
...
ValueError: must specify a valid vertex of the quiver
```

```
>>> from sage.all import *
>>> P.S(QQ, Integer(4))
Traceback (most recent call last):
...
ValueError: must specify a valid vertex of the quiver
```

algebra(k , *order*='negdegrevlex')

Return the path algebra of the underlying quiver.

INPUT:

- k – a commutative ring

- `order` – (optional) string, one of 'negdegrevlex' (default), 'degrevlex', 'negdeglex' or 'deglex', defining the monomial order to be used

Note

Monomial orders that are not degree orders are not supported.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['d']}, 3:{1:['c']}})
sage: P = Q.path_semigroup()
sage: P.algebra(GF(3))
Path algebra of Multi-digraph on 3 vertices over Finite Field of size 3
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['d',
↪ '']}, Integer(3):{Integer(1):['c']}})
>>> P = Q.path_semigroup()
>>> P.algebra(GF(Integer(3)))
Path algebra of Multi-digraph on 3 vertices over Finite Field of size 3
```

Now some example with different monomial orderings:

```
sage: P1 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'))
sage: P2 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↪ order='degrevlex')
sage: P3 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↪ order='negdeglex')
sage: P4 = DiGraph({1:{1:['x','y','z']}}).path_semigroup().algebra(GF(25,'t'),
↪ order='deglex')
sage: P1.order_string()
'negdegrevlex'
sage: sage_eval('(x+2*z+1)^3', P1.gens_dict())
e_1 + z + 3*x + 2*z*z + x*z + z*x + 3*x*x + 3*z*z*z + 4*x*z*z + 4*z*x*z +
↪ 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x
sage: sage_eval('(x+2*z+1)^3', P2.gens_dict())
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↪ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
sage: sage_eval('(x+2*z+1)^3', P3.gens_dict())
e_1 + z + 3*x + 2*z*z + z*x + x*z + 3*x*x + 3*z*z*z + 4*z*z*x + 4*z*x*z +
↪ 2*z*x*x + 4*x*z*z + 2*x*z*x + 2*x*x*z + x*x*x
sage: sage_eval('(x+2*z+1)^3', P4.gens_dict())
3*z*z*z + 4*z*z*x + 4*z*x*z + 2*z*x*x + 4*x*z*z + 2*x*z*x + 2*x*x*z + x*x*x +
↪ 2*z*z + z*x + x*z + 3*x*x + z + 3*x + e_1
```

```
>>> from sage.all import *
>>> P1 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↪ algebra(GF(Integer(25),'t'))
>>> P2 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↪ algebra(GF(Integer(25),'t'), order='degrevlex')
>>> P3 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↪ algebra(GF(Integer(25),'t'), order='negdeglex')
```

(continues on next page)

(continued from previous page)

```
>>> P4 = DiGraph({Integer(1):{Integer(1):['x','y','z']}}).path_semigroup().
↳ algebra(GF(Integer(25),'t'), order='deglex')
>>> P1.order_string()
'negdegrevlex'
>>> sage_eval('(x+2*z+1)^3', P1.gens_dict())
e_1 + z + 3*x + 2*z*z + x*z + z*x + 3*x*x + 3*z*z*z + 4*x*z*z + 4*z*x*z +
↳ 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x
>>> sage_eval('(x+2*z+1)^3', P2.gens_dict())
3*z*z*z + 4*x*z*z + 4*z*x*z + 2*x*x*z + 4*z*z*x + 2*x*z*x + 2*z*x*x + x*x*x +
↳ 2*z*z + x*z + z*x + 3*x*x + z + 3*x + e_1
>>> sage_eval('(x+2*z+1)^3', P3.gens_dict())
e_1 + z + 3*x + 2*z*z + z*x + x*z + 3*x*x + 3*z*z*z + 4*z*z*x + 4*z*x*z +
↳ 2*z*x*x + 4*x*z*z + 2*x*z*x + 2*x*x*z + x*x*x
>>> sage_eval('(x+2*z+1)^3', P4.gens_dict())
3*z*z*z + 4*z*z*x + 4*z*x*z + 2*z*x*x + 4*x*z*z + 2*x*z*x + 2*x*x*z + x*x*x +
↳ 2*z*z + z*x + x*z + 3*x*x + z + 3*x + e_1
```

all_paths (start=None, end=None)

List of all paths between a pair of vertices (start, end).

INPUT:

- start – integer or None (default: None); the initial vertex of the paths in the output; if None is given then the initial vertex is arbitrary.
- end – integer or None (default: None); the terminal vertex of the paths in the output; if None is given then the terminal vertex is arbitrary

OUTPUT: list of paths, excluding the invalid path

Todo

This currently does not work for quivers with cycles, even if there are only finitely many paths from start to end.

Note

If there are multiple edges between two vertices, the method `sage.graphs.digraph.all_paths()` will not differentiate between them. But this method, which is not for digraphs but for their path semigroup associated with them, will.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 2:{3:['d']}})
sage: F = Q.path_semigroup()
sage: F.all_paths(1, 3)
[a*d, b*d, c]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳ Integer(2):{Integer(3):['d']}})
```

(continues on next page)

(continued from previous page)

```
>>> F = Q.path_semigroup()
>>> F.all_paths(Integer(1), Integer(3))
[a*d, b*d, c]
```

If `start=end` then we expect only the trivial path at that vertex:

```
sage: F.all_paths(1, 1)
[e_1]
```

```
>>> from sage.all import *
>>> F.all_paths(Integer(1), Integer(1))
[e_1]
```

The empty list is returned if there are no paths between the given vertices:

```
sage: F.all_paths(3, 1)
[]
```

```
>>> from sage.all import *
>>> F.all_paths(Integer(3), Integer(1))
[]
```

If `end=None` then all edge paths beginning at `start` are returned, including the trivial path:

```
sage: F.all_paths(2)
[e_2, d]
```

```
>>> from sage.all import *
>>> F.all_paths(Integer(2))
[e_2, d]
```

If `start=None` then all edge paths ending at `end` are returned, including the trivial path. Note that the two edges from vertex 1 to vertex 2 count as two different edge paths:

```
sage: F.all_paths(None, 2)
[a, b, e_2]
sage: F.all_paths(end=2)
[a, b, e_2]
```

```
>>> from sage.all import *
>>> F.all_paths(None, Integer(2))
[a, b, e_2]
>>> F.all_paths(end=Integer(2))
[a, b, e_2]
```

If `start=end=None` then all edge paths are returned, including trivial paths:

```
sage: F.all_paths()
[e_1, a, b, a*d, b*d, c, e_2, d, e_3]
```

```
>>> from sage.all import *
>>> F.all_paths()
[e_1, a, b, a*d, b*d, c, e_2, d, e_3]
```

The vertex given must be a vertex of the quiver:

```
sage: F.all_paths(1, 4)
Traceback (most recent call last):
...
ValueError: the end vertex 4 is not a vertex of the quiver
```

```
>>> from sage.all import *
>>> F.all_paths(Integer(1), Integer(4))
Traceback (most recent call last):
...
ValueError: the end vertex 4 is not a vertex of the quiver
```

If the underlying quiver is cyclic, a `ValueError` is raised:

```
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}})
sage: F = Q.path_semigroup()
sage: F.all_paths()
Traceback (most recent call last):
...
ValueError: the underlying quiver has cycles, thus, there may be an infinity
↳ of directed paths
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳ Integer(3):{Integer(1):['d']}})
>>> F = Q.path_semigroup()
>>> F.all_paths()
Traceback (most recent call last):
...
ValueError: the underlying quiver has cycles, thus, there may be an infinity
↳ of directed paths
```

arrows()

Return the elements corresponding to edges of the underlying quiver.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}}).path_semigroup()
sage: P.arrows()
(a, b, c, d)
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳ Integer(3):{Integer(1):['d']}}).path_semigroup()
>>> P.arrows()
(a, b, c, d)
```

cardinality()

EXAMPLES:

```

sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 2:{3:['d']}})
sage: F = Q.path_semigroup()
sage: F.cardinality()
9
sage: A = F.algebra(QQ)
sage: list(A.basis())
[e_1, e_2, e_3, a, b, c, d, a*d, b*d]
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}})
sage: F = Q.path_semigroup()
sage: F.cardinality()
+Infinity
sage: A = F.algebra(QQ)
sage: list(A.basis())
Traceback (most recent call last):
...
ValueError: the underlying quiver has cycles, thus, there may be an infinity
↳of directed paths
    
```

```

>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(2):{Integer(3):['d']}})
>>> F = Q.path_semigroup()
>>> F.cardinality()
9
>>> A = F.algebra(QQ)
>>> list(A.basis())
[e_1, e_2, e_3, a, b, c, d, a*d, b*d]
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(3):{Integer(1):['d']}})
>>> F = Q.path_semigroup()
>>> F.cardinality()
+Infinity
>>> A = F.algebra(QQ)
>>> list(A.basis())
Traceback (most recent call last):
...
ValueError: the underlying quiver has cycles, thus, there may be an infinity
↳of directed paths
    
```

free_module(k)

Return a free module of rank 1 over kP , where P is self. (In other words, the regular representation.)

INPUT:

- k – ring; the base ring of the representation

OUTPUT:

- *QuiverRep_with_path_basis*, the path algebra considered as a right module over itself.

EXAMPLES:

```

sage: Q = DiGraph({1:{2:['a','b'], 3:['c','d']}, 2:{3:['e']}}).path_
↳semigroup()
    
```

(continues on next page)

(continued from previous page)

```
sage: Q.free_module(GF(3)).dimension_vector()
(1, 3, 6)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b'], Integer(3): ['c', 'd']},
↳Integer(2):{Integer(3):['e']}}).path_semigroup()
>>> Q.free_module(GF(Integer(3))).dimension_vector()
(1, 3, 6)
```

gen(i)

Return generator number i .

INPUT:

- i – integer

OUTPUT:

An idempotent, if i is smaller than the number of vertices, or an arrow otherwise.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}}).path_semigroup()
sage: P.1 # indirect doctest
e_2
sage: P.idempotents()[1]
e_2
sage: P.5
c
sage: P.gens()[5]
c
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(3):{Integer(1):['d']}}).path_semigroup()
>>> P.gen(1) # indirect doctest
e_2
>>> P.idempotents()[Integer(1)]
e_2
>>> P.gen(5)
c
>>> P.gens()[Integer(5)]
c
```

gens()

Return the tuple of generators.

Note

This coincides with the sum of the output of `idempotents()` and `arrows()`.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}}).path_semigroup()
sage: P.gens()
(e_1, e_2, e_3, a, b, c, d)
sage: P.gens() == P.idempotents() + P.arrows()
True
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(3):{Integer(1):['d']}}).path_semigroup()
>>> P.gens()
(e_1, e_2, e_3, a, b, c, d)
>>> P.gens() == P.idempotents() + P.arrows()
True
```

idempotents()

Return the idempotents corresponding to the vertices of the underlying quiver.

EXAMPLES:

```
sage: P = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}}).path_semigroup()
sage: P.idempotents()
(e_1, e_2, e_3)
```

```
>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(3):{Integer(1):['d']}}).path_semigroup()
>>> P.idempotents()
(e_1, e_2, e_3)
```

injective(k, vertex)

alias of *I*().

is_finite()

This partial semigroup is finite if and only if the underlying quiver is acyclic.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 2:{3:['d']}})
sage: Q.path_semigroup().is_finite()
True
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}})
sage: Q.path_semigroup().is_finite()
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(2):{Integer(3):['d']}})
>>> Q.path_semigroup().is_finite()
True
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']},
↳Integer(3):{Integer(1):['d']}})
>>> Q.path_semigroup().is_finite()
False
```

iter_paths_by_length_and_endpoint (d, v)

An iterator over quiver paths with a fixed length and end point.

INPUT:

- d – integer; the path length
- v – a vertex; end point of the paths

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['d']}, 3:{1:['c']}})
sage: F = Q.path_semigroup()
sage: F.is_finite()
False
sage: list(F.iter_paths_by_length_and_endpoint(4,1))
[c*a*d*c, c*b*d*c]
sage: list(F.iter_paths_by_length_and_endpoint(5,1))
[d*c*a*d*c, d*c*b*d*c]
sage: list(F.iter_paths_by_length_and_endpoint(5,2))
[c*a*d*c*a, c*b*d*c*a, c*a*d*c*b, c*b*d*c*b]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['d',
↪ '']}, Integer(3):{Integer(1):['c']}})
>>> F = Q.path_semigroup()
>>> F.is_finite()
False
>>> list(F.iter_paths_by_length_and_endpoint(Integer(4),Integer(1)))
[c*a*d*c, c*b*d*c]
>>> list(F.iter_paths_by_length_and_endpoint(Integer(5),Integer(1)))
[d*c*a*d*c, d*c*b*d*c]
>>> list(F.iter_paths_by_length_and_endpoint(Integer(5),Integer(2)))
[c*a*d*c*a, c*b*d*c*a, c*a*d*c*b, c*b*d*c*b]
```

iter_paths_by_length_and_startpoint (d, v)

An iterator over quiver paths with a fixed length and start point.

INPUT:

- d – integer; the path length
- v – a vertex; start point of the paths

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['d']}, 3:{1:['c']}})
sage: P = Q.path_semigroup()
sage: P.is_finite()
False
sage: list(P.iter_paths_by_length_and_startpoint(4,1))
[a*d*c*a, a*d*c*b, b*d*c*a, b*d*c*b]
sage: list(P.iter_paths_by_length_and_startpoint(5,1))
[a*d*c*a*d, a*d*c*b*d, b*d*c*a*d, b*d*c*b*d]
sage: list(P.iter_paths_by_length_and_startpoint(5,2))
[d*c*a*d*c, d*c*b*d*c]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['d'
↪']}, Integer(3):{Integer(1):['c']}}})
>>> P = Q.path_semigroup()
>>> P.is_finite()
False
>>> list(P.iter_paths_by_length_and_startpoint(Integer(4),Integer(1)))
[a*d*c*a, a*d*c*b, b*d*c*a, b*d*c*b]
>>> list(P.iter_paths_by_length_and_startpoint(Integer(5),Integer(1)))
[a*d*c*a*d, a*d*c*b*d, b*d*c*a*d, b*d*c*b*d]
>>> list(P.iter_paths_by_length_and_startpoint(Integer(5),Integer(2)))
[d*c*a*d*c, d*c*b*d*c]
```

`ngens()`

Return the number of generators (`arrows()` and `idempotents()`).

EXAMPLES:

```
sage: F = DiGraph({1:{2:['a','b'], 3:['c']}, 3:{1:['d']}}).path_semigroup()
sage: F.ngens()
7
```

```
>>> from sage.all import *
>>> F = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']}, ↪
↪Integer(3):{Integer(1):['d']}}).path_semigroup()
>>> F.ngens()
7
```

`projective(k, vertex)`

alias of `P()`.

`quiver()`

Return the underlying quiver (i.e., digraph) of this path semigroup.

Note

The returned digraph always is an immutable copy of the originally given digraph that is made weighted.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['d']}, 3:{1:['c']}},
....:             weighted=False)
sage: F = Q.path_semigroup()
sage: F.quiver() == Q
False
sage: Q.weighted(True)
sage: F.quiver() == Q
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['d'
↪']}, Integer(3):{Integer(1):['c']}}),
```

(continues on next page)

(continued from previous page)

```
... weighted=False)
>>> F = Q.path_semigroup()
>>> F.quiver() == Q
False
>>> Q.weighted(True)
>>> F.quiver() == Q
True
```

representation (*k*, **args*, ***kws*)

Return a representation of the quiver.

For more information see the `QuiverRep` documentation.

reverse ()

The path semigroup of the reverse quiver.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['d']}, 3:{1:['c']}})
sage: F = Q.path_semigroup()
sage: F.reverse() is Q.reverse().path_semigroup()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['d',
↪ '']}, Integer(3):{Integer(1):['c']}})
>>> F = Q.path_semigroup()
>>> F.reverse() is Q.reverse().path_semigroup()
True
```

simple (*k*, *vertex*)

alias of `s()`.

QUIVER PATHS

`sage.quivers.paths.NewQuiverPath(Q, start, end, biseq_data)`

Return a new quiver path for given defining data.

INPUT:

- `Q` – the path semigroup of a quiver
- `start` – integer; the label of the startpoint
- `end` – integer; the label of the endpoint
- `biseq_data` – tuple formed by
 - a string, encoding a bitmap representing the path as integer at base 32
 - the number of bits used to store the path
 - the number of bits used to store a single item
 - the number of items in the path

`class sage.quivers.paths.QuiverPath`

Bases: `MonoidElement`

Class for paths in a quiver.

A path is given by two vertices, `start` and `end`, and a finite (possibly empty) list of edges $e_1, e_2, \dots, e_n$ such that the initial vertex of e_1 is `start`, the final vertex of e_i is the initial vertex of e_{i+1} , and the final vertex of e_n is `end`. In the case where no edges are specified, we must have `start = end` and the path is called the trivial path at the given vertex.

Note

Do *not* use this constructor directly! Instead, pass the input to the path semigroup that shall be the parent of this path.

EXAMPLES:

Specify a path by giving a list of edges:

```
sage: Q = DiGraph({1:{2:['a', 'd'], 3:['e']}, 2:{3:['b']}, 3:{1:['f'], 4:['c']}})
sage: F = Q.path_semigroup()
sage: p = F([(1, 2, 'a'), (2, 3, 'b')])
sage: p
a*b
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','d'], Integer(3):['e']}, Integer(2):
↳ {Integer(3):['b']}, Integer(3):{Integer(1):['f'], Integer(4):['c']}})
>>> F = Q.path_semigroup()
>>> p = F([(Integer(1), Integer(2), 'a'), (Integer(2), Integer(3), 'b')])
>>> p
a*b
```

Paths are not *unique*, but different representations of “the same” path yield *equal* paths:

```
sage: q = F([(1, 1)]) * F([(1, 2, 'a'), (2, 3, 'b')]) * F([(3, 3)])
sage: p is q
False
sage: p == q
True
```

```
>>> from sage.all import *
>>> q = F([(Integer(1), Integer(1))]) * F([(Integer(1), Integer(2), 'a'),
↳ (Integer(2), Integer(3), 'b')]) * F([(Integer(3), Integer(3))])
>>> p is q
False
>>> p == q
True
```

The `*` operator is concatenation of paths. If the two paths do not compose, its result is `None`:

```
sage: print(p*q)
None
sage: p*F([(3, 4, 'c')])
a*b*c
sage: F([(2, 3, 'b'), (3, 1, 'f')]) * p
b*f*a*b
```

```
>>> from sage.all import *
>>> print(p*q)
None
>>> p*F([(Integer(3), Integer(4), 'c')])
a*b*c
>>> F([(Integer(2), Integer(3), 'b'), (Integer(3), Integer(1), 'f')]) * p
b*f*a*b
```

The length of a path is the number of edges in that path. Trivial paths are therefore length-0:

```
sage: len(p)
2
sage: triv = F([(1, 1)])
sage: len(triv)
0
```

```
>>> from sage.all import *
>>> len(p)
2
```

(continues on next page)

(continued from previous page)

```
>>> triv = F([(Integer(1), Integer(1))])
>>> len(triv)
0
```

List index and slice notation can be used to access the edges in a path. QuiverPaths can also be iterated over. Trivial paths have no elements:

```
sage: for x in p: print(x)
(1, 2, 'a')
(2, 3, 'b')
sage: list(triv)
[]
```

```
>>> from sage.all import *
>>> for x in p: print(x)
(1, 2, 'a')
(2, 3, 'b')
>>> list(triv)
[]
```

There are methods giving the initial and terminal vertex of a path:

```
sage: p.initial_vertex()
1
sage: p.terminal_vertex()
3
```

```
>>> from sage.all import *
>>> p.initial_vertex()
1
>>> p.terminal_vertex()
3
```

complement (*subpath*)

Return a pair (a, b) of paths s.t. $\text{self} = a * \text{subpath} * b$, or $(\text{None}, \text{None})$ if *subpath* is not a subpath of this path.

Note

a is chosen of minimal length.

EXAMPLES:

```
sage: S = DiGraph({1:{1:['a', 'b', 'c', 'd']}}).path_semigroup()
sage: S.inject_variables()
Defining e_1, a, b, c, d
sage: (b*c*a*d*b*a*d*d).complement(a*d)
(b*c, b*a*d*d)
sage: (b*c*a*d*b).complement(a*c)
(None, None)
```

```
>>> from sage.all import *
>>> S = DiGraph({Integer(1):{Integer(1):['a','b','c','d']}}).path_semigroup()
>>> S.inject_variables()
Defining e_1, a, b, c, d
>>> (b*c*a*d*b*a*d*d).complement(a*d)
(b*c, b*a*d*d)
>>> (b*c*a*d*b).complement(a*c)
(None, None)
```

degree()

Return the length of the path.

`length()` and `degree()` are aliases

gcd(*P*)

Greatest common divisor of two quiver paths, with co-factors.

For paths, by “greatest common divisor”, we mean the largest terminal segment of the first path that is an initial segment of the second path.

INPUT:

- *P* – a *QuiverPath*

OUTPUT:

- *QuiverPath*’s `((C1,G,C2))` such that `self = C1*G` and `P = G*C2`, or
- `(None, None, None)`, if the paths do not overlap (or belong to different quivers).

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}, 2:{1:['b'], 3:['c']}, 3:{1:['d']}}).path_
↪semigroup()
sage: p1 = Q(['c','d','a','b','a','c','d'])
sage: p1
c*d*a*b*a*c*d
sage: p2 = Q(['a','b','a','c','d','a','c','d','a','b'])
sage: p2
a*b*a*c*d*a*c*d*a*b
sage: S1, G, S2 = p1.gcd(p2)
sage: S1, G, S2
(c*d, a*b*a*c*d, a*c*d*a*b)
sage: S1*G == p1
True
sage: G*S2 == p2
True
sage: p2.gcd(p1)
(a*b*a*c*d*a, c*d*a*b, a*c*d)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(1):['b'],
↪Integer(3):['c']}, Integer(3):{Integer(1):['d']}}).path_semigroup()
>>> p1 = Q(['c','d','a','b','a','c','d'])
>>> p1
c*d*a*b*a*c*d
>>> p2 = Q(['a','b','a','c','d','a','c','d','a','b'])
```

(continues on next page)

(continued from previous page)

```
>>> p2
a*b*a*c*d*a*c*d*a*b
>>> s1, G, s2 = p1.gcd(p2)
>>> s1, G, s2
(c*d, a*b*a*c*d, a*c*d*a*b)
>>> s1*G == p1
True
>>> G*s2 == p2
True
>>> p2.gcd(p1)
(a*b*a*c*d*a, c*d*a*b, a*c*d)
```

We test that a full overlap is detected:

```
sage: p2.gcd(p2)
(e_1, a*b*a*c*d*a*c*d*a*b, e_1)
```

```
>>> from sage.all import *
>>> p2.gcd(p2)
(e_1, a*b*a*c*d*a*c*d*a*b, e_1)
```

The absence of an overlap is detected:

```
sage: p2[2:-1]
a*c*d*a*c*d*a
sage: p2[1:]
b*a*c*d*a*c*d*a*b
sage: print(p2[2:-1].gcd(p2[1:]))
(None, None, None)
```

```
>>> from sage.all import *
>>> p2[Integer(2):-Integer(1)]
a*c*d*a*c*d*a
>>> p2[Integer(1):]
b*a*c*d*a*c*d*a*b
>>> print(p2[Integer(2):-Integer(1)].gcd(p2[Integer(1):]))
(None, None, None)
```

has_prefix(*subpath*)

Tells whether this path starts with a given sub-path.

INPUT:

- *subpath* – a path in the same path semigroup as this path

OUTPUT: 0 or 1, which stands for False resp. True

EXAMPLES:

```
sage: S = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}).path_semigroup()
sage: S.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: (c*b*e*a).has_prefix(b*e)
```

(continues on next page)

(continued from previous page)

```
0
sage: (c*b*e*a).has_prefix(c*b)
1
sage: (c*b*e*a).has_prefix(e_1)
1
sage: (c*b*e*a).has_prefix(e_2)
0
```

```
>>> from sage.all import *
>>> S = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):
↳ {Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'],
↳ Integer(2):['f']}}).path_semigroup()
>>> S.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> (c*b*e*a).has_prefix(b*e)
0
>>> (c*b*e*a).has_prefix(c*b)
1
>>> (c*b*e*a).has_prefix(e_1)
1
>>> (c*b*e*a).has_prefix(e_2)
0
```

has_subpath (*subpath*)

Tells whether this path contains a given sub-path.

INPUT:

- *subpath* – a path of positive length in the same path semigroup as this path

EXAMPLES:

```
sage: S = DiGraph({0:{1:['a'], 2:['b']}, 1:{0:['c'], 1:['d']}, 2:{0:['e'], 2:['f']}}).path_semigroup()
sage: S.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
sage: (c*b*e*a).has_subpath(b*e)
1
sage: (c*b*e*a).has_subpath(b*f)
0
sage: (c*b*e*a).has_subpath(e_1)
Traceback (most recent call last):
...
ValueError: we only consider sub-paths of positive length
sage: (c*b*e*a).has_subpath(None)
Traceback (most recent call last):
...
ValueError: the given sub-path is empty
```

```
>>> from sage.all import *
>>> S = DiGraph({Integer(0):{Integer(1):['a'], Integer(2):['b']}, Integer(1):
↳ {Integer(0):['c'], Integer(1):['d']}, Integer(2):{Integer(0):['e'],
↳ Integer(2):['f']}}).path_semigroup()
```

(continues on next page)

(continued from previous page)

```
>>> S.inject_variables()
Defining e_0, e_1, e_2, a, b, c, d, e, f
>>> (c*b*e*a).has_subpath(b*e)
1
>>> (c*b*e*a).has_subpath(b*f)
0
>>> (c*b*e*a).has_subpath(e_1)
Traceback (most recent call last):
...
ValueError: we only consider sub-paths of positive length
>>> (c*b*e*a).has_subpath(None)
Traceback (most recent call last):
...
ValueError: the given sub-path is empty
```

initial_vertex()

Return the initial vertex of the path.

OUTPUT: integer; the label of the initial vertex

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}, 2:{3:['b']}}).path_semigroup()
sage: y = Q([(1, 2, 'a'), (2, 3, 'b')])
sage: y.initial_vertex()
1
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b']}}
↳).path_semigroup()
>>> y = Q([(Integer(1), Integer(2), 'a'), (Integer(2), Integer(3), 'b')])
>>> y.initial_vertex()
1
```

length()

Return the length of the path.

`length()` and `degree()` are aliases

reversal()

Return the path along the same edges in reverse order in the opposite quiver.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}, 2:{3:['b']}, 3:{4:['c']}, 1:{4:['d']}}).path_
↳semigroup()
sage: p = Q([(1, 2, 'a'), (2, 3, 'b'), (3, 1, 'd'), (1, 2, 'a'), (2, 3, 'b'),
↳(3, 4, 'c')])
sage: p
a*b*d*a*b*c
sage: p.reversal()
c*b*a*d*b*a
sage: e = Q.idempotents()[0]
sage: e
```

(continues on next page)

(continued from previous page)

```
e_1
sage: e.reversal()
e_1
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b']},
↳ Integer(3):{Integer(4):['c'], Integer(1):['d']}}).path_semigroup()
>>> p = Q([(Integer(1), Integer(2), 'a'), (Integer(2), Integer(3), 'b'),
↳ (Integer(3), Integer(1), 'd'), (Integer(1), Integer(2), 'a'), (Integer(2),
↳ Integer(3), 'b'), (Integer(3), Integer(4), 'c')])
>>> p
a*b*d*a*b*c
>>> p.reversal()
c*b*a*d*b*a
>>> e = Q.idempotents()[Integer(0)]
>>> e
e_1
>>> e.reversal()
e_1
```

terminal_vertex()

Return the terminal vertex of the path.

OUTPUT: integer; the label of the terminal vertex

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}, 2:{3:['b']}}).path_semigroup()
sage: y = Q([(1, 2, 'a'), (2, 3, 'b')])
sage: y.terminal_vertex()
3
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}, Integer(2):{Integer(3):['b']}}
↳ ).path_semigroup()
>>> y = Q([(Integer(1), Integer(2), 'a'), (Integer(2), Integer(3), 'b')])
>>> y.terminal_vertex()
3
```

QUIVER REPRESENTATIONS

AUTHORS:

- Jim Stark (2012-03-04): Initial implementation of acyclic quivers without relations.
- Simon King (2013-05, 2014-02): Split code up. Allow cyclic quivers where possible.

A quiver is a directed graph used for representation theory. In our representation theoretic code, it is assumed that

- the vertices of the quiver are labelled by integers, and
- each edge of the quiver is labelled with a nonempty string. The label cannot begin with 'e_' or contain '*' and distinct edges must have distinct labels.

As far as the `DiGraph` class is concerned, a path is a finite list of pairwise distinct vertices $v_1, \dots, v_n$ such that there exists an edge from v_i to v_{i+1} . If there are multiple edges between the same two vertices this does not contribute additional paths as listed by the `DiGraph` class; for example only two paths are listed from 1 to 3 in `Q`:

```
sage: Q = DiGraph({1:{2:['a','b'], 3:['c']}, 2:{3:['d']}})
sage: Q.edges(sort=True)
[(1, 2, 'a'), (1, 2, 'b'), (1, 3, 'c'), (2, 3, 'd')]
sage: Q.all_paths(1, 3)
[[1, 2, 3], [1, 3]]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']}, Integer(2):
↳ {Integer(3):['d']}})
>>> Q.edges(sort=True)
[(1, 2, 'a'), (1, 2, 'b'), (1, 3, 'c'), (2, 3, 'd')]
>>> Q.all_paths(Integer(1), Integer(3))
[[1, 2, 3], [1, 3]]
```

The notion of a path in a quiver (in representation theory) is fundamentally different in several aspects. First, paths are no longer required to have distinct vertices, or even distinct edges; thus, “path” in quiver theory is closer to the notion of “walk” in graph theory. Furthermore, paths in quiver theory “know” their edges, so parallel edges between the same two vertices of a Quiver make different paths. But paths in quiver theory also “know” their vertices, so that a length-0 path from a to a is not the same as a length-0 path from b to b for $a \neq b$. Formally, we say that a path is given by two vertices, `start` and `end`, and a finite (possibly empty) list of edges $e_1, e_2, \dots, e_n$ such that the initial vertex of e_1 is `start`, the final vertex of e_i is the initial vertex of e_{i+1} , and the final vertex of e_n is `end`. In the case where no edges are specified, we must have `start = end` and the path is called the trivial path at the given vertex.

Quiver paths in the sense stated above correspond to the elements of a partial semigroup, with multiplication of paths given by concatenation. Hence, rather than overloading the method name inherited from `DiGraph` or inventing a new method name, we move this functionality to this so-called *path semigroup*. Note that with this definition there are three paths from 1 to 3 in our example:

```
sage: Q.path_semigroup().all_paths(1, 3)
[a*d, b*d, c]
```

```
>>> from sage.all import *
>>> Q.path_semigroup().all_paths(Integer(1), Integer(3))
[a*d, b*d, c]
```

The returned paths are of type *QuiverPath*, which are elements in the path semigroup that is associated with the quiver (a partial semigroup, which does not generally have a neutral element). You can specify a *QuiverPath* by giving an edge or a list of edges, passed as arguments to the path semigroup containing this path. Here an edge is a tuple of the form (i, j, l) , where i and j are vertices and l is the label of an edge from i to j :

```
sage: p = Q.path_semigroup()([(1, 2, 'a'), (2, 3, 'd')])
sage: p
a*d
```

```
>>> from sage.all import *
>>> p = Q.path_semigroup()([(Integer(1), Integer(2), 'a'), (Integer(2), Integer(3), 'd
↪')])
>>> p
a*d
```

Trivial paths are indicated by passing a list containing the tuple $(\text{vertex}, \text{vertex})$:

```
sage: Q.path_semigroup()([(3, 3)])
e_3
```

```
>>> from sage.all import *
>>> Q.path_semigroup()([(Integer(3), Integer(3))])
e_3
```

Here is an alternative way to define a path:

```
sage: PQ = Q.path_semigroup()
sage: q = PQ(['a', 'd'])
sage: p == q
True
```

```
>>> from sage.all import *
>>> PQ = Q.path_semigroup()
>>> q = PQ(['a', 'd'])
>>> p == q
True
```

If the vertices along the path do not match, a value error is raised:

```
sage: inv1 = PQ([(2, 3, 'd'), (1, 2, 'a')])
Traceback (most recent call last):
...
ValueError: edge d ends at 3, but edge a starts at 1
sage: inv2 = PQ([(1, 2, 'a'), (1, 2, 'a')])
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: edge a ends at 2, but edge a starts at 1
sage: inv3 = PQ([(1, 2, 'x')])
Traceback (most recent call last):
...
ValueError: (1, 2, 'x') is not an edge
```

```
>>> from sage.all import *
>>> inv1 = PQ([(Integer(2), Integer(3), 'd'), (Integer(1), Integer(2), 'a')])
Traceback (most recent call last):
...
ValueError: edge d ends at 3, but edge a starts at 1
>>> inv2 = PQ([(Integer(1), Integer(2), 'a'), (Integer(1), Integer(2), 'a')])
Traceback (most recent call last):
...
ValueError: edge a ends at 2, but edge a starts at 1
>>> inv3 = PQ([(Integer(1), Integer(2), 'x')])
Traceback (most recent call last):
...
ValueError: (1, 2, 'x') is not an edge
```

The `*` operator is concatenation of paths. If the two paths do not compose, then the result is `None` (whence the “partial” in “partial semigroup”).

```
sage: print(p*q)
None
```

```
>>> from sage.all import *
>>> print(p*q)
None
```

Let us now construct a larger quiver:

```
sage: Qbig = DiGraph({1:{2:['a','b'], 3:['c']}, 2:{3:['d']}, 3:{4:['e']}, 4:{5:['f']},
↪ 5:{1:['g']}})
sage: Pbig = Qbig.path_semigroup()
```

```
>>> from sage.all import *
>>> Qbig = DiGraph({Integer(1):{Integer(2):['a','b'], Integer(3):['c']}, Integer(2):
↪ {Integer(3):['d']}, Integer(3):{Integer(4):['e']}, Integer(4):{Integer(5):['f']},
↪ Integer(5):{Integer(1):['g']}})
>>> Pbig = Qbig.path_semigroup()
```

Since Q is a sub-digraph of Q_{big} , we have a coercion of the associated path semigroups:

```
sage: Pbig.has_coerce_map_from(PQ)
True
```

```
>>> from sage.all import *
>>> Pbig.has_coerce_map_from(PQ)
True
```

In particular, `p` is considered to be an element of `Pbig`, and can be composed with paths that were defined for the larger quiver:

```
sage: p in Pbig
True
sage: p*Pbig([(3, 4, 'e')])
a*d*e
sage: Pbig([(4, 5, 'f'), (5, 1, 'g')])*p
f*g*a*d
```

```
>>> from sage.all import *
>>> p in Pbig
True
>>> p*Pbig([(Integer(3), Integer(4), 'e')])
a*d*e
>>> Pbig([(Integer(4), Integer(5), 'f'), (Integer(5), Integer(1), 'g')])*p
f*g*a*d
```

The length of a path is the number of edges in that path:

```
sage: len(p)
2
sage: triv = PQ([(1, 1)])
sage: len(triv)
0
```

```
>>> from sage.all import *
>>> len(p)
2
>>> triv = PQ([(Integer(1), Integer(1))])
>>> len(triv)
0
```

List index and slice notation can be used to access the edges in a path. `QuiverPaths` can also be iterated over. Trivial paths have no elements:

```
sage: for x in p: print(x)
(1, 2, 'a')
(2, 3, 'd')
sage: triv[:]
e_1
```

```
>>> from sage.all import *
>>> for x in p: print(x)
(1, 2, 'a')
(2, 3, 'd')
>>> triv[:]
e_1
```

There are methods giving the initial and terminal vertex of a path:

```
sage: p.initial_vertex()
1
```

(continues on next page)

(continued from previous page)

```
sage: p.terminal_vertex()
3
```

```
>>> from sage.all import *
>>> p.initial_vertex()
1
>>> p.terminal_vertex()
3
```

QuiverPath form the basis of the quiver algebra of a quiver. Given a field k and a quiver Q , the quiver algebra kQ is, as a vector space, the free k -vector space whose basis is the set of all paths in Q . Multiplication is defined on this basis and extended bilinearly. The product of two basis elements is given by path composition when it makes sense and is set to be zero otherwise. Specifically, if the terminal vertex of the left path equals the initial vertex of the right path, then their product is the concatenation of the two paths, and otherwise their product is zero. In sage, quiver algebras are handled by the *QuiverAlgebra* class:

```
sage: A = PQ.algebra(GF(7))
sage: A
Path algebra of Multi-digraph on 3 vertices over Finite Field of size 7
```

```
>>> from sage.all import *
>>> A = PQ.algebra(GF(Integer(7)))
>>> A
Path algebra of Multi-digraph on 3 vertices over Finite Field of size 7
```

Quivers have a method that creates their algebra over a given field (or, more generally, commutative ring). Note that *QuiverAlgebras* are uniquely defined by their quiver and field, and play nicely with coercions of the underlying path semigroups:

```
sage: A is PQ.algebra(GF(7))
True
sage: A is PQ.algebra(RR)
False
sage: Q1 = Q.copy()
sage: Q1.add_vertex(4)
sage: PQ1 = Q1.path_semigroup()
sage: A is PQ1.algebra(GF(7))
False
sage: Pbig.algebra(GF(7)).has_coerce_map_from(A)
True
```

```
>>> from sage.all import *
>>> A is PQ.algebra(GF(Integer(7)))
True
>>> A is PQ.algebra(RR)
False
>>> Q1 = Q.copy()
>>> Q1.add_vertex(Integer(4))
>>> PQ1 = Q1.path_semigroup()
>>> A is PQ1.algebra(GF(Integer(7)))
False
```

(continues on next page)

(continued from previous page)

```
>>> Pbig.algebra(GF(Integer(7))).has_coerce_map_from(A)
True
```

The QuiverAlgebra can create elements from QuiverPaths or from elements of the base ring:

```
sage: A(5)
5*e_1 + 5*e_2 + 5*e_3
sage: r = PQ([(1, 2, 'b'), (2, 3, 'd')])
sage: e2 = PQ([(2, 2)])
sage: x = A(p) + A(e2)
sage: x
a*d + e_2
sage: y = A(p) + A(r)
sage: y
b*d + a*d
```

```
>>> from sage.all import *
>>> A(Integer(5))
5*e_1 + 5*e_2 + 5*e_3
>>> r = PQ([(Integer(1), Integer(2), 'b'), (Integer(2), Integer(3), 'd')])
>>> e2 = PQ([(Integer(2), Integer(2))])
>>> x = A(p) + A(e2)
>>> x
a*d + e_2
>>> y = A(p) + A(r)
>>> y
b*d + a*d
```

QuiverAlgebras are $\mathbf{N}$ -graded algebras. The grading is given by assigning to each basis element the length of the path corresponding to that basis element:

```
sage: x.is_homogeneous()
False
sage: x.degree()
Traceback (most recent call last):
...
ValueError: element is not homogeneous
sage: y.is_homogeneous()
True
sage: y.degree()
2
sage: A[1]
Free module spanned by [a, b, c, d] over Finite Field of size 7
sage: A[2]
Free module spanned by [a*d, b*d] over Finite Field of size 7
```

```
>>> from sage.all import *
>>> x.is_homogeneous()
False
>>> x.degree()
Traceback (most recent call last):
...
```

(continues on next page)

(continued from previous page)

```

ValueError: element is not homogeneous
>>> y.is_homogeneous()
True
>>> y.degree()
2
>>> A[Integer(1)]
Free module spanned by [a, b, c, d] over Finite Field of size 7
>>> A[Integer(2)]
Free module spanned by [a*d, b*d] over Finite Field of size 7
    
```

The category of right modules over a given quiver algebra is equivalent to the category of representations of that quiver. A quiver representation is a diagram in the category of vector spaces whose underlying graph is the quiver. So to each vertex of the quiver we assign a vector space and to each edge of the quiver a linear map between the vector spaces assigned to the start and end vertices of that edge. To create the zero representation we just specify the base ring and the path semigroup:

```

sage: Z = Q1.path_semigroup().representation(GF(5))
sage: Z.is_zero()
True
    
```

```

>>> from sage.all import *
>>> Z = Q1.path_semigroup().representation(GF(Integer(5)))
>>> Z.is_zero()
True
    
```

To each vertex of a quiver there is associated a simple module, an indecomposable projective, and an indecomposable injective, and these can be created from the quiver:

```

sage: S = PQ.S(GF(3), 1)
sage: I = PQ.I(QQ, 2)
sage: P = PQ.P(GF(3), 1)
    
```

```

>>> from sage.all import *
>>> S = PQ.S(GF(Integer(3)), Integer(1))
>>> I = PQ.I(QQ, Integer(2))
>>> P = PQ.P(GF(Integer(3)), Integer(1))
    
```

Radicals, socles, tops, and quotients can all be computed and we can test if modules are simple or semisimple, get their dimension, and test for equality. Like quivers, `QuiverRep` objects are unique and therefore equal if and only if they are identical:

```

sage: P.is_simple()
False
sage: P.dimension()
6
sage: R = P.radical()
sage: P.socle()
Representation with dimension vector (0, 0, 3)
sage: (P/R).is_simple()
True
sage: P == R
False
    
```

(continues on next page)

(continued from previous page)

```
sage: P.top() is P/R
True
```

```
>>> from sage.all import *
>>> P.is_simple()
False
>>> P.dimension()
6
>>> R = P.radical()
>>> P.socle()
Representation with dimension vector (0, 0, 3)
>>> (P/R).is_simple()
True
>>> P == R
False
>>> P.top() is P/R
True
```

There are special methods to deal with modules that are given as right ideals in the quiver algebra. To create such a module pass the keyword `option='paths'` along with a path or list of paths that generate the desired ideal:

```
sage: M = PQ.representation(QQ, [[(1, 1)], [(1, 2, 'a')]], option='paths')
sage: M.dimension_vector()
(1, 2, 3)
```

```
>>> from sage.all import *
>>> M = PQ.representation(QQ, [(Integer(1), Integer(1))], [(Integer(1), Integer(2),
↪ 'a')]], option='paths')
>>> M.dimension_vector()
(1, 2, 3)
```

There are also special methods to deal with modules that are given as the linear dual of a right ideal in the quiver algebra. To create such a module, pass the keyword `option='dual paths'` to the constructor along with a path or list of paths. The module returned is the dual of the ideal created in the opposite quiver by the reverses of the given paths:

```
sage: D = PQ.representation(QQ, [[(1, 1)], [(1, 2, 'a')]], option='dual paths')
sage: D.dimension_vector()
(2, 0, 0)
```

```
>>> from sage.all import *
>>> D = PQ.representation(QQ, [(Integer(1), Integer(1))], [(Integer(1), Integer(2),
↪ 'a')]], option='dual paths')
>>> D.dimension_vector()
(2, 0, 0)
```

For modules that are not a standard module or an ideal of the quiver algebra `QuiverRep` can take as input two dictionaries. The first associates to each vertex a vector space or an integer (the desired dimension of the vector space), the second associates to each edge a map or a matrix or something from which sage can construct a map:

```
sage: PQ2 = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M2 = PQ2.representation(QQ, {1: QQ^2, 2: QQ^1}, {(1, 2, 'a'): [1, 0], (1, 2, 'b
↪ '): [0, 1]})
```

(continues on next page)

(continued from previous page)

```
sage: M.get_space(2)
Vector space of dimension 2 over Rational Field
sage: M2.get_space(2)
Vector space of dimension 1 over Rational Field
sage: M.get_map((1, 2, 'a'))
Vector space morphism represented by the matrix:
[1 0]
Domain: Vector space of dimension 1 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
```

```
>>> from sage.all import *
>>> PQ2 = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M2 = PQ2.representation(QQ, {Integer(1): QQ**Integer(2), Integer(2):_
↳ QQ**Integer(1)}, {(Integer(1), Integer(2), 'a'): [Integer(1), Integer(0)],_
↳ (Integer(1), Integer(2), 'b'): [Integer(0), Integer(1)]})
>>> M.get_space(Integer(2))
Vector space of dimension 2 over Rational Field
>>> M2.get_space(Integer(2))
Vector space of dimension 1 over Rational Field
>>> M.get_map((Integer(1), Integer(2), 'a'))
Vector space morphism represented by the matrix:
[1 0]
Domain: Vector space of dimension 1 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
```

A homomorphism between two quiver representations is given by homomorphisms between the spaces assigned to the vertices of those representations such that those homomorphisms commute with the edge maps of the representations. The homomorphisms are created in the usual Sage syntax, the defining data given by a dictionary associating maps to vertices:

```
sage: P2 = PQ2.P(QQ, 1)
sage: f = P2.hom({1:[1, 1], 2:[[1], [1]]}, M2)
```

```
>>> from sage.all import *
>>> P2 = PQ2.P(QQ, Integer(1))
>>> f = P2.hom({Integer(1):[Integer(1), Integer(1)], Integer(2):[[Integer(1)],_
↳ [Integer(1)]]}, M2)
```

When the domain is given as a right ideal in the quiver algebra we can also create a homomorphism by just giving a single element in the codomain. The map is then induced by acting on that element:

```
sage: x = P2.gens('x')[0]
sage: x
x_0
sage: f == P2.hom(f(x), M2)
True
```

```
>>> from sage.all import *
>>> x = P2.gens('x')[Integer(0)]
>>> x
x_0
```

(continues on next page)

(continued from previous page)

```
>>> f == P2.hom(f(x), M2)
True
```

As you can see, the above homomorphisms can be applied to elements. Just like elements, addition is defined via the + operator. On elements scalar multiplication is defined via the * operator but on homomorphisms * defines composition, so scalar multiplication is done using a method:

```
sage: g = f + f
sage: g == f.scalar_mult(2)
True
sage: g == 2*f           # This multiplies the map with the scalar 2
True
sage: g(x) == 2*f(x)    # This applies the map, then multiplies by the scalar
True
```

```
>>> from sage.all import *
>>> g = f + f
>>> g == f.scalar_mult(Integer(2))
True
>>> g == Integer(2)*f      # This multiplies the map with the scalar 2
True
>>> g(x) == Integer(2)*f(x) # This applies the map, then multiplies by the scalar
True
```

The `direct_sum` method for modules returns only the resulting module by default. But can also return the projection and inclusion homomorphisms into the various factors:

```
sage: N2, inclusions, projections = M2.direct_sum([P2], return_maps=True)
sage: inclusions[0].domain() is M2
True
sage: projections[0].codomain() is M2
True
sage: (projections[0]*inclusions[0]).is_isomorphism()
True
```

```
>>> from sage.all import *
>>> N2, inclusions, projections = M2.direct_sum([P2], return_maps=True)
>>> inclusions[Integer(0)].domain() is M2
True
>>> projections[Integer(0)].codomain() is M2
True
>>> (projections[Integer(0)]*inclusions[Integer(0)]).is_isomorphism()
True
```

As you see above we can determine if a given map is an isomorphism. Testing for injectivity and surjectivity works as well:

```
sage: f.is_injective()
False
sage: f.is_surjective()
False
```

```
>>> from sage.all import *
>>> f.is_injective()
False
>>> f.is_surjective()
False
```

We can create all the standard modules associated to maps:

```
sage: f.kernel()
Representation with dimension vector (0, 1)
sage: f.cokernel()
Representation with dimension vector (1, 0)
sage: im = f.image()
sage: im
Representation with dimension vector (1, 1)
```

```
>>> from sage.all import *
>>> f.kernel()
Representation with dimension vector (0, 1)
>>> f.cokernel()
Representation with dimension vector (1, 0)
>>> im = f.image()
>>> im
Representation with dimension vector (1, 1)
```

These methods, as well as the `submodule` and `quotient` methods that are defined for representations, return only the resulting representation. To get the inclusion map of a submodule or the factor homomorphism of a quotient use `coerce_map_from`:

```
sage: incl = M2.coerce_map_from(im)
sage: incl.domain() is im
True
sage: incl.codomain() is M2
True
sage: incl.is_injective()
True
```

```
>>> from sage.all import *
>>> incl = M2.coerce_map_from(im)
>>> incl.domain() is im
True
>>> incl.codomain() is M2
True
>>> incl.is_injective()
True
```

Both `QuiverRep` objects and `QuiverRepHom` objects have `linear_dual` and `algebraic_dual` methods. The `linear_dual` method applies the functor $\text{Hom}_k(\dots, k)$ where k is the base ring of the representation, and the `algebraic_dual` method applies the functor $\text{Hom}_Q(\dots, kQ)$ where kQ is the quiver algebra. Both these functors yield left modules. A left module is equivalent to a right module over the opposite algebra, and the opposite of a quiver algebra is the algebra of the opposite quiver, so both these methods yield modules and representations of the opposite quiver:

```
sage: f.linear_dual()
Homomorphism of representations of Reverse of (): Multi-digraph on 2 vertices
sage: D = M2.algebraic_dual()
sage: D.quiver() is PQ2.reverse().quiver()
True
```

```
>>> from sage.all import *
>>> f.linear_dual()
Homomorphism of representations of Reverse of (): Multi-digraph on 2 vertices
>>> D = M2.algebraic_dual()
>>> D.quiver() is PQ2.reverse().quiver()
True
```

Todo

Change the wording `Reverse of ()` into something more meaningful.

There is a method returning the projective cover of any module. Note that this method returns the homomorphism; to get the module take the domain of the homomorphism:

```
sage: cov = M2.projective_cover()
sage: cov
Homomorphism of representations of Multi-digraph on 2 vertices
sage: cov.domain()
Representation with dimension vector (2, 4)
```

```
>>> from sage.all import *
>>> cov = M2.projective_cover()
>>> cov
Homomorphism of representations of Multi-digraph on 2 vertices
>>> cov.domain()
Representation with dimension vector (2, 4)
```

As projective covers are computable, so are the transpose and Auslander-Reiten translates of modules:

```
sage: M2.transpose()
Representation with dimension vector (4, 3)
sage: PQ2.I(QQ, 1).AR_translate()
Representation with dimension vector (3, 2)
```

```
>>> from sage.all import *
>>> M2.transpose()
Representation with dimension vector (4, 3)
>>> PQ2.I(QQ, Integer(1)).AR_translate()
Representation with dimension vector (3, 2)
```

We have already used the `gens` method above to get an element of a quiver representation. An element of a quiver representation is simply a choice of element from each of the spaces assigned to the vertices of the quiver. Addition, subtraction, and scalar multiplication are performed pointwise and implemented by the usual operators:

```
sage: M2.dimension_vector()
(2, 1)
sage: x, y, z = M2.gens('xyz')
sage: 2*x + y != x + 2*y
True
```

```
>>> from sage.all import *
>>> M2.dimension_vector()
(2, 1)
>>> x, y, z = M2.gens('xyz')
>>> Integer(2)*x + y != x + Integer(2)*y
True
```

To create a specific element of a given representation we just specify the representation and a dictionary associating to each vertex an element of the space associated to that vertex in the representation:

```
sage: w = M2({1:(1, -1), 2:(3,)})
sage: w.get_element(1)
(1, -1)
```

```
>>> from sage.all import *
>>> w = M2({Integer(1):(Integer(1), -Integer(1)), Integer(2):(Integer(3),)})
>>> w.get_element(Integer(1))
(1, -1)
```

The right action of a quiver algebra on an element is implemented via the `*` operator:

```
sage: A2 = x.quiver().path_semigroup().algebra(QQ)
sage: a = A2('a')
sage: x*a == z
True
```

```
>>> from sage.all import *
>>> A2 = x.quiver().path_semigroup().algebra(QQ)
>>> a = A2('a')
>>> x*a == z
True
```

class sage.quivers.representation.**QuiverRepElement** (*parent, elements=None, name=None*)

Bases: `ModuleElement`

An element of a quiver representation is a choice of element from each of the spaces assigned to the vertices of the quiver. Addition, subtraction, and scalar multiplication of these elements is done pointwise within these spaces.

INPUT:

- `module` – `QuiverRep` (default: `None`); the module to which the element belongs
- `elements` – dictionary (default: empty) associating to each vertex a vector or an object from which sage can create a vector. Not all vertices must be specified, unspecified vertices will be assigned the zero vector of the space associated to that vertex in the given module. Keys that do not correspond to a vertex are ignored.
- `name` – string (default: `None`); the name of the element

OUTPUT: `QuiverRepElement`

Note

The constructor needs to know the quiver in order to create an element of a representation over that quiver. The default is to read this information from `module` as well as to fill in unspecified vectors with the zeros of the spaces in `module`. If `module` is `None` then `quiver` *MUST* be a quiver and each vertex *MUST* be specified or an error will result. If both `module` and `quiver` are given then `quiver` is ignored.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = dict((v, GF(3)^2) for v in Q.quiver())
sage: M = Q.representation(GF(3), spaces)
sage: elems = {1: (1, 0), 2: (0, 1), 3: (2, 1)}
sage: M(elems)
Element of quiver representation
sage: v = M(elems, 'v')
sage: v
v
sage: (v + v + v).is_zero()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳{Integer(3):['c']}}).path_semigroup()
>>> spaces = dict((v, GF(Integer(3))**Integer(2)) for v in Q.quiver())
>>> M = Q.representation(GF(Integer(3)), spaces)
>>> elems = {Integer(1): (Integer(1), Integer(0)), Integer(2): (Integer(0),
↳Integer(1)), Integer(3): (Integer(2), Integer(1))}
>>> M(elems)
Element of quiver representation
>>> v = M(elems, 'v')
>>> v
v
>>> (v + v + v).is_zero()
True
```

`copy()`

Return a copy of `self`.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = dict((v, GF(3)^2) for v in Q.quiver())
sage: M = Q.representation(GF(3), spaces)
sage: elems = {1: (1, 0), 2: (0, 1), 3: (2, 1)}
sage: v = M(elems)
sage: w = v.copy()
sage: w._set_element((0, 0), 1)
sage: w.get_element(1)
(0, 0)
sage: v.get_element(1)
(1, 0)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳{Integer(3):['c']}}).path_semigroup()
>>> spaces = dict((v, GF(Integer(3))**Integer(2)) for v in Q.quiver())
>>> M = Q.representation(GF(Integer(3)), spaces)
>>> elems = {Integer(1): (Integer(1), Integer(0)), Integer(2): (Integer(0),
↳Integer(1)), Integer(3): (Integer(2), Integer(1))}
>>> v = M(elems)
>>> w = v.copy()
>>> w._set_element((Integer(0), Integer(0)), Integer(1))
>>> w.get_element(Integer(1))
(0, 0)
>>> v.get_element(Integer(1))
(1, 0)
```

get_element (*vertex*)

Return the element at the given vertex.

INPUT:

- *vertex* – integer; a vertex of the quiver

OUTPUT: the vector assigned to the given vertex

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = dict((v, GF(3)^2) for v in Q.quiver())
sage: M = Q.representation(GF(3), spaces)
sage: elems = {1: (1, 0), 2: (0, 1), 3: (2, 1)}
sage: v = M(elems)
sage: v.get_element(1)
(1, 0)
sage: v.get_element(3)
(2, 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳{Integer(3):['c']}}).path_semigroup()
>>> spaces = dict((v, GF(Integer(3))**Integer(2)) for v in Q.quiver())
>>> M = Q.representation(GF(Integer(3)), spaces)
>>> elems = {Integer(1): (Integer(1), Integer(0)), Integer(2): (Integer(0),
↳Integer(1)), Integer(3): (Integer(2), Integer(1))}
>>> v = M(elems)
>>> v.get_element(Integer(1))
(1, 0)
>>> v.get_element(Integer(3))
(2, 1)
```

is_zero ()

Test whether *self* is zero.

OUTPUT: boolean, True if the element is the zero element, False otherwise

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = dict((v, GF(3)^2) for v in Q.quiver())
sage: M = Q.representation(GF(3), spaces)
sage: elems = {1: (1, 0), 2: (0, 1), 3: (2, 1)}
sage: v = M(elems)
sage: v.is_zero()
False
sage: w = M()
sage: w.is_zero()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳ {Integer(3):['c']}}).path_semigroup()
>>> spaces = dict((v, GF(Integer(3))**Integer(2)) for v in Q.quiver())
>>> M = Q.representation(GF(Integer(3)), spaces)
>>> elems = {Integer(1): (Integer(1), Integer(0)), Integer(2): (Integer(0),
↳ Integer(1)), Integer(3): (Integer(2), Integer(1))}
>>> v = M(elems)
>>> v.is_zero()
False
>>> w = M()
>>> w.is_zero()
True
```

quiver()

Return the quiver of the representation.

OUTPUT: `DiGraph`, the quiver of the representation

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{3:['c']}}).path_semigroup()
sage: P = Q.P(QQ, 1)
sage: v = P.an_element()
sage: v.quiver() is Q.quiver()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳ {Integer(3):['c']}}).path_semigroup()
>>> P = Q.P(QQ, Integer(1))
>>> v = P.an_element()
>>> v.quiver() is Q.quiver()
True
```

support()

Return the support of `self` as a list.

The support is the set of vertices to which a nonzero vector is associated.

OUTPUT: list; the support

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{3:['c']}}).path_semigroup()
sage: spaces = dict((v, GF(3)^2) for v in Q.quiver())
sage: M = Q.representation(GF(3), spaces)
sage: elems = {1: (1, 0), 2: (0, 0), 3: (2, 1)}
sage: v = M(elems)
sage: v.support()
[1, 3]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳ {Integer(3):['c']}}).path_semigroup()
>>> spaces = dict((v, GF(Integer(3))**Integer(2)) for v in Q.quiver())
>>> M = Q.representation(GF(Integer(3)), spaces)
>>> elems = {Integer(1): (Integer(1), Integer(0)), Integer(2): (Integer(0),
↳ Integer(0)), Integer(3): (Integer(2), Integer(1))}
>>> v = M(elems)
>>> v.support()
[1, 3]
```

class sage.quivers.representation.**QuiverRepFactory**

Bases: UniqueFactory

A quiver representation is a diagram in the category of vector spaces whose underlying graph is the quiver. Giving a finite dimensional representation is equivalent to giving a finite dimensional right module for the path algebra of the quiver.

INPUT:

The first two arguments specify the base ring and the quiver, and they are always required:

- k – ring, the base ring of the representation
- P – the partial semigroup formed by the paths of the quiver of the representation

Then to specify the spaces and maps associated to the quiver there are three possible options. The first is the 'values' option, where the next two arguments give the data to be assigned. The following can either be the next two entries in the argument list or they can be passed by keyword. If the argument list is long enough the keywords are ignored; the keywords are only checked in the event that the argument list does not have enough entries after P .

- `spaces` – dictionary (default: empty) associating to each vertex a free module over the base ring k . Not all vertices must be specified; unspecified vertices are automatically set to k^0 . Keys of the dictionary that don't correspond to vertices are ignored.
- `maps` – dictionary (default: empty) associating to each edge a map whose domain and codomain are the spaces associated to the initial and terminal vertex of the edge respectively. Not all edges must be specified; unspecified edges are automatically set to the zero map. Keys of the dictionary that don't correspond to edges are ignored.

The second option is the `paths` option which creates a module by generating a right ideal from a list of paths. Thus the basis elements of this module correspond to paths of the quiver and the maps are given by right multiplication by the corresponding edge. As above this can be passed either as the next entry in the argument list or as a keyword. The keyword is only checked if there is no entry in the argument list after Q .

- `basis` – list; a nonempty list of paths in the quiver Q . Entries that do not represent valid paths are ignored and duplicate paths are deleted. There must be at least one valid path in the list or a `ValueError` is raised. The closure of this list under right multiplication forms the basis of the resulting representation.

The third option is the `dual_paths` option which creates the dual of a left ideal in the quiver algebra. Thus the basis elements of this module correspond to paths of the quiver and the maps are given by deleting the corresponding edge from the start of the path (the edge map is zero on a path if that edge is not the initial edge of the path). As above this can be passed either as the next entry in the argument list or as a keyword.

- `basis` – list; a nonempty list of paths in the quiver Q . Entries that do not represent valid paths are ignored and duplicate paths are deleted. There must be at least one valid path in the list or a `ValueError` is raised. The closure of this list under left multiplication of edges forms the basis of the resulting representation.

Using the second and third options requires that the following keyword be passed to the constructor. This must be passed as a keyword.

- `option` – string (default: `None`); either `'values'` or `'paths'` or `'dual_paths'`. `None` is equivalent to `'values'`

OUTPUT: `QuiverRep`

EXAMPLES:

```
sage: Q1 = DiGraph({1:{2:['a']}}).path_semigroup()
```

```
>>> from sage.all import *
>>> Q1 = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
```

When the `option` keyword is not supplied the constructor uses the `'values'` option and expects the spaces and maps to be specified. If no maps or spaces are given the zero module is created:

```
sage: M = Q1.representation(GF(5))
sage: M.is_zero()
True
```

```
>>> from sage.all import *
>>> M = Q1.representation(GF(Integer(5)))
>>> M.is_zero()
True
```

The simple modules, indecomposable projectives, and indecomposable injectives are examples of quiver representations:

```
sage: S = Q1.S(GF(3), 1)
sage: I = Q1.I(QQ, 2)
sage: P = Q1.P(GF(3), 1)
```

```
>>> from sage.all import *
>>> S = Q1.S(GF(Integer(3)), Integer(1))
>>> I = Q1.I(QQ, Integer(2))
>>> P = Q1.P(GF(Integer(3)), Integer(1))
```

Various standard submodules can be computed, such as radicals and socles. We can also form quotients and test for certain attributes such as semisimplicity:

```
sage: R = P.radical()
sage: R.is_zero()
False
sage: (P/R).is_simple()
True
```

(continues on next page)

(continued from previous page)

```
sage: P == R
False
```

```
>>> from sage.all import *
>>> R = P.radical()
>>> R.is_zero()
False
>>> (P/R).is_simple()
True
>>> P == R
False
```

With the option 'paths' the input data should be a list of `QuiverPaths` or things that `QuiverPaths` can be constructed from. The resulting module is the submodule generated by these paths in the quiver algebra, when considered as a right module over itself:

```
sage: P1 = Q1.representation(QQ, [[(1, 1)]], option='paths')
sage: P1.dimension()
2
```

```
>>> from sage.all import *
>>> P1 = Q1.representation(QQ, [(Integer(1), Integer(1))], option='paths')
>>> P1.dimension()
2
```

In the following example, the 3rd and 4th paths are actually the same, so the duplicate is removed:

```
sage: N = Q1.representation(QQ, [(1, 1)], [(2, 2)], [(1, 2, 'a')],
.....:                        [(1, 2, 'a')]], option='paths')
sage: N.dimension()
3
```

```
>>> from sage.all import *
>>> N = Q1.representation(QQ, [(Integer(1), Integer(1))], [(Integer(2),
↪ Integer(2))], [(Integer(1), Integer(2), 'a')],
...              [(Integer(1), Integer(2), 'a')]], option='paths')
>>> N.dimension()
3
```

The dimension at each vertex equals the number of paths in the closed basis whose terminal point is that vertex:

```
sage: Q2 = DiGraph({1:{2:['a']}, 3:['b', 'c']}, 2:{3:['d']}).path_semigroup()
sage: M = Q2.representation(QQ, [(2, 2)], [(1, 2, 'a')]], option='paths')
sage: M.dimension_vector()
(0, 2, 2)
sage: N = Q2.representation(QQ, [(2, 2)], [(1, 2, 'a'), (2, 3, 'd')]], option=
↪ 'paths')
sage: N.dimension_vector()
(0, 1, 2)
```

```
>>> from sage.all import *
>>> Q2 = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b', 'c']}, ↪
```

(continues on next page)

(continued from previous page)

```

↪Integer(2):{Integer(3):['d']})}.path_semigroup()
>>> M = Q2.representation(QQ, [[(Integer(2), Integer(2))], [(Integer(1), ↪
↪Integer(2), 'a')]], option='paths')
>>> M.dimension_vector()
(0, 2, 2)
>>> N = Q2.representation(QQ, [[(Integer(2), Integer(2))], [(Integer(1), ↪
↪Integer(2), 'a'), (Integer(2), Integer(3), 'd')]], option='paths')
>>> N.dimension_vector()
(0, 1, 2)

```

create_key(*k*, *P*, **args*, ***kws*)

Return a key for the specified module.

The key is a tuple. The first and second entries are the base ring *k* and the partial semigroup *P* formed by the paths of a quiver. The third entry is the *option* and the remaining entries depend on that option. If the option is 'values' and the quiver has *n* vertices then the next *n* entries are the vector spaces to be assigned to those vertices. After that are the matrices of the maps assigned to edges, listed in the same order that *Q.edges(sort=True)* uses. If the option is 'paths' or 'dual paths' then the next entry is a tuple containing a sorted list of the paths that form a basis of the quiver.

INPUT:

See the class documentation.

OUTPUT: tuple

EXAMPLES:

```

sage: P = DiGraph({1:{2:['a']}}).path_semigroup()
sage: from sage.quivers.representation import QuiverRep
sage: QuiverRep.create_key(GF(5), P)
(Finite Field of size 5,
 Partial semigroup formed by the directed paths of Multi-digraph on 2 ↪
↪vertices,
 'values',
 Vector space of dimension 0 over Finite Field of size 5,
 Vector space of dimension 0 over Finite Field of size 5,
 [])

```

```

>>> from sage.all import *
>>> P = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
>>> from sage.quivers.representation import QuiverRep
>>> QuiverRep.create_key(GF(Integer(5)), P)
(Finite Field of size 5,
 Partial semigroup formed by the directed paths of Multi-digraph on 2 ↪
↪vertices,
 'values',
 Vector space of dimension 0 over Finite Field of size 5,
 Vector space of dimension 0 over Finite Field of size 5,
 [])

```

create_object(*version*, *key*, ***extra_args*)

Create a *QuiverRep_generic* or *QuiverRep_with_path_basis* object from the key.

The key is a tuple. The first and second entries are the base ring *k* and the quiver *Q*. The third entry is the

'option' and the remaining entries depend on that option. If the option is 'values' and the quiver has n vertices then the next n entries are the vector spaces to be assigned to those vertices. After that are the matrices of the maps assigned to edges, listed in the same order that `Q.edges(sort=True)` uses. If the option is 'paths' or 'dual paths' then the next entry is a tuple containing a sorted list of the paths that form a basis of the quiver.

INPUT:

- version – the version of sage, this is currently ignored
- key – tuple

OUTPUT: *QuiverRep_generic* or *QuiverRep_with_path_basis*

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}}).path_semigroup()
sage: from sage.quivers.representation import QuiverRep
sage: key = QuiverRep.create_key(GF(5), Q)
sage: QuiverRep.create_object(0, key)
Representation with dimension vector (0, 0)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
>>> from sage.quivers.representation import QuiverRep
>>> key = QuiverRep.create_key(GF(Integer(5)), Q)
>>> QuiverRep.create_object(Integer(0), key)
Representation with dimension vector (0, 0)
```

class `sage.quivers.representation.QuiverRep_generic`($k, P, spaces, maps$)

Bases: `WithEqualityById, Module`

A generic quiver representation.

This class should not be called by the user.

Call `QuiverRep` with `option='values'` (which is the default) instead.

INPUT:

- k – ring, the base ring of the representation
- P – the path semigroup of the quiver Q of the representation
- `spaces` – dictionary (default: empty) associating to each vertex a free module over the base ring k . Not all vertices need to be specified, unspecified vertices are automatically set to k^0 . Keys of the dictionary that don't correspond to vertices are ignored.
- `maps` – dictionary (default: empty) associating to each edge a map whose domain and codomain are the spaces associated to the initial and terminal vertex of the edge respectively. Not all edges need to be specified, unspecified edges are automatically set to the zero map. Keys of the dictionary that don't correspond to edges are ignored.

OUTPUT: `QuiverRep`

EXAMPLES:

```
sage: Q = DiGraph({1:{3:['a']}, 2:{3:['b']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^3, 3: QQ^2}
sage: maps = {(1, 3, 'a'): (QQ^2).Hom(QQ^2).identity(), (2, 3, 'b'): [[1, 0], [0, 1], [0, 1]]}
```

(continues on next page)

(continued from previous page)

```
↪0], [0, 0]]}
sage: M = Q.representation(QQ, spaces, maps)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(3):['a']}, Integer(2):{Integer(3):['b']}}).
↪path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(3), Integer(3):
↪QQ**Integer(2)}
>>> maps = {(Integer(1), Integer(3), 'a'): (QQ**Integer(2)).Hom(QQ**Integer(2)).
↪identity(), (Integer(2), Integer(3), 'b'): [[Integer(1), Integer(0)],
↪[Integer(0), Integer(0)], [Integer(0), Integer(0)]]}
>>> M = Q.representation(QQ, spaces, maps)
```

```
sage: Q = DiGraph({1:{2:['a']}}).path_semigroup()
sage: P = Q.P(GF(3), 1)
sage: I = Q.I(QQ, 1)
sage: P.an_element() in P
True
sage: I.an_element() in P
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
>>> P = Q.P(GF(Integer(3)), Integer(1))
>>> I = Q.I(QQ, Integer(1))
>>> P.an_element() in P
True
>>> I.an_element() in P
False
```

AR_translate()

Return the Auslander-Reiten translate of self.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.representation(GF(3), {1: 1, 2: 1}, {(1, 2, 'a'): 1})
sage: tauM = M.AR_translate()
sage: tauM
Representation with dimension vector (1, 1)
sage: tauM.get_map((1, 2, 'a')).matrix()
[1]
sage: tauM.get_map((1, 2, 'b')).matrix()
[0]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.representation(GF(Integer(3)), {Integer(1): Integer(1), Integer(2):
↪Integer(1)}, {(Integer(1), Integer(2), 'a'): Integer(1)})
>>> tauM = M.AR_translate()
>>> tauM
```

(continues on next page)

(continued from previous page)

```
Representation with dimension vector (1, 1)
>>> tauM.get_map((Integer(1), Integer(2), 'a')).matrix()
[1]
>>> tauM.get_map((Integer(1), Integer(2), 'b')).matrix()
[0]
```

The module `M` above is its own AR translate. This is not always true:

```
sage: Q2 = DiGraph({3:{1:['b']}, 5:{3:['a']}}).path_semigroup()
sage: Q2.S(QQ, 5).AR_translate()
Representation with dimension vector (0, 1, 0)
```

```
>>> from sage.all import *
>>> Q2 = DiGraph({Integer(3):{Integer(1):['b']}, Integer(5):{Integer(3):['a']}}
↳}).path_semigroup()
>>> Q2.S(QQ, Integer(5)).AR_translate()
Representation with dimension vector (0, 1, 0)
```

Element

alias of `QuiverRepElement`

Hom(codomain)

Return the hom space from self to codomain.

For more information see the `QuiverHomSpace` documentation.

actor()

Return the quiver path algebra acting on this representation.

OUTPUT: a quiver path algebra

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}}).path_semigroup()
sage: M = Q.representation(GF(5))
sage: M.base_ring()
Finite Field of size 5
sage: M.actor()
Path algebra of Multi-digraph on 2 vertices over Finite Field of size 5
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
>>> M = Q.representation(GF(Integer(5)))
>>> M.base_ring()
Finite Field of size 5
>>> M.actor()
Path algebra of Multi-digraph on 2 vertices over Finite Field of size 5
```

algebraic_dual(basis=False)

Compute the algebraic dual $\text{Hom}_Q(M, kQ)$ of the module $M = \text{self}$.

INPUT:

- `basis` – boolean; if `False`, then only the module is returned. If `True`, then a tuple is returned. The first element is the `QuiverRep` and the second element is a dictionary which associates to each vertex

a list. The elements of this list are the homomorphisms which correspond to the basis elements of that vertex in the module.

OUTPUT: *QuiverRep* or tuple

Note

Here kQ is the path algebra considered as a right module over itself. If e is an edge of the quiver Q then we let $(fe)(m) = ef(m)$. This gives $\text{Hom}_Q(M, kQ)$ a module structure over the opposite quiver $Q.\text{reverse}()$.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b'], 3: ['c', 'd']}, 2:{3:['e']}}).path_
      ↪semigroup()
sage: Q.free_module(GF(7)).algebraic_dual().dimension_vector()
(7, 2, 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b'], Integer(3): ['c', 'd']},
      ↪Integer(2):{Integer(3):['e']}}).path_semigroup()
>>> Q.free_module(GF(Integer(7))).algebraic_dual().dimension_vector()
(7, 2, 1)
```

an_element()

Return an element of *self*.

OUTPUT: *QuiverRepElement*

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: M.an_element()
Element of quiver representation
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> M.an_element()
Element of quiver representation
```

coordinates (vector)

Return the coordinates when *vector* is expressed in terms of the gens.

INPUT:

- *vector* – *QuiverRepElement*

OUTPUT:

- list, the coefficients when the vector is expressed as a linear combination of the generators of the module

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: x, y, z = M.gens('xyz')
sage: M.coordinates(x - y + z)
[1, -1, 1]
sage: M.coordinates(M.an_element())
[1, 1, 0]
sage: M.an_element() == x + y
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> x, y, z = M.gens('xyz')
>>> M.coordinates(x - y + z)
[1, -1, 1]
>>> M.coordinates(M.an_element())
[1, 1, 0]
>>> M.an_element() == x + y
True
```

dimension (*vertex=None*)

Return the dimension of the space associated to the given vertex *vertex*.

INPUT:

- *vertex* – integer or None (default: None), the given vertex

OUTPUT:

- integer, the dimension over the base ring of the space associated to the given vertex. If *vertex=None* then the dimension over the base ring of the module is returned

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: P = Q.P(GF(2), 1)
sage: P.dimension(1)
1
sage: P.dimension(2)
2
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> P = Q.P(GF(Integer(2)), Integer(1))
>>> P.dimension(Integer(1))
1
>>> P.dimension(Integer(2))
2
```

The total dimension of the module is the sum of the dimensions at each vertex:

```
sage: P.dimension()
3
```

```
>>> from sage.all import *
>>> P.dimension()
3
```

dimension_vector()

Return the dimension vector of the representation.

OUTPUT: tuple

Note

The order of the entries in the tuple matches the order given by calling the `vertices()` method on the quiver.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: P = Q.P(GF(2), 1)
sage: P.dimension_vector()
(1, 2)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> P = Q.P(GF(Integer(2)), Integer(1))
>>> P.dimension_vector()
(1, 2)
```

Each coordinate of the dimension vector is the dimension of the space associated to that coordinate:

```
sage: P.get_space(2).dimension()
2
```

```
>>> from sage.all import *
>>> P.get_space(Integer(2)).dimension()
2
```

direct_sum(modules, return_maps=False)

Return the direct sum of `self` with the given modules `modules`.

The modules must be modules over the same quiver and base ring.

INPUT:

- `modules` – QuiverRep or list of QuiverRep's
- `return_maps` – boolean (default: `False`); if `False`, then the output is a single QuiverRep object which is the direct sum of `self` with the given module or modules. If `True`, then the output is a list `[sum, iota, pi]`. The first entry `sum` is the direct sum of `self` with the given module or modules. Both `iota` and `pi` are lists of QuiverRepHoms with one entry for each summand; `iota[i]` is the inclusion map and `pi[i]` is the projection map of the i -th summand. The summands are ordered as given with `self` being the zeroth summand.

OUTPUT: QuiverRep or tuple

EXAMPLES:

```

sage: Q = DiGraph({1:{2:['a'], 3:['b']}, 2:{4:['c']}, 3:{4:['d']}}).path_
↳semigroup()
sage: P1 = Q.P(QQ, 1)
sage: P2 = Q.P(QQ, 2)
sage: S = P1.direct_sum(P2)
sage: P1.dimension_vector()
(1, 1, 1, 2)
sage: P2.dimension_vector()
(0, 1, 0, 1)
sage: S.dimension_vector()
(1, 2, 1, 3)
sage: S, iota, pi = P1.direct_sum(P2, return_maps=True)
sage: iota[0].domain() is P1
True
sage: iota[1].domain() is P2
True
sage: pi[0].codomain() is P1
True
sage: pi[1].codomain() is P2
True
sage: iota[0].codomain() is S
True
sage: iota[1].codomain() is S
True
sage: pi[0].domain() is S
True
sage: pi[1].domain() is S
True
sage: iota[0].get_matrix(4)
[1 0 0]
[0 1 0]
sage: pi[0].get_matrix(4)
[1 0]
[0 1]
[0 0]
sage: P1prime = S/iota[1].image()
sage: f = P1prime.coerce_map_from(S)
sage: g = f*iota[0]
sage: g.is_isomorphism()
True

```

```

>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}, Integer(2):
↳{Integer(4):['c']}, Integer(3):{Integer(4):['d']}}).path_semigroup()
>>> P1 = Q.P(QQ, Integer(1))
>>> P2 = Q.P(QQ, Integer(2))
>>> S = P1.direct_sum(P2)
>>> P1.dimension_vector()
(1, 1, 1, 2)
>>> P2.dimension_vector()
(0, 1, 0, 1)
>>> S.dimension_vector()

```

(continues on next page)

(continued from previous page)

```
(1, 2, 1, 3)
>>> S, iota, pi = P1.direct_sum(P2, return_maps=True)
>>> iota[Integer(0)].domain() is P1
True
>>> iota[Integer(1)].domain() is P2
True
>>> pi[Integer(0)].codomain() is P1
True
>>> pi[Integer(1)].codomain() is P2
True
>>> iota[Integer(0)].codomain() is S
True
>>> iota[Integer(1)].codomain() is S
True
>>> pi[Integer(0)].domain() is S
True
>>> pi[Integer(1)].domain() is S
True
>>> iota[Integer(0)].get_matrix(Integer(4))
[1 0 0]
[0 1 0]
>>> pi[Integer(0)].get_matrix(Integer(4))
[1 0]
[0 1]
[0 0]
>>> P1prime = S/iota[Integer(1)].image()
>>> f = P1prime.coerce_map_from(S)
>>> g = f*iota[Integer(0)]
>>> g.is_isomorphism()
True
```

gens (*names*='v')

Return a tuple of generators of *self* as a *k*-module.

INPUT:

- *names* – an iterable variable of length equal to the number of generators, or a string (default: 'v'); gives the names of the generators either by giving a name to each generator or by giving a name to which an index will be appended

OUTPUT:

- tuple of *QuiverRepElement* objects, the linear generators of the module (over the base ring)

Note

The generators are ordered first by vertex and then by the order given by the `gens()` method of the space associated to that vertex.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
```

(continues on next page)

(continued from previous page)

```
sage: M.gens()
(v_0, v_1, v_2)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> M.gens()
(v_0, v_1, v_2)
```

If a string is given then it is used as the name of each generator, with the index of the generator appended in order to differentiate them:

```
sage: M.gens('generator')
(generator_0, generator_1, generator_2)
```

```
>>> from sage.all import *
>>> M.gens('generator')
(generator_0, generator_1, generator_2)
```

If a list or other iterable variable is given then each generator is named using the appropriate entry. The length of the variable must equal the number of generators (the dimension of the module):

```
sage: M.gens(['w', 'x', 'y', 'z'])
Traceback (most recent call last):
...
TypeError: can only concatenate list (not "str") to list
sage: M.gens(['x', 'y', 'z'])
(x, y, z)
```

```
>>> from sage.all import *
>>> M.gens(['w', 'x', 'y', 'z'])
Traceback (most recent call last):
...
TypeError: can only concatenate list (not "str") to list
>>> M.gens(['x', 'y', 'z'])
(x, y, z)
```

Strings are iterable, so if the length of the string is equal to the number of generators then the characters of the string will be used as the names:

```
sage: M.gens('xyz')
(x, y, z)
```

```
>>> from sage.all import *
>>> M.gens('xyz')
(x, y, z)
```

get_map(*edge*)

Return the map associated to the given edge *edge*.

INPUT:

- *edge* – tuple of the form (initial vertex, terminal vertex, label) specifying the edge whose map is returned

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: Q.P(ZZ, 1).get_map((1, 2, 'a'))
Free module morphism defined by the matrix
[1 0]
Domain: Ambient free module of rank 1 over the principal ideal domain Integer_
↪Ring
Codomain: Ambient free module of rank 2 over the principal ideal domain_
↪Integer Ring
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> Q.P(ZZ, Integer(1)).get_map((Integer(1), Integer(2), 'a'))
Free module morphism defined by the matrix
[1 0]
Domain: Ambient free module of rank 1 over the principal ideal domain Integer_
↪Ring
Codomain: Ambient free module of rank 2 over the principal ideal domain_
↪Integer Ring
```

`get_space(vertex)`

Return the module associated to the given vertex `vertex`.

INPUT:

- `vertex` – integer; a vertex of the quiver of the module

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a'], 3:['b']}}).path_semigroup()
sage: Q.P(QQ, 1).get_space(1)
Vector space of dimension 1 over Rational Field
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b']}}).path_
↪semigroup()
>>> Q.P(QQ, Integer(1)).get_space(Integer(1))
Vector space of dimension 1 over Rational Field
```

`is_semisimple()`

Test whether the representation is semisimple.

OUTPUT: boolean

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: (M/M.radical()).is_semisimple()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
```

(continues on next page)

(continued from previous page)

```
>>> (M/M.radical()).is_semisimple()
True
```

is_simple()

Test whether the representation is simple.

OUTPUT: boolean

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: Q.P(RR, 1).is_simple()
False
sage: Q.S(RR, 1).is_simple()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> Q.P(RR, Integer(1)).is_simple()
False
>>> Q.S(RR, Integer(1)).is_simple()
True
```

is_zero()

Test whether the representation is zero.

OUTPUT: boolean

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.representation(ZZ)
sage: N = Q.representation(ZZ, {1: 1})
sage: M
Representation with dimension vector (0, 0)
sage: N
Representation with dimension vector (1, 0)
sage: M.is_zero()
True
sage: N.is_zero()
False
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.representation(ZZ)
>>> N = Q.representation(ZZ, {Integer(1): Integer(1)})
>>> M
Representation with dimension vector (0, 0)
>>> N
Representation with dimension vector (1, 0)
>>> M.is_zero()
True
>>> N.is_zero()
False
```

linear_combination_of_basis(*coordinates*)

Return the linear combination of the basis for *self* given by *coordinates*.

INPUT:

- *coordinates* – list; a list whose length is the dimension of *self*. The *i*-th element of this list defines the coefficient of the *i*-th basis vector in the linear combination.

OUTPUT: *QuiverRepElement*

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: x, y, z = M.gens('xyz')
sage: e = x - y + z
sage: M.coordinates(e)
[1, -1, 1]
sage: M.linear_combination_of_basis([1, -1, 1]) == e
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> x, y, z = M.gens('xyz')
>>> e = x - y + z
>>> M.coordinates(e)
[1, -1, 1]
>>> M.linear_combination_of_basis([Integer(1), -Integer(1), Integer(1)]) == e
True
```

linear_dual()

Compute the linear dual $\text{Hom}_k(M, k)$ of the module $M = \text{self}$ over the base ring k .

OUTPUT: *QuiverRep*; the dual representation

Note

If e is an edge of the quiver Q then we let $(fe)(m) = f(me)$. This gives $\text{Hom}_k(M, k)$ a module structure over the opposite quiver $Q.\text{reverse}()$.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: M.linear_dual()
Representation with dimension vector (1, 2, 2)
sage: M.linear_dual().quiver() is Q.reverse().quiver()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):['c', 'd']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
```

(continues on next page)

(continued from previous page)

```
>>> M.linear_dual()
Representation with dimension vector (1, 2, 2)
>>> M.linear_dual().quiver() is Q.reverse().quiver()
True
```

projective_cover (*return_maps=False*)

Return the projective cover of *self*.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c','d']}}).path_semigroup()
sage: S1 = Q.S(GF(3), 1)
sage: f1 = S1.projective_cover()
sage: f1.is_surjective()
True
sage: f1._domain
Representation with dimension vector (1, 2, 4)
sage: Q.P(GF(3), 1)
Representation with dimension vector (1, 2, 4)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↪ 'd']}}).path_semigroup()
>>> S1 = Q.S(GF(Integer(3)), Integer(1))
>>> f1 = S1.projective_cover()
>>> f1.is_surjective()
True
>>> f1._domain
Representation with dimension vector (1, 2, 4)
>>> Q.P(GF(Integer(3)), Integer(1))
Representation with dimension vector (1, 2, 4)
```

quiver ()

Return the quiver of the representation.

OUTPUT: `DiGraph`

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}}).path_semigroup()
sage: M = Q.representation(GF(5))
sage: M.quiver() is Q.quiver()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
>>> M = Q.representation(GF(Integer(5)))
>>> M.quiver() is Q.quiver()
True
```

quotient (*sub, check=True*)

Return the quotient of *self* by the submodule *sub*.

INPUT:

- `sub` – `QuiverRep`; this must be a submodule of `self`, meaning the space associated to each vertex v of `sub` is a subspace of the space associated to v in `self` and the map associated to each edge e of `sub` is the restriction of the map associated to e in `self`
- `check` – `boolean`; if `True` then `sub` is checked to verify that it is indeed a submodule of `self` and an error is raised if it is not

OUTPUT: `QuiverRep`, the quotient module `self / sub`

Note

This function returns only a `QuiverRep` object `quot`. The projection map from `self` to `quot` can be obtained by calling `quot.coerce_map_from(self)`.

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.I(GF(3), 3)
sage: N = Q.S(GF(3), 3)
sage: M.quotient(N)
Representation with dimension vector (2, 1, 0)
sage: M.quotient(M.radical())
Representation with dimension vector (2, 0, 0)
sage: M.quotient(M)
Representation with dimension vector (0, 0, 0)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↳ '']}}).path_semigroup()
>>> M = Q.I(GF(Integer(3)), Integer(3))
>>> N = Q.S(GF(Integer(3)), Integer(3))
>>> M.quotient(N)
Representation with dimension vector (2, 1, 0)
>>> M.quotient(M.radical())
Representation with dimension vector (2, 0, 0)
>>> M.quotient(M)
Representation with dimension vector (0, 0, 0)
```

radical()

Return the Jacobson radical of `self`.

OUTPUT: `QuiverRep`; the Jacobson radical

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: M.radical()
Representation with dimension vector (0, 2, 2)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↳ '']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
```

(continues on next page)

(continued from previous page)

```
>>> M.radical()
Representation with dimension vector (0, 2, 2)
```

right_edge_action(*element*, *path*)

Return the result of *element***path*.

INPUT:

- *element* – *QuiverRepElement*, an element of self
- *path* – *QuiverPath* or list of tuples

OUTPUT:

- *QuiverRepElement*, the result of *element***path* when *path* is considered an element of the path algebra of the quiver

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: v = M.an_element()
sage: v.support()
[1, 2, 3]
sage: M.right_edge_action(v, [(1, 1)]).support()
[1]
sage: M.right_edge_action(v, [(1, 1)]).support()
[1]
sage: M.right_edge_action(v, [(1, 2, 'a')]).support()
[2]
sage: M.right_edge_action(v, 'a') == M.right_edge_action(v, [(1, 2, 'a')])
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↪ '']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> v = M.an_element()
>>> v.support()
[1, 2, 3]
>>> M.right_edge_action(v, [(Integer(1), Integer(1))]).support()
[1]
>>> M.right_edge_action(v, [(Integer(1), Integer(1))]).support()
[1]
>>> M.right_edge_action(v, [(Integer(1), Integer(2), 'a')]).support()
[2]
>>> M.right_edge_action(v, 'a') == M.right_edge_action(v, [(Integer(1), ↪
↪ Integer(2), 'a')])
True
```

socle()

The socle of self.

OUTPUT: *QuiverRep*; the socle

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a','b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: M.socle()
Representation with dimension vector (0, 0, 2)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a','b']}, Integer(2):{Integer(3):['c',
↪']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> M.socle()
Representation with dimension vector (0, 0, 2)
```

submodule (*elements*=[], *spaces*=None)

Return the submodule generated by the data.

INPUT:

- *elements* – a collection of `QuiverRepElements` (default: empty list), each should be an element of `self`
- *spaces* – dictionary (default: empty); should contain entries of the form $\{v: S\}$ where v is a vertex of the quiver and S is a subspace of the vector space associated to v

OUTPUT:

- `QuiverRep`, the smallest subrepresentation of `self` containing the given elements and the given subspaces

Note

This function returns only a `QuiverRep` object `sub`. The inclusion map of `sub` into `M = self` can be obtained by calling `M.coerce_map_from(sub)`.

EXAMPLES:

```
sage: Q = DiGraph({1:{3:['a']}, 2:{3:['b']}}).path_semigroup()
sage: spaces = {1: QQ^2, 2: QQ^3, 3: QQ^2}
sage: maps = {(1, 3, 'a'): (QQ^2).Hom(QQ^2).identity(), (2, 3, 'b'): [[1, 0],
↪[0, 0], [0, 0]]}
sage: M = Q.representation(QQ, spaces, maps)
sage: v = M.an_element()
sage: M.submodule([v])
Representation with dimension vector (1, 1, 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(3):['a']}, Integer(2):{Integer(3):['b']}}
↪).path_semigroup()
>>> spaces = {Integer(1): QQ**Integer(2), Integer(2): QQ**Integer(3),
↪Integer(3): QQ**Integer(2)}
>>> maps = {(Integer(1), Integer(3), 'a'): (QQ**Integer(2)).
↪Hom(QQ**Integer(2)).identity(), (Integer(2), Integer(3), 'b'): [[Integer(1),
↪Integer(0)], [Integer(0), Integer(0)], [Integer(0), Integer(0)]]}
>>> M = Q.representation(QQ, spaces, maps)
```

(continues on next page)

(continued from previous page)

```
>>> v = M.an_element()
>>> M.submodule([v])
Representation with dimension vector (1, 1, 1)
```

The smallest submodule containing the vector space at vertex 1 also contains the entire vector space associated to vertex 3 because there is an isomorphism associated to the edge (1, 3, 'a'):

```
sage: M.submodule(spaces={1: QQ^2})
Representation with dimension vector (2, 0, 2)
```

```
>>> from sage.all import *
>>> M.submodule(spaces={Integer(1): QQ**Integer(2)})
Representation with dimension vector (2, 0, 2)
```

The smallest submodule containing the vector space at vertex 2 also contains the image of the rank 1 homomorphism associated to the edge (2, 3, 'b'):

```
sage: M.submodule(spaces={2: QQ^3})
Representation with dimension vector (0, 3, 1)
```

```
>>> from sage.all import *
>>> M.submodule(spaces={Integer(2): QQ**Integer(3)})
Representation with dimension vector (0, 3, 1)
```

As v is not already contained in this submodule, adding it as a generator yields a larger submodule:

```
sage: v.support()
[1, 2, 3]
sage: M.submodule([v], {2: QQ^3})
Representation with dimension vector (1, 3, 1)
```

```
>>> from sage.all import *
>>> v.support()
[1, 2, 3]
>>> M.submodule([v], {Integer(2): QQ**Integer(3)})
Representation with dimension vector (1, 3, 1)
```

Giving no generating data yields the zero submodule:

```
sage: M.submodule().is_zero()
True
```

```
>>> from sage.all import *
>>> M.submodule().is_zero()
True
```

If the given data generates all of M then the result is M :

```
sage: M.submodule(M.gens()) is M
True
```

```
>>> from sage.all import *
>>> M.submodule(M.gens()) is M
True
```

support()

Return the support of `self` as a list.

OUTPUT:

- list, the vertices of the representation that have nonzero spaces associated to them

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a']}, 3:{2:['b'], 4:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 3)
sage: M
Representation with dimension vector (0, 1, 1, 1)
sage: M.support()
[2, 3, 4]
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a']}, Integer(3):{Integer(2):['b'],
↳ Integer(4):['c']}}).path_semigroup()
>>> M = Q.P(QQ, Integer(3))
>>> M
Representation with dimension vector (0, 1, 1, 1)
>>> M.support()
[2, 3, 4]
```

top()

Return the top of `self`.

OUTPUT: QuiverRep; the quotient of `self` by its radical

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: M.top()
Representation with dimension vector (1, 0, 0)
sage: M.top() == M/M.radical()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):['c
↳ ']}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> M.top()
Representation with dimension vector (1, 0, 0)
>>> M.top() == M/M.radical()
True
```

transpose()

Return the transpose of `self`.

The transpose, $\text{Tr}M$, of a module M is defined as follows. Let $p : P_1 \rightarrow P_2$ be the second map in a minimal projective presentation $P_1 \rightarrow P_2 \rightarrow M \rightarrow 0$ of M . If p^t is the algebraic dual of p then define $\text{Tr}M = \text{coker} p^t$.

OUTPUT: `QuiverRep`

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}}).path_semigroup()
sage: M = Q.representation(GF(3), {1: 1, 2: 1}, {(1, 2, 'a'): 1})
sage: M.transpose()
Representation with dimension vector (1, 1)
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}}).path_semigroup()
>>> M = Q.representation(GF(Integer(3)), {Integer(1): Integer(1), Integer(2):
↪ Integer(1)}, {(Integer(1), Integer(2), 'a'): Integer(1)})
>>> M.transpose()
Representation with dimension vector (1, 1)
```

zero_submodule()

Return the zero submodule of `self`.

OUTPUT: `QuiverRep`; the zero submodule of `self`

EXAMPLES:

```
sage: Q = DiGraph({1:{2:['a', 'b']}, 2:{3:['c']}}).path_semigroup()
sage: M = Q.P(QQ, 1)
sage: M.zero_submodule()
Representation with dimension vector (0, 0, 0)
sage: M.zero_submodule().is_zero()
True
```

```
>>> from sage.all import *
>>> Q = DiGraph({Integer(1):{Integer(2):['a', 'b']}, Integer(2):{Integer(3):['c
↪ ']]}}).path_semigroup()
>>> M = Q.P(QQ, Integer(1))
>>> M.zero_submodule()
Representation with dimension vector (0, 0, 0)
>>> M.zero_submodule().is_zero()
True
```

class `sage.quivers.representation.QuiverRep_with_dual_path_basis`(k, P, basis)

Bases: `QuiverRep_generic`

The basis of the module must be closed under left deletion of an edge; that is, deleting any edge from the beginning of any path in the basis must result in a path also contained in the basis of the module.

INPUT:

- k – ring; the base ring of the representation
- P – the path semigroup of the quiver Q of the representation
- `basis` – list (default: empty); should be a list of paths (also lists) in the quiver Q . Entries that do not represent valid paths are ignored and duplicate paths are deleted. The closure of this list under left deletion forms the basis of the resulting representation.

```
class sage.quivers.representation.QuiverRep_with_path_basis(k, P, basis)
```

Bases: *QuiverRep_generic*

The basis of the module must be closed under right multiplication by an edge; that is, appending any edge to the end of any path in the basis must result in either an invalid path or a valid path also contained in the basis of the module.

INPUT:

- k – ring, the base ring of the representation
- P – the path semigroup of the quiver Q of the representation
- *basis* – list (default: empty); should be a list of paths (also lists) in the quiver Q . Entries that do not represent valid paths are ignored and duplicate paths are deleted. The closure of this list under right multiplication forms the basis of the resulting representation.

```
is_left_module()
```

Test whether the basis is closed under left multiplication.

EXAMPLES:

```
sage: Q1 = DiGraph({1:{2:['a']}}).path_semigroup()
sage: P2 = Q1.representation(QQ, [(2, 2)], option='paths')
sage: P2.is_left_module()
False
```

```
>>> from sage.all import *
>>> Q1 = DiGraph({Integer(1):{Integer(2):['a']}}).path_semigroup()
>>> P2 = Q1.representation(QQ, [(Integer(2), Integer(2))], option='paths')
>>> P2.is_left_module()
False
```

The supplied basis is not closed under left multiplication, but it's not closed under right multiplication either. When the closure under right multiplication is taken the result is also closed under left multiplication and therefore produces a left module structure:

```
sage: kQ = Q1.representation(QQ, [(1, 1)], [(2, 2)], option='paths')
sage: kQ.is_left_module()
True
```

```
>>> from sage.all import *
>>> kQ = Q1.representation(QQ, [(Integer(1), Integer(1))], [(Integer(2), Integer(2))], option='paths')
>>> kQ.is_left_module()
True
```

Taking the right closure of a left closed set produces another left closed set:

```
sage: Q2 = DiGraph({1:{2:['a'], 3:['b', 'c']}, 2:{3:['d']}}).path_semigroup()
sage: M = Q2.representation(QQ, [(2, 2)], [(1, 2, 'a')], option='paths')
sage: M.is_left_module()
True
```

```
>>> from sage.all import *
>>> Q2 = DiGraph({Integer(1):{Integer(2):['a'], Integer(3):['b', 'c']},
```

(continues on next page)

(continued from previous page)

```

↪Integer(2):{Integer(3):['d']}).path_semigroup()
>>> M = Q2.representation(QQ, [[(Integer(2), Integer(2))], [(Integer(1), ↪
↪Integer(2), 'a')]], option='paths')
>>> M.is_left_module()
True

```

Note that the second path is length 2, so even though the edge (1, 2, 'a') appears in the input the path [(1, 2, 'a')] is not in the right closure:

```

sage: N = Q2.representation(QQ, [[(2, 2)], [(1, 2, 'a'), (2, 3, 'd')]], ↪
↪option='paths')
sage: N.is_left_module()
False

```

```

>>> from sage.all import *
>>> N = Q2.representation(QQ, [[(Integer(2), Integer(2))], [(Integer(1), ↪
↪Integer(2), 'a'), (Integer(2), Integer(3), 'd')]], option='paths')
>>> N.is_left_module()
False

```


INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

q

- `sage.quivers.algebra`, [1](#)
- `sage.quivers.algebra_elements`, [13](#)
- `sage.quivers.ar_quiver`, [27](#)
- `sage.quivers.homspace`, [39](#)
- `sage.quivers.morphism`, [45](#)
- `sage.quivers.path_semigroup`, [61](#)
- `sage.quivers.paths`, [75](#)
- `sage.quivers.representation`, [83](#)

A

`actor()` (*sage.quivers.representation.QuiverRep_generic method*), 105
`algebra()` (*sage.quivers.path_semigroup.PathSemigroup method*), 64
`algebraic_dual()` (*sage.quivers.morphism.QuiverRepHom method*), 47
`algebraic_dual()` (*sage.quivers.representation.QuiverRep_generic method*), 105
`all_paths()` (*sage.quivers.path_semigroup.PathSemigroup method*), 66
`an_element()` (*sage.quivers.representation.QuiverRep_generic method*), 106
`AR_translate()` (*sage.quivers.representation.QuiverRep_generic method*), 104
`arrows()` (*sage.quivers.algebra.PathAlgebra method*), 3
`arrows()` (*sage.quivers.path_semigroup.PathSemigroup method*), 68
`AuslanderReitenQuiver` (class in *sage.quivers.ar_quiver*), 27
`AuslanderReitenQuiver.Element` (class in *sage.quivers.ar_quiver*), 30

B

`base_ring()` (*sage.quivers.homspace.QuiverHomSpace method*), 39
`base_ring()` (*sage.quivers.morphism.QuiverRepHom method*), 47

C

`cardinality()` (*sage.quivers.path_semigroup.PathSemigroup method*), 68
`codomain()` (*sage.quivers.homspace.QuiverHomSpace method*), 40
`codomain()` (*sage.quivers.morphism.QuiverRepHom method*), 48
`coefficient()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 15
`coefficients()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 16
`cokernel()` (*sage.quivers.morphism.QuiverRepHom method*), 48

`complement()` (*sage.quivers.paths.QuiverPath method*), 77
`coordinates()` (*sage.quivers.homspace.QuiverHomSpace method*), 40
`coordinates()` (*sage.quivers.representation.QuiverRep_generic method*), 106
`copy()` (*sage.quivers.representation.QuiverRepElement method*), 96
`create_key()` (*sage.quivers.representation.QuiverRepFactory method*), 102
`create_object()` (*sage.quivers.representation.QuiverRepFactory method*), 102

D

`degree()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 17
`degree()` (*sage.quivers.paths.QuiverPath method*), 78
`degree_on_basis()` (*sage.quivers.algebra.PathAlgebra method*), 4
`detect_dynkin_quiver()` (in module *sage.quivers.ar_quiver*), 36
`digraph()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver method*), 32
`digraph_postinjectives()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver method*), 33
`digraph_preprojectives()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver method*), 33
`dimension()` (*sage.quivers.homspace.QuiverHomSpace method*), 41
`dimension()` (*sage.quivers.representation.QuiverRep_generic method*), 107
`dimension_vector()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver.Element method*), 30
`dimension_vector()` (*sage.quivers.representation.QuiverRep_generic method*), 108
`dimension_vectors_of_level()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver method*), 34
`direct_sum()` (*sage.quivers.morphism.QuiverRepHom method*), 49

`direct_sum()` (*sage.quivers.representation.QuiverRep_generic* method), 108
`domain()` (*sage.quivers.homspace.QuiverHomSpace* method), 41
`domain()` (*sage.quivers.morphism.QuiverRepHom* method), 50

E

`Element` (*sage.quivers.algebra.PathAlgebra* attribute), 3
`Element` (*sage.quivers.homspace.QuiverHomSpace* attribute), 39
`Element` (*sage.quivers.path_semigroup.PathSemigroup* attribute), 62
`Element` (*sage.quivers.representation.QuiverRep_generic* attribute), 105

F

`free_module()` (*sage.quivers.path_semigroup.PathSemigroup* method), 69

G

`gcd()` (*sage.quivers.paths.QuiverPath* method), 78
`gen()` (*sage.quivers.algebra.PathAlgebra* method), 5
`gen()` (*sage.quivers.path_semigroup.PathSemigroup* method), 70
`gens()` (*sage.quivers.algebra.PathAlgebra* method), 5
`gens()` (*sage.quivers.homspace.QuiverHomSpace* method), 41
`gens()` (*sage.quivers.path_semigroup.PathSemigroup* method), 70
`gens()` (*sage.quivers.representation.QuiverRep_generic* method), 110
`get_element()` (*sage.quivers.representation.QuiverRepElement* method), 97
`get_map()` (*sage.quivers.morphism.QuiverRepHom* method), 51
`get_map()` (*sage.quivers.representation.QuiverRep_generic* method), 111
`get_matrix()` (*sage.quivers.morphism.QuiverRepHom* method), 51
`get_space()` (*sage.quivers.representation.QuiverRep_generic* method), 112

H

`has_prefix()` (*sage.quivers.paths.QuiverPath* method), 79
`has_subpath()` (*sage.quivers.paths.QuiverPath* method), 80
`Hom()` (*sage.quivers.representation.QuiverRep_generic* method), 105
`homogeneous_component()` (*sage.quivers.algebra.PathAlgebra* method), 5
`homogeneous_components()` (*sage.quivers.algebra.PathAlgebra* method), 6

I

`I()` (*sage.quivers.path_semigroup.PathSemigroup* method), 62
`idempotents()` (*sage.quivers.algebra.PathAlgebra* method), 7
`idempotents()` (*sage.quivers.path_semigroup.PathSemigroup* method), 71
`image()` (*sage.quivers.morphism.QuiverRepHom* method), 52
`initial_vertex()` (*sage.quivers.paths.QuiverPath* method), 81
`injective()` (*sage.quivers.path_semigroup.PathSemigroup* method), 71
`injectives()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver* method), 35
`inverse_translation()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver.Element* method), 30
`is_endomorphism()` (*sage.quivers.morphism.QuiverRepHom* method), 53
`is_finite()` (*sage.quivers.path_semigroup.PathSemigroup* method), 71
`is_homogeneous()` (*sage.quivers.algebra_elements.PathAlgebraElement* method), 17
`is_injective()` (*sage.quivers.morphism.QuiverRepHom* method), 53
`is_isomorphism()` (*sage.quivers.morphism.QuiverRepHom* method), 54
`is_left_module()` (*sage.quivers.representation.QuiverRep_with_path_basis* method), 122
`is_semisimple()` (*sage.quivers.representation.QuiverRep_generic* method), 112
`is_simple()` (*sage.quivers.representation.QuiverRep_generic* method), 113
`is_surjective()` (*sage.quivers.morphism.QuiverRepHom* method), 54
`is_zero()` (*sage.quivers.morphism.QuiverRepHom* method), 55
`is_zero()` (*sage.quivers.representation.QuiverRep_generic* method), 113
`is_zero()` (*sage.quivers.representation.QuiverRepElement* method), 97
`iscalar_mult()` (*sage.quivers.morphism.QuiverRepHom* method), 55
`iter_paths_by_length_and_endpoint()` (*sage.quivers.path_semigroup.PathSemigroup* method), 71
`iter_paths_by_length_and_startpoint()` (*sage.quivers.path_semigroup.PathSemigroup* method), 72

K

`kernel()` (*sage.quivers.morphism.QuiverRepHom* method), 56

L

`left_module()` (*sage.quivers.homspace.QuiverHomSpace method*), 42
`length()` (*sage.quivers.paths.QuiverPath method*), 81
`level()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver.Element method*), 31
`lift()` (*sage.quivers.morphism.QuiverRepHom method*), 57
`linear_combination()` (*sage.quivers.algebra.PathAlgebra method*), 7
`linear_combination_of_basis()` (*sage.quivers.representation.QuiverRep_generic method*), 113
`linear_dual()` (*sage.quivers.morphism.QuiverRepHom method*), 57
`linear_dual()` (*sage.quivers.representation.QuiverRep_generic method*), 114

M

`module`
 sage.quivers.algebra, 1
 sage.quivers.algebra_elements, 13
 sage.quivers.ar_quiver, 27
 sage.quivers.homspace, 39
 sage.quivers.morphism, 45
 sage.quivers.path_semigroup, 61
 sage.quivers.paths, 75
 sage.quivers.representation, 83
`monomial_coefficients()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 18
`monomials()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 19

N

`natural_map()` (*sage.quivers.homspace.QuiverHomSpace method*), 43
`NewQuiverPath()` (*in module sage.quivers.paths*), 75
`ngens()` (*sage.quivers.algebra.PathAlgebra method*), 8
`ngens()` (*sage.quivers.path_semigroup.PathSemigroup method*), 73

O

`one()` (*sage.quivers.algebra.PathAlgebra method*), 8
`options` (*sage.quivers.ar_quiver.AuslanderReitenQuiver attribute*), 35
`order_string()` (*sage.quivers.algebra.PathAlgebra method*), 9

P

`P()` (*sage.quivers.path_semigroup.PathSemigroup method*), 63
`path_algebra_element_unpickle()` (*in module sage.quivers.algebra_elements*), 24
`PathAlgebra` (*class in sage.quivers.algebra*), 1

`PathAlgebraElement` (*class in sage.quivers.algebra_elements*), 13
`PathSemigroup` (*class in sage.quivers.path_semigroup*), 61
`projective()` (*sage.quivers.path_semigroup.PathSemigroup method*), 73
`projective_cover()` (*sage.quivers.representation.QuiverRep_generic method*), 115
`projectives()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver method*), 35

Q

`quiver()` (*sage.quivers.algebra.PathAlgebra method*), 9
`quiver()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver method*), 35
`quiver()` (*sage.quivers.homspace.QuiverHomSpace method*), 44
`quiver()` (*sage.quivers.morphism.QuiverRepHom method*), 59
`quiver()` (*sage.quivers.path_semigroup.PathSemigroup method*), 73
`quiver()` (*sage.quivers.representation.QuiverRep_generic method*), 115
`quiver()` (*sage.quivers.representation.QuiverRepElement method*), 98
`QuiverHomSpace` (*class in sage.quivers.homspace*), 39
`QuiverPath` (*class in sage.quivers.paths*), 75
`QuiverRep_generic` (*class in sage.quivers.representation*), 103
`QuiverRep_with_dual_path_basis` (*class in sage.quivers.representation*), 121
`QuiverRep_with_path_basis` (*class in sage.quivers.representation*), 121
`QuiverRepElement` (*class in sage.quivers.representation*), 95
`QuiverRepFactory` (*class in sage.quivers.representation*), 99
`QuiverRepHom` (*class in sage.quivers.morphism*), 45
`quotient()` (*sage.quivers.representation.QuiverRep_generic method*), 115

R

`radical()` (*sage.quivers.representation.QuiverRep_generic method*), 116
`rank()` (*sage.quivers.morphism.QuiverRepHom method*), 59
`representation()` (*sage.quivers.path_semigroup.PathSemigroup method*), 74
`reversal()` (*sage.quivers.paths.QuiverPath method*), 81
`reverse()` (*sage.quivers.path_semigroup.PathSemigroup method*), 74
`right_edge_action()` (*sage.quivers.representation.QuiverRep_generic method*), 117

S

`S()` (*sage.quivers.path_semigroup.PathSemigroup method*), 64
`sage.quivers.algebra`
 module, 1
`sage.quivers.algebra_elements`
 module, 13
`sage.quivers.ar_quiver`
 module, 27
`sage.quivers.homspace`
 module, 39
`sage.quivers.morphism`
 module, 45
`sage.quivers.path_semigroup`
 module, 61
`sage.quivers.paths`
 module, 75
`sage.quivers.representation`
 module, 83
`scalar_mult()` (*sage.quivers.morphism.QuiverRepHom method*), 59
`semigroup()` (*sage.quivers.algebra.PathAlgebra method*), 10
`simple()` (*sage.quivers.path_semigroup.PathSemigroup method*), 74
`simples()` (*sage.quivers.ar_quiver.AuslanderReiten-Quiver method*), 36
`socle()` (*sage.quivers.representation.QuiverRep_generic method*), 117
`sort_by_vertices()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 20
`submodule()` (*sage.quivers.representation.Quiver-Rep_generic method*), 118
`sum()` (*sage.quivers.algebra.PathAlgebra method*), 10
`support()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 21
`support()` (*sage.quivers.representation.Quiver-Rep_generic method*), 120
`support()` (*sage.quivers.representation.QuiverRepElement method*), 98
`support_of_term()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 23

T

`terminal_vertex()` (*sage.quivers.paths.QuiverPath method*), 82
`terms()` (*sage.quivers.algebra_elements.PathAlgebraElement method*), 23
`top()` (*sage.quivers.representation.QuiverRep_generic method*), 120
`translation()` (*sage.quivers.ar_quiver.AuslanderReitenQuiver.Element method*), 31
`transpose()` (*sage.quivers.representation.Quiver-Rep_generic method*), 120

V

`vertex()` (*sage.quivers.ar_quiver.AuslanderReiten-Quiver.Element method*), 32

Z

`zero()` (*sage.quivers.homspace.QuiverHomSpace method*), 44
`zero_submodule()` (*sage.quivers.representation.Quiver-Rep_generic method*), 121