

Lesson

Wednesday

Introduction to Programming

(/introduction-to-programming)

/ Arrays and Looping (/introduction-to-programming/arrays-and-looping)

/ Rewriting Git History with Rebase

Text

Cheat sheet

Terminology

- **Rebase:** The act of moving a branch to a new base commit (essentially just moving a branch from one commit to another).
- **Squashing:** The act of combining multiple commits together into one.

Commands

- `$ git log --oneline`: Returns a repository's log of commits, each condensed to a single line.
- `$ git commit --amend -m "updated commit message here.:"`: Modifies a repository's most recent commit message with the new message provided.
- `$ git rebase -i`: Changes commit messages and combines multiple commits by "squashing" them together:
 - rewrite commit messages by changing pick to reword

- squash one or more commit messages by changing pick to squash

Examples

See a project's commit history with the `git log` command. Add the `--oneline` flag to display the history in an easier to read format:

```
$ git log --oneline
d7e33de something css related
32ccc0b do something with html
9db82b6 update readme
79e9de2 add readme
827ad58 add initial files
```

Amend the most recent Git commit:

```
$ git commit --amend -m "add styling to main page"
```

[Previous \(/introduction-to-programming/arrays-and-looping/practice-using-tdd-with-text-analyzer\)](#)

[Next \(/introduction-to-programming/arrays-and-looping/practice-rewriting-git-history-with-rebase\)](#)

Lesson 33 of 50

Last updated March 24, 2023

[disable dark mode](#)



© 2023 Epicodus (<http://www.epicodus.com/>), Inc.