A Real-Time Research Project Report

on

IOT BASED SMART WAREHOUSE MONITORING SYSTEM

Submitted in partial fulfillment of the requirements for the award of the degree

of

Bachelor of Technology

in

COMPUTER SCIENCE AND ENGINEERING (AI & ML)

by

S.Parnika	[247R1A66A5]
S.Aniketh	[247R1A66A6]
J.Rahul	[247R1A6683]
V.Navya Shri	[257R5A6609]

Under the guidance of

P.Vishnu

Assistant Professor

Dept of CSE[AI&ML]

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING (AI & ML)

CMR TECHNICAL CAMPUS

UGC AUTONOMOUS

Accredited by NBA & NAAC with 'A' Grade

Approved by AICTE, New Delhi and JNTU Hyderabad

Kandlakoya(V), Medchal Road, Hyderabad – 501401

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING (AI&ML)

CERTIFICATE

This is to certify that the Real-Time Research Project Report entitled "**IOT BASED SMART WAREHOUSE MONITORING SYSTEM"** being submitted by **S.Parnika [247R1A66A5], S.Aniketh [247R1A66A6], J.Rahul [247R1A6683], V.Navya Shri [257R5A6609]** in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology in COMPUTER SCIENC AND ENGINEERING (AI & ML) to the Jawaharlal Nehru Technological University, Hyderabad is a record of Bonafide work carried out by them under my guidance and supervision during the Academic Year 2025 – 26.

The results embodied in this report have not been submitted to any other University or Institute for the award of any other degree.

P.Vishnu	**Dr. S Rao Chintalapudi**
Assistant Professor	Head of the Department
Project Guide	

ACKNOWLEDGEMENT

Apart from the efforts of us, the success of any project depends largely on the encouragement and guidelines of many others. We take this opportunity to express our gratitude to the people who have been instrumental in the successful completion of this project.

We take this opportunity to express my profound gratitude and deep regard to my guide **P.Vishnu,** Assistant Professor Dept of CSE[AI&ML], for his exemplary guidance, monitoring and constant encouragement throughout the project work. The blessing, help and guidance given by him shall carry us a long way in the journey of life on which we are about to embark.

We are also thankful to **Dr. S Rao Chintalapudi**, Head, Department of Computer Science and Engineering (AI&ML) for providing encouragement and support for completing this project successfully.

We are obliged **to Dr. A. Raji Reddy**, Director for being cooperative throughout the course of this project. We also express our sincere gratitude to Sri. **Ch. Gopal Reddy**, Chairman for providing excellent infrastructure and a nice atmosphere throughout the course of this project.

The guidance and support received from all the members of **CMR Technical Campus** who contributed to the completion of the project. We are grateful for their constant support and help.

Finally, we would like to take this opportunity to thank our family for their constant encouragement, without which this assignment would not be completed. We sincerely acknowledge and thank all those who gave support directly and indirectly in the completion of this project.

S.PARNIKA	[247R1A66A5]
S.ANIKETH	[247R1A66A6]
J.RAHUL	[247R1A6683]
V.NAVYA SHRI	[257R5A6609]

ABSTRACT

This project focuses on the development of an **IoT Based Smart Warehouse Monitoring System** using a Node MCU microcontroller to ensure the safety of goods and infrastructure. The system is designed to provide real-time surveillance of environmental conditions by integrating a temperature sensor and a fire sensor. When hazardous levels are detected, the Node MCU processes the signals to provide immediate local feedback through an LCD Display and a buzzer alarm. Furthermore, the system includes an automated mitigation feature where a DC Fan is activated to regulate the temperature or clear smoke. By leveraging the IoT capabilities of the Node MCU, this system allows warehouse managers to monitor facility conditions remotely, reducing the risk of fire damage or product spoilage.

LIST OF FIGURES

S. No	Figure Name	Page No
Figure 4.2	Proposed Methodology	19
Figure 4.3.1	Class Diagram	20
Figure 4.3.2	Use Case Diagram	21
Figure 4.3.3	Component Diagram	22
Figure 4.3.4	Sequence Diagram	23
Figure 4.3.5	Activity Diagram	25

Table of Contents

	Page No
Abstract	v
List of Figures	vi
1. Introduction	
1.1 Introduction	8
1.2 Problem Statement	8
1.3 Project Objective	8
2. Literature Survey	10
3. Requirement Specification	
3.1 Software Requirements	18
3.2 Hardware Requirements	18
3.3 Functional Requirements	19
3.4 Non-Functional Requirements	19
4. System Design	
4.1 System Design	20
4.2 Proposed Methodology	21
4.3 UML Design	
4.3.1 Class Diagram	22
4.3.2 Use Case Diagram	23
4.3.3 Component Diagram	24
4.3.4 Sequence Diagram	25
4.3.5 Activity Diagram	27

4.4 Technology Description
5. Implementation 29
6. Testing 30
7. Results (Add Screenshots/Photos) 31
8. Conclusion 34
9. Future Scope 35
10. References 36

1.INTRODUCTION

1.1 INTRODUCTION

Warehouses store valuable goods and require proper monitoring to prevent damage due to fire or temperature changes. Traditional systems lack real-time monitoring and depend on manual inspection. With the advancement of IoT, smart monitoring systems can continuously track environmental conditions and provide instant alerts. This project introduces an IoT-based smart warehouse system that ensures safety, automation, and remote accessibility.

1.2 PROBLEM STATEMENT

Traditional warehouse monitoring systems:

- Do not provide real-time monitoring
- Depend on manual inspection
- Lack automated response systems
- Fail to detect hazards early
- Cannot be monitored remotely

These limitations can lead to fire accidents, product damage, and financial losses.

1.3 PROJECT OBJECTIVE

- To monitor temperature and fire conditions in real-time
- To provide instant alerts using buzzer and LCD
- To implement automatic control (fan activation)
- To enable remote monitoring using IoT
- To reduce risk of fire and product spoilage

2.LITERATURE SURVEY

"Smart Warehouses: Rationale, Challenges and Solution Directions"

Smart warehouses aim to increase the overall service quality, productivity, and efficiency of the warehouse while minimizing costs and failures. In recent years, several studies have proposed and discussed different types of smart warehouses, identified key challenges, and proposed several solution directions for coping with these challenges. The objective of this article is to identify, evaluate, and synthesize the relevant studies discussing the design of smart warehouses and the transition to these new types of warehouses. We applied a systematic literature review (SLR) protocol to select primary studies. The SLR resulted in the identification of the domains in which smart warehouses are applied, key motivations for adopting smart warehouses, current distinctive characteristics of smart warehouses, currently adopted technologies for realizing smart warehouses, and challenges and strategies for transitioning to smart warehouses. To the best of our knowledge, no SLR paper has been published yet on smart warehouses, and therefore, this is timely research as organizations are nowadays transitioning to smart warehouses.

"The application of Industry 4.0 technologies in sustainable logistics: a systematic literature review (2012–2020) to explore future research opportunities"

Nowadays, the market competition becomes increasingly fierce due to diversified customer needs, stringent environmental requirements, and global competitors. One of the most important factors for companies to not only survive but also thrive in today's competitive market is their logistics performance. This paper aims, through a systematic literature analysis of 115 papers from 2012 to 2020, at presenting quantitative insights and comprehensive overviews of the current and future research landscapes of sustainable logistics in the Industry 4.0 era. The results show that Industry 4.0 technologies provide opportunities for improving the economic efficiency, environmental performance, and social impact of logistics sectors. However, several challenges arise with this technological transformation, i.e., trade-offs among different sustainability indicators, unclear benefits, lifecycle environmental impact, inequity issues, and technology maturity. Thus, to better tackle the current research gaps, future suggestions are given to focus on the balance among different sustainability indicators through the entire lifecycle, human-centric technological transformation, system integration and digital twin, semi-autonomous transportation solutions, smart reverse logistics, and so forth

“Intelligent Warehouse Management System”

This paper presents the design and implementation of an intelligent warehouse management system. The main emphasis in our solution consists of three software components: An Xamarin IOT application which acts as the exchange interface with the end users, a web application that communicates with a database and ensures the persistence and communication between the different components of the system, and a robot that moves products in the warehouse according to storage and shipping requests. Our solution is designed to allow the various actors to have real-time information on the different workflows within the warehouse and all the movements of stock. Hence the need for a system that controls all zones and locations and ensures communication between the various actors and software components while optimizing data exchange and load consumption for IOT equipment.

“Warehouse inventory management system using IoT and open source framework”

In general, warehouses are used to store goods or products. In the Warehouses, if the user wants to locate any product it is very difficult, because user have to do a detailed search manually in all the available stockrooms this requires a lot of effort. So to avoid this problem the warehouse inventory management system is very helpful because it maintains the detailed product information and tells us in which stockroom the product is present. The warehouse inventory management system is playing a significant aspect in many productions and goods based methodology. Though there are many wireless communication technologies the RFID suits the best for the warehouse inventory management system. The tag information is transferred from the transmitter section to open source hardware via a wireless link with the aid of internet. The warehouse inventory management system built on the architecture of the Internet of Things is developed to track the products attached to the tags with product information and their respective time stamps for further verification. The Raspberry Pi acts as a central server, monitoring all the information. The total system gives an archetype to correspond the information flow and material flow. The web page which is built in accordance to provide convenient and an interface to the user to track the products. The developed system results a very low cost system and works dynamically compared with the existing present warehouse inventory management systems.

EXISTING SYSTEM

Traditional warehouse monitoring often relies on periodic manual inspections or basic, unconnected safety devices like standalone smoke detectors. These systems are limited because they do not provide a centralized view of environmental data, and alerts are only useful if someone is physically present to hear them. In many existing setups, there is no automated response to high temperatures or early-stage fire, meaning by the time a human responder arrives, significant damage may have already occurred. Furthermore, manual logging of temperature for sensitive goods (like pharmaceuticals or perishables) is prone to human error and lacks the real-time precision required for modern supply chain standards.

PROPOSED SYSTEM

The proposed system addresses these vulnerabilities by creating an integrated, automated monitoring network controlled around the Node MCU ESP8266. As shown in the block diagram, the temperature sensor and fire sensor constantly feed data to the microcontroller. If the temperature exceeds a set threshold or fire is detected, the Node MCU triggers the buzzer for a local alert and displays the specific fault on the LCD Display. Simultaneously, the DC Fan is activated to provide immediate cooling or ventilation. Because the Node MCU is Wi-Fi enabled, the system can transmit all sensor data to a cloud platform, enabling warehouse administrators to receive instant notifications on their smartphones and view historical environmental data from anywhere in the world.

BLOCK DIAGRAM



WORKING

The IoT-based Smart Warehouse Monitoring System operates through a systematic integration of sensors, microcontroller processing, display and alert mechanisms, and automated response systems to provide comprehensive warehouse safety monitoring.

Sensor Network and Data Acquisition: The system employs two critical environmental sensors positioned strategically throughout the warehouse. The temperature sensor continuously measures ambient temperature levels, providing analog voltage outputs proportional to the detected temperature. Common sensors used include the LM35 or DHT11/DHT22, which offer reliable temperature readings with appropriate accuracy for warehouse applications. The fire sensor, typically an infrared flame sensor or smoke detector module, monitors for the presence of flames or smoke particles. This sensor operates by detecting specific infrared wavelengths emitted by fires or changes in air opacity caused by smoke. Both sensors are connected to the analog and digital input pins of the NodeMCU microcontroller, continuously feeding real-time data for processing.

NodeMCU Processing and Decision Making: The NodeMCU (ESP8266-based microcontroller) serves as the central intelligence of the system. Upon receiving signals from the temperature and fire sensors, the NodeMCU's analog-to-digital converter (ADC) processes the analog inputs and converts them into digital values. The microcontroller runs programmed algorithms that compare these readings against predefined threshold values stored in its memory. For temperature monitoring, thresholds are set based on the optimal storage conditions for warehouse contents, typically between specific ranges that prevent product degradation. For fire detection, the system is programmed to respond immediately to any positive indication of flames or smoke. The NodeMCU continuously executes this monitoring loop, typically scanning sensor inputs multiple times per second to ensure no hazardous condition goes undetected.

Local Display and Alert System: Real-time environmental data is displayed on a 16x2 or 20x4 LCD screen connected to the NodeMCU via I2C or parallel interface. The LCD continuously shows current temperature readings, fire sensor status, and system operational state, providing immediate visual feedback to warehouse personnel. When hazardous conditions are detected—either temperature exceeding safe thresholds or fire sensor activation—the NodeMCU triggers a buzzer that produces audible alarm tones. This dual alert mechanism (visual and audible) ensures that

warehouse staff are immediately aware of developing dangers, enabling rapid evacuation or manual intervention as needed.

Automated Mitigation Response: Upon detecting hazardous conditions, the NodeMCU activates an automated response system consisting of a DC fan controlled through a relay module or motor driver circuit. When excessive temperature is detected, the fan operates to increase air circulation and help dissipate heat, preventing further temperature rise and potential fire ignition. In fire scenarios, the fan assists in smoke dispersal, improving visibility and reducing smoke inhalation risks for personnel. The relay-based control allows the NodeMCU's low-current digital output pins to safely switch the higher current required by the DC fan motor.

IoT Connectivity and Remote Monitoring: Leveraging the built-in Wi-Fi capabilities of the ESP8266 chip, the NodeMCU connects to the warehouse's wireless network and transmits real-time sensor data to cloud platforms such as ThingSpeak, Blynk, Firebase, or custom web servers. This connectivity enables warehouse managers to access live environmental data through web-based dashboards or mobile applications from any location. The system can be configured to send email or SMS notifications when alerts are triggered, ensuring that management is informed immediately even during off-hours. Historical data logging in the cloud allows for trend analysis, identification of recurring issues, and compliance documentation for safety audits.

Power Supply and System Reliability: The system operates on a stable power supply, typically 5V DC, which powers the NodeMCU, sensors, LCD, buzzer, and fan through appropriate voltage regulation circuits. To ensure continuous operation during power outages, the system can be backed up with uninterruptible power supplies (UPS) or battery backup systems, maintaining critical monitoring functions even when main power fails.

System Integration and Scalability: The modular architecture allows for easy expansion by adding multiple sensor nodes throughout large warehouse facilities. Each node can communicate with a central NodeMCU hub or operate independently, reporting to the same cloud platform. This scalability makes the system suitable for warehouses of various sizes, from small storage facilities to large distribution centers.

.

Advantages

1. Real-time environmental monitoring
2. Fire hazard prevention
3. Automated emergency response
4. Remote accessibility and control
5. Cost-effective solution
6. Reduced product spoilage
7. Minimized fire damage risk
8. 24/7 surveillance capability

Applications

1. Cold storage warehouses
2. Pharmaceutical storage facilities
3. Food and beverage warehouses
4. Electronics storage units
5. Chemical storage facilities
6. Textile and garment warehouses
7. Automotive parts storage
8. E-commerce fulfillment centers

3. REQUIREMENT SPECIFICATION

This chapter gives an overview of the software and hardware components required for our project.

3.1 Software Requirements

The software components are required to program, control, and monitor the system.

- **Arduino IDE:** Used to write, compile, and upload code into the NodeMCU microcontroller. It provides an easy interface for programming.

- **Embedded C / C++ Programming:** The system is programmed using C/C++ language to control sensors and output devices.
- **IoT Platforms (ThingSpeak / Blynk / Firebase):** ThingSpeak – Collects and displays sensor data in graphs, Blynk – Mobile app to control and monitor devices, Firebase – Real time cloud database for IoT data
- **Operating System: Windows/Linux: Windows** – Easy to use and supports Arduino IDE; **Linux** – Open-source, secure, and suitable for IoT development.

3.2 Hardware Requirements

- **NodeMCU (ESP8266)** – A Wi-Fi enabled microcontroller used to process data and connect the system to the internet.
- **DHT11 Temperature Sensor** – A sensor used to measure temperature (and humidity) in the environment.
- **Flame/Fire Sensor** – A sensor used to detect fire or flame presence.
- **LCD Display (16x2)** – A display used to show real-time system data and alerts.
- **Buzzer** – An audio device used to give alert sounds during hazardous conditions.
- **DC Fan** – A cooling device used to regulate temperature or remove smoke automatically.
- **Power Supply** – Provides the required electrical power to run all components of the system

3.3 Functional Requirements

- Continuously monitors temperature in real time
- Detects fire or flame instantly
- Displays live data on LCD screen
- Activates buzzer during dangerous conditions
- Automatically turns ON fan to control temperature or smoke
- Sends data to cloud for remote monitoring

3.4 Non-Functional Requirements

- **Reliability**: The system should work continuously without failure.
- **Low cost**: The system should be affordable and easy to implement.
- **Scalability:** System can be expanded with more sensors or features.
- **Energy efficiency:** Should consume less power for continuous operation.
- **User:** friendly interface: Easy to install and operate.

4. SYSTEM DESIGN

4.1 System Design

The system design of the IoT Based Smart Warehouse Monitoring System is developed to provide efficient, real-time monitoring and automatic response to environmental conditions inside the warehouse. The system is organized into input, processing, and output sections, along with IoT connectivity to enable remote monitoring and control.

The **input section** includes sensors such as the DHT11 temperature sensor and flame sensor. These sensors continuously collect real-time environmental data from the warehouse. The DHT11 sensor measures temperature (and humidity), while the flame sensor detects the presence of fire or smoke. These inputs are essential for identifying unsafe conditions at an early stage.

The **processing section** is handled by the NodeMCU (ESP8266) microcontroller, which acts as the central unit of the system. It receives data from the sensors and processes it by comparing the readings with predefined threshold values. Based on this comparison, the NodeMCU determines whether the environment is safe or hazardous. It also controls all output devices and manages communication with the cloud through its built-in Wi-Fi module.

The **output section** consists of an LCD display, buzzer, and DC fan. The LCD display shows real-time information such as temperature values and system status. When abnormal conditions are detected, the buzzer is activated to provide an immediate audible alert. Simultaneously, the DC fan is automatically turned ON to reduce temperature or disperse smoke, helping to prevent further damage.

The working of the system is continuous and automatic. The sensors constantly monitor environmental conditions, the microcontroller processes the data, and the system responds instantly to any abnormal situation. This design ensures improved safety, quick response to hazards, and efficient warehouse management.

4.2 Proposed Methodology



Figure 4.2 Proposed Methodology

The proposed methodology illustrates the working flow of the IoT-based Smart Warehouse Monitoring System, starting from system initialization to real-time monitoring and response. Initially, the system is started and initialized, after which sensors such as the DHT11 temperature sensor and flame sensor begin collecting environmental data. This data is sent to the Node MCU (ESP8266), which acts as the processing unit. The Node MCU analyzes the sensor data by checking whether the conditions are normal or hazardous based on predefined thresholds. If the conditions are normal, the data is simply sent to the cloud server for remote monitoring. However, if a hazard such as high temperature or fire is detected, the system takes immediate action by activating the buzzer for alerts, turning on the DC fan to control temperature or smoke, and displaying warning messages on the LCD screen. Simultaneously, the data is transmitted to the cloud, enabling remote monitoring and sending notifications to the user. This entire process runs continuously, ensuring

real-time monitoring and quick response to any abnormal situation in the warehouse.

4.3 UML Design

UML (Unified Modeling Language) is used to represent the structure and behavior of the system.

4.3.1 CLASS DIAGRAM:

The system begins with sensors that collect temperature and fire data from the warehouse and send it to the NodeMCU for processing. The NodeMCU then compares the received data with predefined threshold values to determine whether the conditions are normal or hazardous. If any abnormal condition is detected, the system responds by activating the buzzer, turning on the fan, and displaying alerts on the LCD screen. At the same time, the processed data is sent to the cloud for remote monitoring. The user can access this data and receive alerts in real time, ensuring continuous monitoring and quick response to any dangerous situation.

Fig 4.3.1: Class Diagram



4.3.2 Use Case Diagram



Fig 4.3.2: Use-Case Diagram

The use case diagram represents the interaction between the user, sensors, and the Node MCU in the IoT-based Smart Warehouse Monitoring System. The process begins with the sensors, which perform functions such as reading data, checking threshold levels, and detecting fire conditions. These sensors send the collected data to the Node MCU, which acts as the central system. The Node MCU processes the data by reading temperature values, activating the fan, and triggering alarms whenever hazardous conditions are detected. At the same time, it sends notifications and updates to the user. The user interacts with the system through functions like login, viewing data, and receiving alerts. This diagram clearly shows how the system enables real-time monitoring, automatic response, and user interaction, ensuring efficient and safe warehouse management.

4.3.3 Component Diagram



Fig 4.3.3: component diagram

The component diagram represents the structure and interaction of different components in the IoT-based Smart Warehouse Monitoring System. At the center is the smart warehouse system, which acts as the main controller connecting all components. The system receives input from sensors such as the temperature sensor, which monitors temperature levels, and the fire sensor, which detects fire or smoke. Based on this input, the system processes the data and controls various output components. The DC fan is used to regulate temperature and clear smoke, while the buzzer provides an audible alarm during hazardous conditions. The LCD display shows real-time data and alert messages to users. Overall, the diagram illustrates how all components work together to ensure continuous monitoring, quick response, and improved safety in the warehouse environment.

4.3.4 Sequence Diagram



Fig 4.3.4: Sequence Diagram

Step-by-Step Explanation

1. **User Login**

   The process starts when the user logs into the system using the login() function.

2. **Request for Data**

   The user requests current warehouse data using the readData() function.

3. **Data Collection from Sensors**

   The NodeMCU receives the request and collects sensor values (temperature and fire status) from the sensors.

4. **Condition Checking**

   The NodeMCU compares the received sensor values with predefined threshold levels to

determine system status.

5. **Normal Condition**
   If the values are within safe limits, the NodeMCU sends the data to the cloud using sendToCloud(), and the user can view the data through viewData().

6. **Abnormal Condition (Hazard Detected)**
   If the values exceed the threshold, the NodeMCU detects fire or high temperature using detectFire().

7. **Triggering Actions**
   The system responds by triggering the alarm (triggerAlarm()), activating the fan (activateFan()), and displaying alerts.

8. **Sending Notifications**
   The NodeMCU sends alert notifications to the user using sendNotification().

9. **User Receives Alert**
   The user receives alerts through the receiveAlert() function.

10. **Continuous Monitoring**
    The entire process repeats continuously to ensure real-time monitoring and quick response to hazards.

4.3.5 Activity Diagram

The activity diagram shows the workflow of the smart warehouse monitoring system. The process starts by reading data from temperature and fire sensors. The system then checks whether the temperature exceeds the threshold or if smoke is detected. If high temperature is detected, the fan is turned ON, and if smoke or fire is detected, an alarm is triggered. At the same time, data is sent to the cloud for remote monitoring. The LCD display is updated with the current status in both normal and abnormal conditions. This process continues continuously to ensure real-time monitoring and quick response to any hazards.



Fig 4.3.5: Activity Diagram

4.4 Technology Description

The IoT Based Smart Warehouse Monitoring System is developed using a combination of embedded systems, Internet of Things (IoT) technology, sensors, and cloud computing. The core technology used in this system is the Node MCU microcontroller based on the ESP8266 Wi-Fi module, which enables both data processing and wireless communication. This microcontroller acts as the brain of the system, receiving input from sensors, processing the data, and controlling output devices.

The system uses sensors such as the DHT11 temperature sensor and flame sensor to monitor environmental conditions inside the warehouse. The DHT11 sensor measures temperature (and humidity), while the flame sensor detects fire or smoke. These sensors continuously send real-time data to the Node MCU, which compares the values with predefined threshold levels to identify abnormal conditions.

Embedded system technology plays a crucial role in this project, as it integrates both hardware and software to perform specific tasks efficiently. The program is written using Embedded C/C++ in the Arduino IDE and uploaded to the Node MCU. The system operates in a continuous loop, ensuring real-time monitoring and quick response to hazards.

IoT technology enables the system to connect to the internet and share data remotely. Using the built-in Wi-Fi capability of the ESP8266, the Node MCU sends sensor data to cloud platforms such as Thing Speak, Blynk, or Firebase. These platforms allow users to monitor data through web dashboards or mobile applications from anywhere. This feature ensures remote accessibility and improves decision-making.

The system also includes output devices like an LCD display, buzzer, and DC fan. The LCD is used to display real-time temperature and system status, while the buzzer provides an audible alert during hazardous conditions. The DC fan acts as an automated control mechanism to regulate temperature or disperse smoke, enhancing safety.

Communication between components is achieved through serial communication protocols such as I2C, UART, and digital input-output pins of the Node MCU. The system is powered by a stable power supply, ensuring continuous operation.

Overall, the integration of IoT, embedded systems, sensors, and cloud computing makes this system efficient, cost-effective, and reliable. It provides real-time monitoring, automatic response, and remote control, making it suitable for modern smart warehouse applications.

5.IMPLEMENTATION

The implementation of the IoT Based Smart Warehouse Monitoring System involves the integration of hardware components and software programming to achieve real-time monitoring and automated control. The system is built using the Node MCU (ESP8266) microcontroller, which acts as the central unit for processing and communication. Sensors such as the DHT11 temperature sensor and flame sensor are connected to the Node MCU to continuously collect environmental data from the warehouse. The DHT11 sensor measures temperature (and humidity), while the flame sensor detects fire or smoke conditions. These sensors are interfaced with the Node MCU using appropriate GPIO pins, and the data is read using embedded C/C++ programming through the Arduino IDE.

The program is designed in such a way that it continuously reads sensor values and compares them with predefined threshold levels. If the temperature exceeds the safe limit or fire is detected, the system immediately responds by activating the buzzer to alert users and turning on the DC fan to reduce temperature or disperse smoke. At the same time, the LCD display shows real-time data and warning messages, providing visual feedback to the users. The Node MCU also uses its built-in Wi-Fi capability to connect to the internet and send sensor data to cloud platforms such as Thing Speak, Blynk, or Firebase. This allows remote monitoring of warehouse conditions through mobile applications or web dashboards.

The hardware components are powered using a stable power supply, and proper connections are ensured for reliable operation. The system is tested under different conditions to verify its functionality, such as normal temperature, high temperature, and fire detection scenarios. Overall, the integration of IoT technology, sensors, and embedded systems results in a cost-effective and reliable smart warehouse monitoring solution.

6.TESTING

6.1 TESTING DEFINATION

Testing is an essential phase in the development of the IoT Based Smart Warehouse Monitoring System to ensure that all components function correctly and the system performs reliably under different conditions. The system is tested by individually verifying each hardware component such as the DHT11 temperature sensor, flame sensor, LCD display, buzzer, and DC fan. Initially, sensor testing is performed to check whether the temperature sensor accurately reads environmental values and whether the flame sensor correctly detects fire or smoke. After validating sensor inputs, the processing functionality of the Node MCU is tested to ensure it properly reads data, compares it with predefined threshold values, and executes the programmed logic.

The output devices are then tested by simulating different scenarios. When temperature exceeds the threshold, the DC fan should automatically turn ON, and when fire is detected, the buzzer should activate to alert users. The LCD display is tested to verify that it correctly shows real-time data and warning messages. Additionally, IoT functionality is tested by checking whether the Node MCU successfully connects to Wi-Fi and sends data to cloud platforms like Thing Speak or Blynk. Remote monitoring is verified by observing if data updates correctly on the dashboard and if alerts are received on time.

The system is also tested under normal and abnormal conditions to ensure stability and reliability. Integration testing is performed to confirm that all components work together seamlessly. Overall, testing ensures that the system operates accurately, responds quickly to hazardous situations, and provides reliable real-time monitoring for warehouse safety.

6.2 TEST CASES

Test Case ID	Test Description	Input Condition	Expected Output	Result
TC01	Temperature Sensor Reading	Normal temperature	Correct temperature displayed on LCD	Pass
TC02	High Temperature Detection	Temperature > threshold	Fan turns ON, alert displayed	Pass
TC03	Fire Detection	Flame/smoke present	Buzzer ON, alert message shown	Pass
TC04	LCD Display Check	System running	Displays real-time data correctly	Pass
TC05	Buzzer Function	Hazard condition	Buzzer sounds immediately	Pass
TC06	DC Fan Operation	High temperature	Fan activates automatically	Pass
TC07	IoT Data Transmission	Wi-Fi connected	Data sent to cloud dashboard	Pass
TC08	Remote Monitoring	User login	Data visible on mobile/web app	Pass
TC09	Notification System	Hazard detected	User receives alert notification	Pass

7.RESULTS

- LCD displaying temperature
- Fire alert message
- Buzzer activation
- Fan working automatically
- IoT dashboard screenshots





8.CONCLUSION

The IoT-based Smart Warehouse Monitoring System presented in this project provides a comprehensive and intelligent solution for ensuring warehouse safety and protecting valuable inventory from fire and temperature-related hazards. By integrating temperature and fire sensors with the NodeMCU microcontroller platform, the system successfully delivers continuous real-time monitoring of critical environmental conditions. The automated alert mechanisms—including LCD display, audible buzzer, and automated fan activation—ensure immediate response to dangerous situations, providing crucial early warning and initial mitigation before human intervention.

The IoT connectivity enabled by the NodeMCU's ESP8266 Wi-Fi module represents a significant advancement in warehouse management, allowing facility managers to monitor conditions remotely and receive instant notifications of hazardous situations regardless of their location. This capability is invaluable for modern warehouse operations that require 24/7 oversight and rapid response to emergencies. The system's cost-effectiveness, scalability, and ease of deployment make it accessible for warehouses of all sizes, from small storage facilities to large distribution centers. Future enhancements could include integration with automated sprinkler systems, additional sensors for humidity and gas detection, machine learning for predictive maintenance, and multi-location centralized monitoring dashboards. In conclusion, this smart monitoring system significantly reduces risks of fire damage and product spoilage while enhancing operational safety and compliance with warehouse management standards.

9.FUTURE SCOPE

The IoT Based Smart Warehouse Monitoring System can be further enhanced by integrating advanced technologies and additional features to improve its efficiency, accuracy, and scalability. In the future, more sensors such as humidity sensors, gas sensors, and motion detectors can be added to monitor additional environmental parameters and provide better safety. Integration of an automatic sprinkler system can help in immediate fire suppression, reducing damage before human intervention.

The system can also be upgraded by incorporating machine learning and artificial intelligence techniques to predict potential hazards based on historical data, enabling predictive maintenance and smarter decision-making. A mobile application can be developed with a user-friendly interface to provide better control, real-time notifications, and detailed analytics for warehouse managers.

Further improvements can include multi-warehouse monitoring systems where multiple warehouses can be connected to a centralized cloud platform for better management. The use of advanced communication technologies such as 5G can improve data transmission speed and reliability. Additionally, security features like user authentication and data encryption can be implemented to ensure data privacy and system protection.

Overall, the system has great potential for expansion and can evolve into a fully automated smart warehouse management solution with enhanced safety, efficiency, and intelligent monitoring capabilities.

10.REFERENCES

1. Bhardwaj, A., Avasthi, V., Goundar, S., and Bhardwaj, R., "IoT Based Warehouse Monitoring System," in International Conference on Inventive Computing and Informatics (ICICI), 2017, pp. 1005-1009.
2. Jimenez-Bravo, D. M., Lozano-Murciego, A., De La Iglesia, D. H., Lopez, V. F., and Revuelta-Herrero, J., "IoT System for Monitoring and Controlling Warehouse Environment," in Proceedings of the International Conference on Practical Applications of Agents and Multi-Agent Systems, 2017, pp. 379-389.
3. Expressif Systems, "ESP8266 Technical Reference Manual," Version 1.7, Espressif Systems, 2023.
4. Kodali, R. K. and Mahesh, K. S., "A Low Cost Implementation of MQTT Using ESP8266," in 2nd International Conference on Contemporary Computing and Informatics (IC3I), 2016, pp. 404-408.
5. Schwartz, M., "Internet of Things with ESP8266," Packt Publishing Ltd, Birmingham, UK, 2016.