org.apache.commons.csv.CSVParserTest:434: $stack12 = interfaceinvoke $stack5.<java.util.List: int size()>()

org.apache.commons.csv.CSVParserTest:431: interfaceinvoke $stack5.<java.util.List: boolean add(java.lang.Object)>(record)

org.apache.commons.csv.CSVParserTest:430: if $stack10 == 0

org.apache.commons.csv.CSVParserTest:426: specialinvoke $stack5.<java.util.ArrayList: void <init>()>()

org.apache.commons.csv.CSVParserTest:430: record = (org.apache.commons.csv.CSVRecord) $stack26 org.apache.commons.csv.CSVParserTest:426: $stack5 = new java.util.ArrayList

org.apache.commons.csv.CSVParser$1:294: return $stack3

org.apache.commons.csv.CSVParserTest:428: specialinvoke $stack6.<java.io.StringReader: void <init>(java.lang.String)>("a,b,cn1,2,3nx,y,z")

org.apache.commons.csv.CSVParserTest:428: $stack6 = new java.io.StringReader

org.apache.commons.csv.ExtendedBufferedReader:49: specialinvoke this.<java.io.BufferedReader: void <init>(java.io.Reader)>(reader)

org.apache.commons.csv.CSVParser:122: specialinvoke $stack6.<org.apache.commons.csv.ExtendedBufferedReader: void <init>(java.io.Reader)>(input)

org.apache.commons.csv.CSVParser:122: $stack6 = new org.apache.commons.csv.ExtendedBufferedReader

org.apache.commons.csv.CSVFormat:839: specialinvoke $stack2.<org.apache.commons.csv.CSVParser: void <init>(java.io.Reader,org.apache.commons.csv.CSVFormat)>(in, this) org.apache.commons.csv.Constants:36: <org.apache.commons.csv.Constants: java.lang.Character DOUBLE_QUOTE_CHAR> = $stack0

org.apache.commons.csv.Constants:36: $stack0 = staticinvoke <java.lang.Character: java.lang.Character valueOf(char)>(34)

org.apache.commons.csv.CSVFormat:442: $stack1 = <org.apache.commons.csv.Constants: java.lang.Character DOUBLE_QUOTE_CHAR>

org.apache.commons.csv.CSVFormat:486: $stack3 = staticinvoke <org.apache.commons.csv.CSVFormat: org.apache.commons.csv.CSVFormat$CSVFormatBuilder newBuilder()>()

org.apache.commons.csv.CSVFormat:442: specialinvoke $stack0.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: void <init>(char,java.lang.Character,org.apache.commons.csv.Quote,java.lang.Character,java.lang.Character,boolean,boolean,java.lang.String,java.lang.String,java.lang.String[])>(44, $stack1, null, null, null, 0, 1, "rn", "", null)

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:115: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character quoteChar> = quoteChar org.apache.commons.csv.CSVFormat$CSVFormatBuilder:118: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character escape> = escape org.apache.commons.csv.CSVFormat$CSVFormatBuilder:114: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: char delimiter> = delimiter

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack11 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: char delimiter>

org.apache.commons.csv.CSVFormat:486: $stack4 = virtualinvoke $stack3.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: org.apache.commons.csv.CSVFormat build()>()

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack10 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character quoteChar> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: specialinvoke $stack1.<org.apache.commons.csv.CSVFormat: void <init>(char,java.lang.Character,org.apache.commons.csv.Quote,java.lang.Character,java.lang.Character,boolean,boolean,java.lang.String,java.lang.String,java.lang.String[])>($stack11, $stack10, $stack9, $stack8, $stack7, $stack6, $stack5, $stack4, $stack3, $stack2) org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack7 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character escape>

org.apache.commons.csv.CSVFormat:607: this.<org.apache.commons.csv.CSVFormat: java.lang.Character quoteChar> = quoteChar org.apache.commons.csv.CSVFormat:610: this.<org.apache.commons.csv.CSVFormat: java.lang.Character escape> = escape org.apache.commons.csv.CSVFormat:606: this.<org.apache.commons.csv.CSVFormat: char delimiter> = delimiter

org.apache.commons.csv.CSVFormat:710: $stack1 = this.<org.apache.commons.csv.CSVFormat: char delimiter>

org.apache.commons.csv.Lexer:60: $stack3 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: char getDelimiter()>()

org.apache.commons.csv.CSVLexer:37: specialinvoke this.<org.apache.commons.csv.Lexer: void <init>(org.apache.commons.csv.CSVFormat,org.apache.commons.csv.ExtendedBufferedReader)>(format, in)

org.apache.commons.csv.CSVFormat:761: $stack1 = this.<org.apache.commons.csv.CSVFormat: java.lang.Character quoteChar>

org.apache.commons.csv.Lexer:62: $stack6 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: java.lang.Character getQuoteChar()>()

org.apache.commons.csv.CSVFormat:719: $stack1 = this.<org.apache.commons.csv.CSVFormat: java.lang.Character escape>

org.apache.commons.csv.Lexer:61: $stack4 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: java.lang.Character getEscape()>()

org.apache.commons.csv.CSVFormat:839: $stack2 = new org.apache.commons.csv.CSVParser

org.apache.commons.csv.CSVParserTest:430: $stack8 = virtualinvoke $stack7.<org.apache.commons.csv.CSVFormat: java.lang.Iterable parse(java.io.Reader)>($stack6)

org.apache.commons.csv.Lexer:59: this.<org.apache.commons.csv.Lexer: org.apache.commons.csv.ExtendedBufferedReader in> = in

org.apache.commons.csv.ExtendedBufferedReader:40: this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar> = $i0

org.apache.commons.csv.CSVParser:122: specialinvoke $stack5.<org.apache.commons.csv.CSVLexer: void <init>(org.apache.commons.csv.CSVFormat,org.apache.commons.csv.ExtendedBufferedReader)>(format, $stack6)

org.apache.commons.csv.ExtendedBufferedReader:-1: $i0 = (int) -2

org.apache.commons.csv.CSVParser:123: $stack7 = specialinvoke this.<org.apache.commons.csv.CSVParser: java.util.Map initializeHeader(org.apache.commons.csv.CSVFormat)>(format)

org.apache.commons.csv.CSVParser:92: this.<org.apache.commons.csv.CSVParser: java.util.List record> = $stack3

org.apache.commons.csv.CSVParser:92: specialinvoke $stack3.<java.util.ArrayList: void <init>()>()

org.apache.commons.csv.CSVParser:92: $stack3 = new java.util.ArrayList

org.apache.commons.csv.CSVParser:123: this.<org.apache.commons.csv.CSVParser: java.util.Map headerMap> = $stack7

org.apache.commons.csv.CSVParser:269: return hdrMap

org.apache.commons.csv.CSVParser:247: hdrMap = null

org.apache.commons.csv.CSVParser:93: specialinvoke $stack4.<org.apache.commons.csv.Token: void <init>()>()

org.apache.commons.csv.CSVParser:185: $stack4 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:195: interfaceinvoke $stack68.<java.util.List: boolean add(java.lang.Object)>($stack69)

org.apache.commons.csv.CSVParser$1:282: $stack3 = virtualinvoke $stack2.<org.apache.commons.csv.CSVParser: org.apache.commons.csv.CSVRecord nextRecord()>()

org.apache.commons.csv.CSVParser:190: tableswitch($stack13) { case 1:

org.apache.commons.csv.CSVParser:195: $stack69 = virtualinvoke $stack67.<java.lang.StringBuilder: java.lang.String toString()>()

org.apache.commons.csv.CSVParser:195: $stack68 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser$1:291: $stack4 = specialinvoke this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord getNextRecord()>()

org.apache.commons.csv.Token:55: specialinvoke $stack2.<java.lang.StringBuilder: void <init>(int)>(50)

org.apache.commons.csv.Token:55: $stack2 = new java.lang.StringBuilder

org.apache.commons.csv.Token:55: this.<org.apache.commons.csv.Token: java.lang.StringBuilder content> = $stack2

org.apache.commons.csv.Token$Type:34: specialinvoke this.<java.lang.Enum: void <init>(java.lang.String,int)>(l1, l2)

org.apache.commons.csv.Token$Type:48: specialinvoke $stack4.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("COMMENT", 4) org.apache.commons.csv.Token$Type:45: specialinvoke $stack3.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("EORECORD", 3) org.apache.commons.csv.Token$Type:42: specialinvoke $stack2.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("EOF", 2) org.apache.commons.csv.Token$Type:39: specialinvoke $stack1.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("TOKEN", 1) org.apache.commons.csv.Token$Type:36: specialinvoke $stack0.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("INVALID", 0) org.apache.commons.csv.Token$Type:42: $stack2 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:36: $stack0 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:45: $stack3 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:39: $stack1 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:48: $stack4 = new org.apache.commons.csv.Token$Type

org.apache.commons.csv.Token$Type:36: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID> = $stack0

org.apache.commons.csv.Token$Type:34: return

org.apache.commons.csv.Token:62: $stack2 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.CSVParser:188: virtualinvoke $stack5.<org.apache.commons.csv.Token: void reset()>()

org.apache.commons.csv.CSVLexer:96: $stack16 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.CSVParser:189: virtualinvoke $stack7.<org.apache.commons.csv.Lexer: org.apache.commons.csv.Token nextToken(org.apache.commons.csv.Token)>($stack6)

org.apache.commons.csv.Token$Type:34: $stack6 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.Token$Type:39: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN> = $stack1

org.apache.commons.csv.CSVLexer:160: $stack29 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN>

org.apache.commons.csv.CSVLexer:124: specialinvoke this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.Token parseSimpleToken(org.apache.commons.csv.Token,int)>(token, c)

org.apache.commons.csv.CSVLexer:116: if $stack21 == 0

org.apache.commons.csv.Token$Type:34: $stack7 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN>

org.apache.commons.csv.Token$Type:42: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EOF> = $stack2

org.apache.commons.csv.CSVLexer:156: $stack33 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EOF>

org.apache.commons.csv.Token$Type:34: $stack8 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EOF>

org.apache.commons.csv.Token$Type:45: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD> = $stack3

org.apache.commons.csv.CSVLexer:153: $stack35 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD>

org.apache.commons.csv.Token$Type:34: $stack9 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD>

org.apache.commons.csv.Token$Type:48: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type COMMENT> = $stack4

org.apache.commons.csv.Token$Type:34: $stack10 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type COMMENT>

org.apache.commons.csv.Token$Type:34: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type[] $VALUES> = $stack5

org.apache.commons.csv.Token$Type:34: $stack5[2] = $stack8 org.apache.commons.csv.Token$Type:34: $stack5[0] = $stack6 org.apache.commons.csv.Token$Type:34: $stack5[3] = $stack9 org.apache.commons.csv.Token$Type:34: $stack5[1] = $stack7 org.apache.commons.csv.Token$Type:34: $stack5[4] = $stack10 org.apache.commons.csv.Token$Type:34: $stack5 = newarray (org.apache.commons.csv.Token$Type)[5]

org.apache.commons.csv.Token$Type:34: $stack0 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type[] $VALUES>

org.apache.commons.csv.CSVParser$2:190: $stack1 = staticinvoke <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type[] values()>()

org.apache.commons.csv.Token:61: $stack1 = this.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVLexer:171: virtualinvoke $stack9.<java.lang.StringBuilder: java.lang.StringBuilder append(char)>($stack8)

org.apache.commons.csv.CSVLexer:171: $stack8 = (char) c org.apache.commons.csv.CSVLexer:171: $stack9 = tkn.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVLexer:162: if $stack7 == 0

org.apache.commons.csv.ExtendedBufferedReader:50: return

org.apache.commons.csv.ExtendedBufferedReader:71: $stack1 = this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar>

org.apache.commons.csv.CSVLexer:55: lastChar = virtualinvoke $stack6.<org.apache.commons.csv.ExtendedBufferedReader: int getLastChar()>() org.apache.commons.csv.ExtendedBufferedReader:58: this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar> = $stack2

org.apache.commons.csv.CSVLexer:58: $stack9 = virtualinvoke $stack8.<org.apache.commons.csv.ExtendedBufferedReader: int read()>()

org.apache.commons.csv.ExtendedBufferedReader:54: $stack2 = specialinvoke this.<java.io.BufferedReader: int read()>()

org.apache.commons.csv.CSVLexer:172: c = virtualinvoke $stack11.<org.apache.commons.csv.ExtendedBufferedReader: int read()>()

org.apache.commons.csv.Lexer:61: this.<org.apache.commons.csv.Lexer: char escape> = $stack5

org.apache.commons.csv.Lexer:69: return $stack2

org.apache.commons.csv.Lexer:61: $stack5 = specialinvoke this.<org.apache.commons.csv.Lexer: char mapNullToDisabled(java.lang.Character)>($stack4) org.apache.commons.csv.Lexer:62: $stack7 = specialinvoke this.<org.apache.commons.csv.Lexer: char mapNullToDisabled(java.lang.Character)>($stack6)

org.apache.commons.csv.Lexer:69: $stack2 = virtualinvoke c.<java.lang.Character: char charValue()>() org.apache.commons.csv.Lexer:69: $stack2 = 65534

org.apache.commons.csv.Lexer:60: this.<org.apache.commons.csv.Lexer: char delimiter> = $stack3

org.apache.commons.csv.CSVFormat:710: return $stack1

org.apache.commons.csv.Lexer:62: this.<org.apache.commons.csv.Lexer: char quoteChar> = $stack7

org.apache.commons.csv.CSVLexer:172: $stack11 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in> org.apache.commons.csv.CSVLexer:58: $stack8 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.Lexer:167: $stack2 = this.<org.apache.commons.csv.Lexer: char delimiter>

org.apache.commons.csv.CSVLexer:106: $stack19 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isDelimiter(int)>(c) org.apache.commons.csv.CSVLexer:159: $stack6 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isDelimiter(int)>(c)

org.apache.commons.csv.CSVFormat:719: return $stack1

org.apache.commons.csv.Lexer:69: if c != null

org.apache.commons.csv.CSVFormat:761: return $stack1

org.apache.commons.csv.Lexer:171: $stack2 = this.<org.apache.commons.csv.Lexer: char escape>

org.apache.commons.csv.CSVLexer:162: $stack7 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEscape(int)>(c)

org.apache.commons.csv.Lexer:175: $stack2 = this.<org.apache.commons.csv.Lexer: char quoteChar>

org.apache.commons.csv.CSVLexer:113: $stack20 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isQuoteChar(int)>(c)

org.apache.commons.csv.CSVParser:219: $stack39 = this.<org.apache.commons.csv.CSVParser: java.util.Map headerMap>

org.apache.commons.csv.CSVParser$1:294: if $stack2 == null

org.apache.commons.csv.CSVParser$1:294: $stack2 = this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord current>

org.apache.commons.csv.CSVParserTest:430: $stack10 = interfaceinvoke $stack9.<java.util.Iterator: boolean hasNext()>()

org.apache.commons.csv.CSVParser$1:291: this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord current> = $stack4

org.apache.commons.csv.CSVParser$1:290: $stack1 = this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord current>

org.apache.commons.csv.CSVParser$1:299: this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord current> = null

org.apache.commons.csv.CSVParser$1:277: $stack1 = virtualinvoke this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord next()>()

org.apache.commons.csv.CSVParser$1:282: return $stack3 org.apache.commons.csv.CSVParser$1:290: if $stack1 != null

org.apache.commons.csv.CSVParser$1:294: $stack3 = 0 org.apache.commons.csv.CSVParser$1:294: $stack3 = 1 org.apache.commons.csv.CSVParser$1:277: return $stack1

org.apache.commons.csv.CSVParser:221: return result

org.apache.commons.csv.CSVParser:219: result = $stack32

org.apache.commons.csv.CSVParser:184: result = null

org.apache.commons.csv.CSVParser$1:282: $stack2 = this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVParser this$0>

org.apache.commons.csv.CSVRecord:52: this.<org.apache.commons.csv.CSVRecord: java.util.Map mapping> = mapping org.apache.commons.csv.CSVRecord:53: this.<org.apache.commons.csv.CSVRecord: java.lang.String comment> = comment

org.apache.commons.csv.CSVRecord:51: this.<org.apache.commons.csv.CSVRecord: java.lang.String[] values> = $stack6

org.apache.commons.csv.CSVRecord:50: this.<org.apache.commons.csv.CSVRecord: long recordNumber> = recordNumber

org.apache.commons.csv.CSVRecord:49: specialinvoke this.<java.lang.Object: void <init>()>()

org.apache.commons.csv.CSVParser:219: $stack32 = new org.apache.commons.csv.CSVRecord

org.apache.commons.csv.CSVParser:216: if $stack28 != 0

org.apache.commons.csv.CSVParser:219: specialinvoke $stack32.<org.apache.commons.csv.CSVRecord: void <init>(java.lang.String[],java.util.Map,java.lang.String,long)>($stack40, $stack39, $stack31, $stack38)

org.apache.commons.csv.CSVParser:218: $stack31 = null

org.apache.commons.csv.CSVRecord:51: $stack6 = values

org.apache.commons.csv.CSVParser:219: $stack38 = this.<org.apache.commons.csv.CSVParser: long recordNumber>

org.apache.commons.csv.CSVParser:216: $stack28 = interfaceinvoke $stack27.<java.util.List: boolean isEmpty()>()

org.apache.commons.csv.CSVParser:192: $stack72 = $stack71.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVParser:192: $stack73 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:192: interfaceinvoke $stack73.<java.util.List: boolean add(java.lang.Object)>($stack74)

org.apache.commons.csv.CSVParser:185: interfaceinvoke $stack4.<java.util.List: void clear()>()

org.apache.commons.csv.CSVParser:192: $stack74 = virtualinvoke $stack72.<java.lang.StringBuilder: java.lang.String toString()>()

org.apache.commons.csv.CSVParser:190: $stack12 = virtualinvoke $stack10.<org.apache.commons.csv.Token$Type: int ordinal()>()

org.apache.commons.csv.CSVParser:190: $stack10 = $stack9.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type>

org.apache.commons.csv.CSVLexer:156: tkn.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack33 org.apache.commons.csv.CSVLexer:153: tkn.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack35

org.apache.commons.csv.CSVLexer:160: tkn.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack29

org.apache.commons.csv.CSVParser:190: $stack13 = $stack11[$stack12]

org.apache.commons.csv.CSVParser:190: $stack11 = <org.apache.commons.csv.CSVParser$2: int[] $SwitchMap$org$apache$commonscsvToken$Type>

org.apache.commons.csv.CSVParser:217: this.<org.apache.commons.csv.CSVParser: long recordNumber> = $stack30

org.apache.commons.csv.CSVParser:217: $stack30 = $stack29 + 1L

org.apache.commons.csv.CSVParser:195: $stack67 = $stack66.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVParser$2:190: <org.apache.commons.csv.CSVParser$2: int[] $SwitchMap$org$apache$commonscsvToken$Type> = $stack3

org.apache.commons.csv.CSVParser:219: $stack34 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:199: interfaceinvoke $stack63.<java.util.List: boolean add(java.lang.Object)>($stack64)

org.apache.commons.csv.CSVParser:199: $stack63 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:199: $stack64 = virtualinvoke $stack62.<java.lang.StringBuilder: java.lang.String toString()>()

org.apache.commons.csv.CSVParser:198: if $stack60 == 0

org.apache.commons.csv.CSVLexer:152: if $stack4 == 0

org.apache.commons.csv.CSVLexer:159: if $stack6 == 0

org.apache.commons.csv.CSVParser$2:190: $stack3 = newarray (int)[$stack2]

org.apache.commons.csv.CSVParser:218: if sb != null

org.apache.commons.csv.CSVParser:186: sb = null

org.apache.commons.csv.CSVParser:216: $stack27 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:217: $stack29 = this.<org.apache.commons.csv.CSVParser: long recordNumber>

org.apache.commons.csv.CSVParser:219: $stack36 = newarray (java.lang.String)[$stack35]

org.apache.commons.csv.CSVParser:219: $stack35 = interfaceinvoke $stack33.<java.util.List: int size()>()

org.apache.commons.csv.CSVParser:219: $stack33 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:219: $stack40 = (java.lang.String[]) $stack37

org.apache.commons.csv.CSVParser:219: $stack37 = interfaceinvoke $stack34.<java.util.List: java.lang.Object[] toArray(java.lang.Object[])>($stack36)

org.apache.commons.csv.Token:62: this.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack2 org.apache.commons.csv.Token:61: virtualinvoke $stack1.<java.lang.StringBuilder: void setLength(int)>(0)

org.apache.commons.csv.CSVLexer:96: $stack17 = token.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type>

org.apache.commons.csv.CSVLexer:96: if $stack17 != $stack16

org.apache.commons.csv.CSVLexer:88: if $stack15 == 0

org.apache.commons.csv.CSVLexer:82: if $stack43 == 0

org.apache.commons.csv.Lexer:156: return $stack2

org.apache.commons.csv.CSVLexer:82: $stack43 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>(c)

org.apache.commons.csv.CSVLexer:58: c = $stack9

org.apache.commons.csv.ExtendedBufferedReader:59: return $stack5

org.apache.commons.csv.CSVLexer:116: $stack21 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>(c) org.apache.commons.csv.ExtendedBufferedReader:59: $stack5 = this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar>

org.apache.commons.csv.Lexer:163: return $stack2 org.apache.commons.csv.CSVLexer:63: eol = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean readEndOfLine(int)>($stack9)

org.apache.commons.csv.CSVLexer:155: $stack5 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>(c)

org.apache.commons.csv.Lexer:163: $stack2 = 1 org.apache.commons.csv.Lexer:163: $stack2 = 0

org.apache.commons.csv.ExtendedBufferedReader:71: return $stack1 org.apache.commons.csv.CSVLexer:88: $stack15 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isStartOfLine(int)>(lastChar)

org.apache.commons.csv.Lexer:156: if c == 10

org.apache.commons.csv.Lexer:137: if c != 13

org.apache.commons.csv.Lexer:137: if c == 10

org.apache.commons.csv.CSVLexer:152: $stack4 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean readEndOfLine(int)>(c)

org.apache.commons.csv.Lexer:137: return $stack2

org.apache.commons.csv.Lexer:137: $stack2 = 0 org.apache.commons.csv.Lexer:137: $stack2 = 1

org.apache.commons.csv.CSVLexer:109: if eol == 0

org.apache.commons.csv.CSVLexer:106: if $stack19 == 0

org.apache.commons.csv.Lexer:167: return $stack3

org.apache.commons.csv.Lexer:163: if c != $i0

org.apache.commons.csv.Lexer:-1: $i0 = (int) -1

org.apache.commons.csv.Lexer:156: $stack2 = 0

org.apache.commons.csv.Lexer:156: $stack2 = 1

org.apache.commons.csv.Lexer:167: $stack3 = 0 org.apache.commons.csv.Lexer:167: $stack3 = 1

org.apache.commons.csv.Lexer:167: if c != $i0

org.apache.commons.csv.Lexer:-1: $i0 = (int) $stack2

org.apache.commons.csv.CSVLexer:113: if $stack20 == 0

org.apache.commons.csv.Lexer:175: return $stack3

org.apache.commons.csv.Lexer:175: $stack3 = 0

org.apache.commons.csv.Lexer:175: if c != $i0

org.apache.commons.csv.Lexer:171: return $stack3

org.apache.commons.csv.CSVLexer:155: if $stack5 == 0

org.apache.commons.csv.Lexer:171: $stack3 = 0

org.apache.commons.csv.Lexer:171: if c != $i0

org.apache.commons.csv.Token$Type:34: return $stack2

org.apache.commons.csv.Token$Type:34: $stack2 = (org.apache.commons.csv.Token$Type[]) $stack1

org.apache.commons.csv.Token$Type:34: $stack1 = virtualinvoke $stack0.<java.lang.Object: java.lang.Object clone()>()

org.apache.commons.csv.CSVParser$2:190: $stack2 = lengthof $stack1

org.apache.commons.csv.CSVRecord:51: if values == null org.apache.commons.csv.CSVRecord:54: return

org.apache.commons.csv.CSVParser$1:298: next = this.<org.apache.commons.csv.CSVParser$1: org.apache.commons.csv.CSVRecord current>

org.apache.commons.csv.CSVParserTest:430: $stack26 = interfaceinvoke $stack9.<java.util.Iterator: java.lang.Object next()>()

org.apache.commons.csv.CSVParser$1:309: return next

org.apache.commons.csv.CSVParser:199: $stack62 = $stack61.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVParser:198: $stack60 = $stack59.<org.apache.commons.csv.Token: boolean isReady>

org.apache.commons.csv.CSVLexer:157: tkn.<org.apache.commons.csv.Token: boolean isReady> = 1

org.apache.commons.csv.CSVParserTest:434: $stack13 = (long) $stack12 org.apache.commons.csv.CSVParserTest:434: staticinvoke <org.junit.Assert: void assertEquals(long,long)>(3L, $stack13)