

com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest:41: staticinvoke <com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest: void assertNotNull(java.lang.Object)>(r)

com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest:36: r = (com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest\$Config) \$stack3

com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest:36: \$stack3 = virtualinvoke \$stack2.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.Object readValue(java.lang.String,java.lang.Class)>("<Config id='123'>n <entry id='foo'> </entry>n</Config>n", class "Lcom/fasterxml/jackson/dataformat/xml/lists/EmptyListDeserTest\$Config;")

com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest:36: \$stack2 = this.<com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest: com.fasterxml.jackson.dataformat.xml.XmlMapper MAPPER>

com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest:32: this.<com.fasterxml.jackson.dataformat.xml.lists.EmptyListDeserTest: com.fasterxml.jackson.dataformat.xml.XmlMapper MAPPER> = \$stack1

com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector:34: specialinvoke this.<com.fasterxml.jackson.databind.introspect.JacksonAnnotationIntrospector: void <init>()>()

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:123: specialinvoke \$u0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector: void <init>(boolean)>(\$stack2)

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:61: \$stack6 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: com.fasterxml.jackson.databind.AnnotationIntrospector _constructIntrospector()>()