com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:29: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlTestBase: void setUp()>()

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:214: $stack90 = virtualinvoke $stack89.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inRoot()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:214: staticinvoke <com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: void assertTrue(boolean)>($stack90)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:31: this.<com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: com.fasterxml.jackson.dataformat.xml.XmlFactory _xmlFactory> = $stack2

com.fasterxml.jackson.dataformat.xml.XmlFactory:120: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLOutputFactory _xmlOutputFactory> = xmlOut com.fasterxml.jackson.dataformat.xml.XmlFactory:119: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory> = xmlIn

com.fasterxml.jackson.dataformat.xml.XmlFactory:115: if xmlOut != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:111: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: java.lang.String _cfgNameForTextElement> = nameForTextElem

com.fasterxml.jackson.dataformat.xml.XmlFactory:110: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlGeneratorFeatures> = xgFeatures com.fasterxml.jackson.dataformat.xml.XmlFactory:108: specialinvoke this.<com.fasterxml.jackson.core.JsonFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec)>(oc) com.fasterxml.jackson.dataformat.xml.XmlFactory:109: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlParserFeatures> = xpFeatures

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:31: $stack2 = new com.fasterxml.jackson.dataformat.xml.XmlFactory

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,int,int,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory,java.lang.String)>(oc, $stack5, $stack4, xmlIn, xmlOut, null)

com.fasterxml.jackson.dataformat.xml.XmlFactory:139: virtualinvoke xmlOut.<javax.xml.stream.XMLOutputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isRepairingNamespaces", $stack3) com.fasterxml.jackson.dataformat.xml.XmlFactory:116: xmlOut = staticinvoke <javax.xml.stream.XMLOutputFactory: javax.xml.stream.XMLOutputFactory newInstance()>() com.fasterxml.jackson.dataformat.xml.XmlFactory:141: virtualinvoke xmlIn.<javax.xml.stream.XMLInputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isCoalescing", $stack4) com.fasterxml.jackson.dataformat.xml.XmlFactory:113: xmlIn = staticinvoke <javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLInputFactory newInstance()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack4 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:31: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:48: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: $stack0 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:54: return flags

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(null, null, null) com.fasterxml.jackson.dataformat.xml.XmlFactory:43: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> = $stack0

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:77: return flags

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:71: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: $stack1 = staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> = $stack1 com.fasterxml.jackson.dataformat.xml.XmlFactory:84: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:102: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:118: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void _initFactories(javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(xmlIn, xmlOut)

com.fasterxml.jackson.dataformat.xml.XmlFactory:139: $stack3 = <java.lang.Boolean: java.lang.Boolean TRUE> com.fasterxml.jackson.dataformat.xml.XmlFactory:141: $stack4 = <java.lang.Boolean: java.lang.Boolean TRUE> com.fasterxml.jackson.dataformat.xml.XmlFactory:112: if xmlIn != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:121: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:142: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:554: $stack5 = this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory>

com.fasterxml.jackson.dataformat.xml.XmlFactory:29: $stack3 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser _createParser(java.io.Reader,com.fasterxml.jackson.core.io.IOContext)>(x0, x1)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: $stack43 = this.<com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: com.fasterxml.jackson.dataformat.xml.XmlFactory _xmlFactory> com.fasterxml.jackson.dataformat.xml.XmlFactory:554: $stack6 = virtualinvoke $stack5.<javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLStreamReader createXMLStreamReader(java.io.Reader)>(r)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: $stack44 = virtualinvoke $stack43.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.core.JsonParser createParser(java.io.Reader)>($stack42)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: specialinvoke $stack42.<java.io.StringReader: void <init>(java.lang.String)>("<array><elem>value</elem><elem><property>123</property></elem><elem>1</elem></array>")

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: $stack42 = new java.io.StringReader

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: xp = (com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser) $stack44

com.fasterxml.jackson.dataformat.xml.XmlFactory:555: $stack7 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLStreamReader _initializeXmlReader(javax.xml.stream.XMLStreamReader)>($stack6) com.fasterxml.jackson.dataformat.xml.XmlFactory:559: specialinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: void <init>(com.fasterxml.jackson.core.io.IOContext,int,int,com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLStreamReader)>(ctxt, $stack11, $stack10, $stack9, $stack7)

com.fasterxml.jackson.dataformat.xml.XmlFactory:651: return sr

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:108: $stack4 = staticinvoke <org.codehaus.stax2.ri.Stax2ReaderAdapter: org.codehaus.stax2.XMLStreamReader2 wrapIfNecessary(javax.xml.stream.XMLStreamReader)>(xmlReader)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:173: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: void <init>(javax.xml.stream.XMLStreamReader,java.lang.Object)>(xmlReader, $stack9)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:172: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = $stack7

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:172: $stack7 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:170: $stack6 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createRootContext(int,int)>($i0, $i1)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:170: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: return $stack2

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:62: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _columnNr> = colNr com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:61: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _lineNr> = lineNr

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: $stack2 = new com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:63: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _index> = $i0 com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:59: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _type> = type com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:60: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parent> = parent

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:58: specialinvoke this.<com.fasterxml.jackson.core.JsonStreamContext: void <init>()>() com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:48: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child> = null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i0 = (int) -1

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:187: $stack48 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i1 = (int) -1

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(null, 0, lineNr, colNr) com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:101: specialinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(this, 2, lineNr, colNr) com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i4 = (int) -1

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:199: $stack64 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: $stack109 = virtualinvoke $stack108.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createChildObjectContext(int,int)>($i0, $i1) com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:481: $stack93 = virtualinvoke $stack92.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createChildObjectContext(int,int)>($i4, $i5)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i5 = (int) -1

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:-1: $i0 = (int) -1

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:101: $stack4 = new com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:64: return

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:99: ctxt = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: $stack108 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:449: t = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:201: $stack68 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:480: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = $stack91

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:478: if $stack73 == 0 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:480: $stack91 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken FIELD_NAME>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:448: $stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:203: $stack72 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:195: $stack58 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:209: $stack82 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>() com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:451: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = null com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:413: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = null com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:206: $stack78 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:448: if $stack3 == null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:407: if t != $stack2

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:112: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount> = $stack10

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:112: $stack10 = interfaceinvoke $stack9.<org.codehaus.stax2.XMLStreamReader2: int getAttributeCount()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:112: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:109: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:62: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex> = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:108: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader> = $stack4

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:310: $stack7 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:401: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex> = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:162: $stack3 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:347: $stack30 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _initStartElement()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:320: $stack13 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _initStartElement()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:487: t#4 = virtualinvoke $stack87.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:171: $stack2 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>() com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:472: t#4 = virtualinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:363: $stack11 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:317: $stack8 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _collectUntilTag()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:319: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader> com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:354: $stack2 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:400: $stack7 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:340: lookupswitch($stack27) { case 2:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:319: if $stack10 != 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:305: $stack2 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:426: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 1 com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:483: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 2 com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:325: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 5

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:408: if $stack9 == null com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:333: $stack3 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _handleEndElement()>() com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:344: $stack29 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _handleEndElement()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:310: $stack6 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:400: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount> = $stack8

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:400: $stack8 = interfaceinvoke $stack7.<org.codehaus.stax2.XMLStreamReader2: int getAttributeCount()>()

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:214: $stack89 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext getParsingContext()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:517: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack62 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:518: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.util.Set _namesToWrap> = $stack64

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:516: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack60

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:482: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack94

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:481: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack93

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack33

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:538: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:536: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.lang.String _currText> = $stack8

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:511: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:488: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> = 1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:408: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack5

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack109

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:450: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = t

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:447: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: byte[] _binaryValue> = null

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:213: $stack88 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:510: if $stack57 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:118: return $stack1 com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:156: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:516: $stack60 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken END_ARRAY> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:516: $stack60 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken END_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:482: $stack94 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:102: return $stack4

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:545: if $stack32 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: $stack33 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken VALUE_STRING>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:537: if $stack9 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:179: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:484: if $stack75 == 0

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:191: $stack52 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean isExpectedStartArrayToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:408: $stack5 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_ARRAY>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:481: $stack92 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:100: if ctxt != null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:406: t = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken>

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:118: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parent>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:517: $stack62 = virtualinvoke $stack61.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext getParent()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:545: $stack31 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:484: $stack74 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:407: $stack2 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:545: $stack32 = virtualinvoke $stack31.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inArray()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:537: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:478: $stack73 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:546: if $stack35 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:950: return 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:949: if $i0 <= 32

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:484: $stack75 = virtualinvoke $stack74.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inArray()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:544: virtualinvoke $stack30.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: void skipEndElement()>() com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:536: $stack8 = virtualinvoke $stack7.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String getText()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:179: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _textValue>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:546: $stack34 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.lang.String _currText> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:546: $stack35 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _isEmpty(java.lang.String)>($stack34)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:476: if t#4 != 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:158: $stack2 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _repeatElement>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:305: tableswitch($stack2) { case 1:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:310: if $stack7 >= $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:319: $stack10 = interfaceinvoke $stack9.<org.codehaus.stax2.XMLStreamReader2: int getEventType()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:408: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: com.fasterxml.jackson.dataformat.xml.deser.ElementWrapper _currentWrapper>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:354: $stack3 = interfaceinvoke $stack2.<org.codehaus.stax2.XMLStreamReader2: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:358: return text

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:363: text = interfaceinvoke $stack11.<org.codehaus.stax2.XMLStreamReader2: java.lang.String getText()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:362: if text != null

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:352: text = null com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:354: tableswitch($stack3) { case 1:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:324: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _textValue> = $stack8

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:323: if $stack8 == null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:946: if str != null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:949: $stack6 = virtualinvoke str.<java.lang.String: char charAt(int)>(i)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:948: i = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i0 = (int) $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:340: $stack27 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _skipUntilTag()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:382: return $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:162: return $stack3

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:378: $stack6 = interfaceinvoke $stack5.<org.codehaus.stax2.XMLStreamReader2: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:516: $stack58 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:510: $stack57 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:518: $stack64 = virtualinvoke $stack63.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: java.util.Set getNamesToWrap()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:516: if $stack59 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:516: $stack59 = virtualinvoke $stack58.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inArray()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:156: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: java.util.Set _namesToWrap>