com.fasterxml.jackson.dataformat.xml.XmlFactory:29: $stack5 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser _createParser(byte[],int,int,com.fasterxml.jackson.core.io.IOContext)>(x0, x1, x2, x3)

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:134: specialinvoke $stack7.<com.fasterxml.jackson.databind.ObjectMapper: void <init>()>()

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:134: $stack7 = new com.fasterxml.jackson.databind.ObjectMapper

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:141: $stack17 = virtualinvoke $stack7.<com.fasterxml.jackson.databind.ObjectMapper: com.fasterxml.jackson.databind.ObjectReader readerFor(java.lang.Class)>(class "Lcom/fasterxml/jackson/dataformat/xml/stream/FormatDetectionTest$ListPOJO;")

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke this.<com.fasterxml.jackson.databind.ObjectMapper: void <init>(com.fasterxml.jackson.core.JsonFactory,com.fasterxml.jackson.databind.ser.DefaultSerializerProvider,com.fasterxml.jackson.databind.deser.DefaultDeserializationContext)>(xmlFactory, $u1, null)

com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:41: specialinvoke this.<com.fasterxml.jackson.databind.ser.DefaultSerializerProvider: void <init>()>() com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:42: this.<com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider: com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup _rootNameLookup> = rootNames com.fasterxml.jackson.dataformat.xml.XmlMapper:79: $u1 = new com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider

com.fasterxml.jackson.dataformat.xml.XmlMapper:67: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>(com.fasterxml.jackson.dataformat.xml.XmlFactory,com.fasterxml.jackson.dataformat.xml.JacksonXmlModule)>(xmlFactory, $stack2)

com.fasterxml.jackson.dataformat.xml.XmlFactory:119: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory> = xmlIn com.fasterxml.jackson.dataformat.xml.XmlFactory:120: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLOutputFactory _xmlOutputFactory> = xmlOut

com.fasterxml.jackson.dataformat.xml.XmlFactory:115: if xmlOut != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:111: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: java.lang.String _cfgNameForTextElement> = nameForTextElem

com.fasterxml.jackson.dataformat.xml.XmlFactory:110: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlGeneratorFeatures> = xgFeatures com.fasterxml.jackson.dataformat.xml.XmlFactory:109: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlParserFeatures> = xpFeatures

com.fasterxml.jackson.dataformat.xml.XmlFactory:108: specialinvoke this.<com.fasterxml.jackson.core.JsonFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec)>(oc)

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: $stack1 = new com.fasterxml.jackson.dataformat.xml.XmlFactory com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:135: $stack8 = new com.fasterxml.jackson.dataformat.xml.XmlMapper

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke $u1.<com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider: void <init>(com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup)>($u0)

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: $u0 = new com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:30: specialinvoke this.<java.lang.Object: void <init>()>() com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: this.<com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup: com.fasterxml.jackson.databind.util.LRUMap _rootNames> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>(com.fasterxml.jackson.dataformat.xml.XmlFactory)>($stack1)

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,int,int,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory,java.lang.String)>(oc, $stack5, $stack4, xmlIn, xmlOut, null)

com.fasterxml.jackson.dataformat.xml.XmlFactory:141: virtualinvoke xmlIn.<javax.xml.stream.XMLInputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isCoalescing", $stack4) com.fasterxml.jackson.dataformat.xml.XmlFactory:139: virtualinvoke xmlOut.<javax.xml.stream.XMLOutputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isRepairingNamespaces", $stack3) com.fasterxml.jackson.dataformat.xml.XmlFactory:113: xmlIn = staticinvoke <javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLInputFactory newInstance()>() com.fasterxml.jackson.dataformat.xml.XmlFactory:116: xmlOut = staticinvoke <javax.xml.stream.XMLOutputFactory: javax.xml.stream.XMLOutputFactory newInstance()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack4 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS>

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:135: specialinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>()>()

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack20 = virtualinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.ObjectReader readerFor(java.lang.Class)>(class "Lcom/fasterxml/jackson/dataformat/xml/stream/FormatDetectionTest$ListPOJO;")

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:139: $stack16 = virtualinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.String writeValueAsString(java.lang.Object)>($stack9)

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.SerializationConfig _serializationConfig> = $stack7

com.fasterxml.jackson.dataformat.xml.XmlMapper:80: this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule _xmlModule> = module

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO:27: specialinvoke this.<java.lang.Object: void <init>()>()

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:136: $stack9 = new com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO:28: this.<com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO: java.util.List v> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack7 = virtualinvoke $stack6.<com.fasterxml.jackson.databind.SerializationConfig: com.fasterxml.jackson.databind.SerializationConfig withDefaultPrettyPrinter(com.fasterxml.jackson.core.PrettyPrinter)>($stack5)

com.fasterxml.jackson.dataformat.xml.XmlMapper:67: $stack2 = <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule DEFAULT_XML_MODULE>

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule DEFAULT_XML_MODULE> = $stack0

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:30: this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: boolean _cfgDefaultUseWrapper> = 1 com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:40: this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: java.lang.String _cfgNameForTextElement> = ""

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:50: specialinvoke this.<com.fasterxml.jackson.databind.module.SimpleModule: void <init>(java.lang.String,com.fasterxml.jackson.core.Version)>("JackxonXmlModule", $stack1) com.fasterxml.jackson.dataformat.xml.XmlMapper:35: $stack0 = new com.fasterxml.jackson.dataformat.xml.JacksonXmlModule

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: specialinvoke $stack0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: void <init>()>()

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:50: $stack1 = <com.fasterxml.jackson.dataformat.xml.PackageVersion: com.fasterxml.jackson.core.Version VERSION>

com.fasterxml.jackson.dataformat.xml.PackageVersion:13: <com.fasterxml.jackson.dataformat.xml.PackageVersion: com.fasterxml.jackson.core.Version VERSION> = $stack0

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:51: return

com.fasterxml.jackson.dataformat.xml.PackageVersion:13: $stack0 = staticinvoke <com.fasterxml.jackson.core.util.VersionUtil: com.fasterxml.jackson.core.Version parseVersion(java.lang.String,java.lang.String,java.lang.String)>("2.7.0-rc4-SNAPSHOT", "com.fasterxml.jackson.dataformat", "jackson-dataformat-xml")

com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter:106: specialinvoke this.<java.lang.Object: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:37: $stack1 = new com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter com.fasterxml.jackson.dataformat.xml.XmlMapper:37: specialinvoke $stack1.<com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:37: <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter DEFAULT_XML_PRETTY_PRINTER> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter DEFAULT_XML_PRETTY_PRINTER>

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: specialinvoke $stack1.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:48: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: $stack0 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:54: return flags

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(null, null, null) com.fasterxml.jackson.dataformat.xml.XmlFactory:43: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> = $stack0

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:77: return flags

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:71: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: $stack1 = staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: return com.fasterxml.jackson.dataformat.xml.XmlFactory:49: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlFactory:102: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:118: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void _initFactories(javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(xmlIn, xmlOut)

com.fasterxml.jackson.dataformat.xml.XmlFactory:139: $stack3 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:112: if xmlIn != null com.fasterxml.jackson.dataformat.xml.XmlFactory:121: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:142: return com.fasterxml.jackson.dataformat.xml.XmlFactory:141: $stack4 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlMapper:68: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:87: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:83: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.ObjectMapper registerModule(com.fasterxml.jackson.databind.Module)>($r0)

com.fasterxml.jackson.dataformat.xml.XmlMapper:-1: $r0 = (com.fasterxml.jackson.databind.Module) module com.fasterxml.jackson.dataformat.xml.XmlMapper:82: if module == null com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack6 = this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.SerializationConfig _serializationConfig> com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup: void <init>()>()

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: $stack1 = new com.fasterxml.jackson.databind.util.LRUMap

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: specialinvoke $stack1.<com.fasterxml.jackson.databind.util.LRUMap: void <init>(int,int)>(40, 200)

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:30: return

com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:43: return

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:136: specialinvoke $stack9.<com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO: void <init>()>()

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO:28: $stack1 = new java.util.ArrayList

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:58: specialinvoke this.<com.fasterxml.jackson.core.JsonStreamContext: void <init>()>()

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO:28: specialinvoke $stack1.<java.util.ArrayList: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:101: specialinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(this, 2, lineNr, colNr)

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO:28: return

com.fasterxml.jackson.dataformat.xml.XmlTestBase:264: $stack3 = virtualinvoke str.<java.lang.String: byte[] getBytes(java.lang.String)>("UTF-8")

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack22 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest: byte[] utf8Bytes(java.lang.String)>($stack16)

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack21 = virtualinvoke $stack17.<com.fasterxml.jackson.databind.ObjectReader: com.fasterxml.jackson.databind.ObjectReader withFormatDetection(com.fasterxml.jackson.databind.ObjectReader[])>($stack18)

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack18 = newarray (com.fasterxml.jackson.databind.ObjectReader)[2] com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack18[1] = $stack20 com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack18[0] = $stack17

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: $stack23 = virtualinvoke $stack21.<com.fasterxml.jackson.databind.ObjectReader: java.lang.Object readValue(byte[])>($stack22)

com.fasterxml.jackson.dataformat.xml.XmlTestBase:264: return $stack3

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:142: resultList = (com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO) $stack23

com.fasterxml.jackson.dataformat.xml.XmlFactory:598: specialinvoke $u1.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: void <init>(com.fasterxml.jackson.core.io.IOContext,int,int,com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLStreamReader)>(ctxt, $stack14, $stack13, $stack12, $stack10)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:170: $stack6 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createRootContext(int,int)>($i0, $i1)

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(null, 0, lineNr, colNr)

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:48: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child> = null

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:99: ctxt = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: $stack109 = virtualinvoke $stack108.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createChildObjectContext(int,int)>($i0, $i1)

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:100: if ctxt != null

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:146: $stack24 = resultList.<com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest$ListPOJO: java.util.List v>

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:145: staticinvoke <com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest: void assertNotNull(java.lang.Object)>(resultList)

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:146: $stack26 = interfaceinvoke $stack24.<java.util.List: int size()>()

com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest:146: staticinvoke <com.fasterxml.jackson.dataformat.xml.stream.FormatDetectionTest: void assertEquals(int,int)>(2, $stack26)