

com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization:68: staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization: void assertNotNull(java.lang.Object)>(map)



com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization:56: map = (java.util.Map) \$stack4



com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization:56: \$stack4 = virtualinvoke \$stack3.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.Object readValue(java.lang.String,java.lang.Class)>("<order><person lang='en'>John Smith</person></order>", class "Ljava/util/Map;")



com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization:56: \$stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization: com.fasterxml.jackson.dataformat.xml.XmlMapper MAPPER>



com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization:30: this.<com.fasterxml.jackson.dataformat.xml.deser.TestDeserialization: com.fasterxml.jackson.dataformat.xml.XmlMapper MAPPER> = \$stack1



com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector:34: specialinvoke this.<com.fasterxml.jackson.databind.introspect.JacksonAnnotationIntrospector: void <init>()>()



com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:123: specialinvoke \$u0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector: void <init>(boolean)>(\$stack2)



com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:61: \$stack6 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: com.fasterxml.jackson.databind.AnnotationIntrospector _constructIntrospector()>()