com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:29: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlTestBase: void setUp()>()

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:241: staticinvoke <com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: void assertEquals(java.lang.String,java.lang.String)>("9", $stack23)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:31: $stack2 = new com.fasterxml.jackson.dataformat.xml.XmlFactory

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:31: this.<com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: com.fasterxml.jackson.dataformat.xml.XmlFactory _xmlFactory> = $stack2

com.fasterxml.jackson.dataformat.xml.XmlFactory:120: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLOutputFactory _xmlOutputFactory> = xmlOut com.fasterxml.jackson.dataformat.xml.XmlFactory:119: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory> = xmlIn

com.fasterxml.jackson.dataformat.xml.XmlFactory:115: if xmlOut != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:111: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: java.lang.String _cfgNameForTextElement> = nameForTextElem

com.fasterxml.jackson.dataformat.xml.XmlFactory:109: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlParserFeatures> = xpFeatures com.fasterxml.jackson.dataformat.xml.XmlFactory:110: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlGeneratorFeatures> = xgFeatures

com.fasterxml.jackson.dataformat.xml.XmlFactory:108: specialinvoke this.<com.fasterxml.jackson.core.JsonFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec)>(oc)

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,int,int,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory,java.lang.String)>(oc, $stack5, $stack4, xmlIn, xmlOut, null)

com.fasterxml.jackson.dataformat.xml.XmlFactory:139: virtualinvoke xmlOut.<javax.xml.stream.XMLOutputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isRepairingNamespaces", $stack3) com.fasterxml.jackson.dataformat.xml.XmlFactory:116: xmlOut = staticinvoke <javax.xml.stream.XMLOutputFactory: javax.xml.stream.XMLOutputFactory newInstance()>() com.fasterxml.jackson.dataformat.xml.XmlFactory:141: virtualinvoke xmlIn.<javax.xml.stream.XMLInputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isCoalescing", $stack4) com.fasterxml.jackson.dataformat.xml.XmlFactory:113: xmlIn = staticinvoke <javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLInputFactory newInstance()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack4 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:31: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:48: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: $stack0 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:54: return flags

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> = $stack0 com.fasterxml.jackson.dataformat.xml.XmlFactory:84: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(null, null, null)

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:77: return flags

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:71: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: $stack1 = staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> = $stack1 com.fasterxml.jackson.dataformat.xml.XmlFactory:84: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:102: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:121: return com.fasterxml.jackson.dataformat.xml.XmlFactory:118: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void _initFactories(javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(xmlIn, xmlOut)

com.fasterxml.jackson.dataformat.xml.XmlFactory:139: $stack3 = <java.lang.Boolean: java.lang.Boolean TRUE> com.fasterxml.jackson.dataformat.xml.XmlFactory:141: $stack4 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:112: if xmlIn != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:142: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:554: $stack5 = this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory>

com.fasterxml.jackson.dataformat.xml.XmlFactory:29: $stack3 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser _createParser(java.io.Reader,com.fasterxml.jackson.core.io.IOContext)>(x0, x1)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:229: $stack4 = this.<com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: com.fasterxml.jackson.dataformat.xml.XmlFactory _xmlFactory>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:229: $stack5 = virtualinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.core.JsonParser createParser(java.io.Reader)>($stack3)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:229: specialinvoke $stack3.<java.io.StringReader: void <init>(java.lang.String)>("<data max="7" offset="9"/>")

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:229: $stack3 = new java.io.StringReader

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:229: xp = (com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser) $stack5

com.fasterxml.jackson.dataformat.xml.XmlFactory:559: specialinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: void <init>(com.fasterxml.jackson.core.io.IOContext,int,int,com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLStreamReader)>(ctxt, $stack11, $stack10, $stack9, $stack7) com.fasterxml.jackson.dataformat.xml.XmlFactory:555: $stack7 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLStreamReader _initializeXmlReader(javax.xml.stream.XMLStreamReader)>($stack6)

com.fasterxml.jackson.dataformat.xml.XmlFactory:554: $stack6 = virtualinvoke $stack5.<javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLStreamReader createXMLStreamReader(java.io.Reader)>(r)

com.fasterxml.jackson.dataformat.xml.XmlFactory:651: return sr

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:108: $stack4 = staticinvoke <org.codehaus.stax2.ri.Stax2ReaderAdapter: org.codehaus.stax2.XMLStreamReader2 wrapIfNecessary(javax.xml.stream.XMLStreamReader)>(xmlReader)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:173: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: void <init>(javax.xml.stream.XMLStreamReader,java.lang.Object)>(xmlReader, $stack9)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:170: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: return $stack2

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:170: $stack6 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createRootContext(int,int)>($i0, $i1)

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:62: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _columnNr> = colNr com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:61: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _lineNr> = lineNr

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:63: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _index> = $i0 com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:59: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _type> = type com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:60: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parent> = parent

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:48: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child> = null

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:58: specialinvoke this.<com.fasterxml.jackson.core.JsonStreamContext: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: $stack2 = new com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i1 = (int) -1

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:232: $stack7 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:172: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = $stack7

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:172: $stack7 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i0 = (int) -1

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:79: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(null, 0, lineNr, colNr) com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:101: specialinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(this, 2, lineNr, colNr)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: $stack109 = virtualinvoke $stack108.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createChildObjectContext(int,int)>($i0, $i1)

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:-1: $i0 = (int) -1 com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:64: return com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:101: $stack4 = new com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:99: ctxt = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: $stack108 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:448: $stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:451: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = null com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:238: $stack17 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:233: $stack9 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:235: $stack13 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:449: t = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:112: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:108: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader> = $stack4

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:112: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount> = $stack10

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:112: $stack10 = interfaceinvoke $stack9.<org.codehaus.stax2.XMLStreamReader2: int getAttributeCount()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:109: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 1 com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:62: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex> = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:313: $stack20 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:307: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex> = $stack5

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:162: $stack3 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:307: $stack5 = $stack4 + 1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:472: t#4 = virtualinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:310: $stack7 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:313: $stack21 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader> com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:307: $stack4 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:305: $stack2 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:314: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 3 com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:330: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 4

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:305: tableswitch($stack2) { case 1:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:310: $stack6 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:241: $stack23 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.lang.String getText()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:534: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack45

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:533: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.lang.String _currText> = $stack44

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:531: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack50

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:511: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:454: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack109

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:450: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = t

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:447: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: byte[] _binaryValue> = null

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:240: $stack21 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:534: $stack45 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken VALUE_STRING>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:179: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:531: $stack50 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken FIELD_NAME>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:523: if $stack46 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:102: return $stack4

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:448: if $stack3 == null

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:100: if ctxt != null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:523: $stack46 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:310: if $stack7 >= $stack6 com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:313: $stack22 = interfaceinvoke $stack21.<org.codehaus.stax2.XMLStreamReader2: java.lang.String getAttributeValue(int)>($stack20)

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:313: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _textValue> = $stack22

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:179: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _textValue>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:533: $stack44 = virtualinvoke $stack43.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String getText()>()