com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:219: $stack96 = virtualinvoke $stack95.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inRoot()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:219: staticinvoke <com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: void assertTrue(boolean)>($stack96)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:26: $stack2 = new com.fasterxml.jackson.dataformat.xml.XmlFactory

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:24: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlTestBase: void setUp()>()

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:26: this.<com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: com.fasterxml.jackson.dataformat.xml.XmlFactory _xmlFactory> = $stack2

com.fasterxml.jackson.dataformat.xml.XmlFactory:124: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLOutputFactory _xmlOutputFactory> = xmlOut com.fasterxml.jackson.dataformat.xml.XmlFactory:123: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory> = xmlIn

com.fasterxml.jackson.dataformat.xml.XmlFactory:119: if xmlOut != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:111: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: java.lang.String _cfgNameForTextElement> = nameForTextElem

com.fasterxml.jackson.dataformat.xml.XmlFactory:110: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlGeneratorFeatures> = xgFeatures com.fasterxml.jackson.dataformat.xml.XmlFactory:109: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlParserFeatures> = xpFeatures

com.fasterxml.jackson.dataformat.xml.XmlFactory:108: specialinvoke this.<com.fasterxml.jackson.core.JsonFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec)>(oc)

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,int,int,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory,java.lang.String)>(oc, $stack5, $stack4, xmlIn, xmlOut, null)

com.fasterxml.jackson.dataformat.xml.XmlFactory:143: virtualinvoke xmlOut.<javax.xml.stream.XMLOutputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isRepairingNamespaces", $stack3) com.fasterxml.jackson.dataformat.xml.XmlFactory:120: xmlOut = staticinvoke <javax.xml.stream.XMLOutputFactory: javax.xml.stream.XMLOutputFactory newInstance()>() com.fasterxml.jackson.dataformat.xml.XmlFactory:145: virtualinvoke xmlIn.<javax.xml.stream.XMLInputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isCoalescing", $stack4)

com.fasterxml.jackson.dataformat.xml.XmlFactory:113: xmlIn = $stack15

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack4 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:26: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:64: $stack6 = virtualinvoke f.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: boolean enabledByDefault()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: $stack0 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:65: flags = flags | $stack9

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:77: return $stack1 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:64: if $stack6 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:62: flags = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:65: $stack9 = virtualinvoke f.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int getMask()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:77: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int _mask> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:76: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:68: return flags

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:76: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: boolean _defaultState>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:71: specialinvoke this.<java.lang.Enum: void <init>(java.lang.String,int)>(l1, l2)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:50: $stack0 = new com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:50: specialinvoke $stack0.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: void <init>(java.lang.String,int,boolean)>("EMPTY_ELEMENT_AS_NULL", 0, 1)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:73: $stack5 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int ordinal()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:72: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: boolean _defaultState> = defaultState

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:73: $stack6 = 1 << $stack5

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:73: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int _mask> = $stack6

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(null, null, null) com.fasterxml.jackson.dataformat.xml.XmlFactory:49: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> = $stack1 com.fasterxml.jackson.dataformat.xml.XmlFactory:43: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> = $stack0

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: $stack1 = staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:102: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:122: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void _initFactories(javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(xmlIn, xmlOut) com.fasterxml.jackson.dataformat.xml.XmlFactory:113: $stack15 = staticinvoke <javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLInputFactory newInstance()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:145: $stack4 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:125: return com.fasterxml.jackson.dataformat.xml.XmlFactory:112: if xmlIn != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:146: return com.fasterxml.jackson.dataformat.xml.XmlFactory:143: $stack3 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:550: $stack5 = this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory>

com.fasterxml.jackson.dataformat.xml.XmlFactory:29: $stack3 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser _createParser(java.io.Reader,com.fasterxml.jackson.core.io.IOContext)>(x0, x1)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: $stack44 = this.<com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest: com.fasterxml.jackson.dataformat.xml.XmlFactory _xmlFactory>

com.fasterxml.jackson.dataformat.xml.XmlFactory:550: $stack6 = virtualinvoke $stack5.<javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLStreamReader createXMLStreamReader(java.io.Reader)>(r)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: $stack45 = virtualinvoke $stack44.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.core.JsonParser createParser(java.io.Reader)>($stack43)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: specialinvoke $stack43.<java.io.StringReader: void <init>(java.lang.String)>("<array><elem>value</elem><elem><property>123</property></elem><elem>1</elem></array>")

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: $stack43 = new java.io.StringReader

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:184: xp = (com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser) $stack45

com.fasterxml.jackson.dataformat.xml.XmlFactory:555: specialinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: void <init>(com.fasterxml.jackson.core.io.IOContext,int,int,com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLStreamReader)>(ctxt, $stack11, $stack10, $stack9, $stack7) com.fasterxml.jackson.dataformat.xml.XmlFactory:554: $stack7 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLStreamReader _initializeXmlReader(javax.xml.stream.XMLStreamReader)>($stack6)

com.fasterxml.jackson.dataformat.xml.XmlFactory:659: return sr

com.fasterxml.jackson.dataformat.xml.XmlFactory:653: if $stack3 == 1

com.fasterxml.jackson.dataformat.xml.XmlFactory:653: $stack3 = interfaceinvoke sr.<javax.xml.stream.XMLStreamReader: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:122: $stack5 = staticinvoke <org.codehaus.stax2.ri.Stax2ReaderAdapter: org.codehaus.stax2.XMLStreamReader2 wrapIfNecessary(javax.xml.stream.XMLStreamReader)>(xmlReader)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:187: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: void <init>(javax.xml.stream.XMLStreamReader,java.lang.Object,int)>(xmlReader, $stack9, $stack10)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i0 = (int) -1

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:187: $stack49 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i1 = (int) -1 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:184: $stack6 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createRootContext(int,int)>($i0, $i1) com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:186: $stack7 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:184: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:99: return $stack2

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:66: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _lineNr> = lineNr com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:67: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _columnNr> = colNr

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:99: $stack2 = new com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:68: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _index> = $i0

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:65: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parent> = parent

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:64: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: int _type> = type

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:63: specialinvoke this.<com.fasterxml.jackson.core.JsonStreamContext: void <init>()>() com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:53: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child> = null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:186: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = $stack7

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i4 = (int) -1

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:99: specialinvoke $stack2.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(null, 0, lineNr, colNr) com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:121: specialinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: void <init>(com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext,int,int,int)>(this, 2, lineNr, colNr)

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:199: $stack65 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i5 = (int) -1 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:480: $stack110 = virtualinvoke $stack109.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createChildObjectContext(int,int)>($i0, $i1) com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:511: $stack94 = virtualinvoke $stack93.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext createChildObjectContext(int,int)>($i4, $i5)

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:-1: $i0 = (int) -1

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:121: $stack4 = new com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:69: return

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:119: ctxt = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _child>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:480: $stack109 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:475: t = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:201: $stack69 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:510: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = $stack92

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:510: $stack92 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken FIELD_NAME>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:474: $stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:214: $stack88 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:477: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = null

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:195: $stack59 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:435: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken> = null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:474: if $stack3 == null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:432: if $stack8 != $stack7

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:122: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader> = $stack5

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:126: $stack11 = interfaceinvoke $stack10.<org.codehaus.stax2.XMLStreamReader2: int getAttributeCount()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:126: $stack10 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:123: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:126: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount> = $stack11

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:75: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex> = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:314: $stack10 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:461: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _nextAttributeIndex> = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:183: $stack2 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:366: $stack40 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _initStartElement()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:327: $stack16 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _initStartElement()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:180: if $stack1 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:372: $stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:321: $stack11 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _collectUntilTag()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:407: $stack7 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader> com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:322: $stack12 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:460: $stack7 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:359: lookupswitch($stack37) { case 2:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:325: if $stack11 == null

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:382: $stack5 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: org.codehaus.stax2.XMLStreamReader2 _xmlReader>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:309: $stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:543: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 2

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:337: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 5

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:486: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _currentState> = 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:468: if $stack9 == null com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:352: $stack5 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _handleEndElement()>() com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:363: $stack39 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _handleEndElement()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:314: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:460: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _attributeCount> = $stack8

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:460: $stack8 = interfaceinvoke $stack7.<org.codehaus.stax2.XMLStreamReader2: int getAttributeCount()>()

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:219: $stack95 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext getParsingContext()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:558: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.util.Set _namesToWrap> = $stack59

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:557: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack57

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack55

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:512: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack95

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:511: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack94

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:598: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack30

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:578: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:576: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.lang.String _currText> = $stack8

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:522: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf> = 1 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:426: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = $stack5

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:480: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext> = $stack110

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:476: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken> = t

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:473: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: byte[] _binaryValue> = null

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:218: $stack94 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>() com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:211: $stack84 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:180: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:545: if $stack52 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:141: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: $stack55 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken END_OBJECT> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: $stack55 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken END_ARRAY>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:512: $stack95 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT> com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:508: if $stack74 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:122: return $stack4

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:588: if $stack29 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:598: $stack30 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken VALUE_STRING>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:577: if $stack9 == 0

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:203: $stack73 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken nextToken()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:196: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:514: if $stack76 == 0 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:425: if t != $stack2 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:426: $stack5 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_ARRAY>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:511: $stack93 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:120: if ctxt != null

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:424: t = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _currToken>

com.fasterxml.jackson.dataformat.xml.stream.XmlParserTest:191: $stack53 = virtualinvoke xp.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean isExpectedStartArrayToken()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:432: $stack8 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.JsonToken _nextToken>

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:141: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parent>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:557: $stack57 = virtualinvoke $stack56.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext getParent()>() com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:514: $stack75 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:588: $stack28 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:432: $stack7 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken END_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:425: $stack2 = <com.fasterxml.jackson.core.JsonToken: com.fasterxml.jackson.core.JsonToken START_OBJECT>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:577: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:589: if $stack32 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:1024: return 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:1023: if $i0 <= 32

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:576: $stack8 = virtualinvoke $stack7.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String getText()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:588: $stack29 = virtualinvoke $stack28.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inArray()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:514: $stack76 = virtualinvoke $stack75.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inArray()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:500: t#4 = virtualinvoke $stack4.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:589: $stack32 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _isEmpty(java.lang.String)>($stack31)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:518: t#4 = virtualinvoke $stack88.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:589: $stack31 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: java.lang.String _currText>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:196: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _textValue>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:584: virtualinvoke $stack27.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: void skipEndElement()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:508: $stack74 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:506: if t#4 != 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:180: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _repeatElement>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:188: $stack2 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:314: if $stack10 >= $stack9

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:309: tableswitch($stack3) { case 1:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:322: $stack13 = interfaceinvoke $stack12.<org.codehaus.stax2.XMLStreamReader2: int getEventType()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:322: if $stack13 != 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:324: if $stack22 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:322: $stack22 = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:322: $stack22 = 1

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:384: if text != null

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:372: $stack4 = interfaceinvoke $stack3.<org.codehaus.stax2.XMLStreamReader2: boolean isEmptyElement()>() com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:380: text = null com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:382: $stack6 = interfaceinvoke $stack5.<org.codehaus.stax2.XMLStreamReader2: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:372: if $stack4 == 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:382: tableswitch($stack6) { case 1:

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:183: return $stack2

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:425: $stack6 = interfaceinvoke $stack5.<org.codehaus.stax2.XMLStreamReader2: int next()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:359: $stack37 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: int _skipUntilTag()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:384: return $stack15

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:384: $stack15 = ""

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:468: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: com.fasterxml.jackson.dataformat.xml.deser.ElementWrapper _currentWrapper>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:335: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: boolean _mixedText> = 0

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:400: $stack14 = text

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:409: text = $stack8

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:408: if text != null

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:440: return $stack4

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:407: $stack8 = specialinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _getText(org.codehaus.stax2.XMLStreamReader2)>($stack7)

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:440: $stack4 = interfaceinvoke r.<org.codehaus.stax2.XMLStreamReader2: java.lang.String getText()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:400: return $stack14

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:336: this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: java.lang.String _textValue> = $stack11

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:334: if $stack11 == null

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:347: $stack4 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream: boolean _mixedText>

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:347: if $stack4 == 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:1023: $stack6 = virtualinvoke str.<java.lang.String: char charAt(int)>(i)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:1020: if str != null com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:1022: i = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:-1: $i0 = (int) $stack6

com.fasterxml.jackson.dataformat.xml.deser.XmlTokenStream:429: return $stack6

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: $stack53 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext _parsingContext>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:545: $stack52 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: boolean _mayBeLeaf>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: $stack54 = virtualinvoke $stack53.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: boolean inArray()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:558: $stack59 = virtualinvoke $stack58.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: java.util.Set getNamesToWrap()>()

com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext:180: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.XmlReadContext: java.util.Set _namesToWrap>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:556: if $stack54 == 0