com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:62: $stack10 = virtualinvoke $stack7.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.String writeValueAsString(java.lang.Object)>($stack8)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo:26: specialinvoke this.<java.lang.Object: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.SerializationConfig _serializationConfig> = $stack7

com.fasterxml.jackson.dataformat.xml.XmlMapper:80: this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule _xmlModule> = module

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke this.<com.fasterxml.jackson.databind.ObjectMapper: void <init>(com.fasterxml.jackson.core.JsonFactory,com.fasterxml.jackson.databind.ser.DefaultSerializerProvider,com.fasterxml.jackson.databind.deser.DefaultDeserializationContext)>(xmlFactory, $u1, null)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:61: specialinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: void <init>(int,int)>(2, 3) com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:61: $stack8 = new com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:59: $stack7 = new com.fasterxml.jackson.dataformat.xml.XmlMapper com.fasterxml.jackson.dataformat.xml.XmlMapper:49: $stack1 = new com.fasterxml.jackson.dataformat.xml.XmlFactory

com.fasterxml.jackson.dataformat.xml.XmlMapper:67: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>(com.fasterxml.jackson.dataformat.xml.XmlFactory,com.fasterxml.jackson.dataformat.xml.JacksonXmlModule)>(xmlFactory, $stack2)

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack7 = virtualinvoke $stack6.<com.fasterxml.jackson.databind.SerializationConfig: com.fasterxml.jackson.databind.SerializationConfig withDefaultPrettyPrinter(com.fasterxml.jackson.core.PrettyPrinter)>($stack5)

com.fasterxml.jackson.dataformat.xml.XmlMapper:67: $stack2 = <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule DEFAULT_XML_MODULE>

com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:41: specialinvoke this.<com.fasterxml.jackson.databind.ser.DefaultSerializerProvider: void <init>()>() com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:42: this.<com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider: com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup _rootNameLookup> = rootNames

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: $u1 = new com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider

com.fasterxml.jackson.dataformat.xml.XmlFactory:123: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory> = xmlIn com.fasterxml.jackson.dataformat.xml.XmlFactory:124: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLOutputFactory _xmlOutputFactory> = xmlOut

com.fasterxml.jackson.dataformat.xml.XmlFactory:119: if xmlOut != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:111: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: java.lang.String _cfgNameForTextElement> = nameForTextElem

com.fasterxml.jackson.dataformat.xml.XmlFactory:109: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlParserFeatures> = xpFeatures com.fasterxml.jackson.dataformat.xml.XmlFactory:110: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlGeneratorFeatures> = xgFeatures

com.fasterxml.jackson.dataformat.xml.XmlFactory:108: specialinvoke this.<com.fasterxml.jackson.core.JsonFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec)>(oc)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:59: specialinvoke $stack7.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke $u1.<com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider: void <init>(com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup)>($u0)

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: $u0 = new com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:30: specialinvoke this.<java.lang.Object: void <init>()>() com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: this.<com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup: com.fasterxml.jackson.databind.util.LRUMap _rootNames> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>(com.fasterxml.jackson.dataformat.xml.XmlFactory)>($stack1)

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,int,int,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory,java.lang.String)>(oc, $stack5, $stack4, xmlIn, xmlOut, null)

com.fasterxml.jackson.dataformat.xml.XmlFactory:145: virtualinvoke xmlIn.<javax.xml.stream.XMLInputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isCoalescing", $stack4) com.fasterxml.jackson.dataformat.xml.XmlFactory:143: virtualinvoke xmlOut.<javax.xml.stream.XMLOutputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isRepairingNamespaces", $stack3) com.fasterxml.jackson.dataformat.xml.XmlFactory:120: xmlOut = staticinvoke <javax.xml.stream.XMLOutputFactory: javax.xml.stream.XMLOutputFactory newInstance()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:113: xmlIn = $stack15

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack4 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS>

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:-1: $r0 = (com.fasterxml.jackson.databind.JsonDeserializer) $u0

com.fasterxml.jackson.dataformat.xml.deser.XmlStringDeserializer:23: specialinvoke this.<com.fasterxml.jackson.databind.deser.std.StdScalarDeserializer: void <init>(java.lang.Class)>(class "Ljava/lang/String;")

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:52: $u0 = new com.fasterxml.jackson.dataformat.xml.deser.XmlStringDeserializer

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: specialinvoke $stack0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: $stack0 = new com.fasterxml.jackson.dataformat.xml.JacksonXmlModule

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:52: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.deser.XmlStringDeserializer: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule DEFAULT_XML_MODULE> = $stack0

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:41: this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: java.lang.String _cfgNameForTextElement> = "" com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:31: this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: boolean _cfgDefaultUseWrapper> = 1

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:51: specialinvoke this.<com.fasterxml.jackson.databind.module.SimpleModule: void <init>(java.lang.String,com.fasterxml.jackson.core.Version)>("JacksonXmlModule", $stack2)

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:51: $stack2 = <com.fasterxml.jackson.dataformat.xml.PackageVersion: com.fasterxml.jackson.core.Version VERSION>

com.fasterxml.jackson.dataformat.xml.PackageVersion:13: <com.fasterxml.jackson.dataformat.xml.PackageVersion: com.fasterxml.jackson.core.Version VERSION> = $stack0

com.fasterxml.jackson.dataformat.xml.PackageVersion:13: $stack0 = staticinvoke <com.fasterxml.jackson.core.util.VersionUtil: com.fasterxml.jackson.core.Version parseVersion(java.lang.String,java.lang.String,java.lang.String)>("2.9.8-SNAPSHOT", "com.fasterxml.jackson.dataformat", "jackson-dataformat-xml")

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:53: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: com.fasterxml.jackson.databind.module.SimpleModule addDeserializer(java.lang.Class,com.fasterxml.jackson.databind.JsonDeserializer)>(class "Ljava/lang/String;", $r0)

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:55: return

com.fasterxml.jackson.dataformat.xml.deser.XmlStringDeserializer:23: return

com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter:106: specialinvoke this.<java.lang.Object: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:37: $stack1 = new com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter com.fasterxml.jackson.dataformat.xml.XmlMapper:37: specialinvoke $stack1.<com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:37: <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter DEFAULT_XML_PRETTY_PRINTER> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter DEFAULT_XML_PRETTY_PRINTER>

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: specialinvoke $stack1.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:64: $stack6 = virtualinvoke f.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: boolean enabledByDefault()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: $stack0 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:68: return flags

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:65: flags = flags | $stack9

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:62: flags = 0

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:64: if $stack6 == 0 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:77: return $stack1

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:65: $stack9 = virtualinvoke f.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int getMask()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:76: return $stack1 com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:77: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int _mask>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:76: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: boolean _defaultState>

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:73: $stack5 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int ordinal()>()

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:72: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: boolean _defaultState> = defaultState

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:71: specialinvoke this.<java.lang.Enum: void <init>(java.lang.String,int)>(l1, l2)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:50: specialinvoke $stack0.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: void <init>(java.lang.String,int,boolean)>("EMPTY_ELEMENT_AS_NULL", 0, 1) com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:50: $stack0 = new com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:73: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int _mask> = $stack6

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature:73: $stack6 = 1 << $stack5

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> = $stack0 com.fasterxml.jackson.dataformat.xml.XmlFactory:84: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(null, null, null) com.fasterxml.jackson.dataformat.xml.XmlFactory:49: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: $stack1 = staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:102: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:122: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void _initFactories(javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(xmlIn, xmlOut) com.fasterxml.jackson.dataformat.xml.XmlFactory:112: if xmlIn != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:145: $stack4 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:113: $stack15 = staticinvoke <javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLInputFactory newInstance()>() com.fasterxml.jackson.dataformat.xml.XmlFactory:125: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:146: return com.fasterxml.jackson.dataformat.xml.XmlFactory:143: $stack3 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlMapper:68: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack6 = this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.SerializationConfig _serializationConfig>

com.fasterxml.jackson.dataformat.xml.XmlMapper:90: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:83: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.ObjectMapper registerModule(com.fasterxml.jackson.databind.Module)>($r0)

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup: void <init>()>() com.fasterxml.jackson.dataformat.xml.XmlMapper:82: if module == null com.fasterxml.jackson.dataformat.xml.XmlMapper:-1: $r0 = (com.fasterxml.jackson.databind.Module) module

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: specialinvoke $stack1.<com.fasterxml.jackson.databind.util.LRUMap: void <init>(int,int)>(40, 200)

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: $stack1 = new com.fasterxml.jackson.databind.util.LRUMap com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:30: return

com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:43: return

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:66: $stack14 = virtualinvoke mapper2.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.String writeValueAsString(java.lang.Object)>($stack8)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:65: mapper2 = (com.fasterxml.jackson.dataformat.xml.XmlMapper) $stack12 com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo:28: this.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int y> = y0 com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo:27: this.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int x> = x0

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:97: return $stack8 com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo:29: return

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:68: $stack17 = $stack8.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int x>

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:69: $stack19 = $stack8.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int y>

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:67: p2 = (com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo) $stack15 com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:68: staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability: void assertEquals(int,int)>($stack17, $stack16)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:67: $stack15 = virtualinvoke mapper2.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.Object readValue(java.lang.String,java.lang.Class)>("<MyPojo><x>2</x><y>3</y></MyPojo>", class "Lcom/fasterxml/jackson/dataformat/xml/ser/TestJDKSerializability$MyPojo;") com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:68: $stack16 = p2.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int x>

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:84: $stack6 = virtualinvoke $stack4.<java.io.ByteArrayOutputStream: byte[] toByteArray()>()

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:80: specialinvoke $stack4.<java.io.ByteArrayOutputStream: void <init>(int)>(1000) com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:81: specialinvoke $stack5.<java.io.ObjectOutputStream: void <init>(java.io.OutputStream)>($stack4)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:80: $stack4 = new java.io.ByteArrayOutputStream

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:64: $stack11 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability: byte[] jdkSerialize(java.lang.Object)>($stack7)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:81: $stack5 = new java.io.ObjectOutputStream

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:84: return $stack6

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:90: specialinvoke $stack7.<java.io.ByteArrayInputStream: void <init>(byte[])>(raw)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:90: $stack7 = new java.io.ByteArrayInputStream

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:65: $stack12 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability: java.lang.Object jdkDeserialize(byte[])>($stack11)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:92: $stack8 = virtualinvoke $stack6.<java.io.ObjectInputStream: java.lang.Object readObject()>()

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:90: specialinvoke $stack6.<java.io.ObjectInputStream: void <init>(java.io.InputStream)>($stack7)

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:90: $stack6 = new java.io.ObjectInputStream

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:69: $stack18 = p2.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int y>

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo:32: this.<com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability$MyPojo: int y> = y

com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability:69: staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.TestJDKSerializability: void assertEquals(int,int)>($stack19, $stack18)