org.apache.commons.csv.CSVParserTest:87: org.apache.commons.csv.CSVParserTest:87: staticinvoke <org.junit.Assert: void assertTrue(boolean)>($stack24)

org.apache.commons.csv.CSVParser:219: result = $stack32

org.apache.commons.csv.CSVRecord:52: this.<org.apache.commons.csv.CSVRecord: java.util.Map mapping> = mapping org.apache.commons.csv.CSVRecord:53: this.<org.apache.commons.csv.CSVRecord: java.lang.String comment> = comment

org.apache.commons.csv.CSVRecord:51: this.<org.apache.commons.csv.CSVRecord: java.lang.String[] values> = $stack6

org.apache.commons.csv.CSVRecord:50: this.<org.apache.commons.csv.CSVRecord: long recordNumber> = recordNumber

org.apache.commons.csv.CSVRecord:49: specialinvoke this.<java.lang.Object: void <init>()>()

org.apache.commons.csv.CSVParser:219: $stack35 = interfaceinvoke $stack33.<java.util.List: int size()>()

org.apache.commons.csv.CSVParser:219: $stack32 = new org.apache.commons.csv.CSVRecord

org.apache.commons.csv.CSVParser:217: this.<org.apache.commons.csv.CSVParser: long recordNumber> = $stack30

org.apache.commons.csv.CSVParser:216: if $stack28 != 0

org.apache.commons.csv.CSVParser:185: interfaceinvoke $stack4.<java.util.List: void clear()>()

org.apache.commons.csv.CSVParser:123: this.<org.apache.commons.csv.CSVParser: java.util.Map headerMap> = $stack7

org.apache.commons.csv.CSVParser:122: this.<org.apache.commons.csv.CSVParser: org.apache.commons.csv.Lexer lexer> = $stack5

org.apache.commons.csv.CSVParser:93: this.<org.apache.commons.csv.CSVParser: org.apache.commons.csv.Token reusableToken> = $stack4

org.apache.commons.csv.CSVParser:92: this.<org.apache.commons.csv.CSVParser: java.util.List record> = $stack3

org.apache.commons.csv.CSVParser:121: specialinvoke this.<java.lang.Object: void <init>()>()

org.apache.commons.csv.CSVParserTest:84: $stack4 = new org.apache.commons.csv.CSVParser

org.apache.commons.csv.CSVParser:219: specialinvoke $stack32.<org.apache.commons.csv.CSVRecord: void <init>(java.lang.String[],java.util.Map,java.lang.String,long)>($stack40, $stack39, $stack31, $stack38)

org.apache.commons.csv.CSVParser:218: $stack31 = null

org.apache.commons.csv.CSVParser:219: $stack39 = this.<org.apache.commons.csv.CSVParser: java.util.Map headerMap>

org.apache.commons.csv.CSVRecord:51: $stack6 = values

org.apache.commons.csv.CSVParser:219: $stack38 = this.<org.apache.commons.csv.CSVParser: long recordNumber>

org.apache.commons.csv.CSVParser:237: $stack4 = virtualinvoke this.<org.apache.commons.csv.CSVParser: org.apache.commons.csv.CSVRecord nextRecord()>()

org.apache.commons.csv.CSVParser:219: $stack33 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:217: $stack30 = $stack29 + 1L

org.apache.commons.csv.CSVParser:216: $stack28 = interfaceinvoke $stack27.<java.util.List: boolean isEmpty()>()

org.apache.commons.csv.CSVParser:185: $stack4 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParserTest:84: specialinvoke $stack4.<org.apache.commons.csv.CSVParser: void <init>(java.io.Reader,org.apache.commons.csv.CSVFormat)>($stack5, $stack8)

org.apache.commons.csv.CSVParser:269: return hdrMap

org.apache.commons.csv.Lexer:58: this.<org.apache.commons.csv.Lexer: org.apache.commons.csv.CSVFormat format> = format

org.apache.commons.csv.Lexer:65: this.<org.apache.commons.csv.Lexer: boolean ignoreEmptyLines> = $stack11 org.apache.commons.csv.Lexer:64: this.<org.apache.commons.csv.Lexer: boolean ignoreSurroundingSpaces> = $stack10

org.apache.commons.csv.Lexer:63: this.<org.apache.commons.csv.Lexer: char commmentStart> = $stack9 org.apache.commons.csv.Lexer:61: this.<org.apache.commons.csv.Lexer: char escape> = $stack5 org.apache.commons.csv.Lexer:62: this.<org.apache.commons.csv.Lexer: char quoteChar> = $stack7

org.apache.commons.csv.Lexer:60: this.<org.apache.commons.csv.Lexer: char delimiter> = $stack3

org.apache.commons.csv.Lexer:59: this.<org.apache.commons.csv.Lexer: org.apache.commons.csv.ExtendedBufferedReader in> = in

org.apache.commons.csv.Lexer:57: specialinvoke this.<java.lang.Object: void <init>()>()

org.apache.commons.csv.CSVParser:122: $stack5 = new org.apache.commons.csv.CSVLexer

org.apache.commons.csv.CSVParser:93: $stack4 = new org.apache.commons.csv.Token

org.apache.commons.csv.Token:29: specialinvoke this.<java.lang.Object: void <init>()>() org.apache.commons.csv.Token:52: this.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack1 org.apache.commons.csv.Token:55: this.<org.apache.commons.csv.Token: java.lang.StringBuilder content> = $stack2

org.apache.commons.csv.CSVParser:92: specialinvoke $stack3.<java.util.ArrayList: void <init>()>()

org.apache.commons.csv.CSVParser:92: $stack3 = new java.util.ArrayList

org.apache.commons.csv.ExtendedBufferedReader:49: specialinvoke this.<java.io.BufferedReader: void <init>(java.io.Reader)>(reader)

org.apache.commons.csv.CSVParser:122: specialinvoke $stack6.<org.apache.commons.csv.ExtendedBufferedReader: void <init>(java.io.Reader)>(input)

org.apache.commons.csv.CSVParser:122: $stack6 = new org.apache.commons.csv.ExtendedBufferedReader org.apache.commons.csv.CSVParserTest:84: specialinvoke $stack5.<java.io.StringReader: void <init>(java.lang.String)>("a,b,c,dn a , b , 1 2 n"foo baar", b,n "foon,,n"",,n""",d,en")

org.apache.commons.csv.CSVParserTest:84: $stack5 = new java.io.StringReader

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:329: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: boolean ignoreSurroundingSpaces> = ignoreSurroundingSpaces

org.apache.commons.csv.CSVParserTest:84: $stack7 = virtualinvoke $stack6.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: org.apache.commons.csv.CSVFormat$CSVFormatBuilder withIgnoreSurroundingSpaces(boolean)>(1) org.apache.commons.csv.CSVParserTest:84: $stack6 = staticinvoke <org.apache.commons.csv.CSVFormat: org.apache.commons.csv.CSVFormat$CSVFormatBuilder newBuilder()>()

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:330: return this

org.apache.commons.csv.Constants:36: <org.apache.commons.csv.Constants: java.lang.Character DOUBLE_QUOTE_CHAR> = $stack0

org.apache.commons.csv.Constants:36: $stack0 = staticinvoke <java.lang.Character: java.lang.Character valueOf(char)>(34)

org.apache.commons.csv.CSVFormat:442: $stack1 = <org.apache.commons.csv.Constants: java.lang.Character DOUBLE_QUOTE_CHAR>

org.apache.commons.csv.CSVFormat:527: $stack12 = staticinvoke <org.apache.commons.csv.CSVFormat: org.apache.commons.csv.CSVFormat$CSVFormatBuilder newBuilder()>()

org.apache.commons.csv.CSVFormat:442: specialinvoke $stack0.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: void <init>(char,java.lang.Character,org.apache.commons.csv.Quote,java.lang.Character,java.lang.Character,boolean,boolean,java.lang.String,java.lang.String,java.lang.String[])>(44, $stack1, null, null, null, 0, 1, "rn", "", null)

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:120: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: boolean ignoreEmptyLines> = ignoreEmptyLines org.apache.commons.csv.CSVFormat$CSVFormatBuilder:121: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.String recordSeparator> = recordSeparator org.apache.commons.csv.CSVFormat$CSVFormatBuilder:122: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.String nullToString> = nullToString org.apache.commons.csv.CSVFormat$CSVFormatBuilder:116: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: org.apache.commons.csv.Quote quotePolicy> = quotePolicy org.apache.commons.csv.CSVFormat$CSVFormatBuilder:123: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.String[] header> = header org.apache.commons.csv.CSVFormat$CSVFormatBuilder:114: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: char delimiter> = delimiter org.apache.commons.csv.CSVFormat$CSVFormatBuilder:117: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character commentStart> = commentStart org.apache.commons.csv.CSVFormat$CSVFormatBuilder:118: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character escape> = escape org.apache.commons.csv.CSVFormat$CSVFormatBuilder:115: this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character quoteChar> = quoteChar

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack11 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: char delimiter>

org.apache.commons.csv.CSVParserTest:84: $stack8 = virtualinvoke $stack7.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: org.apache.commons.csv.CSVFormat build()>()

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack5 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: boolean ignoreEmptyLines> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack4 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.String recordSeparator> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack3 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.String nullToString> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack9 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: org.apache.commons.csv.Quote quotePolicy> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack2 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.String[] header> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack8 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character commentStart> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack7 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character escape> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack10 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: java.lang.Character quoteChar> org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack6 = this.<org.apache.commons.csv.CSVFormat$CSVFormatBuilder: boolean ignoreSurroundingSpaces>

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: return $stack1

org.apache.commons.csv.CSVFormat:615: this.<org.apache.commons.csv.CSVFormat: java.lang.String[] header> = $stack13

org.apache.commons.csv.CSVFormat:612: this.<org.apache.commons.csv.CSVFormat: boolean ignoreEmptyLines> = ignoreEmptyLines org.apache.commons.csv.CSVFormat:613: this.<org.apache.commons.csv.CSVFormat: java.lang.String recordSeparator> = recordSeparator org.apache.commons.csv.CSVFormat:614: this.<org.apache.commons.csv.CSVFormat: java.lang.String nullToString> = nullToString org.apache.commons.csv.CSVFormat:608: this.<org.apache.commons.csv.CSVFormat: org.apache.commons.csv.Quote quotePolicy> = quotePolicy org.apache.commons.csv.CSVFormat:606: this.<org.apache.commons.csv.CSVFormat: char delimiter> = delimiter org.apache.commons.csv.CSVFormat:609: this.<org.apache.commons.csv.CSVFormat: java.lang.Character commentStart> = commentStart org.apache.commons.csv.CSVFormat:610: this.<org.apache.commons.csv.CSVFormat: java.lang.Character escape> = escape org.apache.commons.csv.CSVFormat:607: this.<org.apache.commons.csv.CSVFormat: java.lang.Character quoteChar> = quoteChar org.apache.commons.csv.CSVFormat:611: this.<org.apache.commons.csv.CSVFormat: boolean ignoreSurroundingSpaces> = ignoreSurroundingSpaces

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: $stack1 = new org.apache.commons.csv.CSVFormat org.apache.commons.csv.CSVFormat:602: specialinvoke this.<java.lang.Object: void <init>()>()

org.apache.commons.csv.CSVFormat$CSVFormatBuilder:148: specialinvoke $stack1.<org.apache.commons.csv.CSVFormat: void <init>(char,java.lang.Character,org.apache.commons.csv.Quote,java.lang.Character,java.lang.Character,boolean,boolean,java.lang.String,java.lang.String,java.lang.String[])>($stack11, $stack10, $stack9, $stack8, $stack7, $stack6, $stack5, $stack4, $stack3, $stack2)

org.apache.commons.csv.CSVFormat:615: $stack13 = null

org.apache.commons.csv.CSVFormat:615: if header != null org.apache.commons.csv.CSVFormat:616: return

org.apache.commons.csv.CSVFormat:710: $stack1 = this.<org.apache.commons.csv.CSVFormat: char delimiter>

org.apache.commons.csv.Lexer:60: $stack3 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: char getDelimiter()>()

org.apache.commons.csv.CSVLexer:37: specialinvoke this.<org.apache.commons.csv.Lexer: void <init>(org.apache.commons.csv.CSVFormat,org.apache.commons.csv.ExtendedBufferedReader)>(format, in)

org.apache.commons.csv.CSVFormat:761: $stack1 = this.<org.apache.commons.csv.CSVFormat: java.lang.Character quoteChar>

org.apache.commons.csv.Lexer:62: $stack6 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: java.lang.Character getQuoteChar()>()

org.apache.commons.csv.CSVFormat:701: $stack1 = this.<org.apache.commons.csv.CSVFormat: java.lang.Character commentStart>

org.apache.commons.csv.Lexer:63: $stack8 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: java.lang.Character getCommentStart()>()

org.apache.commons.csv.CSVFormat:719: $stack1 = this.<org.apache.commons.csv.CSVFormat: java.lang.Character escape>

org.apache.commons.csv.Lexer:61: $stack4 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: java.lang.Character getEscape()>()

org.apache.commons.csv.CSVFormat:743: $stack1 = this.<org.apache.commons.csv.CSVFormat: boolean ignoreSurroundingSpaces>

org.apache.commons.csv.Lexer:64: $stack10 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: boolean getIgnoreSurroundingSpaces()>()

org.apache.commons.csv.CSVFormat:733: $stack1 = this.<org.apache.commons.csv.CSVFormat: boolean ignoreEmptyLines>

org.apache.commons.csv.Lexer:65: $stack11 = virtualinvoke format.<org.apache.commons.csv.CSVFormat: boolean getIgnoreEmptyLines()>()

org.apache.commons.csv.CSVParser:122: specialinvoke $stack5.<org.apache.commons.csv.CSVLexer: void <init>(org.apache.commons.csv.CSVFormat,org.apache.commons.csv.ExtendedBufferedReader)>(format, $stack6)

org.apache.commons.csv.CSVParser:93: specialinvoke $stack4.<org.apache.commons.csv.Token: void <init>()>()

org.apache.commons.csv.Token:55: specialinvoke $stack2.<java.lang.StringBuilder: void <init>(int)>(50)

org.apache.commons.csv.Token:55: $stack2 = new java.lang.StringBuilder

org.apache.commons.csv.Token:52: $stack1 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.CSVParser:123: $stack7 = specialinvoke this.<org.apache.commons.csv.CSVParser: java.util.Map initializeHeader(org.apache.commons.csv.CSVFormat)>(format)

org.apache.commons.csv.CSVFormat:733: return $stack1 org.apache.commons.csv.CSVFormat:743: return $stack1

org.apache.commons.csv.Lexer:69: return $stack2

org.apache.commons.csv.CSVFormat:710: return $stack1

org.apache.commons.csv.ExtendedBufferedReader:40: this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar> = $i0

org.apache.commons.csv.CSVParser:124: return

org.apache.commons.csv.CSVParser:247: hdrMap = null

org.apache.commons.csv.CSVParser:195: interfaceinvoke $stack68.<java.util.List: boolean add(java.lang.Object)>($stack69)

org.apache.commons.csv.CSVParser:190: tableswitch($stack13) { case 1:

org.apache.commons.csv.CSVParser:195: $stack69 = virtualinvoke $stack67.<java.lang.StringBuilder: java.lang.String toString()>()

org.apache.commons.csv.CSVParser:195: $stack68 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParserTest:85: $stack9 = virtualinvoke $stack4.<org.apache.commons.csv.CSVParser: java.util.List getRecords()>()

org.apache.commons.csv.Token$Type:36: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID> = $stack0

org.apache.commons.csv.Token$Type:34: specialinvoke this.<java.lang.Enum: void <init>(java.lang.String,int)>(l1, l2)

org.apache.commons.csv.Token$Type:36: $stack0 = new org.apache.commons.csv.Token$Type

org.apache.commons.csv.Token:55: return

org.apache.commons.csv.Token$Type:36: specialinvoke $stack0.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("INVALID", 0) org.apache.commons.csv.Token$Type:39: specialinvoke $stack1.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("TOKEN", 1) org.apache.commons.csv.Token$Type:42: specialinvoke $stack2.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("EOF", 2) org.apache.commons.csv.Token$Type:48: specialinvoke $stack4.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("COMMENT", 4) org.apache.commons.csv.Token$Type:45: specialinvoke $stack3.<org.apache.commons.csv.Token$Type: void <init>(java.lang.String,int)>("EORECORD", 3) org.apache.commons.csv.Token$Type:39: $stack1 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:45: $stack3 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:48: $stack4 = new org.apache.commons.csv.Token$Type org.apache.commons.csv.Token$Type:42: $stack2 = new org.apache.commons.csv.Token$Type

org.apache.commons.csv.Token$Type:34: return

org.apache.commons.csv.Token:62: $stack2 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.CSVParser:188: virtualinvoke $stack5.<org.apache.commons.csv.Token: void reset()>()

org.apache.commons.csv.CSVLexer:96: $stack16 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.CSVParser:189: virtualinvoke $stack7.<org.apache.commons.csv.Lexer: org.apache.commons.csv.Token nextToken(org.apache.commons.csv.Token)>($stack6)

org.apache.commons.csv.Token$Type:34: $stack6 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type INVALID>

org.apache.commons.csv.Token$Type:39: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN> = $stack1

org.apache.commons.csv.CSVLexer:227: $stack45 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN> org.apache.commons.csv.Token$Type:34: $stack7 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN>

org.apache.commons.csv.CSVLexer:115: specialinvoke this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.Token parseEncapsulatedToken(org.apache.commons.csv.Token)>(token)

org.apache.commons.csv.CSVLexer:113: if $stack20 == 0

org.apache.commons.csv.CSVLexer:160: $stack29 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type TOKEN>

org.apache.commons.csv.CSVLexer:124: specialinvoke this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.Token parseSimpleToken(org.apache.commons.csv.Token,int)>(token, c)

org.apache.commons.csv.CSVLexer:116: if $stack21 == 0

org.apache.commons.csv.Token$Type:42: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EOF> = $stack2

org.apache.commons.csv.Token$Type:34: $stack8 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EOF>

org.apache.commons.csv.Token$Type:45: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD> = $stack3

org.apache.commons.csv.CSVLexer:153: $stack35 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD> org.apache.commons.csv.Token$Type:34: $stack9 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD> org.apache.commons.csv.CSVLexer:112: $stack26 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type EORECORD>

org.apache.commons.csv.Token$Type:48: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type COMMENT> = $stack4

org.apache.commons.csv.Token$Type:34: $stack10 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type COMMENT>

org.apache.commons.csv.Token$Type:34: <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type[] $VALUES> = $stack5

org.apache.commons.csv.Token$Type:34: $stack5[1] = $stack7 org.apache.commons.csv.Token$Type:34: $stack5[0] = $stack6 org.apache.commons.csv.Token$Type:34: $stack5[3] = $stack9 org.apache.commons.csv.Token$Type:34: $stack5[4] = $stack10 org.apache.commons.csv.Token$Type:34: $stack5 = newarray (org.apache.commons.csv.Token$Type)[5] org.apache.commons.csv.Token$Type:34: $stack5[2] = $stack8

org.apache.commons.csv.Token$Type:34: $stack0 = <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type[] $VALUES>

org.apache.commons.csv.CSVParser$2:190: $stack1 = staticinvoke <org.apache.commons.csv.Token$Type: org.apache.commons.csv.Token$Type[] values()>()

org.apache.commons.csv.Token:61: $stack1 = this.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVLexer:221: virtualinvoke $stack49.<java.lang.StringBuilder: java.lang.StringBuilder append(char)>($stack48)

org.apache.commons.csv.Token:61: virtualinvoke $stack1.<java.lang.StringBuilder: void setLength(int)>(0)

org.apache.commons.csv.CSVLexer:249: virtualinvoke $stack13.<java.lang.StringBuilder: java.lang.StringBuilder append(char)>($stack12)

org.apache.commons.csv.CSVLexer:171: virtualinvoke $stack9.<java.lang.StringBuilder: java.lang.StringBuilder append(char)>($stack8)

org.apache.commons.csv.CSVLexer:218: if $stack26 == 0

org.apache.commons.csv.CSVLexer:221: $stack48 = (char) $stack47

org.apache.commons.csv.CSVLexer:221: $stack49 = tkn.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVLexer:249: $stack13 = tkn.<org.apache.commons.csv.Token: java.lang.StringBuilder content> org.apache.commons.csv.CSVLexer:249: $stack12 = (char) $stack8

org.apache.commons.csv.CSVLexer:243: if $stack11 == 0

org.apache.commons.csv.CSVLexer:171: $stack9 = tkn.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVLexer:171: $stack8 = (char) c

org.apache.commons.csv.CSVLexer:162: if $stack7 == 0

org.apache.commons.csv.ExtendedBufferedReader:50: return org.apache.commons.csv.ExtendedBufferedReader:-1: $i0 = (int) -2

org.apache.commons.csv.ExtendedBufferedReader:71: $stack1 = this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar>

org.apache.commons.csv.ExtendedBufferedReader:58: this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar> = $stack2 org.apache.commons.csv.CSVLexer:55: lastChar = virtualinvoke $stack6.<org.apache.commons.csv.ExtendedBufferedReader: int getLastChar()>()

org.apache.commons.csv.CSVLexer:58: $stack9 = virtualinvoke $stack8.<org.apache.commons.csv.ExtendedBufferedReader: int read()>()

org.apache.commons.csv.ExtendedBufferedReader:54: $stack2 = specialinvoke this.<java.io.BufferedReader: int read()>()

org.apache.commons.csv.CSVLexer:208: $stack8 = virtualinvoke $stack7.<org.apache.commons.csv.ExtendedBufferedReader: int read()>() org.apache.commons.csv.CSVLexer:220: $stack47 = virtualinvoke $stack46.<org.apache.commons.csv.ExtendedBufferedReader: int read()>() org.apache.commons.csv.CSVLexer:225: $stack28 = virtualinvoke $stack27.<org.apache.commons.csv.ExtendedBufferedReader: int read()>() org.apache.commons.csv.CSVLexer:172: c = virtualinvoke $stack11.<org.apache.commons.csv.ExtendedBufferedReader: int read()>() org.apache.commons.csv.CSVLexer:100: $stack32 = virtualinvoke $stack31.<org.apache.commons.csv.ExtendedBufferedReader: int read()>()

org.apache.commons.csv.CSVLexer:38: return

org.apache.commons.csv.Lexer:61: $stack5 = specialinvoke this.<org.apache.commons.csv.Lexer: char mapNullToDisabled(java.lang.Character)>($stack4) org.apache.commons.csv.Lexer:62: $stack7 = specialinvoke this.<org.apache.commons.csv.Lexer: char mapNullToDisabled(java.lang.Character)>($stack6) org.apache.commons.csv.Lexer:63: $stack9 = specialinvoke this.<org.apache.commons.csv.Lexer: char mapNullToDisabled(java.lang.Character)>($stack8)

org.apache.commons.csv.Lexer:69: $stack2 = virtualinvoke c.<java.lang.Character: char charValue()>() org.apache.commons.csv.Lexer:69: $stack2 = 65534

org.apache.commons.csv.Lexer:66: return

org.apache.commons.csv.CSVLexer:208: $stack7 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.CSVLexer:58: $stack8 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.CSVLexer:172: $stack11 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.CSVLexer:220: $stack46 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.CSVLexer:218: $stack24 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in> org.apache.commons.csv.CSVLexer:100: $stack31 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.CSVLexer:225: $stack27 = this.<org.apache.commons.csv.CSVLexer: org.apache.commons.csv.ExtendedBufferedReader in>

org.apache.commons.csv.Lexer:167: $stack2 = this.<org.apache.commons.csv.Lexer: char delimiter>

org.apache.commons.csv.CSVLexer:226: $stack29 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isDelimiter(int)>($stack28) org.apache.commons.csv.CSVLexer:159: $stack6 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isDelimiter(int)>(c) org.apache.commons.csv.CSVLexer:106: $stack19 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isDelimiter(int)>(c)

org.apache.commons.csv.CSVFormat:719: return $stack1

org.apache.commons.csv.Lexer:69: if c != null

org.apache.commons.csv.CSVFormat:701: return $stack1 org.apache.commons.csv.CSVFormat:761: return $stack1

org.apache.commons.csv.Lexer:171: $stack2 = this.<org.apache.commons.csv.Lexer: char escape>

org.apache.commons.csv.CSVLexer:162: $stack7 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEscape(int)>(c)

org.apache.commons.csv.Lexer:175: $stack2 = this.<org.apache.commons.csv.Lexer: char quoteChar>

org.apache.commons.csv.CSVLexer:218: $stack26 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isQuoteChar(int)>($stack25) org.apache.commons.csv.CSVLexer:113: $stack20 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isQuoteChar(int)>(c)

org.apache.commons.csv.CSVLexer:98: $stack18 = this.<org.apache.commons.csv.CSVLexer: boolean ignoreSurroundingSpaces>

org.apache.commons.csv.CSVParser:238: interfaceinvoke $stack3.<java.util.List: boolean add(java.lang.Object)>($stack4)

org.apache.commons.csv.CSVParser:237: if $stack4 == null

org.apache.commons.csv.CSVParser:221: return result

org.apache.commons.csv.CSVParser:235: specialinvoke $stack3.<java.util.ArrayList: void <init>()>()

org.apache.commons.csv.CSVParser:235: $stack3 = new java.util.ArrayList

org.apache.commons.csv.CSVParser:240: return $stack3

org.apache.commons.csv.CSVParser:190: $stack12 = virtualinvoke $stack10.<org.apache.commons.csv.Token$Type: int ordinal()>()

org.apache.commons.csv.CSVParser:190: $stack10 = $stack9.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type>

org.apache.commons.csv.CSVLexer:112: token.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack26

org.apache.commons.csv.CSVLexer:227: tkn.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack45

org.apache.commons.csv.CSVLexer:153: tkn.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack35

org.apache.commons.csv.CSVLexer:160: tkn.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack29

org.apache.commons.csv.CSVParser:192: interfaceinvoke $stack73.<java.util.List: boolean add(java.lang.Object)>($stack74)

org.apache.commons.csv.CSVParser:192: $stack74 = virtualinvoke $stack72.<java.lang.StringBuilder: java.lang.String toString()>()

org.apache.commons.csv.CSVParser:192: $stack73 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:192: $stack72 = $stack71.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVParser:190: $stack13 = $stack11[$stack12]

org.apache.commons.csv.CSVParser:218: if sb != null

org.apache.commons.csv.CSVParser:186: sb = null

org.apache.commons.csv.CSVParser:190: $stack11 = <org.apache.commons.csv.CSVParser$2: int[] $SwitchMap$org$apache$commonscsvToken$Type>

org.apache.commons.csv.CSVParser$2:190: <org.apache.commons.csv.CSVParser$2: int[] $SwitchMap$org$apache$commonscsvToken$Type> = $stack3

org.apache.commons.csv.CSVParser$2:190: $stack3 = newarray (int)[$stack2]

org.apache.commons.csv.CSVParser:216: $stack27 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:195: $stack67 = $stack66.<org.apache.commons.csv.Token: java.lang.StringBuilder content>

org.apache.commons.csv.CSVParser:217: $stack29 = this.<org.apache.commons.csv.CSVParser: long recordNumber>

org.apache.commons.csv.CSVParser:219: $stack36 = newarray (java.lang.String)[$stack35]

org.apache.commons.csv.CSVLexer:109: if eol == 0

org.apache.commons.csv.CSVLexer:226: if $stack29 == 0

org.apache.commons.csv.CSVLexer:152: if $stack4 == 0

org.apache.commons.csv.CSVLexer:159: if $stack6 == 0

org.apache.commons.csv.CSVParser:219: $stack34 = this.<org.apache.commons.csv.CSVParser: java.util.List record>

org.apache.commons.csv.CSVParser:219: $stack40 = (java.lang.String[]) $stack37

org.apache.commons.csv.CSVParser:219: $stack37 = interfaceinvoke $stack34.<java.util.List: java.lang.Object[] toArray(java.lang.Object[])>($stack36)

org.apache.commons.csv.Token:62: this.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type> = $stack2

org.apache.commons.csv.CSVLexer:96: $stack17 = token.<org.apache.commons.csv.Token: org.apache.commons.csv.Token$Type type>

org.apache.commons.csv.CSVLexer:88: $stack15 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isStartOfLine(int)>(lastChar)

org.apache.commons.csv.CSVLexer:82: $stack43 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>(c)

org.apache.commons.csv.CSVLexer:96: if $stack17 != $stack16

org.apache.commons.csv.CSVLexer:88: if $stack15 == 0

org.apache.commons.csv.CSVLexer:82: if $stack43 == 0

org.apache.commons.csv.Lexer:156: return $stack2

org.apache.commons.csv.CSVLexer:116: $stack21 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>(c)

org.apache.commons.csv.CSVLexer:63: eol = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean readEndOfLine(int)>($stack9)

org.apache.commons.csv.CSVLexer:58: c = $stack9

org.apache.commons.csv.ExtendedBufferedReader:59: return $stack5

org.apache.commons.csv.ExtendedBufferedReader:59: $stack5 = this.<org.apache.commons.csv.ExtendedBufferedReader: int lastChar>

org.apache.commons.csv.Lexer:163: return $stack2

org.apache.commons.csv.CSVLexer:243: $stack11 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>($stack8) org.apache.commons.csv.CSVLexer:155: $stack5 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isEndOfFile(int)>(c)

org.apache.commons.csv.Lexer:163: $stack2 = 0

org.apache.commons.csv.ExtendedBufferedReader:71: return $stack1

org.apache.commons.csv.Lexer:156: if c == 10

org.apache.commons.csv.Lexer:137: if c != 13

org.apache.commons.csv.Lexer:137: if c == 10

org.apache.commons.csv.CSVLexer:101: eol = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean readEndOfLine(int)>($stack32)

org.apache.commons.csv.CSVLexer:152: $stack4 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean readEndOfLine(int)>(c)

org.apache.commons.csv.CSVLexer:100: c = $stack32

org.apache.commons.csv.CSVLexer:99: if eol != 0

org.apache.commons.csv.Lexer:137: return $stack2

org.apache.commons.csv.Lexer:137: $stack2 = 0 org.apache.commons.csv.Lexer:137: $stack2 = 1

org.apache.commons.csv.CSVLexer:106: if $stack19 == 0

org.apache.commons.csv.Lexer:167: return $stack3

org.apache.commons.csv.Lexer:-1: $i0 = (int) -1

org.apache.commons.csv.Lexer:163: if c != $i0

org.apache.commons.csv.Lexer:167: $stack3 = 1 org.apache.commons.csv.Lexer:167: $stack3 = 0 org.apache.commons.csv.Lexer:156: $stack2 = 1 org.apache.commons.csv.Lexer:156: $stack2 = 0

org.apache.commons.csv.Lexer:167: if c != $i0

org.apache.commons.csv.Lexer:-1: $i0 = (int) $stack2

org.apache.commons.csv.Lexer:175: return $stack3

org.apache.commons.csv.Lexer:175: $stack3 = 0 org.apache.commons.csv.Lexer:175: $stack3 = 1

org.apache.commons.csv.Lexer:175: if c != $i0

org.apache.commons.csv.ExtendedBufferedReader:142: return $stack2

org.apache.commons.csv.CSVLexer:218: $stack25 = virtualinvoke $stack24.<org.apache.commons.csv.ExtendedBufferedReader: int lookAhead()>()

org.apache.commons.csv.ExtendedBufferedReader:139: $stack2 = specialinvoke this.<java.io.BufferedReader: int read()>()

org.apache.commons.csv.Lexer:171: return $stack3

org.apache.commons.csv.CSVLexer:155: if $stack5 == 0

org.apache.commons.csv.Lexer:171: $stack3 = 0

org.apache.commons.csv.Lexer:171: if c != $i0

org.apache.commons.csv.Token$Type:34: return $stack2

org.apache.commons.csv.Token$Type:34: $stack2 = (org.apache.commons.csv.Token$Type[]) $stack1

org.apache.commons.csv.Token$Type:34: $stack1 = virtualinvoke $stack0.<java.lang.Object: java.lang.Object clone()>()

org.apache.commons.csv.CSVParser$2:190: $stack2 = lengthof $stack1

org.apache.commons.csv.CSVRecord:51: if values == null org.apache.commons.csv.CSVRecord:54: return

org.apache.commons.csv.CSVLexer:99: $stack28 = virtualinvoke this.<org.apache.commons.csv.CSVLexer: boolean isWhitespace(int)>(c)

org.apache.commons.csv.CSVLexer:101:

org.apache.commons.csv.CSVLexer:98: if $stack18 == 0

org.apache.commons.csv.CSVLexer:99: if $stack28 == 0

org.apache.commons.csv.Lexer:146: return $stack6

org.apache.commons.csv.Lexer:146: $stack6 = 1

org.apache.commons.csv.ExtendedBufferedReader:138: specialinvoke this.<java.io.BufferedReader: void mark(int)>(1)

org.apache.commons.csv.CSVParserTest:87: $stack15 = interfaceinvoke $stack9.<java.util.List: int size()>()

org.apache.commons.csv.CSVParserTest:86: $stack13 = interfaceinvoke $stack9.<java.util.List: int size()>()

org.apache.commons.csv.CSVParserTest:87: if $stack15 <= 0

org.apache.commons.csv.CSVParserTest:87: $stack24 = 1