com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke this.<com.fasterxml.jackson.databind.ObjectMapper: void <init>(com.fasterxml.jackson.core.JsonFactory,com.fasterxml.jackson.databind.ser.DefaultSerializerProvider,com.fasterxml.jackson.databind.deser.DefaultDeserializationContext)>(xmlFactory, $u1, null)

com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:42: this.<com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider: com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup _rootNameLookup> = rootNames com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:41: specialinvoke this.<com.fasterxml.jackson.databind.ser.DefaultSerializerProvider: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: $u1 = new com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider

com.fasterxml.jackson.dataformat.xml.XmlMapper:67: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>(com.fasterxml.jackson.dataformat.xml.XmlFactory,com.fasterxml.jackson.dataformat.xml.JacksonXmlModule)>(xmlFactory, $stack2)

com.fasterxml.jackson.dataformat.xml.XmlFactory:119: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLInputFactory _xmlInputFactory> = xmlIn com.fasterxml.jackson.dataformat.xml.XmlFactory:120: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: javax.xml.stream.XMLOutputFactory _xmlOutputFactory> = xmlOut

com.fasterxml.jackson.dataformat.xml.XmlFactory:115: if xmlOut != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:109: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlParserFeatures> = xpFeatures com.fasterxml.jackson.dataformat.xml.XmlFactory:108: specialinvoke this.<com.fasterxml.jackson.core.JsonFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec)>(oc) com.fasterxml.jackson.dataformat.xml.XmlFactory:111: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: java.lang.String _cfgNameForTextElement> = nameForTextElem com.fasterxml.jackson.dataformat.xml.XmlFactory:110: this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: int _xmlGeneratorFeatures> = xgFeatures

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:78: $u0 = new com.fasterxml.jackson.dataformat.xml.XmlMapper com.fasterxml.jackson.dataformat.xml.XmlMapper:49: $stack1 = new com.fasterxml.jackson.dataformat.xml.XmlFactory

com.fasterxml.jackson.dataformat.xml.XmlMapper:79: $u0 = new com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: this.<com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup: com.fasterxml.jackson.databind.util.LRUMap _rootNames> = $stack1 com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:30: specialinvoke this.<java.lang.Object: void <init>()>() com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke $u1.<com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider: void <init>(com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup)>($u0)

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>(com.fasterxml.jackson.dataformat.xml.XmlFactory)>($stack1)

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,int,int,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory,java.lang.String)>(oc, $stack5, $stack4, xmlIn, xmlOut, null)

com.fasterxml.jackson.dataformat.xml.XmlFactory:113: xmlIn = staticinvoke <javax.xml.stream.XMLInputFactory: javax.xml.stream.XMLInputFactory newInstance()>() com.fasterxml.jackson.dataformat.xml.XmlFactory:141: virtualinvoke xmlIn.<javax.xml.stream.XMLInputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isCoalescing", $stack4) com.fasterxml.jackson.dataformat.xml.XmlFactory:139: virtualinvoke xmlOut.<javax.xml.stream.XMLOutputFactory: void setProperty(java.lang.String,java.lang.Object)>("javax.xml.stream.isRepairingNamespaces", $stack3) com.fasterxml.jackson.dataformat.xml.XmlFactory:116: xmlOut = staticinvoke <javax.xml.stream.XMLOutputFactory: javax.xml.stream.XMLOutputFactory newInstance()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> com.fasterxml.jackson.dataformat.xml.XmlFactory:100: $stack4 = <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS>

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:78: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.XmlMapper: void <init>()>()

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:87: $stack21 = virtualinvoke $u0.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.Object readValue(java.lang.String,java.lang.Class)>($stack20, class "Lcom/fasterxml/jackson/dataformat/xml/ser/TestSerializerCustom$Item;")

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:85: $stack20 = virtualinvoke $u0.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.String writeValueAsString(java.lang.Object)>($u6)

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.SerializationConfig _serializationConfig> = $stack7

com.fasterxml.jackson.dataformat.xml.XmlMapper:80: this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule _xmlModule> = module

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item:26: this.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item: com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo obj> = obj com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:84: $u6 = new com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item:24: specialinvoke this.<java.lang.Object: void <init>()>() com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item:25: this.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item: java.lang.String name> = name

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack7 = virtualinvoke $stack6.<com.fasterxml.jackson.databind.SerializationConfig: com.fasterxml.jackson.databind.SerializationConfig withDefaultPrettyPrinter(com.fasterxml.jackson.core.PrettyPrinter)>($stack5)

com.fasterxml.jackson.dataformat.xml.XmlMapper:67: $stack2 = <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule DEFAULT_XML_MODULE>

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.JacksonXmlModule DEFAULT_XML_MODULE> = $stack0

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:40: this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: java.lang.String _cfgNameForTextElement> = "" com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:30: this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: boolean _cfgDefaultUseWrapper> = 1

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: $stack0 = new com.fasterxml.jackson.dataformat.xml.JacksonXmlModule com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:50: specialinvoke this.<com.fasterxml.jackson.databind.module.SimpleModule: void <init>(java.lang.String,com.fasterxml.jackson.core.Version)>("JackxonXmlModule", $stack1)

com.fasterxml.jackson.dataformat.xml.XmlMapper:35: specialinvoke $stack0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: void <init>()>()

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:51: return com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:50: $stack1 = <com.fasterxml.jackson.dataformat.xml.PackageVersion: com.fasterxml.jackson.core.Version VERSION>

com.fasterxml.jackson.dataformat.xml.PackageVersion:13: <com.fasterxml.jackson.dataformat.xml.PackageVersion: com.fasterxml.jackson.core.Version VERSION> = $stack0

com.fasterxml.jackson.dataformat.xml.PackageVersion:13: $stack0 = staticinvoke <com.fasterxml.jackson.core.util.VersionUtil: com.fasterxml.jackson.core.Version parseVersion(java.lang.String,java.lang.String,java.lang.String)>("2.7.0-rc4-SNAPSHOT", "com.fasterxml.jackson.dataformat", "jackson-dataformat-xml")

com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter:106: specialinvoke this.<java.lang.Object: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:37: specialinvoke $stack1.<com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter: void <init>()>() com.fasterxml.jackson.dataformat.xml.XmlMapper:37: $stack1 = new com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter

com.fasterxml.jackson.dataformat.xml.XmlMapper:37: <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter DEFAULT_XML_PRETTY_PRINTER> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack5 = <com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.dataformat.xml.util.DefaultXmlPrettyPrinter DEFAULT_XML_PRETTY_PRINTER>

com.fasterxml.jackson.dataformat.xml.XmlMapper:49: specialinvoke $stack1.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_PARSER_FEATURE_FLAGS> = $stack0

com.fasterxml.jackson.dataformat.xml.XmlFactory:43: $stack0 = staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: specialinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void <init>(com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(null, null, null)

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:77: return flags

com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature:71: flags = 0

com.fasterxml.jackson.dataformat.xml.XmlFactory:49: $stack1 = staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.ToXmlGenerator$Feature: int collectDefaults()>()

com.fasterxml.jackson.dataformat.xml.XmlFactory:84: return com.fasterxml.jackson.dataformat.xml.XmlFactory:49: <com.fasterxml.jackson.dataformat.xml.XmlFactory: int DEFAULT_XML_GENERATOR_FEATURE_FLAGS> = $stack1

com.fasterxml.jackson.dataformat.xml.XmlFactory:102: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:118: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: void _initFactories(javax.xml.stream.XMLInputFactory,javax.xml.stream.XMLOutputFactory)>(xmlIn, xmlOut)

com.fasterxml.jackson.dataformat.xml.XmlFactory:141: $stack4 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:112: if xmlIn != null

com.fasterxml.jackson.dataformat.xml.XmlFactory:139: $stack3 = <java.lang.Boolean: java.lang.Boolean TRUE>

com.fasterxml.jackson.dataformat.xml.XmlFactory:121: return

com.fasterxml.jackson.dataformat.xml.XmlFactory:142: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:68: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:82: if module == null com.fasterxml.jackson.dataformat.xml.XmlMapper:86: $stack6 = this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.SerializationConfig _serializationConfig> com.fasterxml.jackson.dataformat.xml.XmlMapper:79: specialinvoke $u0.<com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup: void <init>()>()

com.fasterxml.jackson.dataformat.xml.XmlMapper:87: return

com.fasterxml.jackson.dataformat.xml.XmlMapper:83: virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.ObjectMapper registerModule(com.fasterxml.jackson.databind.Module)>($r0)

com.fasterxml.jackson.dataformat.xml.XmlMapper:-1: $r0 = (com.fasterxml.jackson.databind.Module) module

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: specialinvoke $stack1.<com.fasterxml.jackson.databind.util.LRUMap: void <init>(int,int)>(40, 200)

com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:30: return com.fasterxml.jackson.dataformat.xml.util.XmlRootNameLookup:28: $stack1 = new com.fasterxml.jackson.databind.util.LRUMap

com.fasterxml.jackson.dataformat.xml.ser.XmlSerializerProvider:43: return

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo:33: specialinvoke this.<java.lang.Object: void <init>()>() com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo:34: this.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo: java.lang.String name> = name com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:51: $stack13 = (com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo) $stack12 com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:51: specialinvoke $u1.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item: void <init>(java.lang.String,com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo)>($stack11, $stack13) com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:84: specialinvoke $u6.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item: void <init>(java.lang.String,com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo)>("itemName", $u5)

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:84: $u5 = new com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:51: $stack11 = virtualinvoke $stack10.<com.fasterxml.jackson.databind.JsonNode: java.lang.String asText()>()

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:38: $stack3 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer: com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item deserialize(com.fasterxml.jackson.core.JsonParser,com.fasterxml.jackson.databind.DeserializationContext)>(x0, x1)

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:84: specialinvoke $u5.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo: void <init>(java.lang.String)>("fooName") com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:51: $stack12 = virtualinvoke $stack6.<com.fasterxml.jackson.core.ObjectCodec: java.lang.Object treeToValue(com.fasterxml.jackson.core.TreeNode,java.lang.Class)>($r0, class "Lcom/fasterxml/jackson/dataformat/xml/ser/TestSerializerCustom$Foo;")

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo:35: return

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:51: $stack10 = virtualinvoke json.<com.fasterxml.jackson.databind.JsonNode: com.fasterxml.jackson.databind.JsonNode path(java.lang.String)>("name")

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item:27: return

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:87: result = (com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item) $stack21

com.fasterxml.jackson.dataformat.xml.XmlFactory:559: $stack9 = this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.core.ObjectCodec _objectCodec>

com.fasterxml.jackson.dataformat.xml.XmlFactory:429: $stack7 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.XmlFactory: com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser _createParser(java.io.Reader,com.fasterxml.jackson.core.io.IOContext)>(r, $stack5)

com.fasterxml.jackson.dataformat.xml.XmlFactory:559: specialinvoke $stack8.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: void <init>(com.fasterxml.jackson.core.io.IOContext,int,int,com.fasterxml.jackson.core.ObjectCodec,javax.xml.stream.XMLStreamReader)>(ctxt, $stack11, $stack10, $stack9, $stack7)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:169: this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.ObjectCodec _objectCodec> = codec

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:183: $stack1 = this.<com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser: com.fasterxml.jackson.core.ObjectCodec _objectCodec>

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:45: $stack6 = virtualinvoke jp.<com.fasterxml.jackson.core.JsonParser: com.fasterxml.jackson.core.ObjectCodec getCodec()>()

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:46: json = (com.fasterxml.jackson.databind.JsonNode) $stack7

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:46: $stack7 = virtualinvoke $stack6.<com.fasterxml.jackson.core.ObjectCodec: com.fasterxml.jackson.core.TreeNode readTree(com.fasterxml.jackson.core.JsonParser)>(jp)

com.fasterxml.jackson.dataformat.xml.deser.FromXmlParser:183: return $stack1

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:-1: $r0 = (com.fasterxml.jackson.core.TreeNode) $stack8

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$ItemDeserializer:47: $stack8 = virtualinvoke json.<com.fasterxml.jackson.databind.JsonNode: com.fasterxml.jackson.databind.JsonNode get(java.lang.String)>("obj")

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:89: $stack22 = result.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item: java.lang.String name>

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:90: $stack23 = result.<com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Item: com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom$Foo obj>

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:88: staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom: void assertNotNull(java.lang.Object)>(result) com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:89: staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom: void assertEquals(java.lang.String,java.lang.String)>("itemName", $stack22)

com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom:90: staticinvoke <com.fasterxml.jackson.dataformat.xml.ser.TestSerializerCustom: void assertNotNull(java.lang.Object)>($stack23)