

com.fasterxml.jackson.dataformat.xml.deser.TestStringValues:105: staticinvoke <com.fasterxml.jackson.dataformat.xml.deser.TestStringValues: void assertNotNull(java.lang.Object)>(result)

com.fasterxml.jackson.dataformat.xml.deser.TestStringValues:104: result = (com.fasterxml.jackson.dataformat.xml.deser.TestStringValues\$Issue167Bean) \$stack4

com.fasterxml.jackson.dataformat.xml.deser.TestStringValues:104: \$stack4 = virtualinvoke \$stack3.<com.fasterxml.jackson.dataformat.xml.XmlMapper: java.lang.Object readValue(java.lang.String,java.lang.Class)>("<a xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'>n<d xsi:nil='true'/>nn", class "Lcom/fasterxml/jackson/dataformat/xml/deser/TestStringValues\$Issue167Bean;")

com.fasterxml.jackson.dataformat.xml.deser.TestStringValues:104: \$stack3 = this.<com.fasterxml.jackson.dataformat.xml.deser.TestStringValues: com.fasterxml.jackson.dataformat.xml.XmlMapper MAPPER>

com.fasterxml.jackson.dataformat.xml.deser.TestStringValues:28: this.<com.fasterxml.jackson.dataformat.xml.deser.TestStringValues: com.fasterxml.jackson.dataformat.xml.XmlMapper MAPPER> = \$stack1

com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector:34: specialinvoke this.<com.fasterxml.jackson.databind.introspect.JacksonAnnotationIntrospector: void <init>()>()

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:123: specialinvoke \$u0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector: void <init>(boolean)>(\$stack2)

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:61: \$stack6 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: com.fasterxml.jackson.databind.AnnotationIntrospector _constructIntrospector()>()

com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:72: specialinvoke this.<com.fasterxml.jackson.databind.module.SimpleModule: void setupModule(com.fasterxml.jackson.databind.Module\$SetupContext)>(context)

