

com.fasterxml.jackson.dataformat.xml.misc.RootNameTest:81: staticinvoke <com.fasterxml.jackson.dataformat.xml.misc.RootNameTest: void assertEquals(java.lang.String,java.lang.String)>("<ruby/>", \$stack10)



com.fasterxml.jackson.dataformat.xml.misc.RootNameTest:80: \$stack10 = virtualinvoke \$stack5.<com.fasterxml.jackson.databind.ObjectWriter: java.lang.String writeValueAsString(java.lang.Object)>(null)



com.fasterxml.jackson.dataformat.xml.misc.RootNameTest:71: \$stack5 = virtualinvoke \$stack4.<com.fasterxml.jackson.databind.ObjectWriter: com.fasterxml.jackson.databind.ObjectWriter withRootName(java.lang.String)>("ruby")



com.fasterxml.jackson.dataformat.xml.misc.RootNameTest:71: \$stack4 = virtualinvoke \$stack3.<com.fasterxml.jackson.dataformat.xml.XmlMapper: com.fasterxml.jackson.databind.ObjectWriter writer()>()



com.fasterxml.jackson.dataformat.xml.misc.RootNameTest:71: \$stack3 = this.<com.fasterxml.jackson.dataformat.xml.misc.RootNameTest: com.fasterxml.jackson.dataformat.xml.XmlMapper _xmlMapper>



com.fasterxml.jackson.dataformat.xml.misc.RootNameTest:39: this.<com.fasterxml.jackson.dataformat.xml.misc.RootNameTest: com.fasterxml.jackson.dataformat.xml.XmlMapper _xmlMapper> = \$stack1



com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector:34: specialinvoke this.<com.fasterxml.jackson.databind.introspect.JacksonAnnotationIntrospector: void <init>()>()



com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:126: specialinvoke \$u0.<com.fasterxml.jackson.dataformat.xml.JacksonXmlAnnotationIntrospector: void <init>(boolean)>(\$stack2)



com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:65: \$stack6 = virtualinvoke this.<com.fasterxml.jackson.dataformat.xml.JacksonXmlModule: com.fasterxml.jackson.databind.AnnotationIntrospector _constructIntrospector()>()



com.fasterxml.jackson.dataformat.xml.JacksonXmlModule:75: specialinvoke this.<com.fasterxml.jackson.databind.module.SimpleModule: void setupModule(com.fasterxml.jackson.databind.Module\$SetupContext)>(context)