TiGERtms

Asterisk Post CDR Rest API - TigerTMS iLink

This Protocol will provide a one way interface between the Asterisk IP Switch and the TigerTMS Middleware using a REST HTTP(S) requests and responses.
The examples provided are in HTTP to show how the commands are built and responses returned.
This Interface is to be used for posting Asterisk CDR Records to the TigerTMS system in real time.

CDR [POST]

Function	API to send Asterisk CDR records
Description	As new Data is pushed into the Asterisk CD-R Database details should also be passed to connected guests for CDR processing. The format should be JSON, with the field names reflecting those of the Asterisk. A reply will be returned to show if the Post was successful or unsuccessful. If the service is not running i.e. HTTP 401 or other errors returned, the CDR should be buffered in the Asterisk and sent when the link is re-established. The HTTP Header will contain siteid for multi-tenanted hosted solutions Posting data is passed in the HTTP Body in JSON

Request :

Header	Description
siteid	Site id – configurable agreed by both parties

Body	Description
message	JSON containing CDR details. See example

Asterisk CDR Names used.

Field	Type	Description	Access
accountcode	String (20)	An account code associated with the Party A channel	r/w
src	String (80)	The Caller ID Number	r
dst	String (80)	The destination extension	r
dcontext	String (80)	The destination context	r
clid	String (80)	The Caller ID with text	r
channel	String (80)	The name of the Party A channel	r
dstchannel	String (80)	The name of the Party B channel	r
lastapp	String (80)	The last application the Party A channel executed	r
lastdata	String (80)	The application data for the last application the Party A channel executed	r
start	Date/time	The time the CDR was created	r
answer	Date/time	The time when Party A was answered, or when the bridge between Party A and Party B was created	r
end	Date/time	The time when the CDR was finished. This occurs when either party hangs up, or when the bridge between the parties is broken	r
duration	Integer	The time in seconds from start until end	r
billsec	Integer	The time in seconds from answer until end	r
disposition	Enum	The final known disposition of the CDR record. See CDR dispositions for possible values	r

Field	Type	Description	Access
amaflags	Enum	A flag specified on the Party A channel. See AMA records for possible values	r/w
uniqueid	String (32)	A unique identifier for the Party A channel	r

The field names are simply mapped to JSON as per the example below. One CDR per call :

Example :

CDR Post Example.

POST http://81.138.87.203/API/CDR HTTP/1.1
siteid: 00200
Content-Type: text/json

{"message":{"ccsrc":"","clid":"821<821>","src":"821","dst":"630","calleenum":"630","dcontext":"DLPN_DialPlan1","channel":"SIP/821-0000002","dstchannel":"","lastapp":"Hangup","lastdata":"","start":"2017-05-17 16:51:42","answer":"2017-05-17 16:51:42","end":"2017-05-17 16:51:42","duration":"0","billsec":"0","disposition":"8","amaflags":"3","accountcode":"","calltype":"","uniqueid":"149501102.5"}}

CDR Response Example.

TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;

`"{"response": "RECEIVEDOK"}"` Or `"{"response": "ERROR"}"`

On Error response, try 3 times then dump and log the failed CDR posting and move on to the next.