TiGERtms

Asterisk Rest API - TigerTMS iLink

This Protocol will provide a one way interface between the TigerTMS Middleware and the Asterisk IP Switch using a REST HTTP(S) requests and responses.

The examples provided are in HTTP to show how the commands are built and responses returned.

SetGuest Request [POST]

Function	API to alter Guest names and class of service
Description	The TigerTMS system will forward Guest Details on Checkin/Checkout from the PMS to the Asterisk system. The Asterisk system will used the Occupied Status to determine if the Class of Service on the extension should be restricted or unrestricted. If the occupied Status for the Extension goes to “vacant” then any MWI,DDI,DND settings should be routinely cleared. The Asterisk Server will validate the extension and information and either return whether the Post was successful or unsuccessful. The HTTP Header will contain siteid for multi-tenanted hosted solutions Posting data is passed in the HTTP Body in JSON

Request :

Header	Description
siteid	Site id – configurable agreed by both parties

Body	Description
setguest	JSON containing guest details. See example

Examples :

SetGuest Post Example.

POST http://81.138.87.203/API/setguest HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Content-Length: 131
Expect: 100-continue

{"extn":"4100","status":"occupied","title":"Mr","firstname":"John","lastname":"Smith","language":"english","group":"BAE","vip":"1"}

On Checkout the status will be set to Vacant, along with the name.

{"extn":"4100","status":"vacant","title":"","firstname":"4100","lastname":"vacant","language":"","group":"","vip":""}

SetGuest Response Example.

TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Server: Microsoft-IIS/7.5
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Content-Length: 69

{"result":"success","information":"updated guest for extension 4100"}

A failed response should be returned with details for us to log if any problems occur.

Eg.

{"result":"failed","information":"invalid extension 4100"}

SetCOS Request [POST]

Function	API to alter the class of service
Description	Although the Class of Service will be set on Check-in and Checkout it is possible to override within the PMS system. For example, they may want to restrict access if young adults are in the room.

Request :

Header	Description
Siteid	Site id – configurable agreed by both parties

Body	Description
Classofservice	JSON containing class of service level. See example The COS from the PMS is normally 0 – Barred, 1- Local, 2 – National, 3 – No restrictions. But we tend to only use barred/No restrictions.(or whatever the hotel have in place for the no restrictions)

SetCOS Post Example.

```
POST http://81.138.87.203/API/setcos HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Content-Length: 25
Expect: 100-continue

{"extn":"4100","cos":"2"}
```

SetCOS Response Example.

```
TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Content-Length: 67

{"result":"success","information":"updated cos for extension 4100"}
```

SetMW Request [POST]

Function	API to alter the state of the Message Waiting Indicator
Description	This will be sent if an external system is doing Voicemail/Message Waiting to switch the lamp on the Guests Telephone. If Innline is being used, this may be achieved by SipNotify

Request :

Header	Description
Siteid	Site id – configurable agreed by both parties

Body	Description
MessageWaiting	JSON containing MW Lamp Status “on” or “off”

SetMW Post Example.

POST http://81.138.87.203/API/setmw HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Content-Length: 25
Expect: 100-continue

{"extn":"4100","mw":"on"}

SetMW Response Example.

TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Server: Microsoft-IIS/7.5
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Content-Length: 66

{"result":"success","information":"updated mw for extension 4100"}

SetSIPData Request [POST]

Function	API to alter the Sip Password
Description	If we are using iConnect to add Bring Your Own Devices (guest mobiles) to a system then we need the ability to modify the SIP password on Check-in and Check-out. We tend to allocate three or four additional extensions per room for BYOD.

Request :

Header	Description
Siteid	Site id – configurable agreed by both parties

Body	Description
SipData	JSON containing Sip Password. See example

SetSipData Post Example.

POST http://81.138.87.203/API/setsipdata HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Content-Length: 41
Expect: 100-continue

{"extn":"4100","sippassword":"Smith1234"}

SetSipData Response Example.

TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Server: Microsoft-IIS/7.5
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Content-Length: 71

{"result":"success","information":"updated sipdata for extension 4100"}

SetDDI Request [POST]

Function	API to alter the DDI configured for the Extension.
Description	Normally sent by the PMS to route a hotel DDI directly to the guest's extension. Operation will be : "set" and "clear"

Request :

Header	Description
Siteid	Site id – configurable agreed by both parties

Body	Description
DDIInformation	JSON containing DDI and operation "set" or "clear". See example

SetDDI Post Example.

POST http://81.138.87.203/API/setddi HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Content-Length: 46
Expect: 100-continue

{"extn":"4100","ddi":"5543","operation":"set"}

SetDDI Response Example.

TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Server: Microsoft-IIS/7.5
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Content-Length: 67

{"result":"success","information":"updated ddi for extension 4100"}

SetDND Request [POST]

Function	API to alter the Do Not Disturb configured for the Extension.
Description	The Guest can set this through the PMS or external device if he doesn't want to be disturbed.

Request :

Header	Description
Siteid	Site id – configurable agreed by both parties

Body	Description
DND	JSON containing DND Status "on" or "off"

SetDND Post Example.

```
POST http://81.138.87.203/API/setdnd HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Content-Length: 26
Expect: 100-continue

{"extn":"4100","dnd":"on"}
```

SetDDI Response Example.

```
TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Server: Microsoft-IIS/7.5
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Content-Length: 67

{"result":"success","information":"updated dnd for extension 4100"}
```

SetWakeup Request [POST]

Function	API to Set/Clear Wakeup Calls for the Extension.
Description	Wakeup can be Set on the PMS or by the Connected Guests iCharge System.

Request :

Header	Description
Siteid	Site id – configurable agreed by both parties

Body	Description
Wakeup	JSON containing the Wakeup Information extn : the extension number action : set, clear, clearall wakeuptime – datetime for the wakeup format : dd-mm-yyyy hh:mm:ss note : wakeuptime will be blank on action clearall and ALL wakeups for that extension should be cleared.

SetWakeup Post Example.

POST http://81.138.87.203/API/setwakeup HTTP/1.1
siteid: 00200
Content-Type: text/json
Host: 81.138.87.203
Expect: 100-continue

{"extn":"4100","action":"set",”wakeuptime”:”24-08-2017 08:00:00}

{"extn":"4100","action":"clear",”wakeuptime”:”24-08-2017 08:00:00}

{"extn":"4100","action":"clearall",”wakeuptime”:””}

SetWakeup Response Example.

TTP/1.1 200 OK
Cache-Control: private
Content-Type: text/json;
Server: Microsoft-IIS/7.5
X-AspNet-Version: 4.0.30319
X-Powered-By: ASP.NET
Content-Length: 67

{"result":"success","information":"set wakeup for extension 4100"}