

In C++, the `stdatomic.h` header provides a set of atomic operations and types for working with atomic variables in multi-threaded environments. The operations are designed to ensure thread safety while working with shared variables in concurrent programming. Below is a list of the APIs and declarations related to atomic operations in `stdatomic.h` (C++11 and later):

1. Atomic Types

- **`std::atomic<T>`**: A template class that provides atomic operations for a given type `T`. It is the core type for atomic variables.
- **`std::atomic_flag`**: A special atomic type for flag-style operations (typically used for simple boolean flags).

2. Atomic Operations

These operations provide atomic access to variables with specified memory order semantics:

`std::atomic::load`: Atomically loads the value of the atomic variable.

```
cpp
Copy
T load(std::memory_order order = std::memory_order_seq_cst) const;
```

- **`std::atomic::store`**: Atomically stores a value into the atomic variable.

```
cpp
Copy
void store(T desired, std::memory_order order = std::memory_order_seq_cst);
```

- **`std::atomic::exchange`**: Atomically exchanges the value of the atomic variable with a new value.

```
cpp
Copy
T exchange(T desired, std::memory_order order = std::memory_order_seq_cst);
```

- **`std::atomic::compare_exchange_weak`**: Performs an atomic compare-and-swap (CAS) operation. This operation checks whether the current value of the atomic variable is equal to the expected value and, if so, replaces it with a new value.

```
cpp
Copy
bool compare_exchange_weak(T& expected, T desired, std::memory_order success, std::memory_order failure);
```

- - `compare_exchange_weak` may fail spuriously (i.e., even if the expected value is equal to the current value).

`std::atomic::compare_exchange_strong`: Similar to `compare_exchange_weak`, but does not fail spuriously.

```
cpp
Copy
bool compare_exchange_strong(T& expected, T desired, std::memory_order success, std::memory_order failure);
```

- **`std::atomic::fetch_add`**: Atomically adds a value to the atomic variable and returns the old value.

```
cpp
Copy
T fetch_add(T arg, std::memory_order order = std::memory_order_seq_cst);
```

- **`std::atomic::fetch_sub`**: Atomically subtracts a value from the atomic variable and returns the old value.

```
cpp
Copy
T fetch_sub(T arg, std::memory_order order = std::memory_order_seq_cst);
```

•

std::atomic::fetch_or: Atomically performs a bitwise OR operation on the atomic variable and returns the old value.

cpp

Copy

```
T fetch_or(T arg, std::memory_order order = std::memory_order_seq_cst);
```

•

std::atomic::fetch_and: Atomically performs a bitwise AND operation on the atomic variable and returns the old value.

cpp

Copy

```
T fetch_and(T arg, std::memory_order order = std::memory_order_seq_cst);
```

•

std::atomic::fetch_xor: Atomically performs a bitwise XOR operation on the atomic variable and returns the old value.

cpp

Copy

```
T fetch_xor(T arg, std::memory_order order = std::memory_order_seq_cst);
```

•

3. Atomic Flag Operations (**std::atomic_flag**)

std::atomic_flag is a simpler atomic type used mainly for flag-based synchronization.

std::atomic_flag::clear: Clears the atomic flag (sets it to **false**).

cpp

Copy

```
void clear(std::memory_order order = std::memory_order_seq_cst);
```

•

std::atomic_flag::test_and_set: Tests whether the atomic flag is set (true), and if not, sets it to true atomically.

cpp

Copy

```
bool test_and_set(std::memory_order order = std::memory_order_seq_cst);
```

•

4. Memory Order Types

In C++11, memory ordering defines the relationship between atomic operations with respect to the visibility of memory writes between different threads. The available memory order types are:

- **std::memory_order_relaxed**: No synchronization or ordering constraints.
- **std::memory_order_consume**: Ensures that dependencies on the consumed value are synchronized.
- **std::memory_order_acquire**: Ensures that all previous operations on the current thread are completed before the atomic operation.
- **std::memory_order_release**: Ensures that all subsequent operations on the current thread are not started until after the atomic operation.
- **std::memory_order_acq_rel**: Combines acquire and release semantics.
- **std::memory_order_seq_cst**: The default memory order, providing the strongest ordering (sequential consistency).

5. Special Operations for Atomic Types (**std::atomic<T>**)

std::atomic<T>::is_lock_free: Determines if atomic operations on a given type are lock-free.

cpp

Copy

```
bool is_lock_free() const noexcept;
```

•

6. Atomic Utilities

`std::atomic::operator=`: Atomically assigns a value to an atomic variable.

cpp

Copy

```
std::atomic<T>& operator=(T desired);
```

-

`std::atomic::operator T()`: Converts the atomic variable to a regular value.

cpp

Copy

```
operator T() const;
```

-

7. `std::atomic_thread_fence` (Global Function)

This function creates a fence, enforcing a memory ordering between atomic operations in different threads. It acts as a barrier to control memory ordering for operations across threads.

cpp

Copy

```
void atomic_thread_fence(std::memory_order order);
```

8. `std::atomic_signal_fence` (Global Function)

This function acts as a barrier for operations that are related to signals and asynchronous events. It prevents certain kinds of optimizations that could cause issues with signal handling.

cpp

Copy

```
void atomic_signal_fence(std::memory_order order);
```

Summary of Key API Functions in `stdatomic.h`:

- `std::atomic<T>`: Atomic wrapper class for any type T.
- Atomic operations** like `load()`, `store()`, `exchange()`, and `compare_exchange_*`.
- `std::atomic_flag`: A simpler atomic flag type for basic synchronization.
- Atomic arithmetic and bitwise operations**: `fetch_add()`, `fetch_sub()`, `fetch_or()`, `fetch_and()`, `fetch_xor()`.
- Memory ordering**: `std::memory_order_*` options define how memory operations are ordered with respect to atomic operations.
- Atomic fences**: `atomic_thread_fence()` and `atomic_signal_fence()` for enforcing memory order constraints.

These atomic operations and types provide a foundation for building thread-safe, high-performance applications where shared resources are accessed concurrently by multiple threads.

You said:

List all APIs/declarations related to atoimic operation in stdatomic.h in c

ChatGPT said:

In C, the header `<stdatomic.h>` provides a set of atomic operations and types designed to ensure safe access to shared variables in multi-threaded environments. Below is a list of all the APIs and declarations related to atomic operations in the `<stdatomic.h>` header for C (C11 and later).

1. Atomic Types

`atomic`: A generic atomic type that provides atomic operations for a given type.

c

```
Copy
_Atomic(type) var;
```

-

atomic_flag: A special atomic type used for flag-based synchronization, typically for spinlocks.

```
c
Copy
atomic_flag flag;
```

-

2. Atomic Operations

These are functions for performing atomic operations on variables of atomic types.

atomic_load: Atomically loads the value of an atomic variable.

```
c
Copy
T atomic_load(const atomic_type *obj);
```

-

atomic_store: Atomically stores a value into an atomic variable.

```
c
Copy
void atomic_store(atomic_type *obj, T value);
```

-

atomic_exchange: Atomically exchanges the value of the atomic variable with a new value.

```
c
Copy
T atomic_exchange(atomic_type *obj, T value);
```

-

atomic_compare_exchange_weak: Atomically compares and exchanges values. If the current value matches the expected value, it is replaced with a new value.

```
c
Copy
bool atomic_compare_exchange_weak(atomic_type *obj, T *expected, T desired);
```

-

atomic_compare_exchange_strong: Similar to **atomic_compare_exchange_weak**, but less likely to fail spuriously.

```
c
Copy
bool atomic_compare_exchange_strong(atomic_type *obj, T *expected, T desired);
```

-

atomic_fetch_add: Atomically adds a value to the atomic variable and returns the old value.

```
c
Copy
T atomic_fetch_add(atomic_type *obj, T value);
```

-

atomic_fetch_sub: Atomically subtracts a value from the atomic variable and returns the old value.

```
c
Copy
T atomic_fetch_sub(atomic_type *obj, T value);
```

-

atomic_fetch_or: Atomically performs a bitwise OR operation on the atomic variable and returns the old value.

c

Copy

```
T atomic_fetch_or(atomic_type *obj, T value);
```

-

atomic_fetch_and: Atomically performs a bitwise AND operation on the atomic variable and returns the old value.

c

Copy

```
T atomic_fetch_and(atomic_type *obj, T value);
```

-

atomic_fetch_xor: Atomically performs a bitwise XOR operation on the atomic variable and returns the old value.

c

Copy

```
T atomic_fetch_xor(atomic_type *obj, T value);
```

-

3. Atomic Flag Operations (**atomic_flag**)

The atomic flag provides a simple atomic flag-style mechanism (often used for spinlocks).

atomic_flag_clear: Clears the atomic flag (sets it to **false**).

c

Copy

```
void atomic_flag_clear(atomic_flag *flag);
```

-

atomic_flag_test_and_set: Tests if the atomic flag is set (true). If not, it sets it to true atomically.

c

Copy

```
bool atomic_flag_test_and_set(atomic_flag *flag);
```

-

4. Memory Ordering

These functions and types are used to control the memory ordering of atomic operations. Memory order determines the visibility and ordering of operations across different threads.

- **Memory Order Types:**

- **memory_order_relaxed**: No ordering or synchronization constraints.
- **memory_order_consume**: Ensures proper ordering of operations that depend on the consumed value.
- **memory_order_acquire**: Ensures that all operations before the atomic operation in the program are completed before the atomic operation itself.
- **memory_order_release**: Ensures that all operations after the atomic operation in the program are completed after the atomic operation.
- **memory_order_acq_rel**: Combines **acquire** and **release** semantics.
- **memory_order_seq_cst**: The strongest memory order; ensures sequential consistency.

atomic_thread_fence: Enforces a memory barrier between atomic operations to ensure ordering.

c

Copy

```
void atomic_thread_fence(memory_order order);
```

-

atomic_signal_fence: Similar to **atomic_thread_fence**, but specifically for operations affected by signals.

```
c
Copy
void atomic_signal_fence(memory_order order);
```

-

5. Atomic Utilities

atomic_is_lock_free: Checks if atomic operations on a given atomic type are lock-free.

```
c
Copy
bool atomic_is_lock_free(const atomic_type *obj);
```

-

6. Atomic Initializer Macros

ATOMIC_VAR_INIT: Initializes an atomic variable with a specified value.

```
c
Copy
#define ATOMIC_VAR_INIT(value) value
```

-

ATOMIC_FLAG_INIT: Initializes an atomic flag.

```
c
Copy
#define ATOMIC_FLAG_INIT (atomic_flag){0}
```

-

Summary of Key API Functions in **<stdatomic.h>** (C):

- **atomic_load**: Loads an atomic value.
- **atomic_store**: Stores a value atomically.
- **atomic_exchange**: Atomically exchanges a value.
- **atomic_compare_exchange_***: Performs atomic compare-and-swap operations (**weak** or **strong**).
- **atomic_fetch_***: Atomically fetches and updates the value (e.g., **fetch_add**, **fetch_sub**, **fetch_or**, etc.).
- **atomic_flag_clear**: Clears an atomic flag.
- **atomic_flag_test_and_set**: Tests and sets an atomic flag.
- **atomic_is_lock_free**: Checks if an atomic variable's operations are lock-free.
- **atomic_thread_fence**: Memory barrier to enforce ordering of atomic operations.
- **atomic_signal_fence**: Memory barrier specifically for signal-related atomic operations.
- **ATOMIC_VAR_INIT**: Initializes an atomic variable.
- **ATOMIC_FLAG_INIT**: Initializes an atomic flag.

These atomic operations allow C programs to perform thread-safe operations on shared variables, ensuring proper synchronization and memory ordering in concurrent environments.