

CERTIFICATION PRACTICE · OCTOBER 2026

PL-300

Power BI Data Analyst Associate

Ten full-length practice test sets: 450 original questions written to the April 2026 skills outline. Each set is weighted the way the real exam is, with an answer key and an explanation for every question.

10

test sets

45

questions per set

100

minutes per set

450

questions with answers

Prepared for Abhilash Sahani · companion to the PL-300 Study and Question Guide

How to use these sets

Each set is one sitting of the exam. Give yourself **100 minutes**, answer every question before you look at the key, and mark anything you guessed. The answer key for each set follows it immediately. Every question has a sub-area tag, so you can see where your marks went. Then comes an explanation that says why the right answer is right and why the others fail.

Sub-area of the April 2026 skills outline	Questions in every set
1 · Prepare the data (25-30%)	12
P1 · Get or connect to data	4
P2 · Profile and clean the data	3
P3 · Transform and load the data	5
2 · Model the data (25-30%)	12
M1 · Design and implement a data model	4
M2 · Create model calculations by using DAX	6
M3 · Optimize model performance	2
3 · Visualize and analyze the data (25-30%)	13
V1 · Create reports	5
V2 · Enhance reports for usability and storytelling	5
V3 · Identify patterns and trends	3
4 · Manage and secure Power BI (15-20%)	8
S1 · Create and manage workspaces and assets	4
S2 · Secure and govern Power BI items	4

Every set includes a **four-question case study**, counted inside the 45. The real exam has one, and you can't return to it once you leave it. The question formats follow the real exam: single answer, multiple response, Yes/No hot-area grids, drag-and-drop matching, build-list sequencing, and code completion in DAX and Power Query M. Across the bank: Single answer: 398 · Drag and drop: 12 · Build list: 11 · Hot area: 16 · Multiple response: 13.

Scoring

The real exam is scored 1-1000 with 700 to pass. The score is scaled, so it doesn't map to a fixed number of questions. These sets use a stricter rule of thumb: **34 out of 45 (75%)**. Score multi-part items fractionally. Two sets in a row at 75% or more, on sets you haven't seen, is a good sign you're ready to book.

Order of the sets

Set	Focus	Level	Case study
Set 01	Foundations — the whole outline in one sitting	Level 1 · Foundation	Contoso Retail
Set 02	Power Query in depth	Level 1 · Foundation	Northwind Traders
Set 03	Modelling and relationships	Level 2 · Core	Fabrikam Manufacturing
Set 04	DAX essentials	Level 2 · Core	Woodgrove Bank
Set 05	Report craft and storytelling	Level 2 · Core	Litware Healthcare

Set	Focus	Level	Case study
Set 06	Service, sharing and security	Level 2 · Core	Adventure Works Cycles
Set 07	Performance and storage modes	Level 3 · Advanced	Tailspin Toys
Set 08	Analytics, AI and Copilot	Level 3 · Advanced	Proseware Telecom
Set 09	Exam simulation A	Level 3 · Exam simulation	Alpine Ski House
Set 10	Exam simulation B — final rehearsal	Level 3 · Exam simulation	Relecloud Logistics

About these questions. Every question is original, written against the published skills outline and documented product behaviour. None is a real exam item and none is copied from a brain dump: those breach the exam agreement and can cost you the certification. None repeats the 72 questions in the study guide. Power BI ships changes every month, so where a question depends on a limit or a default (refresh counts, Copilot prerequisites, preview features), check the current Microsoft Learn page before exam day.

Blueprint coverage across the bank

Sub-area	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	Total
P1 · Get or connect to data	4	4	4	4	4	4	4	4	4	4	40
P2 · Profile and clean the data	3	3	3	3	3	3	3	3	3	3	30
P3 · Transform and load the data	5	5	5	5	5	5	5	5	5	5	50
M1 · Design and implement a data model	4	4	4	4	4	4	4	4	4	4	40
M2 · Create model calculations by using DAX	6	6	6	6	6	6	6	6	6	6	60
M3 · Optimize model performance	2	2	2	2	2	2	2	2	2	2	20
V1 · Create reports	5	5	5	5	5	5	5	5	5	5	50
V2 · Enhance reports for usability and storytelling	5	5	5	5	5	5	5	5	5	5	50
V3 · Identify patterns and trends	3	3	3	3	3	3	3	3	3	3	30
S1 · Create and manage workspaces and assets	4	4	4	4	4	4	4	4	4	4	40
S2 · Secure and govern Power BI items	4	4	4	4	4	4	4	4	4	4	40

Exam-day reminders the sets are built to train

- **Find the constraint before reading the options.** Look for phrases like *minimise administrative effort, without modifying the semantic model, least privilege, the data must not be copied, minimise the size of the model.*
- **Reference** shares upstream steps; **duplicate** copies them. Clear **Enable load** on staging queries.
- **Import** is the default storage mode. **DirectQuery** for near-real-time or data that must stay in the source. **Direct Lake** when the data already sits as Delta tables in OneLake.
- A date table must be **marked**, have **unique, contiguous dates** and cover **whole years**. Inactive relationships are used with **USERELATIONSHIP**.
- **Edit interactions** stops one visual filtering another. **Sync slicers** shares a slicer across pages. **Drillthrough** with *Keep all filters* carries the context.
- RLS restricts **Viewers** only. Admin, Member and Contributor bypass it. Roles are written in Desktop and members are assigned in the service.
- Data alerts live on **dashboard tiles**. Subscriptions email snapshots. **Publish to web** is public, so it's never the answer for internal data.
- Scheduled refresh: up to **8 a day on Pro, 48 on Premium or Fabric capacity**. A personal-mode gateway is single-user and Import only.

Set 01

Foundations — the whole outline in one sitting

Core vocabulary across all four domains: connectors, Power Query basics, the star schema, first DAX, report features and the service.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 1 · Foundation

12 Prepare the data 25–30%	12 Model the data 25–30%	13 Visualize and analyze the data 25–30%	8 Manage and secure Power BI 15–20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

Your organisation has a certified semantic model in the Power BI service. You must build a new report on it in Power BI Desktop without creating a copy of the data or a local model. How do you connect?

- ☐ A Use Analyze in Excel and publish the workbook
- ☐ B Get data → SQL Server, and import the model's source tables
- ☐ C Get data → Power BI semantic models
- ☐ D Export the model to a .pbix file and open it

Q2 SINGLE ANSWER

The password of the SQL account used by a Power BI Desktop file was changed, and refresh now fails with a credentials error. Where do you enter the new password?

- ☐ A Data source settings → select the source → Edit Permissions
- ☐ B Model view → Properties pane of a table
- ☐ C File → Options → Privacy, set the level to Public
- ☐ D Transform data → Advanced editor, then edit the Source step

Q3 SINGLE ANSWER

A report will be distributed as a Power BI template (.pbit). Whoever opens the template must choose a country from a fixed list, and the queries must load only that country's rows. What should you create?

- ☐ A A Power Query parameter used in a filter step
- ☐ B A slicer on Country with Single select turned on
- ☐ C A calculated column that filters by country
- ☐ D A bookmark for each country

Q4 SINGLE ANSWER

You need to see, for every column in the query, the percentage of values that are valid, errors and empty. Which Power Query view option shows this?

- ☐ A Column quality
- ☐ B Column profile
- ☐ C Column distribution
- ☐ D Show whitespace

Q5 SINGLE ANSWER

Column distribution on a ProductCode column shows 120 distinct and 80 unique. What does the 80 mean?

- ☐ A There are 80 different values in the column
 - ☐ B 80 values are not null
 - ☐ C 80 values occur exactly once in the column
 - ☐ D 80 rows contain errors
-

Q6 SINGLE ANSWER

A Region slicer shows "North" twice. The source contains "North" and "North " with a trailing space. Which Power Query transformation fixes this with one step?

- ☐ A Transform → Format → Clean
 - ☐ B Remove duplicates on the Region column
 - ☐ C Transform → Format → Trim
 - ☐ D Transform → Format → Capitalize Each Word
-

Q7 SINGLE ANSWER

You receive Sales2025 and Sales2026 extracts with identical columns. You need one Sales table containing the rows from both. What should you do?

- ☐ A Pivot the Year column
 - ☐ B Merge queries on OrderID
 - ☐ C Append queries
 - ☐ D Create a relationship between the two tables
-

Q8 SINGLE ANSWER

A Customer table has a PostalCode column. Some codes start with zero, for example 01234, and Power Query detected the column as Whole Number. What should the data type be?

- ☐ A Whole Number
- ☐ B Text
- ☐ C Fixed decimal number
- ☐ D Decimal Number

Q9 DRAG AND DROP — MATCH

Match each requirement to the Power Query transformation that meets it.

Choices — each may be used once, more than once, or not at all

- ☐ A Pivot column
- ☐ B Append queries
- ☐ C Unpivot other columns
- ☐ D Merge queries
- ☐ E Transpose

Requirement	Transformation
1. The source has one column per month; you need a Month column and a Value column	
2. Bring the RegionName from a Regions query into the Sales query using RegionID	
3. Combine this year's and last year's extracts into one table	
4. Field names run down the first column and each record is a column	

Q10 BUILD LIST — SEQUENCE

A REST API returns JSON with a top-level list of order records. You need a typed table with one row per order. Put the actions in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Expand the record column into individual columns
- ☐ B Merge the query with itself
- ☐ C Connect with Web.Contents and parse the response with Json.Document
- ☐ D Convert the list to a table
- ☐ E Set a data type on every column
- ☐ F Unpivot the expanded columns

Q11 SINGLE ANSWER

A CurrencyRates query is loaded into the model and used by relationships. Its data never changes, and it slows every scheduled refresh because the source is slow. The table must stay in the model. What should you change?

- ☐ A Clear Enable load on the query
- ☐ B Delete the query and type the rates into a calculated table
- ☐ C Set the query's privacy level to Private
- ☐ D Clear Include in report refresh on the query

Q12 SINGLE ANSWER

A Product table has one row per ProductKey. A Sales table has many rows per ProductKey. What relationship should Power BI create between them?

- ☐ A Many-to-one from Product to Sales, both directions
- ☐ B Many-to-many between Product and Sales, both directions
- ☐ C One-to-many from Product to Sales, single direction
- ☐ D One-to-one, both directions

Q13 SINGLE ANSWER

A report page needs two date slicers at the same time: one for order date and one for due date, each filtering Sales independently. The Sales table has OrderDateKey and DueDateKey. What is the best model design?

- ☐ A Two date tables, Order Date and Due Date, each with an active relationship to its own key
- ☐ B One Date table with an active relationship to OrderDateKey and an inactive one to DueDateKey, used with USERELATIONSHIP
- ☐ C One Date table related to both keys with both relationships active
- ☐ D A many-to-many relationship between Date and Sales

Q14 SINGLE ANSWER

A Store table has a City column. On a map visual, some cities are placed in the wrong country. Which column property should you set first?

- ☐ A Display folder
- ☐ B Data category: City
- ☐ C Sort by column
- ☐ D Summarize by: Don't summarize

Q15 SINGLE ANSWER

A measure must always return sales of red products, even when a report user selects a different colour in a slicer. Which expression should you use?

- ☐ A `CALCULATE ( [Total Sales], 'Product'[Color] = "Red" )`
- ☐ B `SUMX ( 'Product', [Total Sales] )`
- ☐ C `FILTER ( 'Product', 'Product'[Color] = "Red" )`
- ☐ D `CALCULATE ( [Total Sales], KEEPFILTERS ( 'Product'[Color] = "Red" ) )`

Q16 SINGLE ANSWER

Complete the measure so it returns year-to-date sales for a calendar year.

Sales YTD = ____ ([Total Sales], 'Date'[Date])

- ☐ A PREVIOUSYEAR
- ☐ B DATESMTD
- ☐ C SAMEPERIODLASTYEAR
- ☐ D TOTALYTD

Q17 SINGLE ANSWER

A Margin % measure divides profit by sales. Some products have zero sales, and the visual shows errors. Which expression returns blank instead of an error for those rows?

- ☐ A `[Profit] / [Sales]`
- ☐ B `IFERROR ( [Profit] / [Sales], 0 )`
- ☐ C `[Profit] / ( [Sales] + 1 )`
- ☐ D `DIVIDE ( [Profit], [Sales] )`

Q18 SINGLE ANSWER

You need the number of different customers who bought something in the current filter context. Sales has one row per order line and a CustomerKey column. Which measure is correct?

- ☐ A COUNTROWS (Sales)
- ☐ B DISTINCTCOUNT (Sales[CustomerKey])
- ☐ C COUNTROWS (Customer)
- ☐ D CALCULATE (COUNT (Sales[CustomerKey]), Sales[Amount] > 0)

Q19 SINGLE ANSWER

Which measure returns sales for the same period in the previous year, for whatever period is selected (a month, a quarter or a year)?

- ☐ A CALCULATE ([Total Sales], SAMEPERIODLASTYEAR ('Date'[Date]))
- ☐ B [Total Sales] - 365
- ☐ C CALCULATE ([Total Sales], 'Date'[Year] = YEAR (TODAY ()) - 1)
- ☐ D CALCULATE ([Total Sales], ALL ('Date'))

Q20 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about calculated columns and measures, select Yes if it is true.

Statement	Yes	No
1. A calculated column is evaluated during refresh and stored in the model.	☐	☐
2. A measure can be placed on a slicer to filter other visuals.	☐	☐
3. A measure is evaluated at query time in the filter context of the visual.	☐	☐

Q21 SINGLE ANSWER

Performance Analyzer shows a table visual taking 9,000 ms, of which DAX query is 8,700 ms and Visual display is 200 ms. Where should you focus?

- ☐ A The report theme
- ☐ B The visual's formatting options and conditional formatting
- ☐ C The measures and model behind the visual
- ☐ D The number of visuals on the page

Q22 MULTIPLE RESPONSE — CHOOSE TWO

A model is larger than expected. Which two actions reduce its size without removing anything the reports use?

- ☐ A Turn off Auto date/time in Options
- ☐ B Set every relationship to Both directions
- ☐ C Change every Text column to the Whole Number data type
- ☐ D Add a calculated column that concatenates key columns
- ☐ E Remove columns that no report, measure or relationship uses

Q23 SINGLE ANSWER

Executives want to see monthly revenue for the last 24 months and spot the trend. Which visual is most appropriate?

- ☐ A Pie chart with one slice per month
 - ☐ B Treemap
 - ☐ C Table with one row per month
 - ☐ D Line chart over the 24 months
-

Q24 SINGLE ANSWER

The marketing team requires every new report to use the corporate colours, fonts and default visual formatting. What is the most efficient approach?

- ☐ A Create and apply a JSON report theme
 - ☐ B Create a bookmark with the formatting
 - ☐ C Format every visual manually in each report
 - ☐ D Use a background image in each report
-

Q25 SINGLE ANSWER

The operations team needs a formatted list of 50,000 order lines that prints across many pages with a header on every page, and exports cleanly to Excel. Which item should you build?

- ☐ A A dashboard with a pinned table
 - ☐ B A paginated report (Power BI Report Builder)
 - ☐ C A Power BI report page with a large table visual
 - ☐ D A Q&A visual
-

Q26 SINGLE ANSWER

A Product table has a column of web addresses. In a table visual, each address must appear as a clickable hyperlink. What should you do?

- ☐ A Set the column's Data category to Image URL
 - ☐ B Set the column's Data category to Web URL
 - ☐ C Apply a background colour rule to the column
 - ☐ D Create a bookmark for each address
-

Q27 SINGLE ANSWER

You want to add a Copilot narrative visual to a report. Which environment supports Copilot in Power BI?

- ☐ A Any workspace, as long as every author has a Pro licence
- ☐ B A workspace on a Fabric trial capacity with Copilot switched on
- ☐ C My workspace with a free licence
- ☐ D Paid Fabric capacity (F2 or higher) or Premium (P1 or higher)

Q28 SINGLE ANSWER

When a user selects a value in a Region slicer, a card showing company-wide revenue must not change. Other visuals on the page must still be filtered. What should you configure?

- ☐ A A visual-level filter on the card
- ☐ B Edit interactions: set the card to None
- ☐ C Sync slicers so the slicer is hidden on the page
- ☐ D Lock the card in the Selection pane

Q29 SINGLE ANSWER

Two buttons must switch the same page area between a chart and a table showing the same data. The current slicer selections must not change when a user clicks either button. How should you set up the bookmarks?

- ☐ A Two bookmarks with Data and Display both on, each hiding one visual
- ☐ B Two bookmarks, Display only (Data cleared), each hiding one visual
- ☐ C One bookmark per slicer value, each showing both visuals
- ☐ D Use drillthrough instead of bookmarks

Q30 SINGLE ANSWER

Field staff open a report on their phones. In the Power BI mobile app, the page shows the desktop layout shrunk down. What should you do?

- ☐ A Create a mobile layout for the page
- ☐ B Increase the font size in the theme
- ☐ C Change the page size to Letter
- ☐ D Create a dashboard and pin the key visuals to it

Q31 SINGLE ANSWER

Report users can export the underlying rows from visuals, which exposes detail the business wants to keep hidden. Users must still be able to export the summarised data a visual shows. What should you change?

- ☐ A Hide the detailed columns in the model
- ☐ B Apply a sensitivity label that blocks exports
- ☐ C Set export data to summarised data only
- ☐ D Remove the users' Build permission

Q32 SINGLE ANSWER

A bar chart of sales by product category is sorted alphabetically. Users want the largest category at the top. What should you do?

- ☐ A Apply a Top N filter showing the top 100 categories by sales
- ☐ B Sort the visual by the Sales measure, descending
- ☐ C Create a Sort by column on the category
- ☐ D Rename the categories with numbers

Q33 SINGLE ANSWER

A manager wants to explore profit across region, then product category, then sales channel, letting Power BI suggest the next split that explains the most. Which visual should you use?

- ☐ A Waterfall chart by region
 - ☐ B Gauge
 - ☐ C Decomposition tree
 - ☐ D Ribbon chart
-

Q34 SINGLE ANSWER

A scatter chart plots customers by annual spend and visit frequency. You want Power BI to find groups of similar customers automatically. What should you use?

- ☐ A A constant line on the Analytics pane
 - ☐ B Grouping on the customer name
 - ☐ C Automatically find clusters
 - ☐ D Binning on annual spend
-

Q35 SINGLE ANSWER

Three hundred sales staff need to view a set of reports. They must not see draft content in the workspace. What is the most efficient way to distribute the reports?

- ☐ A Share each report individually with each user
 - ☐ B Add all 300 users to the workspace with the Viewer role
 - ☐ C Use Publish to web and email the link
 - ☐ D Publish an app and grant a security group access
-

Q36 SINGLE ANSWER

A semantic model imports data from a SQL Server database on the company network. It must refresh every morning in the Power BI service. What is required?

- ☐ A An on-premises data gateway
 - ☐ B DirectQuery storage mode
 - ☐ C A OneLake shortcut
 - ☐ D A Pro licence for every report viewer
-

Q37 SINGLE ANSWER

A report author believes a new semantic model is ready for others to use. No formal review process exists. What can the author do to signal this?

- ☐ A Certify the semantic model
- ☐ B Mark the model as a date table
- ☐ C Apply the Highly Confidential sensitivity label
- ☐ D Promote the semantic model

Q38 SINGLE ANSWER

Which statement about Power BI dashboards is correct?

- ☐ A Data alerts can be set on any report visual but not on dashboard tiles.
- ☐ B Dashboards are created in Power BI Desktop and published with the report.
- ☐ C A dashboard can have several pages.
- ☐ D A dashboard can contain tiles pinned from several reports.

Q39 SINGLE ANSWER

Finance analysts must build their own reports on the published Finance semantic model, in their own workspaces. They must not edit the model. Which permission should you grant on the model?

- ☐ A Build
- ☐ B Write
- ☐ C Reshare
- ☐ D Read

Q40 SINGLE ANSWER

Internal auditors must open and interact with reports in a workspace. They must not create, edit or share anything. Which workspace role should you assign?

- ☐ A Admin
- ☐ B Member
- ☐ C Contributor
- ☐ D Viewer

Q41 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about sensitivity labels in Power BI, select Yes if it is true.

Statement	Yes	No
1. Labels are defined in Microsoft Purview, not in Power BI.	☐	☐
2. Applying a label to a report removes Viewer access for users outside the finance department.	☐	☐
3. A label on a report stays on a PowerPoint file exported from it.	☐	☐

Case study · Contoso Retail

Questions 42–45

Existing environment

Contoso Retail runs 120 stores in five regions. Point-of-sale data is written to a SQL Server database in the head-office data centre: about 40 million sales rows a year. Monthly sales targets per store are kept in an Excel workbook on SharePoint. A Store table lists every store and its region, and a mapping table lists the email address of each store manager. Reports are used mainly between 08:00 and 20:00.

Requirements

1. Store managers need yesterday's data each morning. Intraday data is not required.
2. Sales and targets must be analysed together by store and by month.
3. The regional director wants to know which factors are associated with small basket sizes.
4. Each store manager must see only their own store's data. Managers come and go every month, and the solution must need no change when they do.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

Which storage mode should you use for the sales fact table?

- ☐ A Dual
 - ☐ B Import
 - ☐ C Live connection
 - ☐ D DirectQuery
-

Q43 SINGLE ANSWER

How should you model sales and targets so both can be analysed by store?

- ☐ A Merge the target into every sales row in Power Query
 - ☐ B Create a many-to-many relationship directly between Sales and Targets on StoreID
 - ☐ C A shared Store dimension related one-to-many to both tables
 - ☐ D Append Targets to Sales
-

Q44 SINGLE ANSWER

Which visual meets the regional director's requirement?

- ☐ A Matrix with conditional formatting
 - ☐ B Funnel chart
 - ☐ C Smart narrative
 - ☐ D Key influencers
-

Q45 SINGLE ANSWER

You create one role with a DAX filter that compares the manager mapping table to USERPRINCIPALNAME(). Where do you assign the store managers to the role?

- ☐ A In Power BI Desktop, under Modeling → Manage roles, before publishing
- ☐ B In the service, on the semantic model's Security page, adding a group
- ☐ C In the app's audience settings
- ☐ D In the workspace access pane, adding the managers as Contributors

End of Set 01 — answers follow on the next page.

Set 01 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	C	P1		16	D	M2		31	C	V2	
2	A	P1		17	D	M2		32	B	V2	
3	A	P1		18	B	M2		33	C	V3	
4	A	P2		19	A	M2		34	C	V3	
5	C	P2		20	Yes · No · Yes	M2		35	D	S1	
6	C	P2		21	C	M3		36	A	S1	
7	C	P3		22	A, E	M3		37	D	S1	
8	B	P3		23	D	V1		38	D	S1	
9	1→C 2→D 3→B 4→E	P3		24	A	V1		39	A	S2	
10	C → D → A → E	P3		25	B	V1		40	D	S2	
11	D	P3		26	B	V1		41	Yes · No · Yes	S2	
12	C	M1		27	D	V1		42	B	P1	
13	A	M1		28	B	V2		43	C	M1	
14	B	M1		29	B	V2		44	D	V3	
15	A	M2		30	A	V2		45	B	S2	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: C P1 · Get or connect to data

Connecting to a published semantic model gives a live connection: the report uses the shared model directly, with no local copy of the data. Importing the source tables builds a second, ungoverned model. A .pbix download is a copy. Analyze in Excel produces an Excel workbook, not a Power BI report.

Q2 Answer: A P1 · Get or connect to data

Credentials are stored per data source, not per query. Data source settings lists every source the file uses and lets you edit or clear its credentials. The Advanced editor shows the M code, which never contains the stored password. Privacy levels control how data is combined, not how you sign in.

Q3 Answer: A P1 · Get or connect to data

When a .pbix file opens, Power BI prompts for the value of each parameter, and a parameter used in a filter step limits which rows are loaded. A slicer or bookmark filters the report after all the data is already loaded. A calculated column can't stop rows loading.

Q4 Answer: A P2 · Profile and clean the data

Column quality shows the Valid, Error and Empty percentages under each column header. Column distribution shows distinct and unique counts with a small histogram. Column profile shows detailed statistics for one selected column. Show whitespace only reveals spaces and line feeds in cell values.

Q5 Answer: C P2 · Profile and clean the data

Unique counts values that appear exactly once. Distinct counts how many different values exist, which is 120 here. Remember profiling looks at the first 1,000 rows unless you switch it to the entire data set.

Q6 Answer: C P2 · Profile and clean the data

Trim removes leading and trailing whitespace, so both values become "North". Clean removes non-printable control characters, not spaces. Capitalisation changes letter case only. Removing duplicates on Region would delete fact rows rather than fix the value.

Q7 Answer: C P3 · Transform and load the data

Append stacks rows from tables with the same shape. Merge joins columns from another table on a key, which isn't the requirement. A relationship keeps two separate tables in the model, so every measure would have to add them together.

Q8 Answer: B P3 · Transform and load the data

Postal codes are identifiers, not quantities. Stored as a number, 01234 becomes 1234 and the leading zero is lost. Text keeps the value exactly as it appears and stops it being summed by accident.

Q9 Answer: 1→C 2→D 3→B 4→E P3 · Transform and load the data

Unpivot turns columns into attribute/value rows, and Unpivot other columns copes with months added later. Merge joins columns on a key. Append stacks rows. Transpose rotates the whole table so rows become columns. Pivot does the opposite of unpivot and isn't needed here.

Q10 Answer: C → D → A → E P3 · Transform and load the data

Parsing gives a list of records. Converting the list to a table gives one column of records. Expanding that column creates one column per field. Setting data types comes last, so the types apply to the expanded columns rather than to the record column.

Q11 Answer: D P3 · Transform and load the data

Clearing Include in report refresh keeps the table and its data in the model but skips it during refresh. Clearing Enable load would remove the table from the model, breaking the relationships. Retyping the data creates a maintenance problem, and privacy levels don't affect refresh frequency.

Q12 Answer: C M1 · Design and implement a data model

The dimension side holds one row per key and the fact side holds many, so the relationship is one-to-many with filters flowing from Product to Sales. Single direction is the default and the safe choice. Both directions adds ambiguity and is rarely needed.

Q13 Answer: A M1 · Design and implement a data model

USERRELATIONSHIP activates the second relationship inside a measure, but a slicer can only filter through the active relationship. Two independent slicers need two role-playing date tables, each actively related. Power BI won't allow two active relationships between the same two tables.

Q14 Answer: B M1 · Design and implement a data model

The data category tells Bing maps what kind of location the value is. City (plus country or state columns in the location well) reduces wrong guesses. Sort by column changes ordering. The summarisation setting controls default aggregation. Display folders only organise the field list.

Q15 Answer: A M2 · Create model calculations by using DAX

A filter argument in CALCULATE replaces any existing filter on the same column, so the slicer's colour is overridden by Red. KEEPFILTERS intersects with the slicer instead, giving blank when another colour is selected. FILTER on its own returns a table, not a value. SUMX adds sales for every product.

Q16 Answer: D M2 · Create model calculations by using DAX

TOTALYTD evaluates the expression from the start of the year to the last date in the current filter context. DATESMTD is month-to-date. SAMEPERIODLASTYEAR and PREVIOUSYEAR shift to last year rather than accumulating this year.

Q17 Answer: D M2 · Create model calculations by using DAX

DIVIDE returns blank, or an optional alternate result, when the denominator is zero, and it's the recommended pattern. The / operator returns an error or infinity. IFERROR works but is slower and returns 0, which shows the product as 0% instead of hiding it. Adding 1 changes the answer.

Q18 Answer: B M2 · Create model calculations by using DAX

DISTINCTCOUNT counts each customer once, however many lines they have. COUNT and COUNTROWS count order lines. COUNTROWS(Customer) counts customers in the dimension whether or not they bought, unless a filter happens to flow from Sales, which it doesn't by default.

Q19 Answer: A M2 · Create model calculations by using DAX

SAMEPERIODLASTYEAR shifts the current set of dates back one year, so it works at any granularity. Filtering on last calendar year ignores the period the user selected. Subtracting 365 changes the value, not the period. ALL('Date') removes the date filter and returns sales for all time.

Q20 Answer: Yes · No · Yes M2 · Create model calculations by using DAX

Calculated columns are computed row by row at refresh and take memory. Measures are computed when a visual queries them, in that visual's filter context. Slicers need column values, so a measure can't be used directly as a slicer field.

Q21 Answer: C M3 · Optimize model performance

When almost all the time is in DAX query, the engine is the bottleneck: the measure logic, relationships or model size. Visual display and Other are small, so reducing visuals or changing formatting won't help much. Copy the query into DAX query view to investigate further.

Q22 Answer: A, E M3 · Optimize model performance

Unused columns cost memory for nothing, and Auto date/time creates a hidden date table for every date column. Cross-filter direction doesn't change size. Extra calculated columns add size. Changing data types wholesale would break the text columns.

Q23 Answer: D V1 · Create reports

A line chart over a continuous time axis is the standard way to show a trend. Pie charts and treemaps show part-to-whole at one point in time. A table shows exact values but makes a trend hard to see.

Q24 Answer: A V1 · Create reports

A report theme (JSON file) sets the colour palette, fonts and default visual formatting in one step, and it can be shared and reused. Formatting manually doesn't scale. Bookmarks capture view state, not formatting. A background image doesn't change the visuals.

Q25 Answer: B V1 · Create reports

Paginated reports are made for pixel-perfect, multi-page, printable output with repeating headers, and for exporting large tabular results. A report table visual scrolls on screen and isn't designed for printing long lists. Dashboards and Q&A are summary and exploration tools.

Q26 Answer: B V1 · Create reports

With the Web URL data category, table and matrix visuals display the value as a clickable link. Image URL renders the address as a picture. Background colour rules change formatting only. Bookmarks don't open external web addresses.

Q27 Answer: D V1 · Create reports

Copilot needs a paid Fabric capacity (F2 or above) or Premium (P1 or above), plus the tenant setting for Azure OpenAI features. Trial capacities aren't supported. A Pro licence on its own, without such a capacity, isn't enough.

Q28 Answer: B V2 · Enhance reports for usability and storytelling

Edit interactions controls how one visual affects each other visual on the page. Setting None on the card stops the slicer filtering it, while the other visuals stay filtered. A visual-level filter adds a filter but doesn't remove the slicer's effect. The Selection pane controls visibility and layering.

Q29 Answer: B V2 · Enhance reports for usability and storytelling

With Data cleared, a bookmark doesn't capture or reapply filter and slicer state. With Display selected, it captures which visuals are visible. Each bookmark shows one visual and hides the other, and the buttons point to them. A Data bookmark would reset the slicers to their saved values.

Q30 Answer: A V2 · Enhance reports for usability and storytelling

The mobile layout is a separate phone canvas for each page. Visuals must be placed on it explicitly, and the app uses it in portrait mode. Changing the page size or the theme doesn't create a phone-optimised layout.

Q31 Answer: C V2 · Enhance reports for usability and storytelling

The export data setting controls whether users can export summarised data, summarised plus underlying data, or nothing. Choosing summarised only meets the requirement directly. Sensitivity labels protect exported files but don't stop the export. Hiding columns doesn't stop underlying-data export of the visible fields.

Q32 Answer: B V2 · Enhance reports for usability and storytelling

The visual's sort setting (More options → Sort axis) can sort by the measure in descending order. Sort by column fixes the order of a column against another column, for example month name by month number, and doesn't sort by value. Renaming is a workaround. Top N filters rows but doesn't sort them.

Q33 Answer: C V3 · Identify patterns and trends

The decomposition tree lets users drill into a measure across dimensions in any order, and its AI splits (High value, Low value) suggest the next best dimension. A ribbon chart shows rank changes over time. A waterfall shows how values add up to a total. A gauge shows one value against a target.

Q34 Answer: C V3 · Identify patterns and trends

Clustering finds groups of similar points on a scatter chart and creates a new field identifying each cluster. Binning buckets one numeric column into equal ranges. Grouping combines values you pick manually. A constant line is a reference line, not a grouping.

Q35 Answer: D S1 · Create and manage workspaces and assets

An app packages selected content for consumers, keeps drafts out of view, and can be granted to a security group in one step. Sharing reports one by one doesn't scale. Workspace Viewers see every item in the workspace, drafts included. Publish to web makes content public on the internet.

Q36 Answer: A S1 · Create and manage workspaces and assets

The service reaches sources on a private network through an on-premises data gateway, using a connection mapped to the semantic model. Viewer licensing doesn't affect refresh. DirectQuery would also need the gateway. Shortcuts are a Fabric lakehouse feature and don't refresh a semantic model from SQL Server.

Q37 Answer: D S1 · Create and manage workspaces and assets

Any user with write permission on an item can promote it. Certification is restricted to users the tenant admin authorises, usually after a review. Sensitivity labels classify content. They don't endorse it.

Q38 Answer: D S1 · Create and manage workspaces and assets

A dashboard is a single canvas of tiles, which can come from several reports and semantic models. It's created in the service, not in Desktop, and it has only one page. Power BI data alerts are set on dashboard tiles such as cards, KPIs and gauges.

Q39 Answer: A S2 · Secure and govern Power BI items

Build permission lets users create reports, use Analyze in Excel and query the model from other workspaces, without changing it. Read only lets them view existing content. Write lets them change the model. Reshare lets them share it further, which wasn't asked for.

Q40 Answer: D S2 · Secure and govern Power BI items

Viewer is the least-privileged workspace role: view and interact only. Contributor can create and edit content. Member can also share and publish the app. Admin can do everything, including managing access.

Q41 Answer: Yes · No · Yes S2 · Secure and govern Power BI items

Labels and their protection settings are defined in Microsoft Purview and applied to Power BI items. They classify content and protect exported files, but they don't change who can open the item inside Power BI. That's controlled by roles and permissions.

Q42 Answer: B P1 · Get or connect to data

Overnight data meets the requirement, so Import gives the best performance and full DAX with a scheduled refresh through the gateway. DirectQuery would send every visual query to the store database during trading hours with no benefit. Live connection applies to existing semantic models. Dual is only meaningful for dimensions in a composite model.

Q43 Answer: C M1 · Design and implement a data model

Two fact tables at different grains should share conformed dimensions. A Store dimension filtering both facts lets measures from each work side by side. Relating the facts directly creates a many-to-many relationship and ambiguous totals. Merging or appending mixes grains in one table.

Q44 Answer: D V3 · Identify patterns and trends

Key influencers analyses which factors are associated with a metric being high or low, which is exactly the director's question. Smart narrative describes what is on the page. A funnel shows stages. A matrix shows values but leaves the analysis to the user.

Q45 Answer: B S2 · Secure and govern Power BI items

Roles are defined in Desktop, but members are assigned in the service on the semantic model's Security page. Adding a group means monthly staff changes are handled by group membership, not by editing Power BI. Contributors bypass RLS, and app audiences control which content is visible, not which rows.

Power Query in depth

Connectors, privacy levels, dataflows, profiling, cleaning, joins, grouping and keys, with the other domains at full weight.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 1 · Foundation

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

A query reads an Excel workbook of employee salaries. The workbook must never be sent to any other data source during query evaluation. Which privacy level should you set for it?

- ☐ A Organizational
- ☐ B Public
- ☐ C Private
- ☐ D None

Q2 SINGLE ANSWER

Each month a new CSV file with the same columns is saved to the same SharePoint Online folder. The report must include every file, and new files must be picked up automatically on refresh. How should you connect?

- ☐ A Ask the business to paste each month into one workbook
- ☐ B Use the SharePoint folder connector and Combine files
- ☐ C Use the Web connector with the URL of the newest file
- ☐ D Connect to each file with the Text/CSV connector and append them

Q3 SINGLE ANSWER

Ten semantic models in different workspaces each clean the same Customer table from the ERP system with the same 25 Power Query steps. You want the logic in one place in the Power BI service, reusable by all ten models. What should you create?

- ☐ A A dataflow for the cleaned Customer table
- ☐ B A shared bookmark containing the 25 steps
- ☐ C A calculated table in each of the ten models
- ☐ D A .pbix template containing the query

Q4 SINGLE ANSWER

Regulations say a patient-records table must not be copied out of the hospital's SQL database, but reports must show it. The database is reachable through a gateway. Which storage mode should you use for this table?

- ☐ A DirectQuery
- ☐ B Import with incremental refresh
- ☐ C Dual
- ☐ D Import

Q5 SINGLE ANSWER

A numeric Discount column has a few cells that show Error after a type change. Every row must be kept, and the failed cells must become null. Which action should you use?

- ☐ A Keep errors
- ☐ B Remove blank rows, then change the type
- ☐ C Remove errors from the Discount column
- ☐ D Replace errors, with the value null

Q6 SINGLE ANSWER

A CSV from the German subsidiary stores amounts as 1.234,56. On your English (United States) machine they load as text or wrong numbers. What should you do?

- ☐ A Set the column's data category to Currency
- ☐ B Change the Windows regional settings of the gateway
- ☐ C Use Replace values to swap the commas and dots, then change type
- ☐ D Change Type → Using Locale, with locale German (Germany)

Q7 SINGLE ANSWER

Customer IDs should be unique, but you suspect some appear more than once. You want a quick list of only the rows whose CustomerID is repeated. What should you do in Power Query?

- ☐ A Turn on Column quality
- ☐ B Select CustomerID and choose Keep Rows → Keep duplicates
- ☐ C Group by CustomerID with the All rows operation
- ☐ D Select CustomerID and choose Remove duplicates

Q8 HOT AREA — YES / NO FOR EACH STATEMENT

You merge Orders (left table) with Customers (right table) on CustomerID. For each statement, select Yes if it is true.

Statement	Yes	No
1. A Left outer join keeps every order, with nulls where no customer matches.	☐	☐
2. An Inner join keeps every customer, even those with no orders.	☐	☐
3. A Right anti join returns customers that have no orders.	☐	☐

Q9 SINGLE ANSWER

You need, for each customer, only their most recent order row, with all of that row's columns. Which approach works in Power Query?

- ☐ A Remove duplicates on CustomerID without sorting the table first
- ☐ B Group by CustomerID (All rows), then take each table's latest row
- ☐ C Append the Orders query to itself, then remove duplicates
- ☐ D Pivot the OrderDate column by CustomerID

Q10 SINGLE ANSWER

Without writing M code, you must add a SizeBand column: "Small" when Quantity is below 10, "Medium" below 100, otherwise "Large". Which feature should you use?

- ☐ A Add Column → Index column
 - ☐ B Transform → Unpivot columns
 - ☐ C Add Column → Conditional column
 - ☐ D Transform → Pivot column
-

Q11 BUILD LIST — SEQUENCE

You must give the Product dimension an integer surrogate key and replace the text ProductCode in Sales with that key. Put the required actions in order.

Select the 5 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Remove the ProductCode column from Sales
 - ☐ B In the Product query, remove duplicates on ProductCode
 - ☐ C In the Product query, add an Index column starting from 1 and rename it ProductKey
 - ☐ D In the Sales query, merge with Product on ProductCode
 - ☐ E Append Product to Sales
 - ☐ F Expand only ProductKey from the merged column
-

Q12 SINGLE ANSWER

A Budget table holds amounts per product Category per month. The Product table has one row per product, including a Category column. Users must filter both budget and actual sales by category with one slicer. What is the recommended design?

- ☐ A Merge Budget into Product
 - ☐ B Relate Budget directly to Sales on the Category column, many-to-many
 - ☐ C Create a one-to-one relationship between Budget and Product
 - ☐ D A Category dimension related one-to-many to both Product and Budget
-

Q13 SINGLE ANSWER

Report authors are confused by ProductKey, CustomerKey and DateKey columns in the Sales table field list. The columns must stay for the relationships. What should you do?

- ☐ A Rename them with a leading underscore
 - ☐ B Move them to a display folder named Keys
 - ☐ C Hide the columns in report view
 - ☐ D Delete the columns
-

Q14 SINGLE ANSWER

Sales managers want a slider on the report to try discount rates from 0% to 30% and see the effect on projected revenue. Which feature creates the table and measure they need?

- ☐ A A bookmark for each discount rate
- ☐ B A numeric range parameter (what-if parameter)
- ☐ C Incremental refresh
- ☐ D A calculation group with one item per discount rate

Q15 SINGLE ANSWER

A Margin % measure shows 0.2381 in visuals. It must always show as 23.8% wherever it's used. What should you change?

- ☐ A Each visual's data label display units and decimals
- ☐ B The DAX, to multiply the result by 100 and round
- ☐ C The data type of the Sales table
- ☐ D The measure's format: Percentage, one decimal place

Q16 SINGLE ANSWER

Sales has an Amount column. You need the number of sales rows where Amount is greater than 1,000, in the current filter context. Which measure is correct?

- ☐ A `CALCULATE ( COUNTROWS ( Sales ), Sales[Amount] > 1000 )`
- ☐ B `COUNTX ( Sales, Sales[Amount] > 1000 )`
- ☐ C `COUNTROWS ( Sales ) > 1000`
- ☐ D `CALCULATE ( SUM ( Sales[Amount] ), Sales[Amount] > 1000 )`

Q17 SINGLE ANSWER

Sales has Quantity and UnitPrice columns but no revenue column. You need a Revenue measure without adding a column. Which expression is correct?

- ☐ A `CALCULATE ( SUM ( Sales[Quantity] ), Sales[UnitPrice] )`
- ☐ B `SUM ( Sales[Quantity] ) * SUM ( Sales[UnitPrice] )`
- ☐ C `SUMMARIZE ( Sales, Sales[Quantity] )`
- ☐ D `SUMX ( Sales, Sales[Quantity] * Sales[UnitPrice] )`

Q18 SINGLE ANSWER

You need a rolling 12-month sales measure ending at the last date in the current filter context. Complete the expression.

```
Sales R12M =  
CALCULATE ( [Total Sales],  
    ____ )
```

- ☐ A `PARALLELPERIOD ( 'Date'[Date], -12, MONTH )`
- ☐ B `DATESINPERIOD ( 'Date'[Date], MAX ( 'Date'[Date] ), -12, MONTH )`
- ☐ C `SAMEPERIODLASTYEAR ( 'Date'[Date] )`
- ☐ D `DATESYTD ( 'Date'[Date] )`

Q19 SINGLE ANSWER

What is the main benefit of the VAR in this measure?

```
Sales Growth % =  
VAR Curr = [Total Sales]  
VAR Prev = [Sales PY]  
RETURN DIVIDE ( Curr - Prev, Prev )
```

- ☐ A Each variable is evaluated once, then reused in the RETURN
- ☐ B Variables are stored in the model, so other measures can reuse their values
- ☐ C VAR fixes the filter context, so the measure ignores slicers
- ☐ D VAR turns the measure into a calculated column

Q20 SINGLE ANSWER

A measure must return "High" when [Margin %] is at least 40%, "Medium" when it's at least 20%, otherwise "Low". Which pattern is the clearest?

- ☐ A SWITCH (TRUE (), [Margin %] >= 0.4, "High", [Margin %] >= 0.2, "Medium", "Low")
 - ☐ B SWITCH ([Margin %], 0.4, "High", 0.2, "Medium", "Low")
 - ☐ C SWITCH (TRUE (), [Margin %] >= 0.2, "Medium", [Margin %] >= 0.4, "High", "Low")
 - ☐ D IF ([Margin %], "High", "Low")
-

Q21 SINGLE ANSWER

You want to run and test a DAX query against the model inside Power BI Desktop, including a measure definition you haven't added yet. Which statement starts the query in DAX query view?

- ☐ A SELECT
 - ☐ B RETURN
 - ☐ C EVALUATE
 - ☐ D MEASURE
-

Q22 SINGLE ANSWER

A 200-million-row fact table has a TransactionDateTime column with a different value on almost every row. It's the largest column in the model. Reports filter by date and by hour. What should you do?

- ☐ A Change it to Text
 - ☐ B Mark the fact table as a date table using this column
 - ☐ C Set the column's Summarize by to None and hide it from report view
 - ☐ D Split it into Date and hour columns, then remove the original
-

Q23 SINGLE ANSWER

A table shows revenue growth by product. Users want a green up arrow when growth is positive and a red down arrow when it's negative. What should you configure?

- ☐ A Conditional formatting → Icons on the growth column
- ☐ B Sort the table by growth
- ☐ C Conditional formatting → Data bars on the growth column
- ☐ D A bookmark for positive growth

Q24 DRAG AND DROP — MATCH

Match each requirement to the most appropriate visual.

Choices — each may be used once, more than once, or not at all

- ☐ A Ribbon chart
- ☐ B Gauge
- ☐ C Funnel chart
- ☐ D Waterfall chart
- ☐ E KPI

Requirement	Visual
1. Show this month's revenue against target, with the trend behind it, in one compact element	
2. Show how last year's profit becomes this year's profit through increases and decreases by driver	
3. Show one value on a dial between a minimum and a maximum, with a target marker	

Q25 SINGLE ANSWER

A report will be shown on a wall display with an ultra-wide 32:9 screen. The page must fill the screen without letterboxing. What should you change?

- ☐ A The page view, set to Actual size instead of Fit to page
- ☐ B Canvas settings → Custom size matching 32:9
- ☐ C The mobile layout
- ☐ D The theme

Q26 SINGLE ANSWER

You plan to use Copilot to create a new report page from a prompt. What change to the semantic model will most improve the quality of what Copilot builds?

- ☐ A Turn on Auto date/time
- ☐ B Remove all relationships
- ☐ C Switch every table to DirectQuery so Copilot sees live data
- ☐ D Add clear names, descriptions and synonyms

Q27 SINGLE ANSWER

A page must always show the last 7 days of data, moving forward automatically each day, with no change by the author. Which slicer setting meets this?

- ☐ A A page-level filter Date is after 1 January
- ☐ B A relative date slicer set to Last 7 days
- ☐ C A between date slicer with fixed start and end dates
- ☐ D A list slicer on Date

Q28 SINGLE ANSWER

You create a drillthrough page with Product[Category] in its Drill through well. What does Power BI add to the page automatically?

- ☐ A A Category slicer synced to the source page
- ☐ B A tooltip page
- ☐ C A bookmark for every category
- ☐ D A Back button to the source page

Q29 SINGLE ANSWER

A Year slicer must keep the same selection on pages 1, 2 and 3, but page 4 must be filtered independently by its own Year slicer. What should you do?

- ☐ A Sync slicers: sync pages 1-3, leave page 4 unsynced
- ☐ B Use a report-level filter on Year with a slicer on page 4
- ☐ C Copy the slicer to every page
- ☐ D Use drillthrough from page 1

Q30 SINGLE ANSWER

Report authors want a slicer that lets viewers choose whether a chart shows Revenue, Profit or Units, and the chart's axis title must change to match. Which feature should you use?

- ☐ A Personalize visuals
- ☐ B A field parameter with the three measures
- ☐ C A calculation group with three items
- ☐ D Three bookmarks

Q31 SINGLE ANSWER

A bar chart shows Revenue by Region. When users hover over a bar, the tooltip must also show the Margin % measure, which isn't on the chart. What is the simplest way?

- ☐ A Create a report-page tooltip that shows Margin %
- ☐ B Add Margin % to the Y-axis
- ☐ C Add Margin % to the visual's Tooltips well
- ☐ D Create a bookmark

Q32 SINGLE ANSWER

A line chart shows daily website orders over a year. You want Power BI to flag unexpected spikes and dips automatically and suggest possible explanations. What should you use?

- ☐ A Binning on the date axis
- ☐ B A forecast in the Analytics pane
- ☐ C An average line
- ☐ D Find anomalies on the line chart

Q33 SINGLE ANSWER

A column chart shows a sharp drop in revenue from March to April. A manager wants Power BI to suggest which dimensions contributed most to the drop. What should they do?

- ☐ A Add a forecast from the Analytics pane
 - ☐ B Analyze → Explain the decrease on the April column
 - ☐ C Turn on data labels
 - ☐ D Add a trend line and an average line from the Analytics pane
-

Q34 SINGLE ANSWER

Users ask the Q&A visual about "turnover", but the measure is called Revenue, so Q&A doesn't understand. What should you configure?

- ☐ A Add turnover as a synonym for Revenue
 - ☐ B Rename the Revenue measure Turnover
 - ☐ C Add a smart narrative that mentions turnover
 - ☐ D Create a bookmark named turnover
-

Q35 MULTIPLE RESPONSE — CHOOSE TWO

Which two workspace roles can publish or update the workspace app by default?

- ☐ A App audience member
 - ☐ B Admin
 - ☐ C Contributor
 - ☐ D Viewer
 - ☐ E Member
-

Q36 SINGLE ANSWER

A sales manager wants a snapshot of a report page emailed to her and her team every Monday at 08:00. What should you set up?

- ☐ A A data alert on a dashboard tile
 - ☐ B A Publish to web link
 - ☐ C A subscription on the report page
 - ☐ D A deployment pipeline with a weekly schedule
-

Q37 SINGLE ANSWER

A semantic model uses DirectQuery to an on-premises Oracle database and is used by 200 people. Which gateway setup is appropriate?

- ☐ A A personal-mode gateway on the developer's laptop
- ☐ B A standard on-premises data gateway on a server
- ☐ C No gateway; DirectQuery connects from each user's browser
- ☐ D A virtual network gateway in Azure only

Q38 SINGLE ANSWER

You have created RLS roles in Power BI Desktop. How can you check what a member of the Europe role will see before you publish?

- ☐ A Modeling → View as, and select the Europe role
- ☐ B Use Performance Analyzer
- ☐ C Publish and ask a colleague to log in
- ☐ D Open DAX query view and run EVALUATE Europe

Q39 SINGLE ANSWER

Users in the India role must see only rows where Customer[Country] is India. Countries rarely change and only three roles are needed. Which role filter is correct?

- ☐ A [Country] = USERPRINCIPALNAME() on the Customer table
- ☐ B FILTER (ALL (Customer), TRUE ())
- ☐ C [Country] = "India" on the Customer table
- ☐ D [Country] <> "India" on the Sales table

Q40 SINGLE ANSWER

You share a report with a consultant. The consultant must be able to view it but must not be able to share it with anyone else. What should you do when sharing?

- ☐ A Clear "Allow recipients to share this report"
- ☐ B Give the consultant the workspace Member role
- ☐ C Apply a sensitivity label
- ☐ D Grant Build permission on the semantic model

Q41 SINGLE ANSWER

A model must hide the Salary column completely from some users. The column must not even appear in their field list or be queryable. Row filters aren't needed. Which feature, and where is it authored?

- ☐ A Row-level security, authored in Manage roles
- ☐ B A sensitivity label on the model
- ☐ C Object-level security, authored in Tabular Editor
- ☐ D Hiding the column in report view, in Power BI Desktop

Case study · Northwind Traders

Questions 42–45

Existing environment

Northwind Traders distributes food products from three warehouses. Every night the warehouse system saves a CSV of the day's orders to a SharePoint folder. Each file has a header row, the order lines, and a final row that starts with the word Total. Orders contain OrderDate, DueDate, ShipDate, Warehouse, Product and Quantity. A Power BI Pro workspace is used.

Requirements

1. All nightly files must be included automatically on each refresh.
2. Managers need the number of orders that shipped after their due date.
3. From a summary page, managers must open a detailed page for one warehouse, filtered to that warehouse.
4. The operations manager wants an email whenever late orders for the day exceed 50.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

After combining the files from the folder, every combined file still includes its Total row. Where and how should you remove it?

- ☐ A In the final combined query, remove the last row
 - ☐ B Delete the Total rows in each CSV by hand
 - ☐ C In Transform Sample File, remove the bottom row
 - ☐ D Filter the Warehouse column to remove blanks
-

Q43 SINGLE ANSWER

Which measure counts orders that shipped late?

- ☐ A COUNTROWS (FILTER (Orders, Orders[ShipDate] > Orders[DueDate]))
 - ☐ B COUNT (Orders[ShipDate]) > COUNT (Orders[DueDate])
 - ☐ C CALCULATE (COUNTROWS (Orders), ALL (Orders))
 - ☐ D DATEDIFF (Orders[DueDate], Orders[ShipDate], DAY)
-

Q44 SINGLE ANSWER

How should you build the warehouse detail page?

- ☐ A Create a tooltip page
 - ☐ B Create a bookmark for each warehouse
 - ☐ C Add Warehouse to the Drill through well of the detail page
 - ☐ D Add a Warehouse slicer to the summary page and sync it
-

Q45 SINGLE ANSWER

How do you meet the operations manager's alert requirement?

- ☐ A Use Publish to web
- ☐ B Set conditional formatting on the card to turn red above 50
- ☐ C Create a daily subscription to the report page
- ☐ D Set a data alert on a dashboard tile of today's late orders

End of Set 02 — answers follow on the next page.

Set 02 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	C	P1		16	A	M2		31	C	V2	
2	B	P1		17	D	M2		32	D	V3	
3	A	P1		18	B	M2		33	B	V3	
4	A	P1		19	A	M2		34	A	V3	
5	D	P2		20	A	M2		35	B, E	S1	
6	D	P2		21	C	M3		36	C	S1	
7	B	P2		22	D	M3		37	B	S1	
8	Yes · No · Yes	P3		23	A	V1		38	A	S2	
9	B	P3		24	1→E 2→D 3→B	V1		39	C	S2	
10	C	P3		25	B	V1		40	A	S2	
11	B → C → D → F → A	P3		26	D	V1		41	C	S2	
12	D	M1		27	B	V1		42	C	P3	
13	C	M1		28	D	V2		43	A	M2	
14	B	M1		29	A	V2		44	C	V2	
15	D	M1		30	B	V2		45	D	S1	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 **Answer: C** P1 · Get or connect to data

Private data is never shared with any other source when Power Query combines data. Organizational data can be shared with other Organizational sources. Public data can be shared with anything. Setting the correct level is how you stop sensitive data leaking during folding.

Q2 Answer: B P1 · Get or connect to data

The SharePoint folder connector lists every file, and Combine files applies the same transformation to all of them through a sample file. New files in the folder are included on the next refresh. Connecting file by file means editing the query every month.

Q3 Answer: A P1 · Get or connect to data

A dataflow runs Power Query in the service and stores the result, so any semantic model can connect to the cleaned table. Changes are made once. A template is a starting point that still copies the steps into each file. Calculated tables are DAX and can't call the ERP connector.

Q4 Answer: A P1 · Get or connect to data

DirectQuery leaves the data in the source and sends a query each time a visual needs it, so no copy is stored in Power BI. Import, with or without incremental refresh, copies the data into the model. Dual also keeps an imported copy.

Q5 Answer: D P2 · Profile and clean the data

Replace errors keeps the rows and substitutes a value of your choice, here null. Remove errors deletes the rows that contain errors, which breaks the requirement. Keep errors does the opposite, keeping only the failing rows, which is useful for investigation but not as a fix.

Q6 Answer: D P2 · Profile and clean the data

Change Type Using Locale tells Power Query which culture the source text uses, so the separators are interpreted correctly wherever the file is refreshed. Replacing characters by hand is fragile. Machine settings shouldn't decide how data is parsed. A data category doesn't parse text.

Q7 Answer: B P2 · Profile and clean the data

Keep duplicates returns only the rows whose values in the selected column occur more than once, which is the investigation you want. Remove duplicates hides the problem. Column quality shows valid, error and empty percentages, not repeats. Grouping can find them but needs more steps.

Q8 Answer: Yes · No · Yes P3 · Transform and load the data

Left outer keeps all left rows. Inner keeps only rows that match on both sides, so customers without orders drop out. Right anti returns rows from the right table with no match in the left, which here means customers who never ordered.

Q9 Answer: B P3 · Transform and load the data

Group by with the All rows operation keeps each customer's rows as a nested table, from which you can take the row with the maximum date (for example with Table.Max). Removing duplicates without a guaranteed sort order isn't reliable for picking the latest row. Pivoting and appending don't solve the problem.

Q10 Answer: C P3 · Transform and load the data

A conditional column builds if-then-else logic through a dialog, with one rule per row and an Else value. Pivot and unpivot reshape the table. An index column adds row numbers.

Q11 Answer: B → C → D → F → A P3 · Transform and load the data

The dimension must have one row per code before the key is numbered. The fact then looks up the key through a merge, keeps only the key, and drops the text code. Narrow integer keys make relationships smaller and faster.

Q12 Answer: D M1 · Design and implement a data model

A Category dimension at the budget's grain can filter Budget directly and Product (and through it Sales). The slicer uses Category[Category]. Relating two facts directly, or merging budget values into a product-grain table, breaks the grain. A one-to-one relationship isn't possible because many products share a category.

Q13 Answer: C M1 · Design and implement a data model

Hiding a column removes it from the report field list while it still works in relationships and DAX. Deleting it would break the relationships. Renaming or using a display folder still leaves the keys visible to authors.

Q14 Answer: B M1 · Design and implement a data model

A numeric range parameter creates a calculated table of values, a measure that returns the selected value, and a slider slicer. Your revenue measure then references the parameter measure. Calculation groups apply logic to existing measures. Bookmarks and incremental refresh solve different problems.

Q15 Answer: D M1 · Design and implement a data model

A format string on the measure applies wherever the measure is used, in every visual and report built on the model. Formatting each visual must be repeated. Multiplying by 100 shows 23.81 without a % sign and breaks other calculations.

Q16 Answer: A M2 · Create model calculations by using DAX

The filter argument keeps only rows with Amount above 1,000, and COUNTROWS counts them while respecting the visual's existing filters. The others return TRUE or FALSE, count every row, or add up amounts instead of counting rows.

Q17 Answer: D M2 · Create model calculations by using DAX

SUMX iterates the table, multiplies quantity by price for each row and then adds the results. Multiplying the two totals gives a wrong number whenever there's more than one row. SUMMARIZE returns a table. The CALCULATE expression isn't valid.

Q18 Answer: B M2 · Create model calculations by using DAX

DATESINPERIOD returns the dates from the end date back 12 months, which CALCULATE uses as the filter. DATESYTD resets each January. SAMEPERIODLASTYEAR shifts to last year. PARALLELPERIOD returns whole periods shifted back, not a rolling window.

Q19 Answer: A M2 · Create model calculations by using DAX

A variable is evaluated once, where it's defined, and can be referenced several times in the RETURN. That improves readability and performance. Variables exist only inside that measure's evaluation. They don't change filter context or storage.

Q20 Answer: A M2 · Create model calculations by using DAX

SWITCH(TRUE(), ...) tests each condition in order and returns the first match, which handles ranges. SWITCH on the value itself only matches exact values like 0.4. IF with no comparison isn't a range test. Testing 20% first returns Medium for every margin of 20% or more, so High is never reached.

Q21 Answer: C M3 · Optimize model performance

A DAX query begins with EVALUATE followed by a table expression. A DEFINE block before it can hold MEASURE definitions to test before you add them to the model. SELECT is SQL. RETURN belongs inside a VAR expression.

Q22 Answer: D M3 · Optimize model performance

Column size is driven by cardinality. Splitting date and time gives two columns with far fewer distinct values, which compress much better, and the Date column can relate to the date table. Text would be larger. Marking a date table or changing summarisation doesn't change storage.

Q23 Answer: A V1 · Create reports

Icon conditional formatting places icons such as arrows next to values, based on rules or a field value. Data bars show magnitude, not direction. Bookmarks and sorting don't add indicators.

Q24 Answer: 1→E 2→D 3→B V1 · Create reports

A KPI shows a value, its goal and a trend. A waterfall shows a running total built from positive and negative contributions. A gauge shows a single value within a range against a target. A funnel shows sequential stages, and a ribbon chart shows how ranking changes over time.

Q25 Answer: B V1 · Create reports

Canvas settings control the page size. A custom size can match any aspect ratio. Page view changes how the page is displayed in the editor, not its dimensions. Themes change styling. Mobile layout is for phones.

Q26 Answer: D V1 · Create reports

Copilot works from the model's metadata. Descriptive names, descriptions and synonyms help it choose the right fields and measures. Storage mode and Auto date/time don't help it understand the data, and removing relationships breaks the model.

Q27 Answer: B V1 · Create reports

A relative date slicer, or a relative date filter, evaluates the period relative to today each time the report is used. Fixed dates or lists need manual updates.

Q28 Answer: D V2 · Enhance reports for usability and storytelling

When you add a field to the Drill through well, Power BI adds a Back button that takes users back to the source page. Category filtering comes from the drillthrough action itself, not from a slicer.

Q29 Answer: A V2 · Enhance reports for usability and storytelling

The Sync slicers pane controls, per page, whether a slicer shares its selection (Sync) and whether it's shown (Visible). Pages 1–3 sync and page 4 stays independent. A report-level filter applies to every page. Copying a slicer without syncing doesn't share the selection.

Q30 Answer: B V2 · Enhance reports for usability and storytelling

A field parameter creates a table of fields that a slicer can switch between. The visual uses the chosen field, including its name. Bookmarks need three copies of the chart. Personalize visuals lets each viewer change the visual themselves, but the requirement is a designed slicer. A calculation group would keep one measure name.

Q31 Answer: C V2 · Enhance reports for usability and storytelling

Fields in the Tooltips well appear in the default tooltip without being plotted. A report-page tooltip is for richer custom content. Adding the measure to the axis would plot it.

Q32 Answer: D V3 · Identify patterns and trends

Anomaly detection marks points outside the expected range, with a sensitivity setting, and lists possible explanations from fields you choose. Forecasting projects future values. An average line is a static reference. Binning groups the axis.

Q33 Answer: B V3 · Identify patterns and trends

Analyze → Explain the decrease runs an analysis of the change between the two points and shows which categories contributed. Trend lines, forecasts and data labels describe the series but don't explain the change.

Q34 Answer: A V3 · Identify patterns and trends

Synonyms teach Q&A the alternative words users type, without renaming the measure for everyone else. Renaming breaks the business's standard terminology. Smart narrative and bookmarks don't change how Q&A interprets questions.

Q35 Answer: B, E S1 · Create and manage workspaces and assets

By default, Admins and Members can publish and update the app. Contributors can create and edit content but can't update the app unless an admin turns on the setting that allows it. Viewers and app audience members only consume content.

Q36 Answer: C S1 · Create and manage workspaces and assets

A subscription emails a snapshot and link on a schedule, and the owner can include other recipients. A data alert fires when a dashboard tile crosses a threshold, not on a schedule. Publish to web is public. Deployment pipelines promote content between stages.

Q37 Answer: B S1 · Create and manage workspaces and assets

DirectQuery to an on-premises source needs a standard (enterprise) gateway. Personal mode supports only Import refresh for one user, and a laptop isn't always on. Browsers never connect to the database directly.

Q38 Answer: A S2 · Secure and govern Power BI items

View as applies one or more roles (and optionally another user name) to the report in Desktop, so you can check the result. You can also test in the service later with Test as role. DAX query view and Performance Analyzer don't apply roles.

Q39 Answer: C S2 · Secure and govern Power BI items

A static role filter is a DAX boolean expression on a table. Rows where it's TRUE are visible, and the filter flows to related tables. Comparing a country to the user name is meaningless. `FILTER(ALL(...))` returns a table, not a row condition. The last filter shows every other country.

Q40 Answer: A S2 · Secure and govern Power BI items

The share dialog lets you control resharing. Clearing that option gives view access without the right to share further. The Member role grants far more. Labels don't control sharing. Build lets the consultant create content, which goes beyond what's needed.

Q41 Answer: C S2 · Secure and govern Power BI items

Object-level security secures tables or columns for a role, so they aren't visible or queryable. It's set through the XMLA endpoint or tools like Tabular Editor rather than the Desktop UI. RLS filters rows. Hidden columns can still be queried, and labels classify content.

Q42 Answer: C P3 · Transform and load the data

Steps in Transform Sample File run against every file before they are appended, so removing the bottom row there drops each file's Total row. Removing the last row of the combined query only removes the final file's total. Editing the files by hand isn't sustainable.

Q43 Answer: A M2 · Create model calculations by using DAX

`FILTER` iterates Orders and keeps rows where the ship date is after the due date, and `COUNTROWS` counts them within the current filter context. Comparing two counts returns TRUE or FALSE. `ALL` removes every filter. `DATEDIFF` needs scalar dates, not columns, in a measure.

Q44 Answer: C V2 · Enhance reports for usability and storytelling

Drillthrough lets users right-click a warehouse on the summary page and open the detail page filtered to it, with a Back button. Bookmarks per warehouse don't scale. A synced slicer filters but doesn't navigate. Tooltip pages appear on hover.

Q45 Answer: D S1 · Create and manage workspaces and assets

Power BI data alerts are set on dashboard tiles such as cards, KPIs and gauges, and email the user when the value crosses the threshold. A subscription sends a scheduled snapshot whatever the value. Conditional formatting changes colour but sends nothing.

Set 03

Modelling and relationships

Cardinality, filter direction, role-playing and snowflaked dimensions, virtual relationships and the filter-modifier functions.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 2 · Core

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 MULTIPLE RESPONSE — CHOOSE TWO

A semantic model will refresh on a schedule in the Power BI service. Which two of its sources require an on-premises data gateway?

- ☐ A SQL Server database in the company data centre
- ☐ A SharePoint Online document library
- ☐ A OneDrive for Business folder
- ☐ An Azure SQL Database reachable over a public endpoint
- ☐ Excel files on a network file share (\\fileserver\finance)

Q2 SINGLE ANSWER

An Excel workbook contains a formatted table named tblSales on Sheet1. Users sometimes add notes below the table. In the Navigator, which object should you select?

- ☐ Sheet1
- ☐ Both, then append them
- ☐ tblSales
- ☐ The workbook's named range Print_Area

Q3 SINGLE ANSWER

A Power BI Desktop file combines two sources you fully trust. Combining them is slow because privacy checks stop query folding. Where can you tell Power BI to ignore privacy levels for this file?

- ☐ Data source settings → Edit Permissions → Credentials
- ☐ Transform data → Query properties
- ☐ Model view → Table properties
- ☐ File → Options and settings → Options → Current file → Privacy

Q4 SINGLE ANSWER

You need the minimum, maximum, average and standard deviation of a Quantity column, plus its most frequent values. Which Power Query feature shows these together?

- ☐ Column profile
- ☐ Query dependencies
- ☐ Column quality
- ☐ Column distribution

Q5 SINGLE ANSWER

In an exported report, the section name appears only on the last row of each block of rows, and the rows above it are null. Which transformation fills the nulls correctly?

- ☐ A Replace errors
- ☐ B Transpose
- ☐ C Fill up
- ☐ D Fill down

Q6 SINGLE ANSWER

A Country column contains about 40 spellings of the same countries (US, U.S., USA, United States...). The business maintains a list of correct names. What is the most maintainable fix?

- ☐ A Remove duplicates on Country
- ☐ B Use Capitalize Each Word, then Trim and Clean
- ☐ C Add a Replace values step for each of the 40 spellings
- ☐ D Merge a mapping table of variant and correct names

Q7 BUILD LIST — SEQUENCE

A query has columns Product, Attribute and Value, with Attribute holding Colour, Size and Weight. You need one column per attribute and one row per product, without summing anything. Put the actions in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Choose Unpivot other columns
- ☐ B Promote the first row to headers
- ☐ C Choose Value as the values column
- ☐ D Choose Transform → Pivot column
- ☐ E Select the Attribute column
- ☐ F Under Advanced options, set the aggregation to Don't aggregate

Q8 SINGLE ANSWER

A file has 30 queries, and you need to see which queries feed which, and which are loaded to the model. Which Power Query feature shows this?

- ☐ A Home → Manage parameters
- ☐ B Model view
- ☐ C View → Column profile
- ☐ D View → Query dependencies

Q9 SINGLE ANSWER

A FullName column holds values like "Sahani, Abhilash Kumar". You need LastName and FirstNames columns, splitting only at the first comma. Which option should you use?

- ☐ A Split column → By delimiter, comma, at the left-most delimiter
- ☐ B Split column → By number of characters
- ☐ C Extract → Last characters
- ☐ D Split column → By delimiter, comma, at each occurrence

Q10 SINGLE ANSWER

A Price column is detected as Decimal Number. Totals over millions of rows show tiny rounding differences against the finance system, which stores four decimal places. Which data type should you use?

- ☐ A Whole number
- ☐ B Percentage
- ☐ C Fixed decimal number
- ☐ D Text

Q11 SINGLE ANSWER

The source view keeps gaining new columns, but the model must only ever load six specific columns. Which step keeps the query stable when new columns appear?

- ☐ A Promote headers
- ☐ B Choose columns (Remove other columns)
- ☐ C Change type on all columns
- ☐ D Remove columns, selecting the ones you don't need

Q12 SINGLE ANSWER

Product filters Sales, and Customer filters Sales, both one-to-many in a single direction. A measure COUNTROWS(Customer) returns the same value for every product colour. You must count customers who bought each colour, without changing the relationship for the rest of the model. What should you do?

- ☐ A Set the Customer-Sales relationship's cross-filter direction to Both in the model
- ☐ B Merge Customer into Product
- ☐ C Use CROSSFILTER with BOTH on that relationship inside the measure's CALCULATE
- ☐ D Create a many-to-many relationship between Product and Customer

Q13 SINGLE ANSWER

Customer and CustomerDetails share CustomerID with exactly one row each per customer, and they're related one-to-one. Reports always use both. What is the recommended change?

- ☐ A Create a many-to-many relationship
- ☐ B Keep the one-to-one relationship and set it to Both
- ☐ C Merge CustomerDetails into Customer in Power Query
- ☐ D Hide CustomerDetails

Q14 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about the Assume referential integrity relationship property, select Yes if it is true.

Statement	Yes	No
1. It is available on relationships between DirectQuery tables from the same source.	☐	☐
2. It makes Power BI generate inner joins instead of outer joins in the SQL it sends.	☐	☐
3. Turning it on is safe even when the fact contains keys that aren't in the dimension.	☐	☐

Q15 DRAG AND DROP — MATCH

Match each requirement to the DAX function you would use inside CALCULATE.

Choices — each may be used once, more than once, or not at all

- A** REMOVEFILTERS
- B** RELATEDTABLE
- C** ALLSELECTED
- D** VALUES
- E** KEEPFILTERS

Requirement	Function
1. Percent of the grand total, ignoring every slicer on Product	
2. Percent of the total of the products the user has selected in the slicer	
3. Red-product sales that still respect a Colour slicer (blank when another colour is chosen)	

Q16 SINGLE ANSWER

You need a calculated column in Sales that holds the list price from the related Product table (Product to Sales is one-to-many). Which expression should you use?

- A** LOOKUPVALUE ('Product'[ListPrice])
- B** RELATEDTABLE ('Product')
- C** RELATED ('Product'[ListPrice])
- D** VALUES ('Product'[ListPrice])

Q17 SINGLE ANSWER

Balances has one row per account per day. You need the average daily balance across the dates in the current selection, where [Balance] sums the balance for a day. Which measure is correct?

- A** SUM (Balances[Amount]) / 365
- B** AVERAGEX (VALUES ('Date'[Date]), [Balance])
- C** AVERAGEX (Balances, Balances[Amount])
- D** AVERAGE (Balances[Amount])

Q18 SINGLE ANSWER

A Targets table has a MonthStart column but no relationship to the Date table, and you can't add one. A measure must return targets for the months selected through the Date table. Which expression should you use?

- A** CALCULATE (SUM (Targets[Amount]), TREATAS (VALUES ('Date'[MonthStart]), Targets[MonthStart]))
- B** SUM (Targets[Amount])
- C** CALCULATE (SUM (Targets[Amount]), USERRELATIONSHIP ('Date'[MonthStart], Targets[MonthStart]))
- D** CALCULATE (SUM (Targets[Amount]), ALL ('Date'))

Q19 SINGLE ANSWER

In a matrix with Category and Product on the rows, a measure must show values on product rows but blank on category subtotals and the grand total. Which pattern works?

- ☐ A SELECTEDVALUE ('Product'[Product])
 - ☐ B IF (HASONEVALUE ('Product'[Category]), [Total Sales])
 - ☐ C IF (ISBLANK ([Total Sales]), BLANK ())
 - ☐ D IF (ISINSCOPE ('Product'[Product]), [Total Sales])
-

Q20 SINGLE ANSWER

Performance Analyzer shows that most visuals on a page have a short DAX query time but a long Other time. What does this usually mean, and what helps?

- ☐ A Visuals wait on other visuals, so use fewer visuals
 - ☐ B The custom theme is too complex, so revert to the default
 - ☐ C The DAX measures are slow, so rewrite them with variables
 - ☐ D The model needs more relationships
-

Q21 SINGLE ANSWER

A DirectQuery report sends a query to the source each time a user changes any of six slicers, which overloads the database. Users don't mind clicking once when they've finished choosing. What should you configure?

- ☐ A Query reduction: add Apply buttons to slicers
 - ☐ B Switch the slicers to dropdown style so fewer queries run
 - ☐ C Turn on automatic page refresh
 - ☐ D Turn on Auto date/time
-

Q22 SINGLE ANSWER

A matrix shows monthly sales. You need a column showing the change from the previous month, defined only on this visual, with no new model measure. Which visual calculation should you write?

- ☐ A [Sales] - SAMEPERIODLASTYEAR ([Sales])
 - ☐ B RUNNINGSUM ([Sales])
 - ☐ C [Sales] - PREVIOUS ([Sales])
 - ☐ D [Sales] - CALCULATE ([Sales], PREVIOUSMONTH ('Date'[Date]))
-

Q23 SINGLE ANSWER

An analyst wants to see whether marketing spend and revenue move together across 200 stores. Which visual is most appropriate?

- ☐ A Donut chart of revenue by store
- ☐ B Card
- ☐ C Stacked column chart of spend and revenue by store
- ☐ D Scatter chart with one point per store

Q24 SINGLE ANSWER

In a table of stores, the Revenue column must show a horizontal bar in each cell proportional to the value. What should you apply?

- ☐ A A KPI visual
- ☐ B Conditional formatting → Web URL
- ☐ C Conditional formatting → Icons
- ☐ D Conditional formatting → Data bars

Q25 SINGLE ANSWER

Which requirement points to a Power BI report rather than a paginated report?

- ☐ A An invoice layout must match a pre-printed form exactly
- ☐ B Users must click a bar and have every other visual cross-filter
- ☐ C A 200-page statement must print with page numbers
- ☐ D A list of 80,000 rows must export to Excel in one go

Q26 MULTIPLE RESPONSE — CHOOSE TWO

You want to use Copilot in Power BI to suggest content for a new report page. Which two conditions must be met?

- ☐ A The tenant setting that allows users to use Copilot and other Azure OpenAI features is enabled
- ☐ B Every viewer has a Fabric trial
- ☐ C The report has been published to the web
- ☐ D The semantic model uses DirectQuery
- ☐ E The report is in a workspace on a paid Fabric capacity (F2 or higher) or Premium P1 or higher

Q27 SINGLE ANSWER

A report reader personalised a chart to show Profit by Channel instead of Revenue by Region, and wants to come back to that view later. What should they do?

- ☐ A Ask the author to save the report
- ☐ B Save it as a personal bookmark
- ☐ C Pin the chart to a dashboard
- ☐ D Export the chart to PowerPoint

Q28 SINGLE ANSWER

Keyboard users report that tabbing moves around the page in a confusing order and stops on decorative shapes. What should you fix?

- ☐ A The page size and canvas alignment
- ☐ B The tab order in the Selection pane
- ☐ C The report theme colours
- ☐ D The visual interactions in Edit interactions mode

Q29 BUILD LIST — SEQUENCE

Users of a Sales report must right-click a customer and open a Customer Detail page that lives in a separate report. Put the required steps in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Publish both reports to the same workspace
 - ☐ B Pin the detail page to a dashboard
 - ☐ C In the Sales report in the service, right-click a customer and choose Drill through
 - ☐ D In the Customer Detail report, add Customer to the drillthrough well and set Cross-report to On
 - ☐ E Create a bookmark in the Sales report
 - ☐ F In the Sales report's options, allow visuals to use drillthrough targets from other reports
-

Q30 SINGLE ANSWER

A report has 12 pages and gets new pages often. You need a row of navigation buttons, one per page, that updates automatically when pages are added or hidden. What should you insert?

- ☐ A A page navigator
 - ☐ B A drillthrough button
 - ☐ C A bookmark navigator
 - ☐ D Twelve blank buttons with page navigation actions
-

Q31 SINGLE ANSWER

A DirectQuery report in a Pro workspace (shared capacity) must refresh its visuals every 5 minutes. Automatic page refresh won't accept 5 minutes. What is required?

- ☐ A Move the workspace to Premium or Fabric capacity
 - ☐ B Change the report to Import
 - ☐ C Create a dashboard tile
 - ☐ D Increase the scheduled refresh count to 48 per day
-

Q32 SINGLE ANSWER

A line chart shows monthly demand estimates. Each estimate has a low and a high value in the model. You want the chart to show this range around each point. What should you add?

- ☐ A Error bars using the bound fields
 - ☐ B A constant line
 - ☐ C A median line
 - ☐ D A forecast with a confidence interval
-

Q33 SINGLE ANSWER

A slicer lists 30 product subcategories. Five low-volume subcategories must appear together as "Other". Users must not need a new column in the source. What should you use?

- ☐ A Clustering
- ☐ B Bins on the subcategory field
- ☐ C Groups (Group data) on the subcategory field
- ☐ D A top N filter

Q34 SINGLE ANSWER

A new analyst wants a quick plain-language overview of what a published semantic model contains: its tables, key measures and what it can answer. What can they use?

- ☐ A Query dependencies view in Power Query
- ☐ B Performance Analyzer
- ☐ C The Analytics pane
- ☐ D Copilot, asked to summarise the model

Q35 SINGLE ANSWER

Five hundred employees with free licences must view reports. The company doesn't want to buy Pro licences for them. What is required?

- ☐ A Give them the Viewer role in a Pro workspace, through an app
- ☐ B Use Publish to web
- ☐ C Email them PDF exports
- ☐ D An F64 (or P1) or larger capacity, shared through an app

Q36 SINGLE ANSWER

You publish Sales.pbix to a workspace that already contains a report and semantic model called Sales. What happens when you confirm Replace?

- ☐ A Only the model's data is refreshed
- ☐ B Both the report and the semantic model are replaced
- ☐ C Only the report is replaced
- ☐ D A second report and model named Sales (1) are created

Q37 DRAG AND DROP — MATCH

Match each sharing scenario to the most appropriate distribution method.

Choices — each may be used once, more than once, or not at all

- ☐ A Workspace Admin role
- ☐ B Direct share of the report
- ☐ C Publish to web
- ☐ D Embed in SharePoint Online
- ☐ E Workspace app

Scenario	Method
1. A whole department needs a curated set of reports, kept separate from work in progress	
2. One colleague needs to see one report today	
3. Reports must appear on the intranet's SharePoint Online page, respecting each user's permissions	
4. Non-sensitive public statistics must appear on a public website	

Q38 SINGLE ANSWER

You want only the Data Governance team to be able to certify content. What must happen first?

- ☐ A Each workspace Admin enables certification in workspace settings
- ☐ B A Fabric admin enables certification for that team's group
- ☐ C The Data Governance team is given Contributor in every workspace
- ☐ D Content is labelled Highly Confidential

Q39 HOT AREA — YES / NO FOR EACH STATEMENT

A semantic model has RLS. For each statement, select Yes if it is true.

Statement	Yes	No
1. RLS applies to a user who has Build permission and creates a report in their own workspace.	☐	☐
2. RLS applies to workspace Members of the model's workspace.	☐	☐
3. A user who belongs to two roles sees the rows allowed by either role.	☐	☐

Q40 SINGLE ANSWER

Each manager must see their own sales and the sales of everyone who reports to them, at any depth. An Employee table has EmployeeID, ManagerID and Email. What should the role use?

- ☐ A A many-to-many relationship between Employee and Sales
- ☐ B PATH and PATHCONTAINS with the signed-in user's EmployeeID
- ☐ C Employee[Email] = USERPRINCIPALNAME() on the Employee table
- ☐ D One static role per manager, listing each team member

Q41 SINGLE ANSWER

A Highly Confidential label is applied to a semantic model. Report authors create new reports from it. With label inheritance from data sources and semantic models enabled, what happens?

- ☐ A New reports inherit the Highly Confidential label
- ☐ B Report authors lose Build permission
- ☐ C The label is removed from the model when a report is created
- ☐ D Exports from the reports are blocked

Case study · Fabrikam Manufacturing

Questions 42–45

Existing environment

Fabrikam has four plants. Machine sensor readings (about 3 billion rows) are loaded every 15 minutes into Delta tables in a Microsoft Fabric lakehouse. Production orders are in Azure SQL Database. Quality inspections record inspected and defective units per batch. The model currently has Machine related to Plant, and Plant related to Region, as separate tables. Several managers run more than one plant.

Requirements

- Sensor reports must show data within minutes of each load, with Import-like performance, without copying the data into the model.
- Report authors find the Machine → Plant → Region chain confusing, and filtering by region is slow.
- A Defect Rate measure must divide defective units by inspected units and show blank where nothing was inspected.
- Plant managers must see only the plants they manage, including managers with more than one plant.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

Which storage mode should you use for the sensor fact table?

- ☐ A Dual
 - ☐ B Direct Lake
 - ☐ C Import with scheduled refresh 48 times a day
 - ☐ D DirectQuery to the SQL analytics endpoint
-

Q43 SINGLE ANSWER

How should you fix the Machine → Plant → Region chain?

- ☐ A Merge Plant and Region into the Machine table in Power Query
 - ☐ B Add a direct relationship from Region to the fact table
 - ☐ C Set every relationship in the chain to Both for faster filtering
 - ☐ D Hide the Plant and Region tables
-

Q44 SINGLE ANSWER

Complete the Defect Rate measure.

Defect Rate = ____

- ☐ A `SUM ( Inspections[Defective] ) / SUM ( Inspections[Inspected] )`
 - ☐ B `DIVIDE ( Inspections[Defective], Inspections[Inspected] )`
 - ☐ C `AVERAGE ( Inspections[Defective] )`
 - ☐ D `DIVIDE ( SUM ( Inspections[Defective] ), SUM ( Inspections[Inspected] ) )`
-

Q45 SINGLE ANSWER

Which design meets the plant-manager security requirement?

- ☐ A Give each manager the Viewer role in a separate workspace per plant
- ☐ B A filter `Plant[ManagerEmail] = USERPRINCIPALNAME()` on the Plant table, in one role
- ☐ C A manager-plant mapping table, filtered by `USERPRINCIPALNAME()` in one role
- ☐ D One static role per plant, with managers added to each role they need

End of Set 03 — answers follow on the next page.

Set 03 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	A, E	P1		16	C	M2		31	A	V2	
2	C	P1		17	B	M2		32	A	V3	
3	D	P1		18	A	M2		33	C	V3	
4	A	P2		19	D	M2		34	D	V3	
5	C	P2		20	A	M3		35	D	S1	
6	D	P2		21	A	M3		36	B	S1	
7	E → D → C → F	P3		22	C	V1		37	1→E 2→B 3→D 4→C	S1	
8	D	P3		23	D	V1		38	B	S1	
9	A	P3		24	D	V1		39	Yes · No · Yes	S2	
10	C	P3		25	B	V1		40	B	S2	
11	B	P3		26	A, E	V1		41	A	S2	
12	C	M1		27	B	V2		42	B	P1	
13	C	M1		28	B	V2		43	A	M1	
14	Yes · Yes · No	M1		29	D → F → A → C	V2		44	D	M2	
15	1→A 2→C 3→E	M2		30	A	V2		45	C	S2	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: A, E P1 · Get or connect to data

Anything on the private network, such as an on-premises database or a UNC file share, is reached through a gateway. SharePoint Online, OneDrive and a publicly reachable Azure SQL Database are cloud sources the service can reach directly.

Q2 Answer: C P1 · Get or connect to data

Selecting the table object returns exactly the table's rows and columns, however the sheet around it changes. Selecting the sheet returns every used cell, including the notes, and breaks when the layout changes.

Q3 Answer: D P1 · Get or connect to data

The Current file privacy option can be set to ignore privacy levels, which may improve performance. Use it only when every source can safely be combined. Credentials, query properties and table properties don't control privacy evaluation.

Q4 Answer: A P2 · Profile and clean the data

Column profile shows column statistics (count, errors, empty, distinct, unique, min, max, average, standard deviation and more) and a value distribution chart for the selected column. Column quality and distribution show summaries in the header area only.

Q5 Answer: C P2 · Profile and clean the data

Fill up copies a value upward into the null cells above it, which is what you need when the label is on the last row of each block. Fill down copies downward, for labels on the first row. Replace errors and Transpose don't fill gaps.

Q6 Answer: D P2 · Profile and clean the data

A mapping table puts the rules in data the business can maintain, and one merge applies them all. Dozens of Replace values steps are hard to maintain. Changing case or removing duplicates doesn't standardise spellings.

Q7 Answer: E → D → C → F P3 · Transform and load the data

Pivot turns the values of the selected column into new column headers. The values column supplies the cell contents. Don't aggregate is needed because the values are text and there is one value per product and attribute.

Q8 Answer: D P3 · Transform and load the data

Query dependencies shows a diagram of every query, its sources and the queries that reference it, and indicates which are loaded. Column profile describes one column. Manage parameters lists parameters. Model view shows relationships between loaded tables, not query lineage.

Q9 Answer: A P3 · Transform and load the data

Splitting at the left-most delimiter produces exactly two columns: the text before the first comma and everything after it. Splitting at each occurrence would create extra columns if there were more commas. Fixed-width splits don't work for names of different lengths.

Q10 Answer: C P3 · Transform and load the data

Fixed decimal number (currency) stores four decimal places exactly, which avoids floating-point rounding in totals. Whole number loses the decimals. Text can't be summed. Percentage is a format, not a precision fix.

Q11 Answer: B P3 · Transform and load the data

Choose columns, or Remove other columns, records the columns to keep, so new source columns are ignored automatically. Remove columns records the columns to drop, so any new column would flow into the model.

Q12 Answer: C M1 · Design and implement a data model

CROSSFILTER changes the filter direction only while that measure is evaluated, so Sales can filter Customer for this calculation alone. Setting the relationship to Both affects every visual and can create ambiguity. (Counting distinct Sales[CustomerKey] is another valid approach.)

Q13 Answer: C M1 · Design and implement a data model

A one-to-one relationship between two tables describing the same entity usually means they should be one table. Merging them simplifies the model and removes a relationship. The other options keep the unnecessary split.

Q14 Answer: Yes · Yes · No M1 · Design and implement a data model

Assume referential integrity applies to DirectQuery and lets the engine use inner joins, which are faster. If the fact has keys missing from the dimension, those rows silently disappear from results, so only use it when integrity is guaranteed.

Q15 Answer: 1→A 2→C 3→E M2 · Create model calculations by using DAX

REMOVEFILTERS clears filters, as ALL does when used as a modifier. ALLSELECTED restores the selection made outside the visual, so totals match what the user selected. KEEPFILTERS intersects a new filter with the existing one instead of replacing it. VALUES and RELATEDTABLE return tables but don't change filter behaviour like this.

Q16 Answer: C M2 · Create model calculations by using DAX

In a row context on the many side, RELATED follows the relationship to the one side and returns the single related value. RELATEDTABLE goes the other way and returns a table. LOOKUPVALUE needs search arguments. VALUES returns a column of values, not the related one.

Q17 Answer: B M2 · Create model calculations by using DAX

Balances are semi-additive: they mustn't be summed over time. AVERAGEX over the selected dates evaluates the daily total for each date, then averages those totals. AVERAGE over rows averages individual account rows, not daily totals. Dividing by 365 assumes a full year is selected.

Q18 Answer: A M2 · Create model calculations by using DAX

TREATAS applies the values selected in Date[MonthStart] as a filter on Targets[MonthStart]. That's a virtual relationship for this measure. A plain SUM ignores the date selection. ALL removes the filter. USERELATIONSHIP only activates an existing inactive relationship, and there isn't one.

Q19 Answer: D M2 · Create model calculations by using DAX

ISINSCOPE returns TRUE only when the Product level is being grouped, so subtotals and totals return blank. HASONEVALUE on Category is also true on product rows and on the category subtotal. ISBLANK doesn't detect the level. SELECTEDVALUE returns a name, not the measure.

Q20 Answer: A M3 · Optimize model performance

Other is time spent waiting, mostly for other visuals' queries or background work. A page with many visuals queues them. Reducing or combining visuals helps. Slow measures show as DAX query time instead.

Q21 Answer: A M3 · Optimize model performance

The query-reduction options in Options can add Apply buttons to slicers and to the filter pane, so queries are sent only when the user applies their choices. Page refresh would add queries. Slicer style and Auto date/time don't reduce queries.

Q22 Answer: C V1 · Create reports

Visual calculations work on the data in the visual. PREVIOUS returns the value from the previous row along the axis, so the difference is the month-on-month change. PREVIOUSMONTH inside CALCULATE is model DAX, which the requirement rules out. RUNNINGSUM accumulates rather than compares. SAMEPERIODLASTYEAR doesn't take a measure.

Q23 Answer: D V1 · Create reports

A scatter chart plots two measures against each other, one point per store, so correlation and outliers are visible. Column, donut and card visuals show values by category or a single value, not a relationship between two measures.

Q24 Answer: D V1 · Create reports

Data bars draw a bar in the cell scaled to the value, which makes magnitudes easy to compare. Icons show symbols based on rules. Web URL turns a value into a link. A KPI visual is a separate visual.

Q25 Answer: B V1 · Create reports

Interactive cross-filtering and exploration is what Power BI reports are for. Long printable documents, pixel-perfect forms and exporting very large tables are classic paginated-report requirements.

Q26 Answer: A, E V1 · Create reports

Copilot needs the tenant setting enabled and a workspace on supported paid capacity. Storage mode doesn't matter, trial capacities aren't supported, and Publish to web is unrelated (and public).

Q27 Answer: B V2 · Enhance reports for usability and storytelling

Personalised visuals can be kept by saving a personal bookmark, which belongs to that reader only. The author's saved report doesn't include a reader's personalisation. Exporting or pinning creates a copy elsewhere, not a reusable view in the report.

Q28 Answer: B V2 · Enhance reports for usability and storytelling

The Selection pane has a Tab order view where you set the sequence and can stop decorative objects receiving focus. That's a core accessibility setting. Page size, colours and interactions don't control keyboard navigation.

Q29 Answer: D → F → A → C V2 · Enhance reports for usability and storytelling

Cross-report drillthrough needs the target page set as a cross-report target, the source report allowed to use such targets, and both reports in the same workspace. Then the option appears in the right-click menu.

Q30 Answer: A V2 · Enhance reports for usability and storytelling

The page navigator creates one button per page and stays in sync as pages are added, renamed or hidden. A bookmark navigator lists bookmarks. Individual buttons must be maintained by hand. Drillthrough is contextual navigation, not a page menu.

Q31 Answer: A V2 · Enhance reports for usability and storytelling

In shared capacity, automatic page refresh has a 30-minute minimum. On Premium or Fabric capacity, the capacity admin sets the minimum, which can be much lower. Import mode doesn't use automatic page refresh for new data. Scheduled refresh is a different feature.

Q32 Answer: A V3 · Identify patterns and trends

Error bars draw a range around each data point from upper and lower bound fields. A median line, constant line or forecast doesn't show the per-point range.

Q33 Answer: C V3 · Identify patterns and trends

Grouping combines selected category values into a named group in the model, with the rest kept as they are, or as Other. Bins are for numeric and date ranges. Clustering finds groups on a scatter chart. A top N filter hides values rather than combining them.

Q34 Answer: D V3 · Identify patterns and trends

Summarising the underlying semantic model is one of the Copilot tasks in the outline. It describes the model in plain language from its metadata. Performance Analyzer measures speed, query dependencies is a Power Query view, and the Analytics pane adds lines to visuals.

Q35 Answer: D S1 · Create and manage workspaces and assets

Free users can view content in workspaces on F64 or P1 and larger capacities. In a Pro workspace, every viewer needs a Pro (or PPU) licence, whatever their role. Publish to web exposes the content publicly, and PDF emails lose interactivity.

Q36 Answer: B S1 · Create and manage workspaces and assets

Publishing a .pbix with the same name replaces both the existing report and its semantic model. Settings such as scheduled refresh and credentials are kept, but the model definition and data come from the file.

Q37 Answer: 1→E 2→B 3→D 4→C S1 · Create and manage workspaces and assets

Apps are for curated, scalable distribution. Direct share suits one-off access. The SharePoint Online web part embeds reports securely, so users still need permission. Publish to web is public and only for non-sensitive data. Admin is a management role, not a way to distribute content.

Q38 Answer: B S1 · Create and manage workspaces and assets

Certification is controlled by a tenant setting in the admin portal, which also defines who can certify. Workspace roles don't grant the right to certify, and sensitivity labels are unrelated to endorsement.

Q39 Answer: Yes · No · Yes S2 · Secure and govern Power BI items

RLS applies to users who only read the model, including Build users querying it from elsewhere. Workspace Admins, Members and Contributors have edit rights and bypass it. Role membership is additive, so a user in two roles sees the union of the rows each role allows.

Q40 Answer: B S2 · Secure and govern Power BI items

PATH creates a delimited list of each employee's management chain. PATHCONTAINS tests whether the signed-in manager's ID appears in that chain, so all descendants are visible. Matching only the email shows the manager's own rows. Static roles don't scale.

Q41 Answer: A S2 · Secure and govern Power BI items

Downstream inheritance applies the label of the semantic model to content created from it, so classification flows with the data. Labels don't change permissions. Exported files carry the label, with whatever protection it defines.

Q42 Answer: B P1 · Get or connect to data

Direct Lake reads the Delta tables in OneLake directly with Import-like speed and no data copy. A refresh only reframes the model to the latest table version. Import copies 3 billion rows. DirectQuery would be slower. Dual is for dimensions in composite models.

Q43 Answer: A M1 · Design and implement a data model

Flattening a snowflaked dimension into one table makes the model simpler for authors and removes relationship hops. Bidirectional filters add ambiguity. A second path to the fact creates an ambiguous model. Hiding tables removes the attributes authors need.

Q44 Answer: D M2 · Create model calculations by using DAX

DIVIDE returns blank when the denominator is zero, which meets the requirement. The / operator returns an error or infinity. AVERAGE of defects isn't a rate. DIVIDE needs scalar expressions, so passing columns without aggregating fails in a measure.

Q45 Answer: C S2 · Secure and govern Power BI items

A mapping table with one row per manager per plant handles managers with several plants in one dynamic role, with a filter on Plant such as [PlantID] IN CALCULATETABLE (VALUES (PlantSecurity[PlantID]), PlantSecurity[Email] = USERPRINCIPALNAME ()). A single ManagerEmail column on Plant allows only one manager per plant. Static roles per plant work but need maintenance. Separate workspaces duplicate content.

DAX essentials

CALCULATE, context transition, iterators, time intelligence and semi-additive balances, with the rest of the outline at full weight.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 2 · Core

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

In Power BI Desktop, you want to browse the Fabric lakehouses, warehouses and semantic models you have access to and connect to one of them. Which Get data entry point lists them?

- ☐ A Blank query
- ☐ B Web
- ☐ C OneLake catalog
- ☐ D Folder

Q2 SINGLE ANSWER

You are configuring incremental refresh. RangeStart and RangeEnd are Date/Time parameters. Which filter on OrderDateTime stops rows on a partition boundary from loading twice?

- ☐ A [OrderDateTime] = RangeStart
- ☐ B [OrderDateTime] >= RangeStart and [OrderDateTime] <= RangeEnd
- ☐ C [OrderDateTime] >= RangeStart and [OrderDateTime] < RangeEnd
- ☐ D [OrderDateTime] > RangeStart and [OrderDateTime] <= RangeEnd + 1

Q3 SINGLE ANSWER

A report is live-connected to a shared semantic model. The author must add a small Excel table of regional targets and relate it to the model's Region table. What should the author do?

- ☐ A Import the shared model's tables into a new file
- ☐ B Paste the targets into a DAX calculated column
- ☐ C Select Make changes to this model
- ☐ D Ask for workspace Admin on the shared model

Q4 SINGLE ANSWER

Twelve queries in a file connect to SQL server SQLPROD01, which is being renamed SQLPROD02. You want to change all twelve in one place without editing each query. Where do you do this?

- ☐ A Options → Global → Data load
- ☐ B Each query's Source step in the Advanced editor
- ☐ C Model view → Properties
- ☐ D Data source settings → select the source → Change Source

Q5 SINGLE ANSWER

Text exported from a mainframe contains non-printable control characters, so values that look identical don't match in merges. Which transformation removes them?

- ☐ A Clean
 - ☐ B Replace errors
 - ☐ C Lowercase
 - ☐ D Trim
-

Q6 SINGLE ANSWER

After applying changes, Power BI reports that 37 rows of the Orders query contain errors. You need to see exactly which rows failed and why. What should you do?

- ☐ A Turn on Column quality and Column distribution
 - ☐ B Delete the Orders query and import it again
 - ☐ C Select View errors to open an errors query
 - ☐ D Open Performance Analyzer
-

Q7 SINGLE ANSWER

A Suppliers query must be matched to an Invoices query on company name, but names differ slightly ("Contoso Ltd" vs "Contoso Limited"). Which Merge option helps?

- ☐ A Use fuzzy matching, with a similarity threshold
 - ☐ B Use a Left anti join
 - ☐ C Append the two queries
 - ☐ D Use Group by on the name
-

Q8 SINGLE ANSWER

The Sales OrderDate column is Date/Time and every value has a 00:00 time. The Date table's Date column is of type Date. You want a clean relationship and smaller storage. What should you do in Power Query?

- ☐ A Change the OrderDate column type to Text
 - ☐ B Change the Date table's column to Text
 - ☐ C Add an index column
 - ☐ D Change the OrderDate column type to Date
-

Q9 SINGLE ANSWER

You append NorthSales and SouthSales. NorthSales has a column named Amount and SouthSales has Amt. After the append, half the rows have null Amount. What is the fix?

- ☐ A Change both columns to Text
- ☐ B Use Merge queries instead of Append
- ☐ C Replace nulls with 0 after appending
- ☐ D Rename Amt to Amount in SouthSales before appending

Q10 MULTIPLE RESPONSE — CHOOSE TWO

Sales and Price can only be matched on the combination of Region and ProductCode. Power BI relationships use a single column. Which two actions together create a working relationship?

- ☐ A Create two active relationships, one on Region and one on ProductCode
 - ☐ B Relate the two tables on the new combined key columns
 - ☐ C Add a combined key column (Region & "|" & ProductCode) in both queries in Power Query
 - ☐ D Set the relationship on Region to Both
 - ☐ E Create a many-to-many relationship on ProductCode alone
-

Q11 BUILD LIST — SEQUENCE

No date table exists in any source. You decide to build one in Power Query and use it for time intelligence. Put the required actions in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Merge the date list with the Sales query
 - ☐ B Load the table and mark it as a date table in the model
 - ☐ C Turn on Auto date/time
 - ☐ D Add Year, Month and MonthNumber columns
 - ☐ E Create a list of dates with List.Dates covering whole years
 - ☐ F Convert the list to a table and set the column type to Date
-

Q12 SINGLE ANSWER

You set the sort-by column of MonthName to MonthKey (values like 202501, 202601). Power BI shows an error. What should you do?

- ☐ A Remove the relationship to Sales
 - ☐ B Sort MonthName by MonthNumber (1–12) instead
 - ☐ C Sort MonthName by Date
 - ☐ D Change MonthName to a number
-

Q13 SINGLE ANSWER

Report users want to drill from Year to Quarter to Month in visuals without adding three fields each time. What should you create in the model?

- ☐ A Three calculated columns
 - ☐ B A Year-Quarter-Month hierarchy on the Date table
 - ☐ C A bookmark
 - ☐ D A calculation group with Year, Quarter and Month items
-

Q14 SINGLE ANSWER

Which is a good use case for a calculated table?

- ☐ A Removing duplicate customers before they're loaded from the source
- ☐ B A role-playing ShipDate table copied from the Date table
- ☐ C Cleaning text values that come from a CSV
- ☐ D Combining the monthly CSV files in a folder

Q15 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about column properties, select Yes if it is true.

Statement	Yes	No
1. A Year column that is summed in visuals should have Summarize by set to Don't summarize.	☐	☐
2. Setting a column's data category to Country/Region changes its data type to Text.	☐	☐
3. A format string set on a column applies in every visual that uses that column.	☐	☐

Q16 SINGLE ANSWER

Which measure returns quarter-to-date sales?

- ☐ A TOTALQTD ([Total Sales], 'Date'[Date])
- ☐ B TOTALYTD ([Total Sales], 'Date'[Date], "3/31")
- ☐ C CALCULATE ([Total Sales], QUARTER ('Date'[Date]))
- ☐ D DATESQTD ([Total Sales])

Q17 SINGLE ANSWER

In the Customer table, a calculated column CustSales = [Total Sales] returns each customer's own sales, but CustSales2 = SUM (Sales[Amount]) returns the grand total on every row. Why?

- ☐ A Measures are stored in the Customer table
- ☐ B SUM ignores relationships in every case
- ☐ C Calculated columns can't use aggregation functions such as SUM
- ☐ D Measure references trigger context transition; SUM doesn't

Q18 SINGLE ANSWER

A card must show the combined sales of the top five products by sales, whatever the visual is filtered to. Which measure is correct?

- ☐ A CALCULATE ([Total Sales], TOPN (5, ALL ('Product'[Name]), [Total Sales]))
- ☐ B MAXX ('Product', [Total Sales]) * 5
- ☐ C TOPN (5, 'Product', [Total Sales])
- ☐ D SUMX (FILTER ('Product', RANKX ('Product', [Total Sales]) <= 5), [Total Sales])

Q19 SINGLE ANSWER

Operations wants the delivery time, in days, below which 90% of deliveries fall. Which function should the measure use?

- ☐ A MAX (Deliveries[Days])
- ☐ B PERCENTILE.INC (Deliveries[Days], 0.9)
- ☐ C AVERAGE (Deliveries[Days]) * 0.9
- ☐ D STDEV.P (Deliveries[Days])

Q20 DRAG AND DROP — MATCH

Match each requirement to the time-intelligence function that fits it.

Choices — each may be used once, more than once, or not at all

- A** TOTALYTD
- B** DATEADD
- C** FIRSTDATE
- D** DATESBETWEEN
- E** LASTNONBLANK

Requirement	Function
1. Opening balance on the first day of the selected period	
2. Closing balance on the last date that actually has data	
3. Sales for the same dates shifted back one quarter	
4. Sales during a fixed promotion window, 1 to 15 March	

Q21 SINGLE ANSWER

A fact table stores one row per sensor reading per second, but every report shows daily totals by machine. The model is too large. What is the most effective change?

- A** Change the table to DirectQuery
- B** Group to one row per machine per day in Power Query
- C** Hide the timestamp column
- D** Add a calculated column with the date and hide the timestamp

Q22 SINGLE ANSWER

Two large tables are related many-to-many on a long text column, and visuals using them are slow. Which change is most likely to help?

- A** A dimension with integer keys, one-to-many to both tables
- B** Change the many-to-many relationship's cross-filter direction to Both
- C** Add more measures
- D** Turn on Auto date/time

Q23 SINGLE ANSWER

A matrix shows sales by Category and Product. You need a column showing each row's share of the grand total, written as a visual calculation. Complete the expression.

% of total = ____

- A** DIVIDE ([Sales], COLLAPSEALL ([Sales], ROWS))
- B** DIVIDE ([Sales], PREVIOUS ([Sales]))
- C** RUNNINGSUM ([Sales])
- D** DIVIDE ([Sales], CALCULATE ([Sales], ALL ('Product')))

Q24 SINGLE ANSWER

You need the same column chart of monthly sales repeated for each of six regions, in a grid with shared axes. Which feature should you use?

- ☐ A Six copies of the chart with visual-level filters
 - ☐ B A drillthrough page
 - ☐ C Small multiples on the column chart, with Region
 - ☐ D A matrix
-

Q25 SINGLE ANSWER

A page filter limits the page to the current financial year. Viewers must see that the filter exists but must not be able to change it. What should you do in the Filters pane?

- ☐ A Delete the filter
 - ☐ B Convert it to a slicer
 - ☐ C Lock the filter
 - ☐ D Hide the filter
-

Q26 SINGLE ANSWER

Executives want an AI-written text summary of the visuals on a page that updates when they change slicers. What should you add?

- ☐ A A text box with typed commentary
 - ☐ B A narrative visual with Copilot
 - ☐ C A bookmark navigator
 - ☐ D A Q&A visual
-

Q27 SINGLE ANSWER

A bookmark should apply a set of slicer selections but leave users on whatever page they're viewing when they use it from a bookmark navigator. Which bookmark option should you clear?

- ☐ A All visuals
 - ☐ B Display
 - ☐ C Current page
 - ☐ D Data
-

Q28 SINGLE ANSWER

When users select a bar in a column chart, another chart on the page dims the unrelated portions of its bars. They want the other chart to show only the filtered values instead. What should you change?

- ☐ A Sync the slicers
- ☐ B Edit interactions: set the chart to Filter
- ☐ C Turn off drillthrough
- ☐ D Add a visual-level filter to the target chart

Q29 SINGLE ANSWER

A line chart distinguishes Actual and Target only by red and green lines. Some users can't tell them apart. Which change best improves accessibility?

- ☐ A Remove the legend
 - ☐ B Distinct line styles or markers, with labels
 - ☐ C Make the lines thicker and the colours brighter
 - ☐ D Change the background to black for more contrast
-

Q30 SINGLE ANSWER

Users don't know that they can right-click to drill through. You want a visible button that becomes active when a customer is selected and opens the Customer Detail page for that customer. How do you configure the button?

- ☐ A Set the action type to Q&A
 - ☐ B Set the action type to Drill through
 - ☐ C Set the action type to Bookmark
 - ☐ D Set the action type to Page navigation
-

Q31 BUILD LIST — SEQUENCE

Field engineers need a phone-friendly version of the Overview page. Put the steps in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Create a dashboard
 - ☐ B Publish the report so the Power BI mobile app uses the layout in portrait mode
 - ☐ C Change the page size to 9:16
 - ☐ D Drag the four key visuals onto the phone canvas and resize them
 - ☐ E Select View → Mobile layout
 - ☐ F Open the Overview page in Power BI Desktop
-

Q32 SINGLE ANSWER

A churn analysis needs to find combinations of customer attributes, such as tenure under 6 months on the basic plan in the North region, where churn is much higher than average. Which view should you use?

- ☐ A Key influencers → Top segments
 - ☐ B A funnel chart
 - ☐ C Key influencers → Key influencers
 - ☐ D A decomposition tree with no AI splits
-

Q33 SINGLE ANSWER

A column chart of delivery times by depot needs a line showing the 90th percentile across depots, so outliers stand out. Where do you add it?

- ☐ A A calculated column on Depot
- ☐ B The Filters pane: a top N filter
- ☐ C The Analytics pane: a percentile line set to 90%
- ☐ D The Format pane: data labels

Q34 SINGLE ANSWER

You add a forecast to a line chart of monthly sales that peaks every December. The forecast looks flat. Which setting should you change?

- ☐ A Change the line to a column chart
- ☐ B Turn on data labels
- ☐ C Lower the confidence interval to 50%
- ☐ D Set the seasonality to 12 points

Q35 SINGLE ANSWER

A data steward wants an email whenever a scheduled refresh of a semantic model fails, even though they don't own the model. What should you configure?

- ☐ A Sync slicers
- ☐ B A subscription to the report
- ☐ C Refresh failure notifications, with the steward as a contact
- ☐ D A data alert on a dashboard tile showing the last refresh date

Q36 SINGLE ANSWER

Content moves through Development, Test and Production stages in a deployment pipeline. Each stage's semantic model must connect to a different SQL database. What should you configure?

- ☐ A A personal gateway per stage
- ☐ B Sensitivity labels per stage
- ☐ C A separate .pbix file per stage, each with its own source
- ☐ D Deployment rules in the Test and Production stages

Q37 SINGLE ANSWER

You updated a report in a workspace, but app users still see the old version. What should you do?

- ☐ A Clear the browser cache of each user
- ☐ B Refresh the semantic model
- ☐ C Re-share the report directly
- ☐ D Update the app

Q38 SINGLE ANSWER

A developer must add other colleagues to a workspace as Contributors and Viewers, but must not be able to delete the workspace or change its settings. Which role should you assign?

- ☐ A Contributor
- ☐ B Viewer
- ☐ C Member
- ☐ D Admin

Q39 SINGLE ANSWER

Where do you check, in the Power BI service, what a member of an RLS role will see in a published report?

- ☐ A In Performance Analyzer
- ☐ B In the app's audience settings for that role
- ☐ C In the workspace settings
- ☐ D Test as role, on the model's Security page

Q40 SINGLE ANSWER

Compliance requires that every report published to the service has a sensitivity label. What should you configure?

- ☐ A A mandatory labelling policy in Microsoft Purview
- ☐ B Automatic page refresh
- ☐ C A certification process for every published report
- ☐ D Workspace Viewer roles for all users

Q41 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about Publish to web, select Yes if it is true.

Statement	Yes	No
1. Anyone with the link or embed code can view the report, without signing in.	☐	☐
2. Publish to web respects row-level security, so each viewer sees only their own rows.	☐	☐
3. A tenant administrator can turn Publish to web off, or limit it to specific users.	☐	☐

Case study · Woodgrove Bank

Questions 42–45

Existing environment

Woodgrove Bank's core banking system exports a daily snapshot of every account balance, one row per account per calendar day, as CSV. The balance column is text such as "12,450.75 CR" or "980.10 DR", where DR means a negative balance. Transactions, Branch and Customer tables are also loaded. The model refreshes at 03:00 through a single on-premises data gateway installed on one server.

Requirements

1. Balances must be numeric, with debit balances negative.
2. Monthly reports must show each account's balance on the last day of each month, never the sum of daily balances.
3. Risk managers want each customer's risk rating cell coloured using the colour the risk team stores for that rating.
4. Last month the gateway server was patched overnight and the refresh failed. Refresh must continue even if one gateway machine is offline.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

How should you convert the balance text?

- ☐ A Split on the space, type the amount, negate DR amounts
- ☐ B Use Fill down on the column
- ☐ C Use Replace errors with 0
- ☐ D Change the column type to Decimal Number using a locale

Q43 SINGLE ANSWER

Which measure returns the month-end balance?

- ☐ A TOTALMTD (SUM (Balances[Amount]), 'Date'[Date])
 - ☐ B SUM (Balances[Amount])
 - ☐ C AVERAGE (Balances[Amount])
 - ☐ D CLOSINGBALANCEMONTH (SUM (Balances[Amount]), 'Date'[Date])
-

Q44 SINGLE ANSWER

The risk team keeps a hex colour per rating in the RiskRating table. How should you colour the cells?

- ☐ A Create rules-based formatting with one rule per rating, typing each colour
 - ☐ B Field value formatting with a measure that returns the hex colour
 - ☐ C Apply a report theme
 - ☐ D Use gradient formatting on the rating
-

Q45 SINGLE ANSWER

How do you make the scheduled refresh resilient to one gateway machine being offline?

- ☐ A Add a gateway on another server to the same cluster
- ☐ B Move the refresh to 04:00, when the gateway server is idle
- ☐ C Give the data steward Admin on the workspace
- ☐ D Switch to a personal-mode gateway

End of Set 04 — answers follow on the next page.

Set 04 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	C	P1		16	A	M2		31	F → E → D → B	V2	
2	C	P1		17	D	M2		32	A	V3	
3	C	P1		18	A	M2		33	C	V3	
4	D	P1		19	B	M2		34	D	V3	
5	A	P2		20	1→C 2→E 3→B 4→D	M2		35	C	S1	
6	C	P2		21	B	M3		36	D	S1	
7	A	P3		22	A	M3		37	D	S1	
8	D	P3		23	A	V1		38	C	S2	
9	D	P3		24	C	V1		39	D	S2	
10	B, C	P3		25	C	V1		40	A	S2	
11	E → F → D → B	P3		26	B	V1		41	Yes · No · Yes	S2	
12	B	M1		27	C	V2		42	A	P2	
13	B	M1		28	B	V2		43	D	M2	
14	B	M1		29	B	V2		44	B	V1	
15	Yes · No · Yes	M1		30	B	V2		45	A	S1	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: C P1 · Get or connect to data

The OneLake catalog in Power BI Desktop lists Fabric items you can access, including lakehouses, warehouses and semantic models, and connects to them. Blank query, Web and Folder are generic connectors with no catalog of Fabric items.

Q2 Answer: C P1 · Get or connect to data

One side of the range must be inclusive and the other exclusive, so a row exactly on a boundary lands in exactly one partition. Making both inclusive loads boundary rows into two partitions. An equality filter would load almost nothing.

Q3 Answer: C P1 · Get or connect to data

Make changes to this model converts the live connection into DirectQuery for Power BI semantic models, so local tables like the Excel targets can be added and related. The shared model stays unchanged. Importing creates an ungoverned copy. Admin rights aren't needed.

Q4 Answer: D P1 · Get or connect to data

Change Source in Data source settings updates every query that uses that source in one action. Editing each query's Source step works but repeats the change twelve times. (A server-name parameter would also work, if it had been set up earlier.)

Q5 Answer: A P2 · Profile and clean the data

Clean removes non-printable characters. Trim removes only leading and trailing spaces. Changing case doesn't remove characters, and the values aren't errors, so Replace errors does nothing here.

Q6 Answer: C P2 · Profile and clean the data

View errors builds an errors query that isolates the problem rows and shows each error. That's the fastest way to diagnose import errors. Column quality and distribution show percentages and counts, not failing rows. Performance Analyzer measures report performance.

Q7 Answer: A P3 · Transform and load the data

Fuzzy matching in a merge pairs values that are similar rather than identical, with a threshold and optional transformation table. An anti join returns rows that don't match. Append stacks rows. Grouping doesn't compare two tables.

Q8 Answer: D P3 · Transform and load the data

Converting to Date matches the date table's type, drops the meaningless time part and reduces storage. Text columns relate less efficiently and break time-intelligence logic. An index column doesn't help.

Q9 Answer: D P3 · Transform and load the data

Append matches columns by name. Different names produce two partly empty columns. Renaming them first fixes the cause. Replacing nulls with 0 hides the problem and gives wrong totals. Merge joins tables rather than stacking them.

Q10 Answer: B, C P3 · Transform and load the data

A relationship needs one column on each side, so build a combined key in both tables and relate on it. Power BI allows only one active relationship between two tables. Relating on one column alone would match the wrong rows.

Q11 Answer: E → F → D → B P3 · Transform and load the data

Generate the dates, convert them to a typed table, add the attributes reports need, then mark the table as a date table after loading so time intelligence uses it. Marking happens in the model, not in Power Query.

Q12 Answer: B M1 · Design and implement a data model

A sort-by column must have exactly one value for each value of the column being sorted. "January" has several MonthKey values (one per year), so the sort fails. MonthNumber has one value per month name. Date has many values per month name too.

Q13 Answer: B M1 · Design and implement a data model

A hierarchy groups levels so authors drag one field and users can drill up and down. Calculated columns add fields but not drill behaviour. Calculation groups change measures. Bookmarks store views.

Q14 Answer: B M1 · Design and implement a data model

Calculated tables are DAX tables built from data already in the model, such as a copy of the Date table for another role, or a disconnected parameter table. Cleaning and combining source files is a Power Query task done before loading.

Q15 Answer: Yes · No · Yes M1 · Design and implement a data model

Numeric attributes such as Year or ID shouldn't be aggregated, so set them to Don't summarize. Data category only describes the meaning of the values, mainly for maps, and doesn't change the data type. Model-level formats apply everywhere the column is used.

Q16 Answer: A M2 · Create model calculations by using DAX

TOTALQTD accumulates from the start of the quarter to the last date in context. TOTALYTD with a year-end date is a fiscal year-to-date. DATESQTD takes a date column, not a measure, and returns dates. QUARTER returns a number, which isn't a valid filter.

Q17 Answer: D M2 · Create model calculations by using DAX

A measure reference is wrapped in an implicit CALCULATE, which converts the row context into a filter context on that customer. SUM in a calculated column has a row context but no filter context, so it sums the whole Sales table.

Q18 Answer: A M2 · Create model calculations by using DAX

TOPN returns the five products with the highest sales, and CALCULATE uses that table as a filter on the sales measure. TOPN on its own returns a table, not a value. Ranking over 'Product' without ALL follows the visual's filters, so the top five change with them. MAXX times five isn't the top-five total.

Q19 Answer: B M2 · Create model calculations by using DAX

PERCENTILE.INC returns the value at the given percentile, here the 90th. Ninety percent of the average isn't a percentile. MAX returns the worst case. Standard deviation measures spread, not a threshold.

Q20 Answer: 1→C 2→E 3→B 4→D M2 · Create model calculations by using DAX

FIRSTDATE returns the first date in context. LASTNONBLANK finds the last date where an expression isn't blank. DATEADD shifts dates by an interval. DATESBETWEEN returns a fixed range. TOTALYTD accumulates the year, which none of these need.

Q21 Answer: B M3 · Optimize model performance

Reducing granularity to what the reports use can cut row count by orders of magnitude, which shrinks the model and speeds up queries. Hiding a column doesn't reduce storage. DirectQuery moves the problem to the source. A calculated column adds size.

Q22 Answer: A M3 · Optimize model performance

Many-to-many relationships on high-cardinality text keys are expensive. A proper dimension with integer keys gives efficient one-to-many relationships. Bidirectional filtering usually adds cost. The other options don't address the relationship.

Q23 Answer: A V1 · Create reports

COLLAPSEALL evaluates the expression at the top of the row axis, the grand total, so dividing by it gives the share of total. The CALCULATE version is model DAX, not a visual calculation. RUNNINGSUM accumulates. PREVIOUS compares with the previous row.

Q24 Answer: C V1 · Create reports

Small multiples split a visual into a grid of copies, one per value of a field, with consistent axes. Copying the chart six times is harder to maintain. A matrix shows numbers, not charts. Drillthrough shows one region at a time.

Q25 Answer: C V1 · Create reports

A locked filter is visible to viewers but can't be changed. A hidden filter still applies but isn't shown. Deleting removes the restriction. A slicer is designed to be changed.

Q26 Answer: B V1 · Create reports

The narrative visual with Copilot generates a summary of the report's data and refreshes it as filters change. A text box is static. Q&A answers questions users type. A bookmark navigator moves between bookmarks.

Q27 Answer: C V2 · Enhance reports for usability and storytelling

With Current page cleared, the bookmark applies its captured state without switching to the page where it was created. Data controls filters and slicers, which you need. Display controls visibility. All visuals vs Selected visuals controls scope.

Q28 Answer: B V2 · Enhance reports for usability and storytelling

Edit interactions offers Filter, Highlight and None for each target visual. Highlight dims the parts that don't match. Filter redraws the visual with only matching data. The other options don't change cross-visual behaviour.

Q29 Answer: B V2 · Enhance reports for usability and storytelling

Accessible design never relies on colour alone: different marker shapes or line styles, plus clear labels, let everyone tell the series apart. Thickness and background don't solve the colour problem. Removing the legend makes it worse.

Q30 Answer: B V2 · Enhance reports for usability and storytelling

A button with the Drill through action is disabled until a valid selection is made, then opens the destination page filtered to the selection. Page navigation doesn't pass the selection. Bookmarks and Q&A do other things.

Q31 Answer: F → E → D → B V2 · Enhance reports for usability and storytelling

The mobile layout is designed per page from the View ribbon. Visuals are placed on the phone canvas explicitly, then the layout is used by the mobile app after publishing.

Q32 Answer: A V3 · Identify patterns and trends

Top segments finds groups of attribute combinations where the outcome is unusually likely, and describes their size and rate. The Key influencers tab ranks individual factors. A manual decomposition tree needs the user to guess the splits. A funnel shows stages.

Q33 Answer: C V3 · Identify patterns and trends

The Analytics pane adds reference lines, including min, max, average, median and percentile lines, which recalculate as the data changes. Data labels and top N filters don't draw a reference line.

Q34 Answer: D V3 · Identify patterns and trends

Seasonality tells the forecast how many points make one cycle. Monthly data with a yearly pattern has a seasonality of 12. The confidence interval only changes the band's width. Visual type and labels don't change the model.

Q35 Answer: C S1 · Create and manage workspaces and assets

Refresh failure notifications can go to the model owner and to listed contacts. Data alerts react to tile values, and subscriptions send report snapshots. Neither reports on refresh failures.

Q36 Answer: D S1 · Create and manage workspaces and assets

Deployment rules change data sources or parameter values when content is deployed to a stage, so one model definition connects to the correct database in each stage. Separate files defeat the purpose of the pipeline. Gateways and labels don't change connections.

Q37 Answer: D S1 · Create and manage workspaces and assets

An app shows a published snapshot of the workspace content. Changes reach app users only when the app is updated. Refreshing data doesn't publish report changes. Re-sharing bypasses the app.

Q38 Answer: C S2 · Secure and govern Power BI items

Members can add people with the Member role or lower, share content and publish the app. Only Admins can delete the workspace and manage all its settings. Contributors and Viewers can't add people to the workspace.

Q39 Answer: D S2 · Secure and govern Power BI items

Test as role on the semantic model's Security page opens the report with that role's filters applied, and you can also test as a specific user. Workspace and app settings don't apply roles. Performance Analyzer is a Desktop timing tool.

Q40 Answer: A S2 · Secure and govern Power BI items

A mandatory labelling policy makes users apply a label when they save or publish content, so nothing is left unlabelled. Certification is endorsement. Roles control access. Page refresh is unrelated.

Q41 Answer: Yes · No · Yes S2 · Secure and govern Power BI items

Publish to web creates a public, anonymous link, so it's only for non-sensitive content. Reports whose models use RLS can't be published to web. Admins control the feature through a tenant setting and can manage existing embed codes.

Q42 Answer: A P2 · Profile and clean the data

Splitting separates the amount from the CR/DR indicator, the amount can then be typed as a number, and a conditional column applies the sign. Changing the type of the combined text fails with errors. Replacing errors with 0 loses every balance. Fill down doesn't apply.

Q43 Answer: D M2 · Create model calculations by using DAX

CLOSINGBALANCEMONTH evaluates the expression on the last date of the month. Snapshots exist for every calendar day, so that date always has data. A plain SUM or TOTALMTD adds daily balances together, which overstates the balance. An average is a different metric.

Q44 Answer: B V1 · Create reports

Formatting by field value uses a measure or column that returns a colour, so the colours come from the risk team's data and change when they change. Typed rules would need editing whenever the colours change. A gradient doesn't use their colours, and a theme isn't per cell.

Q45 Answer: A S1 · Create and manage workspaces and assets

A gateway cluster with several members provides high availability: if one machine is unavailable, requests go to another member. A personal gateway is single-user and still one machine. Changing the time or roles doesn't remove the single point of failure.

Report craft and storytelling

Visual choice, formatting, tooltips, bookmarks and navigation, accessibility and AI visuals, plus the core of every other domain.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 2 · Core

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

A government web page publishes a table of regional population figures in HTML. You want to load it into Power BI and refresh it. Which connector should you use?

- ☐ A SharePoint folder
- ☐ B Text/CSV, pointing at the page's URL
- ☐ C Blank query with the figures typed in by hand
- ☐ D Web, then pick the table in the Navigator

Q2 SINGLE ANSWER

While developing, you want Power BI Desktop to load only the first 1,000 rows of a 200-million-row source, but the published model must load everything. What is a clean way to do this?

- ☐ A Delete rows in the source during development, then restore them before publishing
- ☐ B Turn off Enable load in Desktop and turn it back on in the service
- ☐ C Use a slicer to show 1,000 rows
- ☐ D A RowLimit parameter in a Keep top rows step, set high in the service

Q3 SINGLE ANSWER

A composite model has a DirectQuery Sales fact and an Import aggregation table. The Product dimension relates to both. To avoid limited relationships and let the engine choose the fastest path, which storage mode should Product use?

- ☐ A Dual
- ☐ B Live connection
- ☐ C Import
- ☐ D DirectQuery

Q4 SINGLE ANSWER

A Comments column contains empty text (""), rather than null, so Column quality reports it as 0% empty. You want empty strings treated as missing values. What should you do?

- ☐ A Use Replace values, replacing empty text with null
- ☐ B Use Trim
- ☐ C Change the type to Whole Number
- ☐ D Use Remove empty from the filter menu on every column

Q5 SINGLE ANSWER

A source export sometimes contains exact duplicate rows, identical in every column, because of a bug. What is the correct fix in Power Query?

- ☐ A Keep duplicates
 - ☐ B Select only the first column, then Remove duplicates
 - ☐ C Group by every column with Count rows and keep the count
 - ☐ D Select all columns, then Remove duplicates
-

Q6 SINGLE ANSWER

A query previews without errors in Power Query, but refresh fails with "DataFormat.Error: We couldn't convert to Number". What is the most likely cause?

- ☐ A A value outside the preview rows can't be converted
 - ☐ B The model has too many relationships for the refresh to complete
 - ☐ C The report theme is invalid
 - ☐ D The gateway is offline, so the source can't be read during refresh
-

Q7 SINGLE ANSWER

After merging Sales with Region and expanding RegionName, the new column is named "Region.RegionName". You want it named "RegionName" without adding a rename step. What should you do when expanding?

- ☐ A Clear Use original column name as prefix
 - ☐ B Expand every column
 - ☐ C Select Aggregate instead of Expand
 - ☐ D Choose a Left anti join
-

Q8 SINGLE ANSWER

A ProductLabel column holds text like "Trail Bike [TB-200]". You need just the code inside the square brackets. Which transformation needs no code?

- ☐ A Extract → Text between delimiters, using [and]
- ☐ B Split column → By number of characters
- ☐ C Replace values
- ☐ D Format → Clean

Q9 DRAG AND DROP — MATCH

Match each column to the most appropriate data type.

Choices — each may be used once, more than once, or not at all

- ☐ A Whole number
- ☐ B Date/Time
- ☐ C True/False
- ☐ D Text
- ☐ E Fixed decimal number

Column	Data type
1. Postal code such as 01234	
2. Unit price stored to four decimal places	
3. Order timestamp where the hour matters	
4. IsActive flag with values TRUE and FALSE	

Q10 SINGLE ANSWER

An XML file contains Orders elements, each with nested OrderLine elements. You need one row per order line, with the order number on each row. What should you do after connecting?

- ☐ A Append the query to itself
- ☐ B Expand the nested OrderLine table column
- ☐ C Pivot the OrderLine column on the order number
- ☐ D Transpose the table

Q11 BUILD LIST — SEQUENCE

An Excel export has three title rows, then a header row, then one column per month. You need a clean table with Product, Month and Value. Put the actions in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Select Product and choose Unpivot other columns
- ☐ B Rename Attribute to Month and set the data types
- ☐ C Transpose the table
- ☐ D Remove duplicates on Product
- ☐ E Use first row as headers
- ☐ F Remove the top 3 rows

Q12 SINGLE ANSWER

In model view, a relationship between Sales and Date is drawn as a dashed line. What does that mean?

- ☐ A It is a many-to-many relationship
- ☐ B It is a limited relationship, because one side is a DirectQuery source
- ☐ C It is a bidirectional relationship
- ☐ D It is inactive and only used when a measure calls USERELATIONSHIP

Q13 SINGLE ANSWER

A Product table has a column of image addresses. Table visuals must show the product picture. Which property should you set?

- ☐ A Data category: Image URL
- ☐ B Format: Text
- ☐ C Data category: Web URL
- ☐ D Summarize by: Count

Q14 SINGLE ANSWER

A model has 60 measures in one table, and authors struggle to find them. You want them grouped as Sales, Margin and Inventory in the field list, without changing any DAX. What should you use?

- ☐ A Three new tables with one measure each
- ☐ B Display folders on the measures
- ☐ C Perspectives in Desktop
- ☐ D Calculation groups

Q15 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about relationships in Power BI, select Yes if it is true.

Statement	Yes	No
1. Only one relationship between two tables can be active at a time.	☐	☐
2. On the one side of a one-to-many relationship, the column must contain unique values.	☐	☐
3. You can create a relationship between a Text column and a Whole Number column.	☐	☐

Q16 SINGLE ANSWER

In a matrix with Category and Product rows, a measure must show each product's share of its own category. Which expression is correct?

- ☐ A `DIVIDE ( [Sales], CALCULATE ( [Sales], ALL ( 'Product' ) ) )`
- ☐ B `DIVIDE ( [Sales], CALCULATE ( [Sales], ALLEXCEPT ( 'Product', 'Product'[Category] ) ) )`
- ☐ C `DIVIDE ( [Sales], [Sales] )`
- ☐ D `DIVIDE ( [Sales], CALCULATE ( [Sales], ALLSELECTED ( ) ) )`

Q17 SINGLE ANSWER

A card's title must read "Sales for North" when one region is selected, and "Sales for all regions" otherwise. Which measure should drive the title?

- ☐ A `"Sales for " & VALUES ( Region[Region] )`
- ☐ B `"Sales for " & MAX ( Region[Region] )`
- ☐ C `"Sales for " & SELECTEDVALUE ( Region[Region], "all regions" )`
- ☐ D `"Sales for " & FIRSTNONBLANK ( Region[Region], 1 )`

Q18 SINGLE ANSWER

You need the number of customers with no sales in the selected period. Which measure is correct?

- ☐ (A) COUNTROWS (FILTER (Customer, ISBLANK ([Total Sales])))
 - ☐ (B) COUNTBLANK (Sales[Amount])
 - ☐ (C) DISTINCTCOUNT (Sales[CustomerKey])
 - ☐ (D) COUNTROWS (Customer) - COUNTROWS (Sales)
-

Q19 SINGLE ANSWER

Survey scores come from a random sample of customers, and analysts want the standard deviation as an estimate for the whole customer base. Which function should you use?

- ☐ (A) STDEV.P
 - ☐ (B) STDEV.S
 - ☐ (C) VAR.P
 - ☐ (D) MEDIAN
-

Q20 SINGLE ANSWER

You need the average sales per customer, counting only customers who bought in the current filter context. Which measure is correct?

- ☐ (A) [Total Sales] / COUNTROWS (Customer)
 - ☐ (B) AVERAGE (Sales[Amount])
 - ☐ (C) AVERAGEX (Sales, Sales[Amount])
 - ☐ (D) AVERAGEX (VALUES (Sales[CustomerKey]), [Total Sales])
-

Q21 SINGLE ANSWER

Complete the YTD calculation item in a calculation group so it applies to whatever measure is in the visual.

`CALCULATE ( ____, DATESYTD ( 'Date'[Date] ) )`

- ☐ (A) SELECTEDMEASURE ()
 - ☐ (B) [Total Sales]
 - ☐ (C) ISSELECTEDMEASURE ()
 - ☐ (D) SELECTEDVALUE ('Date'[Date])
-

Q22 SINGLE ANSWER

Performance Analyzer shows a map visual with 30,000 points has a short DAX query time but a very long Visual display time. What should you do?

- ☐ (A) Turn off Auto date/time
- ☐ (B) Rewrite the measure with variables to cut query time
- ☐ (C) Add an index column to the location table to speed lookups
- ☐ (D) Render fewer points by aggregating or filtering

Q23 SINGLE ANSWER

Performance Analyzer identifies a slow visual. You want to inspect and rerun the exact DAX that the visual sends to the model. What is the quickest route?

- ☐ A Use Analyze in Excel and inspect the PivotTable's query
 - ☐ B Export the visual's data to CSV and inspect it in Excel
 - ☐ C Open Power Query and refresh
 - ☐ D Copy query, then run it in DAX query view
-

Q24 SINGLE ANSWER

For one report only, you want to change the eight data colours. The corporate theme must stay unchanged for other reports. What is quickest?

- ☐ A Apply conditional formatting to every visual
 - ☐ B Edit the corporate JSON theme file, then re-import it here
 - ☐ C Change the Windows display colours
 - ☐ D Customize current theme and change the data colours
-

Q25 SINGLE ANSWER

A chart title must change to reflect the selected region. You have a measure that returns the title text. How do you use it?

- ☐ A Put the measure in the Tooltips well
 - ☐ B Create a bookmark per region, each with its own typed title
 - ☐ C Title → fx → Field value, choosing the measure
 - ☐ D Type the measure name in square brackets into the title text
-

Q26 SINGLE ANSWER

A Region slicer must allow only one region to be selected at a time. What should you configure?

- ☐ A Lock the slicer in the Filters pane
 - ☐ B Turn on Single select in the slicer settings
 - ☐ C Set the slicer style to Dropdown in the format settings
 - ☐ D Add a visual-level filter
-

Q27 SINGLE ANSWER

A visual must colour each state of a country by its sales value, filling the state's shape. Which visual fits best?

- ☐ A Map (bubble map)
- ☐ B Gauge
- ☐ C Filled map
- ☐ D Scatter chart

Q28 SINGLE ANSWER

A table shows profit variance, which can be negative or positive. The background must be red for negatives, white at zero and green for positives, with smooth shading. What should you configure?

- ☐ A A theme with three colours
 - ☐ B Gradient background colour with a middle colour at 0
 - ☐ C Data bars with red negative and green positive bars
 - ☐ D Icon conditional formatting with three rules (below, at and above 0)
-

Q29 SINGLE ANSWER

You built a report-page tooltip called Trend Tooltip. It must appear only when users hover over the Sales by Month chart, not on other visuals. What should you do?

- ☐ A Turn on Allow use as tooltip on every page of the report
 - ☐ B On the chart, set the tooltip to the Trend Tooltip page
 - ☐ C Add the chart to a bookmark
 - ☐ D Set the Trend Tooltip page's canvas size to Letter
-

Q30 SINGLE ANSWER

During a presentation, you want one visual to stand out while the others on the page fade into the background, and you want to save that state. What should you use?

- ☐ A Spotlight, captured in a bookmark
 - ☐ B Change the theme to dark
 - ☐ C Focus mode exported to PDF
 - ☐ D Hide all other visuals permanently
-

Q31 SINGLE ANSWER

Users' slicer and filter changes are kept when they return to a report, but management wants every visit to start with the author's default filters. What should you change?

- ☐ A Delete the bookmarks
 - ☐ B Lock every slicer
 - ☐ C Turn off persistent filters in the report settings
 - ☐ D Remove the users' Build permission on the semantic model
-

Q32 SINGLE ANSWER

On a kiosk-style report, viewers keep opening visual menus (export, focus mode, sort) from the icons above each visual. The author wants those icons gone for viewers. What should you change?

- ☐ A Remove the report theme
- ☐ B Set Edit interactions to None for every visual
- ☐ C Turn off the visual header in the format settings
- ☐ D Lock and hide the Filters pane in the report settings

Q33 SINGLE ANSWER

A scatter chart of advertising spend against sales should show the overall direction of the relationship as a straight line. Where do you add it?

- ☐ A Filters pane → Top N
 - ☐ B Analytics pane → Trend line
 - ☐ C Analytics pane → Forecast
 - ☐ D Format pane → Data labels
-

Q34 SINGLE ANSWER

A user typed a question in the Q&A visual and got a good bar chart. You want to keep it as a normal visual on the page. What should you do?

- ☐ A Take a screenshot
 - ☐ B Pin the Q&A visual to a dashboard as a new tile
 - ☐ C Turn this Q&A result into a standard visual
 - ☐ D Create a bookmark
-

Q35 SINGLE ANSWER

A new workspace must run on the organisation's Fabric capacity so that features such as Copilot and free-licence viewing are available. Where do you set this?

- ☐ A The data gateway's connection settings for the workspace
 - ☐ B Report settings in Power BI Desktop, before publishing
 - ☐ C Workspace settings → License info, choosing Fabric capacity
 - ☐ D The app's audience settings, choosing a capacity per audience
-

Q36 SINGLE ANSWER

A dashboard tile must keep the interactivity of a whole report page, including its slicers, rather than being a static visual. What should you pin?

- ☐ A A Q&A answer
 - ☐ B A screenshot of the page uploaded as an image tile
 - ☐ C The whole report page, as a live page tile
 - ☐ D Each visual separately
-

Q37 SINGLE ANSWER

A workspace admin wants to know which reports are actually viewed, by how many people, and how often. What should they use?

- ☐ A The deployment pipeline's compare view between stages
- ☐ B Query dependencies
- ☐ C Usage metrics for the reports in the workspace
- ☐ D Performance Analyzer

Q38 MULTIPLE RESPONSE — CHOOSE TWO

Which two types of content can you include in a workspace app?

- ☐ A On-premises data gateways
 - ☐ B Deployment pipelines
 - ☐ C Tenant settings
 - ☐ D Reports
 - ☐ E Dashboards
-

Q39 SINGLE ANSWER

A semantic model's report users currently have Build permission, but only the analytics team should be able to create new reports on it. Everyone else must keep viewing the existing reports. What should you do?

- ☐ A Remove Build from all but the analytics team, keeping Read
 - ☐ B Remove everyone except the analytics team from the workspace
 - ☐ C Turn off Publish to web
 - ☐ D Apply a sensitivity label that restricts report creation
-

Q40 SINGLE ANSWER

Your organisation wants new Power BI reports and models to receive the General sensitivity label automatically, so users only change it when needed. What should be configured?

- ☐ A A deployment rule
 - ☐ B A default label in the Purview label policy
 - ☐ C An app audience
 - ☐ D A certification setting in the tenant admin portal
-

Q41 SINGLE ANSWER

One RLS role must show both the North and South regions. Which filter expression on the Region table is correct?

- ☐ A `Region[Region] = "North, South"`
- ☐ B `CONTAINSSTRING ( "North", "South" )`
- ☐ C `Region[Region] IN { "North", "South" }`
- ☐ D `Region[Region] = "North" && Region[Region] = "South"`

Existing environment

Litware runs 25 clinics. Appointments are stored in Azure SQL Database. After each visit, patients complete a satisfaction survey stored in a SharePoint Online list. The report has six pages. Each clinic has a manager, and a small head-office team oversees all clinics.

Requirements

1. Survey responses must refresh with the rest of the model, with no gateway to maintain.
2. At the monthly board meeting, the analyst must walk through six saved views of the report in a fixed order, some of which switch between a chart and a table.
3. Operations wants to break average wait time down by clinic, then doctor, then appointment type, to see which contributes most.
4. Clinic managers must see only their own clinic. The head-office team must see all clinics through the same report.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

How should you connect to the survey responses?

- ☐ A Export the list to CSV every month
- ☐ B The SharePoint Online list connector
- ☐ C A blank query with the data pasted in
- ☐ D The on-premises data gateway with the Folder connector

Q43 SINGLE ANSWER

How should you support the board walk-through?

- ☐ A Use automatic page refresh to cycle through the views
- ☐ B Create six separate reports and link them with buttons
- ☐ C Use Edit interactions
- ☐ D A bookmark per view, stepped through in order

Q44 SINGLE ANSWER

Which visual meets the operations requirement?

- ☐ A Decomposition tree
- ☐ B Card
- ☐ C Ribbon chart
- ☐ D Key influencers

Q45 SINGLE ANSWER

You have a dynamic Clinic role that filters by the signed-in manager's email. How do you let the head-office team see all clinics?

- ☐ A Add the head-office team to the existing Clinic role as members
- ☐ B Give the head-office team the workspace Viewer role
- ☐ C Remove RLS from the model
- ☐ D Add the group to a second role, AllClinics, with no filter

End of Set 05 — answers follow on the next page.

Set 05 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	D	P1		16	B	M2		31	C	V2	
2	D	P1		17	C	M2		32	C	V2	
3	A	P1		18	A	M2		33	B	V3	
4	A	P2		19	B	M2		34	C	V3	
5	D	P2		20	D	M2		35	C	S1	
6	A	P2		21	A	M2		36	C	S1	
7	A	P3		22	D	M3		37	C	S1	
8	A	P3		23	D	M3		38	D, E	S1	
9	1→D 2→E 3→B 4→C	P3		24	D	V1		39	A	S2	
10	B	P3		25	C	V1		40	B	S2	
11	F → E → A → B	P3		26	B	V1		41	C	S2	
12	D	M1		27	C	V1		42	B	P1	
13	A	M1		28	B	V1		43	D	V2	
14	B	M1		29	B	V2		44	A	V3	
15	Yes · Yes · No	M1		30	A	V2		45	D	S2	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: **D** P1 · Get or connect to data

The Web connector reads an HTML page and offers the tables it detects in the Navigator, and the query refreshes from the page. Text/CSV expects a file. A typed table never refreshes. SharePoint folder is for document libraries.

Q2 Answer: D P1 · Get or connect to data

A parameter-driven row limit keeps development fast, and the parameter can be changed in the semantic model settings after publishing, without editing the query. A slicer only filters what's shown. Disabling load removes the table altogether.

Q3 Answer: A P1 · Get or connect to data

Dual tables act as Import or DirectQuery depending on the query. Queries that hit the Import aggregation use the in-memory copy, and queries that reach the DirectQuery fact can join at the source. A pure Import or pure DirectQuery dimension forces one of the two paths to be inefficient.

Q4 Answer: A P2 · Profile and clean the data

Replacing empty text with null makes missing values consistent, so profiling, filters and DAX treat them as blank. Trim only removes spaces. Changing the type to a number creates errors. Removing empty rows deletes data.

Q5 Answer: D P2 · Profile and clean the data

Removing duplicates across all columns removes only rows that are identical in every column. Using a single column could delete legitimate rows that share a value. Keep duplicates does the opposite.

Q6 Answer: A P2 · Profile and clean the data

The editor previews and profiles a sample of rows, and the full refresh processes everything. A bad value later in the data, such as text in a numeric column, only fails during refresh. Profiling the entire data set or checking the source's values finds it.

Q7 Answer: A P3 · Transform and load the data

The expand dialog adds the merged column's name as a prefix by default. Clearing that option keeps the original field names. Aggregate summarises the nested table instead of expanding it. Join kind doesn't change column names.

Q8 Answer: A P3 · Transform and load the data

Text between delimiters returns the part between the start and end delimiter, whatever the label's length. A fixed character count fails for labels of different lengths. Replace values and Clean don't extract substrings.

Q9 Answer: 1→D 2→E 3→B 4→C P3 · Transform and load the data

Identifiers with leading zeros are text. Currency-style amounts are best as fixed decimal. A timestamp needs Date/Time when the time part is used. Flags are True/False. Whole number would lose decimals and leading zeros.

Q10 Answer: B P3 · Transform and load the data

Semi-structured data arrives as nested tables or records. Expanding the nested column produces one row per child element, alongside its parent's fields. Transposing and pivoting reshape flat tables and don't flatten nesting.

Q11 Answer: F → E → A → B P3 · Transform and load the data

Title rows must go before the real header row can be promoted. Unpivot other columns then turns the month columns into rows, and the final step names and types the result.

Q12 Answer: D M1 · Design and implement a data model

Inactive relationships are drawn with a dashed line and are only used when activated with USERELATIONSHIP in a calculation. Cardinality and direction are shown with markers and arrows. Limited relationships are shown with different markers, not a dashed line.

Q13 **Answer: A** M1 · Design and implement a data model

With the Image URL data category, table, matrix, slicer and card visuals render the address as an image. Web URL shows a clickable link. Format and summarisation don't render images.

Q14 **Answer: B** M1 · Design and implement a data model

Display folders organise fields into folders in the field list, purely for navigation. Calculation groups change how measures calculate. Moving measures into many tables is clumsy. Perspectives aren't authored in the Desktop UI and aren't a security feature.

Q15 **Answer: Yes · Yes · No** M1 · Design and implement a data model

Power BI allows one active relationship between two tables, and others stay inactive. The one side must be unique, or the model can't treat it as one. Relationship columns must have matching data types, so text and number columns must first be converted to the same type.

Q16 **Answer: B** M2 · Create model calculations by using DAX

ALLEXCEPT removes every filter on Product except Category, so the denominator is the current category's total. ALL('Product') gives the grand total. ALLSELECTED gives the visible total. Dividing a measure by itself returns 1.

Q17 **Answer: C** M2 · Create model calculations by using DAX

SELECTEDVALUE returns the single selected value, or the alternate text when there are zero or several. VALUES errors when more than one value is visible. MAX and FIRSTNONBLANK return a region name even when several are selected, which would mislead.

Q18 **Answer: A** M2 · Create model calculations by using DAX

FILTER iterates customers, and context transition evaluates [Total Sales] for each customer in the period, so ISBLANK finds those with no sales. COUNTBLANK counts blank amounts in fact rows. Subtracting row counts mixes customers with order lines. DISTINCTCOUNT counts customers who did buy.

Q19 **Answer: B** M2 · Create model calculations by using DAX

STDEV.S estimates standard deviation from a sample, using $n - 1$. STDEV.P assumes the data is the whole population. VAR.P is population variance, not standard deviation. MEDIAN is a measure of central tendency.

Q20 **Answer: D** M2 · Create model calculations by using DAX

VALUES returns the customers present in the filtered sales, and AVERAGEX averages each customer's total. AVERAGE over Sales[Amount] is the average line value. Dividing by all customers includes those who didn't buy. AVERAGEX over Sales rows is still a line average.

Q21 **Answer: A** M2 · Create model calculations by using DAX

SELECTEDMEASURE returns the measure currently being evaluated, which is how one calculation item applies to every measure. Hard-coding [Total Sales] would make the item work for only one measure. SELECTEDVALUE returns a date. ISSELECTEDMEASURE tests which measure is in use.

Q22 **Answer: D** M3 · Optimize model performance

Visual display time is spent drawing the result, and too many points is a common cause. Showing fewer points speeds rendering. The query is already fast, so rewriting DAX won't help.

Q23 **Answer: D** M3 · Optimize model performance

Copy query captures the DAX the visual generated, and DAX query view lets you run and edit it inside Desktop, including trying alternative measure definitions. The other options don't show the visual's query.

Q24 Answer: D V1 · Create reports

Customize current theme changes the theme saved in this report only, without editing the shared JSON file. Editing the corporate file would affect every report that uses it. Conditional formatting per visual is laborious.

Q25 Answer: C V1 · Create reports

Titles, like many text properties, accept conditional formatting by field value, so a measure can supply dynamic text. Typing the name shows it literally. Bookmarks per region don't scale. Tooltips appear on hover only.

Q26 Answer: B V1 · Create reports

Single select limits a slicer to one value. Dropdown changes how it's displayed, not how many values can be picked. Filters and locking don't change slicer selection behaviour.

Q27 Answer: C V1 · Create reports

A filled map (choropleth) shades geographic areas such as states by value. A bubble map places circles sized by value at locations. Scatter charts and gauges aren't geographic.

Q28 Answer: B V1 · Create reports

Gradient formatting with minimum, centre and maximum colours (centre fixed at 0) gives diverging shading. Data bars show length, not colour scales. Icons are discrete symbols. A theme doesn't colour cells by value.

Q29 Answer: B V2 · Enhance reports for usability and storytelling

Setting a visual's tooltip to a specific report page connects that page to that visual only. Allow use as tooltip is required on the tooltip page itself, but it doesn't choose which visuals use it. Bookmarks and page sizes don't control this.

Q30 Answer: A V2 · Enhance reports for usability and storytelling

Spotlight fades every other visual on the page, and a bookmark can capture that display state for the presentation. Focus mode opens one visual full screen but isn't stored with Display state in the same way. Hiding visuals permanently removes them.

Q31 Answer: C V2 · Enhance reports for usability and storytelling

Persistent filters keep each user's last filter state by default. Turning the setting off means everyone starts from the published state. Locking applies to filter-pane filters, not to slicers. Bookmarks and permissions don't control this.

Q32 Answer: C V2 · Enhance reports for usability and storytelling

The visual header holds the icons and menus above a visual. Turning it off hides them in the service. Locking filters or changing interactions doesn't remove the header.

Q33 Answer: B V3 · Identify patterns and trends

A trend line fits a linear trend through the scatter points. Forecasts apply to line charts with a time axis. Data labels and top N filters don't show a trend.

Q34 Answer: C V3 · Identify patterns and trends

Q&A can convert its current answer into a regular visual with the same fields, which you can then format like any other. A screenshot is static. Pinning and bookmarks keep the Q&A visual rather than converting it.

Q35 Answer: C S1 · Create and manage workspaces and assets

A workspace's licence mode and capacity assignment are set in the workspace settings. Reports, gateways and app audiences don't decide which capacity a workspace uses.

Q36 Answer: C S1 · Create and manage workspaces and assets

Pinning a live page puts the whole page on the dashboard as an interactive tile that keeps its slicers and visuals. Pinning individual visuals creates separate tiles. A screenshot isn't interactive.

Q37 Answer: C S1 · Create and manage workspaces and assets

Usage metrics reports show views, viewers and trends for reports and dashboards. Performance Analyzer measures load times in Desktop. Pipeline compare shows differences between stages. Query dependencies shows Power Query lineage.

Q38 Answer: D, E S1 · Create and manage workspaces and assets

Apps package content from a workspace, such as reports, dashboards, paginated reports and workbooks, for consumers. Gateways, pipelines and tenant settings are infrastructure and administration items, not app content.

Q39 Answer: A S2 · Secure and govern Power BI items

Read lets users view reports built on the model, and Build lets them create new content on it. Managing these on the model gives the right split. Removing workspace access would also stop viewing. Labels and Publish to web don't control Build.

Q40 Answer: B S2 · Secure and govern Power BI items

Label policies can set a default label applied to new content, so nothing starts unlabelled. Certification is endorsement. App audiences control visibility. Deployment rules change data sources between pipeline stages.

Q41 Answer: C S2 · Secure and govern Power BI items

IN with a list returns TRUE for either value. Two equality tests joined with AND can never both be true on one row. Comparing to one combined string matches nothing. The CONTAINSSTRING expression doesn't reference the column.

Q42 Answer: B P1 · Get or connect to data

The SharePoint Online list connector reads the list directly from the cloud, so scheduled refresh needs no gateway. CSV exports and pasted data don't refresh. A gateway and the Folder connector are for on-premises files.

Q43 Answer: D V2 · Enhance reports for usability and storytelling

Bookmarks capture each view, including chart/table visibility and filter state, and can be stepped through in order like slides. Separate reports or interaction settings don't create a sequence. Page refresh is unrelated.

Q44 Answer: A V3 · Identify patterns and trends

A decomposition tree breaks a measure down across several dimensions in the order the user chooses, showing each level's contribution. Key influencers ranks factors for an outcome rather than drilling hierarchically. A ribbon chart shows rank over time.

Q45 Answer: D S2 · Secure and govern Power BI items

A role with no filter grants access to all rows, and adding the head-office group to it gives them every clinic, since RLS roles are additive. Viewer access alone is still filtered by RLS. Removing RLS exposes everything to everyone. Adding head office to the Clinic role filters them by their own email, which matches no clinic.

Service, sharing and security

Gateways, credentials, apps, subscriptions, alerts, roles, RLS and external sharing, alongside the full modelling and reporting outline.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 2 · Core

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

Opportunity and account data lives in Dynamics 365 Sales. Which connector is the recommended way to bring it into Power BI?

- ☐ A Web
- ☐ B OData feed to the user's mailbox
- ☐ C Folder
- ☐ D Dataverse

Q2 SINGLE ANSWER

A model merges a SQL Server table and a SharePoint list. Both contain internal company data that may safely be combined, and you want folding to work. Which privacy levels should you set?

- ☐ A None for both
- ☐ B Private for both sources
- ☐ C Organizational for both sources
- ☐ D Public for the SQL source and Private for SharePoint

Q3 BUILD LIST — SEQUENCE

You published a semantic model that imports from an Azure SQL Database, and scheduled refresh fails because no credentials are stored in the service. Put the actions in order to get it refreshing daily.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Choose the authentication method and sign in
- ☐ B Use Publish to web
- ☐ C Install a personal-mode gateway
- ☐ D Turn on scheduled refresh and set the daily time
- ☐ E Open the semantic model's settings in the workspace
- ☐ F Expand Data source credentials and choose Edit credentials

Q4 SINGLE ANSWER

Your company has an Azure Analysis Services model with all enterprise measures. Report authors must build reports on it without creating a local model. How should they connect?

- ☐ A Connect live to the Analysis Services model
- ☐ B Use a dataflow to copy the model
- ☐ C Import the model's tables with the SQL Server connector
- ☐ D Use the Excel connector on an exported workbook

Q5 SINGLE ANSWER

A PaymentType column contains Card, card and CARD. Power Query treats them as three values, and the totals don't reconcile. What is the best fix?

- ☐ A Filter out the lowercase and mixed-case values
 - ☐ B Change the column to Whole Number
 - ☐ C Remove duplicates on PaymentType, keeping the first spelling
 - ☐ D Apply Format → Capitalize Each Word or Uppercase
-

Q6 SINGLE ANSWER

Column profile shows negative values in Quantity. The business confirms they are product returns, not errors. Returns must stay in the data but be easy to analyse separately. What should you do?

- ☐ A Change Quantity to Text
 - ☐ B Add a conditional column flagging rows with Quantity < 0 as "Return"
 - ☐ C Replace negative values with 0 and keep the rows
 - ☐ D Move the negative rows into a separate Returns query that isn't loaded
-

Q7 SINGLE ANSWER

The automatic Changed Type step detected a ProductCode column as Whole Number because the first rows look numeric. Later rows contain codes such as "A1023", which become errors. What should you do?

- ☐ A Turn off Column quality
 - ☐ B Change the column's type to Text
 - ☐ C Remove errors
 - ☐ D Replace errors with 0 after the Changed Type step
-

Q8 SINGLE ANSWER

You need one row per Region showing total sales and the most recent order date. Which Power Query approach does this in one step?

- ☐ A Remove duplicates on Region
 - ☐ B Group by Region (Basic) with Sum of Sales, then sort by OrderDate
 - ☐ C Group by Region (Advanced): Sum of Sales, Max of OrderDate
 - ☐ D Pivot Region
-

Q9 SINGLE ANSWER

In Power Query, Sales must look up a price from a Price query where the match is on both Region and ProductCode. What should you do?

- ☐ A Merge on Region and ProductCode, selected in the same order
- ☐ B Create two separate merges, one per column, and combine the results
- ☐ C Append Price to Sales
- ☐ D Merge on ProductCode only

Q10 MULTIPLE RESPONSE — CHOOSE TWO

A file has these queries: Staging_Customers (referenced by Customers and Contacts), FX_Lookup (used only in a merge into Sales), Sales, Customers and Date. Which two queries should have Enable load cleared?

- ☐ A Customers
- ☐ B Date
- ☐ C Sales
- ☐ D Staging_Customers
- ☐ E FX_Lookup

Q11 SINGLE ANSWER

Product codes must be six characters, padded with leading zeros ("42" becomes "000042"). Complete the custom column formula.

```
= Table.AddColumn ( Source, "ProductCode", each ____ )
```

- ☐ A Number.Round ([Code], 6)
- ☐ B Text.PadEnd ([Code], 6, "0")
- ☐ C Text.Start ([Code], 6)
- ☐ D Text.PadStart ([Code], 6, "0")

Q12 SINGLE ANSWER

Power BI created a many-to-many relationship between Customer and Sales because CustomerID isn't unique in the Customer table. Investigation shows the duplicates are exact copies of the same customers. What should you do?

- ☐ A Keep the many-to-many relationship and set it to Both
- ☐ B Remove duplicate customers, then make it one-to-many
- ☐ C Use TREATAS in every measure
- ☐ D Delete the relationship

Q13 SINGLE ANSWER

A Size column has values S, M, L and XL, and visuals sort them alphabetically (L, M, S, XL). What should you do?

- ☐ A Rename the values 1-S, 2-M, 3-L and 4-XL
- ☐ B Change Size to a number
- ☐ C Add a SizeOrder column and sort Size by it
- ☐ D Sort each visual by a measure that returns 1-4

Q14 SINGLE ANSWER

When authors drag UnitPrice into a visual, Power BI sums it, which is meaningless. Authors should get the average by default. What should you change?

- ☐ A Change UnitPrice to Text
- ☐ B Mark UnitPrice as a key column
- ☐ C Hide UnitPrice
- ☐ D Set UnitPrice's Summarize by property to Average

Q15 SINGLE ANSWER

A matrix shows months on rows. A column must show the full previous year's total sales on every month row. Which filter should the measure use inside CALCULATE?

- ☐ A PARALLELPERIOD ('Date'[Date], -1, YEAR)
- ☐ B SAMEPERIODLASTYEAR ('Date'[Date])
- ☐ C DATESYTD ('Date'[Date])
- ☐ D DATEADD ('Date'[Date], -1, MONTH)

Q16 SINGLE ANSWER

You need a model measure, usable in any visual, that returns the average of the last three months' monthly sales, ending at the last month in context. Which expression is correct?

- ☐ A CALCULATE (AVERAGEX (VALUES ('Date'[YearMonth]), [Total Sales]), DATESINPERIOD ('Date'[Date], MAX ('Date'[Date]), -3, MONTH))
- ☐ B AVERAGEX (DATESINPERIOD ('Date'[Date], MAX ('Date'[Date]), -3, MONTH), [Total Sales])
- ☐ C MOVINGAVERAGE ([Total Sales], 3)
- ☐ D CALCULATE (AVERAGEX (VALUES (Sales[OrderDateKey]), [Total Sales]), DATESINPERIOD ('Date'[Date], MAX ('Date'[Date]), -3, MONTH))

Q17 SINGLE ANSWER

Products must be ranked by sales against all products, and the ranks must not change when users filter the visual with a slicer. Which expression should you use?

- ☐ A RANKX (ALL ('Product'[Name]), [Total Sales])
- ☐ B TOPN (1, 'Product', [Total Sales])
- ☐ C RANKX (ALLSELECTED ('Product'[Name]), [Total Sales])
- ☐ D RANKX (VALUES ('Product'[Name]), [Total Sales])

Q18 SINGLE ANSWER

An analyst who doesn't write DAX needs a running total of sales by date. What is the fastest built-in way to create the measure?

- ☐ A Use a visual-level filter
- ☐ B Turn on Auto date/time
- ☐ C Create a calculated column with SUM over Sales
- ☐ D Use a quick measure (Running total)

Q19 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about CALCULATE, select Yes if it is true.

Statement	Yes	No
1. A filter argument on a column replaces any existing filter on that same column.	☐	☐
2. A filter argument on a dimension column also filters related fact tables through relationships.	☐	☐
3. A boolean filter argument can reference a measure, for example [Total Sales] > 1000.	☐	☐

Q20 SINGLE ANSWER

You need a calculated column in Customer that shows how many sales rows each customer has. Product and Customer relate one-to-many to Sales. Which expression is correct?

- ☐ A COUNTROWS (Sales)
 - ☐ B RELATED (Sales[OrderID])
 - ☐ C COUNTROWS (RELATEDTABLE (Sales))
 - ☐ D DISTINCTCOUNT (Customer[CustomerKey])
-

Q21 SINGLE ANSWER

A sensor table stores temperatures with eight decimal places, so almost every value is unique and the column is large. Reports only need two decimals. What should you do?

- ☐ A Change the column to Text
 - ☐ B Hide the column
 - ☐ C Round to two decimals in Power Query
 - ☐ D Add a measure that rounds the value to two decimals
-

Q22 MULTIPLE RESPONSE — CHOOSE TWO

Which two actions improve the performance of a DirectQuery report against a well-maintained SQL database?

- ☐ A Reduce the number of visuals on each page, or add Apply buttons through query reduction
 - ☐ B Add complex calculated columns to the DirectQuery tables
 - ☐ C Turn on automatic page refresh every second
 - ☐ D Set every relationship to Both
 - ☐ E Turn on Assume referential integrity on relationships where every fact key exists in the dimension
-

Q23 SINGLE ANSWER

Sales managers want to see how the ranking of the top five products changes from month to month, with the highest-ranked product on top each month. Which visual fits best?

- ☐ A Card
 - ☐ B Ribbon chart
 - ☐ C Gauge
 - ☐ D Pie chart
-

Q24 SINGLE ANSWER

A report has a helper page used only as a drillthrough target. It must not appear in the page tabs for readers, but drillthrough must still work. What should you do?

- ☐ A Hide the page
- ☐ B Move the page to another report
- ☐ C Delete the page
- ☐ D Lock the page

Q25 SINGLE ANSWER

Which tool do you use to author a paginated report (.rdl) for Power BI?

- ☐ A Power BI Report Builder
- ☐ B Power Query Online
- ☐ C Power BI Desktop's Report view
- ☐ D Tabular Editor

Q26 SINGLE ANSWER

When you open the Copilot pane in Power BI Desktop for the first time, it asks you to select a workspace. Why?

- ☐ A The report will be published there automatically
- ☐ B Copilot needs a workspace on a capacity that supports it
- ☐ C To choose where personal bookmarks are stored
- ☐ D The semantic model will be moved to that workspace to run Copilot

Q27 DRAG AND DROP — MATCH

Match each formatting requirement for a table column to the conditional-formatting type that meets it.

Choices — each may be used once, more than once, or not at all

- ☐ A Icons
- ☐ B Font colour (rules)
- ☐ C Data bars
- ☐ D Web URL
- ☐ E Background colour (gradient)

Requirement	Formatting type
1. An arrow next to each value shows whether growth is up or down	
2. Cells are shaded from light to dark as the value increases	
3. A bar inside each cell is proportional to the value	
4. Each value opens a related web page when selected	

Q28 SINGLE ANSWER

While arranging a complex page, you keep moving visuals by accident. You want to stop visuals being moved or resized while you work on formatting. What should you do?

- ☐ A Turn on View → Lock objects
- ☐ B Hide the visuals
- ☐ C Create a bookmark
- ☐ D Group every visual in the Selection pane

Q29 SINGLE ANSWER

A matrix has Category, Subcategory and Product on rows. Users want to see all levels at once with indentation, instead of drilling one level at a time. What should they do?

- ☐ A Use drillthrough to a page with a flat table
- ☐ B Use a bookmark
- ☐ C Use Expand all down one level in the hierarchy
- ☐ D Use a report-page tooltip that lists every level

Q30 SINGLE ANSWER

In a table visual, users want rows sorted by Region and then, within each region, by Sales descending. How do they sort by more than one column?

- ☐ A Use Sort by column in the model
- ☐ B Sort by Region, then Shift-click the Sales header
- ☐ C Use a bookmark
- ☐ D Create a calculated column combining Region and Sales, and sort by it

Q31 SINGLE ANSWER

A slide deck for the monthly review must show report pages with data that updates when the deck is opened, not static images. Which export option should you use?

- ☐ A Export to PDF
- ☐ B Print to paper
- ☐ C Export to PowerPoint as images
- ☐ D Export to PowerPoint with Embed live data

Q32 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about Personalize visuals, select Yes if it is true.

Statement	Yes	No
1. The feature must be enabled in the report's settings before readers can use it.	☐	☐
2. A change a reader makes is visible to every other user of the report.	☐	☐
3. Readers can change the visual type, for example from a column chart to a line chart.	☐	☐

Q33 SINGLE ANSWER

The Key influencers visual must explain what drives a numeric outcome, house sale price, rather than a category. Is this supported, and what does the visual show?

- ☐ A No: you must use a decomposition tree
- ☐ B No: Key influencers only supports categorical outcomes
- ☐ C Yes, but only as a pie chart
- ☐ D Yes: it shows how each factor moves the average price

Q34 SINGLE ANSWER

A column chart shows product mix by region. North looks different from the others. A user wants Power BI to find where North's distribution differs most. What should they use?

- ☐ A Add a forecast for each region from the Analytics pane
 - ☐ B Right-click North → Analyze → Explain the increase
 - ☐ C Analyze → Find where this distribution is different
 - ☐ D Group the regions
-

Q35 SINGLE ANSWER

A line chart of daily output must show horizontal lines at the period's highest and lowest values, updating as filters change. What should you add?

- ☐ A Data labels
 - ☐ B Max line and Min line from the Analytics pane
 - ☐ C A forecast
 - ☐ D Two constant lines typed manually
-

Q36 SINGLE ANSWER

A report author keeps the .pbix file on a SharePoint Online site. Changes saved to the file must reach the published report automatically, without republishing. How should the report be brought into the workspace?

- ☐ A Publish from Desktop each time the file changes
 - ☐ B Use Publish to web with the SharePoint file's link
 - ☐ C Upload it from SharePoint in the service
 - ☐ D Email the file to the workspace
-

Q37 SINGLE ANSWER

After publishing a model that imports from an on-premises SQL Server, the settings page shows the gateway connection isn't configured, so refresh can't be scheduled. A gateway is installed and running. What should you do?

- ☐ A Install a personal gateway on your laptop and sign in to it
 - ☐ B Switch the model to DirectQuery so no gateway is needed
 - ☐ C Republish the model from Desktop with credentials saved
 - ☐ D Map the source to a gateway connection for the server
-

Q38 SINGLE ANSWER

A manager sets a data alert on a dashboard tile and expects her whole team to be notified, but only she receives the email. Why?

- ☐ A Alerts work only on report visuals
 - ☐ B The tile must be a pie chart
 - ☐ C Data alerts are personal: only their creator is notified
 - ☐ D The team needs the Admin role on the dashboard's workspace
-

Q39 SINGLE ANSWER

A report developer must publish reports from Power BI Desktop to a workspace and edit content there. They must not manage access or publish the app. Which role meets this with least privilege?

- ☐ A Contributor
- ☐ B Viewer
- ☐ C Admin
- ☐ D Member

Q40 SINGLE ANSWER

An external auditing firm must view three reports using their own company credentials, with access you can revoke. What should you do?

- ☐ A Email them PDF exports of the three reports each month
- ☐ B Use Publish to web
- ☐ C Invite them as Entra B2B guests and share the reports
- ☐ D Create Power BI accounts in your tenant with shared passwords

Q41 SINGLE ANSWER

A report with the Highly Confidential label, configured with encryption, is exported to Excel. What happens to the exported file?

- ☐ A The label is removed during export
- ☐ B It keeps the label and its protection
- ☐ C The file is converted to PDF
- ☐ D The export is always blocked for encrypted labels

Case study · Adventure Works Cycles

Questions 42–45

Existing environment

Adventure Works sells bicycles through 300 independent dealers. Web orders arrive as JSON with an OrderTimestamp field holding Unix epoch seconds. Each dealer can belong to several sales territories, and each territory has many dealers. Dealers are external companies whose staff sign in as Microsoft Entra B2B guests.

Requirements

1. Order dates must be real date/time values in the model.
2. Sales must be analysable by territory, even though dealers belong to several territories.
3. Each dealer's purchasing contact wants a PDF of the whole Dealer report emailed every Monday.
4. Each dealer must see only their own sales rows. A DealerUsers table maps guest email addresses to DealerID.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

Which custom column formula converts OrderTimestamp to a datetime?

- ☐ A DateTime.From ([OrderTimestamp])
- ☐ B #datetime (1970, 1, 1, 0, 0, 0) + #duration (0, 0, 0, [OrderTimestamp])
- ☐ C #date ([OrderTimestamp], 1, 1)
- ☐ D Date.From (Text.From ([OrderTimestamp]))

Q43 SINGLE ANSWER

How should you model dealers and territories?

- ☐ A Add a DealerTerritory bridge, with bridge-Dealer filtering set to Both
 - ☐ B Add a TerritoryID column to Dealer and keep only the first territory
 - ☐ C Merge Territory into Sales
 - ☐ D Relate Territory directly to Sales with a many-to-many relationship on DealerID
-

Q44 SINGLE ANSWER

How do you deliver the Monday PDF to each dealer contact?

- ☐ A Set a data alert that emails the PDF to every dealer contact on Mondays
 - ☐ B A weekly subscription with the report attached as PDF
 - ☐ C Use Publish to web
 - ☐ D Use Export to PowerPoint
-

Q45 SINGLE ANSWER

Which role filter, on the Dealer table, meets the security requirement?

- ☐ A Dealer[DealerID] = USERNAME ()
- ☐ B TRUE ()
- ☐ C Dealer[DealerID] = CUSTOMDATA ()
- ☐ D Dealer[DealerID] IN CALCULATETABLE (VALUES (DealerUsers[DealerID]), DealerUsers[Email] = USERPRINCIPALNAME ())

End of Set 06 — answers follow on the next page.

Set 06 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	D	P1		16	A	M2		31	D	V2	
2	C	P1		17	A	M2		32	Yes · No · Yes	V2	
3	E → F → A → D	P1		18	D	M2		33	D	V3	
4	A	P1		19	Yes · Yes · No	M2		34	C	V3	
5	D	P2		20	C	M2		35	B	V3	
6	B	P2		21	C	M3		36	C	S1	
7	B	P2		22	A, E	M3		37	D	S1	
8	C	P3		23	B	V1		38	C	S1	
9	A	P3		24	A	V1		39	A	S2	
10	D, E	P3		25	A	V1		40	C	S2	
11	D	P3		26	B	V1		41	B	S2	
12	B	M1		27	1→A 2→E 3→C 4→D	V1		42	B	P3	
13	C	M1		28	A	V2		43	A	M1	
14	D	M1		29	C	V2		44	B	S1	
15	A	M2		30	B	V2		45	D	S2	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: D P1 · Get or connect to data

Dynamics 365 apps store their data in Dataverse, and the Dataverse connector reads tables, relationships and choice labels directly. Web and Folder are generic connectors, and a mailbox isn't the data source.

Q2 Answer: C P1 · Get or connect to data

Organizational sources can share data with other Organizational sources during evaluation, which allows the merge to fold. Private sources never share data, which blocks folding and can raise firewall errors. Mixing Public with Private restricts the merge as well.

Q3 Answer: E → F → A → D P1 · Get or connect to data

Cloud data source credentials for refresh are stored on the semantic model's settings page. Once they're valid, you can turn on scheduled refresh there. An Azure SQL Database with a public endpoint doesn't need a gateway, and Publish to web has nothing to do with refresh.

Q4 Answer: A P1 · Get or connect to data

A live connection to Analysis Services uses the model as-is, with no local copy, and report-level measures can still be added. Importing the underlying tables recreates the model outside governance. Dataflows and Excel exports copy data.

Q5 Answer: D P2 · Profile and clean the data

Power Query is case-sensitive, so the three spellings are different values. Standardising the case makes them one. The model's engine compares text without regard to case, which can make results confusing until the source text is consistent. Removing or filtering rows loses data.

Q6 Answer: B P2 · Profile and clean the data

Resolving an inconsistency doesn't always mean deleting it. The values are valid, so labelling them keeps every row and lets reports split sales and returns. Removing or zeroing them changes the totals.

Q7 Answer: B P2 · Profile and clean the data

Type detection looks at a sample of rows, so it guessed wrongly. Codes are identifiers, so the type should be Text, which makes the errors disappear. Removing or replacing errors destroys valid rows.

Q8 Answer: C P3 · Transform and load the data

The Advanced option of Group by allows several aggregations, here a sum and a maximum, in one step. Basic allows one aggregation. Pivot and Remove duplicates don't aggregate correctly.

Q9 Answer: A P3 · Transform and load the data

Merge supports multi-column keys: select the columns in each table (Ctrl-click) in the same order. Matching on one column would return several prices per row. Append stacks rows, which is a different operation.

Q10 Answer: D, E P3 · Transform and load the data

Queries that exist only as inputs to other queries don't need to be loaded into the model. Clearing Enable load keeps them out of memory and the field list, and they still run when the queries that use them refresh. Sales, Customers and Date are model tables.

Q11 Answer: D P3 · Transform and load the data

Text.PadStart adds the pad character to the start of the text until it reaches the given length. PadEnd pads at the end. Number.Round works on numbers. Text.Start truncates rather than pads.

Q12 Answer: B M1 · Design and implement a data model

A dimension must be unique on its key. Fixing the duplicates at load lets you create the correct one-to-many relationship. Many-to-many relationships cost performance and can give confusing totals when they only hide a data-quality problem.

Q13 Answer: C M1 · Design and implement a data model

Sort by column lets a text column follow the order of another column with one value per text value. Renaming values works but changes what users see. Sorting by a measure doesn't give a fixed category order.

Q14 Answer: D M1 · Design and implement a data model

The default summarisation decides how a numeric column is aggregated when it's added to a visual. Average suits a price. Authors can still change it per visual, and explicit measures remain the best practice for reusable calculations.

Q15 Answer: A M2 · Create model calculations by using DAX

PARALLELPERIOD returns whole periods. Shifting back one year from any month returns all dates of the previous year. SAMEPERIODLASTYEAR returns only the same month last year. DATEADD by a month shifts to the prior month. DATESYTD accumulates the current year.

Q16 Answer: A M2 · Create model calculations by using DAX

The three-month window is applied as a filter, and AVERAGEX then averages the sales of each month in it. Iterating DATESINPERIOD directly averages daily sales, not monthly. MOVINGAVERAGE is a visual calculation function, not a model measure. Iterating the order dates inside the window also averages per day rather than per month.

Q17 Answer: A M2 · Create model calculations by using DAX

ALL removes filters from the product names, so each product is ranked against the full list whatever the slicer shows. ALLSELECTED ranks within the user's selection. VALUES ranks within the visual's current context, usually giving every row rank 1. TOPN returns a table.

Q18 Answer: D M2 · Create model calculations by using DAX

Quick measures generate the DAX for common patterns, including running totals, from a dialog, and the result is an ordinary measure you can inspect. A calculated column with SUM returns the grand total on every row. Filters and Auto date/time don't create running totals.

Q19 Answer: Yes · Yes · No M2 · Create model calculations by using DAX

CALCULATE replaces filters on the columns it filters, and the new filter propagates through relationships like any other. Boolean filter arguments must compare columns. To filter by a measure, use a table filter such as FILTER over the column's values.

Q20 Answer: C M2 · Create model calculations by using DAX

RELATEDTABLE returns the Sales rows related to the current customer row, and COUNTROWS counts them. COUNTROWS(Sales) counts the whole table on every row. RELATED works from the many side to the one side, not the reverse.

Q21 Answer: C M3 · Optimize model performance

Rounding at load reduces the number of distinct values, which improves compression and shrinks the model. Text is larger. Hiding doesn't change storage. A rounding measure leaves the stored column as large as before.

Q22 Answer: A, E M3 · Optimize model performance

Inner joins from referential integrity and fewer queries per interaction both reduce load on the source. Bidirectional relationships, complex calculated columns and very frequent page refresh all add queries or complexity.

Q23 Answer: B V1 · Create reports

A ribbon chart orders categories by value within each period and connects them with ribbons, so rank changes stand out. Pie charts, gauges and cards don't show rank over time.

Q24 Answer: A V1 · Create reports

Hidden pages don't appear in the page navigation for readers, but drillthrough, buttons and bookmarks can still take users there. Deleting it removes the target. Pages can't be locked.

Q25 Answer: A V1 · Create reports

Paginated reports are authored in Power BI Report Builder and published to the service. Desktop authors interactive reports, Tabular Editor edits models, and Power Query Online is for dataflows and data preparation.

Q26 Answer: B V1 · Create reports

In Desktop, Copilot needs a workspace on an eligible capacity (F2 or higher, or P1 or higher) to run against. Choosing the workspace doesn't publish or move anything.

Q27 Answer: 1→A 2→E 3→C 4→D V1 · Create reports

Icons add symbols based on rules or a field value. A background gradient shades cells by value. Data bars draw an in-cell bar. Web URL turns a value into a link. Font colour changes the text colour, which none of these requirements ask for.

Q28 Answer: A V2 · Enhance reports for usability and storytelling

Lock objects stops visuals being moved or resized on the canvas while you keep editing their properties. Grouping, hiding and bookmarking don't prevent accidental moves.

Q29 Answer: C V2 · Enhance reports for usability and storytelling

Expanding all down one level shows the next level for every parent, and repeating it shows all levels in a stepped layout. Drillthrough opens another page. Bookmarks and tooltips don't expand hierarchies.

Q30 Answer: B V2 · Enhance reports for usability and storytelling

Table visuals support multi-column sorting by holding Shift while selecting additional column headers. Combining columns or changing model sort order doesn't give an on-the-fly secondary sort.

Q31 Answer: D V2 · Enhance reports for usability and storytelling

Embed live data inserts the report into PowerPoint through the Power BI add-in, so the slide shows current, interactive data. PDF and image exports are snapshots.

Q32 Answer: Yes · No · Yes V2 · Enhance reports for usability and storytelling

Personalize visuals is turned on per report, and can be turned off per visual. Readers' changes are their own and can be saved as personal bookmarks. They can swap measures, dimensions and visual types, without edit permission.

Q33 Answer: D V3 · Identify patterns and trends

Key influencers analyses numeric (continuous) metrics as well as categorical outcomes. For numeric targets, it reports how each factor moves the average of the metric.

Q34 Answer: C V3 · Identify patterns and trends

Find where this distribution is different compares the selected value's distribution with the rest and highlights the categories that differ most. Explain the increase applies to changes between two data points, for example in a time series.

Q35 Answer: B V3 · Identify patterns and trends

Max and min lines are dynamic: they recalculate for the data in the visual. Constant lines stay where you typed them. Data labels and forecasts don't add reference lines.

Q36 Answer: C S1 · Create and manage workspaces and assets

Uploading from OneDrive or SharePoint creates a connection to the file, and the service picks up saved changes automatically. Publishing from Desktop works but must be repeated. The other options don't keep the report in sync.

Q37 Answer: D S1 · Create and manage workspaces and assets

The model's on-premises source must be mapped to a gateway connection for that server and database, created by a gateway admin, with credentials. A personal gateway isn't for shared production refresh. Switching modes or republishing doesn't create the mapping.

Q38 Answer: C S1 · Create and manage workspaces and assets

Each data alert belongs to the user who created it, and only that user is notified. An alert can trigger a Power Automate flow to notify others. Alerts are set on dashboard tiles like cards, KPIs and gauges, not on pie charts.

Q39 Answer: A S2 · Secure and govern Power BI items

Contributors can publish, create, edit and delete content, and schedule refresh, but can't add users or, by default, update the app. Member and Admin grant more. Viewer can't publish.

Q40 Answer: C S2 · Secure and govern Power BI items

B2B guest access lets external users sign in with their own identity while you control and revoke their permissions. Publish to web is public. Shared accounts break accountability. PDF emails can't be revoked once sent.

Q41 Answer: B S2 · Secure and govern Power BI items

Sensitivity labels persist to supported export formats, and a label with encryption protects the file outside Power BI. Labels don't block export by themselves. Export settings and tenant settings control that.

Q42 Answer: B P3 · Transform and load the data

Unix time counts seconds from 1 January 1970, so adding a duration of that many seconds to the epoch gives the datetime. `DateTime.From` on a number treats it as days since 1899, which gives wrong dates. The other expressions produce invalid or wrong values.

Q43 Answer: A M1 · Design and implement a data model

A bridge table resolves the many-to-many relationship between dealers and territories. Letting the bridge filter Dealer passes the territory selection through to Sales. Keeping only one territory loses data. Direct many-to-many or merging duplicates sales across territories in uncontrolled ways.

Q44 Answer: B S1 · Create and manage workspaces and assets

Report subscriptions can attach the full report as a PDF (or PowerPoint) on a schedule, and recipients still only see data their access allows. Data alerts trigger on thresholds. Manual export doesn't schedule. Publish to web is public.

Q45 Answer: D S2 · Secure and govern Power BI items

`USERPRINCIPALNAME()` returns the signed-in user's sign-in name. Looking it up in the mapping table returns that user's DealerIDs, which then filter Dealer and, through it, Sales. A DealerID never equals a user name. `CUSTOMDATA` is for embedded scenarios. `TRUE()` shows everything.

Performance and storage modes

Import, DirectQuery, Direct Lake, Dual and hybrid tables; query folding, aggregations, model size and the DAX patterns that scale.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 3 · Advanced

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

A Direct Lake semantic model built on a lakehouse's SQL analytics endpoint is fast most of the time. Visuals that use one table, which is actually a SQL view, are consistently slower. What explains this?

- ☐ A The capacity is paused
- ☐ B Direct Lake re-imports views on every query instead of caching them
- ☐ C Views are always imported
- ☐ D Views fall back to DirectQuery; Direct Lake reads Delta tables only

Q2 SINGLE ANSWER

A DirectQuery report queries a large SQL function that takes a CountryCode argument. A slicer selection must be passed into the M query so the source only computes the chosen country. What should you use?

- ☐ A A dynamic M query parameter bound to the slicer
- ☐ B A calculation group
- ☐ C A report-level filter
- ☐ D A what-if parameter whose value the M query reads

Q3 SINGLE ANSWER

On Premium capacity, a sales table holds five years of history. Imported performance is needed for history, but today's orders must appear immediately without waiting for a refresh. What should you configure?

- ☐ A DirectQuery for the whole table, including the five years of history
- ☐ B Incremental refresh with real-time DirectQuery data (a hybrid table)
- ☐ C A separate DirectQuery report for today's orders only
- ☐ D Import with 48 scheduled refreshes a day, one every 30 minutes

Q4 SINGLE ANSWER

A ShipDate text column uses "00/00/0000" for orders not yet shipped, and these become errors when the column is typed as Date. Unshipped orders must stay in the data with no ship date. What should you do?

- ☐ A Replace "00/00/0000" with null before the type change
- ☐ B Change the type to Text permanently
- ☐ C Fill down the ShipDate column
- ☐ D Remove errors after the type change

Q5 SINGLE ANSWER

With profiling switched to the entire data set, a CustomerID column in a 1,000,000-row table shows 1,000,000 distinct and 1,000,000 unique values, with 0% empty. What can you conclude?

- ☐ A The column has many duplicates, so it can't be used as a key
 - ☐ B Every value occurs once, so it can be a dimension key
 - ☐ C Half the values are blank
 - ☐ D The column must be split before use
-

Q6 SINGLE ANSWER

The data team must review rows that fail type conversion each day, but the model must load only valid rows. What is the cleanest Power Query design?

- ☐ A Turn off Column quality
 - ☐ B Keep errors in an unloaded reference query; Remove errors in the main query
 - ☐ C Load both valid and invalid rows into the model, and hide the invalid ones with a report filter
 - ☐ D Use Replace errors with 0 in the main query
-

Q7 SINGLE ANSWER

When you configure incremental refresh, Power BI warns that the query can't be folded. The query filters on RangeStart and RangeEnd, but an Added Index Column step comes before the filter. What should you do?

- ☐ A Change the parameters to Text
 - ☐ B Ignore the warning; folding only affects DirectQuery, not incremental refresh
 - ☐ C Turn off Enable load
 - ☐ D Move the date filter before the index step, or remove the index
-

Q8 SINGLE ANSWER

You must combine Sales_EU and Sales_US into a new third query, leaving both original queries unchanged. Which command should you use?

- ☐ A Append queries as new
 - ☐ B Duplicate
 - ☐ C Append queries
 - ☐ D Merge queries
-

Q9 SINGLE ANSWER

A JSON field named tags holds a list such as {"red", "sale", "new"} for each product. You need one text column per product containing "red, sale, new", keeping one row per product. What should you do?

- ☐ A Pivot the tags column
- ☐ B Use Split column into rows
- ☐ C Extract Values on the list, with a comma delimiter
- ☐ D Expand the list to new rows, then remove duplicates

Q10 DRAG AND DROP — MATCH

You merge Orders (first table) with Customers (second table) on CustomerID. Match each requirement to the join kind.

Choices — each may be used once, more than once, or not at all

- A** Full outer
- B** Inner
- C** Left anti
- D** Left outer
- E** Right anti

Requirement	Join kind
1. Only orders that have a matching customer	
2. Every order, with customer details where available	
3. Orders whose CustomerID doesn't exist in Customers (orphans)	
4. Every order and every customer, matched where possible	

Q11 BUILD LIST — SEQUENCE

Put the steps to set up incremental refresh on a large Sales table in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- A** Create RangeStart and RangeEnd parameters of type Date/Time
- B** Publish the model; the first refresh in the service creates the partitions
- C** Switch Sales to DirectQuery
- D** Turn off Enable load on Sales
- E** Define the incremental refresh policy on the Sales table in Power BI Desktop
- F** Filter the OrderDate column using the two parameters in Power Query

Q12 SINGLE ANSWER

In a composite model, an imported Budget table is related to a DirectQuery Sales table from a different source. Power BI marks the relationship as limited. Which statement is true?

- A** The relationship behaves exactly like a regular one-to-many relationship
- B** Limited relationships only exist in Direct Lake models
- C** RELATED can't cross it, and no blank row is added for unmatched values
- D** The relationship is automatically converted to Import

Q13 SINGLE ANSWER

RLS is defined on a Users table that relates to a UserRegion bridge table, which relates to Region and then Sales. The role's filter doesn't reach Sales because one relationship filters the wrong way. What should you configure on that relationship?

- A** Make the relationship inactive and activate it with USERRELATIONSHIP in the role
- B** Change cardinality to one-to-one
- C** Set it to Both and turn on Apply security filter in both directions
- D** Hide the bridge table

Q14 SINGLE ANSWER

An AgeBand column ("18-24", "25-34"...) is used in many slicers. Where should you create it for the best model compression and reuse?

- ☐ A As a visual calculation
- ☐ B In each report, as a group on the Age column
- ☐ C As a measure that returns the band for each customer
- ☐ D In the source or Power Query

Q15 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about storage modes in Power BI Desktop, select Yes if it is true.

Statement	Yes	No
1. A Dual table can serve a query either from its imported copy or by querying the source.	☐	☐
2. A composite model can't contain Import tables.	☐	☐
3. After a table has been switched to Import, it can't be switched back to DirectQuery.	☐	☐

Q16 SINGLE ANSWER

Which filter is generally the most efficient way to keep only red products inside CALCULATE?

- ☐ A `FILTER ( ALL ( 'Product' ), 'Product'[Color] = "Red" )`
- ☐ B `FILTER ( Sales, RELATED ( 'Product'[Color] ) = "Red" )`
- ☐ C `'Product'[Color] = "Red"`
- ☐ D `FILTER ( 'Product', 'Product'[Color] = "Red" )`

Q17 SINGLE ANSWER

A calculation group has items Current, PY and YoY %. YoY % must display as a percentage, while the others keep the original measure's currency format. What should you configure?

- ☐ A A separate measure for every combination
- ☐ B The Format property of the calculation group column in the model
- ☐ C A theme
- ☐ D A dynamic format string on the YoY % calculation item

Q18 SINGLE ANSWER

A model has two calculation groups: Time Intelligence (YTD, PY) and Currency (USD, EUR). Users report that YTD in EUR is wrong because conversion runs before the YTD calculation. What controls the order in which the groups apply?

- ☐ A The calculation groups' Precedence property
- ☐ B The name of each group
- ☐ C The sort-by column of the Date table
- ☐ D The order of items within each group

Q19 SINGLE ANSWER

A calculation must be available when users connect to the model with Analyze in Excel, and in every report built on the model. Which should you create?

- ☐ A A report-level measure in a live-connected report
 - ☐ B A visual calculation
 - ☐ C A quick filter
 - ☐ D A model measure
-

Q20 SINGLE ANSWER

Bonus = IF ([Total Sales] > 10000, [Total Sales] * 0.05, 0). Rows per salesperson are correct, but the grand total applies the rule to total sales instead of adding each person's bonus. How do you fix the total?

- ☐ A Bonus = CALCULATE (IF ([Total Sales] > 10000, [Total Sales] * 0.05), ALL (Salesperson))
 - ☐ B Turn off totals in the visual
 - ☐ C Bonus = SUMX (VALUES (Salesperson[ID]), IF ([Total Sales] > 10000, [Total Sales] * 0.05, 0))
 - ☐ D Change the visual to a matrix
-

Q21 SINGLE ANSWER

A converted-sales measure must only return a value when exactly one currency is selected in the Currency slicer, and blank otherwise. Which pattern should you use?

- ☐ A IF (HASONEVALUE (Currency[Code]), [Sales] * SELECTEDVALUE (Currency[Rate]))
 - ☐ B [Sales] * MAX (Currency[Rate])
 - ☐ C [Sales] * SUM (Currency[Rate])
 - ☐ D IF (ISBLANK (Currency[Code]), [Sales])
-

Q22 SINGLE ANSWER

A DirectQuery fact table has 5 billion rows. Most visuals show sales by month and product category. You add an imported summary table at that grain. What else is needed so those visuals use the summary automatically?

- ☐ A Turn on Auto date/time
 - ☐ B Rename the summary table Sales
 - ☐ C Create a relationship between the summary and the detail table on their keys
 - ☐ D Manage aggregations on the summary table, mapped to the detail table
-

Q23 SINGLE ANSWER

A Power BI report page must show an operational paginated report, with its parameters passed from the page's slicers. What should you add?

- ☐ A The Paginated report visual, with fields mapped to its parameters
 - ☐ B A Q&A visual
 - ☐ C A web URL to Report Builder with the parameters in the query string
 - ☐ D An image of the paginated report
-

Q24 SINGLE ANSWER

Across 40 reports, every new card visual must have its category label turned off and a specific font size, by default. What is the most maintainable approach?

- ☐ A Format each card manually
 - ☐ B Add card visualStyles to the corporate JSON theme
 - ☐ C Copy one formatted card into every report and use it as a template
 - ☐ D Use a bookmark
-

Q25 SINGLE ANSWER

An author wants Copilot to propose several outlines of possible report pages from the model, then pick one to build. Which Copilot capability is this?

- ☐ A Summarise the semantic model
 - ☐ B Explain a DAX query
 - ☐ C Suggest content for a new report page
 - ☐ D Create a narrative visual
-

Q26 SINGLE ANSWER

A Customer slicer lists 5,000 names, and users can't find the one they need. What is the simplest improvement?

- ☐ A Split the slicer into 26 slicers by first letter
 - ☐ B Turn on Search in the slicer
 - ☐ C Remove the slicer
 - ☐ D Change it to a between slicer
-

Q27 SINGLE ANSWER

In an Import-mode report, the Page refresh option is missing from the page's format settings. Why?

- ☐ A The theme disables it
 - ☐ B The page has more than ten visuals
 - ☐ C It's only available for DirectQuery and similar sources
 - ☐ D Page refresh needs a mobile layout before it appears in settings
-

Q28 SINGLE ANSWER

Each chart's alt text must describe its current values for screen-reader users, for example "Revenue this month: 1.2M", and update as filters change. What should you do?

- ☐ A Type a fixed alt text for each chart that includes this month's value
- ☐ B Add a text box under each chart
- ☐ C Use a high-contrast theme
- ☐ D Set the Alt text with fx to a measure that builds the description

Q29 SINGLE ANSWER

Two different slicers, one on page 1 and one on page 3, both use Date[Year] and must share a selection. They aren't copies of each other. What should you configure?

- ☐ A Use a report-level filter on Date[Year] instead of slicers
 - ☐ B Use drillthrough
 - ☐ C Copy one slicer over the other
 - ☐ D Give both slicers the same group name in Sync slicers
-

Q30 SINGLE ANSWER

Across a whole report, selecting a data point should cross-filter other visuals instead of cross-highlighting them, without setting Edit interactions for every pair of visuals. What should you change?

- ☐ A Each visual's format pane, under the Interactions card
 - ☐ B The report's default visual interaction setting
 - ☐ C The persistent filters setting for the report
 - ☐ D The theme
-

Q31 MULTIPLE RESPONSE — CHOOSE TWO

Which two changes help screen-reader users understand a report?

- ☐ A Remove the tab order
 - ☐ B Add alt text to each visual
 - ☐ C Give every visual a meaningful title
 - ☐ D Use colour as the only way to show status
 - ☐ E Put text into background images
-

Q32 SINGLE ANSWER

Anomaly detection on a daily line chart flags too many points as anomalies, most of them normal weekend dips. What should you change first?

- ☐ A Raise the sensitivity
 - ☐ B Add a forecast
 - ☐ C Lower the anomaly detection sensitivity
 - ☐ D Remove the date axis
-

Q33 SINGLE ANSWER

A monthly sales line includes the current, incomplete month, which drags the forecast down. How should you configure the forecast?

- ☐ A Set Ignore the last to 1 point
- ☐ B Increase the confidence interval
- ☐ C Turn off the forecast
- ☐ D Set the seasonality to 1

Q34 SINGLE ANSWER

A DaysLate column ranges from 0 to 60. Managers want a histogram of late deliveries in weekly buckets (0–6, 7–13 and so on). What should you create?

- ☐ A Bins on DaysLate with a bin size of 7
 - ☐ B Clusters on DaysLate
 - ☐ C A slicer on DaysLate
 - ☐ D A group with 60 manual items
-

Q35 SINGLE ANSWER

On Premium capacity, an imported semantic model is expected to grow past 10 GB. What should you enable so it can grow and refresh efficiently?

- ☐ A Auto date/time
 - ☐ B Large semantic model storage format
 - ☐ C Personal gateway
 - ☐ D Publish to web
-

Q36 SINGLE ANSWER

The team wants to deploy metadata changes, such as new measures and partitions, to a published model with Tabular Editor, without republishing the .pbix. What must be enabled?

- ☐ A XMLA endpoint set to Read Write
 - ☐ B Usage metrics
 - ☐ C Persistent filters on the semantic model
 - ☐ D Publish to web
-

Q37 SINGLE ANSWER

In a deployment pipeline, the compare view shows that only one of 12 reports changed in Development. You want to deploy just that report to Test. What should you do?

- ☐ A Deploy all content every time
 - ☐ B Select only the changed report and deploy it
 - ☐ C Recreate the Test workspace
 - ☐ D Publish the report from Desktop directly to the Test workspace
-

Q38 SINGLE ANSWER

On Premium capacity, a Sales dashboard must show data no more than 15 minutes old. Why can't a 15-minute scheduled refresh be configured for an Import model, and what is a better fit?

- ☐ A Scheduled refresh can't run on weekdays
- ☐ B Refresh runs in 30-minute slots; use DirectQuery or a hybrid table
- ☐ C Import models can't be refreshed on Premium
- ☐ D Premium allows only 8 refreshes per day; use a Pro workspace instead

Q39 SINGLE ANSWER

A DirectQuery model uses an on-premises SQL Server that already applies row filtering based on the connecting user. Each report user must reach SQL Server with their own identity. What should you configure?

- ☐ A RLS roles with USERNAME() that copy the SQL filters
- ☐ B Publish to web
- ☐ C A personal gateway
- ☐ D SSO for DirectQuery on the gateway data source

Q40 SINGLE ANSWER

The organisation must stop all content from being shared with external guest users. Where is this controlled?

- ☐ A In each report's settings
- ☐ B In Power Query privacy levels
- ☐ C In the Fabric admin portal tenant settings
- ☐ D In each workspace's licence mode and access settings

Q41 SINGLE ANSWER

One workspace app must show the Sales audience three reports and the Finance audience five, and some reports appear in both. Each group must not see the other's reports. What should you configure?

- ☐ A Sensitivity labels
- ☐ B App audiences, each with the right reports and security group
- ☐ C RLS roles named Sales and Finance
- ☐ D Two separate workspaces and apps, each with copies of the shared reports

Case study · Tailspin Toys

Questions 42–45

Existing environment

Tailspin Toys sells toys online. Orders are stored as Delta tables in a Fabric lakehouse and loaded hourly. Website click events stream into a Fabric Eventhouse (KQL database). Reports run on an F64 capacity. The executive overview page has 14 separate card visuals. Marketing analysts are Contributors in the model's workspace.

Requirements

1. The live traffic page must show click activity that is no more than one minute old.
2. The executive overview page must load faster. Performance Analyzer shows each card's DAX query takes about 300 ms, but most of the page's time is listed as Other.
3. Marketing needs a visual of how many sessions move from product view to cart, to checkout, to purchase.
4. Regional marketing analysts must see only their region's data, including in reports they build themselves.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

How should the live traffic page get its data?

- ☐ A A CSV export every minute
 - ☐ B A dashboard tile with a data alert
 - ☐ C DirectQuery to the KQL database with automatic page refresh
 - ☐ D Import from the Eventhouse with scheduled refresh every minute
-

Q43 SINGLE ANSWER

Which change will most reduce the overview page's load time?

- ☐ A Convert the model to Import
 - ☐ B Rewrite each card's measure with variables to cut its query time
 - ☐ C Add a forecast to each card
 - ☐ D Replace the 14 cards with a few multi-value visuals
-

Q44 SINGLE ANSWER

Which visual meets marketing's requirement?

- ☐ A Funnel chart
 - ☐ B Treemap
 - ☐ C Waterfall chart
 - ☐ D Scatter chart
-

Q45 SINGLE ANSWER

You add dynamic RLS for regions, but analysts still see every region. What should you change?

- ☐ A Make the analysts Viewers with Build permission on the model
- ☐ B Add the analysts to a second role with the same region filter
- ☐ C Use USERNAME() instead of USERPRINCIPALNAME()
- ☐ D Apply a sensitivity label

End of Set 07 — answers follow on the next page.

Set 07 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	D	P1		16	C	M2		31	B, C	V2	
2	A	P1		17	D	M2		32	C	V3	
3	B	P1		18	A	M2		33	A	V3	
4	A	P2		19	D	M2		34	A	V3	
5	B	P2		20	C	M2		35	B	S1	
6	B	P2		21	A	M2		36	A	S1	
7	D	P3		22	D	M3		37	B	S1	
8	A	P3		23	A	V1		38	B	S1	
9	C	P3		24	B	V1		39	D	S2	
10	1→B 2→D 3→C 4→A	P3		25	C	V1		40	C	S2	
11	A → F → E → B	P3		26	B	V1		41	B	S2	
12	C	M1		27	C	V2		42	C	P1	
13	C	M1		28	D	V2		43	D	M3	
14	D	M1		29	D	V2		44	A	V1	
15	Yes · No · Yes	M1		30	B	V2		45	A	S2	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: D P1 · Get or connect to data

Direct Lake loads column data from Delta tables in OneLake. Views aren't Delta tables, so a Direct Lake on SQL model answers those queries through DirectQuery fallback. Materialising the view as a Delta table restores Direct Lake behaviour.

Q2 Answer: A P1 · Get or connect to data

Dynamic M query parameters let a slicer or filter value be bound to an M parameter, which is then used inside the source query or function. What-if parameters are DAX tables. Calculation groups change measures. A report filter is applied to the generated query, not passed as a function argument.

Q3 Answer: B P1 · Get or connect to data

A hybrid table keeps historical partitions imported and adds a DirectQuery partition for the most recent period, so the latest rows are queried live. Scheduled refresh still lags. Full DirectQuery gives up Import performance for history. Separate reports fragment the analysis.

Q4 Answer: A P2 · Profile and clean the data

Converting the placeholder to null first means the type change succeeds and unshipped orders keep an empty ship date. Removing errors deletes those orders. Keeping the column as text breaks date logic. Fill down invents dates that don't exist.

Q5 Answer: B P2 · Profile and clean the data

When distinct and unique both equal the row count and nothing is empty, every value appears once: the definition of a usable key. Duplicates would make unique lower than distinct.

Q6 Answer: B P2 · Profile and clean the data

A reference query that keeps errors gives the team a review list, and the main query removes them so only valid rows load. Replacing errors with 0 hides problems and distorts totals. Loading invalid rows pollutes the model.

Q7 Answer: D P3 · Transform and load the data

Adding an index column usually stops folding, so later steps run locally and each refresh would read the full table. The RangeStart/RangeEnd filter must fold so each partition reads only its own rows. Parameter types must stay Date/Time.

Q8 Answer: A P3 · Transform and load the data

Append queries as new creates a separate query containing the combined rows, leaving the originals as they are. Plain Append adds the rows to the selected query itself. Merge joins columns. Duplicate copies one query.

Q9 Answer: C P3 · Transform and load the data

Extract Values concatenates the items of a list into one text value with a delimiter, keeping the row count unchanged. Expanding to new rows creates one row per tag. Pivot and split don't apply to a list column here.

Q10 Answer: 1→B 2→D 3→C 4→A P3 · Transform and load the data

Inner keeps matched rows only. Left outer keeps all orders. Left anti keeps orders with no match, which finds orphaned keys. Full outer keeps everything from both sides. Right anti would return customers with no orders.

Q11 Answer: A → F → E → B P3 · Transform and load the data

The parameters must exist, with those exact names and the Date/Time type, before the filter can use them. The policy is defined on the table in Desktop, and partitions are created by the first refresh in the service, not in Desktop.

Q12 Answer: C M1 · Design and implement a data model

Relationships across source groups are limited: the join is evaluated as an inner join between groups, unmatched rows don't produce a blank member, and functions such as RELATED aren't available across them. This affects totals and DAX, so design with it in mind.

Q13 Answer: C M1 · Design and implement a data model

For a security filter to travel against a relationship's default direction, the relationship must be bidirectional and set to apply security filters in both directions. Making it inactive or hiding the table stops the filter altogether.

Q14 Answer: D M1 · Design and implement a data model

Columns created in the source or Power Query are compressed together with the rest of the table and are available to every downstream tool. DAX calculated columns are computed after load and are generally less efficient. Measures and visual calculations can't be used as slicer fields.

Q15 Answer: Yes · No · Yes M1 · Design and implement a data model

Dual tables are answered from memory or the source depending on the query. Composite models mix Import with DirectQuery (or Dual) tables by definition. Desktop allows a table to change from DirectQuery or Dual to Import, but not from Import back to DirectQuery.

Q16 Answer: C M2 · Create model calculations by using DAX

A boolean filter on a single column is internally a filter over just that column's values, which is cheap. FILTER over a whole table iterates every row and can carry extra columns into the filter. Filtering the fact table is the most expensive option.

Q17 Answer: D M2 · Create model calculations by using DAX

Calculation items can have a format string expression that overrides the measure's format for that item only, for example "0.0%". Setting a column format would apply to every item. Separate measures defeat the purpose of the group.

Q18 Answer: A M2 · Create model calculations by using DAX

When several calculation groups apply to one measure, the group with the higher precedence is applied first. Item ordinal only controls display order within a group. Names and sort order don't affect evaluation.

Q19 Answer: D M2 · Create model calculations by using DAX

Model measures are part of the semantic model, so Excel and every report can use them. Visual calculations exist only on their visual. Report-level measures exist only in that report. Filters aren't calculations.

Q20 Answer: C M2 · Create model calculations by using DAX

Non-additive logic evaluated at the total level sees the total, not each person. Iterating the salespeople with SUMX applies the rule per person and adds the results, at every level. Hiding totals avoids the issue rather than solving it. ALL computes one value for everyone.

Q21 Answer: A M2 · Create model calculations by using DAX

HASONEVALUE checks that exactly one currency is in context before converting, and SELECTEDVALUE returns that rate. MAX or SUM of rates gives a meaningless number when several are selected. ISBLANK on a column needs a row context and doesn't test the selection.

Q22 Answer: D M3 · Optimize model performance

User-defined aggregations need the summary table's columns mapped (Sum, GroupBy and so on) to the detail table's columns in Manage aggregations. The engine then redirects matching queries to the in-memory summary. Renaming or relating the tables doesn't enable aggregation awareness.

Q23 Answer: A V1 · Create reports

The Paginated report visual renders a published paginated report inside a Power BI report and can pass field values into its parameters, so slicers drive it. Images and links don't stay in sync with the page's filters.

Q24 Answer: B V1 · Create reports

A JSON theme can set default formatting for specific visual types through visualStyles, so every new card follows the standard. Manual formatting and copying don't scale and drift over time.

Q25 Answer: C V1 · Create reports

Suggesting content for a new report page gives the author candidate page ideas to choose from before Copilot builds one. Summarising describes the model. A narrative visual describes data on a page.

Q26 Answer: B V1 · Create reports

Search lets users type to find a value in a long list. Splitting by letter is clumsy. A between slicer is for numeric and date ranges.

Q27 Answer: C V2 · Enhance reports for usability and storytelling

Automatic page refresh re-queries the source. Imported data only changes on refresh, so the feature applies to DirectQuery and similar sources. The other options aren't related.

Q28 Answer: D V2 · Enhance reports for usability and storytelling

Alt text can be driven by a measure, so screen readers announce current, filtered values. Fixed alt text goes stale. Text boxes add clutter and aren't tied to the visual. High contrast helps low-vision users but doesn't add descriptions.

Q29 Answer: D V2 · Enhance reports for usability and storytelling

Sync slicers groups let separate slicers on the same field share their selection, even if they weren't copied from each other. A report filter applies everywhere but isn't interactive in the same way.

Q30 Answer: B V2 · Enhance reports for usability and storytelling

A report-level setting switches the default interaction for every visual to filtering. Edit interactions is still available for exceptions. Themes and persistent filters don't control interactions.

Q31 Answer: B, C V2 · Enhance reports for usability and storytelling

Screen readers announce alt text and titles. Colour-only encoding, broken tab order and text embedded in images are all accessibility problems.

Q32 Answer: C V3 · Identify patterns and trends

Sensitivity controls how far a point must be from the expected range to be flagged. Lowering it reduces false positives. Raising it flags even more points. The date axis is required for the feature.

Q33 Answer: A V3 · Identify patterns and trends

Ignoring the last point excludes the incomplete month from the model used for the forecast. The confidence interval only changes the shaded band. A seasonality of 1 removes the seasonal pattern.

Q34 Answer: A V3 · Identify patterns and trends

Binning creates equal-size numeric ranges, here 7 days wide, which a column chart then shows as a histogram. Manual grouping is tedious. Clustering is for scatter charts. A slicer filters rather than buckets.

Q35 Answer: B S1 · Create and manage workspaces and assets

The large semantic model storage format lets models grow beyond the default size limit, up to the capacity's limits, and improves XMLA write operations. The other options don't affect model size limits.

Q36 Answer: A S1 · Create and manage workspaces and assets

External tools write to published models through the XMLA endpoint, which must be set to Read Write in the capacity settings. The other features don't let tools change models.

Q37 Answer: B S1 · Create and manage workspaces and assets

Deployment pipelines let you choose which items to deploy, so only the changed report moves to Test. Deploying everything works but risks overwriting other work. Publishing directly bypasses the pipeline.

Q38 Answer: B S1 · Create and manage workspaces and assets

The scheduled refresh UI allows up to 48 refreshes a day, in 30-minute slots, on Premium or Fabric capacity. Fresher data calls for DirectQuery, a hybrid table, or API-driven refreshes. Eight a day is the Pro limit.

Q39 Answer: D S2 · Secure and govern Power BI items

With SSO for DirectQuery through the gateway, each user's identity is passed to the source, so the source's own security applies. Otherwise every query runs under the stored credentials. Recreating the rules as RLS duplicates logic. A personal gateway doesn't support DirectQuery.

Q40 Answer: C S2 · Secure and govern Power BI items

Tenant settings in the admin portal control whether content can be shared with external users and what guests can do. Report, workspace and privacy-level settings don't govern external sharing for the whole organisation.

Q41 Answer: B S2 · Secure and govern Power BI items

Audiences in one app control which content each group of users can see, without duplicating reports. RLS filters rows inside a model rather than hiding reports. Labels classify content.

Q42 Answer: C P1 · Get or connect to data

DirectQuery to the KQL database queries the latest events, and automatic page refresh (allowed at short intervals on capacity) re-queries regularly. Scheduled Import refresh can't run every minute. CSV exports and alerts don't provide live visuals.

Q43 Answer: D M3 · Optimize model performance

Other is mostly time spent waiting for other visuals, so the number of visuals is the problem, not individual queries. Fewer visuals means fewer queries competing. The DAX is already fast, and storage mode isn't the bottleneck.

Q44 Answer: A V1 · Create reports

A funnel chart shows how many items reach each stage of a sequential process, making drop-off between stages visible. Waterfall charts show contributions to a total. Scatter charts compare two measures. Treemaps show part-to-whole.

Q45 Answer: A S2 · Secure and govern Power BI items

Contributors, like Members and Admins, have edit rights and bypass RLS. As Viewers with Build permission, the analysts can create their own reports on the model, and RLS filters their data. The function choice and labels don't change the bypass.

Set 08

Analytics, AI and Copilot

AI visuals, the Analytics pane, Copilot, advanced DAX patterns and distribution, at full blueprint weight.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 3 · Advanced

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

One Excel workbook holds 12 monthly sheets with identical layouts, and a new sheet is added each month. You need all sheets, including future ones, in one table. What should you do?

- ☐ A Connect to each sheet separately and append the twelve queries together
- ☐ B Use Transpose on the first sheet
- ☐ C Filter the navigation table to Kind = "Sheet", then expand Data
- ☐ D Use the Folder connector pointed at the workbook's file path

Q2 SINGLE ANSWER

The SharePoint folder connector asks for a URL. Your files are in <https://contoso.sharepoint.com/sites/Finance/Shared Documents/Exports>. What should you enter?

- ☐ A The URL of one file
- ☐ B A OneDrive personal URL
- ☐ C The site URL: <https://contoso.sharepoint.com/sites/Finance>
- ☐ D The full folder URL: [.../sites/Finance/Shared Documents/Exports](https://contoso.sharepoint.com/sites/Finance/Shared Documents/Exports)

Q3 SINGLE ANSWER

An Azure SQL Database is reachable only through a private endpoint in an Azure virtual network, and no on-premises servers exist. Scheduled refresh in the service must reach it. Which gateway option fits?

- ☐ A Publish to web
- ☐ B A personal-mode gateway on a laptop
- ☐ C A virtual network (VNet) data gateway
- ☐ D No gateway, because Azure SQL is always public

Q4 SINGLE ANSWER

A 300 MB source is updated once a night. Reports need fast visuals and complex time-intelligence DAX. No real-time requirement exists. Which storage mode should you choose?

- ☐ A DirectQuery
- ☐ B Import
- ☐ C Dual for every table
- ☐ D Live connection

Q5 SINGLE ANSWER

A merge on Email misses many matches because one table has "A.Kumar@contoso.com" and the other has "a.kumar@contoso.com". What should you do before merging?

- ☐ A Change the join kind to Full outer
 - ☐ B Convert the Email column to lowercase in both queries
 - ☐ C Remove duplicates on Email
 - ☐ D Use Trim on one query
-

Q6 SINGLE ANSWER

An Excel export contains completely empty rows between blocks of data, and they appear as rows of nulls. What should you do?

- ☐ A Fill down
 - ☐ B Replace errors
 - ☐ C Use first row as headers
 - ☐ D Remove Rows → Remove blank rows
-

Q7 SINGLE ANSWER

Twenty CSV sources need the same 15 cleaning steps. You want to define the steps once and apply them to each source. What should you create?

- ☐ A A custom function, invoked on each source
 - ☐ B Twenty duplicated queries, one per CSV source
 - ☐ C A calculation group with one item per source
 - ☐ D A DAX calculated table
-

Q8 SINGLE ANSWER

A Tickets table has a Status column (Open, Pending, Closed). You need one row per Team with a column per status holding the number of tickets. Which transformation should you use?

- ☐ A Transpose the table
 - ☐ B Pivot the Status column, counting TicketID
 - ☐ C Unpivot the Status column into attribute-value pairs
 - ☐ D Merge Tickets with itself
-

Q9 SINGLE ANSWER

You need a MonthStart column (the first day of each order's month) for a monthly fact table, without writing M. Which option should you use?

- ☐ A Add Column → Date → Month → Start of Month
- ☐ B Add Column → Statistics → Count
- ☐ C Add Column → Index column
- ☐ D Transform → Round

Q10 MULTIPLE RESPONSE — CHOOSE TWO

A query against SQL Server must keep folding. Which two steps typically fold into the SQL sent to the server?

- ☐ A Filter rows on a column value
 - ☐ B Change type using a non-default locale
 - ☐ C Add an index column
 - ☐ D Remove columns
 - ☐ E A custom column that calls a custom M function
-

Q11 BUILD LIST — SEQUENCE

You need to combine 50 CSV files from a folder that share one layout. Put the actions in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Choose Combine & Transform Data
 - ☐ B Append each file manually
 - ☐ C Apply cleaning steps in the Transform Sample File query so they run for every file
 - ☐ D Get data → Folder and select the folder
 - ☐ E Choose the sample file and confirm the delimiter and settings
 - ☐ F Turn off Enable load on the combined query
-

Q12 SINGLE ANSWER

A fact table has eight low-cardinality Yes/No flag columns (IsOnline, IsPromo, IsGift...), and authors find them cluttered. Which modelling pattern groups them efficiently?

- ☐ A A junk dimension of the distinct flag combinations
 - ☐ B Calculated columns in a Flags table
 - ☐ C Hiding all the flags
 - ☐ D A separate dimension table for each of the eight flags
-

Q13 SINGLE ANSWER

Sales has an OrderNumber column used only to identify orders and to drill to order detail. Should you create an Order dimension for it?

- ☐ A No. Keep it in the fact table as a degenerate dimension.
 - ☐ B No. Delete the column.
 - ☐ C Yes, related to Sales with a many-to-many relationship
 - ☐ D Yes. Every descriptive column must move to a dimension table.
-

Q14 SINGLE ANSWER

A Store table has Latitude and Longitude columns. Map visuals must place stores exactly at those coordinates. What should you set?

- ☐ A Data category Latitude and Longitude on the respective columns
- ☐ B Summarize by Sum
- ☐ C Data category City on both columns, placed in the map's Location well
- ☐ D A hierarchy of the two columns

Q15 SINGLE ANSWER

A Revenue measure must display as 1.2K, 3.4M or 2.1B depending on its size, while keeping the value numeric for sorting and further calculations. What should you use?

- ☐ A Three separate measures
 - ☐ B A text column with the formatted value
 - ☐ C A dynamic format string for the measure
 - ☐ D `FORMAT ( [Revenue], "#,0.0,,M" )` as the measure itself
-

Q16 SINGLE ANSWER

A calculation group's YTD item must not apply to the Margin % measure, which should be returned unchanged. Which item expression should you use?

- ☐ A `IF ( ISBLANK ( SELECTEDMEASURE () ), BLANK () )`
 - ☐ B `CALCULATE ( [Margin %], DATESYTD ( 'Date'[Date] ) )`
 - ☐ C `IF ( SELECTEDMEASURENAME () = "Margin %", CALCULATE ( SELECTEDMEASURE (), DATESYTD ( 'Date'[Date] ) ), SELECTEDMEASURE () )`
 - ☐ D `IF ( SELECTEDMEASURENAME () = "Margin %", SELECTEDMEASURE (), CALCULATE ( SELECTEDMEASURE (), DATESYTD ( 'Date'[Date] ) ) )`
-

Q17 SINGLE ANSWER

You need a calculated column on Customer that ranks each customer by lifetime sales across all customers (1 = highest). Which expression is correct?

- ☐ A `RANKX ( ALL ( Customer ), [Total Sales] )`
 - ☐ B `TOPN ( 1, Customer, [Total Sales] )`
 - ☐ C `RANKX ( Customer, SUM ( Sales[Amount] ) )`
 - ☐ D `RANK.EQ ( [Total Sales], Customer[CustomerKey] )`
-

Q18 SINGLE ANSWER

Sales relates to Date on an integer DateKey (20260131). Sales YTD returns the same value as Sales on every row. Date[Date] is of Date type and holds unique, contiguous dates. What should you do?

- ☐ A Change DateKey to Text
 - ☐ B Turn on Auto date/time
 - ☐ C Use TOTALYTD with DateKey
 - ☐ D Mark the Date table as a date table, using Date[Date]
-

Q19 SINGLE ANSWER

Which measure returns the quantity-weighted average selling price?

- ☐ A `AVERAGEX ( Sales, Sales[UnitPrice] )`
- ☐ B `AVERAGE ( Sales[UnitPrice] )`
- ☐ C `DIVIDE ( SUMX ( Sales, Sales[Quantity] * Sales[UnitPrice] ), COUNTROWS ( Sales ) )`
- ☐ D `DIVIDE ( SUMX ( Sales, Sales[Quantity] * Sales[UnitPrice] ), SUM ( Sales[Quantity] ) )`

Q20 SINGLE ANSWER

A disconnected Band table has Band, Min and Max columns (Low 0-1,000, Mid 1,000-10,000, High 10,000+). A measure must count customers whose sales fall in the band on each row of a visual. Which expression is correct?

- ☐ A DISTINCTCOUNT (Band[Band])
- ☐ B COUNTROWS (Band)
- ☐ C COUNTROWS (FILTER (VALUES (Customer[CustomerKey]), [Total Sales] >= MIN (Band[Min]) && [Total Sales] < MAX (Band[Max])))
- ☐ D COUNTROWS (FILTER (Customer, SUM (Sales[Amount]) >= MIN (Band[Min]) && SUM (Sales[Amount]) < MAX (Band[Max])))

Q21 SINGLE ANSWER

A model loads ten years of transactions, but every report shows only the last two years, and the business confirms older data isn't needed. What is the most effective way to reduce model size?

- ☐ A Hide old rows in each visual
- ☐ B Filter the query in Power Query to the last two years
- ☐ C Create measures that ignore dates older than two years
- ☐ D Add a report-level filter that keeps only the last two years

Q22 SINGLE ANSWER

A table visual lists every transaction (over a million rows) with eight columns, and the page is slow to render. Users only ever look at recent, filtered subsets. What is the best fix?

- ☐ A Turn off totals and keep the visual otherwise unchanged
- ☐ B Change the theme
- ☐ C Add more columns
- ☐ D Add filters so the visual returns far fewer rows

Q23 SINGLE ANSWER

A matrix shows months under years. You need a running total that restarts at the beginning of each year, as a visual calculation. Complete the expression.

YTD running = ____

- ☐ A RUNNINGSUM ([Sales])
- ☐ B RUNNINGSUM ([Sales], HIGHESTPARENT)
- ☐ C COLLAPSE ([Sales], ROWS)
- ☐ D MOVINGAVERAGE ([Sales], 12)

Q24 SINGLE ANSWER

A narrative visual with Copilot summarises the whole page, but executives want it to describe only the three KPI visuals at the top. What should you do?

- ☐ A Delete the other visuals from the page
- ☐ B Replace it with a text box that describes the KPIs
- ☐ C Scope the visual to summarise selected visuals
- ☐ D Move the KPIs to a dashboard

Q25 SINGLE ANSWER

A chart must show monthly revenue as columns and margin % as a line, each on its own axis scale. Which visual should you use?

- ☐ A Clustered column chart with both measures on one axis
- ☐ B Two separate pie charts
- ☐ C Line and clustered column chart with a secondary axis
- ☐ D Stacked area chart

Q26 SINGLE ANSWER

A slicer must let users pick a year and then expand it to pick individual months within that year, in one control. What should you do?

- ☐ A Make a hierarchy slicer with Year and Month
- ☐ B Use a between date slicer on the Date column
- ☐ C Use two slicers, one for Year and one for Month
- ☐ D Use a relative date slicer

Q27 DRAG AND DROP — MATCH

Match each layout requirement to the visual that fits it best.

Choices — each may be used once, more than once, or not at all

- ☐ A Matrix
- ☐ B Card
- ☐ C Treemap
- ☐ D Line chart
- ☐ E Table

Requirement	Visual
1. Category in rows, year in columns, with subtotals on both	
2. A flat list of invoices with one column per field and a total row	
3. One headline number, such as total revenue this year	
4. Monthly revenue over three years, to show the trend	

Q28 SINGLE ANSWER

Users get lost after choosing many slicer values and want one click to reset every slicer on the page. What is the simplest built-in solution?

- ☐ A Ask users to refresh the browser
- ☐ B Insert a button with the Clear all slicers action
- ☐ C Lock all slicers
- ☐ D Create a bookmark for every slicer

Q29 SINGLE ANSWER

A report-page tooltip about product categories must appear automatically on every visual that uses Product[Category], without configuring each visual. What should you do on the tooltip page?

- ☐ A Hide the tooltip page
- ☐ B Create a bookmark
- ☐ C Add Product[Category] to its Tooltip fields well
- ☐ D Set the Tooltip option to Default on each visual that uses Category

Q30 SINGLE ANSWER

When users drill down from Year to Quarter in a column chart, other visuals on the page don't change. They should be filtered to the drilled-into year. What should you configure?

- ☐ A Turn on Drilling filters other visuals
- ☐ B Set Edit interactions to None for the chart
- ☐ C A drillthrough page
- ☐ D Sync slicers

Q31 SINGLE ANSWER

A report is always saved by authors on whichever page they were last editing, so readers open it on random pages. Readers must always land on the Overview page. What is the simplest fix?

- ☐ A Hide every other page
- ☐ B Add a bookmark navigator with Overview as its first bookmark
- ☐ C Save and publish with Overview as the active page
- ☐ D Use persistent filters

Q32 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about the Sync slicers pane, select Yes if it is true.

Statement	Yes	No
1. A slicer can be synced to a page without being visible on that page.	☐	☐
2. A slicer can be visible on a page without sharing its selection with the other pages.	☐	☐
3. Synced slicers share their selections across different reports in the same workspace.	☐	☐

Q33 SINGLE ANSWER

You can't find the Find anomalies option for a column chart of daily orders. What should you change?

- ☐ A Add a legend
- ☐ B Use a line chart with a continuous date axis
- ☐ C Use a pie chart
- ☐ D Switch the X-axis to categorical in the column chart

Q34 SINGLE ANSWER

The service-level target is that 95% of tickets close within 48 hours. A line chart of the weekly on-time rate must show the target as a horizontal reference. What should you add?

- ☐ A A constant line at 0.95
- ☐ B An average line from the Analytics pane
- ☐ C A forecast
- ☐ D A trend line on the weekly on-time rate

Q35 SINGLE ANSWER

Analysts outside the Finance workspace can't find the endorsed Finance semantic model in the OneLake catalog to request access. What should you configure on the model?

- ☐ A Publish it to the web
- ☐ B Move it to My workspace
- ☐ C Remove its endorsement so it shows in search
- ☐ D Make the endorsed model discoverable

Q36 SINGLE ANSWER

Users requesting access to a workspace's content should reach the BI team's distribution list rather than individual admins. What should you configure?

- ☐ A A data alert
- ☐ B A deployment rule in the pipeline
- ☐ C The app's theme
- ☐ D The workspace contact list

Q37 SINGLE ANSWER

A newly published app must appear automatically for every member of the Sales security group, without them looking for it under Apps. What should you do?

- ☐ A Use Publish to web
- ☐ B Share the workspace URL with the Sales group by email
- ☐ C Add the Sales group to the workspace as Viewers
- ☐ D Turn on automatic install for the app audience

Q38 SINGLE ANSWER

Users belong to a Region role (filters Region) and a Product role (filters Category). They see the union of both roles' rows, but the business requires the intersection (their region and their category only). What should you do?

- ☐ A Create one role filtering both Region and Category
- ☐ B Use bidirectional relationships
- ☐ C Assign users to both roles and set role precedence
- ☐ D Remove RLS and use page filters

Q39 SINGLE ANSWER

You're publishing a workspace app. App users must also be able to build their own reports on the app's semantic models. What can you do as part of publishing?

- ☐ A Give app users the workspace Admin role
- ☐ B Grant app users Build permission on the semantic models
- ☐ C Turn on persistent filters so users can save their views
- ☐ D Use Publish to web

Q40 SINGLE ANSWER

A new user can open a report on an RLS-secured model, but every visual shows an error or no data. Other users are fine. What is the most likely cause?

- ☐ A The user isn't a member of any RLS role on the model
- ☐ B The model has too many measures
- ☐ C The report theme failed to load
- ☐ D The user's browser is out of date

Q41 SINGLE ANSWER

Policy says users may lower a report's sensitivity label (for example from Confidential to General) only if they explain why. What should be configured?

- ☐ A An app audience restricted to label owners
- ☐ B A data alert
- ☐ C Certification of the report by a Fabric admin
- ☐ D A label policy that requires justification

Case study · Proseware Telecom

Questions 42–45

Existing environment

Proseware is a mobile operator with two million subscribers. The Customer table includes StartDate, ChurnDate (blank for active customers), TenureMonths and Phone. Phone numbers were captured in mixed formats, such as "+91 98480 12345", "098480-12345" and "(98480) 12345". Executives work mainly in Microsoft Teams.

Requirements

1. Phone numbers must be stored as digits only, so they can be matched against the billing system.
2. A measure must count customers who were active at the start of the selected period.
3. Analysts want to see how churn varies across tenure, in six-month buckets.
4. Executives must be able to open the churn report from their leadership channel in Teams.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

Which custom column formula keeps only the digits?

- ☐ A Number.From ([Phone])
- ☐ B Text.Remove ([Phone], { "0".."9" })
- ☐ C Text.Select ([Phone], { "0".."9" })
- ☐ D Text.Trim ([Phone])

Q43 SINGLE ANSWER

Which measure counts customers active at the start of the selected period? The Date table doesn't filter Customer.

- ☐ A CALCULATE (COUNTROWS (Customer), ISBLANK (Customer[ChurnDate]))
- ☐ B VAR S = MIN ('Date'[Date]) RETURN COUNTROWS (FILTER (Customer, Customer[StartDate] < S && (ISBLANK (Customer[ChurnDate]) || Customer[ChurnDate] >= S)))
- ☐ C VAR S = MAX ('Date'[Date]) RETURN COUNTROWS (FILTER (Customer, Customer[StartDate] < S && (ISBLANK (Customer[ChurnDate]) || Customer[ChurnDate] >= S)))
- ☐ D COUNTROWS (Customer)

Q44 SINGLE ANSWER

How should you show churn by tenure bucket?

- ☐ A Add a forecast on tenure in six-month steps
- ☐ B Create bins of size 6 on TenureMonths
- ☐ C Use a gauge per bucket
- ☐ D Create clusters on TenureMonths

Q45 SINGLE ANSWER

How do you meet the Teams requirement?

- ☐ A Export the report to PDF weekly and post it in the channel
- ☐ B Email the .pbix to executives
- ☐ C Use Publish to web and post the link in the channel
- ☐ D Add the report as a tab in the leadership Teams channel

End of Set 08 — answers follow on the next page.

Set 08 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	C	P1		16	D	M2		31	C	V2	
2	C	P1		17	A	M2		32	Yes · Yes · No	V2	
3	C	P1		18	D	M2		33	B	V3	
4	B	P1		19	D	M2		34	A	V3	
5	B	P2		20	C	M2		35	D	S1	
6	D	P2		21	B	M3		36	D	S1	
7	A	P3		22	D	M3		37	D	S1	
8	B	P3		23	B	V1		38	A	S2	
9	A	P3		24	C	V1		39	B	S2	
10	A, D	P3		25	C	V1		40	A	S2	
11	D → A → E → C	P3		26	A	V1		41	D	S2	
12	A	M1		27	1→A 2→E 3→B 4→D	V1		42	C	P2	
13	A	M1		28	B	V2		43	B	M2	
14	A	M1		29	C	V2		44	B	V3	
15	C	M1		30	A	V2		45	D	S1	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: C P1 · Get or connect to data

The workbook's navigation table lists every sheet. Keeping the sheet rows and expanding their Data column combines all of them, and new sheets are picked up on refresh. Connecting to sheets one by one needs editing each month. The Folder connector expects a folder of files.

Q2 Answer: C P1 · Get or connect to data

The SharePoint folder connector expects the site root URL. It then lists all files in the site's libraries, and you filter on Folder Path to the Exports folder. Entering the folder or file URL fails or returns nothing.

Q3 Answer: C P1 · Get or connect to data

A VNet data gateway is a managed gateway injected into your virtual network, so the service can reach private Azure resources without installing anything. Personal mode is single-user and needs a machine that's always on. A private endpoint means the database isn't public.

Q4 Answer: B P1 · Get or connect to data

Import gives the best query performance and full DAX support, and nightly freshness matches the source. DirectQuery adds latency and restricts some DAX patterns for no benefit. Dual is for composite models, and live connection is for existing semantic models.

Q5 Answer: B P2 · Profile and clean the data

Power Query comparisons are case-sensitive, so the values must be standardised before the merge. Lowercasing both sides is the simplest fix. Trim deals with spaces, not case. Changing the join kind or removing duplicates doesn't make the values match.

Q6 Answer: D P2 · Profile and clean the data

Remove blank rows deletes rows where every column is null or empty, leaving the real data. Fill down would copy values into the empty rows. Replace errors and header promotion don't address them.

Q7 Answer: A P3 · Transform and load the data

A Power Query function wraps the steps with a parameter, such as a file path or table, and can be invoked for every source, so changes are made once. Duplicated queries repeat the logic twenty times. Calculation groups and DAX tables can't run Power Query steps.

Q8 Answer: B P3 · Transform and load the data

Pivot turns each status into a column, and counting TicketID gives the number of tickets per team and status. Unpivot does the reverse. Transpose rotates the whole table. Merge joins tables.

Q9 Answer: A P3 · Transform and load the data

The Date menu has Start of Month, which returns the first day of the month for each date. That's ideal as a monthly key. The other options don't produce dates.

Q10 Answer: A, D P3 · Transform and load the data

Row filters and column selection translate directly into WHERE and SELECT clauses. Index columns, custom M functions and locale-specific type conversions usually can't be expressed in SQL, so folding stops at that step.

Q11 Answer: D → A → E → C P3 · Transform and load the data

The Folder connector lists the files. Combine & Transform builds a sample-file query and a function. Cleaning steps go in the sample-file transform so they apply to each file before the files are appended.

Q12 Answer: A M1 · Design and implement a data model

A junk dimension collects unrelated low-cardinality attributes into one small table of their combinations, so the fact only needs one key. Eight separate dimensions add relationships. Hiding them removes useful slicing.

Q13 Answer: A M1 · Design and implement a data model

An identifier with no other attributes belongs in the fact as a degenerate dimension. A separate table would just duplicate the column and add a relationship. Deleting it removes drill capability.

Q14 Answer: A M1 · Design and implement a data model

Categorising the columns as Latitude and Longitude and placing them in those wells plots exact coordinates without geocoding. City categories would make Bing interpret numbers as place names. Coordinates should not be summed.

Q15 Answer: C M1 · Design and implement a data model

Dynamic format strings change how a measure is displayed based on a DAX expression while the value stays numeric. FORMAT returns text, which breaks sorting, totals and charts. Text columns and separate measures add complexity.

Q16 Answer: D M2 · Create model calculations by using DAX

SELECTEDMEASURENAME returns the name of the measure being evaluated, so the item can skip Margin % and apply YTD to everything else. Hard-coding a measure breaks the item for every other measure. Swapping the IF branches applies YTD only to Margin %, and the ISBLANK test doesn't implement YTD.

Q17 Answer: A M2 · Create model calculations by using DAX

RANKX over all customers evaluates [Total Sales] for each one, with context transition from the measure reference, and ranks the current row against them. SUM without context transition returns the grand total for every row, so every customer would tie. RANK.EQ isn't used this way, and TOPN returns a table.

Q18 Answer: D M2 · Create model calculations by using DAX

When the relationship uses a non-date key, time-intelligence functions need the table marked as a date table, so the engine can remove filters from the whole Date table during the calculation. DateKey isn't a date, so TOTALYTD can't use it. Auto date/time doesn't apply to custom date tables.

Q19 Answer: D M2 · Create model calculations by using DAX

A weighted average divides total revenue by total quantity, so lines with more units count more. AVERAGE and AVERAGEX give each order line's price equal weight, whatever its quantity, and dividing revenue by the row count gives revenue per line, not price per unit.

Q20 Answer: C M2 · Create model calculations by using DAX

Dynamic segmentation iterates customers, evaluates each one's sales, and keeps those within the current band's bounds, which come from the band row in the visual. SUM inside FILTER has no context transition, so it tests the same total for every customer rather than each customer's own sales. Counting the Band table or its bands doesn't evaluate customers.

Q21 Answer: B M3 · Optimize model performance

Removing unnecessary rows at load cuts memory and refresh time. Report filters and measures still leave all ten years in the model. Pair this with a rolling date filter or incremental refresh so the window moves forward.

Q22 Answer: D M3 · Optimize model performance

Huge row counts in table visuals are expensive to query and render. Limiting the rows returned, by filtering or requiring a selection first, solves both. Turning off totals helps a little at best.

Q23 Answer: B V1 · Create reports

The reset parameter HIGHESTPARENT restarts the running sum when the top level of the row hierarchy, the year, changes. Without a reset it runs across all years. MOVINGAVERAGE averages, and COLLAPSE returns the parent's value.

Q24 Answer: C V1 · Create reports

The Copilot narrative visual can summarise the entire report, the current page or selected visuals, so you can scope it to the three KPIs. Removing visuals or switching to static text loses functionality.

Q25 Answer: C V1 · Create reports

Combo charts plot columns and a line together, and a secondary Y-axis lets a percentage share the chart with currency values. The other visuals can't show both measures on different scales together.

Q26 Answer: A V1 · Create reports

Adding several levels to a slicer creates a hierarchy slicer with expandable levels. Two separate slicers work but aren't one control. Relative and between date slicers select ranges, not a hierarchy.

Q27 Answer: 1→A 2→E 3→B 4→D V1 · Create reports

A matrix gives a cross-tab with row and column groups and subtotals. A table is a flat list. A card shows a single value. A line chart shows a trend over time. A treemap shows part-to-whole with nested rectangles, which none of these need.

Q28 Answer: B V2 · Enhance reports for usability and storytelling

The Clear all slicers button action resets every slicer on the page in one click. Refreshing doesn't necessarily clear saved filters. A bookmark per slicer is overkill. Locking prevents use.

Q29 Answer: C V2 · Enhance reports for usability and storytelling

Fields in the tooltip page's Tooltip fields well make the page appear automatically on any visual that uses those fields. Visuals left on Auto pick it up. Setting Default turns the custom page off. Hiding the page has no effect on tooltips.

Q30 Answer: A V2 · Enhance reports for usability and storytelling

The Drilling filters other visuals option makes a drill-down action filter the other visuals on the page. It's off by default for some visuals. Setting interactions to None stops filtering altogether.

Q31 Answer: C V2 · Enhance reports for usability and storytelling

The service opens a report on the page that was active when it was saved and published. Ending authoring on Overview fixes the landing page. Hiding pages removes them from navigation. Bookmark navigators and persistent filters don't control the landing page.

Q32 Answer: Yes · Yes · No V2 · Enhance reports for usability and storytelling

Sync and Visible are independent check boxes, so a slicer can filter a page while hidden, or appear on a page independently. Syncing works only between pages of the same report.

Q33 Answer: B V3 · Identify patterns and trends

Anomaly detection is available for line charts with a time series on a continuous axis. Column charts, legends and a categorical axis don't enable it.

Q34 Answer: A V3 · Identify patterns and trends

A constant line marks a fixed value, such as a target, that doesn't change with the data. An average line moves with the data. Trend lines and forecasts describe the data's direction.

Q35 Answer: D S1 · Create and manage workspaces and assets

Discoverability lets users who don't have access see that an endorsed item exists and request access. Publish to web makes it public. Moving it or removing endorsement makes discovery harder.

Q36 Answer: D S1 · Create and manage workspaces and assets

The workspace contact list determines who receives notifications and requests about the workspace. Data alerts, themes and deployment rules don't route access requests.

Q37 Answer: D S1 · Create and manage workspaces and assets

Push-installed apps appear in users' app lists automatically, if the tenant allows pushing apps. Workspace access gives a different experience and exposes all content. Publish to web is public.

Q38 Answer: A S2 · Secure and govern Power BI items

Membership in several roles is additive, which gives a union. To require both conditions, the filters must be in the same role, where filters on different tables combine as an intersection. Roles have no precedence setting.

Q39 Answer: B S2 · Secure and govern Power BI items

App settings can grant Build permission on the underlying semantic models to everyone with app access, so they can create their own reports. Workspace Admin is far more access than needed. The other options don't grant Build.

Q40 Answer: A S2 · Secure and govern Power BI items

When RLS is defined, users with read access who aren't in any role get no data. Adding the user, or their group, to the right role fixes it. The other causes would affect everyone.

Q41 Answer: D S2 · Secure and govern Power BI items

Purview label policies can require users to provide a justification when they lower a classification or remove a label, and the action is audited. Certification, audiences and alerts are unrelated.

Q42 Answer: C P2 · Profile and clean the data

Text.Select keeps only the characters in the given list, here the digits, removing spaces, brackets, dashes and plus signs. Text.Remove would remove the digits instead. Trim handles spaces only. Number.From fails on the formatting characters.

Q43 Answer: B M2 · Create model calculations by using DAX

The period start comes from the Date selection, and a customer was active then if they started before it and had not churned before it. Using MAX tests the end of the period instead. COUNTROWS(Customer) counts everyone. Counting customers with a blank churn date gives today's active base, not the base at the start of the period.

Q44 Answer: B V3 · Identify patterns and trends

Bins of size 6 turn tenure into equal six-month buckets, which a column chart can show against churn rate. Clustering finds groups on a scatter chart. Forecasts project time series. Gauges show single values.

Q45 Answer: D S1 · Create and manage workspaces and assets

Power BI reports can be added as tabs in Teams channels, respecting each user's Power BI permissions, and apps can be opened in the Power BI app for Teams. Emailing files, public links or PDFs lose interactivity, governance, or both.

Exam simulation A

A mixed paper at real exam difficulty: every sub-area, every question format, no theme. Sit it under timed conditions.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 3 · Exam simulation

12 Prepare the data 25-30%	12 Model the data 25-30%	13 Visualize and analyze the data 25-30%	8 Manage and secure Power BI 15-20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

A supplier sends a monthly price list as a PDF containing a formatted table. You need the table in Power BI. Which connector should you use?

- ☐ A Text/CSV, with the delimiter set to a tab
- ☐ B Blank query with the table typed in
- ☐ C Web
- ☐ D PDF, then pick the table in the Navigator

Q2 SINGLE ANSWER

An Excel workbook is stored in OneDrive for Business. Scheduled refresh in the service must not need a gateway. How should you connect in Power BI Desktop?

- ☐ A Copy the file to a network share
- ☐ B Use the file's OneDrive/SharePoint web URL
- ☐ C Email the file to yourself each month
- ☐ D Use the C:\Users\...\OneDrive path with the Excel connector

Q3 MULTIPLE RESPONSE — CHOOSE TWO

Which two statements about Direct Lake storage mode are true?

- ☐ A It can connect to any on-premises SQL Server database
- ☐ B It requires the semantic model to be on Microsoft Fabric capacity
- ☐ C It copies the data into the model on a refresh schedule, like Import
- ☐ D It works in a Pro workspace on shared capacity
- ☐ E It reads data from Delta tables in OneLake

Q4 SINGLE ANSWER

A report is live-connected to a published semantic model. An author wants to add a calculated column. Which statement is correct?

- ☐ A Calculated columns can be added freely in a live connection
- ☐ B Nothing can be added in a live connection
- ☐ C Only report-level measures can be added, not columns
- ☐ D Calculated columns are added automatically to the shared model

Q5 SINGLE ANSWER

Refresh fails with "Expression.Error: The column 'Region' of the table wasn't found". What has most likely happened?

- ☐ A The model has an RLS role on Region
- ☐ B Region contains null values
- ☐ C A source column was renamed or removed
- ☐ D The gateway is offline, so the source can't be read

Q6 SINGLE ANSWER

In an order-lines source, a null Quantity means the line was entered without units. The business says these should be treated as 0. Where and how should you fix this?

- ☐ A In each visual, set Show items with no data
- ☐ B In DAX, wrap every measure in IF(ISBLANK())
- ☐ C In Power Query, replace null with 0
- ☐ D Delete the rows with a null Quantity

Q7 SINGLE ANSWER

A custom column divides Revenue by Units, and rows with zero units produce errors. The column must be null for those rows instead. Complete the custom column formula.

```
= Table.AddColumn ( Source, "PricePerUnit", each ____ )
```

- ☐ A [Revenue] / [Units] ?? null
- ☐ B if [Units] then [Revenue] / [Units]
- ☐ C try [Revenue] / [Units] otherwise null
- ☐ D Number.From ([Revenue] / [Units])

Q8 SINGLE ANSWER

A merge must match supplier names such as "IBM" to "International Business Machines". The data team keeps a two-column list of known equivalents. What should you use?

- ☐ A Remove duplicates
- ☐ B Group by supplier name and keep the first row
- ☐ C A Left anti join against the list of equivalents
- ☐ D Fuzzy merge with a transformation table

Q9 SINGLE ANSWER

You need an OrderSequence column numbering each customer's orders in date order (1 for their first order, 2 for the second, and so on). What is a correct Power Query approach?

- ☐ A Merge the table with itself on OrderDate
- ☐ B Sort by OrderDate, group by CustomerID (All rows), and index each group
- ☐ C Pivot OrderDate
- ☐ D Sort by CustomerID and OrderDate, then add one index column to the whole table

Q10 DRAG AND DROP — MATCH

Match each query to the load setting it should have.

Choices — each may be used once, more than once, or not at all

- ☐ A Leave Enable load and Include in report refresh on
- ☐ B Clear Enable load
- ☐ C Delete the query
- ☐ D Clear Include in report refresh

Query	Setting
1. Staging query used only as the source of three reference queries	
2. Historical archive table, loaded once, whose source never changes	
3. Sales fact table refreshed nightly	

Q11 SINGLE ANSWER

A Notes column contains free text, and you need the first ten characters as a ShortNote column, without writing M. Which option should you use?

- ☐ A Split column → By delimiter
- ☐ B Transform → Trim
- ☐ C Add Column → Extract → First characters (10)
- ☐ D Add Column → Index column

Q12 SINGLE ANSWER

An Employee table has EmployeeID and ManagerID, a parent-child hierarchy of up to four levels. Users want a Level 1 to Level 4 hierarchy in a matrix. What should you do?

- ☐ A Set the relationship to Both
- ☐ B Use a calculation group with one item per level
- ☐ C Use PATH and PATHITEM to build Level1–Level4 columns
- ☐ D Create a many-to-many relationship from Employee to itself

Q13 SINGLE ANSWER

Users must slice customers by the year of their first purchase. Which object should you create in the Customer table?

- ☐ A A what-if parameter
- ☐ B A calculated column using `CALCULATE ( MIN ( Sales[OrderDate] ) )`
- ☐ C A visual calculation on a table of customers
- ☐ D A measure: `CALCULATE ( MIN ( Sales[OrderDate] ), ALLEXCEPT ( Sales, Sales[CustomerKey] ) )`

Q14 SINGLE ANSWER

The fiscal year starts in April. Month names in visuals must run April, May ... March. What should you do?

- ☐ A Sort MonthName alphabetically
- ☐ B Sort MonthName by a fiscal month number
- ☐ C Sort MonthName by MonthNumber (January = 1)
- ☐ D Rename the months with numbers

Q15 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about calculated tables, select Yes if it is true.

Statement	Yes	No
1. A calculated table is recalculated whenever the model is refreshed.	☐	☐
2. A calculated table can be used as the source of a slicer.	☐	☐
3. A calculated table can have its own incremental refresh policy.	☐	☐

Q16 SINGLE ANSWER

You need a cumulative (all-time running) sales total that ends at the last date in the current filter context. Which measure is correct?

- ☐ A CALCULATE ([Total Sales], ALL ('Date'))
- ☐ B CALCULATE ([Total Sales], FILTER (ALL ('Date'[Date]), 'Date'[Date] <= MIN ('Date'[Date])))
- ☐ C CALCULATE ([Total Sales], FILTER (ALL ('Date'[Date]), 'Date'[Date] <= MAX ('Date'[Date])))
- ☐ D TOTALYTD ([Total Sales], 'Date'[Date])

Q17 SINGLE ANSWER

Sales[ProductKey] contains some blanks for unmatched lines. A measure must count the distinct products sold, excluding the blank. Which function should you use?

- ☐ A DISTINCTCOUNTNOBLANK (Sales[ProductKey])
- ☐ B COUNT (Sales[ProductKey])
- ☐ C DISTINCTCOUNT (Sales[ProductKey])
- ☐ D COUNTROWS (Sales)

Q18 SINGLE ANSWER

A Rates table has one row per Date and Currency, with a Rate column. In the Sales table, a calculated column must fetch the rate for each row's OrderDate and Currency. There is no relationship on both columns. Which expression is correct?

- ☐ A LOOKUPVALUE (Rates[Rate], Rates[Date], Sales[OrderDate], Rates[Currency], Sales[Currency])
- ☐ B RELATED (Rates[Rate])
- ☐ C LOOKUPVALUE (Rates[Rate], Rates[Date], MAX (Sales[OrderDate]), Rates[Currency], Sales[Currency])
- ☐ D VALUES (Rates[Rate])

Q19 SINGLE ANSWER

Finance wants the spend of a typical customer, unaffected by a few very large accounts. Which measure fits?

- ☐ A AVERAGE (Sales[Amount])
- ☐ B SUM (Sales[Amount]) / 2
- ☐ C MEDIANX (VALUES (Customer[CustomerKey]), [Total Sales])
- ☐ D MAXX (Customer, [Total Sales])

Q20 DRAG AND DROP — MATCH

Match each requirement to the DAX pattern that meets it.

Choices — each may be used once, more than once, or not at all

- ☐ A COUNTROWS with FILTER
- ☐ B CONCATENATEX
- ☐ C MAXX over dates
- ☐ D SUMX
- ☐ E AVERAGEX over stores

Requirement	Pattern
1. Revenue computed row by row from Quantity and UnitPrice	
2. Highest single-day sales within the selected month	
3. Average sales per store	
4. Number of stores whose sales beat their target	

Q21 SINGLE ANSWER

A 100-million-row Sales table has 12 calculated columns that use RELATED to copy attributes from Product and Customer. The model is large and refresh is slow. What should you do?

- ☐ A Switch Product and Customer to DirectQuery storage
- ☐ B Remove the copied columns
- ☐ C Add more calculated columns
- ☐ D Set the Product and Customer relationships to Both

Q22 SINGLE ANSWER

Fact and dimension tables are joined on 36-character GUID text keys. What change typically reduces model size and speeds up relationships most?

- ☐ A Hide the key columns
- ☐ B Add an index to the GUIDs in DAX
- ☐ C Convert the GUIDs to uppercase
- ☐ D Replace the GUIDs with integer surrogate keys

Q23 SINGLE ANSWER

A visual calculation must use Product[ListPrice], which isn't currently in the matrix. What should you do?

- ☐ A Use RELATED (Product[ListPrice]) in the visual calculation
- ☐ B Visual calculations can reference any model column directly
- ☐ C Create a calculated column
- ☐ D Add ListPrice to the visual, hidden if needed

Q24 SINGLE ANSWER

A report needs an automatically generated text summary of key figures, but your organisation has no Fabric or Premium capacity for Copilot. Which visual should you use?

- ☐ A Narrative visual with Copilot
 - ☐ B Smart narrative
 - ☐ C Key influencers
 - ☐ D Q&A with Copilot
-

Q25 SINGLE ANSWER

Background colour formatting on a matrix's Margin % column must also colour the subtotal and total rows. What should you set in the conditional formatting dialog?

- ☐ A Apply to: Values and totals
 - ☐ B Apply to: Values only
 - ☐ C Summarization: Sum
 - ☐ D Format style: Gradient
-

Q26 SINGLE ANSWER

A bar chart must show only the ten customers with the highest sales, and stay correct as data changes. What should you configure?

- ☐ A A visual-level Top N filter by Sales
 - ☐ B Sort descending and resize the chart
 - ☐ C A page filter selecting ten customer names
 - ☐ D A slicer
-

Q27 SINGLE ANSWER

A model has 80 measures with no descriptions, and Copilot gives poor results. You want descriptions added quickly, with the option to review them. What can you use?

- ☐ A DAX query view, with EVALUATE over INFO.MEASURES ()
 - ☐ B Performance Analyzer
 - ☐ C Sync slicers
 - ☐ D Copilot to draft each measure's description
-

Q28 SINGLE ANSWER

You changed which visuals a bookmark hides, but clicking the bookmark still shows the old state. What should you do?

- ☐ A Use Update on the bookmark
 - ☐ B Delete the page
 - ☐ C Rename the bookmark to refresh its state
 - ☐ D Sync the slicers
-

Q29 SINGLE ANSWER

A button must open the company's SharePoint policy page in a new browser tab. Which action type should you use?

- ☐ A Drill through
- ☐ B Web URL
- ☐ C Bookmark
- ☐ D Page navigation

Q30 SINGLE ANSWER

To meet WCAG guidance for normal-size text, what minimum contrast ratio should text have against its background in your report theme?

- ☐ A 1.5:1
- ☐ B 4.5:1
- ☐ C 10:1 for every element
- ☐ D 2:1

Q31 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about drillthrough, select Yes if it is true.

Statement	Yes	No
1. With Keep all filters on, the target page receives every filter applied to the source visual, not just the drillthrough field.	☐	☐
2. A hidden page can still be a drillthrough target.	☐	☐
3. Adding a field to the Drill through well automatically adds a slicer for that field to the page.	☐	☐

Q32 SINGLE ANSWER

In a decomposition tree of defect rate, you want Power BI to choose, at the next level, the dimension where the defect rate is lowest. Which split should you use?

- ☐ A A Top N filter
- ☐ B The AI split Low value
- ☐ C The AI split High value
- ☐ D A manual split by Plant

Q33 SINGLE ANSWER

Users type "big orders" in Q&A and expect orders over 10,000. Q&A doesn't understand the phrase. What should you do?

- ☐ A Add a smart narrative that explains the term
- ☐ B Rename the Sales table Big Orders
- ☐ C Create a bookmark
- ☐ D Use Teach Q&A to define "big orders"

Q34 SINGLE ANSWER

On a scatter chart of stores, points more than three standard deviations from the mean margin must appear in red. What should you do?

- ☐ A Colour markers by rule on a z-score measure
 - ☐ B Add a forecast
 - ☐ C Use clustering to group the stores automatically
 - ☐ D Increase the marker size for stores with high margin
-

Q35 SINGLE ANSWER

The owner of a semantic model has left the company, and refresh credentials can no longer be updated. A workspace Member must now manage the model's settings. What should they do?

- ☐ A Create a new gateway
 - ☐ B Republish the model under a new name
 - ☐ C Use Take over on the semantic model's settings page
 - ☐ D Delete and recreate the workspace
-

Q36 SINGLE ANSWER

A Pro workspace model's scheduled refresh stopped running. Nobody has opened its reports or dashboards for over two months. What is the most likely reason?

- ☐ A The model reached 48 refreshes
 - ☐ B Pro licences must be renewed by the admin every month
 - ☐ C The gateway was deleted automatically
 - ☐ D Refresh pauses after two months of inactivity
-

Q37 SINGLE ANSWER

When you set a data alert on a dashboard card tile, how often can Power BI check the alert condition?

- ☐ A Only when the report is opened
 - ☐ B Every second
 - ☐ C At most once an hour, or at most once every 24 hours
 - ☐ D Once a week
-

Q38 SINGLE ANSWER

In a workspace, which role is the least-privileged one that can share items, such as giving another user access to a report, by default?

- ☐ A Admin
- ☐ B Member
- ☐ C Contributor
- ☐ D Viewer

Q39 SINGLE ANSWER

Viewers of a workspace must not see a draft report that's still in development. The draft must stay with the other content during development. What is the best approach?

- ☐ A Give consumers the Contributor role
- ☐ B Apply a sensitivity label to the draft
- ☐ C Hide the draft report's pages
- ☐ D Publish an app that excludes the draft

Q40 MULTIPLE RESPONSE — CHOOSE TWO

Which two Power BI items can have Microsoft Purview sensitivity labels applied?

- ☐ A On-premises data gateways
- ☐ B Capacities
- ☐ C Dashboards
- ☐ D Workspace roles
- ☐ E Semantic models

Q41 SINGLE ANSWER

Users find a certified semantic model in the OneLake catalog but can't open it. Why?

- ☐ A Certification doesn't grant access to the model
- ☐ B Certification hides the data
- ☐ C The model must also be promoted
- ☐ D Certified models are always read-only to everyone

Case study · Alpine Ski House

Questions 42–45

Existing environment

Alpine Ski House runs three ski resorts. Lift-ticket sales are stored in an on-premises SQL Server. A Weather table in the same database has a Payload column containing JSON text, such as {"snowCm": 35, "tempC": -6}. The ski season runs from November to April. The model is in a workspace on a Fabric F64 capacity.

Requirements

1. Snow depth and temperature must be separate numeric columns.
2. Managers need season-to-date ticket revenue, where each season ends on 30 April.
3. Hovering over a resort on the map must show a small chart of that resort's snow depth over the last 30 days.
4. During opening hours (08:00–17:00), the model must refresh every 30 minutes.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

How should you turn Payload into columns?

- ☐ A Transform → Parse → JSON, then expand the record
- ☐ B Unpivot Payload
- ☐ C Use Column from examples on Payload
- ☐ D Split Payload by the comma delimiter, then by the colon

Q43 SINGLE ANSWER

Which measure returns season-to-date revenue?

- ☐ (A) TOTALYTD ([Ticket Revenue], 'Date'[Date], "4/30")
 - ☐ (B) TOTALYTD ([Ticket Revenue], 'Date'[Date])
 - ☐ (C) TOTALMTD ([Ticket Revenue], 'Date'[Date])
 - ☐ (D) SAMEPERIODLASTYEAR ([Ticket Revenue])
-

Q44 SINGLE ANSWER

How do you build the map hover experience?

- ☐ (A) A bookmark
 - ☐ (B) A drillthrough page with the 30-day snow chart
 - ☐ (C) Add snow depth to the map's bubble size
 - ☐ (D) A report page tooltip set on the map
-

Q45 SINGLE ANSWER

How do you meet the refresh requirement?

- ☐ (A) Half-hourly scheduled refresh through a standard gateway
- ☐ (B) Use Publish to web
- ☐ (C) Use a personal-mode gateway with 48 refreshes
- ☐ (D) It isn't possible; the maximum is 8 refreshes a day on any capacity

End of Set 09 — answers follow on the next page.

Set 09 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	D	P1		16	C	M2		31	Yes · Yes · No	V2	
2	B	P1		17	A	M2		32	B	V3	
3	B, E	P1		18	A	M2		33	D	V3	
4	C	P1		19	C	M2		34	A	V3	
5	C	P2		20	1→D 2→C 3→E 4→A	M2		35	C	S1	
6	C	P2		21	B	M3		36	D	S1	
7	C	P2		22	D	M3		37	C	S1	
8	D	P3		23	D	V1		38	B	S2	
9	B	P3		24	B	V1		39	D	S2	
10	1→B 2→D 3→A	P3		25	A	V1		40	C, E	S2	
11	C	P3		26	A	V1		41	A	S2	
12	C	M1		27	D	V1		42	A	P3	
13	B	M1		28	A	V2		43	A	M2	
14	B	M1		29	B	V2		44	D	V2	
15	Yes · Yes · No	M1		30	B	V2		45	A	S1	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: D P1 · Get or connect to data

The PDF connector detects tables and pages in a PDF and lets you choose one in the Navigator. Text/CSV and Web expect other formats. A blank query would require typing the data.

Q2 Answer: B P1 · Get or connect to data

Connecting through the cloud URL lets the service read the file directly, so no gateway is needed. A local synced path is an on-premises file path in the service's eyes and needs a gateway. Network shares also need one.

Q3 Answer: B, E P1 · Get or connect to data

Direct Lake is a Fabric capability that loads Delta-Parquet column data from OneLake into memory on demand. Refresh only reframes the model to the latest table version, without copying data. It doesn't connect to arbitrary databases and needs Fabric capacity.

Q4 Answer: C P1 · Get or connect to data

Live-connected reports have no local model, so only report-level measures are allowed. Adding columns or tables needs either a composite model (Make changes to this model) or a change by the model's owner.

Q5 Answer: C P2 · Profile and clean the data

Power Query steps refer to columns by name. When the source renames or drops a column, the first step that references it fails with this error. Fix the step, or make the query resilient with Choose columns or a rename map. Nulls and RLS don't cause this error.

Q6 Answer: C P2 · Profile and clean the data

Applying the business rule once at load means every measure and visual agrees. Fixing it in each measure or visual is repetitive and error-prone. Deleting rows loses data the business wants kept.

Q7 Answer: C P2 · Profile and clean the data

try ... otherwise catches the error raised for each row and returns the fallback value, here null. The if expression is invalid because [Units] isn't a logical value. The ?? operator only replaces null results, not errors. Number.From doesn't handle the error.

Q8 Answer: D P3 · Transform and load the data

A transformation table maps known values to their equivalents during a fuzzy merge, handling cases that similarity alone can't. Anti joins find non-matches. Removing duplicates and grouping don't pair different spellings.

Q9 Answer: B P3 · Transform and load the data

Grouping keeps each customer's rows in a nested table, and an index added inside each table restarts at 1 per customer. A single index column numbers all rows continuously, even after sorting. Pivoting and self-merging don't produce sequences.

Q10 Answer: 1→B 2→D 3→A P3 · Transform and load the data

Staging queries feed other queries, so they don't need to load. A static archive stays in the model but can skip refresh. The fact table needs both settings on. Deleting any of these queries would break the model.

Q11 Answer: C P3 · Transform and load the data

Extract First characters returns a fixed number of leading characters. Splitting needs a delimiter. Trim only removes spaces. An index column numbers rows.

Q12 Answer: C M1 · Design and implement a data model

Power BI hierarchies need one column per level. PATH flattens the parent-child chain, and PATHITEM extracts each level, which you can then turn into a hierarchy. Self-relationships and calculation groups don't flatten a parent-child structure.

Q13 Answer: B M1 · Design and implement a data model

Slicers need column values. A calculated column evaluates each customer's first purchase date through context transition, and a year column can be derived from it. A measure can't be placed on a slicer. Visual calculations and what-if parameters don't create customer attributes.

Q14 Answer: B M1 · Design and implement a data model

Sort by column applies the order of another column. A fiscal month number puts April first. Sorting by the calendar month number starts with January. Alphabetical sorting is wrong in both cases.

Q15 Answer: Yes · Yes · No M1 · Design and implement a data model

Calculated tables are evaluated from model data after each refresh and behave like any table in visuals, including slicers. Incremental refresh applies to tables loaded through Power Query with RangeStart and RangeEnd, not to DAX tables.

Q16 Answer: C M2 · Create model calculations by using DAX

Removing the date filter and keeping every date up to the current maximum gives an all-time running total. TOTALYTD resets each year. Using MIN ends the total at the first date in the current context rather than the last. ALL('Date') returns the all-time total on every row.

Q17 Answer: A M2 · Create model calculations by using DAX

DISTINCTCOUNT counts a blank as one more distinct value. DISTINCTCOUNTNOBLANK leaves it out. COUNTROWS and COUNT count rows, not distinct products.

Q18 Answer: A M2 · Create model calculations by using DAX

LOOKUPVALUE returns the value from the row that matches every search condition, which works without a relationship. RELATED needs a relationship. MAX (Sales[OrderDate]) returns the latest order date in the table, not the row's own date. VALUES ignores the row's date and currency.

Q19 Answer: C M2 · Create model calculations by using DAX

MEDIANX evaluates each customer's total and returns the middle value, which large outliers barely affect. AVERAGE over lines is skewed by large values and works at the wrong grain. MAXX returns the largest customer.

Q20 Answer: 1→D 2→C 3→E 4→A M2 · Create model calculations by using DAX

Iterators evaluate an expression per row of a table and then aggregate: SUMX adds, MAXX takes the highest and AVERAGEX averages. Counting rows that meet a measure-based condition uses COUNTROWS over a FILTER. CONCATENATEX joins text.

Q21 Answer: B M3 · Optimize model performance

Copying dimension attributes onto a huge fact table duplicates data at the fact's row count. The relationships already let visuals use the dimension columns directly, so removing the copies shrinks the model and speeds up refresh.

Q22 Answer: D M3 · Optimize model performance

Long, high-cardinality text keys compress poorly and make joins expensive. Integer surrogate keys are compact and efficient. Changing case or hiding columns doesn't change storage.

Q23 Answer: D V1 · Create reports

Visual calculations can reference only fields that are on the visual, but fields can be added and hidden. RELATED isn't supported in visual calculations. A calculated column doesn't put the value on the visual.

Q24 Answer: B V1 · Create reports

The smart narrative visual generates text summaries with dynamic values and doesn't require Copilot capacity. The Copilot narrative needs eligible capacity. Key influencers analyses drivers rather than summarising.

Q25 Answer: A V1 · Create reports

Conditional formatting has an Apply to option. Values only leaves totals uncoloured, and Values and totals includes subtotals and the grand total. Format style and summarisation don't control that.

Q26 Answer: A V1 · Create reports

A Top N filter keeps the top N items by a measure and re-evaluates as data and other filters change. Hand-picked names go stale. Sorting doesn't limit the items, and a slicer depends on users.

Q27 Answer: D V1 · Create reports

Copilot can draft a description for a measure from its formula in the measure's properties, and the author reviews and keeps it. Good descriptions in turn improve Copilot's other results. The other tools don't write descriptions.

Q28 Answer: A V2 · Enhance reports for usability and storytelling

Bookmarks store a snapshot. After changing the page, use the bookmark's Update command to capture the new state. Renaming doesn't change the stored state.

Q29 Answer: B V2 · Enhance reports for usability and storytelling

The Web URL action opens an external address. Page navigation, bookmarks and drillthrough only move within Power BI content.

Q30 Answer: B V2 · Enhance reports for usability and storytelling

WCAG AA asks for at least 4.5:1 for normal text (3:1 for large text). Lower ratios are hard to read for many users. 10:1 isn't the threshold. Power BI's accessible themes are designed around these ratios.

Q31 Answer: Yes · Yes · No V2 · Enhance reports for usability and storytelling

Keep all filters passes the full filter context of the source. Hidden pages are often used as drillthrough targets. Power BI adds a Back button, not a slicer, when you set up drillthrough.

Q32 Answer: B V3 · Identify patterns and trends

AI splits pick the next dimension automatically: High value finds the highest value of the measure, and Low value finds the lowest. A manual split uses the dimension you choose. Top N filters don't drive the tree.

Q33 Answer: D V3 · Identify patterns and trends

Teach Q&A lets you define what a term means, including conditions such as Amount > 10,000, so later questions use it. Renaming tables or adding narratives and bookmarks doesn't teach Q&A new terms.

Q34 Answer: A V3 · Identify patterns and trends

Outliers can be flagged with a measure, such as a z-score using STDEV.P, and highlighted through conditional formatting of the marker colour. Forecasts and marker size don't identify outliers. Clustering groups points rather than flagging extremes.

Q35 Answer: C S1 · Create and manage workspaces and assets

Take over makes the current user the model's owner, so they can update credentials, gateway mapping and refresh settings. Republishing under a new name breaks reports. Recreating the workspace or gateway isn't needed.

Q36 Answer: D S1 · Create and manage workspaces and assets

Power BI deactivates refresh schedules for models whose content hasn't been used for about two months. Opening the content or re-enabling the schedule restarts it. Licences, gateways and refresh counts don't explain this pattern.

Q37 Answer: C S1 · Create and manage workspaces and assets

Data alerts offer two notification frequencies, at most once an hour or at most once every 24 hours, and evaluate when the tile's data refreshes. Real-time, on-open or weekly options don't exist.

Q38 Answer: B S2 · Secure and govern Power BI items

Members can share items and add users with the Member role or lower. Contributors can create and edit, but can't reshare by default. Viewers only view. Admin also works but isn't least privilege.

Q39 Answer: D S2 · Secure and govern Power BI items

Workspace Viewers see every item in the workspace. An app lets you publish only finished content to consumers. Hidden pages and labels don't hide the report. Contributor access would make it worse.

Q40 Answer: C, E S2 · Secure and govern Power BI items

Sensitivity labels apply to content items such as reports, dashboards, semantic models, dataflows and paginated reports. Gateways, roles and capacities aren't labelled content.

Q41 Answer: A S2 · Secure and govern Power BI items

Endorsement helps people find and trust content but has no effect on permissions. Access must be granted separately, often through an access request on a discoverable model.

Q42 Answer: A P3 · Transform and load the data

Parse JSON turns the text into a record, and expanding the record creates one column per field, which can then be typed. Splitting by comma breaks on nested or reordered JSON. The other options don't parse JSON.

Q43 Answer: A M2 · Create model calculations by using DAX

The year-end-date argument makes the accumulation year end on 30 April, so the year runs 1 May to 30 April and covers each full November–April season. Without it, the year resets in January, mid-season. MTD and SAMEPERIODLASTYEAR answer other questions.

Q44 Answer: D V2 · Enhance reports for usability and storytelling

A report page tooltip shows a small custom page, here a trend chart, when users hover over a visual, filtered to the hovered resort. Drillthrough needs a click and navigates away. Size encoding and bookmarks don't show a trend on hover.

Q45 Answer: A S1 · Create and manage workspaces and assets

On Fabric or Premium capacity, scheduled refresh allows up to 48 slots a day, so 18 half-hourly refreshes fit. The on-premises SQL Server needs a standard gateway. Eight a day is the Pro limit. A personal gateway isn't for shared production refresh.

Exam simulation B — final rehearsal

The hardest paper in the bank: subtle distinctions, multi-step DAX, composite models and governance edge cases. Sit it last.

45 questions

100 minutes

Pass mark used here: 34 / 45 (75%)

Level 3 · Exam simulation

12 Prepare the data 25–30%	12 Model the data 25–30%	13 Visualize and analyze the data 25–30%	8 Manage and secure Power BI 15–20%
---	---------------------------------------	---	--

Q1 SINGLE ANSWER

Cleaned tables produced by a Power BI dataflow (Gen1) in the service must be used in a new Desktop model. Which connector should you use?

- ☐ A Web
- ☐ B Text/CSV
- ☐ C Dataflows (Power BI dataflows)
- ☐ D SQL Server

Q2 SINGLE ANSWER

An Azure SQL Database requires multi-factor authentication through the company's Microsoft Entra ID, and SQL logins are disabled. How should you authenticate in Power BI Desktop?

- ☐ A Anonymous
- ☐ B Microsoft account sign-in
- ☐ C Database: SQL username and password
- ☐ D Windows (current credentials)

Q3 SINGLE ANSWER

A query reads an Excel file from a local path with File.Contents. The file is moving to a SharePoint Online library, and refresh must work without a gateway. What must change?

- ☐ A Read the SharePoint URL in the Source step
- ☐ B Nothing; File.Contents works for SharePoint URLs
- ☐ C Set the privacy level to Public
- ☐ D Only the file name in Data source settings

Q4 SINGLE ANSWER

Refresh fails with DataSource.NotFound in the Source step. Adding Remove errors at the end of the query doesn't help. Why?

- ☐ A The model has too many relationships
- ☐ B Remove errors only works on text columns
- ☐ C Remove errors must be placed directly after Source
- ☐ D It's a step-level error, not a cell-level one

Q5 SINGLE ANSWER

After merging Orders with Customers and expanding a column, Orders has more rows than before. What is the most likely cause, and how do you confirm it?

- ☐ A The join kind was Inner instead of Left outer
 - ☐ B The data types differ
 - ☐ C Privacy levels are wrong
 - ☐ D Duplicate CustomerID values in Customers
-

Q6 SINGLE ANSWER

CSV files from a vendor change often, and the automatic Changed Type step keeps assigning wrong types. You want Power BI to stop detecting types automatically for unstructured sources, and set them yourself. Where is this?

- ☐ A Data source settings → Edit Permissions → Privacy level
 - ☐ B Model view → Properties
 - ☐ C Options → Data Load → Type detection
 - ☐ D Report settings → Visuals
-

Q7 SINGLE ANSWER

Two queries have the same columns but in a different order: Region, Product, Amount in one, and Amount, Region, Product in the other. What happens when you append them?

- ☐ A Columns are matched by name, so the rows line up correctly
 - ☐ B Columns are matched by position, so values end up in the wrong columns
 - ☐ C The append fails
 - ☐ D Power Query merges them on Region
-

Q8 SINGLE ANSWER

A mainframe export is a fixed-width text file: characters 1–8 are the account number, 9–20 the name and 21–30 the balance. Which transformation splits it correctly?

- ☐ A Split column → By lowercase to uppercase
 - ☐ B Unpivot columns
 - ☐ C Split column → By delimiter (space)
 - ☐ D Split column → By positions, at 0, 8 and 20
-

Q9 BUILD LIST — SEQUENCE

The Customer query needs an OrderCount column showing how many orders each customer has, without loading order rows into Customer. Put the actions in order.

Select the 4 actions required and arrange them in the correct order. Not every action is used.

- ☐ A Append Orders to Customers
- ☐ B Expand all Orders columns
- ☐ C Merge Customers with Orders on CustomerID using a Left outer join
- ☐ D Rename the new column OrderCount and set it to Whole Number
- ☐ E Select the expand button on the merged column and choose Aggregate
- ☐ F Choose Count of OrderID

Q10 MULTIPLE RESPONSE — CHOOSE TWO

A source regularly gains extra columns, and the query must keep working and keep loading only the intended data. Which two techniques make the query resilient?

- ☐ A Remove columns by selecting the unwanted ones
- ☐ B Use Transpose
- ☐ C Unpivot other columns, when the new columns are additional months to be unpivoted
- ☐ D Choose columns (Remove other columns) to keep the named columns you need
- ☐ E Hard-code a Changed Type step that lists every column

Q11 SINGLE ANSWER

A custom column must return the number of whole days between OrderDate and ShipDate, both of type Date. Complete the formula.

```
= Table.AddColumn ( Source, "DaysToShip", each ____, Int64.Type )
```

- ☐ A Duration.Days ([ShipDate] - [OrderDate])
- ☐ B Number.From ([ShipDate])
- ☐ C [ShipDate] - [OrderDate]
- ☐ D Date.Day ([ShipDate]) - Date.Day ([OrderDate])

Q12 SINGLE ANSWER

Power BI won't let you make a relationship active and says it would create ambiguous paths between two tables. What should you do?

- ☐ A Set every relationship to Both
- ☐ B Make the other relationship inactive
- ☐ C Create a second Date table for every fact
- ☐ D Delete the fact tables

Q13 SINGLE ANSWER

Business analysts need a small, static mapping table of 12 KPI names and their display order in the model. It has no source system, and they want to edit it occasionally. What is the simplest option?

- ☐ A Use a calculation group
- ☐ B Build a SQL table and a gateway
- ☐ C Create the table with Enter data in Power BI Desktop
- ☐ D Write the values in DAX measures

Q14 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about relationships, select Yes if it is true.

Statement	Yes	No
1. A many-to-one relationship from Sales to Product is the same relationship as one-to-many from Product to Sales.	☐	☐
2. A Product slicer can only filter Sales if the relationship's cross-filter direction is Both.	☐	☐
3. A many-to-many relationship can be set to filter in a single direction.	☐	☐

Q15 SINGLE ANSWER

A table visual shows sales by day. Sales PrevMonth = CALCULATE ([Sales], PREVIOUSMONTH ('Date'[Date])) and Sales Shifted = CALCULATE ([Sales], DATEADD ('Date'[Date], -1, MONTH)). What do you see on the row for 15 March?

- ☐ A Sales PrevMonth shows all of February's sales; Sales Shifted shows sales for 15 February
- ☐ B Sales PrevMonth shows sales for 15 February; Sales Shifted shows all of February's sales
- ☐ C Both show sales for 15 February
- ☐ D Both show all of February's sales

Q16 SINGLE ANSWER

A measure must count new customers: those whose first-ever purchase falls within the selected period. Which expression is correct?

- ☐ A COUNTROWS (FILTER (VALUES (Sales[CustomerKey]), CALCULATE (MIN (Sales[OrderDate]), ALL ('Date')) >= MIN ('Date'[Date])))
- ☐ B COUNTROWS (FILTER (VALUES (Sales[CustomerKey]), CALCULATE (MIN (Sales[OrderDate]), ALLSELECTED ('Date')) >= MIN ('Date'[Date])))
- ☐ C CALCULATE (DISTINCTCOUNT (Sales[CustomerKey]), ALL ('Date'))
- ☐ D COUNTROWS (FILTER (Customer, ISBLANK ([Total Sales])))

Q17 SINGLE ANSWER

A card must show "Select a region" when no region is filtered, and the region's sales otherwise. Cross-filters from other visuals on Region must not count as a selection. Which function tests this correctly?

- ☐ A HASONEFILTER (Sales[Amount])
- ☐ B ISFILTERED (Region[Region])
- ☐ C ISBLANK (Region[Region])
- ☐ D ISCROSSFILTERED (Region[Region])

Q18 SINGLE ANSWER

In a slicer built on a calculation group, the items appear in alphabetical order (PY, Current, YoY %, YTD). They must appear as Current, PY, YTD, YoY %. What should you set?

- ☐ A A sort-by column on the measure table
- ☐ B The Ordinal property of each calculation item
- ☐ C The Precedence of the calculation group
- ☐ D The format string expression

Q19 SINGLE ANSWER

A measure fails with "A table of multiple values was supplied where a single value was expected" when several products are visible. The measure uses VALUES (Product[Category]) inside a text concatenation. What is the best fix for a single-value context?

- ☐ A Wrap the concatenation in IFERROR (..., "Multiple")
- ☐ B Use SELECTEDVALUE (Product[Category], "Multiple")
- ☐ C Use COUNTROWS (Product)
- ☐ D Use ALL (Product[Category])

Q20 SINGLE ANSWER

Before field parameters existed, a report used a disconnected table `MetricPicker[Metric]` with values Revenue, Profit and Units in a slicer. Which measure returns the chosen metric?

- A** `IF ( MetricPicker[Metric] = "Revenue", [Revenue] )`
 - B** `CALCULATE ( [Revenue], MetricPicker[Metric] )`
 - C** `SWITCH ( VALUES ( MetricPicker[Metric] ), "Revenue", [Revenue], "Profit", [Profit], "Units", [Units], [Revenue] )`
 - D** `SWITCH ( SELECTEDVALUE ( MetricPicker[Metric] ), "Revenue", [Revenue], "Profit", [Profit], "Units", [Units] )`
-

Q21 SINGLE ANSWER

In DAX query view, you've rewritten a slow measure under `DEFINE MEASURE` and confirmed it is faster and returns the same results. How do you apply it to the model?

- A** Republish the report without changes
 - B** Restart Power BI Desktop
 - C** Copy the definition into a calculated column in the model
 - D** Use the CodeLens update option above the definition
-

Q22 SINGLE ANSWER

A matrix with Customer and Product on the rows becomes very slow after Show items with no data was turned on. Why, and what should you do?

- A** It evaluates every Customer × Product pair; turn it off
 - B** It removes the relationship; recreate it
 - C** It disables the model's compression; reload the model in Desktop
 - D** It turns on DirectQuery; switch back to Import
-

Q23 SINGLE ANSWER

A paginated report must reuse the measures and RLS of an existing Power BI semantic model rather than defining new queries against the database. How should you build it in Power BI Report Builder?

- A** Export the model to Excel and use the workbook
 - B** Use the semantic model as the data source
 - C** Use a dataflow as the source
 - D** Connect Report Builder directly to the source SQL tables
-

Q24 SINGLE ANSWER

For each region, a chart must show what share of revenue comes from each of four product lines, with every region's bar adding up to 100%. Which visual fits best?

- A** Clustered bar chart
- B** Gauge
- C** 100% stacked bar chart
- D** Line chart

Q25 SINGLE ANSWER

A filter card on Fiscal Year in the Filters pane must allow exactly one year to be selected. What should you set?

- ☐ A Hide the filter
 - ☐ B Use a Top N filter
 - ☐ C Lock the filter
 - ☐ D Turn on Require single selection on the filter card
-

Q26 SINGLE ANSWER

Every visual title across the company's reports must use the Segoe UI Semibold font at 14 pt by default. Which part of a JSON theme sets this most efficiently?

- ☐ A dataColors
 - ☐ B A background image
 - ☐ C textClasses (for example the title class)
 - ☐ D visualStyles for a single visual only
-

Q27 SINGLE ANSWER

A report has 20 bookmarks. A bookmark navigator on the Sales page must show only the five Sales bookmarks. What should you do?

- ☐ A Hide the other pages
 - ☐ B Put the five in a bookmark group for the navigator
 - ☐ C Delete the other 15 bookmarks
 - ☐ D Create five separate buttons, one per Sales bookmark
-

Q28 SINGLE ANSWER

Personalize visuals is on for the report, but one regulatory chart must not be changeable by readers. What should you do?

- ☐ A Hide the chart
 - ☐ B Turn off Personalize visuals for the whole report
 - ☐ C Turn off personalisation for that visual only
 - ☐ D Lock the Filters pane
-

Q29 SINGLE ANSWER

A screen-reader user needs to hear the data values behind a column chart. Which built-in feature presents the chart's data in an accessible table?

- ☐ A Spotlight
- ☐ B Show as a table
- ☐ C Focus mode only
- ☐ D Export to PDF

Q30 SINGLE ANSWER

A bar chart shows sales by product, but users want it sorted by Margin %, which isn't on the axis or in the values. What should you do?

- ☐ A Create a Sort by column on Product
- ☐ B Add Margin % as a second Y-axis series
- ☐ C Add Margin % to Tooltips, then sort by it
- ☐ D Sort the Product table in Power Query by Margin %

Q31 DRAG AND DROP — MATCH

Match each requirement to the report feature that meets it.

Choices — each may be used once, more than once, or not at all

- ☐ A Edit interactions
- ☐ B Report page tooltip
- ☐ C Drillthrough
- ☐ D Sync slicers
- ☐ E Bookmark

Requirement	Feature
1. Selecting a slicer value must not change one particular chart	
2. A Year slicer's selection must carry across five pages	
3. Right-clicking a customer must open a detailed page filtered to that customer	
4. Hovering over a bar must show a small custom page with a trend chart	

Q32 SINGLE ANSWER

Anomaly detection flags a spike in daily returns, but the explanation pane is empty. You want Power BI to suggest which product categories or channels might explain it. What should you do?

- ☐ A Change the chart to a table
- ☐ B Increase the sensitivity of the anomaly detection
- ☐ C Add a forecast
- ☐ D Add Category and Channel to Explain by

Q33 SINGLE ANSWER

In a decomposition tree, the first level must always be Region and users must not be able to remove it, though they can explore any dimensions below it. What should you configure?

- ☐ A Use a page filter on Region
- ☐ B Hide the Region field
- ☐ C Turn off AI splits
- ☐ D Lock the Region level in the decomposition tree

Q34 SINGLE ANSWER

New users don't know what to ask the Q&A visual. You want a few example questions to appear in it. What should you configure?

- ☐ A A smart narrative
- ☐ B Suggested questions in Q&A setup
- ☐ C Synonyms only
- ☐ D A tooltip page

Q35 SINGLE ANSWER

An executive dashboard must appear prominently on the Power BI Home page for everyone who has access to it. What should you do?

- ☐ A Pin it to every user's favourites
- ☐ B Certify the dashboard
- ☐ C Use Publish to web
- ☐ D Feature the dashboard on Home

Q36 SINGLE ANSWER

Ten semantic models import from ten different databases on the same on-premises SQL Server. How many gateways do you need?

- ☐ A One standard gateway with ten connections
- ☐ B Ten personal-mode gateways, one per model
- ☐ C No gateway, because they share a server
- ☐ D Ten gateways, one per database

Q37 SINGLE ANSWER

The Deployment pipelines option is unavailable for a workspace in Pro licence mode. What is required?

- ☐ A Make every user an Admin
- ☐ B Turn on the XMLA read-write endpoint in Desktop
- ☐ C A Premium, PPU or Fabric capacity workspace
- ☐ D Install a gateway

Q38 HOT AREA — YES / NO FOR EACH STATEMENT

For each statement about report subscriptions, select Yes if it is true.

Statement	Yes	No
1. A subscription can attach the full report as a PDF or PowerPoint file.	☐	☐
2. A recipient without access to the report still sees its data in the email.	☐	☐
3. A subscription can be scheduled to send after the semantic model refreshes.	☐	☐

Q39 SINGLE ANSWER

Compliance must find out who viewed or exported a sensitive report over the last 30 days. Where should they look?

- ☐ A Performance Analyzer in Power BI Desktop
- ☐ B The Microsoft Purview audit log
- ☐ C The report's bookmarks
- ☐ D Query dependencies

Q40 SINGLE ANSWER

A report in workspace B uses a semantic model in workspace A. Users who are Viewers of workspace B see errors in every visual. They have no access to workspace A. What should you grant?

- ☐ A The Admin role on workspace B for every Viewer
- ☐ B Build permission on the report in workspace B
- ☐ C Read permission on the model in workspace A
- ☐ D A sensitivity label

Q41 SINGLE ANSWER

An analyst applies the Confidential sensitivity label to a .pbix file in Power BI Desktop and then publishes it. What happens?

- ☐ A The label is removed when the file is published to the service
- ☐ B The label only exists in Desktop
- ☐ C The label carries to the service with the report and model
- ☐ D Publishing is blocked until certification

Case study · Relecloud Logistics

Questions 42–45

Existing environment

Relecloud runs 60 depots across India. Shipments are stored in an on-premises Oracle database: about 80 million rows, plus live updates for in-transit shipments. Each shipment has an OriginDepot and a DestinationDepot. Finance uses an April–March fiscal year. IT has approved a box-and-whisker visual from AppSource. A DepotUsers table maps each manager's email to the DepotIDs they manage.

Requirements

1. The control-tower page must show in-transit shipments with data at most five minutes old, while historical analysis must stay fast.
2. Most measures analyse shipments by origin depot. A few must analyse by destination depot, using the same single Depot slicer.
3. Every report author must have the approved box-and-whisker visual available in Power BI without importing it themselves.
4. Each depot manager must see shipments that start or end at their depots.

Once you move past this case study you cannot return to it. Read the requirements before the questions.

Q42 SINGLE ANSWER

Which design meets the control-tower requirement?

- ☐ A A composite model: Import history, DirectQuery in-transit data, Dual dimensions
- ☐ B Import everything with eight refreshes a day
- ☐ C DirectQuery for the whole model, with automatic page refresh every five minutes
- ☐ D A Publish to web report refreshed hourly

Q43 SINGLE ANSWER

How should you relate the Depot table to Shipments?

- ☐ A Active on OriginDepot, inactive on DestinationDepot
 - ☐ B Two active relationships, one on each of the depot columns
 - ☐ C A many-to-many relationship on both columns
 - ☐ D Two separate Depot tables with separate slicers
-

Q44 SINGLE ANSWER

How do you make the approved visual available to every author?

- ☐ A An admin adds it to Organizational visuals
 - ☐ B Each author downloads it from AppSource
 - ☐ C Create it as a calculation group
 - ☐ D Embed it in the corporate report theme file
-

Q45 SINGLE ANSWER

Which RLS design meets the depot-manager requirement?

- ☐ A A role filter on Depot: [DepotID] = USERPRINCIPALNAME ()
- ☐ B A filter on Depot through the active origin relationship only
- ☐ C A role filter on the Shipments table: VAR D = CALCULATETABLE (VALUES (DepotUsers[DepotID]), DepotUsers[Email] = USERPRINCIPALNAME ()) RETURN Shipments[OriginDepot] IN D && Shipments[DestinationDepot] IN D
- ☐ D A role filter on the Shipments table: VAR D = CALCULATETABLE (VALUES (DepotUsers[DepotID]), DepotUsers[Email] = USERPRINCIPALNAME ()) RETURN Shipments[OriginDepot] IN D || Shipments[DestinationDepot] IN D

End of Set 10 — answers follow on the next page.

Set 10 · Answer key

Q	Answer	Area	✓	Q	Answer	Area	✓	Q	Answer	Area	✓
1	C	P1		16	A	M2		31	1→A 2→D 3→C 4→B	V2	
2	B	P1		17	B	M2		32	D	V3	
3	A	P1		18	B	M2		33	D	V3	
4	D	P2		19	B	M2		34	B	V3	
5	D	P2		20	D	M2		35	D	S1	
6	C	P2		21	D	M3		36	A	S1	
7	A	P3		22	A	M3		37	C	S1	
8	D	P3		23	B	V1		38	Yes · No · Yes	S1	
9	C → E → F → D	P3		24	C	V1		39	B	S2	
10	C, D	P3		25	D	V1		40	C	S2	
11	A	P3		26	C	V1		41	C	S2	
12	B	M1		27	B	V2		42	A	P1	
13	C	M1		28	C	V2		43	A	M1	
14	Yes · No · Yes	M1		29	B	V2		44	A	V1	
15	A	M2		30	C	V2		45	D	S2	

Sub-area	Questions	Your score
P1 · Get or connect to data	4	
P2 · Profile and clean the data	3	
P3 · Transform and load the data	5	
M1 · Design and implement a data model	4	
M2 · Create model calculations by using DAX	6	
M3 · Optimize model performance	2	
V1 · Create reports	5	
V2 · Enhance reports for usability and storytelling	5	
V3 · Identify patterns and trends	3	
S1 · Create and manage workspaces and assets	4	
S2 · Secure and govern Power BI items	4	
Total — 34 or more is a pass on this paper	45	

Scoring: one mark per question. For multiple-response, Yes/No, matching and build-list items, score the fraction of parts you got right (the real exam gives partial credit on multi-part items and never penalises a wrong answer).

Explanations

Q1 Answer: C P1 · Get or connect to data

The Dataflows connector lists the dataflows you have access to and their entities (tables), so you reuse the cleaned output. The generic connectors can't see dataflow outputs.

Q2 Answer: B P1 · Get or connect to data

Signing in with an organisational account uses Microsoft Entra ID, which supports MFA and works when SQL authentication is disabled. Database credentials need SQL logins. Windows authentication is for on-premises domain-joined sources. Anonymous gives no access.

Q3 Answer: A P1 · Get or connect to data

File.Contents reads file-system paths, which the service treats as on-premises sources. Switching the Source step to read the cloud URL lets the service refresh it directly. Renaming the file or changing privacy levels doesn't change how the file is read.

Q4 Answer: D P2 · Profile and clean the data

Cell-level errors affect individual values, so the rows can be removed or replaced. Step-level errors, like an unreachable source, mean there are no rows to clean. Fix the connection, path or credentials instead.

Q5 Answer: D P2 · Profile and clean the data

Each duplicate key on the right side produces an extra joined row when expanded, multiplying orders. Profiling or Keep duplicates on the key exposes the duplicates. An inner join can only reduce the row count.

Q6 Answer: C P2 · Profile and clean the data

The type detection option controls whether Power Query adds an automatic type step for sources such as CSV and Excel. Turning it off lets you define types explicitly. The other settings don't affect type detection.

Q7 Answer: A P3 · Transform and load the data

Append aligns columns by name, not position, so a different order isn't a problem. Different names are the real issue: they create separate, partly null columns.

Q8 Answer: D P3 · Transform and load the data

Fixed-width records are split by character position. Splitting on spaces breaks names that contain spaces and padded fields. Case transitions don't apply here.

Q9 Answer: C → E → F → D P3 · Transform and load the data

The expand dialog's Aggregate option summarises the nested Orders table per customer instead of expanding rows, which keeps one row per customer. A Left outer join keeps customers with no orders, who get a count of 0.

Q10 Answer: C, D P3 · Transform and load the data

Remove other columns ignores any new column, and Unpivot other columns automatically includes new month columns. Removing columns by name lets new columns through. A Changed Type step listing every column breaks when columns are removed and doesn't type the new ones.

Q11 Answer: A P3 · Transform and load the data

Subtracting two dates in M returns a duration, and Duration.Days extracts the whole days as a number. The bare subtraction leaves a duration value. Subtracting day-of-month numbers fails across months.

Q12 Answer: B M1 · Design and implement a data model

Only one filter path between two tables can be active. Leaving the alternative path inactive removes the ambiguity, and measures can still activate it with USERELATIONSHIP. Bidirectional filters usually cause ambiguity rather than fix it.

Q13 Answer: C M1 · Design and implement a data model

Enter data creates a small table stored in the model's Power Query, which can be edited later through the same dialog. Building database infrastructure for twelve rows is overkill. Measures and calculation groups aren't lookup tables.

Q14 Answer: Yes · No · Yes M1 · Design and implement a data model

Cardinality is the same relationship described from either end. Filters flow from the one side to the many side by default, so Single direction is enough for a dimension slicer to filter the fact. Many-to-many relationships support either Single or Both direction.

Q15 Answer: A M2 · Create model calculations by using DAX

PREVIOUSMONTH returns every date of the month before the first date in context, whatever the granularity. DATEADD shifts the dates in context, so at day level it returns the same day a month earlier. This difference often catches people out.

Q16 Answer: A M2 · Create model calculations by using DAX

For each customer active in the period, the first purchase date is computed over all dates. Customers whose first purchase is on or after the period start are new. ALLSELECTED only looks back to the start of the selected range, so earlier buyers can count as new. The ISBLANK pattern counts customers with no sales. ALL('Date') counts customers across all time.

Q17 Answer: B M2 · Create model calculations by using DAX

ISFILTERED is TRUE only when the column is filtered directly. ISCROSSFILTERED is also TRUE when filters reach it through related tables or other columns. HASONEFILTER on an amount column and ISBLANK on a column don't test the selection.

Q18 Answer: B M2 · Create model calculations by using DAX

Each calculation item's ordinal controls the order in which items are displayed. Precedence decides which of several calculation groups applies first. Format strings control display formatting, not order.

Q19 Answer: B M2 · Create model calculations by using DAX

VALUES returns a table, which errors when it holds more than one row and is used as a scalar. SELECTEDVALUE returns the single value when there is exactly one, or the alternate result otherwise. IFERROR hides the problem without defining the multi-value behaviour.

Q20 Answer: D M2 · Create model calculations by using DAX

SELECTEDVALUE reads the slicer's choice, and SWITCH returns the matching measure, returning blank when nothing or several are selected. VALUES raises an error unless exactly one metric is selected, and the other expressions are invalid or ignore the selection. Field parameters now offer a built-in alternative.

Q21 Answer: D M3 · Optimize model performance

DAX query view shows an option above a DEFINE MEASURE block to add or overwrite the measure in the model, so a tested definition can be applied directly. The other actions don't change the measure.

Q22 Answer: A M3 · Optimize model performance

Show items with no data asks for the cross join of the row fields, which can be enormous, and evaluates measures for each combination. Turning it off returns only combinations with data. It doesn't change compression, storage mode or relationships.

Q23 Answer: B V1 · Create reports

Report Builder can connect to a published Power BI semantic model, so the paginated report reuses its measures and respects its RLS. Querying the source tables duplicates logic and bypasses model security.

Q24 Answer: C V1 · Create reports

A 100% stacked bar normalises each bar to the region's total, so you compare shares across regions directly. A clustered bar compares absolute values. Line charts and gauges don't show composition.

Q25 Answer: D V1 · Create reports

Basic filter cards have a Require single selection option that turns their check boxes into single-choice. Locking stops changes altogether. Hiding removes the card from view. Top N limits by value.

Q26 Answer: C V1 · Create reports

textClasses define fonts, sizes and colours for text categories such as titles, labels and callouts across all visuals in one place. dataColors only sets the palette. Per-visual visualStyles would need repeating for every visual type.

Q27 Answer: B V2 · Enhance reports for usability and storytelling

A bookmark navigator can be limited to a bookmark group, so organising bookmarks into groups controls which ones it shows. Deleting bookmarks affects other pages. Separate buttons work but don't update automatically.

Q28 Answer: C V2 · Enhance reports for usability and storytelling

Personalisation can be turned off per visual, keeping it available for every other visual. Turning it off for the report is too broad. Locking filters or hiding the chart doesn't meet the need.

Q29 Answer: B V2 · Enhance reports for usability and storytelling

Show as a table displays the visual's data in a table that screen readers can navigate, and it has a keyboard shortcut, Alt+Shift+F11. Focus mode only enlarges the chart. Spotlight dims other visuals. A PDF export isn't the accessible in-report option.

Q30 Answer: C V2 · Enhance reports for usability and storytelling

A visual can be sorted by any field it contains, including tooltip fields, without plotting it. Sort by column fixes a column's order permanently. Adding it as a series changes the chart, and Power Query order doesn't control visual sorting.

Q31 Answer: 1→A 2→D 3→C 4→B V2 · Enhance reports for usability and storytelling

Edit interactions controls cross-filtering between visuals. Sync slicers shares a slicer's selection across pages. Drillthrough navigates with context. Report page tooltips show a custom page on hover. Bookmarks capture states and aren't needed for any of these.

Q32 Answer: D V3 · Identify patterns and trends

Anomaly explanations are drawn from the fields you list in Explain by. Without them, Power BI has nothing to analyse. Sensitivity changes which points are flagged, not the explanations.

Q33 Answer: D V3 · Identify patterns and trends

Locking a level stops consumers removing it while still letting them expand further levels. Filters and hidden fields don't control the tree's structure. Turning off AI splits only removes the AI options.

Q34 Answer: B V3 · Identify patterns and trends

Q&A setup lets you add suggested questions, which appear in the Q&A visual as clickable prompts. Synonyms help Q&A understand terms but don't suggest questions. Smart narratives and tooltips are unrelated.

Q35 Answer: D S1 · Create and manage workspaces and assets

Featured content appears on Home for users who have access. Certification marks trust but doesn't place content on Home. You can't set other users' favourites. Publish to web is public.

Q36 Answer: A S1 · Create and manage workspaces and assets

A single gateway, ideally a cluster for resilience, can host many connections to different databases and serve many models. One gateway per database adds administration for no benefit. On-premises sources always need a gateway.

Q37 Answer: C S1 · Create and manage workspaces and assets

Deployment pipelines need the workspaces to be on Premium, Premium Per User or Fabric capacity. Roles, gateways and Desktop settings don't enable them in a Pro workspace.

Q38 Answer: Yes · No · Yes S1 · Create and manage workspaces and assets

Subscriptions can include full-report attachments, and they can run on a schedule or after data refresh. Recipients must have access to the content, and what they see respects their permissions.

Q39 Answer: B S2 · Secure and govern Power BI items

User activities such as viewing and exporting Power BI content are recorded in the audit and activity logs, which administrators and compliance teams can search. The other tools don't record user activity.

Q40 Answer: C S2 · Secure and govern Power BI items

Viewing a report requires Read access to the semantic model it uses, wherever that model lives. Granting Read on the model in workspace A fixes the errors. Roles in workspace B don't cover workspace A.

Q41 Answer: C S2 · Secure and govern Power BI items

Labels set in Desktop protect the .pbix file and are carried to the service on publish, for content that doesn't already have a label there. They aren't stripped or blocked, and certification is unrelated.

Q42 Answer: A P1 · Get or connect to data

A composite model keeps history fast in memory while querying live in-transit data directly, refreshed by automatic page refresh. Dual dimensions serve both sides efficiently. Import alone can't be five minutes fresh. All-DirectQuery slows historical analysis.

Q43 Answer: A M1 · Design and implement a data model

With one Depot slicer and mostly origin-based analysis, the origin relationship is active, and destination measures activate the second relationship with USERRELATIONSHIP. Two active relationships aren't allowed. Two Depot tables would need two slicers, which the requirement rules out.

Q44 Answer: A V1 · Create reports

Organizational visuals are deployed centrally by an admin, so every author gets the approved version in their visualisation pane. Downloading individually doesn't scale and bypasses governance. Themes and calculation groups can't add visuals.

Q45 Answer: D S2 · Secure and govern Power BI items

Because the requirement covers both origin and destination, the filter must test both columns on the fact table, using the depots mapped to the signed-in user. Requiring both columns with && drops shipments to or from other depots. Filtering Depot through the active relationship only covers the origin. Comparing a DepotID with a user name matches nothing.