

# Mean-field modeling of brain-scale dynamics for the evaluation of EEG source-space networks

Sahar Allouch<sup>1,2</sup>, Maxime Yochum<sup>1</sup>, Aya Kabbara<sup>1</sup>, Joan Duprez<sup>1</sup>, Mohamad Khalil<sup>2,4</sup>, Fabrice Wendling<sup>1</sup>, Mahmoud Hassan<sup>3</sup>, Julien Modolo<sup>1</sup>

<sup>1</sup>Univ Rennes, LTSI - INSERM U1099, F-35000 Rennes, France

<sup>2</sup>Azm Center for Research in Biotechnology and its Applications, EDST, Tripoli, Lebanon


<sup>3</sup>NeuroKyma, F-35000 Rennes, France

<sup>4</sup>CRSI research center, Faculty of Engineering, Lebanese University, Beirut, Lebanon

## Introduction

### Problematic:

- The absence of a 'ground truth' when applying EEG-source connectivity on real EEG data represents a challenge for comparative studies




### Objective:

- Use **COALIA**, a physiologically-inspired model to generate epileptiform, cortical activity and evaluate the effect of:


- five different electrode densities
- two inverse solution algorithms
- two functional connectivity measures

## Materials and Methods




Pipeline of the study.

## Results




Accuracy of the estimated networks based on different electrode montages for eLORETA/PLV and wMNE/PLV



Average networks over trials for all electrode montages and inverse solution/connectivity measure combinations.

### Qualitative results:

- Higher sensor density → Better performance
- wMNE/wPLI → Best performance
- eLORETA/wPLI → Worst performance
- wMNE/PLV → Most affected by noise



Mean accuracy and standard error of each inverse solution/connectivity measure combination plotted against different levels of noise for the case of 256 electrodes

## Conclusions

- Proof of concept that COALIA can provide a ground-truth for comparative studies aiming at optimizing the EEG-source connectivity pipeline.
- A higher network estimation accuracy requires a high number of EEG electrodes
- A careful choice of an inverse solution/connectivity measure combination is necessary.


### Citation:

Allouch, S., Yochum, M., Kabbara, A., Duprez, J., Khalil, M., Wendling, F., Hassan, M., Modolo, J. (2020). Mean-field modeling of brain-scale dynamics for the evaluation of EEG source-space networks. Brain Topography (minor revision). BioRxiv <https://doi.org/10.1101/2020.09.16.299305>

## Acknowledgments

This work was financed by the Rennes University, the Institute of Clinical Neuroscience of Rennes (project named EEGCog). Authors would also like to thank the Lebanese Association for Scientific Research (LASER) and Campus France, Programme Hubert Curien CEDRE (PROJECT No. 42257YA), for supporting this study. The authors would like to acknowledge the Lebanese National Council for Scientific Research (CNRS-L), the Agence Universitaire de la Francophonie (AUF) and the Lebanese university for granting Ms. Allouch a doctoral scholarship.

## Results



Accuracy of the estimated networks based on different electrode montages for eLORETA/wPLI and wMNE/wPLI