

cTheorems

sahasatvik

<https://github.com/sahasatvik/typst-theorems>

Contents

1. Setup	1
2. Demonstration	2
3. Features	2
3.1. Numbered theorems	2
3.2. References	3
3.3. Chained numbering	3
3.4. Shared numbering	3
3.5. Proofs	3
3.6. Equation tags	4
3.7. Defer, restate, and display	4
3.8. Formatting	5
4. Acknowledgements	5
A. Function documentation	7
A.1. ctheorems	7
A.2. thm-state	12
A.3. thm-counter	18
B. Themes	20
B.1. thm-themes.ams	20

This package provides functions that help create numbered theorem environments, taking heavy inspiration from the L^AT_EX packages `amsthm`, `thmtools`, `apxproof`.

A *theorem environment* combines content with automatically updated *numbering* information. Theorem environments can

- share the same counter (*Theorems* and *Lemmas* often do so)
- have their counters attached to headings or other environments (*Corollaries* are often numbered based upon the parent *Theorem*)
- be `<label>`-ed and `@reference`-d
- be restated or deferred to appear later in the document.

This package also introduces a few miscellaneous features related to mathematical writing.

- Proof environments, with *QED* symbols.
- Equation tags.
- Predefined sets of commonly used theorem environments, and a few themes.

1. Setup

```
#import "@preview/ctheorems:2.0.0": *
#show: thm-rules // Must include!
```

Applying the `thm-rules` show rule — in the same `.typ` file where `ctheorems` functions have been used — is **essential** for displaying theorem environments, references, and equations correctly!

A standard set of theorem environments in the AMS style is available using

```
#import thm-themes.ams: *
```

This lets you immediately use `theorem`, `proof`, `proposition`, `lemma`, `corollary`, `definition`, `example`, `remark`, `claim`. See Appendix B.1 for more details.

2. Demonstration

```
#import "@preview/ctheorems:2.0.0": *
#import thm-themes.ams: *
#show: thm-rules.with(
  qed-symbol:  $\square$ 
)

#definition[Expectation][
  The expectation of a random variable  $X$  on
  a probability space  $(\Omega, \mathcal{E}, \mathbb{P})$  is
  $
  \mathbb{E}[X] = \int X \, d\mathbb{P},
  $ whenever well-defined.
] <expectation>

#remark[
  We require at least one of  $\mathbb{E}[X^+]$ ,
   $\mathbb{E}[X^-]$  to be finite.
]

#proposition[
  For any  $A \in \mathcal{E}$ ,
   $\mathbb{P}(X \in A) = \mathbb{E}[\mathbf{1}_A(X)]$ .
  $
] <prob-exp>

#theorem[Markov][
  Let  $X \geq 0$ . For all  $a > 0$ ,
   $\mathbb{P}(X > a) \leq \mathbb{E}[X] / a$ .
  $
] <markov>

#corollary[Chebyshev][
  Let  $\mathbb{E}[X] = \mu$ ,  $\text{var}[X] = \sigma^2$ .
  Then,
   $\mathbb{P}(|X - \mu| \geq k\sigma) \leq 1 / k^2$ .
  $
] <chebyshev>

#proof[of @markov][
  $
  \mathbb{P}(X > a) \leq \mathbb{E}[\mathbf{1}_{(a, \infty)}(X)]
  \tag*{Prop. 2.1}
  \leq \mathbb{E}\left[\left(\frac{X}{a}\right) \mathbf{1}_{(a, \infty)}(X)\right]
  \leq \frac{\mathbb{E}[X]}{a}.
  $
] <qedhere>
```

Definition 2.1 (Expectation). The expectation of a random variable X on a probability space $(\Omega, \mathcal{E}, \mathbb{P})$ is

$$\mathbb{E}[X] = \int X \, d\mathbb{P},$$

whenever well-defined.

Remark. We require at least one of $\mathbb{E}[X^+]$, $\mathbb{E}[X^-]$ to be finite.

Proposition 2.1. For any $A \in \mathcal{E}$,

$$\mathbb{P}(X \in A) = \mathbb{E}[\mathbf{1}_A(X)].$$

Theorem 2.2 (Markov). Let $X \geq 0$. For all $a > 0$,

$$\mathbb{P}(X > a) \leq \frac{\mathbb{E}[X]}{a}.$$

Corollary 2.2.1 (Chebyshev). Let $\mathbb{E}[X] = \mu$, $\text{var}[X] = \sigma^2$. Then,

$$\mathbb{P}(|X - \mu| \geq k\sigma) \leq \frac{1}{k^2}.$$

Proof of Theorem 2.2.

$$\begin{aligned} \mathbb{P}(X > a) &= \mathbb{E}[\mathbf{1}_{(a, \infty)}(X)] \quad (\text{Prop. 2.1}) \\ &\leq \mathbb{E}\left[\left(\frac{X}{a}\right) \mathbf{1}_{(a, \infty)}(X)\right] \\ &\leq \frac{\mathbb{E}[X]}{a}. \quad \square \end{aligned}$$

3. Features

3.1. Numbered theorems

```
#let theorem = thm.with(
  supplement: "Theorem",
  base-level: 1
)

#theorem("Euclid")[
  There are infinitely many primes.
] <euclid>
```

Theorem 3.1 (Euclid). There are infinitely many primes.

Note that `theorem` inherits its numbering from the current heading (the default `thm.base`). By setting `thm.base-level` to `1`, this theorem only uses the first level count from its base.

3.2. References

Since our theorem has been labeled `<euclid>`, we can reference it elsewhere in the document via `@euclid`.

We will supply a proof of `@euclid` later.

We will supply a proof of Theorem 3.1 later.

3.3. Chained numbering

Theorem environments can be attached together by setting the child's `thm.base` to the parent's `thm.counter`.

```
#let corollary = thm.with(
  supplement: "Corollary",
  base: "Theorem"
)

#corollary(rewrite: true)[
  There is no largest prime number.
] <largest-prime>

#proof([of @largest-prime], defer: true)[
  The existence of a largest prime would
  imply the finitude of the set of primes.
]
```

Corollary 3.1.1. *There is no largest prime number.*

We have set `thm.restate` and `thm.defer` — go to Section 3.7 to find out more!

3.4. Shared numbering

Theorem environments can share the same numbering by setting a common `thm.counter`.

```
#let proposition = thm.with(
  supplement: "Proposition",
  counter: "Theorem",
  base-level: 1
)

#proposition[
  If a natural number divides  $a$  and  $b$ , it
  also divides  $a - b$ .
]
```

Proposition 3.2. *If a natural number divides a and b , it also divides $a - b$.*

For directly manipulating theorem counters, see `thm-counter-get`, `thm-counter-step`, `thm-counter-update`.

3.5. Proofs

Theorems go hand in hand with proofs, which are available using `proof`.

```
#proof[of @euclid][
  Suppose to the contrary that $p_1, p_2,
  dots, p_n$ is a finite enumeration of
  all primes. Set $P = p_1 p_2 \dots p_n$.
  Since $P + 1$ is not in our list, it cannot
  be prime. Thus, some prime factor $p_j$
  divides $P + 1$. Since $p_j$ also divides
  $P$, it must divide the difference $(P + 1)
  - P = 1$, a contradiction.
]
```

Proof of Theorem 3.1. Suppose to the contrary that $p_1, p_2, \dots, p_n$ is a finite enumeration of all primes. Set $P = p_1 p_2 \dots p_n$. Since $P + 1$ is not in our list, it cannot be prime. Thus, some prime factor p_j divides $P + 1$. Since p_j also divides P , it must divide the difference $(P + 1) - P = 1$, a contradiction. ■

Proof environments will float a QED symbol (■) at the bottom right by default. The symbol can be customized by setting `thm-rules.qed-symbol`. If your proof ends in a block equation, or a list/enum, you can place `qedhere` to correctly position the QED symbol.

```
#show: thm-rules.with(qed-symbol: $square$)

#theorem[Prime gaps][
  There are arbitrarily long stretches of
  composite numbers.
]
#proof[
  For any $n > 2$, consider $
    n! + 2, quad
    n! + 3, quad \dots, quad
    n! + n. #qedhere
$
]
```

Theorem 3.3 (Prime gaps). *There are arbitrarily long stretches of composite numbers.*

Proof. For any $n > 2$, consider

$$n! + 2, \quad n! + 3, \quad \dots, \quad n! + n. \quad \square$$

Caution: `qedhere` does not play well with numbered equations!

3.6. Equation tags

Tags can be inserted into equations using `tag`. These float to the right, mimicking `\tag` in $\text{\LaTeX}$.

```
$
(a + b)^2
&= a^2 + 2 a b + b^2 \ \
&\leq 2a^2 + 2b^2 #tag[(AM-GM)] \
&\leq 2 \thinspace \max\{a, b\}^2.
$
```

$$\begin{aligned} (a + b)^2 &= a^2 + 2ab + b^2 \\ &\leq 2a^2 + 2b^2 \quad (\text{AM-GM}) \\ &\leq 2 \max\{a, b\}^2. \end{aligned}$$

3.7. Defer, restate, and display

Theorem environments can be restated, or deferred to later in the document by setting `thm.restate`, `thm.defer` as in the example in Section 3.3, then calling `thm-restate`.

```
#import thm-state: thm-restate, thm-display

#thm-restate()
```

Corollary 3.1.1. *There is no largest prime number.*

Proof of Corollary 3.1.1. The existence of a largest prime would imply the finitude of the set of primes. ■

This is often useful for pushing content to the appendix. For finer control, consider using `thm.restate-keys`.

```
Euclid's Theorem states:
#thm-restate(
  "Euclid",
  all: true,
  fmt: thm  $\Rightarrow$  thm.body
)
```

Euclid's Theorem states: There are infinitely many primes.

The `thm-display` function is the most powerful method for manipulating theorem environments. The following produces a crude outline of named theorem environments (so far), excluding proofs; see `thm.fmt` for more information about the formatting function `fmt`.

```
#thm-display(
  thm  $\Rightarrow$  thm.name  $\neq$  none and thm.supplement  $\neq$  "Proof", // Filter
  fmt: thm  $\Rightarrow$  { // Format
    let head = [*#thm.supplement~#thm.number*]
    if thm.name  $\neq$  none { head = head + [~(#thm.name)] }
    let page = link(thm.loc, [#thm.loc.position().page]) // Get page number
    [#head~#box(width: 1fr, repeat[.])~#page\ ]
  }
)
```

Definition 2.1 (Expectation)	2
Theorem 2.2 (Markov)	2
Corollary 2.2.1 (Chebyshev)	2
Theorem 3.1 (Euclid)	2
Theorem 3.3 (Prime gaps)	4

Setting `thm-display.final` to `true` would extend this search to the entire document.

3.8. Formatting

The default theorem formatting function, `thm-fmt-block` helps with basic customization of the theorem title and body, along with the surrounding block.

```
#let theorem-standout = theorem.with(
  stroke: 1pt + green,
  fill: green.lighten(95%),
  outset: 0.7em,
  spacing: 1.5em
)

#theorem-standout(
  title-fmt: x  $\Rightarrow$  smallcaps(strong(x))
)[
  There are infinitely many composite
  numbers.
]
```

THEOREM 3.4. *There are infinitely many composite numbers.*

See `thm.fmt` for more information on how to write your own custom formatting function.

4. Acknowledgements

Thanks to

- [MJHutchinson](#) for suggesting and implementing the `base-level` and `base: none` features,

- [rmolinari](#) for suggesting and implementing the `separator: ...` feature,
- [DVDTSB](#) for contributing
 - the idea of passing named arguments from the theorem directly to the `fmt` function.
 - the `number: ...` override feature.
 - the `title: ...` override feature in `thm-plain`.
- [PgBiel](#) for fixing breaking changes in version updates.
- The authors of the $\text{\LaTeX}$ packages `amsthm`, `thmtools`, `apxproof`.
- The awesome devs of [typst.app](#) for their support.

A. Function documentation

A.1. ctheorems

- `thm()`
- `proof()`
- `tag()`
- `thm-rules()`
- `thm-fmt-block()`
- `proof-body-fmt()`

Variables:

- `qedhere`

`thm`

Numbered theorem environment.

```
#thm(base: none)[Name][
  #lorem(10)
]

#thm(supplement: "Corollary", base: "Theorem")[
  #lorem(7)
]
```

Theorem 1 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do.*

Corollary 1.1. *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Parameters

```
thm(
  ..args: arguments ,
  body: content ,
  supplement: str content ,
  counter: str auto ,
  fmt: function ,
  base: str none ,
  base-level: int none ,
  name: content ,
  number: content auto none ,
  numbering: str function none ,
  restate: bool ,
  defer: bool ,
  restate-keys: array ,
  ref-fmt: function
) -> figure context
```

..args arguments

Extra arguments. See `thm.name`.

body content

Theorem body.

supplement str or content

Theorem supplement.

Default: "Theorem"

counter `str` or `auto`

Environment counter name. If `auto`, defaults to `thm.supplement`.

Default: `auto`

fmt `function`

Formatting function controlling the appearance of the theorem environment, of the form `thm  $\Rightarrow$  content`. `thm` is a dictionary whose keys are essentially the arguments of `thm()`, with a couple of additions/exceptions.

- The keys `name`, `counter`, `number`, `restate`-keys contain their finally inferred/computed values.
- The key `loc` contains the theorem's location.
- The key `args` contains a dictionary of only the named arguments from `thm.args`.

It is often useful to use `thm.args` to control formatting functions.

Default: `thm-fmt-block`

base `str` or `none`

Base counter name, whose numbering prefixes the theorem environment numbering. If `"heading"`, use the heading counter. If `none`, the theorem environment maintains a global count with no prefix.

Default: `"heading"`

base-level `int` or `none`

Base level, determining the number of levels of the `base` numbering to use for the theorem environment numbering. If `none`, all levels from the `base` numbering are used. Setting a base level higher than what the `base` provides will introduce zeros for padding.

Default: `none`

name `content`

Theorem name. If `auto`, the first positional argument from `thm.args` (if present) is chosen as the theorem environment's name.

Default: `auto`

number `content` or `auto` or `none`

Theorem number. If `auto` (and `thm.numbering` is not `none`), the number is computed based on `thm.counter`, `thm.base`, `thm.base-level`.

Default: `auto`

numbering `str` or `function` or `none`

Theorem numbering style. If `none`, numbering is suppressed.

Default: "1.1"

restate `bool`

Restate flag. See `thm-restate()`.

Default: `false`

defer `bool`

Defer flag. See `thm-restate()`.

Default: `false`

restate-keys `array`

Keys used by `thm-restate.keys` for filtering. If `auto`, defaults to an array containing `thm.supplement` and `thm.name` (if present).

Default: `auto`

ref-fmt `function`

Formatting function for references, with the same form as `thm.fmt`. The `thm` dictionary carries an additional `ref-supplement` key containing the supplement used in the `@cite[ref-supplement]` call.

Default: `thm => {`

```
  let supplement = thm.supplement
  if thm.ref-supplement ≠ none { supplement = thm.ref-supplement }
  if supplement ≠ none and supplement ≠ [] { supplement = [#supplement~] }
  [#supplement#link(thm.loc, (thm.number))]
}
```

proof

Proof environment. Identical to `thm()`, with different defaults. Uses the `thm-fmt-block()` formatting function (for `thm.fmt`), with `proof-body-fmt()` (for `thm-fmt-block.body-fmt`).

```
#thm(base: none)[
  #lorem(6)
]
#proof[
  #lorem(3)
]
```

Theorem 2. *Lorem ipsum dolor sit amet, consectetur.*

Proof. Lorem ipsum dolor. ■

Parameters

`proof()` -> `function`

tag

Add content which floats to the right in an equation.

```

$(a + b)^2
&= a^2 + 2 a b + b^2 \
&\leq 2a^2 + 2b^2 #tag[(AM-GM)] \
&\leq 2 \text{thin} \max\{a, b\}^2.
$

```

$$\begin{aligned}
 (a + b)^2 &= a^2 + 2ab + b^2 \\
 &\leq 2a^2 + 2b^2 \quad (\text{AM-GM}) \\
 &\leq 2 \max\{a, b\}^2.
 \end{aligned}$$

Parameters

```

tag(
  t: any ,
  move: bool
) -> content

```

t any

Content to use as tag

move bool

If **false**, tags occupy no horizontal space in the equation layout. Set this to **true** if equation content overlaps the tag. This will have the minor disadvantage of moving the equation off-center to accommodate the tag.

Note: Trying to determine this option automatically currently causes layout convergence issues in some cases.

Default: **false**

thm-rules

Rules for styling theorem environments, references, proofs, etc. *Must appear at the beginning of the document.*

Parameters

```

thm-rules(
  qed-symbol: content ,
  doc
) -> content

```

qed-symbol content

Symbol displayed at the end of proofs. See [proof\(\)](#), [qedhere](#), [proof-body-fmt\(\)](#). Use as

```

#show: thm-rules.with(
  qed-symbol: $square$
)

#proof[
  #lorem(5)
  $ \int_0^\infty \frac{\sin(x)}{x} \text{thin} dx = \frac{\pi}{2}.
  #qedhere $
]

```

Proof. Lorem ipsum dolor sit amet.

$$\int_0^\infty \frac{\sin(x)}{x} dx = \frac{\pi}{2}. \quad \square$$

Default: **\$qed\$**

thm-fmt-block

Default formatting function for theorem environments, wrapping everything in a block. Intended for use in `thm.fmt`. Named arguments from `thm.args` can override all of the arguments below; any remaining named arguments are passed to the block. Blocks have `width: 100%` set by default.

Parameters

```
thm-fmt-block(  
  thm: dictionary ,  
  block-args: dictionary ,  
  name-fmt: function ,  
  title-fmt: function ,  
  body-fmt: function ,  
  separator: content  
) -> content
```

thm dictionary

Theorem data. See `thm.fmt` for details.

block-args dictionary

Named arguments for the block.

Default: `(:)`

name-fmt function

Formatting for the environment name.

Default: $x \Rightarrow [(#x)]$

title-fmt function

Formatting for the environment title (head and number).

Default: `strong`

body-fmt function

Formatting for the environment body.

Default: $x \Rightarrow x$

separator content

Separator between title and body.

Default: `[*.* ]`

proof-body-fmt

Used as the `body-fmt` in `proof()`, for properly styling proofs by inserting a qed symbol at the end of the body. Also see [qedhere](#).

```
#show: thm-rules.with(qed-symbol: $"Q.E.D."$)

#proof-body-fmt[#lorem(3)]

#proof-body-fmt[
$
  phi.alt(x) = 1/sqrt(2 pi) e^(-x^2/2) #qedhere
$
]
```

Lorem ipsum dolor. Q.E.D.

$$\phi(x) = \frac{1}{\sqrt{2\pi}} e^{-x^2/2} \quad \text{Q.E.D.}$$

Parameters

`proof-body-fmt` (`body`: `content`) -> `content`

body `content`

Proof body.

qedhere `metadata`

If placed in a block equation/enum/list within a proof, place a qed symbol to its right.

```
#proof[
#lorem(3)
$ x^2 + y^2 = z^2. #qedhere $
]

#proof[
+ #lorem(4)
+ #lorem(5) #qedhere
]

#proof[
$
(a + b)^2 &= (a + b)(a + b) \
&= a^2 + 2 a b + b^2. #qedhere
$
]
```

Proof. Lorem ipsum dolor.

$$x^2 + y^2 = z^2. \quad \blacksquare$$

Proof.

1. Lorem ipsum dolor sit. ■
2. Lorem ipsum dolor sit amet. ■

Proof.

$$(a + b)^2 = (a + b)(a + b) \\ = a^2 + 2ab + b^2. \quad \blacksquare$$

A.2. thm-state

Methods for restating, reformatting, filtering, and manipulating theorem environments from elsewhere in the document. Every call to `thm` appends a `thm` data dictionary to the state `thm-stored`, where the keys of `thm` are as described in `thm.fmt`.

Import all functions using

```
#import thm-state: *
```

- `thm-restate()`
- `thm-display()`

Variables:

- `thm-stored`

thm-restate

Displays theorem environments which have been marked to be restated or deferred (by setting `thm.restate`, `thm.defer`), can be filtered. Useful for pushing content to the appendix.

```

#let theorem = thm.with(supplement: "Theorem")
#let lemma = thm.with(
  supplement: "Lemma",
  counter: "Theorem",
)
#let definition = thm.with(
  supplement: "Definition",
  body-fmt: x ⇒ x
)

≡ Heading

#definition[#lorem(2)]
#lemma[#lorem(8)]

#theorem("Name", restate: true)[#lorem(7)]
#proof(defer: true)[
  #lorem(7)
]

#lemma[#lorem(4)]

≡ Appendix

#thm-restate()

```

1 Heading

Definition 1.1. Lorem ipsum.

Lemma 1.1. *Lorem ipsum dolor sit amet, consectetur adipiscing elit.*

Theorem 1.2 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Lemma 1.3. *Lorem ipsum dolor sit.*

2 Appendix

Theorem 1.2 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

Parameters

```

thm-restate(
  ..keys: str content array function,
  fmt: function auto,
  at: label selector location function auto,
  final: bool,
  all: bool
) -> content

```

..keys str or content or array or function

String/content keys, array of keys, or functions used to filter theorem environments. A theorem environment is displayed if it passes *any* of the filters.

If *k* in *keys* is a string/content, theorem environments containing *k* in its array of *restate-keys* will be matched.

```

#let theorem = thm.with(supplement: "Theorem")
#let lemma = thm.with(
  supplement: "Lemma",
  counter: "Theorem",
)

≡ Heading

#theorem(restate: true)[#lorem(6)]
#lemma(restate: true)[#lorem(4)]
#proof(defer: true)[#lorem(7)]
#lemma(restate: true)[#lorem(3)]

≡ Restate lemmas/proofs
#thm-restate("Lemma", "Proof")

```

1 Heading

Theorem 1.1. *Lorem ipsum dolor sit amet, consectetur.*

Lemma 1.2. *Lorem ipsum dolor sit.*

Lemma 1.3. *Lorem ipsum dolor.*

2 Restate lemmas/proofs

Lemma 1.2. *Lorem ipsum dolor sit.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

Lemma 1.3. *Lorem ipsum dolor.*

If `k` in `keys` is an array of `strings/content`, theorem environments containing *all* keys from `k` in its array of `restate-keys` will be matched.

≡ Heading

```
#theorem(
  "Result A",
  restate: true,
  restate-keys: ("Theorem", "Result A")
)[#lorem(6)]
#proof(
  defer: true,
  restate-keys: ("Proof", "Result A")
)[#lorem(7)]
#theorem(restate: true)[#lorem(6)]
#theorem(
  "Result B",
  restate: true,
  restate-keys: ("Theorem", "Result B")
)[#lorem(6)]
#proof(
  defer: true,
  restate-keys: ("Proof", "Result B")
)[#lorem(7)]
```

≡ Restate Result A

```
#thm-restate("Result A")
```

≡ Restate theorems tagged Result B

```
#thm-restate(("Theorem", "Result B"))
```

3 Heading

Theorem 3.1 (Result A). *Lorem ipsum dolor sit amet, consectetur.*

Theorem 3.2. *Lorem ipsum dolor sit amet, consectetur.*

Theorem 3.3 (Result B). *Lorem ipsum dolor sit amet, consectetur.*

4 Restate Result A

Theorem 3.1 (Result A). *Lorem ipsum dolor sit amet, consectetur.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

5 Restate theorems tagged Result B

Theorem 3.3 (Result B). *Lorem ipsum dolor sit amet, consectetur.*

If `k` in `keys` is a function, it must be of the form `restate-keys → bool`.

≡ Heading

```
#theorem(
  restate: true,
  restate-keys: (
    "Theorem", "Unproven claim"
  )
)[#lorem(6)]
#theorem(restate: true)[#lorem(6)]
#lemma(
  "Claim D",
  restate: true,
  restate-keys: ("Lemma", "Claim D")
)[#lorem(6)]
```

≡ Restate claims

```
#thm-restate(
  keys ⇒ keys.any(
    k ⇒ lower(k).contains("claim")
  )
)
```

6 Heading

Theorem 6.1. *Lorem ipsum dolor sit amet, consectetur.*

Theorem 6.2. *Lorem ipsum dolor sit amet, consectetur.*

Lemma 6.3 (Claim D). *Lorem ipsum dolor sit amet, consectetur.*

7 Restate claims

Theorem 6.1. *Lorem ipsum dolor sit amet, consectetur.*

Lemma 6.3 (Claim D). *Lorem ipsum dolor sit amet, consectetur.*

Formatting function, with the same form as `thm.fmt`. The default `auto` uses the originally supplied formatting function `thm.fmt`. See `thm-display.fmt`.

Default: `auto`

at `label` or `selector` or `location` or `function` or `auto`

Location up to which theorem environments will be displayed. The default `auto` uses the location where `thm-restate()` was called. See `thm-display.at`.

Default: `auto`

final `bool`

If `true`, display environments up to the end of the document. Overrides `thm-restate.at`. See `thm-display.final`.

Default: `false`

all `bool`

If `true`, ignores the `thm`'s `restate` or `defer` state (see `thm.restate`, `thm.defer`). Calling `thm-restate(all: true)` is equivalent to `thm-display()`.

Default: `false`

thm-display

Displays all theorem environments, can be filtered.

Every call to `thm()` appends a `thm` dictionary to `thm-stored`. A `thm` dictionary contains complete information about a theorem environment; its keys are as described in `thm.fmt`. This lets theorems be restated, filtered, and otherwise manipulated elsewhere in a document.

```

#let theorem = thm.with(supplement: "Theorem")
#let lemma = thm.with(
  supplement: "Lemma",
  counter: "Theorem",
)
#let definition = thm.with(
  supplement: "Definition",
  body-fmt: x  $\Rightarrow$  x
)

= Heading <h1>

#theorem("Name")[#lorem(7)]
#proof[
  #lorem(7)
]

= New_heading <h2>

#lemma[#lorem(8)]
#definition("Thing")[#lorem(2)]
#lemma[#lorem(4)]

= Display_all

#thm-display()

```

1 Heading

Theorem 1.1 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

2 New heading

Lemma 2.1. *Lorem ipsum dolor sit amet, consectetur adipiscing elit.*

Definition 2.1 (Thing). Lorem ipsum.

Lemma 2.2. *Lorem ipsum dolor sit.*

3 Display all

Theorem 1.1 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

Lemma 2.1. *Lorem ipsum dolor sit amet, consectetur adipiscing elit.*

Definition 2.1 (Thing). Lorem ipsum.

Lemma 2.2. *Lorem ipsum dolor sit.*

Parameters

```

thm-display(
  ..filters: function,
  fmt: function auto,
  at: label selector location function auto,
  final: bool
) -> content

```

..filters function

Filtering functions. Each f in `filters` is a function `thm  $\Rightarrow$  bool`. A theorem environment is displayed if it passes *any* of the filters.

= Display only theorems/proofs

```
#thm-display(  
  thm => thm.supplement == "Theorem",  
  thm => thm.supplement == "Proof",  
)
```

= Display if 'name' is present

```
#thm-display(  
  thm => thm.name != none  
)
```

4 Display only theorems/ proofs

Theorem 1.1 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

5 Display if name is present

Theorem 1.1 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Definition 2.1 (Thing). Lorem ipsum.

fmt **function** or **auto**

Formatting function, with the same form as `thm.fmt`. The default **auto** uses the originally supplied formatting function `thm.fmt`.

```
#thm-display(  
  thm => thm.supplement != "Proof",  
  final: true,  
  fmt: thm => {  
    let head = [~thm.supplement~#thm.number*]  
    if thm.name != none {  
      head = head + [~(#thm.name)]  
    }  
    let page = link(thm.loc,  
[#thm.loc.position().page])  
    [#head~#box(width: 1fr, repeat[.])~#page\ ]  
  }  
)
```

Theorem 1.1 (Name)	16
Lemma 2.1	16
Definition 2.1 (Thing)	16
Lemma 2.2	16

Setting `final: true` ensures that even if this `thm-display()` call is placed at the beginning of the document, all theorem environments are listed.

Default: **auto**

at **label** or **selector** or **location** or **function** or **auto**

Location up to which theorem environments will be displayed. The default **auto** uses the location where `thm-display()` was called.

= Display up to '<h2>'

```
#thm-display(at: <h2>)
```

6 Display up to <h2>

Theorem 1.1 (Name). *Lorem ipsum dolor sit amet, consectetur adipiscing.*

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing. ■

Default: `auto`

final `bool`

If `true`, display all theorem environments up to the end of the document. Useful for creating lists of theorems in the beginning of documents, before they've been stated. Overrides `thm-display.at`.

Default: `false`

thm-stored `state`

State containing theorem environment data, as an array of `thm` dictionaries.

A.3. `thm-counter`

Exposes methods for manipulating counters used by theorem environments. Import all functions using

```
#import thm-counter: *
```

- `thm-counter-get()`
- `thm-counter-step()`
- `thm-counter-update()`

Variables:

- `thm-counters`

`thm-counter-get`

Get theorem counter. Must be wrapped in context. See `thm.counter`.

Parameters

`thm-counter-get(counter: str) -> array`

`thm-counter-step`

Step theorem counter forward, relative to a `base` and `base-level`. Must be wrapped in context. See `thm.counter`, `thm.base`, `thm.base-level`.

Parameters

```
thm-counter-step(  
    counter: str,  
    base: str,  
    base-level: int  
)
```

`thm-counter-update`

Update theorem counter See `thm.counter`.

Parameters

```
thm-counter-update(  
    counter: str,
```

```
    update: function  
  )
```

thm-counters state

State containing a dictionary of theorem environment counters. Each dictionary key is a counter name, and each entry is a counter value (array of integers).

B. Themes

B.1. thm-themes.ams