1RUA25BCA0093 Sahasra Marreboyina, DBMS LAB:

Lab 2:

Practical 1.

```
CREATE TABLE books (
book_id INT PRIMARY KEY,
title VARCHAR(50),
author VARCHAR(50),
price INT );
INSERT INTO books VALUES
(1, 'circie', 'madeline', 350),
(2, '1984', 'george', 400),
(3, 'song of Achillies', 'madeline', 600);
SELECT * FROM books;
```

Output:

Output:

```
+---------+-------------------+----------+-------+
| book_id | title             | author   | price |
+---------+-------------------+----------+-------+
|       1 | circie            | madeline |   350 |
|       2 | 1984              | george   |   400 |
|       3 | song of Achillies | madeline |   600 |
+---------+-------------------+----------+-------+
```

Practical 2.

```
CREATE TABLE players (
player_id INT PRIMARY KEY,
name VARCHAR(50),
game VARCHAR(30),
rank_level VARCHAR(20) DEFAULT 'bronze'
);
INSERT INTO players (player_id, name, game) VALUES
(11, 'lemon', 'genshin'),
(12, 'coffee', 'genshin');
SELECT * FROM players;
```

Output:

Output:

```
+-----------+--------+---------+------------+
| player_id | name   | game    | rank_level |
+-----------+--------+---------+------------+
|        11 | lemon  | genshin | bronze     |
|        12 | coffee | genshin | bronze     |
+-----------+--------+---------+------------+
```

Practical 3.

```
CREATE TABLE flight (
flight_no INT PRIMARY KEY,
destination VARCHAR(50),
gate_no VARCHAR(10) );
INSERT INTO flight VALUES
(101, 'banglore', 't4-z'),
(102, 'dubai', 't2-b'),
(103, 'mumbai', 't3-c');
UPDATE flight SET gate_no = 't2-g' WHERE flight_no = 102;
SELECT * FROM flight;
```

Output:

Output:

```
+-----------+-------------+---------+
| flight_no | destination | gate_no |
+-----------+-------------+---------+
|       101 | banglore    | t4-z    |
|       102 | dubai       | t2-g    |
|       103 | mumbai      | t3-c    |
+-----------+-------------+---------+
```

Practical 4.

```
CREATE TABLE movie (
movie_id INT PRIMARY KEY,
 name VARCHAR(50),
genre VARCHAR(30),
ticket_price INT
);
```

```
INSERT INTO movie VALUES
(21, 'interstellar', 'sci-fi', 250),
(22, 'grand hotel budapest', 'drama', 300),
(23, 'forest gump', 'sci-fi', 350);
UPDATE movie SET ticket_price = ticket_price + 50 WHERE genre = 'sci-fi';
SELECT * FROM movie;
```

Output:

Output:

```
+----------+----------------------+--------+--------------+
| movie_id | name                 | genre  | ticket_price |
+----------+----------------------+--------+--------------+
|       21 | interstellar         | sci-fi |          300 |
|       22 | grand_hotel_budapest | drama  |          300 |
|       23 | forest_gump          | sci-fi |          400 |
+----------+----------------------+--------+--------------+
```

Practical 5.

```
CREATE TABLE driver (
driver_id INT PRIMARY KEY,
name VARCHAR(50),
vehicle_no VARCHAR(20),
rating INT
);
INSERT INTO driver VALUES
(1, 'anjali', 'ka-01-1234', 6),
(2, 'rahul', 'dl-02-5678', 7);
UPDATE driver SET vehicle_no = 'ka-05-9999', rating = 5 WHERE driver_id = 1;
SELECT * FROM driver;
```

Output:

Output:

```
+-----------+--------+------------+--------+
| driver_id | name   | vehicle_no | rating |
+-----------+--------+------------+--------+
|         1 | anjali | ka-05-9999 |      5 |
|         2 | rahul  | dl-02-5678 |      7 |
+-----------+--------+------------+--------+
```

Practical 6.

```
CREATE TABLE inventory (
item_id INT PRIMARY KEY,
item_name VARCHAR(50),
quantity INT
);
INSERT INTO inventory VALUES
(12, 'mouser', 5),
(34, 'usb cable', 10),
(56, 'cpu', 15);
DELETE FROM inventory WHERE item_id = 34;
SELECT * FROM inventory;
```

Output:

Output:

```
+---------+-----------+----------+
| item_id | item_name | quantity |
+---------+-----------+----------+
|      12 | mouser    |        5 |
|      56 | cpu       |       15 |
+---------+-----------+----------+
```

Practical 7.

```
CREATE TABLE train (
train_no INT PRIMARY KEY,
name VARCHAR(50),
seats_left INT
);
INSERT INTO train VALUES
(1201, 'shatabdi', 0),
(1202, 'rajdhani', 45),
(1203, 'garib rath', 0);
DELETE FROM train WHERE seats_left = 0;
SELECT * FROM train;
```

Output:

Output:

```
+----------+----------+------------+
| train_no | name     | seats_left |
+----------+----------+------------+
|     1202 | rajdhani |         45 |
+----------+----------+------------+
```

Practical 8.

```
CREATE TABLE temp_cart (
cart_id INT PRIMARY KEY,
item_name VARCHAR(50),
price INT
);
INSERT INTO temp_cart VALUES
(1, 'chips', 20),
(2, 'coke', 40);
DELETE FROM temp_cart;
SELECT * FROM temp_cart;
```

Output:

Output:

```
Program did not output anything!
```