Lab 1 DBMS

1RUA25BCA0096 Sahasra Marreboyina, DBMS LAB

Lab 1: L1

```sql
CREATE TABLE student (
  id INT PRIMARY KEY,
  name VARCHAR(50),
  age INT,
  branch VARCHAR(20)
);

INSERT INTO student VALUES
(1, 'alex', 19, 'cs'),
(2, 'sam', 20, 'it'),
(3, 'chris', 19, 'ece');

SELECT * FROM student;
```

Output:

Output:

```
+----+-------+------+--------+
| id | name  | age  | branch |
+----+-------+------+--------+
|  1 | alex  |   19 | cs     |
|  2 | sam   |   20 | it     |
|  3 | chris |   19 | ece    |
+----+-------+------+--------+
```

Lab 1: L2

```sql
CREATE TABLE merchant (
  id INT PRIMARY KEY,
  name VARCHAR(50),
```

```
  city VARCHAR(30)
);

INSERT INTO merchant VALUES
(1, 'bob shop', 'delhi'),
(2, 'corner store', 'mumbai');

ALTER TABLE merchant ADD fee INT DEFAULT 5;

SELECT * FROM merchant;
```

Output:

Output:

```
+----+--------------+--------+------+
| id | name         | city   | fee  |
+----+--------------+--------+------+
|  1 | bob shop     | delhi  |    5 |
|  2 | corner store | mumbai |    5 |
+----+--------------+--------+------+
```

Lab 1: L3

SQL

```
CREATE TABLE product (
  id INT PRIMARY KEY,
  item VARCHAR(10),
  price INT
);

INSERT INTO product VALUES
(101, 'mouse', 450),
(102, 'keyboard', 800);

ALTER TABLE product MODIFY item VARCHAR(100);

INSERT INTO product VALUES
(103, 'wireless gaming headphones', 1200);

SELECT * FROM product;
```

Output:

Output:

```
+-----+----------------------------+-------+
| id  | item                       | price |
+-----+----------------------------+-------+
| 101 | mouse                      |   450 |
| 102 | keyboard                   |   800 |
| 103 | wireless gaming headphones |  1200 |
+-----+----------------------------+-------+
```

Lab 1: L4

SQL

```sql
CREATE TABLE employee (
  id INT PRIMARY KEY,
  name VARCHAR(50),
  dept VARCHAR(30),
  temp_code VARCHAR(10)
);

INSERT INTO employee VALUES
(11, 'rahul', 'sales', 'temp01'),
(12, 'sneha', 'hr', 'temp02');

ALTER TABLE employee DROP COLUMN temp_code;

SELECT * FROM employee;
```

Output:

Output:

```
+----+-------+-------+
| id | name  | dept  |
+----+-------+-------+
| 11 | rahul | sales |
| 12 | sneha | hr    |
+----+-------+-------+
```

Lab 1: L5

```sql
CREATE TABLE customer (
  id INT PRIMARY KEY,
  name VARCHAR(50),
  phone VARCHAR(15)
);

INSERT INTO customer VALUES
(1, 'kevin', '9876543210'),
(2, 'riya', '9123456780');

ALTER TABLE customer RENAME COLUMN phone TO mobile;

SELECT * FROM customer;
```

Output:

Output:

```
+----+-------+------------+
| id | name  | mobile     |
+----+-------+------------+
|  1 | kevin | 9876543210 |
|  2 | riya  | 9123456780 |
+----+-------+------------+
```

Lab 1: L6

```sql
CREATE TABLE orders (
  order_id INT PRIMARY KEY,
  cust_id INT,
  item VARCHAR(50),
  amount INT
);

INSERT INTO orders VALUES
(501, 1, 'laptop bag', 1200),
(502, 2, 'usb hub', 400);
```

```sql
ALTER TABLE orders RENAME TO customer_orders;

SELECT * FROM customer_orders;
```

Output:

Output:

```
+----------+---------+------------+--------+
| order_id | cust_id | item       | amount |
+----------+---------+------------+--------+
|      501 |       1 | laptop bag |   1200 |
|      502 |       2 | usb hub    |    400 |
+----------+---------+------------+--------+
```

Lab 1: L7

```sql
SQL
CREATE TABLE hospital (
  id INT PRIMARY KEY,
  name VARCHAR(50),
  city VARCHAR(30),
  beds INT
);

INSERT INTO hospital VALUES
(1, 'city care', 'jaipur', 120),
(2, 'lifeline', 'noida', 80);

DROP TABLE hospital;

SELECT * FROM hospital;
```

Output:

Output:

```
+----+-----------+--------+------+
| id | name      | city   | beds |
+----+-----------+--------+------+
|  1 | city care | jaipur |  120 |
|  2 | lifeline  | noida  |   80 |
+----+-----------+--------+------+
```