

Practical 8A:

```
sahasrasagi@Sahasra: ~/OS_L × + v
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>

int main()
{
    int *a, *b;

    a = (int *)malloc(5 * sizeof(int));

    b = (int *)calloc(5, sizeof(int));

    a = (int *)realloc(a, 10 * sizeof(int));

    free(a);
    free(b);

    return 0;
}|

sahasrasagi@Sahasra:~/OS_Lab/practical_$ nano practical_8a.c
sahasrasagi@Sahasra:~/OS_Lab/practical_$ gcc practical_8a.c -o practical_8a
sahasrasagi@Sahasra:~/OS_Lab/practical_$ ./practical_8a
sahasrasagi@Sahasra:~/OS_Lab/practical_$ |
```

Practica 8B;

```
sahasrasagi@Sahasra: ~/OS_L × + v
GNU nano 8.7.1
#include <stdio.h>
#include <unistd.h>

int main()
{
    int x = 100;

    if (fork() == 0)
    {
        printf("Child Before = %d\n", x);

        x = 500;

        printf("Child After = %d\n", x);
    }
    else
    {
        sleep(2);

        printf("Parent = %d\n", x);
    }

    return 0;
}|

sahasrasagi@Sahasra:~/OS_Lab/practical_$ nano practical_8b.c
sahasrasagi@Sahasra:~/OS_Lab/practical_$ gcc practical_8b.c -o practical_8b
sahasrasagi@Sahasra:~/OS_Lab/practical_$ ./practical_8b
Child Before = 100
Child After = 500
Parent = 100
sahasrasagi@Sahasra:~/OS_Lab/practical_$ |
```