Status	Finished
Started	Tuesday, 20 October 2026, 12:43 PM
Completed	Tuesday, 20 October 2026, 12:46 PM
Duration	2 mins 35 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open(file = “c:\\scores.txt”, “w”)

b. outfile = open(“c:\\scores.txt”, “a”) ✓

c. outfile = open(“c:\\scores.txt”, “rw”)

d. outfile = open(file = “c:\scores.txt”, “w”)

The correct answer is:
outfile = open(“c:\\scores.txt”, “a”)

Question **2**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. The operation is ignored

b. An empty file object is returned

c. A new file is created

d. An error is raised ✓

The correct answer is: An error is raised

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. Text file

b. Both text and binary file ✓

c. Binary file

d. none of the given choices

The correct answer is: Both text and binary file

Question **4**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters ahead from the current position ✓

b. moves the file pointer to the end of a file

c. move the file pointer five characters behind from the current position

d. move the file pointer to beginning of the file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **5**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of single characters

b. a list of lines ✓

c. a list of integers

d. str

The correct answer is:
a list of lines

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

- a. tell() ✓
- b. position()
- c. current()
- d. locate()

The correct answer is: tell()

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

- a. close() ✓
- b. finish()
- c. end()
- d. terminate()

The correct answer is: close()

Question **8**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

- a. 2
- b. null
- c. 0 ✓
- d. garbage
- e. 1

The correct answer is:
0

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

- a. r+ ✓
- b. r
- c. w
- d. a

The correct answer is: r+

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

- a. read(1)
- b. readline() ✓
- c. line()
- d. readlines(1)

The correct answer is: readline()

Question **11**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

- a. Read ✓
- b. Binary
- c. Write
- d. Append

The correct answer is: Read

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

- a. readline(size)
- b. readline() ✓
- c. read()
- d. readlines()

The correct answer is: readline()

Question **13**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

- a. It appends data to the file
- b. It does nothing
- c. It clears the old data and starts fresh ✓
- d. It raises an error

The correct answer is: It clears the old data and starts fresh

Question **14**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
f = open("data.txt", "a")
f.write("Adding new data\n")
f.close()
```

- a. Appends "Adding new data" to the end of the file ✓
- b. Overwrites the file with "Adding new data"
- c. Raises an error because the file is opened in append mode
- d. Opens the file in read mode

The correct answer is: Appends "Adding new data" to the end of the file

Question **15**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. Move file pointer five characters ahead from the beginning

b.
- Move file pointer five characters ahead from the current position. ✓

c.
- Move file pointer five characters behind from the current position.

d.
- Move file pointer five characters behind ahead from the end of a file.

The correct answer is:

- Move file pointer five characters ahead from the current position.