

Assignment 2

1) The “htags1” program is designed to parse HTML-like tags from input and print them with their content, excluding any comments within. It uses a simple algorithm to achieve this. Upon encountering a '<' character, it begins reading characters into a buffer (tag) until it finds '>'. While reading, it ignores any characters if it's inside a comment (inside_comment flag). Once it reads the complete tag, it prints it along with its content. The data structure used is a character array (tag) to store the tag being parsed. The algorithm relies on a loop that continuously reads characters until the end of the input stream is reached.

2)

```
/**
 *author Saheb Singh Arora
 *Student id: 3742233
 */
#include <stdio.h>

void printArr(char arr[], int size) {
    for (int i = 0; i < size; i++) {
        putchar(arr[i]);
    }
}

int main() {
    int c;
    int inside_comment = 0;
    char tag[100];

    while ((c = getchar()) != EOF) {
        if (c == '<') {
            int i = 0;
            tag[i++] = c;
            while ((c = getchar()) != EOF && c != '>') {
                if (!(inside_comment)) {
                }
                tag[i++] = c;
            }
            if (!inside_comment) {
                printArr(tag, i);
                putchar('>');
                putchar('\n');
            }
        }
    }
}
```

```

    return 0;
}

```

3) The “htext1” program, designed by Saheb Singh Arora, is a simple utility to strip HTML tags and comments from an input stream. It operates by iterating through each character of the input, maintaining boolean flags (`insideTag` and `insideComment`) to track whether it's currently within an HTML tag or comment. When encountering a '<' character, it distinguishes between the start of a comment or a tag; if it's a comment, it continues reading until it finds the end marker '-->'. If it's a tag, it skips reading until the closing '>'. Characters outside of tags and comments are then outputted, effectively providing a plain text representation of the input. This algorithmic approach doesn't require complex data structures, relying instead on simple flags and character iteration.

```

4)
/**
 * @author Saheb Singh Arora
 * Student id: 3742233
 */
#include <stdio.h>
#include <stdbool.h>

int main() {
    int character;
    bool insideTag = false;
    bool insideComment = false;

    for (; ;) {
        character = getchar();
        if (character == EOF)
            break;

        if (character == '<') {
            insideTag = true;
            if ((character = getchar()) == '!') {
                if ((character = getchar()) == '-' && (character
= getchar()) == '-') {
                    insideComment = true;
                    insideTag = false;
                    continue;
                } else {


```

```

        ungetc(character, stdin);
        character = '<';
    }
} else {
    ungetc(character, stdin);
    continue;
}
}
if (character == '>') {
    if (insideComment) {
        insideComment = false;
    } else {
        insideTag = false;
    }
    continue;
}
if (!insideTag && !insideComment) {
    putchar(character);
}
}
return 0;
}

```

5)



A terminal window titled "Assignment2 — -zsh — 80x24" is shown. The prompt is "sahebsa@Sahebs-MacBook-Air Assignment2 %". The user enters the command "gcc htags1.c -o htags1", followed by ". ./htags1 < input.html". The output of the program is displayed: "<html>", "", "", and "</html>". The prompt returns to "sahebsa@Sahebs-MacBook-Air Assignment2 %".

```

[sahebsa@Sahebs-MacBook-Air Assignment2 % gcc htags1.c -o htags1
[sahebsa@Sahebs-MacBook-Air Assignment2 % . ./htags1 < input.html
<html>
<b>
</b>
</html>
sahebsa@Sahebs-MacBook-Air Assignment2 %

```

```
Assignment2 — -zsh — 80x24
[sahebsa@Sahebs-MacBook-Air Assignment2 % gcc htext1.c -o htext1
[sahebsa@Sahebs-MacBook-Air Assignment2 % ./htext1 < input.html
dddddTEST
sahebsa@Sahebs-MacBook-Air Assignment2 %
```

6)

```
sahebsa@Sahebs-MacBook-Air Assignment2 % gcc htags1.c -o htags1
sahebsa@Sahebs-MacBook-Air Assignment2 % ./htags1 < input.html
<html>
<b>
</b>
</html>
sahebsa@Sahebs-MacBook-Air Assignment2 % gcc htags1.c -o htags1
sahebsa@Sahebs-MacBook-Air Assignment2 % ./htags1 < A2W2024.html
<html>
<head>
<meta http-equiv=Content-Type content="text/html; charset=unicode">
<meta name=Generator content="Microsoft Word 15 (filtered)">
<style>
<!--
/* Font Definitions */
@font-face
{font-family:"Cambria Math";
panose-1:2 4 5 3 5 4 6 3 2 4;}
@font-face
{font-family:Calibri;
panose-1:2 15 5 2 2 2 4 3 2 4;}
@font-face
{font-family:Times;
panose-1:0 0 5 0 0 0 0 2 0 0;}
/* Style Definitions */
p.MsoNormal, li.MsoNormal, div.MsoNormal
{margin:0cm;
font-size:12.0pt;
font-family:Times;}
p.MsoBodyTextIndent, li.MsoBodyTextIndent, div.MsoBodyTextIndent
{mso-style-link:"Body Text Indent Char";
margin-top:0cm;
margin-right:0cm;
margin-bottom:0cm;
margin-left:1.0cm;
text-indent:1.0cm;
font-size:12.0pt;
font-family:Times;}
a:link, span.MsoHyperlink
{color:blue;
text-decoration:underline;}
span.BodyTextIndentChar
{mso-style-name:"Body Text Indent Char";
mso-style-link:"Body Text Indent";
font-family:Times;}
.MsoChpDefault
{font-size:10.0pt;
font-family:"Calibri",sans-serif;}
@page WordSection1
{size:612.0pt 792.0pt;
margin:72.0pt 90.0pt 72.0pt 90.0pt;}
div.WordSection1
{page:WordSection1;}
-->
</style>
</head>
<body lang=EN-CA link=blue vlink=purple style='word-wrap:break-word'>
```

```

</style>
</head>
<body lang=EN-CA link=blue vlink=purple style='word-wrap:break-word'>
<div class=WordSection1>
<p class=MsoNormal>
<b>
<span lang=EN-US style='font-size:14.0pt;font-family:
"Times New Roman",serif'>
</span>
</b>
</p>
<p class=MsoNormal>
<b>
<span lang=EN-US style='font-size:14.0pt;font-family:
"Times New Roman",serif'>
</span>
</b>
</p>
<p class=MsoNormal>
<b>
<span lang=EN-US style='font-size:14.0pt;font-family:
"Times New Roman",serif'>
</span>
</b>
</p>
<p class=MsoNormal style='text-align:justify'>
<span lang=EN-US
style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoNormal>
<u>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
<b>
</b>
</span>
</u>
</p>
<p class=MsoNormal>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoNormal>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
<a href="https://www.educba.com/types-of-tags-in-html/">
<span
style='text-decoration:none'>
</span>
</a>
</span>
</p>
<p class=MsoNormal>
<span style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:0cm;margin-bottom:.0001pt;text-indent:0cm;line-height:12.0pt'>

```

```

</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:0cm;margin-bottom:.0001pt;text-indent:0cm;line-height:12.0pt'>
<i>
<span
style='font-family:"Times New Roman",serif'>
</span>
</i>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:7.1pt;margin-bottom:.0001pt;text-indent:0cm;line-height:12.0pt'>
<span
lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span
lang=EN-US style='font-family:"Courier New"'>
</span>
<span lang=EN-US
style='font-family:"Times New Roman",serif'>
<b>
</b>
</span>
<span lang=EN-US style='font-family:"Courier New"'>
</span>
<span
lang=EN-US style='font-family:"Times New Roman",serif'>
<a
href="https://linuxcommand.org/lc3_lts0070.php">
</a>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:7.1pt;margin-bottom:.0001pt;text-indent:18.0pt;line-height:
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:25.1pt;margin-bottom:.0001pt;text-indent:18.0pt;line-height:
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
<br>
<br>
<br>
<br>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:25.1pt;margin-bottom:.0001pt;text-indent:18.0pt;line-height:
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
<br>
<br>
<br>
<br>
</span>
</p>

```

```
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
<br>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:7.1pt;margin-bottom:.0001pt;text-indent:0cm;line-height:12.0pt'>
<span
lang=EN-US style='font-family:"Times New Roman",serif'>
<br>
<br>
<br>
</span>
<b>
<span lang=EN-US
style='font-family:"Courier New"'>
</span>
</b>
<span lang=EN-US
style='font-family:"Times New Roman",serif'>
<b>
<span lang=EN-US style='font-family:"Courier New"'>
</span>
</b>
</span>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
<b>
<span lang=EN-US style='font-family:"Courier New"'>
</span>
</b>
</span>
lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Courier New"'>
</span>
</span>
</span>
```

```
<span lang=EN-US style='font-family:"Courier New"'>
</span>
</b>
<span
lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<b>
<span lang=EN-US style='font-family:"Courier New"'>
</span>
</b>
<span
lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Courier New"'>
</span>
<span
lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<p>
< class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span
lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
< class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span
lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
</span>
</p>
< class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:
12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span
lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
</span>
</p>
< class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:
0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:
12.0pt'>
```

```

<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
<u>
</u>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:12.0pt;margin-left:43.1pt;text-indent:-18.0pt;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
<br>
<br>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;text-indent:0cm;line-height:

```

```

<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
<br>
<br>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;margin-right:0cm;margin-bottom:0cm;margin-left:43.1pt;margin-bottom:.0001pt;text-indent:-18.0pt;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-size:7.0pt;font-family:"Times New Roman",serif'>
</span>
<span style='font-family:"Times New Roman",serif'>
</span>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;text-indent:0cm;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoBodyTextIndent style='margin-top:6.0pt;text-indent:0cm;line-height:12.0pt'>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
<p class=MsoNormal>
<span lang=EN-US style='font-family:"Times New Roman",serif'>
</span>
</p>
</div>
</body>
</html>
zsh: abort      ./htags1 < A2W2024.html
sahebsa@Sahebs-MacBook-Air Assignment2 %

```


8

3. In a few sentences describe the design of the htext1 program. Focus on the description of

