

RECENT SCANS

STATIC ANALYZER

DYNAMIC ANALYZER

API

DONATE

DOCS

ABOUT

Search

APP SCORES

Security Score

36/100

Testers Detecting

0/432

MobSF Scorecard

FILE INFORMATION

File Name

DivApplication.apk

Size

1.43MB

MD5

52ab8b2193b3cfc1c737e3a786be363a

SHA1

27e849d9d7b86a3a3357fb3e980433a91d416801

SHA256

Scelfc51fce9bd760b92ab2340477f4d6a8454ae6c5d04a8c9493e4fe34fab7c5

APP INFORMATION

App Name

Div

Package Name

jakhar.aseem.diva

Main Activity

jakhar.aseem.diva.MainActivity

Target SDK

23

Min SDK

15

Max SDK

Android Version Name

1.0

Android Version Code

1

2 / 17

EXPORTED ACTIVITIES

View All

0 / 0

EXPORTED SERVICES

View All

0 / 0

EXPORTED RECEIVERS

View All

1 / 1

EXPORTED PROVIDERS

View All

SCAN OPTIONS

Rescan

Manage Suppressions

Start Dynamic Analysis

Scan Logs

DECOMPILED CODE

View AndroidManifest.xml

View Source

View Smali

Download Java Code

Download Smali Code

Download APK

SIGNER CERTIFICATE

Binary is signed

v1 signature: True

v2 signature: False

v3 signature: False

v4 signature: False

X.509 Subject: C=US, O=Android, CN=Android Debug

Signature Algorithm: rsassa_pkcs1v15

Valid From: 2015-11-02 00:32:11+00:00

Valid To: 2045-10-25 00:32:11+00:00

Issuer: C=US, O=Android, CN=Android Debug

Serial Number: 0x218330df

Hash Algorithm: sha256

MD5: 0b20162ac34ee974d7f63a1862e7eadf

SHA1: ae4ead5aeb4e9e4fc928e7c777f6459f008031

SHA256: 35d7f7ad35dfb826b78fa4b773187ed478540e32c8b8c5653b80568029fc05840

SHA512: e93616958593a7a248e393db296b2101432de5b07c3d7e2bdc8070dc0b58277b46e443eff373004f5a25b61f78c9078f54cc325cb86c17160b0bae13148d1e

Found 1 unique certificates

APPLICATION PERMISSIONS

Search:

PERMISSION	STATUS	INFO	DESCRIPTION	CODE MAPPINGS
android.permission.INTERNET	Normal	full Internet access	Allows an application to create network sockets.	
android.permission.READ_EXTERNAL_STORAGE	Dangerous	read external storage contents	Allows an application to read from external storage.	
android.permission.WRITE_EXTERNAL_STORAGE	Dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.	

Showing 1 to 3 of 3 entries

Previous1Next

ANDROID API

Search:

API	FILES
Content Provider	Show Files
Inter Process Communication	Show Files
Loading Native Code (Shared Library)	Show Files
Local File I/O Operations	Show Files
Starting Activity	Show Files

Showing 1 to 5 of 5 entries

Previous1Next

BROWSABLE ACTIVITIES

Search:

ACTIVITY	INTENT
No data available in table	

Showing 0 to 0 of 0 entries

PreviousNext

NETWORK SECURITY

Search:

NO	SCOPE	SEVERITY	DESCRIPTION
No data available in table			

Showing 0 to 0 of 0 entries

PreviousNext

CERTIFICATE ANALYSIS

HIGH

2

WARNING

0

INFO

1

Search:

TITLE	SEVERITY	DESCRIPTION
Application signed with debug certificate	High	Application signed with a debug certificate. Production application must not be shipped with a debug certificate.
Application vulnerable to Janus Vulnerability	High	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.
Signed Application	Info	Application is signed with a code signing certificate

				Canaries: Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Canaries: Not applicable for Dart/Flutter libraries unless Dart FFI is used.				
4	armeabi-v7a/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False High This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.
5	x86/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True Info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.
6	armeabi/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False High This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.
7	arm64-v8a/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False High This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.
8	x86_64/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False High This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.
9	mips/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False High This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.
10	mips64/libdivajni.so Q Analyzer	False High The binary does not have NX bit set. NX bit offer protection against exploitation of memory corruption vulnerabilities by marking memory page as non-executable. Use option --noexecstack or -z noexecstack to mark stack as non executable.	Dynamic Shared Object (DSO) Info The shared object is build with -PIE flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False High This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO Info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None Info The binary does not have run-time search path or RPATH set.	None Info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True Info Symbols are stripped.

Previous 1 2 Next

5/5

Search:

Showing 0 to 0 of 0 entries

Previous Next

Search:

Showing 0 to 0 of 0 entries

Previous Next

Search:

Showing 0 to 0 of 0 entries

Previous Next

 VirusTotal Report

Triage Report

MetaDefender Report

Hybrid Analysis Report

Search:

Showing 1 to 1 of 1 entries

Previous 1 Next

Search: Showing 1 to 1 of 1 entries

Previous 1 Next

Top Malware Permissions

3/25

5 Other Common Permissions

0/44

```
android.permission.WRITE_EXTERNAL_STORAGE,  
android.permission.READ_EXTERNAL_STORAGE, android.permission.INTERNET
```

Malware Permissions are the top permissions that are widely abused by known malware.
Other Common Permissions are permissions that are commonly abused by known malware.

This app may communicate with the following OFAC sanctioned list of countries.

5/5

Search:

Showing 0 to 0 of 0 entries

Question	Mark
----------	------

🔍 DOMAIN MALWARE CHECK



Search:

DOMAIN	STATUS	GEOLOCATION
payatu.com	ok	IP: 104.26.10.237 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

Showing 1 to 1 of 1 entries

Previous **1** Next

🔗 URLS



Search:

URL	FILE
http://payatu.com	jakhar/aseem/diva/APICreds2Activity.java

Showing 1 to 1 of 1 entries

Previous **1** Next

✉ EMAILS

🕵 TRACKERS



Search:

TRACKER NAME	CATEGORIES	URL
No data available in table		

Showing 0 to 0 of 0 entries

Previous Next

🔑 POSSIBLE HARDCODED SECRETS

▼ Showing all 1 secrets
"pkey": "notespin"

🔤 STRINGS

From APK Resource

► Show all 1281 strings

From Code

► Show all 1242 strings

From Shared Objects

apktool_out/lib/x86_64/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

apktool_out/lib/mips/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

apktool_out/lib/mips64/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

apktool_out/lib/armeabi-v7a/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

apktool_out/lib/x86/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

apktool_out/lib/armeabi/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

apktool_out/lib/arm64-v8a/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

lib/x86_64/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

lib/mips/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

lib/mips64/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

lib/armeabi-v7a/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

lib/x86/libdivajni.so

▼ Showing all 2 strings
.dotdot

AAAAAAAA
olsdfgad;lh

lib/arm64-v8a/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

lib/arm64-v8a/libdivajni.so

▼ Showing all 2 strings
.dotdot
olsdfgad;lh

ACTIVITIES

▼ Showing all 17 activities
jakhar.aseem.diva.MainActivity
jakhar.aseem.diva.LogActivity
jakhar.aseem.diva.HardcodeActivity
jakhar.aseem.diva.InsecureDataStorage1Activity
jakhar.aseem.diva.InsecureDataStorage2Activity
jakhar.aseem.diva.InsecureDataStorage3Activity
jakhar.aseem.diva.InsecureDataStorage4Activity
jakhar.aseem.diva.SQLInjectionActivity
jakhar.aseem.diva.InputValidation2URISchemeActivity
jakhar.aseem.diva.AccessControl1Activity
jakhar.aseem.diva.APICredsActivity
jakhar.aseem.diva.AccessControl2Activity
jakhar.aseem.diva.APICreds2Activity
jakhar.aseem.diva.AccessControl3Activity
jakhar.aseem.diva.Hardcode2Activity
jakhar.aseem.diva.AccessControl3NotesActivity
jakhar.aseem.diva.InputValidation3Activity

SERVICES

RECEIVERS

PROVIDERS

▼ Showing all 1 providers
jakhar.aseem.diva.NotesProvider

LIBRARIES

SBOM

▼ Showing all 1 Packages
jakhar.aseem.diva

FILES

► Show all 390 files

