

AYUSHMAN BHARAT DIGITAL MISSION

[Update Email Address in Healthcare Professional Registry \(HPR\) via APIs](#)

Table of Contents

A. TerminolTokenogy	3
B. Get HPR Token	6
1. Login Via Password	6
2. Login Via Mobile	7
3. Login Via Aadhaar	10
C. Generate Verification Email OTP	12
D. Re-Generate Verification Email OTP	13
E. Verify Email OTP	14

A. Terminology:

- ABDM - Ayushman Bharat Digital Mission
- **Authorization token** - To obtain, the HRP can call 'sessions API' along with the received ClientID and Client Secret. Same must be used in header for other APIs.
- **Client ID** - Post internal approval, Integrator will receive Client ID to access ABDM APIs
- **Client Secret** - Post internal approval, Integrator will receive Client Secret to access ABDM APIs
- HPRID — Healthcare Professional ID
- Sandbox - Sandbox is a framework that will allow technologies or products to be tested in the contained environment in compliance with ABDM standards.

Verify Email Address Via API for registered health professionals-

Below document explains how to update professional's details in HPR systems using APIs.

List of APIs for Upload document in HPR

1	HPRID Gateway Token
2	Get HPR Token
3	Generate Verification Email-OTP
4	Re-Generate Verification Email-OTP
5	Verify Email-OTP

Step 1. HPRIID Gateway Token

Authentication Token need be generated using client ID and client Secret.

To obtain clientId and clientsecret, please register on [Sandbox Application](#).

Headers

REQUEST-ID :

Unique UUID for tracking the end-to-end unique transaction.

Code example: java

<https://www.uuidgenerator.net/dev-corner/java>

TIMESTAMP:

The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds

X-CM-ID :

This value depends on the environment where API is getting executed.

Eg. SBX or PROD.

For SBX- sbx and for PROD- abdm

Method	POST
URL	https://dev.abdm.gov.in/api/hiecm/gateway/v3/sessions
Request Body	<pre>{ "clientId": "*****", "clientSecret": "3***bf3b-d**d-47a2-be2f-10d*****1d9", "grantType": "client_credentials" }</pre>

Response – Previously generated Transaction ID will be returned in the response

Sample Response :


```
{
  "token": "eyJhbGciOiJSUzUxMiJpYWRqaLaE_3FNwvK1Tu8LUuP5rKs27ssssssadassssssssssssssssssZfq-
HToaqcaV9O3ztFE9b4mPulaC3hxUHYLV82bys8roYfv5ICcbqkp4xsBBuWrRQAsrQii7Rk-SsssssssssssssoR-
wfpAJ9uE8Ap_51Ww0ZTTEZ89Cvlum2p3DaM87jm02TiFLCFb26UitRdRK5H-pj8dHyeXNXO8M6Nt-g",
  "expiresIn": 1739713114,
  "refreshToken": null,
  "refreshExpiresIn": 0
}
```

II. Login Via Mobile OTP

Users need to follow the following steps to get HPR token

- 1 [Send OTP](#)
- 2 [Get Public Certificate](#)
- 3 [HPRID Verify OTP](#)
- 4 [Login with HPRID](#)

1. Send OTP

Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://apihpsbx.abdm.gov.in/v4/int/api/v2/auth/loginViaMobileSendOTP
Request Body	<pre>{ "mobile": "9900005000" }</pre>

Sample Response

```
{
  "txnId": "3dba94dd-92d9-494f-9567-ca71e86c0c2d",
  "mobileNumber": "*****5000"
}
```

2. Get Public Certificate

Users need to get public certificate to encrypt the OTP.

Method	Get
URL	https://apihspsbx.abdm.gov.in/v4/int/api/v1/auth/cert

Sample Response

```
-----BEGIN PUBLIC KEY-----
MIIBljANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA6avEoNMbZDtjs7RHc1Si
hYeLvGPYV76mh2ncU2FAyCkK3ubE/7UE2HkimL4ftAqFN3fcKv8430oV3gAuvrk/
5sIOoG8NOMrVflnakdFZyDae66MHVuc1Rzrv8fKDRFRz8UTa1S2xZ9uXRCieQCeB
xeHmDtgcyGDfQzqcTOLGCPu6tLWda/QhW7zeUpowgIIBknHf2nf916lsM1fWnO7
qVUBh6E3PXoLrW4NtvOWEMh3V62BNGzNmW3u8hxdp+uSe3Us/t4WFJRURnAhO5
IDAzojqkWYHkYZTDvidLBvfoX7ZbBPz03u42AOm/uDu4gG/oYqeB5zXe7qJ1ecLu SQIDAQAB
-----END PUBLIC KEY-----
```

3. HPRID verify OTP

After receiving public certificate user needs to encrypt OTP with the public key using RSA Encryption Algo RS512. RSA Encryption to encrypt the data. Cipher Type - RSA/ECB/PKCS1Padding. online tool to encrypt data [click here](#)

Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://apihspsbx.abdm.gov.in/v4/int/api/v2/auth/loginViaMobileSendOTP
Request Body	<pre>{ "txnId": "4c8c4b29-6d7e-4446-8f73-4574d6d14f09", "otp": "M9OCYu/fxGibo/9rCVf0jvE7VDXxVDy2fdXhUHpi97GZp8R9VpBpSJ92C2WRBm46kH3m1tu2TB99gJv VFo0mSpmQ71J501YwbHtT3KLEPc47ytd5zu47eX- TvIaFjFDSl/CvFaiCCS3bU3hBZyGxxvg5lndrR4jo2MUTVsqr4F+We3UDbaE9Ux- gcEO719grzSPlcEtK- CRRFhQZFhrb3iF1e5vCKqWNkPgYbqJasDDY2LL5wtL5NbL7ZBSJTayC6lM8lcrGAlmKGpjE/qy4ucA5t jmlvAvgggZk/mCvlofJWiafCvGolnZHcZVZSfxoZFxlEaaxgKn1RAXclU6XiMEymw==" //"mobile": "97624XXXXX" }</pre>
Sample Response	
<pre>{ "txnId": "fc6d879c-e535-4ff1-9443-5dc6031efcc1", "mobileLinkedHpIdDTO": [{</pre>	

```

        "hprIdNumber": "00-0000-0326-3829",
        "name": "Test",
        "hprId": "test@hpr.abdm"
    }
]
}

```

4. Login with HPRID

Users need to pass hprIdNumber and txnId received in the HPRID verify OTP Api. Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://apihpsbx.abdm.gov.in/v4/int/api/v2/auth/login/userAuthorizedToken
Request Body	<pre> { "hpId": "71-6347-4142-2778", "txnId": "9d130a33-5a9a-4cea-8e47-f9d1b8916329" } </pre>
	<pre> { "token": "eyJhbGciOiJSUzUxMiJ9.eyJocHJZE51bWJlciI6IjcxLTYzNDctNDE0Mi0yNzc4IiwibW9iaWxlIjoiOTk1MzkwNTg2MCIsc2Zf_ttuCMi-jadNJVWnQUnXnJzt3MRezdZuYdv6cTsqmzV4LgijTQ_mshaPYUx7GvLsCszZLgaBCWrl-KFgps85rWgnNNFa6JXExp1UjAms-Im2UxxB0LbZ0vPddXIKh3JWg", "expiresIn": 1739456384, "refreshToken": null, "refreshExpiresIn": null } </pre>

III. Login Via Aadhaar

For login via Aadhaar OTP you need to follow the following steps.

1.	Send OTP
2.	Verify OTP

1. Send OTP

Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://apihspsbx.abdm.gov.in/v4/int/api/v1/auth/init
Request Body	<pre>{ "idType": "hpr_id", "domainName": "@hpr.abdm", "authMethod": "AADHAAR OTP", "hprId": "71-6347-4142-2778" }</pre>

Sample Response

<pre>{ "transactionId": "d4f16edb-2f69-4032-8803-bb6a8fc6e01c", "mobileNumber": "*****5860" }</pre>

2. Verify OTP

Users need to input otp and txnId from above API Send Aadhaar OTP.

Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://apihspsbx.abdm.gov.in/v4/int/api/v1/auth/confirmWithAadhaarOtp
Request Body	<pre>{ "otp": "350991", "txnId": "d4f16edb-2f69-4032-8803-bb6a8fc6e01c" }</pre>
Response Body	
<pre>{ "token": "eyJhbGciOiJSUzUxMiJ9pdcGj5g20EZ-fnOsZ7hVoCrk8cJLe02f3BDuVm_ks7YATADPJ7lLYsfC-4Zk77BywdpXzVKBHqypYugElsAxaY2wu9rw2wwSqIAge6xEwAKe7fpQnNQzLLFZ97tHM501sqzwW2WaQYTXhMsxxEs7su0QoUhWT1UOuK6R_corac1-G00LqhBIimWx9_-A5uaAVwoFP81fLm15OLs8CI7nuA8siqpCtnOt0ZYpVGbIEdyYrswieuyRg", "expiresIn": 1739715555, "refreshToken": null, }</pre>	

```
"refreshExpiresIn": null  
}
```

C. Generate Email-OTP

In this API's system will send an OTP to user input email address to verify user identity. Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://apihpsbx.abdm.gov.in/v4/int/apis/v1/doctors/generate-verification-email
Request Body	<pre>{ "hpr_token": "eyJhbGciOiJSUzUxMiJx6FiWI81whDIrTa9Vq8F2ItvE7SVzKeZrJAat-TiCscze5DbSczAAFrMJHpgxA0mcq8luPb5F-425PEc3nVZqEJXPy-IBxe5VDrXe6NFZaI6jC742XTWoz6Xlw3r7JCNTFC7NRoKAR1fGCK-x8MN_7aA6MByHsinC4rVvEsg", "emailAddress": "kapil.saraswat992@gmail.com", "otp_type": "official" }</pre>

Sample Response

```
{  
  "msg": "Mail sent successfully",  
  "status": "success",  
  "otpLimitExp": null,  
  "expTime": null  
}
```

Request body parameters

Field Name	Mandatory	Datatype	Size	Comments
emailAddress	Yes	Varchar		
otp_type	Yes	Varchar		

D. Re-Generate Email OTP

In this API's if user didn't receive an OTP after this user will use this api to regenerate OTP again for email verification.

Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	POST
URL	https://apihspsbx.abdm.gov.in/v4/int/apis/v1/doctors/resent-verify-email
Request	<pre>{ "hpr_token": "eyJhbGciOiJSUzUxMiJ9.eyJocHJJZE5lbWJlciI6IjcxLTZyNDct- NDE0Mi0yNzc4IiwibW9iaWxlIjoioTklMzkwNTg2MCIsIwckloia2FwaWxrdWlhcjNhcjZFd0QGH- wci5hYmRtIiwic3ViIjojNzEiBxe5VDrXe6NFZaI6jC742XTWoz6Xlw3r7JCNTFC7NRoKAR1fGck- x8MN_7aA6MByHsinC4rVvEsg", "emailAddress": "kapi*****2@gmail.com", "otp_type": "official" }</pre>

Sample Response
<pre>{ "emailAddress": "kap*****@gmail.com", "otp_type": "official" }</pre>

Request body parameters

Field Name	Mandatory	Data types	Size	Comments
emailAddress	Yes	String		
type	Yes	String		

E. Verify Email Address

In this API's user will update email address by input OTP along with other requested parameters mentioned

In the table explains API which user receive in Generate Email OTP and Re-Generate Email OTP.

Add the accessToken received from the HPRID Gateway Token API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	POST
URL	https://apihpsbx.abdm.gov.in/v4/int/apis/v1/doctors/verify-email-otp
Request Body	<pre>{ "hpr_token": "eyJhbGciOiJSUzUxMiJ6FiWI81whDlRta9Vq8F2ItvE7SVzKeZrJAat- TiCscze5DbSczAAFrMJHpgxA0mcq8luPb5F425PEc3nVZqEJIBxe5VDrXe6NFZaI6jC742XTWoz6Xlw3 r7JCNTFC7NRoKAR1fGCK-x8MN_7aA6MByHsinC4rVvEsg", "hpr_id": "71-6347-****-2778", "officialEmail": "Kapil*** @gmail.com", "emailOtp": 103913 }</pre>

Sample Response
<pre>{ "status": "pass", "msg": "Email Verified" }</pre>

Request body parameters.

Field Name	Mandatory	Data Types	Size	Comments
hpr_token	Yes	String		Token you receive from Get HPR Token
hpr_id	Yes	String		
officialEmail	Yes	String		
emailOTP	Yes	Number	6	