```
-- MySQL dump 10.13  Distrib 8.0.39, for Win64 (x86_64)
--
-- Host: localhost    Database: ms_crm
-- ------------------------------------------------------
-- Server version 8.0.39

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!50503 SET NAMES utf8mb4 */;
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
/*!40103 SET TIME_ZONE='+00:00' */;
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0 */;
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;

--
-- Table structure for table `auth_group`
--

DROP TABLE IF EXISTS `auth_group`;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `auth_group` (
  `id` int NOT NULL AUTO_INCREMENT,
  `name` varchar(150) NOT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `name` (`name`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `auth_group`
--

LOCK TABLES `auth_group` WRITE;
/*!40000 ALTER TABLE `auth_group` DISABLE KEYS */;
/*!40000 ALTER TABLE `auth_group` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `auth_group_permissions`
--

DROP TABLE IF EXISTS `auth_group_permissions`;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `auth_group_permissions` (
  `id` bigint NOT NULL AUTO_INCREMENT,
  `group_id` int NOT NULL,
  `permission_id` int NOT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `auth_group_permissions_group_id_permission_id_0cd325b0_uniq` (`group_id`,`permission_id`)
  KEY `auth_group_permissio_permission_id_84c5c92e_fk_auth_perm` (`permission_id`),
  CONSTRAINT `auth_group_permissio_permission_id_84c5c92e_fk_auth_perm` FOREIGN KEY (`permission_id`) R
  CONSTRAINT `auth_group_permissions_group_id_b120cbf9_fk_auth_group_id` FOREIGN KEY (`group_id`) REFER
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `auth_group_permissions`
--
```

```
LOCK TABLES ‘auth_group_permissions‘ WRITE;
/*!40000 ALTER TABLE ‘auth_group_permissions‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘auth_group_permissions‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘auth_permission‘
--

DROP TABLE IF EXISTS ‘auth_permission‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘auth_permission‘ (
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(255) NOT NULL,
  ‘content_type_id‘ int NOT NULL,
  ‘codename‘ varchar(100) NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘auth_permission_content_type_id_codename_01ab375a_uniq‘ (‘content_type_id‘,‘codename‘),
  CONSTRAINT ‘auth_permission_content_type_id_2f476e4b_fk_django_co‘ FOREIGN KEY (‘content_type_id‘) RE
) ENGINE=InnoDB AUTO_INCREMENT=669 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘auth_permission‘
--

LOCK TABLES ‘auth_permission‘ WRITE;
/*!40000 ALTER TABLE ‘auth_permission‘ DISABLE KEYS */;
INSERT INTO ‘auth_permission‘ VALUES (1,’Can add log entry’,1,’add_logentry’),(2,’Can change log entry’
/*!40000 ALTER TABLE ‘auth_permission‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘auth_user‘
--

DROP TABLE IF EXISTS ‘auth_user‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘auth_user‘ (
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘password‘ varchar(128) NOT NULL,
  ‘last_login‘ datetime(6) DEFAULT NULL,
  ‘is_superuser‘ tinyint(1) NOT NULL,
  ‘username‘ varchar(150) NOT NULL,
  ‘first_name‘ varchar(150) NOT NULL,
  ‘last_name‘ varchar(150) NOT NULL,
  ‘email‘ varchar(254) NOT NULL,
  ‘is_staff‘ tinyint(1) NOT NULL,
  ‘is_active‘ tinyint(1) NOT NULL,
  ‘date_joined‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘username‘ (‘username‘)
) ENGINE=InnoDB AUTO_INCREMENT=37 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘auth_user‘
--

LOCK TABLES ‘auth_user‘ WRITE;
```

```
/*!40000 ALTER TABLE ‘auth_user‘ DISABLE KEYS */;
INSERT INTO ‘auth_user‘ VALUES (1,’pbkdf2_sha256$1200000$x51udr2uON7FS3XwKGhhI4$VHrhYTUr/jovNHxJfwcAw6O
/*!40000 ALTER TABLE ‘auth_user‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘auth_user_groups‘
--

DROP TABLE IF EXISTS ‘auth_user_groups‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘auth_user_groups‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘user_id‘ int NOT NULL,
  ‘group_id‘ int NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘auth_user_groups_user_id_group_id_94350c0c_uniq‘ (‘user_id‘,‘group_id‘),
  KEY ‘auth_user_groups_group_id_97559544_fk_auth_group_id‘ (‘group_id‘),
  CONSTRAINT ‘auth_user_groups_group_id_97559544_fk_auth_group_id‘ FOREIGN KEY (‘group_id‘) REFERENCES
  CONSTRAINT ‘auth_user_groups_user_id_6a12ed8b_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFERENCES ‘au
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘auth_user_groups‘
--

LOCK TABLES ‘auth_user_groups‘ WRITE;
/*!40000 ALTER TABLE ‘auth_user_groups‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘auth_user_groups‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘auth_user_user_permissions‘
--

DROP TABLE IF EXISTS ‘auth_user_user_permissions‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘auth_user_user_permissions‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘user_id‘ int NOT NULL,
  ‘permission_id‘ int NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘auth_user_user_permissions_user_id_permission_id_14a6b632_uniq‘ (‘user_id‘,‘permission_id
  KEY ‘auth_user_user_permi_permission_id_1fbb5f2c_fk_auth_perm‘ (‘permission_id‘),
  CONSTRAINT ‘auth_user_user_permi_permission_id_1fbb5f2c_fk_auth_perm‘ FOREIGN KEY (‘permission_id‘) R
  CONSTRAINT ‘auth_user_user_permissions_user_id_a95ead1b_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘auth_user_user_permissions‘
--

LOCK TABLES ‘auth_user_user_permissions‘ WRITE;
/*!40000 ALTER TABLE ‘auth_user_user_permissions‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘auth_user_user_permissions‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘authtoken_token‘
```

```
--

DROP TABLE IF EXISTS ‘authtoken_token‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘authtoken_token‘ (
  ‘key‘ varchar(40) NOT NULL,
  ‘created‘ datetime(6) NOT NULL,
  ‘user_id‘ int NOT NULL,
  PRIMARY KEY (‘key‘),
  UNIQUE KEY ‘user_id‘ (‘user_id‘),
  CONSTRAINT ‘authtoken_token_user_id_35299eff_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFERENCES ‘aut
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘authtoken_token‘
--

LOCK TABLES ‘authtoken_token‘ WRITE;
/*!40000 ALTER TABLE ‘authtoken_token‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘authtoken_token‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_activity_log‘
--

DROP TABLE IF EXISTS ‘core_activity_log‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_activity_log‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘description‘ longtext NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘user_id‘ int DEFAULT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_activity_log_user_id_3c616f6c_fk_auth_user_id‘ (‘user_id‘),
  KEY ‘core_activity_log_created_at_ffcf42b6‘ (‘created_at‘),
  CONSTRAINT ‘core_activity_log_user_id_3c616f6c_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFERENCES ‘a
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_activity_log‘
--

LOCK TABLES ‘core_activity_log‘ WRITE;
/*!40000 ALTER TABLE ‘core_activity_log‘ DISABLE KEYS */;
INSERT INTO ‘core_activity_log‘ VALUES (1,’Staff Login [Email: krishna01@gmail.com]’,’2026-03-17 11:42:
/*!40000 ALTER TABLE ‘core_activity_log‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_business‘
--

DROP TABLE IF EXISTS ‘core_business‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_business‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(100) NOT NULL,
```

```
  ‘email‘ varchar(254) NOT NULL,
  ‘owner_name‘ varchar(100) NOT NULL,
  ‘is_approved‘ tinyint(1) NOT NULL,
  ‘db_name‘ varchar(100) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘name‘ (‘name‘),
  UNIQUE KEY ‘core_business_email_7d23db71_uniq‘ (‘email‘),
  UNIQUE KEY ‘core_business_db_name_9948327e_uniq‘ (‘db_name‘),
  KEY ‘core_business_created_at_6fcad137‘ (‘created_at‘),
  KEY ‘core_business_is_approved_af231d2a‘ (‘is_approved‘),
  KEY ‘core_busine_email_6f5879_idx‘ (‘email‘,‘is_approved‘)
) ENGINE=InnoDB AUTO_INCREMENT=39 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_business‘
--

LOCK TABLES ‘core_business‘ WRITE;
/*!40000 ALTER TABLE ‘core_business‘ DISABLE KEYS */;
INSERT INTO ‘core_business‘ VALUES (1,’https://bananasit.com/’,’ts0279190@gmail.com’,’Sahil’,1,’ms_crm_
/*!40000 ALTER TABLE ‘core_business‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_calendarevent‘
--

DROP TABLE IF EXISTS ‘core_calendarevent‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_calendarevent‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘title‘ varchar(255) NOT NULL,
  ‘date‘ date NOT NULL,
  ‘color‘ varchar(20) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_calendarevent‘
--

LOCK TABLES ‘core_calendarevent‘ WRITE;
/*!40000 ALTER TABLE ‘core_calendarevent‘ DISABLE KEYS */;
INSERT INTO ‘core_calendarevent‘ VALUES (1,’Meeting with Client’,’2026-03-17’,’#0e4ee1’),(2,’Get togeth
/*!40000 ALTER TABLE ‘core_calendarevent‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_client‘
--

DROP TABLE IF EXISTS ‘core_client‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_client‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘company‘ varchar(255) NOT NULL,
  ‘vat_number‘ varchar(100) DEFAULT NULL,
  ‘phone‘ varchar(20) DEFAULT NULL,
```

```
  ‘city‘ varchar(100) DEFAULT NULL,
  ‘state‘ varchar(100) DEFAULT NULL,
  ‘zip_code‘ varchar(20) DEFAULT NULL,
  ‘country‘ varchar(100) DEFAULT NULL,
  ‘currency‘ varchar(10) DEFAULT NULL,
  ‘default_language‘ varchar(50) DEFAULT NULL,
  ‘billing_address‘ longtext,
  ‘shipping_address‘ longtext,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘is_active‘ tinyint(1) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=7 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_client‘
--

LOCK TABLES ‘core_client‘ WRITE;
/*!40000 ALTER TABLE ‘core_client‘ DISABLE KEYS */;
INSERT INTO ‘core_client‘ VALUES (1,’Softinfotech’,’ATU12345678’,’9512839679’,’Surat, Gujarat’,’Gujarat
/*!40000 ALTER TABLE ‘core_client‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contact‘
--

DROP TABLE IF EXISTS ‘core_contact‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contact‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘firstname‘ varchar(191) NOT NULL,
  ‘lastname‘ varchar(191) NOT NULL,
  ‘email‘ varchar(254) NOT NULL,
  ‘company‘ varchar(255) DEFAULT NULL,
  ‘phonenumber‘ varchar(100) DEFAULT NULL,
  ‘title‘ varchar(100) DEFAULT NULL,
  ‘password‘ varchar(255) DEFAULT NULL,
  ‘is_primary‘ tinyint(1) NOT NULL,
  ‘active‘ tinyint(1) NOT NULL,
  ‘direction‘ varchar(10) DEFAULT NULL,
  ‘invoice_emails‘ tinyint(1) NOT NULL,
  ‘estimate_emails‘ tinyint(1) NOT NULL,
  ‘credit_note_emails‘ tinyint(1) NOT NULL,
  ‘contract_emails‘ tinyint(1) NOT NULL,
  ‘task_emails‘ tinyint(1) NOT NULL,
  ‘project_emails‘ tinyint(1) NOT NULL,
  ‘ticket_emails‘ tinyint(1) NOT NULL,
  ‘last_login‘ datetime(6) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=7 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_contact‘
--

LOCK TABLES ‘core_contact‘ WRITE;
/*!40000 ALTER TABLE ‘core_contact‘ DISABLE KEYS */;
INSERT INTO ‘core_contact‘ VALUES (1,’Sahilraj’,’Date’,’sahildate@gmail.com’,’Magnyte Solutions’,’95128
```

```
/*!40000 ALTER TABLE ‘core_contact‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract‘
--

DROP TABLE IF EXISTS ‘core_contract‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘customer‘ varchar(255) DEFAULT NULL,
  ‘subject‘ varchar(255) NOT NULL,
  ‘contract_type‘ varchar(100) DEFAULT NULL,
  ‘contract_value‘ decimal(12,2) NOT NULL,
  ‘start_date‘ date DEFAULT NULL,
  ‘end_date‘ date DEFAULT NULL,
  ‘signature‘ varchar(255) DEFAULT NULL,
  ‘description‘ longtext,
  ‘hide_from_customer‘ tinyint(1) NOT NULL,
  ‘is_trashed‘ tinyint(1) NOT NULL,
  ‘status‘ varchar(20) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘customer_ref_id‘ bigint DEFAULT NULL,
  ‘content‘ longtext,
  PRIMARY KEY (‘id‘),
  KEY ‘core_contract_customer_ref_id_a62b7ac4_fk_core_client_id‘ (‘customer_ref_id‘),
  CONSTRAINT ‘core_contract_customer_ref_id_a62b7ac4_fk_core_client_id‘ FOREIGN KEY (‘customer_ref_id‘)
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_contract‘
--

LOCK TABLES ‘core_contract‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract‘ DISABLE KEYS */;
INSERT INTO ‘core_contract‘ VALUES (1,’Magnyte Solutions’,’SmartTech’,’Service’,311603.00,’2026-02-20’,
/*!40000 ALTER TABLE ‘core_contract‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract_attachment‘
--

DROP TABLE IF EXISTS ‘core_contract_attachment‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract_attachment‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘file‘ varchar(100) NOT NULL,
  ‘filename‘ varchar(255) DEFAULT NULL,
  ‘uploaded_by‘ varchar(191) DEFAULT NULL,
  ‘uploaded_at‘ datetime(6) NOT NULL,
  ‘contract_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_contract_attach_contract_id_a1d19277_fk_core_cont‘ (‘contract_id‘),
  CONSTRAINT ‘core_contract_attach_contract_id_a1d19277_fk_core_cont‘ FOREIGN KEY (‘contract_id‘) REFER
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
```

```
-- Dumping data for table ‘core_contract_attachment‘
--

LOCK TABLES ‘core_contract_attachment‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract_attachment‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_contract_attachment‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract_comment‘
--

DROP TABLE IF EXISTS ‘core_contract_comment‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract_comment‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘comment‘ longtext NOT NULL,
  ‘created_by‘ varchar(191) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘contract_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_contract_comment_contract_id_ae77115e_fk_core_contract_id‘ (‘contract_id‘),
  CONSTRAINT ‘core_contract_comment_contract_id_ae77115e_fk_core_contract_id‘ FOREIGN KEY (‘contract_id
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_contract_comment‘
--

LOCK TABLES ‘core_contract_comment‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract_comment‘ DISABLE KEYS */;
INSERT INTO ‘core_contract_comment‘ VALUES (1,’Good as providing supports’,’krishna01@gmail.com’,’2026-
/*!40000 ALTER TABLE ‘core_contract_comment‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract_note‘
--

DROP TABLE IF EXISTS ‘core_contract_note‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract_note‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘note‘ longtext NOT NULL,
  ‘created_by‘ varchar(191) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘contract_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_contract_note_contract_id_a2cfc2fc_fk_core_contract_id‘ (‘contract_id‘),
  CONSTRAINT ‘core_contract_note_contract_id_a2cfc2fc_fk_core_contract_id‘ FOREIGN KEY (‘contract_id‘)
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_contract_note‘
--

LOCK TABLES ‘core_contract_note‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract_note‘ DISABLE KEYS */;
INSERT INTO ‘core_contract_note‘ VALUES (1,’Goode for taking Support’,’krishna01@gmail.com’,’2026-03-16
```

```
/*!40000 ALTER TABLE ‘core_contract_note‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract_renewal‘
--

DROP TABLE IF EXISTS ‘core_contract_renewal‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract_renewal‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘old_start_date‘ date DEFAULT NULL,
  ‘new_start_date‘ date DEFAULT NULL,
  ‘old_end_date‘ date DEFAULT NULL,
  ‘new_end_date‘ date DEFAULT NULL,
  ‘old_value‘ decimal(12,2) DEFAULT NULL,
  ‘new_value‘ decimal(12,2) DEFAULT NULL,
  ‘notes‘ longtext,
  ‘renewed_by‘ varchar(191) DEFAULT NULL,
  ‘renewed_at‘ datetime(6) NOT NULL,
  ‘contract_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_contract_renewal_contract_id_6b4685d8_fk_core_contract_id‘ (‘contract_id‘),
  CONSTRAINT ‘core_contract_renewal_contract_id_6b4685d8_fk_core_contract_id‘ FOREIGN KEY (‘contract_id
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_contract_renewal‘
--

LOCK TABLES ‘core_contract_renewal‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract_renewal‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_contract_renewal‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract_task‘
--

DROP TABLE IF EXISTS ‘core_contract_task‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract_task‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘subject‘ varchar(255) NOT NULL,
  ‘description‘ longtext,
  ‘start_date‘ date DEFAULT NULL,
  ‘due_date‘ date DEFAULT NULL,
  ‘priority‘ varchar(20) NOT NULL,
  ‘is_public‘ tinyint(1) NOT NULL,
  ‘is_billable‘ tinyint(1) NOT NULL,
  ‘tags‘ varchar(255) DEFAULT NULL,
  ‘created_by‘ varchar(191) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘contract_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_contract_task_contract_id_6f5868a8_fk_core_contract_id‘ (‘contract_id‘),
  CONSTRAINT ‘core_contract_task_contract_id_6f5868a8_fk_core_contract_id‘ FOREIGN KEY (‘contract_id‘)
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
-- Dumping data for table ‘core_contract_task‘
--

LOCK TABLES ‘core_contract_task‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract_task‘ DISABLE KEYS */;
INSERT INTO ‘core_contract_task‘ VALUES (1,’Contract Overview’,’Items can renew with Invoices updates’,
/*!40000 ALTER TABLE ‘core_contract_task‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_contract_type‘
--

DROP TABLE IF EXISTS ‘core_contract_type‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_contract_type‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(191) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘name‘ (‘name‘)
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_contract_type‘
--

LOCK TABLES ‘core_contract_type‘ WRITE;
/*!40000 ALTER TABLE ‘core_contract_type‘ DISABLE KEYS */;
INSERT INTO ‘core_contract_type‘ VALUES (1,’Service’,’2026-03-16 05:30:47.992468’),(2,’Support’,’2026-0
/*!40000 ALTER TABLE ‘core_contract_type‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_creditnote‘
--

DROP TABLE IF EXISTS ‘core_creditnote‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_creditnote‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘deleted_customer_name‘ varchar(255) DEFAULT NULL,
  ‘number‘ int unsigned NOT NULL,
  ‘prefix‘ varchar(20) NOT NULL,
  ‘number_format‘ varchar(30) DEFAULT NULL,
  ‘datecreated‘ datetime(6) NOT NULL,
  ‘date‘ date NOT NULL,
  ‘duedate‘ date DEFAULT NULL,
  ‘project_id‘ int DEFAULT NULL,
  ‘reference_no‘ varchar(100) DEFAULT NULL,
  ‘subtotal‘ decimal(12,2) NOT NULL,
  ‘total_tax‘ decimal(12,2) NOT NULL,
  ‘total‘ decimal(12,2) NOT NULL,
  ‘adjustment‘ decimal(12,2) NOT NULL,
  ‘addedfrom‘ int DEFAULT NULL,
  ‘status‘ int NOT NULL,
  ‘clientnote‘ longtext,
  ‘adminnote‘ longtext,
  ‘terms‘ longtext,
```

```
  ‘currency‘ varchar(20) DEFAULT NULL,
  ‘discount_percent‘ decimal(12,2) NOT NULL,
  ‘discount_total‘ decimal(12,2) NOT NULL,
  ‘discount_type‘ varchar(30) DEFAULT NULL,
  ‘billing_street‘ varchar(255) DEFAULT NULL,
  ‘billing_city‘ varchar(100) DEFAULT NULL,
  ‘billing_state‘ varchar(100) DEFAULT NULL,
  ‘billing_zip‘ varchar(30) DEFAULT NULL,
  ‘billing_country‘ varchar(100) DEFAULT NULL,
  ‘shipping_street‘ varchar(255) DEFAULT NULL,
  ‘shipping_city‘ varchar(100) DEFAULT NULL,
  ‘shipping_state‘ varchar(100) DEFAULT NULL,
  ‘shipping_zip‘ varchar(30) DEFAULT NULL,
  ‘shipping_country‘ varchar(100) DEFAULT NULL,
  ‘include_shipping‘ tinyint(1) NOT NULL,
  ‘show_shipping_on_credit_note‘ tinyint(1) NOT NULL,
  ‘show_quantity_as‘ varchar(30) DEFAULT NULL,
  ‘email_signature‘ longtext,
  ‘items‘ json NOT NULL,
  ‘client_id‘ bigint DEFAULT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_creditnote_client_id_2e62174f_fk_core_client_id‘ (‘client_id‘),
  CONSTRAINT ‘core_creditnote_client_id_2e62174f_fk_core_client_id‘ FOREIGN KEY (‘client_id‘) REFERENCE
  CONSTRAINT ‘core_creditnote_chk_1‘ CHECK ((‘number‘ >= 0))
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_creditnote‘
--

LOCK TABLES ‘core_creditnote‘ WRITE;
/*!40000 ALTER TABLE ‘core_creditnote‘ DISABLE KEYS */;
INSERT INTO ‘core_creditnote‘ VALUES (2,’Banana Infotech’,1,’CN-’,’’,’2026-03-13 09:57:40.162735’,’2026
/*!40000 ALTER TABLE ‘core_creditnote‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_creditnote_reminder‘
--

DROP TABLE IF EXISTS ‘core_creditnote_reminder‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_creditnote_reminder‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘description‘ longtext,
  ‘date‘ datetime(6) DEFAULT NULL,
  ‘status‘ varchar(50) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘credit_note_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_creditnote_remi_credit_note_id_ce2d502e_fk_core_cred‘ (‘credit_note_id‘),
  CONSTRAINT ‘core_creditnote_remi_credit_note_id_ce2d502e_fk_core_cred‘ FOREIGN KEY (‘credit_note_id‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_creditnote_reminder‘
--

LOCK TABLES ‘core_creditnote_reminder‘ WRITE;
/*!40000 ALTER TABLE ‘core_creditnote_reminder‘ DISABLE KEYS */;
```

```
/*!40000 ALTER TABLE ‘core_creditnote_reminder‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_creditnote_task‘
--

DROP TABLE IF EXISTS ‘core_creditnote_task‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_creditnote_task‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘description‘ longtext,
  ‘date‘ datetime(6) DEFAULT NULL,
  ‘status‘ varchar(50) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘credit_note_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_creditnote_task_credit_note_id_0a6f61c7_fk_core_cred‘ (‘credit_note_id‘),
  CONSTRAINT ‘core_creditnote_task_credit_note_id_0a6f61c7_fk_core_cred‘ FOREIGN KEY (‘credit_note_id‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_creditnote_task‘
--

LOCK TABLES ‘core_creditnote_task‘ WRITE;
/*!40000 ALTER TABLE ‘core_creditnote_task‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_creditnote_task‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_customer‘
--

DROP TABLE IF EXISTS ‘core_customer‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_customer‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘company‘ varchar(255) NOT NULL,
  ‘primary_contact‘ varchar(255) DEFAULT NULL,
  ‘email‘ varchar(254) DEFAULT NULL,
  ‘phone‘ varchar(20) DEFAULT NULL,
  ‘is_active‘ tinyint(1) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_customer‘
--

LOCK TABLES ‘core_customer‘ WRITE;
/*!40000 ALTER TABLE ‘core_customer‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_customer‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_emailcampaign‘
--
```

```
DROP TABLE IF EXISTS ‘core_emailcampaign‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_emailcampaign‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘subject‘ varchar(255) NOT NULL,
  ‘message‘ longtext NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_emailcampaign‘
--

LOCK TABLES ‘core_emailcampaign‘ WRITE;
/*!40000 ALTER TABLE ‘core_emailcampaign‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_emailcampaign‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_emailrecipient‘
--

DROP TABLE IF EXISTS ‘core_emailrecipient‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_emailrecipient‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘email‘ varchar(254) NOT NULL,
  ‘is_sent‘ tinyint(1) NOT NULL,
  ‘sent_at‘ datetime(6) DEFAULT NULL,
  ‘campaign_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_emailrecipient_campaign_id_48ff735c_fk_core_emai‘ (‘campaign_id‘),
  CONSTRAINT ‘core_emailrecipient_campaign_id_48ff735c_fk_core_emai‘ FOREIGN KEY (‘campaign_id‘) REFERE
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_emailrecipient‘
--

LOCK TABLES ‘core_emailrecipient‘ WRITE;
/*!40000 ALTER TABLE ‘core_emailrecipient‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_emailrecipient‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_emailtemplate‘
--

DROP TABLE IF EXISTS ‘core_emailtemplate‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_emailtemplate‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘module‘ varchar(50) NOT NULL,
  ‘slug‘ varchar(100) NOT NULL,
  ‘language‘ varchar(20) NOT NULL,
  ‘subject‘ varchar(255) NOT NULL,
```

```
  ‘body‘ longtext NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘core_emailtemplate_module_slug_language_bf4e2407_uniq‘ (‘module‘,‘slug‘,‘language‘),
  KEY ‘core_emailt_module_211275_idx‘ (‘module‘,‘slug‘)
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_emailtemplate‘
--

LOCK TABLES ‘core_emailtemplate‘ WRITE;
/*!40000 ALTER TABLE ‘core_emailtemplate‘ DISABLE KEYS */;
INSERT INTO ‘core_emailtemplate‘ VALUES (1,’client’,’new-client-created’,’english’,’Welcome Client’,’Ne
/*!40000 ALTER TABLE ‘core_emailtemplate‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_estimate‘
--

DROP TABLE IF EXISTS ‘core_estimate‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_estimate‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘estimate_number‘ varchar(100) NOT NULL,
  ‘customer_id‘ bigint NOT NULL,
  ‘amount‘ decimal(10,2) NOT NULL,
  ‘total_tax‘ decimal(10,2) NOT NULL,
  ‘date‘ date NOT NULL,
  ‘expiry_date‘ date NOT NULL,
  ‘status‘ varchar(100) NOT NULL,
  ‘items‘ json NOT NULL DEFAULT (_utf8mb4’[]’),
  PRIMARY KEY (‘id‘),
  KEY ‘core_estimate_customer_id_33c8c666‘ (‘customer_id‘),
  CONSTRAINT ‘core_estimate_customer_id_33c8c666_fk_core_client_id‘ FOREIGN KEY (‘customer_id‘) REFEREN
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_estimate‘
--

LOCK TABLES ‘core_estimate‘ WRITE;
/*!40000 ALTER TABLE ‘core_estimate‘ DISABLE KEYS */;
INSERT INTO ‘core_estimate‘ VALUES (2,’1623-1021’,2,630.00,0.00,’2026-03-03’,’2026-07-15’,’Draft’,’[]’)
/*!40000 ALTER TABLE ‘core_estimate‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_expense‘
--

DROP TABLE IF EXISTS ‘core_expense‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_expense‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(255) NOT NULL,
  ‘category‘ varchar(100) NOT NULL,
  ‘amount‘ decimal(10,2) NOT NULL,
  ‘date‘ date NOT NULL,
```

```
  ‘customer‘ varchar(255) DEFAULT NULL,
  ‘payment_mode‘ varchar(100) DEFAULT NULL,
  ‘status‘ varchar(50) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘currency‘ varchar(20) NOT NULL,
  ‘note‘ longtext,
  ‘reference‘ varchar(255) DEFAULT NULL,
  ‘repeat_every‘ varchar(50) DEFAULT NULL,
  ‘tax1‘ varchar(50) DEFAULT NULL,
  ‘tax2‘ varchar(50) DEFAULT NULL,
  ‘customer_ref_id‘ bigint DEFAULT NULL,
  ‘invoice_ref_id‘ bigint DEFAULT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_expense_customer_ref_id_beb93da2_fk_core_client_id‘ (‘customer_ref_id‘),
  KEY ‘core_expense_invoice_ref_id_4a90cace_fk_core_invoice_id‘ (‘invoice_ref_id‘),
  CONSTRAINT ‘core_expense_customer_ref_id_beb93da2_fk_core_client_id‘ FOREIGN KEY (‘customer_ref_id‘)
  CONSTRAINT ‘core_expense_invoice_ref_id_4a90cace_fk_core_invoice_id‘ FOREIGN KEY (‘invoice_ref_id‘) R
) ENGINE=InnoDB AUTO_INCREMENT=7 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_expense‘
--

LOCK TABLES ‘core_expense‘ WRITE;
/*!40000 ALTER TABLE ‘core_expense‘ DISABLE KEYS */;
INSERT INTO ‘core_expense‘ VALUES (1,’sanjay’,’Office’,350.00,’2026-02-21’,’Customer A’,’Bank’,’Not Inv
/*!40000 ALTER TABLE ‘core_expense‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_invoice‘
--

DROP TABLE IF EXISTS ‘core_invoice‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_invoice‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘invoice_number‘ varchar(50) NOT NULL,
  ‘status‘ varchar(20) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘customer_id‘ bigint NOT NULL,
  ‘due_date‘ date NOT NULL,
  ‘invoice_date‘ date NOT NULL,
  ‘subtotal‘ decimal(10,2) NOT NULL,
  ‘tax_amount‘ decimal(10,2) NOT NULL,
  ‘total_amount‘ decimal(10,2) NOT NULL,
  ‘payment_mode‘ varchar(20) NOT NULL,
  ‘reference_estimate_id‘ bigint DEFAULT NULL,
  ‘items‘ json NOT NULL DEFAULT (_utf8mb4’[]’),
  PRIMARY KEY (‘id‘),
  KEY ‘core_invoice_customer_id_53184093_fk_core_client_id‘ (‘customer_id‘),
  KEY ‘core_invoice_reference_estimate_id_ebfca259_fk_core_estimate_id‘ (‘reference_estimate_id‘),
  CONSTRAINT ‘core_invoice_customer_id_53184093_fk_core_client_id‘ FOREIGN KEY (‘customer_id‘) REFERENC
  CONSTRAINT ‘core_invoice_reference_estimate_id_ebfca259_fk_core_estimate_id‘ FOREIGN KEY (‘reference_
) ENGINE=InnoDB AUTO_INCREMENT=15 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_invoice‘
--
```

```
LOCK TABLES ‘core_invoice‘ WRITE;
/*!40000 ALTER TABLE ‘core_invoice‘ DISABLE KEYS */;
INSERT INTO ‘core_invoice‘ VALUES (4,’003’,’Unpaid’,’2026-03-06 06:43:11.505025’,3,’2026-05-29’,’2026-0
/*!40000 ALTER TABLE ‘core_invoice‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_invoiceemaillog‘
--

DROP TABLE IF EXISTS ‘core_invoiceemaillog‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_invoiceemaillog‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘email‘ varchar(254) NOT NULL,
  ‘message‘ longtext NOT NULL,
  ‘sent_at‘ datetime(6) NOT NULL,
  ‘invoice_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_invoiceemaillog_invoice_id_da411941_fk_core_invoice_id‘ (‘invoice_id‘),
  CONSTRAINT ‘core_invoiceemaillog_invoice_id_da411941_fk_core_invoice_id‘ FOREIGN KEY (‘invoice_id‘) R
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_invoiceemaillog‘
--

LOCK TABLES ‘core_invoiceemaillog‘ WRITE;
/*!40000 ALTER TABLE ‘core_invoiceemaillog‘ DISABLE KEYS */;
INSERT INTO ‘core_invoiceemaillog‘ VALUES (1,’sahildate92@gmail.com’,’Dear Client,\n\nInvoice Number: 0
/*!40000 ALTER TABLE ‘core_invoiceemaillog‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_invoicepayment‘
--

DROP TABLE IF EXISTS ‘core_invoicepayment‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_invoicepayment‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘payment_mode‘ varchar(20) NOT NULL,
  ‘transaction_id‘ varchar(50) NOT NULL,
  ‘amount‘ decimal(10,2) NOT NULL,
  ‘payment_date‘ date NOT NULL,
  ‘invoice_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_invoicepayment_invoice_id_ef4798c7_fk_core_invoice_id‘ (‘invoice_id‘),
  CONSTRAINT ‘core_invoicepayment_invoice_id_ef4798c7_fk_core_invoice_id‘ FOREIGN KEY (‘invoice_id‘) RE
) ENGINE=InnoDB AUTO_INCREMENT=10 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_invoicepayment‘
--

LOCK TABLES ‘core_invoicepayment‘ WRITE;
/*!40000 ALTER TABLE ‘core_invoicepayment‘ DISABLE KEYS */;
INSERT INTO ‘core_invoicepayment‘ VALUES (1,’Auto’,’Auto-4’,541.00,’2026-03-10’,4),(2,’Auto’,’Auto-7’,3
/*!40000 ALTER TABLE ‘core_invoicepayment‘ ENABLE KEYS */;
```

```
UNLOCK TABLES;

--
-- Table structure for table ‘core_invoicereminder‘
--

DROP TABLE IF EXISTS ‘core_invoicereminder‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_invoicereminder‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘description‘ longtext NOT NULL,
  ‘date‘ datetime(6) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘invoice_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_invoicereminder_invoice_id_1ef3f115_fk_core_invoice_id‘ (‘invoice_id‘),
  CONSTRAINT ‘core_invoicereminder_invoice_id_1ef3f115_fk_core_invoice_id‘ FOREIGN KEY (‘invoice_id‘) R
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_invoicereminder‘
--

LOCK TABLES ‘core_invoicereminder‘ WRITE;
/*!40000 ALTER TABLE ‘core_invoicereminder‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_invoicereminder‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_invoicetask‘
--

DROP TABLE IF EXISTS ‘core_invoicetask‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_invoicetask‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘description‘ longtext NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘invoice_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_invoicetask_invoice_id_780e271e_fk_core_invoice_id‘ (‘invoice_id‘),
  CONSTRAINT ‘core_invoicetask_invoice_id_780e271e_fk_core_invoice_id‘ FOREIGN KEY (‘invoice_id‘) REFER
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_invoicetask‘
--

LOCK TABLES ‘core_invoicetask‘ WRITE;
/*!40000 ALTER TABLE ‘core_invoicetask‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_invoicetask‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_item‘
--

DROP TABLE IF EXISTS ‘core_item‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
```

```
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_item‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘description‘ varchar(255) NOT NULL,
  ‘long_description‘ longtext,
  ‘rate‘ decimal(12,2) NOT NULL,
  ‘tax‘ varchar(50) DEFAULT NULL,
  ‘tax2‘ varchar(50) DEFAULT NULL,
  ‘unit‘ varchar(100) DEFAULT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘group_id‘ bigint DEFAULT NULL,
  ‘item_code‘ varchar(100) DEFAULT NULL,
  ‘item_name‘ varchar(255) NOT NULL,
  ‘status‘ varchar(20) NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_item_group_id_86ef4429_fk_core_item_group_id‘ (‘group_id‘),
  KEY ‘core_item_item_code_7eebaa3e‘ (‘item_code‘),
  KEY ‘core_item_item_name_b2d22de3‘ (‘item_name‘),
  KEY ‘core_item_status_db560d8c‘ (‘status‘),
  CONSTRAINT ‘core_item_group_id_86ef4429_fk_core_item_group_id‘ FOREIGN KEY (‘group_id‘) REFERENCES ‘c
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_item‘
--

LOCK TABLES ‘core_item‘ WRITE;
/*!40000 ALTER TABLE ‘core_item‘ DISABLE KEYS */;
INSERT INTO ‘core_item‘ VALUES (1,’Samsung’,’SmartPhone’,150000.00,’5%’,’No Tax’,’1’,’2026-03-14 05:02:
/*!40000 ALTER TABLE ‘core_item‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_item_group‘
--

DROP TABLE IF EXISTS ‘core_item_group‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_item_group‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(191) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘name‘ (‘name‘)
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_item_group‘
--

LOCK TABLES ‘core_item_group‘ WRITE;
/*!40000 ALTER TABLE ‘core_item_group‘ DISABLE KEYS */;
INSERT INTO ‘core_item_group‘ VALUES (2,’SmartTech’,’2026-03-14 05:03:19.779524’);
/*!40000 ALTER TABLE ‘core_item_group‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_lead‘
--
```

```
DROP TABLE IF EXISTS ‘core_lead‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_lead‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(255) NOT NULL,
  ‘email‘ varchar(254) DEFAULT NULL,
  ‘phone‘ varchar(20) DEFAULT NULL,
  ‘status‘ varchar(50) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘source‘ varchar(100) DEFAULT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_lead‘
--

LOCK TABLES ‘core_lead‘ WRITE;
/*!40000 ALTER TABLE ‘core_lead‘ DISABLE KEYS */;
INSERT INTO ‘core_lead‘ VALUES (1,’Sahil Date’,’ts0279190@gmail.com’,’09512839679’,’Contacted’,’2026-02
/*!40000 ALTER TABLE ‘core_lead‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_project‘
--

DROP TABLE IF EXISTS ‘core_project‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_project‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(255) NOT NULL,
  ‘progress‘ smallint unsigned NOT NULL,
  ‘status‘ varchar(32) NOT NULL,
  ‘billing_type‘ varchar(32) NOT NULL,
  ‘total_rate‘ decimal(12,2) NOT NULL,
  ‘estimated_hours‘ decimal(10,2) NOT NULL,
  ‘start_date‘ date DEFAULT NULL,
  ‘deadline‘ date DEFAULT NULL,
  ‘tags‘ varchar(255) DEFAULT NULL,
  ‘description‘ longtext,
  ‘send_email‘ tinyint(1) NOT NULL,
  ‘visible_tabs‘ json NOT NULL,
  ‘settings‘ json NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘updated_at‘ datetime(6) NOT NULL,
  ‘client_id‘ bigint DEFAULT NULL,
  ‘created_by_id‘ int DEFAULT NULL,
  ‘mentor_id‘ int DEFAULT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_projec_client__f4eed2_idx‘ (‘client_id‘,‘status‘),
  KEY ‘core_project_created_by_id_3ae31859_fk_auth_user_id‘ (‘created_by_id‘),
  KEY ‘core_project_name_ebbd35d6‘ (‘name‘),
  KEY ‘core_project_status_4ccd8987‘ (‘status‘),
  KEY ‘core_project_created_at_05ddbca4‘ (‘created_at‘),
  KEY ‘core_project_updated_at_5f0d6b5c‘ (‘updated_at‘),
  KEY ‘core_project_mentor_id_629da69e_fk_auth_user_id‘ (‘mentor_id‘),
  CONSTRAINT ‘core_project_client_id_4ba9e455_fk_core_client_id‘ FOREIGN KEY (‘client_id‘) REFERENCES ‘
  CONSTRAINT ‘core_project_created_by_id_3ae31859_fk_auth_user_id‘ FOREIGN KEY (‘created_by_id‘) REFERE
  CONSTRAINT ‘core_project_mentor_id_629da69e_fk_auth_user_id‘ FOREIGN KEY (‘mentor_id‘) REFERENCES ‘au
```

```
  CONSTRAINT ‘core_project_chk_1‘ CHECK ((‘progress‘ >= 0))
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_project‘
--

LOCK TABLES ‘core_project‘ WRITE;
/*!40000 ALTER TABLE ‘core_project‘ DISABLE KEYS */;
INSERT INTO ‘core_project‘ VALUES (2,’CRM System’,40,’Accepted’,’Fixed Rate’,900000.00,245.00,’2026-01-
/*!40000 ALTER TABLE ‘core_project‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_project_members‘
--

DROP TABLE IF EXISTS ‘core_project_members‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_project_members‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘project_id‘ bigint NOT NULL,
  ‘user_id‘ int NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘core_project_members_project_id_user_id_3750979c_uniq‘ (‘project_id‘,‘user_id‘),
  KEY ‘core_project_members_user_id_25704107_fk_auth_user_id‘ (‘user_id‘),
  CONSTRAINT ‘core_project_members_project_id_9909b3ba_fk_core_project_id‘ FOREIGN KEY (‘project_id‘) R
  CONSTRAINT ‘core_project_members_user_id_25704107_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFERENCES
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_project_members‘
--

LOCK TABLES ‘core_project_members‘ WRITE;
/*!40000 ALTER TABLE ‘core_project_members‘ DISABLE KEYS */;
INSERT INTO ‘core_project_members‘ VALUES (1,2,33),(4,4,28),(3,4,33);
/*!40000 ALTER TABLE ‘core_project_members‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_proposal‘
--

DROP TABLE IF EXISTS ‘core_proposal‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_proposal‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘subject‘ varchar(255) NOT NULL,
  ‘assigned_to_id‘ int DEFAULT NULL,
  ‘created_by_id‘ int DEFAULT NULL,
  ‘adjustment‘ decimal(10,2) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘discount_total‘ decimal(10,2) NOT NULL,
  ‘items‘ json NOT NULL DEFAULT (_utf8mb4’[]’),
  ‘status‘ varchar(20) NOT NULL,
  ‘total‘ decimal(12,2) NOT NULL,
  ‘proposal_to‘ varchar(191) DEFAULT NULL,
  ‘address‘ varchar(200) DEFAULT NULL,
```

```
  ‘city‘ varchar(100) DEFAULT NULL,
  ‘state‘ varchar(100) DEFAULT NULL,
  ‘country‘ varchar(100) DEFAULT NULL,
  ‘zip‘ varchar(50) DEFAULT NULL,
  ‘email‘ varchar(150) DEFAULT NULL,
  ‘phone‘ varchar(50) DEFAULT NULL,
  ‘comments‘ json DEFAULT NULL,
  ‘reminders‘ json DEFAULT NULL,
  ‘tasks‘ json DEFAULT NULL,
  ‘notes‘ json DEFAULT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘core_proposal_assigned_to_id_59739e86_fk_auth_user_id‘ (‘assigned_to_id‘),
  KEY ‘core_proposal_created_by_id_b1be6922_fk_auth_user_id‘ (‘created_by_id‘),
  CONSTRAINT ‘core_proposal_assigned_to_id_59739e86_fk_auth_user_id‘ FOREIGN KEY (‘assigned_to_id‘) REF
  CONSTRAINT ‘core_proposal_created_by_id_b1be6922_fk_auth_user_id‘ FOREIGN KEY (‘created_by_id‘) REFER
) ENGINE=InnoDB AUTO_INCREMENT=13 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_proposal‘
--

LOCK TABLES ‘core_proposal‘ WRITE;
/*!40000 ALTER TABLE ‘core_proposal‘ DISABLE KEYS */;
INSERT INTO ‘core_proposal‘ VALUES (1,’T.V’,33,NULL,0.00,’2026-02-20 09:39:12.909347’,0.00,’[{\"qty\":
/*!40000 ALTER TABLE ‘core_proposal‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_roles‘
--

DROP TABLE IF EXISTS ‘core_roles‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_roles‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(100) NOT NULL,
  ‘permissions‘ longtext NOT NULL,
  ‘is_approved‘ tinyint(1) NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_roles‘
--

LOCK TABLES ‘core_roles‘ WRITE;
/*!40000 ALTER TABLE ‘core_roles‘ DISABLE KEYS */;
INSERT INTO ‘core_roles‘ VALUES (1,’Admin’,’All’,1,’2026-02-16 09:03:45.353429’),(2,’User’,’Basic’,0,’2
/*!40000 ALTER TABLE ‘core_roles‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘core_staffprofile‘
--

DROP TABLE IF EXISTS ‘core_staffprofile‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘core_staffprofile‘ (
```

```
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘manager_id‘ int DEFAULT NULL,
  ‘user_id‘ int NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘user_id‘ (‘user_id‘),
  KEY ‘core_staffprofile_manager_id_cab1203e_fk_auth_user_id‘ (‘manager_id‘),
  CONSTRAINT ‘core_staffprofile_manager_id_cab1203e_fk_auth_user_id‘ FOREIGN KEY (‘manager_id‘) REFEREN
  CONSTRAINT ‘core_staffprofile_user_id_571ae86a_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFERENCES ‘a
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘core_staffprofile‘
--

LOCK TABLES ‘core_staffprofile‘ WRITE;
/*!40000 ALTER TABLE ‘core_staffprofile‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘core_staffprofile‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘django_admin_log‘
--

DROP TABLE IF EXISTS ‘django_admin_log‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘django_admin_log‘ (
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘action_time‘ datetime(6) NOT NULL,
  ‘object_id‘ longtext,
  ‘object_repr‘ varchar(200) NOT NULL,
  ‘action_flag‘ smallint unsigned NOT NULL,
  ‘change_message‘ longtext NOT NULL,
  ‘content_type_id‘ int DEFAULT NULL,
  ‘user_id‘ int NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘django_admin_log_content_type_id_c4bce8eb_fk_django_co‘ (‘content_type_id‘),
  KEY ‘django_admin_log_user_id_c564eba6_fk_auth_user_id‘ (‘user_id‘),
  CONSTRAINT ‘django_admin_log_content_type_id_c4bce8eb_fk_django_co‘ FOREIGN KEY (‘content_type_id‘) R
  CONSTRAINT ‘django_admin_log_user_id_c564eba6_fk_auth_user_id‘ FOREIGN KEY (‘user_id‘) REFERENCES ‘au
  CONSTRAINT ‘django_admin_log_chk_1‘ CHECK ((‘action_flag‘ >= 0))
) ENGINE=InnoDB AUTO_INCREMENT=15 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘django_admin_log‘
--

LOCK TABLES ‘django_admin_log‘ WRITE;
/*!40000 ALTER TABLE ‘django_admin_log‘ DISABLE KEYS */;
INSERT INTO ‘django_admin_log‘ VALUES (1,’2026-02-04 11:02:05.786020’,’3’,’https://techsit.com/’,3,’’,7
/*!40000 ALTER TABLE ‘django_admin_log‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘django_content_type‘
--

DROP TABLE IF EXISTS ‘django_content_type‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘django_content_type‘ (
```

```
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘app_label‘ varchar(100) NOT NULL,
  ‘model‘ varchar(100) NOT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘django_content_type_app_label_model_76bd3d3b_uniq‘ (‘app_label‘,‘model‘)
) ENGINE=InnoDB AUTO_INCREMENT=168 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘django_content_type‘
--

LOCK TABLES ‘django_content_type‘ WRITE;
/*!40000 ALTER TABLE ‘django_content_type‘ DISABLE KEYS */;
INSERT INTO ‘django_content_type‘ VALUES (1,’admin’,’logentry’),(2,’auth’,’group’),(3,’auth’,’permissio
/*!40000 ALTER TABLE ‘django_content_type‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘django_migrations‘
--

DROP TABLE IF EXISTS ‘django_migrations‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘django_migrations‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘app‘ varchar(255) NOT NULL,
  ‘name‘ varchar(255) NOT NULL,
  ‘applied‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=80 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘django_migrations‘
--

LOCK TABLES ‘django_migrations‘ WRITE;
/*!40000 ALTER TABLE ‘django_migrations‘ DISABLE KEYS */;
INSERT INTO ‘django_migrations‘ VALUES (1,’contenttypes’,’0001_initial’,’2026-01-29 05:12:42.662818’),(
/*!40000 ALTER TABLE ‘django_migrations‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘django_session‘
--

DROP TABLE IF EXISTS ‘django_session‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘django_session‘ (
  ‘session_key‘ varchar(40) NOT NULL,
  ‘session_data‘ longtext NOT NULL,
  ‘expire_date‘ datetime(6) NOT NULL,
  PRIMARY KEY (‘session_key‘),
  KEY ‘django_session_expire_date_a5c62663‘ (‘expire_date‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘django_session‘
--
```

```
LOCK TABLES ‘django_session‘ WRITE;
/*!40000 ALTER TABLE ‘django_session‘ DISABLE KEYS */;
INSERT INTO ‘django_session‘ VALUES (’04s85cfr6u7tyqhon63dg4qm9ymdihtt’,’.eJxVjEEOwiAQRe_C2hCgQAeX7j0Dm
/*!40000 ALTER TABLE ‘django_session‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_activity_log‘
--

DROP TABLE IF EXISTS ‘ms_activity_log‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_activity_log‘ (
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘description‘ text NOT NULL,
  ‘date‘ datetime NOT NULL,
  ‘staffid‘ int DEFAULT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=80 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_activity_log‘
--

LOCK TABLES ‘ms_activity_log‘ WRITE;
/*!40000 ALTER TABLE ‘ms_activity_log‘ DISABLE KEYS */;
INSERT INTO ‘ms_activity_log‘ VALUES (1,’Failed Login Attempt [Email: admin@foogletech.com, Is Staff Me
/*!40000 ALTER TABLE ‘ms_activity_log‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_announcements‘
--

DROP TABLE IF EXISTS ‘ms_announcements‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_announcements‘ (
  ‘announcementid‘ int NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(191) NOT NULL,
  ‘message‘ text,
  ‘showtousers‘ int NOT NULL DEFAULT ’0’,
  ‘showtostaff‘ int NOT NULL DEFAULT ’0’,
  ‘showname‘ int NOT NULL DEFAULT ’1’,
  ‘dateadded‘ datetime NOT NULL,
  ‘userid‘ varchar(100) NOT NULL,
  PRIMARY KEY (‘announcementid‘)
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_announcements‘
--

LOCK TABLES ‘ms_announcements‘ WRITE;
/*!40000 ALTER TABLE ‘ms_announcements‘ DISABLE KEYS */;
INSERT INTO ‘ms_announcements‘ VALUES (1,’Today\’s Meeting’,’Today\’s discussion about how the CRM work
/*!40000 ALTER TABLE ‘ms_announcements‘ ENABLE KEYS */;
UNLOCK TABLES;
```

```
--
-- Table structure for table ‘ms_goals‘
--

DROP TABLE IF EXISTS ‘ms_goals‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_goals‘ (
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘subject‘ varchar(191) NOT NULL,
  ‘description‘ text NOT NULL,
  ‘start_date‘ date NOT NULL,
  ‘end_date‘ date NOT NULL,
  ‘goal_type‘ int NOT NULL DEFAULT ’0’,
  ‘contract_type‘ int NOT NULL DEFAULT ’0’,
  ‘achievement‘ int NOT NULL DEFAULT ’0’,
  ‘notify_when_fail‘ int NOT NULL DEFAULT ’0’,
  ‘notify_when_achieve‘ int NOT NULL DEFAULT ’0’,
  ‘notified‘ int NOT NULL DEFAULT ’0’,
  ‘staff_id‘ int NOT NULL DEFAULT ’0’,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_goals‘
--

LOCK TABLES ‘ms_goals‘ WRITE;
/*!40000 ALTER TABLE ‘ms_goals‘ DISABLE KEYS */;
INSERT INTO ‘ms_goals‘ VALUES (1,’SmartTech’,’Done the management properly.’,’2026-03-17’,’2026-06-16’,
/*!40000 ALTER TABLE ‘ms_goals‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_knowledge_base‘
--

DROP TABLE IF EXISTS ‘ms_knowledge_base‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_knowledge_base‘ (
  ‘articleid‘ int NOT NULL AUTO_INCREMENT,
  ‘articlegroup‘ int NOT NULL,
  ‘subject‘ mediumtext NOT NULL,
  ‘description‘ text NOT NULL,
  ‘slug‘ mediumtext NOT NULL,
  ‘active‘ tinyint NOT NULL,
  ‘datecreated‘ datetime NOT NULL,
  ‘article_order‘ int NOT NULL DEFAULT ’0’,
  ‘staff_article‘ int NOT NULL DEFAULT ’0’,
  PRIMARY KEY (‘articleid‘)
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_knowledge_base‘
--

LOCK TABLES ‘ms_knowledge_base‘ WRITE;
/*!40000 ALTER TABLE ‘ms_knowledge_base‘ DISABLE KEYS */;
INSERT INTO ‘ms_knowledge_base‘ VALUES (1,1,’Getting Started’,’Welcome to the Knowledge Base. Add your
/*!40000 ALTER TABLE ‘ms_knowledge_base‘ ENABLE KEYS */;
```

```
UNLOCK TABLES;

--
-- Table structure for table ‘ms_knowledge_base_groups‘
--

DROP TABLE IF EXISTS ‘ms_knowledge_base_groups‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_knowledge_base_groups‘ (
  ‘groupid‘ int NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(191) NOT NULL,
  ‘group_slug‘ text,
  ‘description‘ mediumtext,
  ‘active‘ tinyint NOT NULL,
  ‘color‘ varchar(10) DEFAULT ’#28B8DA’,
  ‘group_order‘ int DEFAULT ’0’,
  PRIMARY KEY (‘groupid‘)
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_knowledge_base_groups‘
--

LOCK TABLES ‘ms_knowledge_base_groups‘ WRITE;
/*!40000 ALTER TABLE ‘ms_knowledge_base_groups‘ DISABLE KEYS */;
INSERT INTO ‘ms_knowledge_base_groups‘ VALUES (1,’General’,’general’,’General knowledge base articles’,
/*!40000 ALTER TABLE ‘ms_knowledge_base_groups‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_roles‘
--

DROP TABLE IF EXISTS ‘ms_roles‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_roles‘ (
  ‘roleid‘ int NOT NULL AUTO_INCREMENT,
  ‘name‘ varchar(100) NOT NULL,
  ‘permissions‘ text,
  PRIMARY KEY (‘roleid‘)
) ENGINE=InnoDB AUTO_INCREMENT=15 DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_roles‘
--

LOCK TABLES ‘ms_roles‘ WRITE;
/*!40000 ALTER TABLE ‘ms_roles‘ DISABLE KEYS */;
INSERT INTO ‘ms_roles‘ VALUES (1,’User’,’Not Accessible ’),(2,’User’,’Not Accessible ’),(3,’User’,’Not
/*!40000 ALTER TABLE ‘ms_roles‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_staff‘
--

DROP TABLE IF EXISTS ‘ms_staff‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
```

```
CREATE TABLE ‘ms_staff‘ (
  ‘staffid‘ int NOT NULL AUTO_INCREMENT,
  ‘email‘ varchar(100) NOT NULL,
  ‘firstname‘ varchar(50) NOT NULL,
  ‘lastname‘ varchar(50) NOT NULL,
  ‘facebook‘ mediumtext,
  ‘linkedin‘ mediumtext,
  ‘phonenumber‘ varchar(30) DEFAULT NULL,
  ‘skype‘ varchar(50) DEFAULT NULL,
  ‘password‘ varchar(250) NOT NULL,
  ‘datecreated‘ datetime NOT NULL,
  ‘profile_image‘ varchar(191) DEFAULT NULL,
  ‘last_ip‘ varchar(40) DEFAULT NULL,
  ‘last_login‘ datetime DEFAULT NULL,
  ‘last_activity‘ datetime DEFAULT NULL,
  ‘last_password_change‘ datetime DEFAULT NULL,
  ‘new_pass_key‘ varchar(32) DEFAULT NULL,
  ‘new_pass_key_requested‘ datetime DEFAULT NULL,
  ‘admin‘ int NOT NULL DEFAULT ’0’,
  ‘role‘ int DEFAULT NULL,
  ‘active‘ int NOT NULL DEFAULT ’1’,
  ‘default_language‘ varchar(40) DEFAULT NULL,
  ‘direction‘ varchar(3) DEFAULT NULL,
  ‘media_path_slug‘ varchar(191) DEFAULT NULL,
  ‘is_not_staff‘ int NOT NULL DEFAULT ’0’,
  ‘hourly_rate‘ decimal(15,2) NOT NULL DEFAULT ’0.00’,
  ‘two_factor_auth_enabled‘ tinyint(1) DEFAULT ’0’,
  ‘two_factor_auth_code‘ varchar(100) DEFAULT NULL,
  ‘two_factor_auth_code_requested‘ datetime DEFAULT NULL,
  ‘email_signature‘ text,
  PRIMARY KEY (‘staffid‘)
) ENGINE=InnoDB AUTO_INCREMENT=8 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_staff‘
--

LOCK TABLES ‘ms_staff‘ WRITE;
/*!40000 ALTER TABLE ‘ms_staff‘ DISABLE KEYS */;
INSERT INTO ‘ms_staff‘ VALUES (1,’admin@example.com’,’Admin’,’User’,NULL,NULL,NULL,NULL,’’,’2026-03-16
/*!40000 ALTER TABLE ‘ms_staff‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_surveys‘
--

DROP TABLE IF EXISTS ‘ms_surveys‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_surveys‘ (
  ‘surveyid‘ int NOT NULL AUTO_INCREMENT,
  ‘subject‘ mediumtext NOT NULL,
  ‘slug‘ mediumtext NOT NULL,
  ‘description‘ text NOT NULL,
  ‘viewdescription‘ text,
  ‘datecreated‘ datetime NOT NULL,
  ‘redirect_url‘ varchar(100) DEFAULT NULL,
  ‘send‘ tinyint(1) NOT NULL DEFAULT ’0’,
  ‘onlyforloggedin‘ int DEFAULT ’0’,
  ‘fromname‘ varchar(100) DEFAULT NULL,
  ‘iprestrict‘ tinyint(1) NOT NULL,
```

```
  ‘active‘ tinyint(1) NOT NULL DEFAULT ’1’,
  ‘hash‘ varchar(32) NOT NULL,
  PRIMARY KEY (‘surveyid‘)
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_surveys‘
--

LOCK TABLES ‘ms_surveys‘ WRITE;
/*!40000 ALTER TABLE ‘ms_surveys‘ DISABLE KEYS */;
INSERT INTO ‘ms_surveys‘ VALUES (1,’Feedback’,’feedback’,’asd’,’asdsad’,’2019-07-12 16:56:30’,’’,0,0,’’
/*!40000 ALTER TABLE ‘ms_surveys‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_tickets_pipe_log‘
--

DROP TABLE IF EXISTS ‘ms_tickets_pipe_log‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_tickets_pipe_log‘ (
  ‘id‘ int NOT NULL AUTO_INCREMENT,
  ‘date‘ datetime NOT NULL,
  ‘email_to‘ varchar(100) NOT NULL,
  ‘name‘ varchar(191) NOT NULL,
  ‘subject‘ varchar(191) NOT NULL,
  ‘message‘ mediumtext NOT NULL,
  ‘email‘ varchar(100) NOT NULL,
  ‘status‘ varchar(100) NOT NULL,
  PRIMARY KEY (‘id‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_tickets_pipe_log‘
--

LOCK TABLES ‘ms_tickets_pipe_log‘ WRITE;
/*!40000 ALTER TABLE ‘ms_tickets_pipe_log‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘ms_tickets_pipe_log‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_user_profiles‘
--

DROP TABLE IF EXISTS ‘ms_user_profiles‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_user_profiles‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘user_id‘ int DEFAULT NULL,
  ‘user_name‘ varchar(100) NOT NULL,
  ‘user_type‘ int DEFAULT NULL,
  ‘business_name‘ varchar(100) NOT NULL,
  ‘user_email‘ varchar(254) NOT NULL,
  ‘contact_number‘ varchar(20) NOT NULL,
  ‘password‘ varchar(255) NOT NULL,
  ‘address‘ longtext NOT NULL,
  ‘city‘ varchar(100) DEFAULT NULL,
```

```
  ‘created_by‘ int DEFAULT NULL,
  ‘updated_by‘ int DEFAULT NULL,
  ‘created_datetime‘ datetime(6) DEFAULT NULL,
  ‘updated_datetime‘ datetime(6) DEFAULT NULL,
  PRIMARY KEY (‘id‘),
  UNIQUE KEY ‘user_email‘ (‘user_email‘)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_user_profiles‘
--

LOCK TABLES ‘ms_user_profiles‘ WRITE;
/*!40000 ALTER TABLE ‘ms_user_profiles‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘ms_user_profiles‘ ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table ‘ms_user_token‘
--

DROP TABLE IF EXISTS ‘ms_user_token‘;
/*!40101 SET @saved_cs_client     = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE ‘ms_user_token‘ (
  ‘id‘ bigint NOT NULL AUTO_INCREMENT,
  ‘access_token‘ longtext NOT NULL,
  ‘refresh_token‘ longtext NOT NULL,
  ‘created_at‘ datetime(6) NOT NULL,
  ‘user_id‘ bigint NOT NULL,
  PRIMARY KEY (‘id‘),
  KEY ‘ms_user_token_user_id_e6163f22_fk_ms_user_profiles_id‘ (‘user_id‘),
  CONSTRAINT ‘ms_user_token_user_id_e6163f22_fk_ms_user_profiles_id‘ FOREIGN KEY (‘user_id‘) REFERENCES
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table ‘ms_user_token‘
--

LOCK TABLES ‘ms_user_token‘ WRITE;
/*!40000 ALTER TABLE ‘ms_user_token‘ DISABLE KEYS */;
/*!40000 ALTER TABLE ‘ms_user_token‘ ENABLE KEYS */;
UNLOCK TABLES;
/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;
/*!40014 SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;
/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;

-- Dump completed on 2026-03-18 17:08:32
```