

# 1) What is HTML, usage, versions, structure

---

## 1. Definition:

- HTML stands for HyperText Markup Language.
- A markup language (not a programming language) used to structure web pages.
- Uses tags (like `<h1>`, `<p>`, `<a>`, etc.) to annotate content.

## 2. Usage:

- Defines the skeleton/framework of a webpage.
- Structures content: headings, paragraphs, lists, images, links, forms.
- Embeds media: images, audio, video, canvas graphics.
- Defines semantics: this part is a navigation menu, this part is an article, etc.
- Works with CSS (for styling) and JavaScript (for interactivity).

## 3. Versions:

- HTML 1.0 (~1991): very basic content only.
- HTML 2.0 (~1995): added forms, tables.
- HTML 3 / 3.2 (~1997): more layout features.
- HTML 4 / 4.01 (~1999): integration with CSS, scripting, multimedia.
- HTML5 (~2014 onward): major update – new semantic tags, built-in media support, modern APIs. Current standard.

## 4. Basic Structure of an HTML Document:

```
<!DOCTYPE html> <html lang="en"> <head> <meta charset="UTF-8" /> <title>Page  
Title</title> </head> <body> <!-- Visible content goes here --> <h1>Main Heading</h1>  
<p>This is a paragraph.</p> <a href="https://example.com">Link example</a> </body>  
</html> `` - <!DOCTYPE html> : declares HTML5 document type. - <html> ... </html> : root  
element. - <head> ... </head> : metadata (title, charset, links to CSS/js). - <body> ...  
</body> : actual content visible to users.
```

## 5. Good Practices:

- Use semantic tags when possible: `<header>`, `<footer>`, `<nav>`, `<article>`, `<section>` etc.
- Ensure proper nesting of tags.
- Use the correct language attribute (lang) on `<html>` for accessibility.
- Use `<meta charset="UTF-8" />` to support international characters.

- Keep HTML structure separated from CSS (styling) and JavaScript (behavior) for clarity and maintainability.

6. Why it matters:

- Good HTML structure improves browser rendering, accessibility, SEO, and maintainability.
- As a developer, starting with clean HTML makes it easier to build larger applications (with CSS/JS frameworks) later.

## **2) Usage of <img>, attributes (src, alt, width, height), accessibility**

---

1. Purpose:

- The <img> element embeds an image into a web page.
- It links to an image file via a URL/path using the src attribute.
- It does not require a closing tag (in HTML5).

2. Key Attributes:

a) src

- Specifies the image source (path or URL).
- Example: src="images/photo.jpg"

b) alt

- Specifies alternate text describing the image.
- If the image fails to load or for screen-readers.
- Example: alt="A mountain peak at sunrise"

c) width

- Specifies the display width (in pixels) of the image.
- Helps reserve layout space before loading.
- Example: width="800"

d) height

- Specifies the display height (in pixels) of the image.
- Example: height="450"

3. Example Usage:

```
  

```

#### 4. Accessibility Best Practices:

- Always include the alt attribute (either meaningful or empty) for <img> elements.
- For meaningful images: alt should describe the image's purpose/content.
- For purely decorative images: use alt="" so assistive tech skips it.
- Use width and height to avoid layout shifts and improve experience.
- Optimize image files for size and format to improve performance.

#### 5. Performance & Responsiveness Tips:

- Don't use oversized image files just scaled down via HTML attributes — resize the actual image file.
- Use width/height attributes for layout hints; use CSS for responsive scaling (e.g., max-width:100%).
- Use relative URLs for images within your project.
- For advanced scenarios, consider using srcset/sizes for different resolutions or formats.

#### 6. Why It Matters:

- Proper <img> usage supports accessibility, performance, and layout stability.
- A good user experience includes images that load gracefully, don't cause layout jumps, and are accessible to everyone.

### 3) Structure (<table>, <tr>, <td>, <th>), rowspan/colspan, styling, accessibility

---

#### ① Table Structure:

- <table>: Defines the table.
- <tr>: Table row.
- <td>: Table data cell.
- <th>: Table header (bold, centered by default).

#### ② Example:

```
<table border="1">
  <tr><th>Subject</th><th>Marks</th></tr>
  <tr><td>Math</td><td>95</td></tr>
</table>
```

#### ③ Rowspan & Colspan:

- rowspan → merges cells vertically.
- colspan → merges cells horizontally.

#### Example:

```
<td rowspan="2">Merged</td>
<td colspan="2">Merged</td>
```

#### ④ Styling Tables:

- Use CSS for borders, background, and alignment.  
table { border-collapse: collapse; width: 50%; }  
th, td { border: 1px solid #333; padding: 8px; }

#### ⑤ Accessibility:

- <caption> for table title.
- <th scope="col"> or <th scope="row"> for screen readers.
- Helps users with disabilities navigate tables.

## 4) Input types, labels, validations, form actions, GET vs POST

---

### HTML Forms — Input Types, Labels, Validations, Actions, and Methods

#### ① Input Types:

- <input type="text"> → Text input
- <input type="password"> → Hidden characters
- <input type="email"> → Validates email
- <input type="number"> → Numeric input
- <input type="date"> → Date picker
- <input type="radio"> → One choice from many
- <input type="checkbox"> → Multiple selections
- <input type="file"> → Upload files
- <input type="submit"> → Submit button
- <input type="reset"> → Clear all fields

#### ② Labels:

- <label for="id">Text</label>
- Connects label to input for accessibility.

Example:

```
<label for="username">Username:</label>  
<input id="username" type="text" name="username">
```

#### ③ Validations:

- required → Field must be filled.
- pattern → Restrict input format using regex.
- minlength / maxlength → Control text length.
- type="email" → Checks valid email.
- min / max → Restrict numeric or date range.

Example:

`<input type="text" pattern="[A-Za-z]{3,10}" required>`

#### ④ Form Actions:

`<form action="/submit" method="POST">`

→ action defines where to send data.

→ method defines how data is sent.

#### ⑤ GET vs POST:

GET:

- Data visible in URL
- Used for searches
- Less secure

POST:

- Data hidden from URL
- Used for login, registration
- More secure and allows larger data


Example:

`<form action="/search" method="GET">`

`<form action="/register" method="POST">`

## 5) `<header>`, `<nav>`, `<article>`, `<footer>`, SEO importance

---

 Topic: Semantic HTML — `<header>`, `<nav>`, `<article>`, `<footer>` and SEO Importance

### ♦ What is Semantic HTML?

Semantic HTML uses meaningful tags that describe the purpose of content. It improves accessibility, code clarity, and SEO ranking.

### ♦ Elements Overview

#### ① `<header>`

- Represents the top or introductory part of a webpage.
- Commonly contains site title, logo, and navigation.



Example:

`<header>`

`<h1>My Website</h1>`

`</header>`

#### ② `<nav>`

- Defines a section of navigation links.
- Helps users move between different parts of the site.

🌱 Example:

```
<nav>
  <a href="#home">Home</a> | <a href="#about">About</a>
</nav>
```

### 3 <article>

- Represents self-contained, reusable content.
- Used for blog posts, news articles, etc.

🌱 Example:

```
<article>
  <h2>My Blog Post</h2>
  <p>Content goes here...</p>
</article>
```

### 4 <footer>

- Represents the bottom section of a webpage.
- Contains copyright, contact, and social links.

🌱 Example:

```
<footer>
  <p>&copy; 2025 My Website</p>
</footer>
```

#### ♦ SEO Importance

- Semantic tags help search engines understand content structure.
- Improves accessibility for screen readers.
- Increases ranking potential by emphasizing key sections.

🎯 Using semantic HTML = Better SEO + Better Accessibility + Cleaner Code.

# 1) Topic: CSS Selectors and Specificity

- ♦ What are Selectors?

Selectors are patterns used to target and style specific HTML elements.

- ♦ Types of Selectors:

## 1) Element Selector

- Targets elements by tag name.
- Example:  
`p { color: blue; }`

## 2) Class Selector (.)

- Targets elements with a specific class.
- Reusable across multiple elements.
- Example:  
`.highlight { background-color: yellow; }`

## 3) ID Selector (#)

- Targets one unique element with a specific ID.
- Example:  
`#header { text-align: center; }`

## 4) Attribute Selector

- Targets elements based on their attributes.
- Example:  
`input[type="text"] { border: 1px solid black; }`

- ♦ Specificity (Priority Order)

- Element selector → Lowest (1)
- Class/Attribute selector → Medium (10)
- ID selector → High (100)
- Inline style → Highest (1000)

### Rule:

If two rules conflict → the one with higher specificity wins.

### Summary:

- Element: Targets by tag name.
- Class: Targets multiple elements with same class.
- ID: Targets a unique element.
- Attribute: Targets based on HTML attribute.
- Specificity controls which style is applied when conflicts occur.

## 2) Topic: CSS Box Model — Content, Padding, Border, Margin, Box-Sizing



### ♦ Box Model Overview:

Every element in CSS is a rectangular box composed of:

1. Content
2. Padding
3. Border
4. Margin

### ♦ Content:

- The actual text, image, or data inside the element.
- Defined using width and height.

✚ Example:

```
div { width: 200px; height: 100px; }
```

### ♦ Padding:

- Space between content and border (inner spacing).
- Increases element's total size.

✚ Example:

```
div { padding: 20px; }
```

### ♦ Border:

- A visible outline around the element.
- Sits between padding and margin.

✚ Example:

```
div { border: 2px solid black; }
```

### ♦ Margin:

- Space outside the border (outer spacing).
- Creates distance between elements.

✚ Example:

```
div { margin: 30px; }
```

### ♦ Box-Sizing:

- Defines how width and height are calculated.
  - content-box → width = content only (default)
  - border-box → width = content + padding + border

✚ Example:

```
div {  
  width: 200px;  
  padding: 20px;  
  border: 10px solid black;  
  box-sizing: border-box;  
}
```



}

#### ✓ Summary:

- Padding, Border, Margin add space.
- box-sizing: border-box is preferred — it simplifies layout control.
- The box model determines how elements occupy space on a page.

## 3) CSS Flexbox & Grid Notes

- ♦ Flexbox → 1D layout system (row/column)
  - Container: `display: flex`
  - `justify-content` → Horizontal alignment
    - `flex-start` | `flex-end` | `center` | `space-between` | `space-around` | `space-evenly`
  - `align-items` → Vertical alignment
    - `stretch` | `flex-start` | `flex-end` | `center` | `baseline`
  - Common combo:
    - `display: flex;`
    - `justify-content: center;`
    - `align-items: center;`
- ♦ CSS Grid → 2D layout system (rows + columns)
  - Container: `display: grid`
  - `grid-template-columns` → Define columns
    - Example: `grid-template-columns: 1fr 1fr 1fr;`
  - `grid-template-rows` → Define rows
  - `gap` → Space between rows/columns
  - `place-items: center` → Center items in both axes
- ♦ Flexbox vs Grid
  - Flexbox → Align items in one direction
  - Grid → Align items in both directions
  - Use Flexbox for smaller UI components, Grid for full-page structure

## 4) CSS Responsive Design — Media Queries, Relative Units, Mobile-First Design

### ① Media Queries:

- Used to apply styles based on screen size, resolution, or device type.
- Syntax:
  - `@media (max-width: 600px) { ... }`
- Common breakpoints:
  - Phones: `max-width: 480px`
  - Tablets: `max-width: 768px`
  - Laptops: `max-width: 1024px`

- Desktops: max-width: 1200px+

## ② Relative Units:

- Help create scalable layouts.
- % → Relative to parent size
- em → Relative to element font size
- rem → Relative to root (html) font size
- vw → % of viewport width
- vh → % of viewport height

## ③ Mobile-First Design:

- Design for small screens first.
- Use min-width media queries to scale up.
- Example:  
Base (mobile) → Tablet (768px+) → Desktop (1024px+)

## ✓ Best Practices:

- Use rem for consistent font scaling.
- Use vw/vh for full-width/height layouts.
- Always start mobile-first, then expand.
- Test on different devices to ensure usability.

## 1) Bootstrap: History & Purpose Notes

### 1. Definition:

- Bootstrap is a free, open-source front-end framework (HTML/CSS/JS) for building responsive, mobile-first websites.

### 2. History:

- Mid 2010: Created internally at Twitter by Mark Otto & Jacob Thornton.
- Originally called Twitter Blueprint, later renamed Bootstrap.
- August 2011: Released open-source on GitHub.
- Version 2: Added responsive grid & more components.
- Version 3: Emphasized mobile-first design.
- Version 4+: Major rewrite (Sass, flexbox, dropped older browsers).
- Used widely online; part of many websites & UI toolkits.

### 3. Purpose / Why use it:

- Speeds up UI development (ready components, grid system).
- Brings consistency to UI across pages or teams.
- Built for responsive layouts across devices.
- Provides many reusable components (buttons, navbars, forms, etc).
- Strong community, documentation, templates.

### 4. When to use:

- Good for rapid development, standard websites, dashboards.
- Great when multiple developers/designers need consistency.
- Ideal when responsive behaviour is required out-of-the-box.

### 5. Things to weigh:

- Customisation may require overriding many defaults.
- May include more than needed for small or highly customised designs.
- Alternatives exist if you want ultra-lightweight or fully custom UI.

## 2) Bootstrap: Setup Notes

### 1. What is Bootstrap setup?

- Including Bootstrap means adding its CSS and JS into your HTML so you can use its components and grid.

### 2. Methods:

#### a) CDN (Content Delivery Network)

- Use `<link>` in `<head>` for CSS.
- Use `<script>` before `</body>` for JS (if needed).
- Fast, no download required, good for quick setup.

- Example:

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.2.3/dist/css/bootstrap.min.css"
      rel="stylesheet" integrity="..." crossorigin="anonymous">
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.2.3/dist/js/bootstrap.bundle.min.js"
integrity="..." crossorigin="anonymous"></script>
```

#### b) Local / Download

- Download Bootstrap CSS/JS files into your project (css/, js/ folders).
- Include them via relative paths.
- Allows customization and offline use.

### 3. Quick Start (CDN):

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Bootstrap Demo</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.x/dist/css/bootstrap.min.css"
rel="stylesheet" integrity="..." crossorigin="anonymous">
</head>
<body>
  <h1 class="text-center">Hello, Bootstrap!</h1>
  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.x/dist/js/bootstrap.bundle.min.js"
integrity="..." crossorigin="anonymous"></script>
</body>
</html>
```

### 4. Why choose which method?

- Use CDN: Quick, standard UI, minimal work.
- Use Local: Custom theme, offline, full control.

### 5. Important notes:

- Always include the meta viewport tag for mobile responsiveness.
- Place CSS <link> in <head>, JS <script> just before closing </body>.
- For Bootstrap 5, you do *not* need jQuery; bundle includes required dependencies.

## 3) Bootstrap Grid System, Responsive Design, and Components

### 1) Grid System:

- Layout based on 12 columns.
- Containers hold rows, rows hold columns.
- .container → Fixed width
- .container-fluid → Full width
- Use .row and .col classes to create layout.
- Responsive column prefixes:  
.col- (mobile), .col-sm-, .col-md-, .col-lg-, .col-xl-

Example:

```
<div class="container">  
  <div class="row">  
    <div class="col-md-6">Half width on tablets+</div>  
    <div class="col-md-6">Half width on tablets+</div>  
  </div>  
</div>
```

### 2) Responsive Design:

- Makes pages adjust to different screen sizes.
- Bootstrap is mobile-first.
- Key classes:  
.d-none / .d-md-block → Hide/show by screen size  
.img-fluid → Makes images responsive
- Uses breakpoints and media queries internally.

### 3) Components:

- Prebuilt UI elements like buttons, cards, navbars, modals.
- Reduces coding effort and ensures consistent design.

Common Components:

Buttons: `<button class="btn btn-primary">`

Alerts: `<div class="alert alert-success">`

Cards: `<div class="card"><div class="card-body">...</div></div>`

Navbar: `<nav class="navbar navbar-expand-lg navbar-light bg-light">`

### Summary:

- Grid → Structure (rows & columns)
- Responsive design → Adjusts to screens
- Components → Ready-made elements to build UI quickly