

Getting Started

What is Segment?
How Segment Works
Getting Started Guide
A Basic Segment Installation
Planning a Full Installation
A Full Segment Installation
Sending Data to Destinations
Testing and Debugging
What's Next
Use Cases

Guides

Connections

Unify

Engage

Privacy

Protocols

Segment App

API

Partners

Glossary

Config API

Help

Getting started

From your workspace's Destination catalog page search for "Drip (Actions)".

Select Drip (Actions) and click Add Destination.

3elect an existing Source to connect to Drip (Actions).

So to the Drip dashboard

5. the Settings tab, select the User Settings, find and copy the API key at the bottom of the page.

a terminal, run echo <your-api-key>: | base64 to encode the API key.

Enter the encoded API Key in the Drip destination settings in Segment.

Sour account ID is a seven digit number that can be found in the address bar of your browser when you are logged into Drip. It is the number after https://www.getdrip.com/.

9nter the **Account ID** in the Drip destination settings in Segment.

Destination Settings

SETTING	DESCRIPTION
Account ID	Required. Account ID for your Drip account. You can find this in your Drip account settings.
API Key	Required. API key for your Drip account. You can find this in your Drip account settings.

Available Presets

Drip (Actions) has the following presets:

PRESET NAME	TRIGGER	DEFAULT ACTION
Track event	Event type = "track"	Track Event
Identify	Event type = "identify"	Identify

Available Actions

Build your own Mappings. Combine supported triggers with the following Drip-supported actions:



Mapping limits per destination

Individual destination instances have support a maximum of 50 mappings.

Track Event

Identify

Track Event

Send track() events to Drip

Track Event is a **Cloud** action. The default Trigger is: type = "track"

Click to show / hide fields

FIELD	DESCRIPTION
Action *	Type: STRING The name of the action.
Email Address *	Type: STRING The person's email address.
Properties	Type: OBJECT Additional properties associated with the event.

Identify

Identify person in Drip

Identify is a **Cloud** action. The default Trigger is: type = "identify"

Click to show / hide fields

FIELD	DESCRIPTION
Custom fields	Type: OBJECT
	Custom fields to add to a person's profile. Non string values will be stringified.
Email Address *	Type: STRING
	The person's email address.
IP Address	Type: STRING
	The person's ip address.
SMS Number	Type: STRING
	The person's sms number.
Status	Type: STRING
	The person's subscription status.
Status Updated At	Type: DATETIME
	The timestamp associated with the update to a person's status.
Tags	Type: STRING
	Comma delimited list of tags to add to a person's profile. e.g. "tag1,tag2".
Timezone	Type: STRING
	The person's timezone.
Enable Batching?	Type: BOOLEAN
	When enabled, Segment will send events in batches.

For more information about developing with Drip, check out their documentation.

This page was last modified: 13 Dec 2024

Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

Visit our Support page

Help improve these docs!

Edit this page

Request docs change

Was this page helpful?



Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

Create free account

