



## Getting Started

What is Segment?  
[How Segment Works](#)  
Getting Started Guide  
A Basic Segment Installation  
Planning a Full Installation  
A Full Segment Installation  
Sending Data to Destinations  
Testing and Debugging  
What's Next  
Use Cases

## Guides

## Connections

## Unify

## Engage

## Privacy

## Protocols

## Segment App

## API

## Partners

## Glossary

## Config API

## Help

Server

Server

## Getting Started

Segment allows you to track events directly into Monetate, and create, test, deploy, and measure personalized marketing campaigns.

### Client-Side

Because the Monetate destination needs to be on the page right away, Segment can't add it for you. That means you'll need to put the Monetate JavaScript snippet on the page. Pop over to Monetate and in Settings > destination > Tag you'll find their snippet.

To get started with Monetate and Segment, just enable the Monetate destination on your Segment **Destinations page**. If you've already copied the Monetate script tag onto your page, you're ready to go!

Copy and paste the code provided immediately after your opening `<head>` tag.

The script looks something like this:

```
<script type="text/javascript">
var monetateT = new Date().getTime();
(function() {
  var p = document.location.protocol;
  if (p == "http:" || p == "https:") {
    var m = document.createElement("script"); m.type = "text/javascript"; m.src = (p == "https:" ? "https://" :
"http://" ) + "e.monetate.net/js/2/[siteId]/p/[domain]/entry.js";
    var e = document.createElement("div"); e.appendChild(m); document.write(e.innerHTML);
  }
})();
</script>
```

Include this snippet on every page you want to run experiments on and track as a goal. This snippet will not change. This separate script is required because Monetate alters the page, if it were loaded async the alterations may cause unappealing results.

## Page

When you call the `page` method with a name and category, we call the 'setPageType' method in Monetate. This allows you to run your campaigns on different page types.

## Track

When you call the `track` method with the event names Viewed Product, Added Product, Order Completed from our [e-commerce API](#) we will call the corresponding `addItem`s, `addReviewRows`, `addConversionRows` in Monetate if the Retail option is not checked in settings, and `addProducts`, `addCartRows`, `addPurchaseRows` if it is. Other event names will not be forwarded to Monetate.

## Settings

Segment lets you change these destination settings from the Segment app without having to touch any code.

SETTING	DESCRIPTION
Retail	<code>boolean</code> , defaults to <code>FALSE</code> . Monetate has two API's Retail and General, Enable this setting to use Monetate's Retail API.

This page was last modified: 15 Jul 2022

## Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

[Visit our Support page](#)

## Help improve these docs!

[Edit this page](#)

[Request docs change](#)

## Was this page helpful?

☐ Yes

☐ No

# Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

Request Demo

or

Create free account

© 2025 Segment.io, Inc.

[Privacy](#)

[Terms](#)

[Website Data Collection Preferences](#)

