



## Getting Started

What is Segment?  
[How Segment Works](#)  
Getting Started Guide  
A Basic Segment Installation  
Planning a Full Installation  
A Full Segment Installation  
Sending Data to Destinations  
Testing and Debugging  
What's Next  
Use Cases

## Guides

## Connections

## Unify

## Engage

## Privacy

## Protocols

## Segment App

## API

## Partners

## Glossary

## Config API

## Help

Go to **1flow.ai > Settings > Project Settings**, copy the 1Flow project key, and paste it into the Destination Settings in Segment.

Depending on the mobile source you've selected, include 1Flow's library by adding the following lines to your dependency configuration.

## Adding the dependency

### Through Xcode

In the Xcode **File** menu, click **Add Packages**. You'll see a dialog where you can search for Swift packages. In the search field, enter the URL to this repository.

```
https://github.com/1Flow-Inc/segment-1flow-ios.git
```

You'll then have the option to pin to a version, or specific branch, as well as which project in your workspace to add it to. Once you've made your selections, click **Add Package**.

## Through Package.swift

Open your Package.swift file and add the following to the `dependencies` section:

```
.package(  
    name: "Segment",  
    url: "https://github.com/1Flow-Inc/segment-1flow-ios.git",  
    from: "1.0.0"  
)
```

## Using the Plugin in your app

Open the file where you set up and configure the Analytics-Swift library. Add this plugin to the list of imports.

```
import Segment  
import SegmentOneFlow // <-- Add this line
```

Just under your Analytics-Swift library setup, call `analytics.add(plugin: ...)` to add an instance of the plugin to the Analytics timeline.

```
let analytics = Analytics(configuration: Configuration(writeKey: "<YOUR WRITE KEY>")  
    .flushAt(3)  
    .trackApplicationLifecycleEvents(true))  
analytics.add(plugin: OneFlowDestination())
```

## Identify

If you're not familiar with the Segment Specs, take a look to understand what the [Identify method](#) does. An example call would look like:

```
analytics.identify(userId: "peter@example.com", traits: [  
    "name": "Peter Gibbons",  
    "email": "peter@example.com",  
    "mobile": 1234567890  
)
```

The Segment identify method is equivalent to `logUser` of 1Flow. `userId` will be `userID` and `traits` will be `userDetails`.

## Track

If you're not familiar with the Segment Specs, take a look to understand what the [Track method](#) does. An example call would look like:

```
analytics.track(name: "ButtonClicked")
```

Any value passed in `name`, will be `eventName` and if you have passed any event property, then it will be event parameters.

## Screen

Send [Screen](#) calls to record which mobile app screens users have viewed. For example:

```
analytics.screen(title: "Home")
```

Segment sends Screen calls to 1Flow as a `screen_[name]` event (or `screen_view` if a screen name isn't provided).

## Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

[Visit our Support page](#)

## Help improve these docs!

 [Edit this page](#)

 [Request docs change](#)

## Was this page helpful?

 [Yes](#)

 [No](#)

## Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

[Request Demo](#)

or

[Create free account](#)

© 2025 Segment.io, Inc.

[Privacy](#)

[Terms](#)

[Website Data Collection Preferences](#)

