



Getting Started

What is Segment?
[How Segment Works](#)
Getting Started Guide
A Basic Segment Installation
Planning a Full Installation
A Full Segment Installation
Sending Data to Destinations
Testing and Debugging
What's Next
Use Cases

Guides

Connections

Unify

Engage

Privacy

Protocols

Segment App

API

Partners

Glossary

Config API

Help

Getting Started

- 1 From the Destinations catalog page in the Segment App, click **Add Destination**.
- 2 Search for **2mee** in the Destinations Catalog and it.
- 3 Click **Configure 2mee**.
- 4 Choose which Source should send data to the 2mee destination.
- 5 Go to 2mee and copy the [API Key and Application ID](#) from the 2mee Dashboard.
- 6 Go back to Segment and paste the API Key and Application ID you just copied in the 2mee destination settings. Make sure to paste the API Key in this format: `Bearer <API Key>`.

Supported methods

2mee supports the following methods, as specified in the [Segment Spec](#).

Identify

Send [Identify](#) calls to check if a user exists within your application. For example:

```
{
  "type": "identify",
  "userId": "<userId>"
}
```

Segment sends Identify calls to 2mee as an `identify` event.

Identify calls with a `userId` not mapped to a device fails with a 400 error code.

Track

Send [Track](#) calls to track the actions your users perform.

Configure the HoloCapsule setting in the [2mee](#) app.

Segment requires the `userId`. Track calls without a `userId` or with a `userId` not mapped to a device fail with a 400 code.

```
{
  "type": "track",
  "event": "<event_name>",
  "userId": "<userId>"
}
```

Segment sends Track calls to 2mee as a `track` event.

Engage

You can send computed traits and audiences generated using [Engage](#) to this destination as a **user property**. To learn more about Engage, schedule a [demo](#).

For user-property destinations, an [identify](#) call is sent to the destination for each user being added and removed. The property name is the snake_cased version of the audience name, with a true/false value to indicate membership. For example, when a user first completes an order in the last 30 days, Engage sends an Identify call with the property `order_completed_last_30days: true`. When the user no longer satisfies this condition (for example, it's been more than 30 days since their last order), Engage sets that value to `false`.

When you first create an audience, Engage sends an Identify call for every user in that audience. Later audience syncs only send updates for users whose membership has changed since the last sync.



Real-time to batch destination sync frequency

Real-time audience syncs to 2mee may take six or more hours for the initial sync to complete. Upon completion, a sync frequency of two to three hours is expected.

Settings

Segment lets you change these destination settings from the Segment app without having to touch any code.

SETTING	DESCRIPTION
API Key (required)	<code>string</code> . Login to your 2Mee account, find the key under Profile section.
Application Id (required)	<code>string</code> . Login to your 2Mee account, get Company Id from Profile section.

Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

[Visit our Support page](#)

Help improve these docs!

[Edit this page](#)

[Request docs change](#)

Was this page helpful?

[Yes](#)

[No](#)

Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

[Request Demo](#)

or

[Create free account](#)

© 2025 Segment.io, Inc.

[Privacy](#)

[Terms](#)

[Website Data Collection Preferences](#)

