

Getting Started

What is Segment?
How Segment Works
Getting Started Guide
A Basic Segment Installation
Planning a Full Installation
A Full Segment Installation
Sending Data to Destinations
Testing and Debugging
What's Next
Use Cases

Guides

Connections

Unify

Engage

Privacy

Protocols

Segment App

API

Partners

Glossary

Config API

Help

combining multiple channels, like push nouncations, in-app messages, emails, and 5ivi5.

Pushwoosh maintains this destination. For any issues with the destination, contact the Pushwoosh support team.

Getting started

Pushwoosh SDK integration

If you configured Segment to receive push tokens, you don't need to integrate the Pushwoosh SDK into your app.

If your Segment implementation doesn't receive push tokens, integrate the Pushwoosh SDK into your app before setting up the Pushwoosh integration.

Segment configuration

from the Segment web app, navigate to **Connections > Destinations**, and click **Add Destination**.

2earch for **Pushwoosh** and select it as the destination.

Shoose the sources you want to connect the Pushwoosh destination to.

Open the destination settings.

5nter your **Pushwoosh API key** and **application code**, which you can find below the project name in Pushwoosh. Verify that the **Enable Destination** switch is toggled on, then click **Save Changes**.

6o to the **Mappings** tab and verify that the **Create or Update User Profile** and **Track Events options** are enabled.

Once you've configured the integration, Pushwoosh will receive events and user attributes from Segment.

Destination Settings

SETTING	DESCRIPTION
Pushwoosh API Key	Required. Pushwoosh API Key from Pushwoosh Control Panel
Pushwoosh Application Code	Required. Pushwoosh Application Code from Pushwoosh Control Panel

Available Presets

Pushwoosh has the following presets:

PRESET NAME	TRIGGER	DEFAULT ACTION
Track Events	Event type = "track" Event type = "page" Event type = "screen"	Track Event
Create or Update User Profile	Event type = "identify"	Create or Update User Profiles

Available Actions

Build your own Mappings. Combine supported triggers with the following Pushwoosh-supported actions:



Mapping limits per destination

Individual destination instances have support a maximum of 50 mappings.

Create or Update User Profiles

Track Event

Create or Update User Profiles

Create or Update a user's profile attributes in Pushwoosh.

Create or Update User Profiles is a **Cloud** action. The default Trigger is: type = "identify"

Click to show / hide fields

FIELD	DESCRIPTION
External User ID	Type: STRING The unique user identifier
Email	Type: STRING The user's email

FIELD	DESCRIPTION
App Version	Type: STRING Version of the app
Device ID	Type: STRING Device ID
Device Model	Type: STRING Device Model
Device Platform	Type: STRING Device Platform
Device Token	Type: STRING Device Token. This is not automatically collected by Segment Mobile SDKs. Add it into the Segment payload if needed
Language	Type: STRING Language
Country	Type: STRING The country code of the user
City	Type: STRING The city of the user
Current Location	Type: OBJECT The user's current longitude/latitude.
Device OS Version	Type: STRING The version of the device OS
Timezone	Type: STRING The timezone of the user
User Agent	Type: STRING User agent of the device
Custom Attributes	Type: OBJECT Custom attributes to send to Pushwoosh

Track Event

Record custom events in Pushwoosh

Track Event is a **Cloud** action. The default Trigger is: type = "track" or type = "page" or type = "screen"

Click to show / hide fields

FIELD	DESCRIPTION
External User ID *	Type: STRING The unique user identifier
Device ID	Type: STRING Device ID
Device Platform	Type: STRING Device Platform
Name *	Type: STRING Event Name
Timestamp *	Type: DATETIME When the event occurred.

FIELD	DESCRIPTION
Event Properties	Type: OBJECT Properties of the event
Batch Data to Pushwoosh	Type: B00LEAN If true, Segment will batch events before sending to Pushwoosh. 100 events per request max.

Engage

You can send computed traits and audiences generated using Engage to this destination as a **user property**. To learn more about Engage, schedule a demo.

For user-property destinations, an identify call is sent to the destination for each user being added and removed. The property name is the snake_cased version of the audience name, with a true/false value to indicate membership. For example, when a user first completes an order in the last 30 days, Engage sends an Identify call with the property order_completed_last_30days: true. When the user no longer satisfies this condition (for example, it's been more than 30 days since their last order), Engage sets that value to false.

When you first create an audience, Engage sends an Identify call for every user in that audience. Later audience syncs only send updates for users whose membership has changed since the last sync.



Real-time to batch destination sync frequency

Real-time audience syncs to Pushwoosh (Actions) may take six or more hours for the initial sync to complete. Upon completion, a sync frequency of two to three hours is expected.

Settings

Segment lets you change these destination settings from the Segment app without having to touch any code.

SETTING	DESCRIPTION
Pushwoosh API Key (required)	password - Pushwoosh API Key from Pushwoosh Control Panel
Pushwoosh Application Code (required)	string . Pushwoosh Application Code from Pushwoosh Control Panel

This page was last modified: 07 Aug 2024

Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

Visit our Support page

Help improve these docs!

Edit this page

♠ Request docs change

Was this page helpful?



Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

Request Demo

or

Create free account

