



Getting Started

What is Segment?
[How Segment Works](#)
Getting Started Guide
A Basic Segment Installation
Planning a Full Installation
A Full Segment Installation
Sending Data to Destinations
Testing and Debugging
What's Next
Use Cases

Guides

Connections

Unify

Engage

Privacy

Protocols

Segment App

API

Partners

Glossary

Config API

Help

The events transferred from Segment to your LiveLike application will appear under the [Actions](#) section.

Getting started

- 1 From the Segment web app dashboard, navigate to Connections > Catalog.
- 2 Under the Destinations tab, search for "LiveLike Cloud Mode (Actions)", and select the destination.
- 3 Click Configure "LiveLike Cloud Mode (Actions)".
- 4 Select the source that will send data to "LiveLike Cloud Mode (Actions)", click **Next** to enter the name of your destination, and click Save.
- 5 On the **Settings** tab, under **Basic Settings**, add the following Connection Settings:
 - Producer Token**: Created in the LiveLike Producer Suite.
 - Client ID**: The app identifier used to reference specific Application in requests made to the LiveLike API.
- 6 To customize the actions mapping, follow the Destinations Actions documentation steps on [Customizing mappings](#). Mappings in Segment allow you to control the events that are sent to LiveLike.

Enable the destination using the toggle switch.

Destination Settings

SETTING	DESCRIPTION
Client ID	<i>Required.</i> Your LiveLike Application Client ID.
Producer Token	<i>Required.</i> Your LiveLike Producer token.

Available Presets

LiveLike has the following presets:

PRESET NAME	TRIGGER	DEFAULT ACTION
Screen Calls	Event type = "screen"	Track Event
Track User Actions	Event type = "track"	Track Event
Page Calls	Event type = "page"	Track Event

Available Actions

Build your own Mappings. Combine supported [triggers](#) with the following LiveLike-supported actions:



Mapping limits per destination

Individual destination instances have support a maximum of 50 mappings.



Track Event

Track Event

Send an event to LiveLike.

Track Event is a **Cloud** action. The default Trigger is: `type = "track"`

Click to show / hide fields

FIELD	DESCRIPTION
Event Name *	Type: <code>STRING</code> The name of the event being performed. For example, <code>User Registration</code> could be an event_name referring the event that is being sent to LiveLike.
Event Type *	Type: <code>STRING</code> The type of event (track/screen/page)
User ID	Type: <code>STRING</code> A unique identifier for a user.
LiveLike User Profile ID	Type: <code>STRING</code> The unique LiveLike user identifier.

FIELD	DESCRIPTION
Custom ID	Type: <code>STRING</code> In case you are not able to store <code>livelike_profile_id</code> , LiveLike provides a way to create your own access tokens which helps us to map your <code>user_id</code> to a unique <code>livelike_profile_id</code> . Please refer LiveLike Docs for more info.
Timestamp *	Type: <code>STRING</code> The date and time when the event occurred in ISO 8601 format. Defaults to current time if not provided. For example, 2019-09-30T15:59:44.933696Z.
Event Properties	Type: <code>OBJECT</code> Properties of the event.

This page was last modified: 30 Aug 2023

Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

[Visit our Support page](#)

Help improve these docs!

[Edit this page](#)

[Request docs change](#)

Was this page helpful?

☒ Yes

☐ No

Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

[Request Demo](#)

or

[Create free account](#)

© 2025 Segment.io, Inc.

[Privacy](#)

[Terms](#)

[Website Data Collection Preferences](#)



