- **Pre-built mapping.** Mappings for Toplyne, are prebuilt with the prescribed parameters and available for customization

- **No 3rd party tool is involved.** Move the data directly from Segment to Toplyne without the requirement of a 3rd party tool to facilitate the data sync.

Getting started

1. From the Segment web app, navigate to **Connections > Catalog** and select the **Destinations** tab of the catalog.

2. Search for **Toplyne Cloud Mode (Actions)** and select it.

3. Click **Configure Toplyne Cloud Mode (Actions)**.

4. Select an existing Source to connect to Toplyne (Actions).

5. To obtain the API key you have to move to the **Toplyne dashboard**

6. From your Toplyne dashboard, navigate to **Settings** > **API Settings** and click on **+ Generate new token**.

7 Enter a name for your token, and select *Does not expire* under *Expiration*. Then click **Generate new token**

8 Copy the access token that has just been generated. This will be the API key that you will enter in Segment.

9 Save your changes and enable the destination.

Destination Settings

SETTING	DESCRIPTION
API Key	*Required.* Your Toplyne API Key

Available Presets

Toplyne Cloud Mode (Actions) has the following presets:

PRESET NAME	TRIGGER	DEFAULT ACTION
Send User Profiles	Event type = "identify"	Send user profiles
Send Events	Event type = "track"	Send events
Send Account Profiles	Event type = "group"	Send Account Profiles

Available Actions

Build your own Mappings. Combine supported triggers with the following Toplyne Cloud Mode-supported actions:

> ℹ️
> **Mapping limits per destination**
>
> Individual destination instances have support a maximum of 50 mappings.

- Send events
- Send Account Profiles
- Send user profiles

Send events

Send event track calls to Toplyne

Send events is a **Cloud** action. The default Trigger is: `type = "track"`

Click to show / hide fields

FIELD	DESCRIPTION
User ID	Type: `STRING` The ID of the user to send events for. Required if anonymousId is not provided
Anonymous ID	Type: `STRING` The anonymous ID of the user to send events for. Required if userId is not provided
Account ID	Type: `STRING` The ID of the account to send events for

FIELD	DESCRIPTION
Event Name *	Type: `STRING` The name of the event to send
Timestamp *	Type: `DATETIME` The timestamp of the event
Event Properties	Type: `OBJECT` The properties of the event

Send Account Profiles

Send group calls to Toplyne

Send Account Profiles is a **Cloud** action. The default Trigger is: `type = "group"`

Click to show / hide fields

FIELD	DESCRIPTION
Account ID *	Type: `STRING` The ID of the account to send properties for
Creation time *	Type: `DATETIME` Toplyne calculates the creation time using the timestamp of the first event or group call
Account Properties	Type: `OBJECT` The properties of the account

Send user profiles

Send identify calls to Toplyne

Send user profiles is a **Cloud** action. The default Trigger is: `type = "identify"`

Click to show / hide fields

FIELD	DESCRIPTION
User ID	Type: `STRING` The ID of the user to send properties for. Required if anonymousId is not provided
Anonymous ID	Type: `STRING` The anonymous ID of the user to send properties for. Required if userId is not provided
Creation time *	Type: `DATETIME` Toplyne calculates the creation time of the user using the timestamp of the first track or identify call
User Properties	Type: `OBJECT` The properties of the user

This page was last modified: 07 Aug 2024

Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

Visit our Support page

Help improve these docs!

Was this page helpful?

👍 Yes

👎 No

Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

Request Demo

or

Create free account