



Documentation

Getting Started

What is Segment?
[How Segment Works](#)
Getting Started Guide
A Basic Segment Installation
Planning a Full Installation
A Full Segment Installation
Sending Data to Destinations
Testing and Debugging
What's Next
Use Cases

Guides

Connections

Unify

Engage

Privacy

Protocols

Segment App

API

Partners

Glossary

Config API

Help

across all stages of product development through unmoderated tests, participant recruiting, and powerful in-product surveys.

Hubble maintains this destination. For any issues with the destination, view [Hubble's documentation](#) or contact [Hubble Support](#).



Analytics.js 2.0

Actions-based destinations may require features found in [Analytics.js 2.0](#). If the destination has Web actions and is connected to a javascript source, [upgrade your Analytics.js](#) source to ensure compatibility.

Getting started

- 1 From the Segment web app, click **Catalog**, then click **Destinations**.
- 2 Search for "Hubble (Actions)" in the catalog.
- 3 Choose a source you would like to connect this destination to.

4. Find your Hubble ID in [Hubble App](#) by navigating to **Account Settings > Integrations > Segment**.
5. Enter your Hubble ID into the **id** field in the Segment web app.

Destination Settings

SETTING	DESCRIPTION
id	<i>Required.</i> Unique identifier for your team (given in Hubble app)

Available Presets

Hubble (Actions) has the following presets:

PRESET NAME	TRIGGER	DEFAULT ACTION
Track event	Event type = "track"	Track
Identify user	Event type = "identify"	Identify

Available Actions

Build your own Mappings. Combine supported [triggers](#) with the following Hubble-supported actions:

Mapping limits per destination
Individual destination instances have support a maximum of 50 mappings.

- Track
- Identify

Track

Track events to trigger Hubble surveys

Track is a **Web** action. The default Trigger is: `type = "track"`

Click to show / hide fields

FIELD	DESCRIPTION
Event *	Type: <code>STRING</code> Event to be tracked
Event Attributes	Type: <code>OBJECT</code> Object containing the attributes (properties) of the event
User ID	Type: <code>STRING</code> Unique identifier of the user
Anonymous ID	Type: <code>STRING</code> Anonymous identifier of the user

Identify

Set identifiers and attributes for a user

Identify is a **Web** action. The default Trigger is: `type = "identify"`

Click to show / hide fields

FIELD	DESCRIPTION
User ID	Type: <code>STRING</code> Unique identifier of the user
Anonymous ID	Type: <code>STRING</code> Anonymous identifier of the user
User Attributes (Traits)	Type: <code>OBJECT</code> User traits used to enrich user identification

Settings

Segment lets you change these destination settings from the Segment app without having to touch any code.

SETTING	DESCRIPTION
id (required)	<code>string</code> . Unique identifier for your team (given in Hubble app)

This page was last modified: 07 Aug 2024

Need support?

Questions? Problems? Need more info? Contact Segment Support for assistance!

Visit our Support page

Help improve these docs!

 Edit this page

 Request docs change

Was this page helpful?

 Yes

 No

Get started with Segment

Segment is the easiest way to integrate your websites & mobile apps data to over 300 analytics and growth tools.

Your work e-mail

Request Demo

or

Create free account

© 2025 Segment.io, Inc.

[Privacy](#)

[Terms](#)

[Website Data Collection Preferences](#)

