```
    51 110.297028      Smartlin_7a:42:9e      Smartlin_7a:42:8a      ARP      42      Who has 10.10.40.174?
Tell 10.10.43.47
 Frame 51: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
     Encapsulation type: Ethernet (1)
     Arrival Time: Aug 22, 2018 13:03:19.224101000 IST
     [Time shift for this packet: 0.000000000 seconds]
     Epoch Time: 1534923199.224101000 seconds
     [Time delta from previous captured frame: 0.831821000 seconds]
     [Time delta from previous displayed frame: 0.831821000 seconds]
     [Time since reference or first frame: 110.297028000 seconds]
     Frame Number: 51
     Frame Length: 42 bytes (336 bits)
     Capture Length: 42 bytes (336 bits)
     [Frame is marked: True]
     [Frame is ignored: False]
     [Protocols in frame: eth:ethertype:arp]
     [Coloring Rule Name: ARP]
     [Coloring Rule String: arp]
 Ethernet II, Src: Smartlin_7a:42:9e (00:17:7c:7a:42:9e), Dst: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
     Destination: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
         Address: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
         .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
         .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
     Source: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
         Address: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
         .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
         .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
     Type: ARP (0x0806)
 Address Resolution Protocol (request)
     Hardware type: Ethernet (1)
     Protocol type: IPv4 (0x0800)
     Hardware size: 6
     Protocol size: 4
     Opcode: request (1)
     Sender MAC address: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
     Sender IP address: 10.10.43.47
     Target MAC address: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
     Target IP address: 10.10.40.174
    52 110.332071      Smartlin_7a:42:8a      Smartlin_7a:42:9e      ARP      42      10.10.40.174 is at
00:17:7c:7a:42:8a
 Frame 52: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
     Encapsulation type: Ethernet (1)
     Arrival Time: Aug 22, 2018 13:03:19.259144000 IST
     [Time shift for this packet: 0.000000000 seconds]
     Epoch Time: 1534923199.259144000 seconds
     [Time delta from previous captured frame: 0.035043000 seconds]
     [Time delta from previous displayed frame: 0.035043000 seconds]
     [Time since reference or first frame: 110.332071000 seconds]
     Frame Number: 52
     Frame Length: 42 bytes (336 bits)
     Capture Length: 42 bytes (336 bits)
     [Frame is marked: True]
     [Frame is ignored: False]
     [Protocols in frame: eth:ethertype:arp]
     [Coloring Rule Name: ARP]
     [Coloring Rule String: arp]
 Ethernet II, Src: Smartlin_7a:42:8a (00:17:7c:7a:42:8a), Dst: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
     Destination: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
         Address: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
         .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
         .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
     Source: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
         Address: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
         .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
         .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
     Type: ARP (0x0806)
 Address Resolution Protocol (reply)
     Hardware type: Ethernet (1)
     Protocol type: IPv4 (0x0800)
     Hardware size: 6
     Protocol size: 4
     Opcode: reply (2)
     Sender MAC address: Smartlin_7a:42:8a (00:17:7c:7a:42:8a)
     Sender IP address: 10.10.40.174
     Target MAC address: Smartlin_7a:42:9e (00:17:7c:7a:42:9e)
     Target IP address: 10.10.43.47
```