

Batch: A1

Experiment Number:8

Roll Number: 16010422012

Name: Ayaan Bhoje

---

**Aim of the Experiment:** To implement Decision Tree Algorithm (ID3 using library)

---

### Program/ Steps:

```
In [1]: import pandas as pd
df = pd.read_csv("titanic_data.csv")
df.head()
```

```
Out[1]:
```

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C85	C
2	3	1	3	Heikinen, Miss. Laina	female	26.0	0	0	STON/O2: 3101282	7.9250	NaN	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	S

```
In [3]: df.drop(['PassengerId', 'Name', 'SibSp', 'Parch', 'Ticket', 'Cabin', 'Embarked'], axis='columns', inplace=True)
```

```
In [4]: df.head()
```

```
Out[4]:
```

	Survived	Pclass	Sex	Age	Fare
0	0	3	male	22.0	7.2500
1	1	1	female	38.0	71.2833
2	1	3	female	26.0	7.9250
3	1	1	female	35.0	53.1000
4	0	3	male	35.0	8.0500

```
In [5]: dfnew = df.head(50)
df1 = dfnew.drop('Survived', axis='columns')
target = dfnew.Survived
```

```
In [6]: #Label Encoding
from sklearn import preprocessing
label_encoder = preprocessing.LabelEncoder()
df1['Sex'] = label_encoder.fit_transform(df1['Sex'])
```

```
In [7]: #Removing Null values
df1.Age = df1.Age.fillna(df1.Age.mean())
df1.head()
```

```
Out[7]:
```

	Pclass	Sex	Age	Fare
0	3	1	22.0	7.2500
1	1	0	38.0	71.2833
2	3	0	26.0	7.9250
3	1	0	35.0	53.1000
4	3	1	35.0	8.0500

```
In [8]: from sklearn.tree import DecisionTreeClassifier

#splitting up the dataset
from sklearn.model_selection import train_test_split
X_train2, X_test2, y_train2, y_test2 = train_test_split(df1,target,test_size=0.2)

#Training the decision tree classifier
m2 = DecisionTreeClassifier(criterion='gini')
m2.fit(X_train2,y_train2)

#Predicting the response for test data
y_pred2 = m2.predict(X_test2)

#Classification Report
from sklearn.metrics import classification_report
print(classification_report(y_test2,y_pred2))
```

	precision	recall	f1-score	support
0	1.00	0.67	0.80	6
1	0.67	1.00	0.80	4
accuracy			0.80	10
macro avg	0.83	0.83	0.80	10
weighted avg	0.87	0.80	0.80	10


```
In [9]: #Accuracy
print("accuracy: ", m2.score(X_test2,y_test2))

accuracy: 0.8
```

```
In [11]: #Confusion Matrix
from sklearn.metrics import confusion_matrix
print(confusion_matrix(y_test2,y_pred2))
```

```
[[4 2]
 [0 4]]
```

```
In [14]: target = target.astype('str')
```



```
In [17]: #Example 1
import pandas as pd
df = pd.read_csv("titanic_data.csv")
df2 = df.head(50).drop('Cabin', axis = 1)
df2
```

```
Out[17]:
```

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	S
1	2	1	1	Cummings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C
2	3	1	3	Heikinen, Miss. Laina	female	26.0	0	0	STON/O2: 3101282	7.9250	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	S
5	6	0	3	Moran, Mr. James	male	NaN	0	0	330877	8.4583	Q
6	7	0	1	McCarthy, Mr. Timothy J	male	54.0	0	0	17463	51.8625	S
7	8	0	3	Palsson, Master. Gosta Leonard	male	2.0	3	1	349909	21.0750	S
8	9	1	3	Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)	female	27.0	0	2	347742	11.1333	S
9	10	1	2	Nasser, Mrs. Nicholas (Adele Achem)	female	14.0	1	0	237736	30.0708	C
10	11	1	3	Sandstrom, Miss. Marguerite Rut	female	4.0	1	1	PP 9549	16.7000	S
11	12	1	1	Bonnell, Miss. Elizabeth	female	58.0	0	0	113783	26.5500	S
12	13	0	3	Saunderscock, Mr. William Henry	male	20.0	0	0	A/5 2151	8.0500	S
13	14	0	3	Andersson, Mr. Anders Johan	male	39.0	1	5	347082	31.2750	S

```
In [18]: from sklearn import preprocessing
label_encoder = preprocessing.LabelEncoder()

#Label Encoding
df2.loc[:,('Name')] = label_encoder.fit_transform(df2['Name'])
df2.loc[:,('Sex')] = label_encoder.fit_transform(df2['Sex'])
df2.loc[:,('Ticket')] = label_encoder.fit_transform(df2['Ticket'])

#Handling Null Values
df2.loc[:,('Age')] = df2.Age.fillna(df2.Age.mean())

em_dummies = pd.get_dummies(df2['Embarked'], drop_first=True)
df2[['Embarked_Q', 'Embarked_S']] = em_dummies
df2.head()
```

```
Out[18]:
```

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked	Embarked_Q	Embarked_S
0	1	0	3	7	1	22.0	1	0	38	7.2500	S	0	1
1	2	1	1	9	0	38.0	1	0	42	71.2833	C	0	0
2	3	1	3	16	0	26.0	0	0	48	7.9250	S	0	1
3	4	1	1	13	0	35.0	1	0	3	53.1000	S	0	1
4	5	0	3	1	1	35.0	0	0	34	8.0500	S	0	1

```
In [19]: df2.drop(['Embarked'],axis=1,inplace=True)
df2.head()
```

Out[19]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked_Q	Embarked_S
0	1	0	3	7	1	22.0	1	0	38	7.2500	0	1
1	2	1	1	9	0	38.0	1	0	42	71.2833	0	0
2	3	1	3	16	0	26.0	0	0	48	7.9250	0	1
3	4	1	1	13	0	35.0	1	0	3	53.1000	0	1
4	5	0	3	1	1	35.0	0	0	34	8.0500	0	1

```
In [20]: #Getting the target column
target1 = df2.Survived
df2 = df2.drop('Survived', axis='columns')
```

```
In [21]: target1 = target1.astype('float')
```

```
In [22]: from sklearn.tree import DecisionTreeClassifier

#Splitting up the dataset
from sklearn.model_selection import train_test_split
X_train1, X_test1, y_train1, y_test1 = train_test_split(df2,target1,test_size=0.2)

#Training the decision tree classifier
m1 = DecisionTreeClassifier(criterion='entropy')
m1.fit(X_train1,y_train1)

#Predicting the response for test data
y_pred1 = m1.predict(X_test1)

#Classification Report
from sklearn.metrics import classification_report
print(classification_report(y_test1,y_pred1))
```

	precision	recall	f1-score	support
0.0	0.88	0.88	0.88	8
1.0	0.50	0.50	0.50	2
accuracy			0.80	10
macro avg	0.69	0.69	0.69	10
weighted avg	0.80	0.80	0.80	10

```
In [23]: #Accuracy
print("accuracy: ", m1.score(X_test1,y_test1))

accuracy: 0.8
```

```
In [24]: #Confusion Matrix
from sklearn.metrics import confusion_matrix
print(confusion_matrix(y_test1,y_pred1))
```


```
[[7 1]
 [1 1]]
```

```

: target1 = target1.astype('str')

from sklearn import tree
%matplotlib inline
from matplotlib import pyplot as plt
fig1, axes1 = plt.subplots(nrows=1, ncols=1, figsize=(4,4), dpi=400)
tree.plot_tree(m1, feature_names=df2.columns, class_names=target1, filled=True, fontsize=2)

```



In [26]: *#Example 3*

```
df3 = pd.read_csv("titanic_data.csv")
df3.head()
X = df3.drop(['Fare', 'Age', 'Cabin'], axis=1)
X['Family'] = X['SibSp'] + X['Parch']
X = X.drop(['SibSp', 'Parch'], axis = 1)
X.head()
```

Out[26]:

	PassengerId	Survived	Pclass	Name	Sex	Ticket	Embarked	Family
0	1	0	3	Braund, Mr. Owen Harris	male	A/5 21171	S	1
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	PC 17599	C	1
2	3	1	3	Heikinen, Miss. Laina	female	STON/O2. 3101282	S	0
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	113803	S	1
4	5	0	3	Allen, Mr. William Henry	male	373450	S	0

```
In [27]: def weClass(x):
        if x==1:
            return x*2
        elif x==2:
            return x*3
        else:
            return x*4

X['Weighted_class'] = X['Pclass'].apply(weClass)
X.head()
```

Out[27]:

	PassengerId	Survived	Pclass	Name	Sex	Ticket	Embarked	Family	Weighted_class
0	1	0	3	Braund, Mr. Owen Harris	male	A/5 21171	S	1	12
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	PC 17599	C	1	2
2	3	1	3	Heikinen, Miss. Laina	female	STON/O2. 3101282	S	0	12
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	113803	S	1	2
4	5	0	3	Allen, Mr. William Henry	male	373450	S	0	12

```
In [28]: newdf=X.drop(['Pclass'], axis = 1)
newdf.head()
```

Out[28]:

	PassengerId	Survived	Name	Sex	Ticket	Embarked	Family	Weighted_class
0	1	0	Braund, Mr. Owen Harris	male	A/5 21171	S	1	12
1	2	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	PC 17599	C	1	2
2	3	1	Heikinen, Miss. Laina	female	STON/O2. 3101282	S	0	12
3	4	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	113803	S	1	2
4	5	0	Allen, Mr. William Henry	male	373450	S	0	12

```
In [29]: from sklearn import preprocessing
label_encoder = preprocessing.LabelEncoder()

#Label Encoding
newdf.loc[:,('Name')] = label_encoder.fit_transform(newdf['Name'])
newdf.loc[:,('Sex')] = label_encoder.fit_transform(newdf['Sex'])
newdf.loc[:,('Ticket')] = label_encoder.fit_transform(newdf['Ticket'])

em_dummies = pd.get_dummies(X['Embarked'], drop_first=True)
newdf[['Embarked_Q', 'Embarked_S']] = em_dummies
newdf = newdf.drop(['Embarked'], axis =1 )
newdf.head()
```

Out[29]:

	PassengerId	Survived	Name	Sex	Ticket	Family	Weighted_class	Embarked_Q	Embarked_S
0	1	0	108	1	523	1	12	0	1
1	2	1	190	0	596	1	2	0	0
2	3	1	353	0	689	0	12	0	1
3	4	1	272	0	49	1	2	0	1
4	5	0	15	1	472	0	12	0	1



In [31]:

```
y = newdf.Survived
y = y.astype('float')
```

In [32]: `from sklearn.tree import DecisionTreeClassifier`



```
#Splitting up the dataset
from sklearn.model_selection import train_test_split
X_train1, X_test1, y_train1, y_test1 = train_test_split(newdf,y,test_size=0.2)

#Training the decision tree classifier
m1 = DecisionTreeClassifier(criterion='entropy')
m1.fit(X_train1,y_train1)

#Predicting the response for test data
y_pred1 = m1.predict(X_test1)

#Classification Report
from sklearn.metrics import classification_report
print(classification_report(y_test1,y_pred1))
```

	precision	recall	f1-score	support
0.0	1.00	1.00	1.00	100
1.0	1.00	1.00	1.00	79
accuracy			1.00	179
macro avg	1.00	1.00	1.00	179
weighted avg	1.00	1.00	1.00	179



Outcomes:CO 5: Understand fundamentals of learning in AI

Conclusion:



We learnt how to make a decision tree and test data and accuracy of that decision tree

**References:**

- Stuart Russell and

Peter Norvig, Artificial Intelligence: A Modern Approach, Se

cond Edition, Pearson Publication

Elaine Rich, Kevin Knight, Artificial Intelligence, Tata McGraw Hill, 1999

---