

IMPERIAL COLLEGE LONDON

DEPARTMENT OF COMPUTING

INDIVIDUAL PROJECT

Equivalences Tutor

Author:
Sahil JAIN

Supervisor:
Fariba SADRI

Second marker:
Ian HODKINSON

June 11, 2013

Abstract

Acknowledgements

I would like to thank Dr. Fariba Sadri for her continuous support and guidance throughout the course of this project. I would also like to thank Dr. Ian Hodgkinson for his value feedback to my interim report.

Above all, I would like to thank my family for being there for me and giving me constant support through my education.

Contents

1	Introduction	3
2	Background	4
2.1	Propositional Logic	4
2.1.1	Syntax	4
2.1.2	Semantics	5
2.2	Equivalences	6
2.2.1	And Equivalences	7
2.2.2	Or Equivalences	7
2.2.3	Not Equivalences	7
2.2.4	Implies Equivalences	7
2.2.5	If and Only If Equivalences	7
2.2.6	De Morgan Equivalences	7
2.2.7	Distributivity of And and Or	7
2.3	Examples of Equivalence Problems	8
2.3.1	Equivalence Examples	8
2.4	Current Logic Tutorial Applications	8
3	Approach and Implementation details	9
3.1	Modelling Logic Formulae	9
3.1.1	Lexer	9
3.1.2	Parser	10
3.2	Abstract Syntax Tree	12
3.3	Logic Expression Generator	13
3.4	Equivalence Solvers	13
3.4.1	Easy Equivalence Solver	13
3.4.2	Hard Equivalence Solver	13
4	Evaluation	14

5	Conclusions and Future Work	15
5.1	Learning outcomes	15
5.2	Potential improvements	15
5.3	Potential extensions	15
A	Equivalences Truth Tables	17
A.1	And Equivalences	17
A.2	Or Equivalences	18
A.3	Not Equivalences	18
A.4	Implies Equivalences	18
A.5	If and Only If Equivalences	19
A.6	De Morgan Equivalences	20
A.7	Distributivity of And and Or	20
B	Truth Tables of all Equivalences	21
B.1	And Equivalences	21
B.2	Or Equivalences	22
B.3	Not Equivalences	22
B.4	Implies Equivalences	22
B.5	If and Only If Equivalences	23
B.6	De Morgan Equivalences	24
B.7	Distributivity of And and Or	24

Chapter 1

Introduction

Logic refers to the study of different modes of reasoning conducted or assessed according to strict principles of validity. Due to Logic being one of the most fundamental aspects of Computer Science, it is taught to every student pursuing a Computing degree at Imperial College London. During the first term in university, every Computing student is taught the Logic course, which aims to provide the students with knowledge of the syntax and semantics of Propositional and Predicate logic. Students can apply this knowledge to complete equivalences and natural deduction proofs.

A logical system is made up of three things:

1. Syntax - this is the formal language specified to express different concepts.
2. Semantics - this is what provides meaning to the language.
3. Proof theory - this is a way of arguing in the language. This allows us to identify valid statements in the language.

In logic, two statements are logically equivalent if they contain the same logical content. Mendelson stated that "two statements are equivalent if they have the same truth value in every model." This can be illustrated in the following example:

Statement 1: *If Sahil is a final year student, then he has to do an individual project*

Statement 2: *If Sahil is not doing an individual project, then he is not a final year student*

As we can see, both statements have the same result in same models. When two logic statements are equivalent, they can be derived by each other, with the use of equivalences which we know to be true.

Chapter 2

Background

This section summarises the necessary background knowledge for understanding this report. It also introduces the concepts of Logic Equivalences.

2.1 Propositional Logic

Before we can define what Propositional Logic is, we have to define what a proposition is. Essentially, a proposition is a statement which is either true or false. This then leads to defining Propositional Logic as a branch of symbolic logic dealing with propositions as units and with their combinations and the connectives that relate them. [1]

2.1.1 Syntax

This is the formal language used in propositional logic. There are three different parts which make up the syntax of propositional logic; atoms, connectives and punctuation.

A propositional atom, or propositional variable, is a symbol which has a truth value, either true or false. Usually, atoms are denoted by letters p , q , r , s , etc.

Connectives are boolean operations which are applied to atoms. There are a total of seven connectives:

- And - written as \wedge . Takes two arguments.
- Or - written as \vee . Takes two arguments.
- Not - written as \neg . Takes one argument.
- If then - written as \rightarrow . Takes two arguments.
- If and only if - written as \leftrightarrow . Takes two arguments.
- Truth - written as \top . Takes zero arguments.
- Falsity - written as \perp . Takes zero arguments.

2.1.2 Semantics

This is the meaning of a logic formula. As each atom has a truth value, there can be several combinations of truth values for each atom. To be more specific, if there are n atoms in a logic formula, then there are a total of 2^n combinations of truth values. Each combination is known as a situation.

Each connective has a different meaning. These meanings can be shown using a truth table and using the atoms p and q .

And

p	q	$p \wedge q$
0	0	0
0	1	0
1	0	0
1	1	1

As we can see, $p \wedge q$ is only true when both p and q are true. Otherwise, $p \wedge q$ is always false.

Or

p	q	$p \vee q$
0	0	0
0	1	1
1	0	1
1	1	1

As we can see, $p \vee q$ is true when either p or q is true. When both p and q are false, $p \vee q$ is false as well.

Not

p	$\neg p$
0	1
1	0

The truth value of $\neg p$ is always the opposite of p .

If Then

p	q	$p \rightarrow q$
0	0	1
0	1	1
1	0	0
1	1	1

$p \rightarrow q$ is true if p is false or/and if q is true. This means that there is only one situation where $p \rightarrow q$ is false, i.e p is true and q is false.

If and Only If

p	q	$p \leftrightarrow q$
0	0	1
0	1	0
1	0	0
1	1	1

$p \leftrightarrow q$ is true if p and q both have the same truth value.

Truth and Falsity

Truth is an atom which is always true, and Falsity is an atom which is always false.

2.2 Equivalences

As we introduced the example of "If Sahil is a final year student, then he has to do an individual project" being the same as "If Sahil is not doing an individual project, then he is not a final year student", all logic formulae are equivalent to other logic formulae.

We can show this by converting the above example into propositional logic. If we let the atom p denote "Sahil is a final year student" and let the atom q denote "Sahil is doing an individual project", then the statement "If Sahil is a final year student, then he has to do an individual project" becomes $p \rightarrow q$ and the statement "If Sahil is not doing an individual project, then he is not a final year student" becomes $\neg q \rightarrow \neg p$.

If we construct the truth tables of both of these formulae, we get:

p	q	$p \rightarrow q$
0	0	1
0	1	1
1	0	0
1	1	1

p	q	$\neg q \rightarrow \neg p$
0	0	1
0	1	1
1	0	0
1	1	1

As we can see, both of the truth tables are the same. This means that in any given situation, both of the logic formulae have the same truth value, meaning that they are equivalent.

There are several defined equivalences for each operator.

2.2.1 And Equivalences

1. $A \wedge B \equiv B \wedge A$ (*Commutativity of And*)
2. $A \wedge A \equiv A$ (*Idempotence of And*)
3. $(A \wedge B) \wedge C \equiv A \wedge (B \wedge C)$ (*Associativity of And*)

2.2.2 Or Equivalences

1. $A \vee B \equiv B \vee A$ (*Commutativity of Or*)
2. $A \vee A \equiv A$ (*Idempotence of Or*)
3. $(A \vee B) \vee C \equiv A \vee (B \vee C)$ (*Associativity of Or*)

2.2.3 Not Equivalences

1. $A \equiv \neg\neg A$

2.2.4 Implies Equivalences

1. $A \rightarrow B \equiv \neg A \vee B$
2. $A \rightarrow B \equiv \neg(A \wedge \neg B)$
3. $\neg(A \rightarrow B) \equiv A \wedge \neg B$

2.2.5 If and Only If Equivalences

1. $A \leftrightarrow B \equiv (A \rightarrow B) \wedge (B \rightarrow A)$
2. $A \leftrightarrow B \equiv (A \wedge B) \vee (\neg A \wedge \neg B)$

2.2.6 De Morgan Equivalences

1. $\neg(A \wedge B) \equiv \neg A \vee \neg B$
2. $\neg(A \vee B) \equiv \neg A \wedge \neg B$

2.2.7 Distributivity of And and Or

1. $A \wedge (B \vee C) \equiv (A \wedge B) \vee (A \wedge C)$
2. $A \vee (B \wedge C) \equiv (A \vee B) \wedge (A \vee C)$

2.3 Examples of Equivalence Problems

2.3.1 Equivalence Examples

1. $\neg(p \rightarrow q) \equiv p \wedge \neg q$
 - (a) $\neg(p \rightarrow q)$
 - (b) $\neg(\neg p \vee q)$ a, Implication rule
 - (c) $\neg\neg p \wedge \neg q$ b, De Morgan's law
 - (d) $p \wedge \neg q$ c, Double Negation rule
2. $\neg((p \wedge q) \rightarrow r) \equiv (p \wedge q) \wedge \neg r$
 - (a) $\neg((p \wedge q) \rightarrow r)$
 - (b) $\neg(\neg(p \wedge q) \vee r)$ a, Implication rule
 - (c) $\neg\neg(p \wedge q) \wedge \neg r$ b, De Morgan's law
 - (d) $(p \wedge q) \wedge \neg r$ c, Double Negation rule
3. $\neg(p \vee \neg q) \vee (\neg p \wedge \neg q) \equiv \neg p$
 - (a) $\neg(p \vee \neg q) \vee (\neg p \wedge \neg q)$
 - (b) $\neg(p \vee \neg q) \vee \neg(p \wedge q)$ a, De Morgan's law
 - (c) $\neg[(p \vee \neg q) \wedge (p \wedge q)]$ b, De Morgan's law
 - (d) $\neg[p \vee (\neg q \wedge q)]$ c, Distributivity
 - (e) $\neg(p \vee \perp)$ d, And rule
 - (f) $\neg p$ e, Or rule

2.4 Current Logic Tutorial Applications

In the first year Logic course, several different concepts are taught to the students. Some of the concepts have applications installed on the lab machines which are produced to help students understand these concepts better. Firstly, there is an application called *Pandora*, which is a learning support tool designed to guide the construction of natural deduction proofs. The second application the department provides is *LOST*, which helps students understand logic semantics better.

Equivalences is a large part of the Logic course, but currently, there is no tutorial application which the students can use to understand how to apply equivalences better, or which provides a user friendly interface for the students to use.

Chapter 3

Implementation

3.1 Modelling Logic Formulae

The first part that had to be implemented was modelling logic formulae so that they could be manipulated when applying equivalences. In the first year Logic course taught by Ian Hodkinson, the students are taught the Logic formation tree.

The example given in the first year slides is:

Using this formation tree, we can model logical formulae in a tree structure in Java by creating our own data structure.

3.1.1 Lexer

The first step in modelling the logical formulae into a tree structure is lexical analysis. This is the process of converting a sequence of characters into a sequence of tokens which can be parsed in the future.

As writing a lexer from scratch would have been very time consuming and tedious, I researched about the tools which had been developed for generating lexers after inputting the lexical grammar. The best tool which I came across was ANTLR, as it provides a very easy to use debugger where you can load the generated code and step through it.

Lexical Grammar

```
lexer grammar LogicLexer;
```

```
options {  
    language = Java;  
}
```

```
@header {  
    package eqtutor;
```

```

}

WHITESPACE: ( '\t' | ' ' | '\r' | '\n' | '\u000C' )+ { $channel = HIDDEN; };

AND : '&';
OR  : '|';
IFTHEN : '->';
IFF   : '<>';
NOT   : '!';

LPAREN : '(';
RPAREN : ')';

ID : ('A'..'Z'|'a'..'z') ('A'..'Z'|'a'..'z'|'_')*;

```

3.1.2 Parser

Once the formulae has been tokenised by the lexer, it then has to be parsed. Parsing is the process where the tokens are used to build a data structure, which is usually a hierarchical structure. This data structure gives a structural representation of the input.

ANTLR provides both lexer and parser generators. Due to having the ability of doing both of these steps using one tool which I had become familiar with, I decided to use the ANTLR parser generator.

Parser Grammar

```

parser grammar LogicParser;

options {
    tokenVocab = LogicLexer;
}

@header {
    package eqtutor;

    import java.util.LinkedList;
    import java.util.List;
    import AST.*;
}

@members {
    private boolean hasFoundError = false;

```

```

    public void displayRecognitionError(String[] tokenNames, RecognitionException e) {
        hasFoundError = true;
    }

    public boolean hasFoundError() {
        return this.hasFoundError;
    }
}

program returns [AST tree]
: e = iffexpr {$tree = new AST(new ASTProgramNode($e.node));} EOF
;

iffexpr returns [ASTPropositionalNode node]
: ifthen = ifexpr {$node = $ifthen.node;}
( IFF iff = iffexpr {$node = new ASTIffNode($ifthen.node, $iff.node);}) *
;

ifexpr returns [ASTPropositionalNode node]
: or = orexpr {$node = $or.node;}
( IFTHEN ifthen = ifexpr {$node = new ASTIfThenNode($or.node, $ifthen.node);}) *
;

orexpr returns [ASTPropositionalNode node]
: and = andexpr {$node = $and.node;}
( OR or = orexpr {$node = new ASTOrNode($and.node, $or.node);}) *
;

andexpr returns [ASTPropositionalNode node]
: not = notexpr {$node = $not.node;}
( AND and = andexpr {$node = new ASTAndNode($not.node, $and.node);}) *
;

notexpr returns [ASTPropositionalNode node]
: NOT not = notexpr {$node = new ASTNotNode($not.node);}
| id = identifier {$node = $id.node;}
;

identifier returns [ASTPropositionalNode node]

```

```

: ID {$node = new ASTIdentifierNode($ID.text);}
| LPAREN iffexpr RPAREN {$node = $iffexpr.node;}
;

```

3.2 Abstract Syntax Tree

The Abstract Syntax Tree (AST) is the tree representation of the structure of the logic expression. Each node of the tree represents either a connective or an identifier of the logic expression.

ANTLR provided an implementation of the AST as well, but I decided not to use it since manipulation of the trees provided was tough and confusing. Due to this, I created my own data structure to store the logic expression.

Once the tree is parsed, we obtain an object of type AST. The tree contains a node of type ASTProgramNode, which is the highest level of the tree. The ASTProgramNode node contains an ASTPropositionalNode. ASTPropositionalNode is an abstract class which contains the abstract methods for all of the propositional operators. The ASTPropositionalNode class is shown below:

```

public abstract class ASTPropositionalNode extends ASTNode {

    /*--Checks if the current node is equal to the input node--*/
    public abstract boolean equals(ASTPropositionalNode node);

    /*--Returns the string representation of the node--*/
    public abstract String toString();

    /*--Returns the string representation of the node which can be parsed--*/
    public abstract String toParserString();

    /*--Returns a tree map of the identifiers in the node--*/
    public abstract TreeMap<String, Integer> numIdentifiers(TreeMap<String, Integer> identifiers);

    /*--Returns the value of the node, e.g TRUTH and TRUTH = TRUTH--*/
    public abstract int value(TreeMap<String, Integer> id);

    /*--Creates the JPanel for the node which is used to solve equivalences--*/
    public abstract JPanel createJPanel(NewPersonalEquivalenceListener l, boolean side);

    /*--Copy constructor for the node--*/
    public abstract ASTPropositionalNode copy();

}

```

3.3 Logic Expression Generator

3.4 Equivalence Solvers

3.4.1 Checking if two formulae are logically equivalent

When a user starts a new equivalence, he has to first put input the start state and the end state. These two formulae are then checked to be equivalent or not, as the user should not be allowed to perform an equivalence problem if the start and end state are not equivalent.

If we were doing this on paper, we would just construct the truth table for the two formulae, and then compare them to be equal. The same idea is programmed in the AST class. As the AST only contains the structure, we have to assign each identifier with a truth value, so that every situation is accounted for while creating a truth table.

To achieve this, firstly a Tree Map of the identifiers is obtained. A Tree Map is used as it sorts the map according to the natural ordering of its keys, which are strings in this case, which means that the keys are stored alphabetically. This means the order of identifiers in the map of both formulae will be the same, allowing for easy comparison of truth tables. Once the tree map of the identifiers is obtained, the size of the map can be used to determine every situation. This is illustrated by the example below:

Consider the formula $p \wedge q \wedge r$, the situations are:

p	q	r
0	0	0
0	0	1
0	1	0
0	1	1
1	0	0
1	0	1
1	1	0
1	1	1

If we look at each situation in order, we can see that they are binary numbers starting from 0, going to 2^n where n is the number of identifiers. This connection can be used to assign values to identifiers. The pseudocode is shown below:

```
public int[][] createTruthTable() {  
    TreeMap<String, Integer> identifiers = this.identifiers();  
    int numIdentifiers = identifiers.size();  
    int temp = (int) Math.pow(2, numIdentifiers);  
    int[][] truthTable = new int[temp][numIdentifiers + 1];  
    for(int i = 0; i < truthTable.length; i++) {  
        String binary = Integer.toBinaryString(i);
```



```

if(binary.length() < numIdentifiers) {
int numZeroes = numIdentifiers - binary.length();
String zeroes = "";
while(zeroes.length() < numZeroes) {
zeroes += "0";
}
binary = zeroes + binary;
}
for(int j = 0; j < truthTable[i].length - 1; j++) {
char c = binary.charAt(j);
int n = Integer.parseInt(Character.toString(c));
truthTable[i][j] = n;
}
}
for(int i = 0; i < truthTable.length; i++) {
Set<String> keys = identifiers.keySet();
TreeMap<String, Integer> id = new TreeMap<String, Integer>();
Iterator<String> it = keys.iterator();
int j = 0;
while(it.hasNext()) {
String key = (String) it.next();
id.put(key, truthTable[i][j]);
j++;
}
truthTable[i][j] = value(id);
}
return truthTable;
}

```

3.4.2 Easy Equivalence Solver

The easy equivalence solver is an interface for solving equivalences where the student can click on either an identifier or an operator, and then a dialog opens which shows the student which equivalences can be applied to the clicked node.

3.4.3 Hard Equivalence Solver

The hard equivalence solver is an interface for solving equivalences where the student enters logic expressions into a text field. This expression is then compared to the previous expression to see if it is logically equivalent, and to see if only one of the given equivalences has been applied.

Chapter 4

Evaluation

Chapter 5

Conclusions and Future Work

5.1 Learning outcomes

5.2 Potential improvements

5.3 Potential extensions

Bibliography

Appendix A

Equivalences Truth Tables

A.1 And Equivalences

1. $A \wedge B \equiv B \wedge A$ (*Commutativity of And*)

A	B	$A \wedge B$	$B \wedge A$
0	0	0	0
0	1	0	0
1	0	0	0
1	1	1	1

2. $A \wedge A \equiv A$ (*Idempotence of And*)

A	$A \wedge A$
0	0
0	0
1	1
1	1

3. $(A \wedge B) \wedge C \equiv A \wedge (B \wedge C)$ (*Associativity of And*)

A	B	C	$(A \wedge B) \wedge C$	$A \wedge (B \wedge C)$
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	0	0
1	0	0	0	0
1	0	1	0	0
1	1	0	0	0
1	1	1	1	1

A.2 Or Equivalences

1. $A \vee B \equiv B \vee A$ (*Commutativity of Or*)

A	B	$A \vee B$	$B \vee A$
0	0	0	0
0	1	1	1
1	0	1	1
1	1	1	1

2. $A \vee A \equiv A$ (*Idempotence of Or*)

A	$A \vee A$
0	0
0	0
1	1
1	1

3. $(A \vee B) \vee C \equiv A \vee (B \vee C)$ (*Associativity of Or*)

A	B	C	$(A \vee B) \vee C$	$A \vee (B \vee C)$
0	0	0	0	0
0	0	1	1	1
0	1	0	1	1
0	1	1	1	1
1	0	0	1	1
1	0	1	1	1
1	1	0	1	1
1	1	1	1	1

A.3 Not Equivalences

1. $A \equiv \neg\neg A$

A	$\neg A$	$\neg\neg A$
0	1	0
1	0	1

A.4 Implies Equivalences

1. $A \rightarrow B \equiv \neg A \vee B$

A	B	$\neg A$	$A \rightarrow B$	$\neg A \vee B$
0	0	1	1	1
0	1	1	1	1
1	0	0	0	0
1	1	0	1	1

2. $A \rightarrow B \equiv \neg(A \wedge \neg B)$

A	B	$\neg B$	$A \wedge \neg B$	$A \rightarrow B$	$\neg(A \wedge \neg B)$
0	0	1	0	1	1
0	1	0	0	1	1
1	0	1	1	0	0
1	1	0	0	1	1

3. $\neg(A \rightarrow B) \equiv A \wedge \neg B$

A	B	$\neg B$	$A \rightarrow B$	$\neg(A \rightarrow B)$	$A \wedge \neg B$
0	0	1	1	0	0
0	1	0	1	0	0
1	0	1	0	1	1
1	1	0	1	0	0

A.5 If and Only If Equivalences

1. $A \leftrightarrow B \equiv (A \rightarrow B) \wedge (B \rightarrow A)$

A	B	$A \rightarrow B$	$B \rightarrow A$	$A \leftrightarrow B$	$(A \rightarrow B) \wedge (B \rightarrow A)$
0	0	1	1	1	1
0	1	1	0	0	0
1	0	0	1	0	0
1	1	1	1	1	1

2. $A \leftrightarrow B \equiv (A \wedge B) \vee (\neg A \wedge \neg B)$

A	B	$A \wedge B$	$\neg A$	$\neg B$	$A \leftrightarrow B$	$(A \wedge B) \vee (\neg A \wedge \neg B)$
0	0	0	1	1	1	1
0	1	0	1	0	0	0
1	0	0	0	1	0	0
1	1	1	0	0	1	1

A.6 De Morgan Equivalences

1. $\neg(A \wedge B) \equiv \neg A \vee \neg B$

A	B	$\neg(A \wedge B)$	$\neg A \vee \neg B$
0	0	1	1
0	1	1	1
1	0	1	1
1	1	0	0

2. $\neg(A \vee B) \equiv \neg A \wedge \neg B$

A	B	$\neg(A \vee B)$	$\neg A \wedge \neg B$
0	0	1	1
0	1	0	0
1	0	0	0
1	1	0	0

A.7 Distributivity of And and Or

1. $A \wedge (B \vee C) \equiv (A \wedge B) \vee (A \wedge C)$

A	B	C	$A \wedge (B \vee C)$	$(A \wedge B) \vee (A \wedge C)$
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	0	0
1	0	0	0	0
1	0	1	1	1
1	1	0	1	1
1	1	1	1	1

2. $A \vee (B \wedge C) \equiv (A \vee B) \wedge (A \vee C)$

A	B	C	$A \vee (B \wedge C)$	$(A \vee B) \wedge (A \vee C)$
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	1	1
1	0	0	1	1
1	0	1	1	1
1	1	0	1	1
1	1	1	1	1

Appendix B

Truth Tables of all Equivalences

B.1 And Equivalences

1. $A \wedge B \equiv B \wedge A$ (*Commutativity of And*)

A	B	$A \wedge B$	$B \wedge A$
0	0	0	0
0	1	0	0
1	0	0	0
1	1	1	1

2. $A \wedge A \equiv A$ (*Idempotence of And*)

A	$A \wedge A$
0	0
0	0
1	1
1	1

3. $(A \wedge B) \wedge C \equiv A \wedge (B \wedge C)$ (*Associativity of And*)

A	B	C	$(A \wedge B) \wedge C$	$A \wedge (B \wedge C)$
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	0	0
1	0	0	0	0
1	0	1	0	0
1	1	0	0	0
1	1	1	1	1

B.2 Or Equivalences

1. $A \vee B \equiv B \vee A$ (*Commutativity of Or*)

A	B	$A \vee B$	$B \vee A$
0	0	0	0
0	1	1	1
1	0	1	1
1	1	1	1

2. $A \vee A \equiv A$ (*Idempotence of Or*)

A	$A \vee A$
0	0
0	0
1	1
1	1

3. $(A \vee B) \vee C \equiv A \vee (B \vee C)$ (*Associativity of Or*)

A	B	C	$(A \vee B) \vee C$	$A \vee (B \vee C)$
0	0	0	0	0
0	0	1	1	1
0	1	0	1	1
0	1	1	1	1
1	0	0	1	1
1	0	1	1	1
1	1	0	1	1
1	1	1	1	1

B.3 Not Equivalences

1. $A \equiv \neg\neg A$

A	$\neg A$	$\neg\neg A$
0	1	0
1	0	1

B.4 Implies Equivalences

1. $A \rightarrow B \equiv \neg A \vee B$

A	B	$\neg A$	$A \rightarrow B$	$\neg A \vee B$
0	0	1	1	1
0	1	1	1	1
1	0	0	0	0
1	1	0	1	1

2. $A \rightarrow B \equiv \neg(A \wedge \neg B)$

A	B	$\neg B$	$A \wedge \neg B$	$A \rightarrow B$	$\neg(A \wedge \neg B)$
0	0	1	0	1	1
0	1	0	0	1	1
1	0	1	1	0	0
1	1	0	0	1	1

3. $\neg(A \rightarrow B) \equiv A \wedge \neg B$

A	B	$\neg B$	$A \rightarrow B$	$\neg(A \rightarrow B)$	$A \wedge \neg B$
0	0	1	1	0	0
0	1	0	1	0	0
1	0	1	0	1	1
1	1	0	1	0	0

B.5 If and Only If Equivalences

1. $A \leftrightarrow B \equiv (A \rightarrow B) \wedge (B \rightarrow A)$

A	B	$A \rightarrow B$	$B \rightarrow A$	$A \leftrightarrow B$	$(A \rightarrow B) \wedge (B \rightarrow A)$
0	0	1	1	1	1
0	1	1	0	0	0
1	0	0	1	0	0
1	1	1	1	1	1

2. $A \leftrightarrow B \equiv (A \wedge B) \vee (\neg A \wedge \neg B)$

A	B	$A \wedge B$	$\neg A$	$\neg B$	$A \leftrightarrow B$	$(A \wedge B) \vee (\neg A \wedge \neg B)$
0	0	0	1	1	1	1
0	1	0	1	0	0	0
1	0	0	0	1	0	0
1	1	1	0	0	1	1

B.6 De Morgan Equivalences

1. $\neg(A \wedge B) \equiv \neg A \vee \neg B$

A	B	$\neg(A \wedge B)$	$\neg A \vee \neg B$
0	0	1	1
0	1	1	1
1	0	1	1
1	1	0	0

2. $\neg(A \vee B) \equiv \neg A \wedge \neg B$

A	B	$\neg(A \vee B)$	$\neg A \wedge \neg B$
0	0	1	1
0	1	0	0
1	0	0	0
1	1	0	0

B.7 Distributivity of And and Or

1. $A \wedge (B \vee C) \equiv (A \wedge B) \vee (A \wedge C)$

A	B	C	$A \wedge (B \vee C)$	$(A \wedge B) \vee (A \wedge C)$
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	0	0
1	0	0	0	0
1	0	1	1	1
1	1	0	1	1
1	1	1	1	1

2. $A \vee (B \wedge C) \equiv (A \vee B) \wedge (A \vee C)$

A	B	C	$A \vee (B \wedge C)$	$(A \vee B) \wedge (A \vee C)$
0	0	0	0	0
0	0	1	0	0
0	1	0	0	0
0	1	1	1	1
1	0	0	1	1
1	0	1	1	1
1	1	0	1	1
1	1	1	1	1