

testcase12_parquet_parquet_mismatch_manual

null comparison

1. Run Summary

| | |
|--------------------|---|
| Application Name | :etl_pipeline_goldlayer |
| Protocol Name | :DATFDemo |
| Protocol File Path | :datf_core//test/testprotocol/testselection_template.xlsx |
| Testcase Name | :testcase12_parquet_parquet_mismatch_manual |
| Testcase Type | :null |
| Test Environment | :SIT |
| Start Time | :18-Mar-2025 04:46:22 UTC |
| End Time | :18-Mar-2025 04:48:18 UTC |
| Run Time | :0:01:56 |
| Test Result | :Failed |
| Reason | :Nulls are not matching for each column |

2. Configuration Details

| | |
|-------------------------|------------------------------|
| Compare Type | :likeobjectcompare |
| testquerygenerationmode | :Manual |
| Testcase Type | :null |
| Source Connection Name | :RawS3Bucket |
| Source Connection Type | :aws-s3 |
| Source Connection Value | :RawS3Bucket |
| Source Format | :parquet |
| Source Name | :patient_data_source_parquet |
| Source Path | :test/data/source |
| Target Connection Name | :CuratedS3Bucket |
| Target Connection Type | :aws-s3 |
| Target Connection Value | :CuratedS3Bucket |
| Target Format | :parquet |
| Target Name | :patient_data_target_parquet |
| Target Path | :test/data/target |
| Primary Keys | :id |

3. Null Summary

| | |
|---------------------------------------|---------|
| Test Result | :Failed |
| No of column has null in source | :5 |
| No of column has null in target | :5 |
| No of columns has null count match | :0 |
| No of columns has null count mismatch | :5 |

4. SQL Queries

4.1 Source Query

SELECT
ADDRESS,BIRTHDATE,BIRTHPLACE,CITY,COUNTY,DEATHDATE,DRIVERS,ETHNICITY,FIRST,GENDER,HEALTH
CARE_COVERAGE,HEALTHCARE_EXPENSES,LAST,LAT,LON,MAIDEN,MARITAL,PASSPORT,PREFIX,RACE,SSN,
STATE,SUFFIX,ZIP,id FROM rawpatients

4.2 Target Query

SELECT
ADDRESS,BIRTHDATE,BIRTHPLACE,CITY,COUNTY,DEATHDATE,DRIVERS,ETHNICITY,FIRST,GENDER,HEALTH
CARE_COVERAGE,HEALTHCARE_EXPENSES,LAST,LAT,LON,MAIDEN,MARITAL,PASSPORT,PREFIX,RACE,SSN,
STATE,SUFFIX,ZIP,id FROM curatedpatients

5. Columns having nulls at source and target

5.1 Columns having nulls in source

| S.No | Column | Count |
|------|-----------|--------|
| 1 | DEATHDATE | 900877 |

| | | |
|---|----------|--------|
| 2 | DRIVERS | 200539 |
| 3 | MAIDEN | 800319 |
| 4 | PASSPORT | 300807 |
| 5 | SUFFIX | 800558 |

5.2 Columns having nulls in target

| S.No | Column | Count |
|------|-----------|--------|
| 1 | DEATHDATE | 901273 |
| 2 | DRIVERS | 200008 |
| 3 | MAIDEN | 800625 |
| 4 | PASSPORT | 299989 |
| 5 | SUFFIX | 800405 |

5.3 Columns having null count mismatch between source and target

| S.No | Source Column Name | Src Null Count | Target Column Name | Tgt Null Count |
|------|--------------------|----------------|--------------------|----------------|
| 1 | DEATHDATE | 900877 | DEATHDATE | 901273 |
| 2 | DRIVERS | 200539 | DRIVERS | 200008 |
| 3 | MAIDEN | 800319 | MAIDEN | 800625 |
| 4 | PASSPORT | 300807 | PASSPORT | 299989 |
| 5 | SUFFIX | 800558 | SUFFIX | 800405 |

testcase23_parquet_snowflake_mismatch

null comparison

1. Run Summary

| | |
|--------------------|---|
| Application Name | :etl_pipeline_goldlayer |
| Protocol Name | :DATFDemo |
| Protocol File Path | :datf_core//test/testprotocol/testselection_template.xlsx |
| Testcase Name | :testcase23_parquet_snowflake_mismatch |
| Testcase Type | :null |
| Test Environment | :SIT |
| Start Time | :18-Mar-2025 04:48:52 UTC |
| End Time | :18-Mar-2025 04:49:42 UTC |
| Run Time | :0:00:49 |
| Test Result | : Failed |
| Reason | :Nulls are not matching for each column |

2. Configuration Details

| | |
|-------------------------|-------------------------------|
| Compare Type | :likeobjectcompare |
| testquerygenerationmode | :Auto |
| Testcase Type | :null |
| Source Connection Name | :RawS3Parquet |
| Source Connection Type | :aws-s3 |
| Source Connection Value | :RawS3Parquet |
| Source Format | :parquet |
| Source Name | :patients_source_parquet |
| Source Path | :test/data/source |
| Source Exclude Columns | :BIRTHDATE,DEATHDATE |
| Target Connection Name | :raw_snowflake_sql_connection |
| Target Connection Type | :snowflake |
| Target Connection Value | :raw_snowflake_sql_connection |
| Target Format | :table |
| Target Name | :SAMPLE_SRC_PATIENTS |
| Target Exclude Columns | :BIRTHDATE,DEATHDATE |
| Primary Keys | :id |

3. Null Summary

| | |
|---------------------------------------|-----------------|
| Test Result | : Failed |
| No of column has null in source | :7 |
| No of column has null in target | :7 |
| No of columns has null count match | :1 |
| No of columns has null count mismatch | :8 |

4. SQL Queries

4.1 Source Query

```
SELECT
ADDRESS,BIRTHPLACE,CITY,COUNTY,DRIVERS,ETHNICITY,FIRST,GENDER,HEALTHCARE_COVERAGE,HEALTHCARE_EXPENSES,LAST,LAT,LON,MAIDEN,MARITAL,PASSPORT,PREFIX,RACE,SSN,STATE,SUFFIX,ZIP,id
FROM actualpatients
```

4.2 Target Query

```
SELECT
ADDRESS,BIRTHPLACE,CITY,COUNTY,DRIVERS,ETHNICITY,FIRST,GENDER,HEALTHCARE_COVERAGE,HEALTHCARE_EXPENSES,ID,LAST,LAT,LON,MAIDEN,MARITAL,PASSPORT,PREFIX,RACE,SSN,STATE,SUFFIX,ZIP
FROM SAMPLE_SRC_PATIENTS
```

5. Columns having nulls at source and target

5.1 Columns having nulls in source

| S.No | Column | Count |
|------|--------|-------|
|------|--------|-------|

| | | |
|---|----------|------|
| 1 | DRIVERS | 213 |
| 2 | MAIDEN | 840 |
| 3 | MARITAL | 380 |
| 4 | PASSPORT | 273 |
| 5 | PREFIX | 244 |
| 6 | SUFFIX | 1159 |
| 7 | ZIP | 543 |

5.2 Columns having nulls in target

| S.No | Column | Count |
|------|----------|-------|
| 1 | DRIVERS | 213 |
| 2 | MAIDEN | 840 |
| 3 | MARITAL | 380 |
| 4 | PASSPORT | 273 |
| 5 | PREFIX | 244 |
| 6 | SUFFIX | 1159 |
| 7 | ZIP | 543 |

5.3 Columns having null count mismatch between source and target

| S.No | Source Column Name | Src Null Count | Target Column Name | Tgt Null Count |
|------|--------------------|----------------|--------------------|----------------|
| 1 | MAIDEN | 840 | LON | 0 |
| 2 | MARITAL | 380 | MAIDEN | 840 |
| 3 | PASSPORT | 273 | MARITAL | 380 |
| 4 | PREFIX | 244 | PASSPORT | 273 |
| 5 | RACE | 0 | PREFIX | 244 |
| 6 | SUFFIX | 1159 | STATE | 0 |
| 7 | ZIP | 543 | SUFFIX | 1159 |
| 8 | id | 0 | ZIP | 543 |

testcase24_snowflake_snowflake_etljob

null comparison

1. Run Summary

Application Name :etl_pipeline_goldlayer
Protocol Name :DATFDemo
Protocol File Path :datf_core//test/testprotocol/testselection_template.xlsx
Testcase Name :testcase24_snowflake_snowflake_etljob
Testcase Type :null
Test Environment :SIT
Start Time :18-Mar-2025 04:50:13 UTC
End Time :18-Mar-2025 04:51:04 UTC
Run Time :0:00:50
Test Result :Failed
Reason :Nulls are not matching for each column

2. Configuration Details

Compare Type :likeobjectcompare
testquerygenerationmode :Auto
Testcase Type :null
Source Connection Name :raw_snowflake_sql_connection
Source Connection Type :snowflake
Source Connection Value :raw_snowflake_sql_connection
Source Format :table
Source Name :SAMPLE_SRC_PATIENTS
Source Exclude Columns :BIRTHDATE,DEATHDATE
Target Connection Name :raw_snowflake_sql_connection
Target Connection Type :snowflake
Target Connection Value :raw_snowflake_sql_connection
Target Format :table
Target Name :SAMPLE_TGT_PATIENTS
Target Exclude Columns :BIRTHDATE,DEATHDATE
Primary Keys :ID

3. Null Summary

Test Result :Failed
No of column has null in source :7
No of column has null in target :9
No of columns has null count match :3
No of columns has null count mismatch :6

4. SQL Queries

4.1 Source Query

```
SELECT  
ADDRESS,BIRTHPLACE,CITY,COUNTY,DRIVERS,ETHNICITY,FIRST,GENDER,HEALTHCARE_COVERAGE,HEALT  
HCARE_EXPENSES,ID,LAST,LAT,LON,MAIDEN,MARITAL,PASSPORT,PREFIX,RACE,SSN,STATE,SUFFIX,ZIP  
FROM SAMPLE_SRC_PATIENTS
```

4.2 Target Query

```
SELECT  
ADDRESS,BIRTHPLACE,CITY,COUNTY,DRIVERS,ETHNICITY,FIRST,GENDER,HEALTHCARE_COVERAGE,HEALT  
HCARE_EXPENSES,ID,LAST,LAT,LON,MAIDEN,MARITAL,PASSPORT,PREFIX,RACE,SSN,STATE,SUFFIX,ZIP  
FROM SAMPLE_TGT_PATIENTS
```

5. Columns having nulls at source and target

5.1 Columns having nulls in source

| S.No | Column | Count |
|------|---------|-------|
| 1 | DRIVERS | 213 |

| | | |
|---|----------|------|
| 2 | MAIDEN | 840 |
| 3 | MARITAL | 380 |
| 4 | PASSPORT | 273 |
| 5 | PREFIX | 244 |
| 6 | SUFFIX | 1159 |
| 7 | ZIP | 543 |

5.2 Columns having nulls in target

| S.No | Column | Count |
|------|-----------|-------|
| 1 | DRIVERS | 213 |
| 2 | ETHNICITY | 6 |
| 3 | MAIDEN | 839 |
| 4 | MARITAL | 381 |
| 5 | PASSPORT | 273 |
| 6 | PREFIX | 244 |
| 7 | RACE | 5 |
| 8 | SUFFIX | 1157 |
| 9 | ZIP | 541 |

5.3 Columns having null count mismatch between source and target

| S.No | Source Column Name | Src Null Count | Target Column Name | Tgt Null Count |
|------|--------------------|----------------|--------------------|----------------|
| 1 | ETHNICITY | 0 | ETHNICITY | 6 |
| 2 | MAIDEN | 840 | MAIDEN | 839 |
| 3 | MARITAL | 380 | MARITAL | 381 |
| 4 | RACE | 0 | RACE | 5 |
| 5 | SUFFIX | 1159 | SUFFIX | 1157 |
| 6 | ZIP | 543 | ZIP | 541 |