

Ceypetco Supreme XHD

Ceypetco Supreme XHD is a premium quality and advanced diesel engine oil specially formulated using highly refined base oils and advanced additive system designed for use in modern, high output, low emission diesel engines including those fitted with Exhaust Gas Recirculation (EGR) as well older turbo charged engines running on low sulfur diesel or conventional high sulfur diesel fuel and operating under severe working conditions.

Features and Benefits

- Excellent protection against corrosive and soot induced wears in severe diesel operation
- Excellent high temperature deposits control
- Excellent TBN retention

Applications

Ceypetco Supreme XHD is ideal for heavy-duty diesel engines used in off-the-road trucks, construction equipment, agricultural equipment, power generators as well as gasoline-powered vehicles

Typical Characteristics

PROPERTIES	METHOD	SAE Grade	
		15W-40	20W-50
Density at 15°C, kg/l	ASTM D4052	0.8790	0.874
Flash Point, °C	ASTM D92	>210	>210
Pour Point, °C	ASTM D97	-30	-25
Kinematic viscosity at 40°C, cSt	ASTM D042	104.6	150.4
Kinematic viscosity at 100°C, cSt	ASTM D042	14.3	18.6
Viscosity Index	ASTM D2270	140	139
Total Base Number, mgKOH/g	ASTM D2896	10.0	10

Performance

- API CH-4

Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.