

Onfinity Smart API

Developer & Integration Guide

Identifier-based API for Onfinity (ViennaAdvantage). Create, update, read and act on master data, CRM records and sales documents using business identifiers instead of internal primary keys.

Version	2.6
Date	13 July 2026
Audience	Integration developers and AI integration agents
Entities	58 - basic setup, financial, master data, CRM, sales, HR/payroll (Section 9)
Capabilities	CRUD + retrieval (filter/sort/page/select) + nested writes + actions

Every function in Section 6 includes a sample request and response. Live source of truth: GET `/v1/_entities` and `/swagger`.

Contents

1. Overview	5
2. Base URL, hosting and docs	5
3. Authentication	5
4. Core concepts	5
5. Response shapes	5
6. Functions	6
7. Field behaviours	11
8. Errors	11
9. Entity reference	12
Basic setup	12
Tenant	12
Organization	12
Role	12
User	12
Calendar	13
FiscalYear	13
Country	13
City	13
SalesRegion	14
Greeting	14
Currency	14
ConversionType	14
CurrencyRate	14
UOM	15
DocType	15
Sequence	15
Tree	15
Financial & accounting	15
AccountingSchema	16
GLCategory	16
TaxCategory	16
Tax	16

Charge	16
Activity	17
Bank	17
PaymentTerm	17
Element	17
AccountGroup	18
Master data	18
BusinessPartner	18
BPGroup	18
Product	19
ProductCategory	19
PriceList	19
DiscountSchema	20
Warehouse	20
CRM	20
Campaign	20
Lead	20
Request	21
Opportunity	21
Channel	22
CampaignType	22
Sales	22
SalesQuotation	22
HR / Payroll (Workday integration)	23
JobFamily	23
Job	23
Department	23
Grade	23
GradeRate	24
Position	24
HolidayCalendar	24
HolidayDay	24
Qualification	24
University	25
PartnerBankAccount	25
EmployeeWorkInfo	25
EmployeeStatutoryInfo	25
EmployeeQualification	26
EmployeeDependent	26
LeaveType	26

LeaveEntry 26

10. Quick start (curl) 28

11. Integration rules for AI agents 28

1. Overview

The Onfinity Smart API is a thin, stateless REST layer in front of Onfinity's core API (VA-API). Callers work with **business identifiers** (search keys, names, ISO codes); the API resolves them to internal foreign keys and performs the insert, update, read, or process call through Onfinity.

Capability	Detail
Identifier-based	Send business keys (e.g. group: "Employees"); the API resolves the IDs.
CRUD	Create / upsert / partial-update / read, by business key.
Retrieval	List / search by identifier filters, with paging, sorting and field selection.
Nested writes	Create a parent and its children (and owned sub-records) in one call.
Window processes	Run record actions (e.g. Lead -> Prospect, complete a quotation).
Dry run	Validate + resolve a write without changing anything.
Stateless	No database; manifests are files; all data lives in Onfinity.
Authorization	Every call runs under the caller's Onfinity role; the API adds no privilege.

2. Base URL, hosting and docs

The Smart API is deployed alongside an Onfinity installation; obtain the base URL from your administrator. All paths are relative to it. An interactive Swagger UI is at `/swagger` and the OpenAPI document at `/swagger/v1/swagger.json`.

Use **HTTPS in production** - credentials travel in headers.

3. Authentication

Every request (except `/health` and `/swagger`) sends two headers, the Onfinity VA-API key pair. They are forwarded unchanged, so each call runs under that key's role - the API cannot exceed what the role permits.

Header	Description
<code>accessKey</code>	VA-API access key (issued by Onfinity).
<code>secretKey</code>	VA-API secret key (issued by Onfinity).

Missing/empty keys -> **401 NO_CREDENTIALS**. Resolving an identifier needs read access to the referenced table; otherwise the reference returns `MISSING_REF`.

4. Core concepts

Concept	Meaning
Business key	The key field uniquely identifies a record (maps to Value or DocumentNo). Reads/updates/actions address records by it.
Reference (ref)	A field whose value is a related record's identifier; resolved to a foreign key. Must match exactly one active record.
List	A human label mapped to an internal code (e.g. <code>productType "Item" -> I</code>).
Derived field	Auto-filled from a related row, no caller input (e.g. a quotation's org/location from the partner).
Owned sub-record	A nested object created first so its id fills a foreign key (e.g. an address).
Children	One-to-many collections sent as arrays; the parent link is set automatically.
Key by reference	Some one-to-one records are keyed by a related record's identifier (e.g. <code>EmployeeStatutoryInfo</code> is keyed by <code>businessPartner</code>) - send that identifier as the key.
Booleans / dates	Booleans accept true/false (stored Y/N). Dates are ISO strings (YYYY-MM-DD).
Dry run	Append <code>?dryRun=true</code> to a write to validate + resolve without changing data.

5. Response shapes

Writes return the mode, business key, internal id and (if sent) the child records. Dry runs add the resolved column values and a children plan. Errors return an error object.

6. Functions

Every function below shows a sample request and response. {entity} is a registered entity (Section 8); {key} is its business key.

6.1 Health check

Liveness

GET /health

No authentication. Confirms the service is up.

Response

```
{ "status": "ok" }
```

6.2 List entities

List registered entities

GET /v1/_entities

Returns the entity names the API serves.

Response

```
[ "BusinessPartner", "Campaign", "Lead", "Product",  
  "Opportunity", "Request", "SalesQuotation" ]
```

6.3 Create (insert-only)

Create a record

POST /v1/{entity}

Inserts a new record. Fails with 409 if the business key already exists. Identifiers are resolved to ids; unsupplied fields use Onfinity model defaults.

Request

```
{  
  "key": "SKU-100", "name": "Widget",  
  "productType": "Item",  
  "category": "1000001", "uom": "Each"  
}
```

Response

```
{  
  "mode": "created",  
  "key": "SKU-100",  
  "recordId": 1041220,  
  "dryRun": false,  
  "children": null  
}
```

POST is insert-only. To create-or-update, use PUT (6.4).

6.4 Upsert

Create or update by key

PUT /v1/{entity}

Inserts if the key is new, otherwise updates. Idempotent - safe to retry.

Request

```
{
  "key": "CUST-0042", "name": "Acme GmbH",
  "isCustomer": true,
  "group": "Employees",
  "priceList": "Gold Partner Price List",
  "paymentTerm": "Immediate"
}
```

Response

```
{
  "mode": "created",           // or "updated"
  "key": "CUST-0042",
  "recordId": 1041220
}
```

6.5 Partial update

Update selected fields

PATCH /v1/{entity}/{key}

Updates only the supplied fields of an existing record. Common use: deactivate a record.

Request

```
{ "isActive": false }
```

Response

```
{
  "mode": "updated",
  "key": "CUST-0042",
  "recordId": 1041220
}
```

6.6 List / search

List records (filter, page, sort, project)

GET /v1/{entity}

Query a collection. Filters use the same field names as writes (identifiers in, identifiers out). Supports paging, sorting and field selection. Returns identifiers by default; add `?ids=true` to also include raw foreign-key ids.

Request

```
// GET /v1/BusinessPartner?isCustomer=true&group=Customers
//      &sort=name&fields=key,name,group&page=1&pageSize=50
```

Response

```
{
  "page": 1, "pageSize": 50, "total": 2569,
  "items": [
    { "key": "CUST-0042", "recordId": 1041220,
      "name": "Acme GmbH", "group": "Customers" }
  ]
}
```

Query parameter	Effect
field=value	filter by any field using its identifier (e.g. group=Customers, isCustomer=true). Text supports a trailing * for prefix match.
page / pageSize	paging (pageSize default 50, max 200). Response includes total.
sort=field / sort=-field	sort ascending / descending; comma-separate for multiple keys.
fields=a,b,c	return only these fields (plus key and recordId).
ids=true	also include raw foreign-key ids next to the names (as <field>Id).

6.7 Read one

Read a record

GET /v1/{entity}/{key}

Returns the record with foreign keys mapped to identifiers and list codes to labels. Options: ?include=children embeds child collections; ?ids=true adds raw fk ids; ?fields=a, b projects selected fields.

Response

```
// GET /v1/Product/VISP0001?include=children
{
  "key": "VISP0001",
  "name": "5 Seater Sofa",
  "productType": "Item",          // code I -> label
  "category": "1000001",         // id -> M_Product_Category.Value
  "uom": "Each", "taxCategory": "Standard",
  "children": {
    "vendors": [ { "recordId": 5012, "vendor": "VEND-01", "poPrice": "420.0" } ],
    "substitutes": [], "relatedProducts": []
  }
}
```

6.8 Dry run

Validate without writing

POST|PUT|PATCH /v1/{entity}?dryRun=true

Performs all validation and identifier resolution and returns exactly what would be written - no change is made. Use it to verify a payload (catches MISSING_REF / MISSING_FIELD safely).

Request

```
{ "key": "VAI159", "name": "Sunny", "group": "Employees",
  "priceList": "Gold Partner Price List", "country": "DE" }
```

Response

```
{
  "mode": "would-update",
  "key": "VAI159",
  "recordId": 1040878,
  "dryRun": true,
  "resolved": {
    "Name": "Sunny",
    "C_BP_Group_ID": 1000035,    // "Employees"
    "M_PriceList_ID": 1000183,  // "Gold Partner Price List"
    "C_Country_ID": 101        // "DE"
  }
}
```

6.9 Nested write (children + owned records)

Create a parent with children in one call

POST /v1/{entity}

Send one-to-many relations as arrays; the parent link is auto-filled. An owned record (e.g. an address) is a nested object created first so its id fills a foreign key.

Request

```
{
  "key": "ACME-001", "name": "Acme GmbH",
  "isCustomer": true, "group": "Employees",
  "contacts": [
    { "name": "Jane Doe", "email": "jane@acme.example" }
  ],
  "locations": [
    { "name": "HQ",
      "address": { "address1": "Hauptstr 1", "city": "Berlin",
                  "postal": "10115", "country": "DE" } }
  ]
}
```

Response

```
{
  "mode": "created",
  "key": "ACME-001",
  "recordId": 1041240,
  "children": {
    "contacts": [ { "table": "AD_User", "id": 1005512 } ],
    "locations": [ { "table": "C_BPartner_Location", "id": 2003318 } ]
  }
}
```

6.10 List actions

List window processes on an entity

GET /v1/{entity}/_actions

Returns the record processes (actions) the entity supports.

Response

```
// GET /v1/Lead/_actions
[
  { "action": "generateProspect",    "label": "Generate Prospect",    "params": [] },
  { "action": "generateOpportunity", "label": "Generate Opportunity", "params": [] },
  { "action": "createRequest",       "label": "Create Request",       "params": [] },
  { "action": "addToTargetList",     "label": "Add To Target List",   "params": [] }
]
```

6.11 Run an action

Run a window process on a record

POST /v1/{entity}/{key}/actions/{action}

Resolves the record by key, then runs the process (optionally with parameters in the body). Returns the process message.

Request

```
// POST /v1/Lead/LEAD-001/actions/generateProspect
{ } // params if the process needs them
```

Response

```
{
  "action": "generateProspect",
  "key": "LEAD-001",
  "recordId": 1000451,
  "message": "Process executed successfully"
}
```

Examples: complete a quotation -> `POST /v1/SalesQuotation/{key}/actions/complete` ; add a partner to a target list -> `.../BusinessPartner/{key}/actions/addToTargetList`.

Menu processes (not bound to a record, e.g. Tenant `initialSetup`) use the keyless form POST `/v1/{entity}/actions/{action}` with parameters in the body.

7. Field behaviours

Behaviour	How it works (caller's view)
Reference	Send the related record's identifier (e.g. group: "Employees"). Resolved to the FK. 0 matches -> MISSING_REF; many -> AMBIGUOUS_REF.
List	Send the label exactly as listed for the field (e.g. productType: "Item"). Wrong value -> BAD_LIST_VALUE.
Derived	Filled automatically from a related record - you do not send it (e.g. a quotation's organisation and bill-to location come from the partner).
Manual vs list price	On a quotation line, send price to USE that price; omit it to let the Onfinity price list set the price.
Defaults	Required fields must be sent on insert. Omitted optional fields take Onfinity's model defaults.

Manual-price example (line price is used as sent):

8. Errors

Code	HTTP	Meaning
NO_CREDENTIALS	401	accessKey / secretKey header missing.
UNKNOWN_ENTITY / UNKNOWN_ACTION	404	No such entity / action.
NOT_FOUND	404	Record (by key) does not exist.
MISSING_KEY / MISSING_FIELD / MISSING_PARAM	400/422	A required key / field / action parameter is absent.
ALREADY_EXISTS	409	POST insert, but the key already exists.
AMBIGUOUS_KEY / AMBIGUOUS_REF	409/422	Key or reference matched more than one record.
MISSING_REF	422	A reference value matched no active record.
BAD_LIST_VALUE / BAD_NUMBER / TOO_LONG	422	A value is not a valid label / number / within length.
VAAPI_ERROR	502	The underlying Onfinity call or process failed (message included).

9. Entity reference

Each entity is addressed by name (e.g. /v1/Lead). Tables show the API field, type, whether required on insert, and how it maps/resolves in Onfinity. Refs/lists carry the resolution. See /swagger for the exhaustive field list.

Basic setup

Tenant

Onfinity table AD_Client. Key: key = tenant name (no Value column).

A raw insert creates only the AD_Client row; full provisioning is the initialSetup process.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
description	string	-	Description
isActive	boolean	-	IsActive (default true)

Actions (POST /v1/Tenant/{key}/actions/{action})

action	Process / effect
initialSetup	MENU action - fully provisions a tenant (client + org + users + roles + accounting + calendar) via MSetup.CreateClient. Params: ClientName, OrgName, AdminUserName, NormalUserName. Call: POST /v1/Tenant/actions/initialSetup

Organization

Onfinity table AD_Org. Key: key = search key (Value).

AD_Client_ID comes from the calling session.

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
isSummary	boolean	-	IsSummary (default false)
salesRegion	ref	-	C_SalesRegion by Value

Role

Onfinity table AD_Role. Key: key = role name (no Value).

Raw insert = role row only; window/org access grants are separate (role window or Initial Client Setup).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
userLevel	string	-	UserLevel mask, e.g. ' CO' (model defaults if omitted)
isAdministrator / isAccessAllOrgs	boolean	-	default false
isCanExport / isCanReport / isCanApproveOwnDoc	boolean	-	default true
confirmQueryRecords	number	-	default 0

User

Onfinity table AD_User. Key: key = search key (Value).

Login enabling / password are handled separately.

Field	Type	Req	Maps to / resolution
key	string	Yes	Value

Field	Type	Req	Maps to / resolution
name	string	Yes	Name
email	string	Yes	EMail
phone / description	string	-	Phone / Description
role	ref	-	AD_Role by Name
businessPartner	ref	-	C_BPartner by Value
greeting	ref	-	C_Greeting by Name

Calendar

Onfinity table C_Calendar. Key: key = calendar name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
description	string	-	Description

FiscalYear

Onfinity table C_Year. Key: key = the year, e.g. '2026' (FiscalYear).

The key is scoped by calendar - pass 'calendar' in the body of reads/actions to select the right year.

Field	Type	Req	Maps to / resolution
key	string	Yes	FiscalYear (unique per calendar)
calendar	ref	Yes	C_Calendar by Name
description	string	-	Description

Children

periods[] - C_Period: name(req), periodNo(req), startDate(req), endDate, periodType(Standard | Adjustment)

Actions (POST /v1/FiscalYear/{key}/actions/{action})

action	Process / effect
createPeriods	auto-generate the year's periods (optional 'month' param)

Country

Onfinity table C_Country. Key: key = ISO country code.

Field	Type	Req	Maps to / resolution
key	string	Yes	CountryCode (ISO alpha-2, e.g. DE)
name	string	Yes	Name
regionName	string	-	RegionName (label for the 'region' field)
salesRegion	ref	-	C_SalesRegion by Value

Children

regions[] - C_Region: name(req), isDefault

City

Onfinity table C_City. Key: key = city name (scoped by country).

City names are not unique - the key is scoped by country; pass 'country' to disambiguate.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
country	ref	-	C_Country by CountryCode

Field	Type	Req	Maps to / resolution
postal	string	-	Postal

SalesRegion

Onfinity table C_SalesRegion. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (what 'salesRegion' refs resolve)
name	string	Yes	Name
isSummary / isDefault	boolean	-	default false

Greeting

Onfinity table C_Greeting. Key: key = greeting name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what 'greeting' refs resolve)
greeting	string	-	Greeting text printed on correspondence
isFirstNameOnly / isDefault	boolean	-	default false

Currency

Onfinity table C_Currency. Key: key = ISO currency code.

Field	Type	Req	Maps to / resolution
key	string	Yes	ISO_Code (3 letters, e.g. EUR)
description	string	Yes	Description
symbol	string	-	CurSymbol
stdPrecision	number	-	StdPrecision (default 2)
costingPrecision	number	-	CostingPrecision (default 4)
isEuro / isEMUMember	boolean	-	IsEuro / IsEMUMember (default false)

ConversionType

Onfinity table C_ConversionType. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (rate type, e.g. Spot)
name	string	Yes	Name
isDefault	boolean	-	default false

CurrencyRate

Onfinity table C_Conversion_Rate. Key: validFrom = ISO date (scoped key).

No single key - identified by (fromCurrency, toCurrency, conversionType, validFrom). Key = validFrom, scoped by the pair + type.

Field	Type	Req	Maps to / resolution
validFrom	string	Yes	ValidFrom (the key)
fromCurrency	ref	Yes	C_Currency by ISO_Code (source)
toCurrency	ref	Yes	C_Currency by ISO_Code (target)
conversionType	ref	Yes	C_ConversionType by Name
multiplyRate	number	Yes	source * rate = target (divideRate auto-derived)
validTo	string	-	ISO date

UOM

Onfinity table C_UOM. Key: key = name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what 'uom' refs resolve)
uomCode	string	Yes	X12DE355 (EDI UOM code, e.g. EA)
symbol	string	-	UOMSymbol
stdPrecision / costingPrecision	number	-	default 0
isDefault	boolean	-	default false

DocType

Onfinity table C_DocType. Key: key = document type name.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what 'docType' refs resolve)
value	string	-	Value (optional search key)
docBaseType	list	Yes	Sales Order Purchase Order AR Invoice AP Invoice AR/AP Credit Memo AR Receipt AP Payment Material Shipment Material Receipt Material Movement Physical Inventory GL Journal GL Document
glCategory	ref	Yes	GL_Category by Name
isSOTrx	boolean	-	IsSOTrx
documentCopies	number	-	DocumentCopies (default 1)
hasCharges / isDefault	boolean	-	default false

Sequence

Onfinity table AD_Sequence. Key: key = sequence name (no Value).

Document / number sequence. System counters are model-defaulted.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
description	string	-	Description
prefix / suffix	string	-	Prefix / Suffix
currentNext	number	-	CurrentNext (default 1000000)
incrementNo	number	-	IncrementNo (default 1)
isAutoSequence	boolean	-	default true

Tree

Onfinity table AD_Tree. Key: key = tree name.

A hierarchy tree. Records of tree-supported tables auto-attach as nodes on insert.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what Element 'tree' resolves)
treeType	list	Yes	Element Value Organization BPartner Product Campaign Activity Sales Region Project Menu ...
table	ref	Yes	AD_Table by TableName (the tree's table, e.g. C_ElementValue)
isAllNodes / isDefault	boolean	-	default false

Financial & accounting

AccountingSchema

Onfinity table C_AcctSchema. Key: key = schema name.

A raw insert creates the header only - NOT a usable schema. The real one (account elements, default accounts, GL categories) is built by Initial Client Setup.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
currency	ref	Yes	C_Currency by ISO_Code
costingMethod	list	-	Standard Costing Average PO Average Invoice Fifo Lifo Weighted Average Cost Last Invoice Last PO Price
costingLevel	list	-	Client Organization Warehouse Batch/Lot
gaap	list	-	International GAAP German HGB French Accounting Standard
autoPeriodControl / isAccrual	boolean	-	default true

GLCategory

Onfinity table GL_Category. Key: key = name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what DocType 'glCategory' resolves)
categoryType	list	Yes	Document Manual Imported Greeting
isDefault	boolean	-	default false

TaxCategory

Onfinity table C_TaxCategory. Key: key = name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
isDefault	boolean	-	IsDefault (default false)

Tax

Onfinity table C_Tax. Key: key = tax name.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
rate	number	Yes	Rate (percentage, e.g. 19)
taxCategory	ref	-	C_TaxCategory by Name
country	ref	-	C_Country by CountryCode
isSalesTax / isDocumentLevel / isTaxExempt / isDefault / isSummary	boolean	-	default false

Charge

Onfinity table C_Charge. Key: key = charge name.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (e.g. Handling, Shipping)
chargeAmt	number	-	ChargeAmt (default 0)
taxCategory	ref	Yes	C_TaxCategory by Name
activity	ref	-	C_Activity by Value

Field	Type	Req	Maps to / resolution
isSameTax / isSameCurrency / isTaxIncluded	boolean	-	isSameTax / isSameCurrency default true

Activity

Onfinity table C_Activity. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (billing code / activity-based costing)
name	string	Yes	Name
description	string	-	Description
isSummary	boolean	-	default false

Bank

Onfinity table C_Bank. Key: key = bank name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
routingNo	string	Yes	RoutingNo (ABA)
isOwnBank	boolean	-	default true

Children

bankAccounts[] - C_BankAccount: accountNo(req), accountType(Checking | Savings), currency(ref), creditLimit, currentBalance, isDefault

PaymentTerm

Onfinity table C_PaymentTerm. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (what 'paymentTerm' refs resolve)
name	string	Yes	Name
netDays	number	-	NetDays (days until due)
discount / discountDays / graceDays	number	-	Discount / DiscountDays / GraceDays (default 0)
afterDelivery / isDueFixed / isDefault	boolean	-	default false

Element

Onfinity table C_Element. Key: key = element name.

Chart of accounts. Accounts auto-attach to the element's tree; send 'parent' on an account to nest it. The full chart is normally built by Initial Client Setup.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
elementType	list	Yes	Account User defined
tree	ref	Yes	AD_Tree by Name (the account tree)
isNaturalAccount	boolean	-	default true
isBalancing	boolean	-	default false
vformat	string	-	VFormat (value mask)

Children

accounts[] - C_ElementValue: value(req, account code), name(req), accountType(Asset|Expense|Liability|Owner's Equity|Revenue|Memo), accountSign(Natural|Debit|Credit), isSummary, accountGroup(ref C_AccountGroup by Name), parent(optional - a sibling account's code, to nest this account under it in the tree)

AccountGroup

Onfinity table C_AccountGroup. Key: key = name (no Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what an account's 'accountGroup' resolves)
value	string	-	Value (optional search key)

Master data

BusinessPartner

Onfinity table C_BPartner. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (upsert identity)
name	string	Yes	Name
isCustomer / isVendor / isProspect / isEmployee / isSalesRep	boolean	-	role flags (default false)
taxId / duns / referenceNo / url	string	-	TaxID / DUNS / ReferenceNo / URL
email / phone / mobile / fax	string	-	EMail / Phone / Mobile / Fax
creditLimit / flatDiscount	number	-	SO_CreditLimit / FlatDiscount
group	ref	Yes	C_BP_Group by Value
priceList	ref	-	M_PriceList by Name
paymentTerm	ref	-	C_PaymentTerm by Value
country	ref	-	C_Country by CountryCode (ISO alpha-2)
greeting / salesRegion	ref	-	C_Greeting by Name / C_SalesRegion by Value
deliveryRule	list	-	Availability Force Complete Line Manual Complete Order
invoiceRule	list	-	After Partial Delivery Immediate After Full Order Delivery Customer Schedule after Delivery

Children

contacts[] - AD_User: name(req), email(req), phone, key

locations[] - C_BPartner_Location: name(req), isBillTo/isShipTo/isPayFrom/isRemitTo, phone, address(owned C_Location: address1/2, city, postal, regionName, country(req))

Actions (POST /v1/BusinessPartner/{key}/actions/{action})

action	Process / effect
generateOpportunity	create an opportunity from this (prospect) partner
generateCustomer	generate a customer account
addToTargetList	add the partner to a marketing target list

BPGroup

Onfinity table C_BP_Group. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (what BusinessPartner 'group' resolves)
name	string	Yes	Name
priceList	ref	-	M_PriceList by Name
isDefault / isConfidentialInfo	boolean	-	default false

Product

Onfinity table M_Product. Key: key = search key (Value).

Also exposes optional inventory/manufacturing flags (isBOM, isManufactured, isDropShip, ...), default false.

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
description / help / sku / upc / make / model	string	-	Description / Help / SKU / UPC / Make / Model
productType	list	Yes	Item Service Expense Resource
category	ref	Yes	M_Product_Category by Value
uom	ref	Yes	C_UOM by Name (e.g. 'Each')
taxCategory / brand	ref	-	C_TaxCategory by Name / M_Brand by Name
isSold / isPurchased / isStocked	boolean	-	default true
qtyTolerance	number	-	QtyTolerance

Children

vendors[] - M_Product_PO: vendor(req, C_BPartner by Value), currency(C_Currency ISO), uom, isCurrentVendor, listPrice, poPrice, orderMin, orderPack, priceEffective, manufacturer

substitutes[] - M_Substitute: name(req), substitute(req, product by Value), description

relatedProducts[] - M_RelatedProduct: name(req), relatedProduct(req, product by Value), relatedType(Alternative|Mandatory|Web Promotion|Supplemental), quantity, uom

ProductCategory

Onfinity table M_Product_Category. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (what 'category' refs resolve)
name	string	Yes	Name
mmPolicy	list	-	FiFo LiFo
taxCategory	ref	-	C_TaxCategory by Name
isDefault / isPurchasedToOrder	boolean	-	default false

PriceList

Onfinity table M_PriceList. Key: key = name (no Value).

Prices live in price-list versions (M_PriceList_Version) + M_ProductPrice, set up separately.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what 'priceList' refs resolve)
currency	ref	Yes	C_Currency by ISO_Code
isSOPriceList	boolean	-	IsSOPriceList (sales=true / purchase=false, default true)

Field	Type	Req	Maps to / resolution
isTaxIncluded / enforcePriceLimit / isDefault	boolean	-	default false
pricePrecision	number	-	PricePrecision (default 2)

DiscountSchema

Onfinity table M_DiscountSchema. Key: key = name (no Value).

Discount breaks/lines are set up separately.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
discountType	list	Yes	Pricelist Breaks Flat Percent
validFrom	string	Yes	ValidFrom (ISO date)
isQuantityBased / isBPartnerFlatDiscount	boolean	-	default false

Warehouse

Onfinity table M_Warehouse. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (what 'warehouse' refs resolve)
name	string	Yes	Name
separator	string	-	Separator (default '-')
isDisallowNegativeInv / isWMSEnabled	boolean	-	default false
address	owned	Yes	owned C_Location: address1, city, postal, country(req)

Children

locators[] - M_Locator: value(req), x/y/z (aisle/bin/level), isDefault, priorityNo(default 50), pickingSeqNo, putawaySeqNo, isAvailableForAllocation/ToPromise

CRM

Campaign

Onfinity table C_Campaign. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
description	string	-	Description
costs	number	-	Costs (defaults 0)
startDate / endDate	string	-	StartDate / EndDate (ISO date)
expectedRevenue / expectedLeads / actualRevenue / ...	number	-	campaign metrics
channel / campaignType	ref	-	C_Channel by Name / C_CampaignType by Name

Lead

Onfinity table C_Lead. Key: key = your external reference (DocumentNo).

Field	Type	Req	Maps to / resolution
key	string	Yes	DocumentNo (your external lead ref; used for dedupe)
name	string	Yes	Name
company / firstName / lastName / contactName / title	string	-	BPName / FirstName / LastName / ContactName / Title
email / phone / mobile / url / description	string	-	EMail / Phone / Mobile / URL / Description
numberEmployees / salesVolume	number	-	NumberEmployees / SalesVolume
leadTarget	list	-	Customer Partnership
source / qualification	ref	-	R_Source by Name / C_LeadQualification by Name
campaign / businessPartner	ref	-	C_Campaign by Value / C_BPartner by Value
country / salesRegion	ref	-	C_Country by CountryCode / C_SalesRegion by Value

Actions (POST /v1/Lead/{key}/actions/{action})

action	Process / effect
generateProspect	convert the lead into a business partner (prospect)
generateOpportunity	create an opportunity from the lead
createRequest	create a request/case from the lead
addToTargetList	add the lead to a target list

Request

Onfinity table R_Request. Key: key = your external reference (DocumentNo).

Field	Type	Req	Maps to / resolution
key	string	Yes	DocumentNo (your external ticket ref)
summary	string	Yes	Summary (the request text)
requestType	ref	Yes	R_RequestType by Name (Request Question Issue Suggestion)
priority	list	-	Urgent High Medium Low Minor
requestAmt / comment	number / string	-	RequestAmt / Help
status / category / source	ref	-	R_Status / R_Category / R_Source by Name
businessPartner / campaign	ref	-	C_BPartner / C_Campaign by Value

Children

updates[] - R_RequestUpdate: result(req, the note text), confidentiality(Public|Partner Confidential|Internal), startTime, endTime

Opportunity

Onfinity table VAS_Opportunity. Key: key = search key (Value).

The C_Opportunity table is an unused stub; the real opportunity table is VAS_Opportunity (VAS module), with line children in VAS_OppLines.

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name

Field	Type	Req	Maps to / resolution
description / comments	string	-	Description / Comments
probability / plannedAmt / estimatedBudget	number	-	Probability / PlannedAmt / VAS_EstimatedBudgetAmt
enquiryDate / decisionDate / nextStepDate	string	-	ISO dates
stage	list	-	Prospecting Discovery/Design Product Evaluation Proposal Negotiation Won Lost/Archived
type	list	-	New Business Renewal Upsell Cross-sell Service Contract
budget	list	-	Confirmed Constrained No Budget Not Discussed Planned
riskLevel	list	-	Financial Technical Timeline Resource Competition Approval Risk
businessPartner / campaign	ref	-	C_BPartner / C_Campaign by Value
currency	ref	-	C_Currency by ISO_Code
lead	ref	-	C_Lead by external reference (DocumentNo)

Children

lines[] - VAS_OppLines: product(req, by Value), qty(req), price (used as sent), plannedAmt, discount, lineNo, description; uom derived from the product

Actions (POST /v1/Opportunity/{key}/actions/{action})

action	Process / effect
generateQuotation	create a sales quotation from the opportunity
generateOrder	create a sales order from the opportunity

Channel

Onfinity table C_Channel. Key: key = channel name.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what Campaign 'channel' resolves)

CampaignType

Onfinity table C_CampaignType. Key: key = campaign type name.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name (what Campaign 'campaignType' resolves)

Sales

SalesQuotation

Onfinity table C_Order. Key: key = nominal (use poReference for your ref).

Transactional document (header + lines). Created as a draft.

Field	Type	Req	Maps to / resolution
key	string	Yes	DocumentNo (the model may reassign it; insert-only)
businessPartner	ref	Yes	C_BPartner by Value
docType	ref	Yes	C_DocType by Name ('Sales Quotation' / 'Sales Proposal')
dateOrdered	string	Yes	DateOrdered (ISO date)
priceList	ref	Yes	M_PriceList by Name
currency	ref	Yes	C_Currency by ISO_Code

Field	Type	Req	Maps to / resolution
warehouse	ref	Yes	M_Warehouse by Value (in the partner's organisation)
paymentTerm	ref	Yes	C_PaymentTerm by Value
poReference / description	string	-	POReference / Description
organisation, bill-to location	derived	-	AD_Org_ID + C_BPartner_Location_ID from the partner (auto)

Children

lines[] - C_OrderLine: product(req, by Value), warehouse(req, by Value), qty(req), price(optional - if sent it is USED, else the price list drives), description. UOM + org are derived.

Actions (POST /v1/SalesQuotation/{key}/actions/{action})

action	Process / effect
complete	complete the document (DocAction CO)
convertToOrder	convert the quotation to a sales order

HR / Payroll (Workday integration)

The HR and payroll tables used when Onfinity is the payroll engine behind Workday: organisation structure (job families, jobs, grades, positions, holiday calendars) plus employee records (work info, statutory info, qualifications, dependents, bank accounts) and leave. The employee is a BusinessPartner - employee-linked entities reference it by its Value.

JobFamily

Onfinity table VA058_JobFamily. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
startDate	string	Yes	VA058_StartDate (ISO date)

Job

Onfinity table VA058_Job. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
startDate	string	Yes	VA058_StartDate (ISO date)
jobFamily	ref	Yes	VA058_JobFamily by Value

Department

Onfinity table VA058_Department. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name

Grade

Onfinity table VA058_Grade. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value

Field	Type	Req	Maps to / resolution
name	string	Yes	Name

GradeRate

Onfinity table VA058_GradeRate. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name

Children

gradeValues[] - VA058_GradeRtValue: grade(req, VA058_Grade by Value), minimum(req), midValue(req), maximum(req), userVal

Position

Onfinity table VA058_Position. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
startDate	string	Yes	VA058_StartDate (ISO date)
job	ref	Yes	VA058_Job by Value
grade	ref	-	VA058_Grade by Value
qualification	ref	-	VA058_Qualification by Name

Children

linkedGrades[] - VA058_PosLinkedGrades: grade(req, VA058_Grade by Value)

HolidayCalendar

Onfinity table VA058_HolidayCalndr. Key: key = calendar name.

Field	Type	Req	Maps to / resolution
key	string	Yes	VA058_HolidayCalendarName
startDate / endDate	string	-	VA058_StartDate / VA058_EndDate (ISO date)

HolidayDay

Onfinity table VA058_HolidayDay. Key: key = holiday name (scoped by calendar).

Holiday days belong to a calendar - pass 'calendar' to disambiguate the key.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
calendar	ref	Yes	VA058_HolidayCalndr by name
date	string	-	Date1 (ISO date)
hours	number	-	VA058_HolidayHrs
hasRegion	boolean	-	VA058_HasRegion (default false)

Children

regions[] - VA058_HolidayCalndrRegion: country(C_Country by CountryCode)

Qualification

Onfinity table VA058_Qualification. Key: key = qualification name.

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
categoryName	list	Yes	Bachelor Master Honors Degree Doctoral Degree Phd
country	ref	Yes	C_Country by CountryCode

University

Onfinity table VA058_University. Key: key = search key (Value).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value
name	string	Yes	Name
country	ref	-	C_Country by CountryCode

PartnerBankAccount

Onfinity table C_BP_BankAccount. Key: accountNo = account number (scoped by employee).

Bank account of an employee/partner. Key = account number, scoped by businessPartner.

Field	Type	Req	Maps to / resolution
accountNo	string	Yes	AccountNo (the key)
businessPartner	ref	Yes	C_BPartner by Value (the employee/partner)
bank	ref	-	C_Bank by Name
accountName	string	-	A_Name
bban	string	-	BBAN
isACH	boolean	-	IsACH (default false)

EmployeeWorkInfo

Onfinity table VA058_EmpWorkInfo. Key: key = assignment reference (scoped by employee).

Field	Type	Req	Maps to / resolution
key	string	Yes	Value (your assignment reference)
businessPartner	ref	Yes	C_BPartner by Value (the employee)
startDate	string	Yes	VA058_StartDate (ISO date)
primary	boolean	Yes	VA058_PrimaryFlag
assignmentStatus	list	Yes	Confirmed Probation Suspended Salary On Hold Resignation Retirement Retrenchment Terminate
department / position / job / grade	ref	-	VA058_Department / VA058_Position / VA058_Job / VA058_Grade by Value
endDate	string	-	VA058_EndDate (ISO date)

EmployeeStatutoryInfo

Onfinity table VA096_StatInfo. Key: businessPartner = the employee (key by reference).

India statutory info, 1:1 with an employee - keyed BY the employee. Resident-status and tax-regime lists are omitted pending code values.

Field	Type	Req	Maps to / resolution
businessPartner	ref	Yes	C_BPartner by Value - IS the key (one record per employee)
contributingToEPF	boolean	-	VA096_IsContributingToEPF
uanNumber / epfNumber	string	-	VA096_UANNumber / VA096_EPFNumber
contributingToTax	boolean	-	VA096_ContToTax

Field	Type	Req	Maps to / resolution
incomeTaxNo	string	-	VA096_IncTaxNo
contributingToESI	boolean	-	VA096_ControESI
esiNumber	string	-	VA096_ESINum
labourWelfareFund	string	-	VA096_LWF

EmployeeQualification

Onfinity table VA058_EmpQualif. Key: key = qualification name (scoped by employee).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
businessPartner	ref	Yes	C_BPartner by Value (the employee)
qualification	ref	-	VA058_Qualification by Name
university	ref	-	VA058_University by Value

EmployeeDependent

Onfinity table VA058_EmpDependents. Key: key = dependent name (scoped by employee).

Field	Type	Req	Maps to / resolution
key	string	Yes	Name
businessPartner	ref	Yes	C_BPartner by Value (the employee)
relationType	list	-	Spouse Child Father Mother Brother Sister Grandfather Grandmother In-Law
gender	list	-	Male Female
dateOfBirth	string	-	VA058_DOB (ISO date)

Children

qualifications[] - VA058_EmpDepQualif: name(req)

LeaveType

Onfinity table VA086_AbsenceType. Key: key = leave type name.

Category / units / balance lists are omitted pending code values.

Field	Type	Req	Maps to / resolution
key	string	Yes	VA086_Type
startDate / endDate	string	-	VA086_StartDate / VA086_EndDate (ISO date)
carriedOver	boolean	-	VA086_IsCarriedOver (default false)
halfDayAllowed	boolean	-	VA086_IsHalfDay (default false)
negativeAllowed	boolean	-	VA086_IsNegativeLeave (default false)
excludeHolidayweek	boolean	-	VA086_IsExcludeHW (default false)

LeaveEntry

Onfinity table VA086_AbsenceEntries. Key: startDate = start date (scoped by employee + leave type).

A leave record. Idempotency key = start date, scoped by employee + leave type.

Field	Type	Req	Maps to / resolution
startDate	string	Yes	VA086_StartDate (the key, ISO date)
businessPartner	ref	Yes	C_BPartner by Value (the employee)
absenceType	ref	Yes	VA086_AbsenceType by name
endDate	string	-	VA086_EndDate (ISO date)
duration	number	-	VA086_Duration (applied days)

Field	Type	Req	Maps to / resolution
approvedDuration	number	-	VA086_ApprovedDuration
comments	string	-	VA086_Comments

10. Quick start (curl)

11. Integration rules for AI agents

Rule	Detail
Discover	GET /v1/_entities ; GET /v1/{entity}/_actions ; /swagger/v1/swagger.json for the schema.
Authenticate	Always send accessKey + secretKey. Without them every data call is 401.
Identifiers, not ids	Send business identifiers for refs (country='DE'), never numeric *_ID values.
Validate first	POST/PUT with ?dryRun=true and inspect 'resolved' before writing.
Upsert	PUT to create-or-update by 'key'; idempotent, safe to retry.
Required fields	Honour the 'Req' column in Section 9 on insert.
References / lists	A ref must resolve to one active record; lists use the exact labels in Section 9.
Nested data	Children as arrays; an owned record (e.g. address) as a nested object. Derived fields are not sent.
Actions	POST /v1/{entity}/{key}/actions/{action}; pass process params in the body when required.
Errors	Parse error.code (Section 8); 4xx = fix the payload, 502 = surface the Onfinity message.

Flow: discover entity + required fields -> build payload with identifiers -> dry-run -> if 'resolved' is correct, repeat without dryRun -> read back / run an action. Treat /v1/_entities and /swagger as the live source of truth; the entity and action sets grow over time.

Onfinity Smart API - Developer & Integration Guide - v2.6 - 13 July 2026.