PRACTICAL NO: 3

Aim - Create a network with three routers with BGP and each router associated network will have minimum three PC. Show connectivity.

1. Align 9 end-devices as follows:



2. Set the DNS, Gateway and Fast Ethernet connections for all the PCs as follows:






PC6
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC6
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 30.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC5
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 00D0.BC5C.D575
IP Configuration
DHCP
Static
IP Address 20.0.0.3
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address: FE80::2D0:BCFF:FE5C:D575
Top


PC5
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC5
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 20.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC4
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 0009.7C5D.1A81
IP Configuration
DHCP
Static
IP Address 20.0.0.2
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address: FE80::209:7CFF:FE5D:1A81
Top


PC4
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC4
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 20.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC3
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 00E0.8F95.7B06
IP Configuration
DHCP
Static
IP Address 20.0.0.1
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address: FE80::2E0:8FFF:FE95:7B06
Top


PC2
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 00E0.A303.7210
IP Configuration
DHCP
Static
IP Address 10.0.0.3
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address: FE80::2E0:A3FF:FE03:7210
Top


PC3
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC3
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 20.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC2
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC2
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 10.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC1
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 0060.475B.B616
IP Configuration
DHCP
Static
IP Address 10.0.0.2
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address FE80::260:47FF:FE5B:B616
Top


PC1
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC1
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 10.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC0
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 000C.85DE.25AC
IP Configuration
DHCP
Static
IP Address 10.0.0.1
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address FE80::20C:85FF:FEDE:25AC
Top


PC0
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
Global Settings
Display Name PC0
Interfaces FastEthernet0
Gateway/DNS IPv4
DHCP
Static
Gateway 10.0.0.4
DNS Server 255.255.255.0
Gateway/DNS IPv6
DHCP
Auto Config
Static
IPv6 Gateway
Top


PC8
Physical Config Desktop Programming Attributes
GLOBAL
Settings
Algorithm Settings
INTERFACE
FastEthernet0
Bluetooth
FastEthernet0
Port Status On
Bandwidth 100 Mbps 10 Mbps Auto
Duplex Half Duplex Full Duplex Auto
MAC Address 0090.0C10.A370
IP Configuration
DHCP
Static
IP Address 30.0.0.3
Subnet Mask 255.255.255.0
IPv6 Configuration
DHCP
Auto Config
Static
IPv6 Address
Link Local Address FE80::290:CFF:FE10:A370
Top

3. Add 3 Switches as follows:



4. Add 3 Routers and connect all the components using Fast Ethernet connection as follows:



5. Power off each of the Routers and add the NIM-2T Module to all the Routers as follows:



6. Connect the Routers using Serial DTE wires as shown:



7. Configure Router 0 using the Command Line Interface as follows:



8. Configure Router 1 using the Command Line Interface as follows:





9. Configure Router 2 using the Command Line Interface as follows:





10. The Final connection will look as shown:



11. Note how intra-connection packet sending succeeds and inter-connection fails:

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Successful	PC0	PC1	ICMP		0.000	N	0	(edit)
	Successful	PC3	PC4	ICMP		0.000	N	1	(edit)
	Successful	PC6	PC7	ICMP		0.000	N	2	(edit)

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Successful	Router0	Router1	ICMP		0.000	N	0	(edit)
	Successful	Router1	Router2	ICMP		0.000	N	1	(edit)

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Failed	PC0	PC3	ICMP		0.000	N	0	(edit)
	Failed	PC3	PC6	ICMP		0.000	N	1	(edit)
	Failed	PC8	PC2	ICMP		0.000	N	2	(edit)

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Failed	Router0	Router2	ICMP		0.000	N	0	(edit)

12. Configure BGP Routing in Router 0 as follows:



13. Configure BGP Routing in Router 1 as follows:



14. Configure BGP Routing in Router 2 as follows;



15. After successful BGP configuration, send packets over the inter-connected network :

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Successful	PC0	PC3	ICMP		0.000	N	0	(edit)
	Failed	PC0	PC6	ICMP		0.000	N	1	(edit)
	Successful	PC0	PC6	ICMP		0.000	N	2	(edit)

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Successful	Router0	Router2	ICMP		0.000	N	0	(edit)
	Successful	Router1	Router0	ICMP		0.000	N	1	(edit)
	Successful	Router2	Router0	ICMP		0.000	N	2	(edit)

16. Finally, in every Router's CLI, type 'show ip route' to get the connection details:

ROUTER 0



ROUTER 1



ROUTER 2


Router2
Physical
Config
CLI
Attributes
IOS Command Line Interface
changed state to up
%LINK-5-CHANGED: Interface Serial0/1/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial0/1/0, changed state to up
%BGP-5-ADJCHANGE: neighbor 50.0.0.1 Up
Router>show ip bgp
BGP table version is 7, local router ID is 50.0.0.2
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
Network Next Hop Metric LocPrf Weight Path
*> 10.0.0.0/8 50.0.0.1 0 0 0 200 100 i
*> 20.0.0.0/8 50.0.0.1 0 0 0 200 i
*> 30.0.0.0/8 0.0.0.0 0 0 32768 i
*> 40.0.0.0/8 50.0.0.1 0 0 0 200 i
*> 50.0.0.0/8 0.0.0.0 0 0 32768 i
* 50.0.0.1 0 0 0 200 i
Router>
Ctrl+F6 to exit CLI focus
Copy
Paste